# CPC COOPERATIVE PATENT CLASSIFICATION

## E FIXED CONSTRUCTIONS

### **BUILDING**

## E06 DOORS, WINDOWS, SHUTTERS, OR ROLLER BLINDS IN GENERAL; LADDERS

# E06B FIXED OR MOVABLE CLOSURES FOR OPENINGS IN BUILDINGS, VEHICLES, FENCES OR LIKE ENCLOSURES IN GENERAL, e.g. DOORS, WINDOWS, BLINDS,

**GATES** (shades or blinds for greenhouses <u>A01G 9/22</u>; curtains <u>A47H</u>; lids for car boots or bonnets <u>B62D 25/10</u>; skylights <u>E04B 7/18</u>; sunshades, awnings <u>E04F 10/00</u>)

### NOTES

- 1. This subclass <u>does not cover</u> combinations of wings or frames with operating, mounting, latching or locking means of the type found in class <u>E05</u>, which are covered by the relevant subclasses of class <u>E05</u>, except such as are covered by groups <u>E06B 7/086</u>, <u>E06B 9/00</u>, or <u>E06B 11/02</u> of this subclass.
- 2. In this subclass, the following terms or expressions are used with the meanings indicated:
  - "wing" means a swingable, slidable or otherwise movable member such as a door or window, for closing an opening;
  - "wing frame" means the peripheral edge or edges which define the outer border of the wing.
- 3. For vehicle door or window arrangements, attention is drawn to Note (1) following the title of subclass B60J.

#### **WARNINGS**

- The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:
   E06B 11/06 covered by E05B 65/0007
- 2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

| 1/00   | Border constructions of openings in walls, floors,  | 1/16 Hollow frames  |
|--------|---|---|
|        | or ceilings; Frames to be rigidly mounted in such   | 1/18 composed of several parts with respect to the        |
|        | openings (E06B 5/00 takes precedence; features  | cross-section of the frame itself                         |
|        | relating also to inner frames or wing frames, features  | 1/20 adjustable with respect to the thickness of          |
|        | relating solely to the mounting of inner frames   | walls   |
|        | E06B 3/00; corner joints or edge joints E06B 3/96)  | 1/22 with integral thresholds of special form             |
| 1/003  | • {Cavity wall closers; Fastening door or window  | 1/24 • Frames of natural stone, concrete, or other stone- |
|        | frames in cavity walls (lintels <u>E04C 3/02</u> )}   | like material   |
| 1/006  | • {of curvilinear outline}  | 1/26 . Frames of plastics                                 |
| 1/02   | <ul> <li>Base frames, i.e. template frames for openings in</li> </ul>                                   | 1/28 Hollow frames ( <u>E06B 1/30</u> takes precedence)   |
|        | walls or the like, provided with means for securing   | 1/30 composed of several parts with respect to the        |
|        | a further rigidly-mounted frame; Special adaptations  | cross-section of the frame itself                         |
|        | of frames to be fixed therein {(E06B 1/003,   | 1/32 . Frames composed of parts made of different         |
|        | E06B 1/24 take precedence; fastening door or  | materials   |
| 1 /0 / | window frames per se E06B 1/56)}  | 1/325 {comprising insulation between two metal            |
| 1/04   | Frames for doors, windows, or the like to be fixed  | section members}  |
|        | in openings ({of curvilinear outline <u>E06B 1/006;</u> } special adaptations for fixing in base frames | 1/34 . Coverings, e.g. protecting against weather, for    |
|        | E06B 1/02; features relating solely to the mounting   | decorative purposes                                       |
|        | of glass panes or other sheets E06B 3/00)   | 1/342 {Reveal covering members disposed alongside         |
| 1/045  | • • {with separate wing abutment strips, e.g.   | of a window frame}  |
| 1/043  | adjustable; Door stops (sealing arrangements  | 1/345 {Renovation window frames covering the              |
|        | E06B 7/16)}   | existing old frames}                                      |
| 1/06   | Wooden frames   | 1/347 • • • {Renovation door frames covering the existing |
| 1/08   | composed of several parts with respect to the   | old frames}   |
| 1/00   | cross-section of the frame itself   | 1/36 . Frames uniquely adapted for windows                |
| 1/10   | adjustable with respect to the thickness of   | 1/363 • • • {Bay windows}                                 |
| 1/10   | walls   | 1/366 {Mullions or transoms therefor}                     |
| 1/12   | Metal frames  | 1/38 for shop, show, or like large windows                |
| 1/14   | • • • of special cross-section (E06B 1/18, E06B 1/22  | 1/40 Frames with parts removable to admit the glass       |
| 1/1-   | take precedence) {not used}   | (E06B 1/38 takes precedence)                              |
|        |   |   |

| 1/222   [for overhead garage doors]   1/205   [End-caps therefor]  | 1/52     | Frames specially adapted for doors                    | 1/702    | • • {Window sills}   |
|--|----------|---|----------|--|
| 1.524   Millions, Transoms   1.525   Flore for wings that can be set up to open either left or right, nutroath or inwands, e.g. provided with growes for easily detachable hinges or lateh plates (decks therefore p. 1598 (3.01) kings therefore 1505 (1.525) (1.525)   with ducts for cubics or pipes   1.526   Fastening frames to the border of openings for to similar contiguous frames (1.666 1.1003 takes proceedence)     1.58  |          |   |          |  |
| 1526   for door wings that can be set up to open either left or right, outwards to rimarch, e.g. provided with grooves for easily detachable lineiges or latch plates (locks therefor EOSD 7/02)   |          |   | 2001/707 | The state of the s |
| either left or right, nutwards or inwards, e.g. provided with grows for easily detachable hinges or lack plates (locks therefor DOS B 6304-hinges therefor DOS D7 022)  1/528 . with ducts for cables or pipes 1/56 . Fastening frames to the border of openings (or to similar contiguous frames (EpGB. 1/603 takes precedence)) 1/58 . by filling up the joints, e.g. by cementing 1/600 v. by mechanical means, e.g. androing means 1/6007 . (hetween similar contiguous frames (bay windows EpGB. 1/601) 1/6015 . [Anchoring means (EpGB. 1/601) 1/6023 . [completely hidden between the frame and the border of the opening, at least part of the means being previously fixed to the wall (1/604 for 1/605) 1/603 . [calquistable] 1/604 . [Clamping means acting perpendicular to the wall opening (1/606 for popening) and held by means of sona action behind a promission on the border of the opening (1/606 for popening and held by means of sona action behind a promission on the border of the opening) 1/6004 . [Separate spear emans setting exclusives): 1/6005 . [Separate spear means setting exclusives): 1/6006 . [In similar popening falls 1/6004 for popening and held by means of sona action behind a promission on the border of the opening) 1/6004 . [Separate spear emans setting on opposite wall or associated surfaces] 1/6005 . [Separate spear emans setting on opposite wall or associated surfaces] 1/6006 . [In similar contiguous frames elst-cally); 1/6007 . [In stream popening means acting on opposite wall or associated surfaces] 1/6008 . [Separate spear emans setting exclusives); 1/6009 . [Separate spear emans setting on opposite wall or associated surfaces] 1/6009 . [Separate spear emans setting perpendicularly towards the opening and held by means of sona action behind a promission on the border of openings and the former of between contiguous frames [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/606] . [1/6 |          |   |          |  |
| 1/528   Fastering frames to fine broader of penning of some states of the some states o   |          |   | 3/00     |  |
| 1/2028   |          | e.g. provided with grooves for easily                 |          |  |
| 1/528   . [with ducts for cables or pipes]     1/56   Fastening frames to the border of openings (or its minular continguous frames (1968) 1/03 lakes precedence; shurters or the file E06B 9/00; glass panes CO3)     1/56   by mechanical means, e.g. auchoring means     1/600   by mechanical means, e.g. auchoring means     1/6015   (Anchoring means E06B 1/6007, Holds 1/60H - Holds 1/60H     1/6015   (Anchoring means E06B 1/6007, Holds 1/60H - Holds 1/60H     1/6024   (Compaing means E06B 1/6007)     1/603   (algostable)     1/6038   (specially adapted for being embedded in the wall of the means being previously fixed to the wall of the opening of Biol Holds (196B 1/60H     1/6046   (Clamping means acting perpendicular to the opening (196B 1/60H     1/6053   (the frame being moved perpendicularly towards the opening and belief by means of sanp action behind a protrusion on the border of the opening (196B 1/60H     1/6061   (with separate clamping means acting on opoposite wall or associated surfaces pracedence)     1/6007   (ols serve-type)     1/6008   (Separate spacer means acting exclusively in the plane of the opening)     1/6009   (Separate spacer means acting exclusively in the plane of the opening)     1/6000   (Separate spacer means acting exclusively in the plane of the opening)     1/6001   (with separate clamping means acting on opoposite wall or associated surfaces     1/6002   (Fastening of covering joints between the wall and the frame (DoBB 1/70H active)     1/6002   (Fastening of covering joints between the wall and the frame (DoBB 1/70H active)     1/6004   (Fastening doof frames to the floor or ceiling: Jamb feet; Cross members unting the jamb feet (190B 1/71 and the floor or window frame part)     1/6002   (Fastening or covering joints between the border of opening and the frame (DoBB 1/60H active)     1/6002   (Fastening separate)     1/6003   (Fastening separate)     1/6004   (Fastening separate)     1/6005   (Fastening separate)     1/6006   (Fastening separate)     1/6007   (Fastening separ   |          |   |          |  |
| 1/25   (with allests for claims or pipes)  |          |   |          |  |
| 1/56   Fastening frames to the border of openings (or to similar configuous frames (DOB JUM3 takes precedence)   | 1/528    |   |          |  |
| to similar configuous frames (1908 100) likes precedence) 1/6007 • (between similar contiguous frames (buy windows 1960 1363) 1/6015 • (Anchoring means (1960 13600) 1/6023 • (completely hidden between the frame and the berder of the opening, and least part of the means being previously fixed to the wall 1/6023 • (alignable) 1/6038 • (specially adapted for being embedded in the wall) 1/6038 • (specially adapted for being embedded in the wall) 1/6040 • (Clamping means acting perpendicular to the wall opening; Fastening frames by tightening or drawing them against a surface parallel to the opening [1960 11600 1868 precedence)) 1/6033 • (the frame being moved perpendicularly towards the opening and held by means of samp action behind a protrusion on the border of the opening; (1960 11600 1868 1868) 1/609 • (Separate spacer means acting on opoposite wall or associated surfaces] 1/6091 • (with separate clamping means acting on opoposite wall or associated surfaces) 1/6092 • (Separate spacer means acting exclusively in the plane of the opening; Shitns; Wedges; 1/16094 • (Mounting frames estatically, e.g. with springs or other leasts; estatically, e.g. with springs or other leasts; estatically continguous frames 1/6092 • (Fastening door frames to the floor or ceiling; 1/6094 • (Pastening door frames to the floor or ceiling; 1/6095 • (Separate spacer means acting on opposite wall or associated surfaces) 1/6094 • (Mounting frames estatically, e.g. with springs or other leasts; material, between the wall and the frame (E060 176046 takes precedence)) 1/6092 • (Fastening door frames to the floor or ceiling; 1/6094 • (With against as uniting the jumb feet (E006 1700 and E066 38052 take precedence) 1/6094 • (Separate flexible joint covering devices where the wall and the fet (E006 17604 takes precedence)) 1/6095 • (Separate flexible joint covering devices where the wall and the fet (E006 17604 takes precedence)) 1/6096 • (Separate flexible joint covering devices where the wall and the fet (E006 17604 takes) 1/6095 • (Separate | 1/56     |   |          |  |
| 1/58   by filling up the joints, e.g. by cementing     1/60   by mechanical means, e.g. anchoring means     1/6001   (between similar contiguous frames (Bay windows E06B 1/503)     1/6015   (Anchoring means (E06B 1/6007, E06B 1/6046 - E06B 1/6092 take precedence)     1/6023   (completely hidden between the frame and the border of the opening, at least part of the means being previous by fixed to the wall (E06B 1/6038 takes precedence)     1/6038   (specially adapted for being embedded in the wall opening. Fastening frames by tightening or drawing them against a surface parallel to the opening (E06B 1/6007 takes precedence)     1/6015   (Clamping means acting perpendicularly towards the opening and held by means of snap action behind a protroision on the border of the opening (E06B 1/6004 takes precedence)     1/6009   (Sperarle spear means acting of opposite wall or associated surfaces)     1/6009   (Sperarle spear means acting of opposite wall or associated surfaces)     1/6009   (Sperarle spear means acting of a complete frame inside a wall opening (E06B 1/6046 takes precedence))     1/6009   (Sperarle spear means acting perpendicularly towards the opening and held by means of snap action behind a protroision on the border of the opening (E06B 1/6046 takes precedence))     1/6009   (Sperarle spear means acting of a complete frame inside a wall opening (E06B 1/6046 takes precedence))     1/6009   (Sperarle spear means acting of a complete frame inside a wall opening (E06B 1/6046 takes precedence))     1/6009   (Frame)   |          |   | 3/01     |  |
| 1/60 by mechanical means, e.g. anchoring means 1/6007 (Separate Spacer means acting exclusively towards the opening and held by means of snap action behind a protrusion on the border of the opening (E061 1/6001 takes precedence)) 1/6018 (Separate spacer means acting exclusively towards the opening and held by means of snap action behind a protrusion on the border of the Opening (E061 1/6001 takes precedence)) 1/6019 (Separate spacer means acting exclusively towards the opening and held by means of snap action behind a protrusion on the border of the Opening (E061 1/6001 takes precedence)) 1/6010 (Separate spacer means acting exclusively towards the opening and held by means of snap action behind a protrusion on the border of the Opening) 1/6011 (Separate spacer means acting exclusively to the plane of the opening (E061 1/6001 takes precedence)) 1/6012 (Separate spacer means acting exclusively to the plane of the opening shirms; Wedges; Tightening of a complete frame inside a wall opening (E061 1/6001 takes precedence)) 1/6014 (Mounting frames elastically, e.g. with springs or other elastic material, between the wall and the frame (E061 1/601 1/31 takes precedence)) 1/6024 (Fastening door frames to the floor or ceiling; Jamb feet. Cross members uniting the Jamb feet (E061 1/61 1/31 takes precedence)) 1/6025 (Separate flexible joint covering devices where the wall surface is parallel to the adjacent door or window frame part) 1/6026 (Separate flexible joint covering strips; Flashings) 1/603 (Separate flexible joint covering strips; Flashings) 1/604 (Separate flexible joint covering strips; Flashings) 1/605 (Separate flexible joint covering strips; Flashings) 1/606 (Separate flexible joint covering strips; Flashings) 1/607 (Separate flexible joint covering strips; Flashings) 1/608 (Separate flexible joint covering strips; Flashings) 1/609 ( | 4 (50    |   |          |  |
| 1/6007   Chetween similar contiguous frames (bay windows EBGB 12/63)   1/6015   Canchoring means (100B 1/6002 take precedence)   1/6023   Completely hidden between the frame and the border of the opening, at least part of the means being previously fixed to the wall (100B 1/6038 takes precedence)   1/6038   Specially adapted for being embedded in the wall 1/6038   Specially adapted for being embedded in the wall 1/6038   Specially adapted for being embedded in the wall 1/6038   Specially adapted for being embedded in the wall 1/6038   Specially adapted for being embedded in the wall 1/6038   Specially adapted for being embedded in the wall 1/6038   Special protection on the opening (1/60B 1/6007 takes precedence)   1/6053   Special construction approximate the opening (1/60B 1/6007 takes precedence)   1/6061   Special protection approximate the opening of the opening of a complete frame inside a wall opening (1/60B 1/6007 takes precedence)   1/6067   Separate spacer means acting on opposite wall or associated surfaces)   Special construction, e.g. made of folded sheet metal or of two or more section parts comected to rot over other classic material, between the wall and the frame (1/60B 1/60B takes precedence)   1/602   Fastering door frames to the floor or ceiling; 1/60B 1/34 takes precedence)   1/602   Fastering door frames to the floor or ceiling; 1/60B 1/60B 1/34 takes precedence)   1/602   Fastering door frames to the floor or ceiling; 1/60B 1/60B 1/34 takes precedence)   1/602   Specially adapted for door frames, 1/60B 1   |          |   |          | <u>E04B 2/00</u> )   |
| windows E06B 1/363)  1/6023  |          |   | 3/02     | • Wings made completely of glass {(E06B 3/4681   |
| 1/6015 . (Anchoring means (2068 1/6007). EGBI 1/6004 - EOBI 1/6009 take precedences) 1/6023 . (completely hidden between the frame and the border of the opening, at least part of the means being previously fixed to the wall (266B 1/6008 takes precedence)) 1/603 . (algiustable) 1/603 . (specially adapted for being embedded in the wall) 1/604 . (Clamping means acting perpendicular to the wall opening; Fastening frames by tightening or drawing them against a surface parallel to the opening; Georgian and held by means of snap action behind a protrusion on the border of the opening and held by means of snap action behind a protrusion on the border of the opening of a complete frame inside a wall opening (260B 1/6084 takes precedence)) 1/604 . (Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (260B 1/6084 takes precedence)) 1/604 . (Mounting frames leastically, e.g. with springs or other elastic material, between the wall and the frame (E90B 1/608 takes precedence)) 1/605 . [Fastening door frames to the floor or ceiling; Jamb feet; Cross members unting the jamb feet (E90B 1/70 and E90B, 3/903 take precedence)) 1/602 . [Fastening door frames to the floor or ceiling; Jamb feet; Cross members unting the jamb feet (E90B 1/70 and E90B, 3/903 take precedence) 1/604 . (with parts to be embedded in the stuce layer or otherwise linked to this layer) 2/601/626 . (comprising expanding foam strips) 1/608 . (speared feexible joint covering strips; Hashings) 1/609 . (speared feexible joint covering strips; Hashings) 1/600 . (speared feexible joint covering strips; Hashings) 1/600 . (speared feexi | 1/600/   |   |          |  |
| 1/6023   .   completely hidden between the frame and the border of the opening, at least part of the means being previously fixed to the wall (2006) 1/603 at least part of the means being previously fixed to the wall (2006) 1/603 at least part of the means being previously fixed to the wall (2006) 1/603 at least part of the means being previously fixed to the wall (2006) 1/603 at least part of the wall (2006) 1/603 at least part of wall (2006) 1/603 at least part of wall (2006) 1/603 at least prevention or drawing them against a surface parallel to the opening (2008) 1/6007 (akes precedence)   3/10  | 1/6015   |   | 3/025    |  |
| 1/6023 . (completely hidden between the frame and the border of the opening, at least part of the means being previously fixed to the wall (1806B 1/6038 takes precedence)) 1/6038 . (specially adapted for being embedded in the wall) 1/6046 . (Clamping means acting perpendicular to the wall opening; Fastening frames by tightening or drawing them against a surface parallel to the opening (1906B 1/680Z) takes precedence)) 1/6053 . (the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening } 1/6061 . (with separate clamping means acting or opposite wall or associated surfaces) 1/6069 . (Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (260B 1/694 takes precedence)) 1/6076 . (of screw-type) 1/6084 . (Mounting frames elastically, e.g. with springs or other clastic material, between the wall and the frame (190B 1/6404 takes precedence)) 1/6092 . (Fastening or covering joints between the border of openings and the frame (190B 1/6404 takes precedence)) 1/6092 . (respecially dapted for doof for fames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part) 1/6092 . (especially adapted for of oof frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part) 1/6094 . (with parts to be embedded in the stucco layer or otherwise linked to this layer) 1/6095 . (especially adapted for door frames; Joint covering strips; Flashings) 1/6096 . (comprising expanding foam strips) 1/6097 . (comprising expanding foam strips) 1/6098 . (comprising expanding foam strips) 1/6099 . (comprising expanding foam strips) 1/6090 . (fastering door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (190B 1/74 alkes) precedence) 1/6090 . (comprising expanding foam strips) 1/6091 . (with parts to be embedded in the stucco layer or otherwise linked to this layer) 1/6 | 1/0015   |   |          |  |
| the border of the opening, at least part of the means being previously fixed to the wall (E06B 1.6038 takes precedence))  1/6038   | 1/6022   |   | 3/04     |  |
| the means being previously fixed to the wall (E06B 1/6038 takes precedence))  1/603  | 1/0023   |   |          |  |
| 1/603   . {adjustable}     1/6038   . {apjustable}     1/6046   . {Clamping means acting perpendicular to the wall opening: Fastening frames by tightening or drawing them against as surface parallel to the opening (E06B 1/6007 takes precedence)     1/6053   . {the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening     1/6061   . {with separate clamping means acting on opposite wall or associated surfaces     1/6069   . {sparate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (B06B 1/6084 takes precedence)     1/6074   . {of screw-type}     1/6084   . {Mounting frames elastically, e.g. with springs or other elastic material, between the wall and the frame (E06B 1/604 dakes precedence)     1/6092   . {Fastening door frames to the floor or ceiling; Jamb feet Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)     1/602   . {Fastening door frames to the floor or ceiling; Jamb feet Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)     1/602   . {Fastening door frames to the floor or ceiling; Jamb feet Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)     1/602   . {Fastening door frames; Ioint covering devices where the wall surface is parallel to the adjacent door or window frame part     2001/624   . {with parts to be embedded in the stucco layer or otherwise linked to this layer     2001/626   . {sepacially adapted for door or window frame part     2001/626   . {sepacial construction, e.g. made of folded sheet metal or of two or more section parts of its covering several two or more section parts of its covering several two or with a filled cavity     1/60   . {with parts to be embedded in the stucco layer or otherwise linked to this layer     2001/626   . {sepacial padapted for door frames; Joint covering strips; Flashings     1/66   . by lossely-inserted means   |          |   | 2.10 =   |  |
| 1/603  |          |   |          |  |
| 1/6038   | 1/603    |   | 3/08     |  |
| 1/6046   Clamping means acting perpendicular to the wall opening; Fastening frames by tightening or drawing them against a surface parallel to the opening (E006 Ho07) takes precedence)     1/6053   (the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening   1/6061   (with separate clamping means acting on opposite wall or associated surfaces)   1/6069   (Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E006 Ho084 takes precedence))   1/6076   (of screw-type)   3/18   of concrete or other stone-like material opening (E006 Ho084 takes precedence))   1/6092   (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (E006 Ho084 takes precedence))   1/6092   (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (E006 Ho084 takes precedence)   1/6092   (Fastening door frames to the floor or ceiling; Jamb feet; Gross members uniting the jamb feet (E006 Ho084 takes precedence)   1/6092   (Fastening door frames to the floor or ceiling; Jamb feet; Gross members uniting the jamb feet (E006 Ho084 takes precedence)   1/6092   (Fastening door frames to the floor or ceiling; Jamb feet; Gross members uniting the jamb feet (E006 Ho084 takes precedence)   1/6092   (Especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part)   2001/624   (with parts to be embedded in the stucco layer or otherwise linked to this layer)   2003/224   (with reinforcing plastic section members)   1/6084   (Eoph Hong) frame   2003/225   (Eoph section from the walls)   2003/226   (Eoph sing expanding foam strips)   2003/226   (Eoph sing expanding foam strips)   2003/226   (With reinforcing wooden section members)   1/6084   (With reinforcing wooden section members)   2003/228   (With reinforcing wooden section members)   1/6084    |          |   |          | - · · · · · · · · · · · · · · · · · · ·  |
| 1/6046 (Clamping means acting perpendicular to the wall opening: Fastening frames by tightening or drawing them against a surface parallel to the opening (E06B 1/6007 takes precedence))  1/6053 (the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening.)  1/6061 (with separate clamping means acting on opposite wall or associated surfaces)  1/6069 . (Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E06B 1/6046 takes precedence))  1/6076 (of screw-type)  1/6078 . (Mounting frames elastically, e.g. with springs or other elastic material, between the wall and the frame (E06B 1/70 and E06B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet (E06B 1/70 and E06B 3/9632 take precedence))  1/62 . Tightening or covering joints between the border of openings and the frame (or between contiguous frames) (E06B 1/34 takes precedence)  2001/624 . (with parts to be embedded in the stucco layer or otherwise linked to this layer)  2001/625 . (comprising expanding foam strips)  2001/626 . (comprising expanding foam strips)  1/66 . by labyrinth packings  1/68 . by profiled external parts  3/24 . specially adapted for double glazing (separable late)  3/16 . Hollow frames (for finetal or of two or more section parts connected to of two or more section parts connected to of two or more section parts connected to fixe or of two or more section parts connected to fixe or more section parts connected to fixe or of two or more section parts connected to fixe or of two or more section parts connected to fixe or of two or more section parts connected to fixe or of two or more section parts connected to fixe or of two or more section parts connected to fixe or of two or more section parts connected to fixe or of two or more section parts connected to cover or otherwise connected to fixe or of two or more section                     |          |   | 3/10     |  |
| wall opening: Fastening frames by tightening or drawing them against a surface parallel to the opening (£06B 1/6007 takes precedence)}  1/6053 (the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening]  1/6061 (with separate clamping means acting on opposite wall or associated surfaces)  1/6069 . (Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (£06B 1/6084 takes precedence))  1/6076 (of screw-type)  1/6076 (of screw-type)  1/6081 . (Mounting frames elastically, e.g. with springs or other elastic material, between the wall and the frame (£06B 1/70 and £06B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (£06B 1/70 and £06B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (£06B 1/70 and £06B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (£06B 1/70 and £06B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (£06B 1/70 and £06B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (£06B 1/70 and £06B 3/9632 take precedence))  1/6092 . (Fastening door frame for between contiguous frames) (£06B 1/34 takes precedence)  1/6093 . (Fastening door frames) (£06B 3/9632 take precedence))  1/6094 . (with a filled cavity)  1/6095 . (with a filled cavity)  1/6096 . (with a filled cavity)  1/6096 . (with a filled cavity)  1/6097 . (with rimforcing section members)  1/6098 . (Especially adapted for door frames; Joint covering feet (£06B 1/70 and £06B 3/9632 take precedence))  1/6099 . (Especially adapted for door frames; Joint covering feet (£06B 1                 | 1/6046   | {Clamping means acting perpendicular to the           |          |  |
| 1/6053 . (the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening]  1/6061 . (with separate clamping means acting on opposite wall or associated surfaces)  1/6069 . (Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening; GEO6B 1/6084 takes precedence))  1/6076 . (of screw-type)  1/6076 . (of screw-type)  1/6076 . (of screw-type)  1/6077 . (Fastening door frames to the floor or ceiling; Jamb feet (EO6B 1/70 and EO6B 3/9632 take precedence))  1/6092 . (Fastening door frames to the floor or ceiling; Jamb feet (EO6B 1/70 and EO6B 3/9632 take precedence))  1/6072 . (ight and EO6B 3/9632 take precedence))  1/6076 . (of screw-type)  1/6076 . (of screw-type)  1/6076 . (of screw-type)  1/6077 . (with a filled cavity)  3/20 . (founded or extruded around a core)  3/20 . (moulded or extruded around a core)  3/22 . (with the frame member having local reinforcements in some parts of its cross-section or with a filled cavity)  3/22 . (with the frame member having local reinforcements in some parts of its cross-section or with a filled cavity)  3/22 . (with the frame member having local reinforcements in some parts of its cross-section or with a filled cavity)  3/22 . (with the frame member having local reinforcements in some parts of its cross-section or with a filled cavity)  3/22 . (with the frame members are part or otherwise the border of openings and the frame (EO6B 1/70 and EO6B 3/9632 take precedence)  2/201/622 . (especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part    2/201/624 . (with parts to be embedded in the stucco layer or otherwise linked to this layer)  2/201/625 . (separate flexible joint covering strips; Flashings)  1/66 . by labyrinth packings  1/66 . by labyrinth packings  1/68 . by profiled external parts  3/24 . specially adapted for doubtle glazing (separa |          |   |          |  |
| 1/6053 (the frame being moved perpendicularly towards the opening and held by means of snap action behind a protrusion on the border of the opening]  1/6061 { with separate clamping means acting on opposite wall or associated surfaces}  1/6069 . { Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E06B 1/6084 takes precedence)}  1/6076 { of screw-type} 1  1/6078 { fo screw-type} 2  1/6078 { fo screw-type} 3/22 . { (moulded or extruded around a core} 3/225 . { (moulded or extruded around a core} 3/225 . { (with he frame (E06B 1/6046 takes precedence)} 3/225 . { (with he frame (E06B 1/6046 takes precedence)} 3/221 . { (with he frame member having local reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements in some parts of its cross-section or with a filled cavity} 3/222 . { (with internal prefabricated reinforcements with a filled cavity} 3/222 . { (with internal prefabricated reinforcements with a filled cavity} 3/222 . { (with internal prefabricated reinforcements with a filled cavity} 3/222 . { (with internal prefabricated reinforcements with a filled cavity} 3/222 . { (with internal prefabricated reinforcements with a filled cavity 3/222 . { (with internal                        |          |   |          |  |
| 1/6015   (the frame feeling moved perpendicularly towards the opening and held by means of sana action behind a protrusion on the border of the opening  |          |   | 3/14     | - · · · · · · · · · · · · · · · · · · ·  |
| snap action behind a protrusion on the border of the opening; loopening opposite wall or associated surfaces}  1/6061  | 1/6053   |   | 3/16     |  |
| 1/6061   . { (with separate clamping means acting on opposite wall or associated surfaces } 1/6069   . { Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E006B 1/6084 takes precedence) } 3/200   . ( (with a filled cavity )   |          |   | 3/10     |  |
| 1/6061   \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \   |          |   |          |  |
| 1/6069   Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E06B 1/6084 takes precedence)   3/205   (moulded or extruded around a core)   3/205   (with the frame member having local reinforcements in some parts of its cross-section or with a filled cavity   3/205   (with timeral prefabricated reinforcements in some parts of its cross-section or with a filled cavity   3/205   (with timeral prefabricated reinforcing section members)   3/221   (with reinforcing presented around a reinforcements in some parts of its cross-section or with a filled cavity   3/205   (moulded or extruded around a reinforcements in some parts of its cross-section or with a filled cavity   3/222   (with reinforcing place around a reinforcements assembled around a reinforcements assembled around a reinforcing core members   2003/224   (with reinforcing place around a    | 1/6061   |   |          |  |
| 1/6069   Separate spacer means acting exclusively in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E06B 1/6084 takes precedence)}   3/20   of plastics of concrete or other stone-like material opening (E06B 1/6084 takes precedence)}   3/20   of plastics of plastics opening (E06B 1/6084 takes precedence)}   3/22   Hollow frames (E06B 3/205 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)}   3/22   Hollow frames (E06B 3/205 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)   other clastic material, between the wall and the frame (E06B 1/6046 takes precedence)   other clastic material of plastics of pla   | 1/6061   |   | 3/163    |  |
| in the plane of the opening; Shims; Wedges; Tightening of a complete frame inside a wall opening (E06B 1/6084 takes precedence)}  1/6076 .   | 1/6060   |   | 2003/166 | {with a filled cavity}   |
| Tightening of a complete frame inside a wall opening (E96B 1/6084 takes precedence)  | 1/0009   |   | 3/18     | of concrete or other stone-like material   |
| opening (E06B 1/6084 takes precedence)}  1/6076 { of screw-type} 3/22 Hollow frames {(E06B 3/205 takes)}  1/6084 {Mounting frames elastically, e.g. with springs or other elastic material, between the wall and the frame (E06B 1/6046 takes precedence)}  1/6092 {Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)}  1/62 . Tightening or covering joints between the border of openings and the frame {or between contiguous frames} {E06B 1/34 takes precedence}  2001/622 . {especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/626 . {comprising expanding foam strips}  2001/627 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  3/20 . {moulded or extruded around a core}  3/22 . Hollow frames {(E06B 3/205 takes) precedence}}  3/221 . {with the frame member having local reinforcements in some parts of its cross-section or with a filled cavity}  3/222 . {with internal prefabricated reinforcing section members inserted after manufacturing of the hollow frame parts as sembled around a reinforcing section members and the frame { (E06B 1/70 and E06B 3/9632 take precedence)}  2003/224 . {(with eniforcing plastic section members}  2003/225 . {(Means for stabilising the insert) tongue }  2003/226 . {(with reinforcing wooden section members}  2003/227 . {(with reinforcing wooden section members}  2003/228 . {(with separate reinforcements situated outside the cavity or in the walls}  2003/228 . {(with separate reinforcements situated outside the cavity or in the walls}  2003/228 . Specially adapted for double glazing (separable)   |          |   | 3/20     | of plastics  |
| 1/6076   |          |   | 3/205    | • • • • {moulded or extruded around a core}  |
| 1/6084 {Mounting frames elastically, e.g. with springs or other elastic material, between the wall and the frame (E06B 1/6046 takes precedence)}  1/6092 {Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)}  1/62 . Tightening or covering joints between the border of openings and the frame (or between contiguous frames) (E06B 1/34 takes precedence)  2/001/622 . {especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2/001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2/001/625 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  1/60 . by profiled external parts   | 1/6076   |   | 3/22     | • • • • Hollow frames {( <u>E06B 3/205</u> takes   |
| or other elastic material, between the wall and the frame (E06B 1/6046 takes precedence)}  1/6092  |          |   |          | precedence)}   |
| 1/6092 {Fastening door frames to the floor or ceiling; Jamb feet; Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)}  1/62 . Tightening or covering joints between the border of openings and the frame {or between contiguous frames} (E06B 1/34 takes precedence)  2001/622 . {especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/626 . {comprising expanding foam strips}  2001/628 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  2/222 . {with internal prefabricated reinforcing systems of the hollow frame part after manufacturing of the hollow frame parts after manufacturing of the hollow frame parts after manufacturing of the hollow frame parts after manufacturing of the hollow frame exponence after manufacturing of the hollow frame parts after manufacturing of the h       |          |   | 3/221    |  |
| Jamb feet; Cross members uniting the jamb feet (E06B 1/70 and E06B 3/9632 take precedence)}  1/62 Tightening or covering joints between the border of openings and the frame {or between contiguous frames} (E06B 1/34 takes precedence)  2001/622 (Eospecially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 (With parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/625 (Separate flexible joint covering strips; Flashings)  1/64 (Separate flexible joint covering strips; Flashings)  1/65 (Separate flexible parts)  1/66 (Separate flexible parts)  1/68 (Separate flexible parts)  1/69 (Separate flexible parts)  1/60 (Separate flexible parts)  1/61 (Sep |          | the frame (E06B 1/6046 takes precedence)}             |          |  |
| feet (E06B 1/70 and E06B 3/9632 take precedence)}  1/62 Tightening or covering joints between the border of openings and the frame { or between contiguous frames} (E06B 1/34 takes precedence)  2001/622 (sepecially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 (with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/625 (Separate flexible joint covering strips; Flashings)  1/64 (by loosely-inserted means, e.g. strip, resilient tongue  1/66 (by labyrinth packings)  1/68 (by profiled external parts)  Tightening or covering joints between the border of openings and the frame { or between contiguous frame } 3/223 (the hollow frame members comprising several U-shaped parts assembled around a reinforcing core member}  2003/224 (with reinforcing plastic section members}  2003/225 (Means for stabilising the insert}  2003/226 (by adhesives or filling up the remainder of the cavity, e.g. together with foam}  2003/227 (with reinforcing wooden section members}  2003/228 (with separate reinforcements situated outside the cavity or in the walls}  1/66 (by labyrinth packings)  1/68 (by profiled external parts)   | 1/6092   | • • • {Fastening door frames to the floor or ceiling; |          |  |
| Tightening or covering joints between the border of openings and the frame {or between contiguous frames} (E06B 1/34 takes precedence)   |          |   | 3/222    |  |
| 1/62 Tightening or covering joints between the border of openings and the frame {or between contiguous frames} (E06B 1/34 takes precedence)  2001/622 (especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 (with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/626 (comprising expanding foam strips)  2001/628 (Separate flexible joint covering strips; Flashings}  1/64 (by loosely-inserted means, e.g. strip, resilient tongue)  1/66 (by labyrinth packings)  1/68 (by loosely-inserted means)  1/68 (by loosely-inserted means)  1/68 (by labyrinth packings)  3/24 (by dhesives or filling up the remainder of the cavity, e.g. with reinforcing wooden section members}  2003/228 (with separate reinforcements situated outside the cavity or in the walls}  3/24 (by adhesives or filling up the remainder of the cavity or in the walls}  1/68 (by labyrinth packings)  3/24 (be hollow frame members comprising several U-shaped parts assembled around a reinforcing core member}  2003/224 (with reinforcing plastic section members}  2003/225 (by adhesives or filling up the remainder of the cavity, e.g. together with foam}  2003/227 (with reinforcing wooden section members}  2003/228 (with separate reinforcements situated outside the cavity or in the walls}  1/68 (by labyrinth packings)  3/24 (be hollow frame members comprising several U-shaped parts assembled around a reinforcing core member}  2003/225 (with reinforcing wooden section members}  2003/228 (with separate reinforcements situated outside the cavity or in the walls}   |          |   |          |  |
| of openings and the frame {or between contiguous frames} (E06B 1/34 takes precedence)  2001/622  | 4.450    |   |          |  |
| frames} (E06B 1/34 takes precedence)  2001/622   | 1/62     |   | 2/222    |  |
| 2001/622 . {especially adapted for door frames; Joint covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/626 . {comprising expanding foam strips}  2001/628 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  2003/224 {with reinforcing plastic section members}  2003/225 {Means for stabilising the insert} 2003/226 {by adhesives or filling up the remainder of the cavity, e.g. together with foam} 2003/227 {with reinforcing wooden section members}  2003/227 {with reinforcing wooden section members}  2003/228 {with separate reinforcements situated outside the cavity or in the walls}  3/24 . specially adapted for double glazing (separable)  |          |   | 3/223    | · · · · · · · · · · · · · · · · · · ·  |
| covering devices where the wall surface is parallel to the adjacent door or window frame part}  2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/626 . {comprising expanding foam strips}  2001/628 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  2003/224 {with reinforcing plastic section members}  2003/225 {Means for stabilising the insert}  2003/226 {by adhesives or filling up the remainder of the cavity, e.g. together with foam}  2003/227 {with reinforcing wooden section members}  2003/228 {with separate reinforcements situated outside the cavity or in the walls}  3/24 . specially adapted for double glazing (separable)  | 2001/622 |   |          |  |
| parallel to the adjacent door or window frame part}  2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2001/626 . {comprising expanding foam strips}  2001/628 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  2003/224 {with reinforcing plastic section members}  2003/225 {Means for stabilising the insert}  2003/226 {by adhesives or filling up the remainder of the cavity, e.g. together with foam}  2003/227 {with reinforcing wooden section members}  2003/228 {with separate reinforcements situated outside the cavity or in the walls}  3/24 . specially adapted for double glazing (separable)   | 2001/022 |   |          |  |
| part}  2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer}  2003/225 {Means for stabilising the insert}  2003/226 {by adhesives or filling up the remainder of the cavity, e.g.  2001/628 . {Separate flexible joint covering strips;  Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  members}  2003/225 {Means for stabilising the insert}   |          |   | 2003/224 |  |
| 2001/624 . {with parts to be embedded in the stucco layer or otherwise linked to this layer} 2003/225 {Means for stabilising the insert} otherwise linked to this layer} 2003/226 {by adhesives or filling up the remainder of the cavity, e.g. together with foam} remainder of the cavity, e.g. together with foam}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue 2003/228 {with reinforcing wooden section members}  1/66 . by labyrinth packings 2003/228 {with separate reinforcements situated outside the cavity or in the walls}  1/68 . by profiled external parts 3/24 specially adapted for double glazing (separable)  |          |   |          |  |
| otherwise linked to this layer}  2001/626 . {comprising expanding foam strips} remainder of the cavity, e.g.  2001/628 . {Separate flexible joint covering strips; Flashings}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  2003/226 {by adhesives or filling up the remainder of the cavity, e.g.  1/60 {with reinforcing wooden section members}  2003/227 {with reinforcing wooden section members}  2003/228 {with separate reinforcements situated outside the cavity or in the walls}  3/24 . specially adapted for double glazing (separable)   | 2001/624 |   | 2003/225 | • • • • • • • • • • • • • • • • • • •  |
| 2001/628 . {Separate flexible joint covering strips; Flashings} 2003/227 {with reinforcing wooden section members}  1/64 . by loosely-inserted means, e.g. strip, resilient tongue 2003/228 {with separate reinforcements situated outside the cavity or in the walls}  1/66 . by labyrinth packings 0utside the cavity or in the walls}  1/68 . by profiled external parts 3/24 specially adapted for double glazing (separable)  |          |   | 2003/226 | • • • • • • • • • • • • • • • • • • •  |
| Flashings }  1/64 . by loosely-inserted means, e.g. strip, resilient tongue  1/66 . by labyrinth packings  1/68 . by profiled external parts  2003/227 {with reinforcing wooden section members}  2003/228 {with separate reinforcements situated outside the cavity or in the walls}  3/24 specially adapted for double glazing (separable)   | 2001/626 | • • {comprising expanding foam strips}                |          |  |
| Flashings  | 2001/628 |   |          |  |
| tongue 2003/228 {with separate reinforcements situated outside the cavity or in the walls}  1/66 . by labyrinth packings outside the cavity or in the walls}  1/68 . by profiled external parts 3/24 specially adapted for double glazing (separable)  |          | Flashings}  | 2003/227 |  |
| 1/66 by labyrinth packings outside the cavity or in the walls} 1/68 by profiled external parts 3/24 specially adapted for double glazing (separable  | 1/64     | by loosely-inserted means, e.g. strip, resilient      |          | •  |
| 1/68 . by profiled external parts 3/24 specially adapted for double glazing (separable   |          | <u> </u>  | 2003/228 |  |
| FOOD 2/64)   |          |   | 2/24     | •  |
| 1/70 • Sills; Thresholds parts for securing panes <u>EUOB 3/64</u> )   |          |   | 3/24     |  |
|  | 1/70     | . Sills; Thresholds                                   |          | parts for securing panes <u>E00D 3/04</u> )  |

| 3/26       | • Compound frames, i.e. one frame within or behind another (E06B 3/28 takes precedence; arrangements of movable frames E06B 3/32) | 3/2634 { without separate insulating elements, e.g. the heat transmission being reduced by a smaller cross-section} |
|------------|---|---|
| 3/2605     | • • • { with frames permanently mounted behind or within each other, each provided with a pane or                                 | 3/26341 {comprising only one metal frame member combined with an insulating frame member}                           |
| 2003/261   | screen} {Frames made of wood}   | 3/26343 { with two or more separate insulating zones alternating with metal section members}                        |
|            | {Frames made of wood} {Frames made of metal}  | 3/26345 {for wooden or plastic section members}   |
|            | {Frames made of metary  | 3/26347 {specially adapted for sliding doors or   |
|            | {with different frames made from different  | windows}  |
| 2002/2028  | materials}  | 2003/26349 {Details of insulating strips}   |
| 3/263      | • Frames with special provision for insulation  | 2003/2635 {Specific form characteristics}   |
| 3/26301    | • • • { with prefabricated insulating strips between  | 2003/26352 {hollow}   |
|            | two metal section members (with two metal   | 2003/26354 {filled}   |
|            | frame members having interpenetrating   | 2003/26356 {Honeycomb}  |
|            | or overlapping parts when mounted   | 2003/26358 {stepped or undulated}   |
|            | E06B 3/26336; combined with insulating elements formed in situ E06B 3/2675)   | 2003/26359 {making flush mounting with  |
| 3/26303    | • • • { with thin strips, e.g. defining a hollow space  | neighbouring metal section members  |
| 3/20303    | between the metal section members }   | possible}   |
| 3/26305    | • • • {Connection details (deformation of portions  | 2003/26361 {Openings, incisions or indents}   |
|            | of the metal frame members <u>E06B 3/273</u> ;  | 2003/26363 {Screw channels}<br>2003/26365 {Composed of several similar parts  |
|            | expansion of the extremities of the insulating  | positioned one after the other  |
|            | elements <u>E06B 3/277</u> )}   | 2003/26367 {making flush mounting with neighbouring   |
| 3/26307    | {Insulating strips and metal section  | metal section members possible}   |
|            | members both having L-shaped ribs, the engagement being made by a movement  | 2003/26369 {Specific material characteristics}  |
|            | transversal to the plane of the strips}   | 2003/2637 {reinforced}  |
| 2003/26309 | {using glue}  | 2003/26372 {with coatings}  |
|            | {Screw or pin connections}  | 2003/26374 {with parts of differing nature}   |
|            | {Snap connections}  | 2003/26376 {Non-plastic materials, e.g. wood, metal}  |
|            | • • • • {Provisions for reducing the shift between  | 2003/26378 {comprising foam}  |
|            | the strips and the metal section members}   | 2003/26379 {Specific characteristics concerning the   |
|            | • {Disconnectable connections or permitting shifting between the sections}  | disposition between the metal section members}  |
| 2003/26318 | {Connecting by rotating the metal section   | 2003/26381 {disposed obliquely}<br>2003/26383 {with two similar parallel strips, one                                |
| 3/2632     | or the strip around its longitudinal axis} {with arrangements reducing the heat   | shifted to one side}  |
| 3/2032     | transmission, other than an interruption in a metal section}  | 2003/26385 { with strips disposed perpendicular to each other}  |
| 2003/26321 | • • • { with additional prefab insulating materials   | 2003/26387 {Performing extra functions}   |
|            | in the hollow space }  • • • • {with coatings reducing the radiation}   | 2003/26389 {Holding sealing strips or forming sealing abutments}  |
|            | • • • {the convection or radiation in a hollow  | 2003/2639 {Provisions for fittings, e.g. locks or   |
|            | space being reduced, e.g. by subdividing the  | hinges}   |
|            | hollow space}   | 2003/26392 {Glazing bars}   |
|            | • • • • { with separate thin walled inserts }   | 2003/26394 {Strengthening arrangements in case of fire}   |
| 2003/26329 | the insulating strips between the metal   | 2003/26396 {specially adapted for sheet metal frames}   |
| 2002/2622  | sections being interconnected}  | 2003/26398 { with two metal sections clamping a pane} 3/267 with insulating elements formed in situ                 |
| 2003/2033  | • • • • { the insulating strips between the metal sections having ribs extending into the   | 3/2675 {combined with prefabricated insulating  |
|            | hollow space}   | elements}   |
| 2003/26332 | {Arrangements reducing the heat transfer in   | 3/273 with prefabricated insulating elements held   |
|            | the glazing rabbet or the space between the   | in position by deformation of portions of the   |
|            | wing and the casing frame}  | {metal} frame members   |
| 2003/26334 | (Contact reducing arrangements between the  | 3/2735 {comprising a sheet metal member, an   |
| 2/0/22     | insulating strips and the metal sections}   | edge or which is bent over the edge of the  |
| 3/26336    | • • • {with two metal frame members having interpenetrating or overlapping parts when   | other metal member with interposition of an insulating element}   |
|            | mounted (involving sheet metal section  | 3/277 with prefabricated insulating elements held in  |
|            | members <u>E06B 3/2735</u> )}   | position by expansion of the {extremities of  |
| 3/26338    | • • • {comprising short insulating elements disposed  | the} insulating elements  |
|            | at intervals}   | 3/28 with additional removable glass panes or the like,   |

framed or unframed

| 3/285    | • • • {flexible transparent foils without a proper frame fixed and sealed at a distance from the                 | 3/4415              | • • • • {Double-hung, i.e. with two vertical sliding panels}                        |
|----------|--|---------------------|---|
|          | existing glass pane}   | 3/4423              | • • • • {disappearing in a wall pocket; Pockets                                     |
| 3/30     | • Coverings, e.g. protecting against weather,  |                     | therefor}   |
|          | for decorative purposes {(for door leaves  | 3/443               | • • • • {specially adapted for furniture}   |
| 3/301    | <ul><li>E06B 3/7001)}</li><li>. {consisting of prefabricated profiled members or</li></ul>                       | 2003/4438           | • {characterised by the material used for the                                       |
| 3/301    | glass}   | 2002/4446           | frames}   |
| 3/302    | • • {Covering wooden frames with metal or plastic  | 2003/4446           | {Wood}  |
| 3/302    | profiled members}  | 2003/4453 2003/4461 | {Metal}   |
| 3/303    | • • • {Covering metal or plastic frames with wooden  | 2003/4461           | <ul><li> {Plastics}</li><li> {with at least two frames made from</li></ul>          |
| 3/304    | profiled members} {the frames consist of two metal section   |                     | different materials}  |
| 3/305    | members with insulating zone in between} {Covering metal frames with plastic or metal                            | 2003/4476           | • • • • {Coverings, e.g. for protecting against weather or for decorative purposes} |
|          | profiled members}  | 2003/4484           | Special provisions for mounting or dismounting sashes                               |
| 3/306    | {Covering plastic frames with metal or plastic   | 2003/4492           | • • • • {provided with screens}   |
| 3/307    | <ul><li>profiled members}</li><li>• • {Coverings with special provisions for</li></ul>                           | 3/46                | • • • Horizontally-sliding wings {(E06B 3/487)                                      |
| 3/307    | insulation, e.g. foam filled}  |                     | takes precedence)}  |
| 3/308    | • • {Wing frames covered on the outside by a rigidly-  | 3/4609              | {for windows  |
| 3/300    | mounted outer frame}   |                     | ( <u>E06B 3/4654</u> - <u>E06B 3/4681</u> take precedence)}                         |
| 3/32     | Arrangements of wings characterised by the manner  | 3/4618              | • • • • • {the sliding wing being arranged beside                                   |
|          | of movement; Arrangements of movable wings   | 3/4016              | a fixed wing (E06B 3/4627 takes   |
|          | in openings; Features of wings or frames relating  |                     | precedence)}  |
|          | solely to the manner of movement of the wing   | 3/4627              | • • • • • { with the sliding wing flush closing or                                  |
|          | {(fittings or supporting means, separable from the   |                     | moving a considerable distance towards  |
|          | frame, for guiding or controlling the movement<br>of wings, arrangements of wings characterised by               |                     | the opening when closing}   |
|          | particular forms of such means <u>E05D</u> )}  | 3/4636              | • • • • • {for doors ( <u>E06B 3/4609</u> and                                       |
| 3/325    | • • {Wings opening towards the outside}  |                     | <u>E06B 3/4654</u> - <u>E06B 3/4681</u> take  |
| 3/34     | • with only one kind of movement (E06B 3/48  |                     | precedence; sliding shower doors  |
|          | takes precedence)  | 3/4645              | A47K 3/34)} { with the sliding wing flush closing or                                |
| 3/341    | {Tilt-and-turn wings}  | 3/4043              | moving a considerable distance towards  |
| 2003/343 | • • • { with at least two axes of rotation without   |                     | the opening when closing}   |
|          | additional frame within the wing}  | 3/4654              | {disappearing in pockets in the wall;   |
| 2003/345 | • • • { with additional rotating frame within the  |                     | Pockets therefor}   |
| 2002/245 | wing}  | 3/4663              | • • • • {specially adapted for furniture}   |
| 2003/346 | • • • { where the additional frame rotates around a  | 3/4672              | • • • • • { with the sliding wing flush closing or                                  |
| 2003/348 | vertical axis}   |                     | moving a considerable distance towards  |
| 2003/346 | • • • {where the additional frame rotates around a horizontal axis}  | 2/4/01              | the opening when closing}   |
| 3/36     | • • • with a single vertical axis of rotation at one   | 3/4681              | • • • • {made of glass panes without frames (E06B 3/4663 takes precedence)}         |
| 3/30     | side of the opening, or swinging through the   | 3/469               | • • • • {Arrangements at the overlapping vertical                                   |
|          | opening (wings requiring lifting before opening  | 3/409               | edges of the wings that engage when   |
|          | E06B 3/52)   |                     | closing}  |
| 3/362    | • • • {Double winged doors or windows}   | 3/48                | Wings connected at their edges, e.g. foldable                                       |
| 3/365    | • • • • {Astragals for double doors}   |                     | wings   |
| 3/367    | • • • {specially adapted for furniture}  | 3/481               | • • • {Wings foldable in a zig-zag manner or bi-fold                                |
| 3/38     | with a horizontal axis of rotation at the top or   |                     | wings}  |
|          | bottom of the opening $\{(\underline{E06B \ 3/5036} \ \text{takes})\}$   | 3/482               | • • • { specially adapted for furniture }   |
| 3/385    | precedence)}   | 3/483               | • • • • {folding upwardly ( <u>E06B 3/482</u> takes                                 |
| 3/383    | <ul><li> {specially adapted for furniture}</li><li> with a vertical or horizontal axis of rotation not</li></ul> | 2/405               | precedence)}  |
| 3/40     | at one side of the opening, e.g. turnover wings  | 3/485               | {Sectional doors}   |
| 2003/403 | • • • {where the axis of rotation is horizontal}   | 3/486               | • • • { with hinges being at least partially integral part of the section panels}   |
| 2003/406 | • • • {where the axis of rotation is vertical}   | 3/487               | • • • { sliding laterally }   |
| 3/42     | Sliding wings; Details of frames with respect to   | 3/488               | • • • {sinding facetary} • • • {with horizontal strengthening means; anti-          |
|          | guiding {(E06B 3/26347 and E06B 3/92 take  | 2, .00              | sag devices}  |
|          | precedence)}   | 3/50                | with more than one kind of movement   |
| 3/44     | Vertically-sliding wings   |                     | ( <u>E06B 3/48</u> takes precedence) { ( <u>E06B 3/92</u> takes                     |
| 3/4407   | • • • • {Single-hung, i.e. having a single vertical  |                     | precedence)}  |
|          | sliding panel}   |                     |   |

| 3/5009         | • • • {where the sliding and rotating movements are necessarily performed simultaneously (E06B 3/5027, E06B 3/5036 take precedence)} | 3/585     | • • • {adjustable, e.g. for accommodating panes of various thickness, or with provisions for altering the clamping force on the pane   |
|----------------|--|-----------|--|
| 3/5018         | • • • { where the pivot axis slides during pivoting  |           | (E06B 3/5871 takes precedence)}  |
| 3/5027         | of the wing } {"Austral" windows}  | 3/5857    | • • • {the fixing being adjustable, e.g. in one of several possible positions}   |
| 3/5036         | {Louvre type windows, e.g. windows made of   | 3/5864    | • • • • { with adjusting screws, wedges or cams }  |
|                | movable strips of glass}   | 3/5871    | • • { pivotally fixed on the frame; Borders with   |
| 3/5045         | • • • {specially adapted for furniture ( <u>E06B 3/52</u> takes precedence)}   | 3/5878    | <ul><li>pivoting parts}</li><li> {the borders being pre-assembled in a frame-</li></ul>  |
| 3/5054         | • • • { where the sliding and rotating movements are independent of each other}  |           | like manner on the pane or on the frame before the pane is fitted to the frame (E06B 3/645   |
| 3/5063         | • • • • {the vertical sliding wings having the possibility of an additional rotational   | 3/5885    | <ul><li>takes precedence)}</li><li>• (Corner arrangements for borders; Devices for making rounded corners)</li></ul>   |
| 0.7070         | movement}  | 2/5902    |  |
| 3/5072         | • • • • {the horizontal sliding wings having the possibility of an additional rotational   | 3/5892    | • • • {Fixing of window panes in openings in door leaves}  |
|                | movement}  | 3/60      | of clamping cleats of metal  |
| 3/5081         | • • • {at least two wings have a different kind of   | 3/605     | • • • {made of sheet metal}  |
| 2,200          | movement}  | 3/62      | • • • of rubber-like elastic cleats  |
| 3/509          | • • • { where one of the sliding and rotating  | 3/6202    |  |
|                | movements necessarily precedes the other}  |           | • • • {positioned between adjoining panes without separate glazing bar}  |
| 3/52           | • • • Wings requiring lifting before opening   | 3/6205    | {having on at least one lateral side no  |
| 3/54<br>3/5409 | <ul><li>Fixing of glass panes or like plates</li><li>• {Means for locally spacing the pane from the</li></ul>                        |           | backing from a separate rigid glazing bead or<br>other stiff part of the window frame}   |
| 3/3407         | surrounding frame}   | 2003/6208 | • • • { with adjustable dimensions }   |
| 2/5/119        |  |           | to the contract of the contrac |
| 3/5418         | • • {Permanently fixing of an additional unframed  |           | • • • • {with tear away strips}  |
| 0/7/07         | pane (compound frames E06B 3/2605)}  |           | • • • {specially adapted for glazing bars}   |
| 3/5427         | • • {the panes mounted flush with the surrounding  | 2003/6217 | • • • { with specific fixing means }   |
|                | frame or with the surrounding panes  | 2003/622  | • • • • {using nails or the like}  |
|                | ( <u>E06B 3/5436</u> takes precedence; supporting structures for curtain walls <u>E04B 2/885</u> )}                                  | 2003/6223 | • • • • { with protruding parts anchored in  |
| 3/5436         | • • {involving holes or indentations in the pane}  | 2002/6226 | grooves}   |
| 3/5445         | {Support arms engaging the holes or  | 2003/6226 | • • • • {with locking strips}  |
| 3/3443         | indentations}  | 2003/6229 | • • • • { with grooves anchoring the cleat on a rim}   |
| 3/5454         | <ul> <li>{inside U-shaped section members}</li> </ul>  | 2003/6232 | • • • • {using glue}   |
| 2003/5463      | • • • {in a preassembled frame, the pane being   | 2003/6235 | • • • {moulded on the pane}  |
|                | consecutively introduced obliquely, rotated and  | 2003/6238 | • • • {having extra functions}   |
|                | shifted}   |           |  |
| 2003/5472      | • • • {in an at least partly preassembled frame by   |           |  |
|                | introducing it through a slot in one of the frame members or inserting the pane before   | 2003/6244 | • • • • { with extra parts sealing against the bottom of the glazing rebate or against the edge of the pane }  |
|                | completing the frame}  | 2003/6247 | . ,  |
| 3/5481         | • • {by means of discrete fixing elements, e.g. glazing clips, glaziers points}  |           | or another window frame}   |
| 3/549          | • • {by clamping the pane between two subframes}   | 2003/625  | • • • {Specific form characteristics}  |
|                | <ul> <li>to y cramping the pane between two subtraines;</li> <li>by means of putty, cement, or adhesives only</li> </ul>             | 2003/6252 | • • • • {wedge-shaped}   |
| 3/56           |  | 2003/6255 | {H-shaped}   |
|                | (E06B 3/64 {E06B 3/5427} take precedence)  | 2003/6258 | {U-shaped}   |
| 3/58           | • by means of borders, cleats, or the like   | 2003/6261 | {S-shaped}   |
|                | $(\{\underline{\text{E06B 3/30}}\}, \underline{\text{E06B 3/64}} \text{ take precedence})$   | 2003/6264 |  |
| 3/5807         | • • { not adjustable }   |           | {hollow}   |
| 3/5814         | • • • {together with putty or fixed by glue}   | 2003/6267 | • • • • {consisting of several separate parts}   |
| 3/5821         | • • • {hooked on or in the frame member, fixed   | 2003/627  | • • • { with specific characteristics concerning the   |
|                | by clips or otherwise elastically fixed  | 2003/6273 | material } {reinforced, e.g. against elongation}   |
|                | $(\underline{E06B \ 3/585} \ takes \ precedence)$  |           | • • • • {remoted, e.g. against elongation} • • • • • {with parts of differing nature, e.g.   |
| 3/5828         | • • • • {on or with auxiliary pieces}  | 2003/02/0 |  |
| 3/5835         | • • • • • {together with parts of the border in  | 2002/22=2 | hardness}  |
|                | the same undercut groove in the frame  |           | • • • • {with coverings or embellisher strips}   |
|                | (E06B 3/5842 takes precedence)}  | 2003/6282 | • • • • {of cellular nature}   |
| 3/5842         | {fixed by a tongue-and-groove or mortise-  | 2003/6285 | • • • • {with provisions for receiving putty or  |
|                | and-tenon connection substantially parallel to   |           | pasty adhesives}   |
|                | the pane}  | 2003/6288 | • • • { with fire resisting properties }   |
|                | t)   | 2003/6291 | • • • {Corner arrangements}  |
|                |  |           | {corner arrangements} {using separate corner members}  |
|                |  | 2003/6294 | • • • • (using separate corner members)  |

| 2003/6297  | • • • { for glazing panels of special shape, e.g. with undulating or U-shaped cross-section }           |            | <ul><li> {comprising lighting means}</li><li> {with coatings}</li></ul>   |
|------------|---|------------|---|
| 3/64       | Fixing of more than one pane to a frame   |            | • • • {with coatings} • • • • {with special shapes}   |
| 3/01       | •   |            | • • • {with special shapes}   |
|            | <u>NOTE</u>   |            | {U-shape}   |
|            | Fixing of multiple glazing units to   | 3/667      | Connectors therefor   |
|            | frames is classified in the relevant groups   | 3/6675     | (for connection between the spacing   |
|            | $E06B \ 3/5409 - E06B \ 3/62$ , except for the  | 3/0073     | elements and false glazing bars}  |
|            | fixing thereof to frames designed for one pane only, which is classified in group E06B 3/645            | 3/67       | characterised by additional arrangements or devices for heat or sound insulation {or for the sound insulation } |
| 3/645      | • • • {of units comprising two or more parallel panes   |            | controlled passage of light}  |
|            | to frames designed for single panes only, e.g. having too shallow a rabbet}                             | 3/6707     | • • • {specially adapted for increased acoustical insulation (doors, windows for insulation                     |
| 3/66       | • Units comprising two or more parallel glass or like   |            | against noise E06B 5/20)  |
|            | panes permanently secured together {(reforming  | 3/6715     | • • • {specially adapted for increased thermal  |
|            | and uniting glass sheets by fusing <u>C03B 23/00</u> ;  |            | insulation or for controlled passage of light   |
|            | joining glass to glass or to other materials  |            | (E06B 3/66323 takes precedence; coating   |
| 2/6604     | <u>C03C 27/00;</u> laminated glass <u>B32B 17/10</u> )}   |            | of glass pains <u>C03C 17/00</u> ; devices or arrangements for controlling the intensity,                       |
| 3/6604     | • • {comprising false glazing bars or similar   |            | colour, phase, polarisation or direction of light   |
|            | decorations between the panes (connectors therefor E06B 3/6675)}  |            | G02F 1/00)}   |
| 3/6608     | • • {without separate spacing elements (E06B 3/6707   | 3/6722     | • • • { with adjustable passage of light }  |
| 3/0008     | and E06B 3/6715 take precedence)  | 3/673      | . Assembling the units (E06B 3/677 takes  |
| 3/6612     | Evacuated glazing units}  | 3/073      | precedence {; making hollow glass sheets or   |
| 3/6617     | <ul> <li>• {Evacuated glazing times}</li> <li>• {one of the panes being larger than another}</li> </ul> |            | bricks <u>C03B 23/24</u> })   |
| 3/6621     | <ul> <li>• (with special provisions for fitting in window)</li> </ul>                                   | 3/67304    | • • {Preparing rigid spacer members before  |
| 3/0021     | frames or to adjacent units; Separate edge  |            | assembly}   |
|            | protecting strips (E06B 3/66347 takes   | 3/67308    | • • • {Making spacer frames, e.g. by bending or   |
|            | precedence)}  |            | assembling straight sections (connectors  |
| 3/6625     | • • {molded on the edges}   |            | E06B 3/667)}  |
| 3/663      | Elements for spacing panes  |            | • • • • {by bending}  |
| 3/66304    | • • {Discrete spacing elements, e.g. for evacuated  | 3/67317    | • • • {Filling of hollow spacer elements with   |
|            | glazing units}  |            | absorbants; Closing off the spacers   |
| 3/66309    | • • • {Section members positioned at the edges of   |            | thereafter}   |
|            | the glazing unit}   | 3/67321    | {Covering spacer elements, e.g. with  |
| 3/66314    | • • • { of tubular shape ( $\underline{E06B \ 3/66323}$ and   | 2/67226    | sealants}   |
|            | E06B 3/66333 take precedence)}  |            | • • {Assembling spacer elements with the panes}   |
|            | • • • • {of rubber, plastics or similar materials}  | 3/6733     | • • • {by applying, e.g. extruding, a ribbon of hardenable material on or between the                           |
| 3/66323    | • • • {comprising an interruption of the heat flow  |            | panes}  |
| 2/66229    | in a direction perpendicular to the unit}   | 3/67334    | • • • {by soldering; Preparing the panes therefor}  |
| 3/66328    | • • • • {of rubber, plastics or similar materials   |            | • • • • (by soldering, Freparing the panes thereof) • • • {Working the edges of already assembled               |
|            | (E06B 3/66314, E06B 3/66323 and E06B 3/66342 take precedence; transparent                               | 3,07337    | units}  |
|            | materials E06B 3/66333)}  | 3/67343    | • • • {Filling or covering the edges with synthetic   |
| 3/66333    | • • • • { of unusual substances, e.g. wood or other   |            | hardenable substances}  |
| 2, 00333   | fibrous materials, glass or other transparent   | 3/67347    | {by extrusion techniques}   |
|            | materials}  | 3/67352    | • • • • {by forming techniques}   |
| 2003/66338 | {of glass}  | 3/67356    | {Covering the edges with bands or profiles}   |
|            | {characterised by their sealed connection to  | 3/6736     | • • • {Heat treatment (for soldering  |
|            | the panes}  |            | E06B 3/67334)}  |
| 3/66347    | • • • • { with integral grooves or rabbets for  | 3/67365    | • • • {Transporting or handling panes,  |
|            | holding the panes (E06B 3/66366 takes   |            | spacer frames or units during assembly  |
|            | precedence)}  |            | ( <u>E06B 3/67304</u> - <u>E06B 3/67339</u> take  |
| 3/66352    | • • • • { with separate sealing strips between the  | 0/4=040    | precedence)}  |
| 2/2-2-     | panes and the spacer}   |            | {Layout of the assembly streets}  |
|            | {Soldered connections or the like}  |            | • • • • {Rotating panes, spacer frames or units}  |
| 3/66361    | • • • { with special structural provisions for  | 2003/67378 | • • • {Apparatus travelling around the periphery  |
|            | holding drying agents, e.g. packed in special   | 2/67292    | of the pane or the unit}  |
| 2161211    | containers}   | 5/6/382    | {Transport of panes or units without  |
| 3/66366    | • • • { specially adapted for units comprising more than two panes or for attaching intermediate        | 2/67296    | touching the bottom edge}   |
|            | sheets}   | 3/0/380    | • • • {Presses; Clamping means holding the panes during assembly}   |
| 3/66371    | • • • {positioned entirely outside the gap between  | 3/67301    | • • • {Apparatus travelling around the periphery of   |
| 2,000,1    | the panes}  | 5,07571    | the pane or the unit}   |
|            | •   |            | * '   |

| 2003/67395 | • • • {Non-planar units or of curvilinear outline, e.g.  | 2003/7065 {Wood fibres}   |
|------------|--|---|
|            | for vehicles}  | 2003/7067 {of layered construction}   |
| 3/677      | • • Evacuating or filling the gap between the  | 2003/7069 {with cladding}   |
|            | panes {; Equilibration of inside and outside   | 2003/7071 {made of a plurality of separate blocks or  |
|            | pressure}; Preventing condensation in the gap  | strips}   |
|            | between the panes (by means of spacing elements <u>E06B 3/663</u> ); Cleaning the gap between the panes      | 2003/7073 {with fire retardant measures in frame}   |
| 3/6775     | • • {Evacuating or filling the gap during  | 2003/7074 {Metal frames}  |
| 3/0773     | assembly}  | 2003/7076 {insulated}   |
| 3/68       | • Window bars {(bay windows <u>E06B 1/363</u> ; joints for   | 2003/7078 { with fire retardant measures in frame}  |
| 3/00       | frame members crossing each other E06B 3/9628)}  | 2003/708 {insulated}  |
| 3/685      | • • {False glazing bars (E06B 3/6604 takes   | 2003/7082 {Plastic frames}  |
| 2,002      | precedence)}   | 2003/7084 {reinforced with metal or wood sections}  |
| 3/70       | • Door leaves (wing frames <u>E06B 3/04</u> )  | 2003/7086 {One-piece frames, e.g. made out of a single  |
| 3/7001     | • • {Coverings therefor; Door leaves imitating   | panel by cutting out a middle portion, moulded  |
|            | traditional raised panel doors, e.g. engraved or   | frames }  2003/7088 {Two-piece frames made of a stile and an U-                                 |
|            | embossed surfaces, with trim strips applied to the   | shaped part surrounding the panel}  |
|            | surfaces}  | 2003/709 {Frame parts being attached to both sides of the                                       |
| 3/7003     | • • {consisting of several adjacent similar elements,  | panel which extends till the door edge}   |
| 2/5005     | e.g. planks, without outer covering panels}  | 2003/7092 • • • { with frame members not directly or resiliently                                |
| 3/7005     | • • • {without a separate supporting frame}  | connected to each other}  |
| 3/7007     | • • {Door leaves with curved, e.g. cylindrical or oval   | 2003/7094 • • {with ventilated innerspace}  |
| 3/7009     | cross-section (E06B 3/7001 takes precedence)}  | 2003/7096 • • { with possibilities to alter the extension of the                                |
| 3/7009     | <ul> <li>{Door leaves with two similar parts placed one<br/>above the other, pivoting separately}</li> </ul> | door}   |
| 2003/7011  | with easily replaceable or interchangeable   | 2003/7098 {with bracing means crossing each other, e.g.   |
| 2003/7011  | panels}  | diagonally disposed}  |
| 2003/7013  | • • { put in place through a slot in the frame }   | 3/72 • consisting of frame and panels {, e.g. of raised   |
| 3/7015     | • • (characterised by the filling between two  | panel type ( <u>E06B 3/7001</u> - <u>E06B 3/7015</u> and  |
| 5,,015     | external panels (fireproof doors <u>E06B 5/16</u> ; noise  | E06B 3/82 take precedence)}   |
|            | insulating doors E06B 5/20)}   | 3/721 {with panels on one lateral side of the frame   |
| 3/7017     | • • { of grating type}   | only}   |
| 2003/7019  | • • {of corrugated type}   | 3/723 • • • {at least one side of the frame consisting solely of a bent panel edge}             |
| 2003/7021  | • • {consisting of wooden strips filling the whole   | 3/725 {with separate hollow frames, e.g. foam-filled}   |
|            | door}  | 3/726 {of metal}  |
| 2003/7023  | • • { of foam type }   | 3/728 {of sheet metal}  |
| 2003/7025  | • • {of cork; of wood or similar fibres}   | 3/74 with wooden panels {or frame ( <u>E06B 3/721</u> ,   |
| 2003/7026  | • • · {of granular type}   | E06B 3/725 and E06B 3/76 take precedence)   |
| 2003/7028  | • • { of cementituous type, e.g. concrete }  | 3/76 with metal panels {( <u>E06B 3/721</u> - <u>E06B 3/725</u>                                 |
|            | {containing a metallic layer}  | take precedence)}   |
| 2003/7032  | • • • {of non-vegetal fibrous material, e.g. glass or  | 3/78 with panels of plastics  |
| 2002/7024  | rock wool}   | $\{(\underline{\text{E06B } 3/721} - \underline{\text{E06B } 3/725} \text{ take precedence})\}$ |
| 2003/7034  | ( f d sbestos )  | 3/80 • • flexible {(upwardly folding flexible screens   |
| 2003/7036  | {of plaster}   | <u>E06B 9/262</u> )}  |
|            | {made from a slurry}   | 3/805 {folding sideways (doors of the bellows type  |
| 2003/704   | • • • {of mineral material which is not further specified}   | E06B 3/94)}   |
| 2003/7042  | • • • { with a fire retardant layer }  | 3/82 • Flush doors, i.e. with completely flat surface   |
|            | {Garage doors}   | (E06B 3/02, {E06B 3/7003 and E06B 3/7015}) take precedence)                                     |
|            | • • {with provisions for locks, hinges or other  | 3/822 {with an internal foursided frame}  |
| 2003/1040  | fittings}  | 3/825 {with a wooden frame}   |
| 2003/7048  | • • {with arcuate periphery; with openings having an   | 3/827 {of metal without an internal frame, e.g. with  |
|            | arcuate periphery}   | exterior panels substantially of metal}   |
| 2003/7049  | • • {Specific panel characteristics}   | 3/84 of plywood {or other wooden panels without   |
|            | {of layered construction involving different   | an internal frame, e.g. with exterior panels  |
|            | materials}   | substantially of wood}  |
| 2003/7053  | • • {corrugated}   | 3/86 • • • of plastics { without an internal frame, e.g. with                                   |
| 2003/7055  | • • {Left-right hinged interchangeable door leaves}  | exterior panels substantially of plastics}  |
| 2003/7057  | • • {with little passing through doors}  | 3/88 Edge-protecting devices for door leaves  |
| 2003/7059  | • • {Specific frame characteristics}   | ({astragals for double doors <u>E06B 3/365}</u> ); finger                                       |
| 2003/7061  | {Wooden frames}  | guards for doors or windows E06B 7/36)  |
| 2003/7063  | (reinforced; in combination with other   | 3/90 • Revolving doors; Cages or housings therefor (turnstiles <u>E06B 11/08</u> )              |
|            | materials, e.g. foam, honeycomb}   | (minsules <u>Doop 11/00</u> )   |

| 3/903    | • • {consisting of arcuate wings revolving around a parallel axis situated outside the wing, e.g. a cylindrical wing revolving around its axis | 3/9646          | • • • • { using two similar connecting pieces each connected with one or the frame members and drawn together at the joint } |
|----------|--|-----------------|--|
| 3/906    | <ul> <li>(E06B 3/906 takes precedence)}</li> <li>• {combining radially extending wings and separately movable arcuate wings}</li> </ul>        | 3/9647          | <ul> <li>. • {the connecting piece being part of or<br/>otherwise linked to the window or door<br/>fittings}</li> </ul>      |
| 3/92     | • Doors or windows extensible when set in position   | 3/9648          | {Mitre joints}   |
|          | (foldable wings <u>E06B 3/48</u> ; sliding wings for   | 3/9649          | • • • {Tie rods spanning the whole width or height   |
|          | windows E06B 3/42; wall-closing devices which  |                 | of the frame; Straps encircling the frame}   |
|          | may be rolled up, e.g. shutters, E06B 9/11)  | 3/968           | characterised by the way the connecting pieces   |
|          | $\{(\underline{\text{E06B 3/01}} \text{ takes precedence})\}$  |                 | are fixed in or on the frame members   |
| 3/921    | • • { with several parts mounted telescopically inside   | 3/9681          | • • • {by press fit or adhesion}   |
|          | each other}  | 3/9682          | • • • • {Mitre joints}   |
| 3/922    | • • {with several wings opening horizontally towards   | 3/9684          | • • • {by hooking protrusions on the connecting  |
|          | the same side of the opening and each closing  |                 | piece in openings of the frame member, e.g.  |
|          | a separate part of the opening (E06B 3/921 and   |                 | by snap-locking (E06B 3/972, E06B 3/976,   |
| 2/024    | E06B 3/928 take precedence)  |                 | E06B 3/98 take precedence)}  |
| 3/924    | • • • {positioned in one plane when closed}  | 3/9685          | • • • • {Mitre joints}   |
| 3/925    | • • {with several wings opening vertically towards   | 3/9687          | • • • { with screws blocking the connecting piece  |
|          | the same side of the opening and each closing  |                 | inside or on the frame member (E06B 3/972,   |
|          | a separate part of the opening (E06B 3/921 and E06B 3/928 take precedence)}  |                 | E06B 3/976 take precedence)  |
| 3/927    | • • {positioned in one plane when closed}  | 3/9688          | {Mitre joints}   |
| 3/928    | {Doors or windows of the lazy tongs type}  | 3/972           | by increasing the cross-section of the   |
| 3/94     | Doors of the bellows type  |                 | connecting pieces, e.g. by expanding the   |
| 3/96     | <ul> <li>Corner joints or edge joints for windows, doors,</li> </ul>   |                 | connecting pieces with wedges (E06B 3/976 takes precedence)  |
| 3/70     | or the like frames or wings {(E06B 3/663 takes   | 3/9725          | {Mitre joints}   |
|          | precedence)}   | 3/976           | by deformation of the frame members  |
| 3/9604   | • • {Welded or soldered joints ( <u>E06B 3/988</u> ,   | 3/7/10          | {(making sheet metal frames for openings   |
|          | E06B 3/99 take precedence; welding of plastics   |                 | B21D 53/74)}   |
|          | B29C 65/00, soldering or welding of metals   | 3/9765          | {Mitre joints}   |
|          | <u>B23K</u> )}   | 3/98            | the connecting pieces being specially adapted  |
| 3/9608   | {Mitre joints}   |                 | for drawing the frame members towards  |
| 3/9612   | • • {by filling in situ the hollow ends of the abutted   |                 | each other ( <u>E06B 3/9684</u> , <u>E06B 3/972</u> ,  |
| 2/0.51.5 | frame members with a hardenable substance}   |                 | E06B 3/976 take precedence)  |
| 3/9616   | • • {characterised by the sealing at the junction of the frame members ( <u>E06B 3/9632</u> takes precedence)}                                 | 3/982           | • • • • {Mitre joints}   |
| 3/962    | • • • {Mitre joints}   | 3/984           | specially adapted for frame members of wood  |
| 3/9624   | <ul><li>• (with means specially adapted for aligning the</li></ul>   |                 | or other material worked in a similar way  |
| 3/9024   | frontal surfaces of adjacent frame member ends   | 2/0945          | (E06B 3/99 takes precedence)   |
| 3/9628   | • {Mitre joints concealed to look like butt joints}  | 3/9845<br>3/988 | <ul><li> {Mitre joints}</li><li>. specially adapted for sheet metal frame members</li></ul>                                  |
| 3/9632   | • {between a jamb and the threshold or sill of   | 3/900           | with an open U-shaped cross-section  |
| 3/7032   | window or door frames}   | 3/9885          | {Mitre joints}   |
| 3/9636   | • • {for frame members having longitudinal screw   | 3/99            | for continuous frame members crossing each   |
|          | receiving channels}  | 3,77            | other with out interruption (window bars   |
| 3/964    | using separate connection pieces, e.g. T-  |                 | E06B 3/68)   |
|          | connection pieces ( <u>E06B 3/9604</u> - <u>E06B 3/9636</u>  | <b>5</b> /00    |  |
|          | and <u>E06B 3/984</u> - <u>E06B 3/99</u> take precedence)  | 5/00            | Doors, windows, or like closures for special purposes {(insulated compound frames  |
| 3/9641   | • • • {part of which remains visible ( <u>E06B 3/9647</u>  |                 | specially adapted for sliding doors or windows   |
|          | takes precedence)}   |                 | E06B 3/26347); Border constructions therefor   |
| 3/9642   | • • • {Butt type joints with at least one frame  | 5/003           | • {Storm doors; Combination-screen-and-storm-  |
|          | member cut off square; T-shape joints (E06B 3/9641, E06B 3/9644, E06B 3/9647,  | 2,002           | doors}   |
|          | E06B 3/9649, E06B 3/968 take precedence)   | 5/006           | • {for furniture ( <u>E06B 3/00</u> , <u>E06B 9/115</u> take   |
| 3/9643   | • • • { for frame members being in one line with   |                 | precedence)}   |
| 2,7013   | each other}  | 5/01            | . Trap-doors   |
| 3/9644   | • • • {L-shaped corner pieces having two articulated   | 5/02            | <ul> <li>for out-buildings or cellars; Other simple closures</li> </ul>  |
|          | or flexible joined legs; Corner joints with  |                 | not designed to be close-fitting   |
|          | variable angle}  | 5/025           | • • {Provisional closures, e.g. temporary security   |
| 3/9645   | • • • {Mitre joints ( <u>E06B 3/9641</u> , <u>E06B 3/9644</u> ,  |                 | doors}   |
|          | E06B 3/9647, E06B 3/9649, E06B 3/968 take  | 5/04            | • with fixed wooden frames   |
|          | precedence)}   | 5/06            | • with fixed metal frames  |
|          |  | 5/08            | with fixed frames made of concrete, stone-like  meterial or plastics.  |
|          |  |                 | material or plastics   |

| 5/10     | for protection against air-raid or other war-like action; for other protective purposes | 7/088    | with facing protective grille or safety guard  |
|----------|---|----------|--|
| 5/103    | • • {safety foils therefor}   | 7/09     | mounted in movable wing, e.g. door   |
| 5/106    | • • {Frames for bullet-proof windows (transparent                                       | 7/092    | operable in two or more distinct sets  |
|          | bullet-proof laminates F41H 5/0407)}  | 7/094    | operable in sequence; characterised by   |
| 5/11     | against burglary  |          | additional independent movement  |
| 5/113    | • • {Arrangements at the edges of the wings, e.g.                                       | 7/096    | operated or interconnected by gearing  |
|          | with door guards to prevent the insertion of  |          | (wing operators with gearing in general  |
|          | prying tools (protection of the locking region  |          | E05F 11/00)  |
|          | by preventing insertion of a tool <u>E05B 17/2003</u> ;                                 | 7/098    | with weather seal  |
|          | means to prevent forced opening by attack,  | 7/10     | • • by special construction of the frame members   |
|          | tampering or jimmying of lock <u>E05B 17/2084</u> ;                                     | 7/12     | <ul> <li>Measures preventing the formation of condensed</li> </ul>   |
|          | anti-tamper devices arranged on or near the   |          | water (double glazing <u>E06B 3/24</u> - <u>E06B 3/28</u>  |
| 5/116    | hinges <u>E05D 11/0018</u> )} {Arrangements preventing the removal of                   |          | {and E06B 3/677}; heating arrangements   |
| 3/110    | glazing panels}   |          | specially adapted for transparent or reflecting areas  |
| 5/12     | against air pressure, explosion, or gas   | 7/14     | H05B 3/84)   |
| 5/125    | {Closures for relieving excess pressure inside  | 7/14     | <ul> <li>Measures for draining-off condensed water or<br/>water leaking-in {frame members for draining off</li> </ul>      |
| 3/123    | the building}   |          | condensation water, throats at the bottom of a sash}   |
| 5/14     | Gasproof doors or similar closures; Adaptation  | 2007/145 | • • {for glass façade, e.g. curtain wall}  |
|          | of fixed constructions therefor   | 7/16     | Sealing arrangements on wings or parts co-   |
| 5/16     | Fireproof doors or similar closures; Adaptations  | ,,10     | operating with the wings ({specially adapted   |
|          | of fixed constructions therefor   |          | for fireproof or similar closures <u>E06B 5/164</u> ; }  |
| 5/161    | • • • {Profile members therefor}  |          | E06B 7/098 takes precedence {; fixed sealing   |
| 5/162    | • • • {Fireproof doors having windows or other  |          | joints E04B 1/68; devices for fitting sealing strips   |
|          | openings, e.g. for permitting ventilation or  |          | <u>E04F 21/00</u> })   |
|          | escape}   | 7/18     | by means of movable edgings, e.g. draught  |
| 5/164    | • • • {Sealing arrangements between the door or   |          | sealings additionally used for bolting {, e.g. by  |
|          | window and its frame, e.g. intumescent seals  | 7/20     | spring force or with operating lever}  |
| 5/165    | specially adapted therefor} {Fireproof windows (layered glass panes                     | 7/20     | <ul> <li>automatically withdrawn when the wing is<br/>opened {, e.g. by means of magnetic attraction,</li> </ul>           |
| 3/103    | with expansion layers for fire protection   |          | a pin or an inclined surface, especially for sills}  |
|          | B32B 17/10311)}   | 2007/202 | {Actuator connected to wing frame}   |
| 5/167    | • • • {Devices blocking doors or windows inside its                                     | 7/205    | with sealing strip mounted on sill   |
|          | frame in case of fire}  | 7/21     | with sealing strip movable in plane of wing  |
| 5/168    | • • • {Shape of edges of wing and/or its frame  | 7/215    | with sealing strip being moved to a retracted  |
|          | specially adapted therefor}   |          | position by elastic means, e.g. springs  |
| 5/18     | against harmful radiation (against heat   | 7/22     | • • by means of elastic edgings, e.g. elastic rubber   |
| 7 /O.O.  | E06B 5/16)  |          | tubes; by means of resilient edgings, e.g. felt or   |
| 5/20     | • for insulation against noise  |          | plush strips, resilient metal strips (E06B 7/18  |
| 5/205    | • • {windows therefor}  | 7/23     | takes precedence)  |
| 7/00     | Special arrangements or measures in connection  | 7/2301   | <ul><li>. Plastic, sponge rubber, or like strips or tubes</li><li> {without an integrally formed part for fixing</li></ul> |
|          | with doors or windows ({arrangements against  | 7/2301   | the edging}  |
|          | burglary at the edges of the wings $\underline{E06B 5/113}$ ;                           | 7/2303   | {hollow}   |
|          | screening or similar protective devices <u>E06B 9/00</u> )                              | 7/2305   | • • • {with an integrally formed part for fixing the   |
| 7/02     | • for providing ventilation, e.g. through double  |          | edging (E06B 7/2316 takes precedence)}   |
|          | windows; Arrangement of ventilation roses (airflow                                      | 7/2307   | • • • • • { with a single sealing-line or -plane   |
| 2007/023 | control members <u>per se F24F 13/08</u> )  {Air flow induced by fan}                   |          | between the wing and the part co-  |
| 2007/025 | {With air flow between panes}   |          | operating with the wing}   |
| 7/03     | Ventilating devices for inserting under upwardly-                                       | 7/2309   | • • • • • {with a hollow sealing part}   |
| 7703     | sliding windows (rain or draught deflectors   | 7/231    | • • • • • {with a solid sealing part}  |
|          | E06B 7/26)  | 7/2312   | • • • • {with two or more sealing-lines or -planes   |
| 7/04     | • • with ventilation wings ( <u>E06B 7/08</u> takes                                     |          | between the wing and part co-operating   |
|          | precedence)   | 7/2314   | with the wing} {characterised by the material}   |
| 7/06     | • • • with one ventilation wing only  | 7/2314   | • • • {characterised by the material} • • • • {used as a seal between the floor and the                                    |
| 7/08     | . Louvre doors, windows or grilles  | 1/2310   | wing }   |
|          | {(shutters <u>E06B 9/04;</u> louvre awnings   | 7/2318   | • • • {by applying over- or under-pressure, e.g.   |
| 7/000    | <u>E04F 10/08</u> - <u>E04F 10/10</u> )}  | 2010     | inflatable (gasproof doors or windows  |
| 7/082    | • • • with rigid or slidable lamellae   |          | E06B 5/12; for vehicles B60J 10/244)}  |
| 7/084    | with rotatable lamellae   | 7/232    | Resilient strips of hard material, e.g. metal  |
| 7/086    | interconnected for concurrent movement  | 7/24     | without separate sealing members, e.g. with  |
|          |   |          | labyrinth  |

| 7/26     | • Rain or draught deflectors, e.g. under sliding wings {also protection against light for doors}                              | 9/0661        |     |    | • • • {Lazy tongue, pantograph or scissor-like systems in the plane of the opening}       |
|----------|---|---------------|-----|----|---|
| 7/28     | • Other arrangements on doors or windows, e.g. door-  | 9/0669        |     |    | • {stored in a zig-zag arrangement}   |
|          | plates, windows adapted to carry plants, hooks for  | 9/0676        |     |    | • { stored in a stacked configuration }   |
|          | window cleaners {(edge protecting devices for   | 2009/0684     |     |    | • • {stored in a spiral like arrangement}   |
|          | door leaves E06B 3/88; special glazing; emergency   | 9/0692        |     |    | {comprising flexible sheets as closing screen}  |
|          | glazing; double glazing <u>E06B 3/66</u> )}   | 9/08          |     |    | coll-type closures (roller blinds E06B 9/40;  |
| 7/285    | • • {Finger plates (escutcheons <u>E05B 15/02</u> )}  | 2/00          | • • |    | perating, guiding or securing devices or  |
| 7/30     | Peep-holes; Devices for speaking through; Doors having windows  |               |     | aı | rrangements for roll-type closures E06B 9/56; sable only as awnings E04F 10/06)           |
| 2007/305 | {Microphone}  | 9/11          |     |    | Roller shutters   |
| 7/32     | Serving doors; Passing-through doors {; Pet-  |               |     |    |   |
| 1/32     | doors}  | 9/115         |     |    | • {specially adapted for furniture}   |
| 7/34     | Doors containing cupboards (cabinet)  | 9/13          | • • | •  | <ul> <li>with closing members of one piece, e.g. of<br/>corrugated sheet metal</li> </ul> |
| .,,      | constructions per se A47B)  | 2000/125      |     |    | _   |
| 7/36     | Finger guards {or other measures preventing}  | 2009/135      |     |    | • {Horizontal shutter reinforcements}   |
| 7730     | harmful access between the door and the door  | 9/15          | • • | •  | • with closing members formed of slats or the   |
|          | frame (safety devices for doors in railway  | 2000/1505     |     |    | like  |
|          | cars <u>B61D 19/026</u> ; for lift doors <u>B66B 13/26</u> ;  |               |     |    | • • {Slat details}  |
|          | detection of obstructions $\underline{E05F 15/40}$ )  |               |     |    | {Coatings}  |
| 7/362    | • • • {the gap between the door and the door frame  | 2009/1516     |     | •  | • • • {Means to increase resistance against   |
| 17302    | at the hinge side being constructed in a way to   |               |     |    | bending}  |
|          | remain too small or too wide to cause injury}   | 2009/1522     |     | •  | • • {Sealing joint between adjacent slats}  |
| 2007/365 | Rounded shape at gap, e.g. cylindrical  | 2009/1527     |     |    | • • • {Transparent slats or transparent   |
| 7/367    | <ul> <li>• • • (Rounded shape at gap, e.g. Symmetrical)</li> <li>• • (by covering the gap between the door and the</li> </ul> |               |     |    | sections in slats}  |
| 7/307    | door frame at the hinge side}   | 2009/1533     |     |    | • • {Slat connections}  |
|          | door traine at the imige side;  | 2009/1538     |     |    | • • {Slats directly connected}  |
| 9/00     | Screening or protective devices for {wall or  | 2009/1544     |     |    | {Engaging section has curved  |
|          | similar} openings, with or without operating  |               |     |    | articulation surfaces}  |
|          | or securing mechanisms; Closures of similar   | 2009/155      |     |    | • • {Slats connected by separate elements}  |
|          | <b>construction</b> (E06B 5/10 takes precedence; wings  | 2009/1555     |     |    | • • • {Flexible elements, e.g. tapes, strips,   |
|          | for doors or windows, connected at their edges,   |               |     |    | cords or chains}  |
|          | E06B 3/48; additional indoor equipment of doors or  | 2009/1561     |     |    | {Strips}  |
|          | windows, not forming part of the proper finishing   |               |     |    | • • • {Rigid elements, e.g. hinges, hooks or  |
|          | work of a building, e.g. curtains, <u>A47H</u> ; gratings as  |               |     | Ī  | profiles}   |
|          | building elements <u>E04C 2/24</u> ; fastening means <u>E05</u> ;   | 2009/1572     |     |    | • • {Locking means to prevent slat  |
|          | operating-mechanisms for wings in general <u>E05F</u> )   | 2007/10/2     |     | ٠  | disengagement)  |
| 2009/002 | • {Safety guards or gates}  | 2009/1577     |     |    | • • {Slat end pieces used for guiding shutter}  |
| 2009/005 | • {Storm panels; hurricane shutters}  |               |     |    | • • {inserted in slat cavity}   |
| 2009/007 | • {Flood panels}  |               |     |    | {inserted in engaging section of adjacent   |
| 9/01     | <ul> <li>Grilles fixed to walls, doors, or windows; Grilles</li> </ul>  | 2007/1200     | • • | •  | slats}  |
|          | moving with doors or windows; Walls formed as   | 2009/1594     |     |    | • • { attached to outer surface of slat }   |
|          | grilles, e.g. claustra {(emergency release of window  | 9/165         |     |    | <ul> <li>with slats disappearing in each other; with</li> </ul>                           |
|          | grilles E05B 65/1033; security bars for wings   | <i>)/</i> 103 | • • | •  | slats the distance between which can be   |
|          | <u>E05C 19/003</u> )}   |               |     |    | altered   |
| 2009/015 | {Mounting details}  | 9/17          |     |    | • Parts or details of roller shutters, e.g.   |
| 9/02     | <ul> <li>Shutters, movable grilles, or other safety closing</li> </ul>  | <i>7/17</i>   | • • | •  | suspension devices, shutter boxes, wicket   |
|          | devices, e.g. against burglary (louvre windows or   |               |     |    | doors, ventilation openings   |
|          | grilles <u>E06B 7/08</u> ; lamellar blinds <u>E06B 9/26</u> )   | 9/17007       |     |    | • • {Shutter boxes; Details or component parts  |
| 9/04     | • of wing type, e.g. revolving or sliding {(trap  | 3/17007       | • • | •  | thereof}  |
|          | doors; louvre doors or windows <u>E06B 7/08</u> )}  | 0/17015       |     |    | • • {made of at most two pieces; Front  |
| 9/06     | • collapsible or foldable, e.g. of the bellows or lazy-   | 2/17013       | • • | •  | opening details}  |
|          | tongs type (bellows-type doors E06B 3/94; roll-   | 0/17023       |     |    | • • {made of more than two pieces}  |
|          | type grilles <u>E06B 9/18</u> )   | 9/1703        |     |    | <ul><li> {Fixing of the box; External plastering</li></ul>                                |
| 9/0607   | • • • {comprising a plurality of similar rigid closing  | 9/1/03        | • • | •  | of the box}   |
|          | elements movable to a storage position}   | 2000/17029    |     |    |   |
| 9/0615   | • • • {characterised by the closing elements}   |               |     |    | {Shutter cleaning arrangements}   |
| 9/0623   | · · · · {Grilles}   |               |     |    | {Bottom bars}   |
| 9/063    | {Bars or rods perpendicular to the closing  |               |     |    | • • {Door in shutter screen; wicket door}   |
|          | direction}  |               |     |    | • • {Connection of the box to the guides}   |
| 9/0638   | {Slats or panels}   |               |     |    | • {Insulation}  |
| 9/0646   | {characterised by the relative arrangement of   |               |     |    | • • {Sealing or antirattling arrangements}  |
|          |   | 2009/17084    |     |    | • • {closing outlet slot of shutter box}  |
|          | the closing elements in the stored position}  |               |     |    |   |
| 9/0653   | the closing elements in the stored position} { stored side by side in the closing plane}                                      |               |     |    | {Manufacturing}   |

| 9/171     | Rollers therefor; Fastening roller shutters to rollers                                | 9/302 without ladder-tape, e.g. with lazy-tongs, with screw spindle          |
|-----------|---|--|
| 2009/1713 | {Telescopic rollers}  | 9/303 with ladder-tape   |
|           | {Arrangements to improve rolling of the   | 9/304 with tilting bar and separate raising shaft                            |
|           | shutter on the roller}  | 9/305 with tilting bar and raising cords guided                              |
| 9/172     | by clamping bars  | along fixed bar  |
| 9/173     | by clasps or buttons  | 9/306 with tilting bar along which the raising                               |
| 9/174     | Bearings specially adapted therefor   | cords are guided   |
| 2009/1743 | {allowing radial roller movement}   | 9/307 Details of tilting bars and their operation                            |
| 2009/1746 | {Axial connection of rollers}   | 9/308 with coaxial tilting bar and raising shaft                             |
| 9/18      | Roll-type grilles   | 9/32 Operating, guiding, or securing devices                                 |
| 9/24      | • Screens or other constructions affording protection                                 | therefor (operation of tilting bars  |
|           | against light, especially against sunshine; Similar                                   | E06B 9/307)  |
|           | screens for privacy or appearance; {Slat blinds}                                      | 9/322 Details of operating devices, e.g.                                     |
|           | (operating, guiding or securing devices or  | pulleys, brakes, spring drums, drives  |
|           | arrangements for roll-type closures E06B 9/56; free-                                  | ({operating devices <u>E06B 9/68</u> };                                      |
|           | hanging flexible screens A47H 23/00)  | devices of general interest specially  |
| 2009/2405 | • • {Areas of differing opacity for light transmission                                | adapted or mounted for storing and   |
|           | control}  | repeatedly paying-out and re-storing lengths of material <u>B65H 75/34</u> ) |
| 2009/2411 | {Coloured fluid flow for light transmission   |  |
| 2000/2415 | control}  | 2009/3222 {Cordless, i.e. user interface without cords}                      |
|           | • • {Light path control; means to control reflection}                                 | 2009/3225 {Arrangements to aid the winding of                                |
|           | • • {Combinations of at least two screens}  | cords rollers}   |
|           | • • • {One vertical sheet and slats}  | 2009/3227 {Axially moving rollers}   |
|           | {Two vertical sheets and slats in-between}  | 9/323 Structure or support of upper box                                      |
|           | {Screens joined one below the other}  | 9/324 Cord-locks {(cord-locks for curtains                                   |
|           | {Parallel screens}  | A47H 3/00)}  |
|           | • • • {moving independently}  | 9/325 Immobilising devices preventing raising                                |
|           | {moving simultaneously}   | 9/326 Details of cords, e.g. buckles, drawing                                |
| 2009/2404 | (featuring transparency control by applying voltage, e.g. LCD, electrochromic panels) | knobs  |
| 2009/247  | {Electrically powered illumination}   | 2009/3265 {Emergency release to prevent                                      |
|           | {Solar cells}   | strangulation or excessive load}   |
| 2009/2482 | • {Special shape}   | 9/327 Guides for raisable lamellar blinds with                               |
| 2009/2488 | {Curved perimeter}  | horizontal lamellae  |
| 2009/2494 | {Trapezoidal or triangular}   | 9/34 roller-type; {Roller shutters with adjustable lamellae}                 |
| 9/26      | • Lamellar or like blinds, e.g. venetian blinds {(for                                 | 9/36 with vertical lamellae {; Supporting rails                              |
|           | vehicles <u>B60J 1/2088</u> )}  | therefor}  |
| 9/262     | with flexibly-interconnected horizontal   | 9/361 {Transmissions located at the end of the                               |
|           | or vertical strips; Concertina blinds {, i.e.   | supporting rail}   |
| 2000/2/22 | upwardly folding flexible screens}  | 9/362 {Travellers; Lamellae suspension stems}                                |
| 2009/2622 | Gathered vertically; Roman, Austrian or   | 9/364 {Operating mechanisms therein}   |
| 2000/2625 | festoon blinds}   | 9/365 {Distance pieces therefor}   |
| 2009/2625 | • • • {Pleated screens, e.g. concertina- or accordion-like}                           | 9/367 {Lamellae suspensions ( <u>E06B 9/362</u> takes                        |
| 2009/2627 | • • • {Cellular screens, e.g. box or honeycomb-                                       | precedence); Bottom weights; Bottom  |
| 2007/2027 | like}   | guides}  |
| 9/264     | Combinations of lamellar blinds with roller   | 9/368 {Driving means other than pulling cords}                               |
|           | shutters, screen windows, windows, or double  | 9/38 Other details   |
|           | panes; Lamellar blinds with special devices   | 9/382 Details of ladder-tapes or ladder chains, e.g.                         |
| 2009/2643 | {Screens between double windows}  | buckles for local shortening of tapes  |
| 2009/2646 | {Magnetic screen operator}  | 9/384 Details of interconnection or interaction of                           |
| 9/266     | Devices or accessories for making or mounting   | tapes and lamellae  9/386 Details of lamellae                                |
|           | lamellar blinds or parts thereof {(cleaning   | 9/388 Details of lamenae  9/388 Details of bottom or upper slats or their    |
|           | of lamellar blinds A47L 4/00; joining   | attachment   |
|           | plastics plates for making venetian blinds  | 9/40 • Roller blinds (usable only as awnings                                 |
| 0/29      | B29C 66/437)} with horizontal lamellae, e.g. non-liftable                             | E04F 10/06)  |
| 9/28      | (louvre windows or gratings <u>E06B 7/08</u> )  | 2009/402 {adjustable without the use of tools or cutting                     |
| 2009/285  | • • • {Means for actuating a rod (being tilt rod or                                   | instruments}   |
| 2007/203  | lift rod)}  | 2009/405 {Two rollers}   |
| 9/30      | liftable  | 2009/407 {Telescopic roller}   |
| 2,30      | •   | -  |

| 9/42      | • • Parts or details of roller blinds, e.g. suspension devices, blind boxes (brackets or adjustable | 2009/6872 | • • • {using counters to determine shutter position}            |
|-----------|---|-----------|---|
|           | mountings for roller blinds and drawable  | 2009/6881 | {Mechanical counters}   |
| 2000/425  | curtains <u>A47H 1/13</u> )   | 2009/689  | • • • • {using end switches}                                    |
| 2009/425  | • • • {Pull chain or cord attached to bottom edge of screen}  | 9/70      | comprising an electric motor positioned outside the roller      |
| 9/44      | Rollers therefor; Fastening roller blinds to rollers  | 9/72      | • • • comprising an electric motor positioned inside the roller |
| 2009/445  | • • • • {by adhesive}   | 2009/725  | • • • { with epicyclic or planetary gear train }                |
| 9/46      | by clamping bars  | 9/74      | adapted for selective electrical or manual                      |
| 9/48      | by clasps or buttons  |           | operation   |
| 9/50      | Bearings specially adapted therefor   | 9/76      | using crank handles   |
| 9/52      | • Devices affording protection against insects, e.g. fly  | 9/78      | • • for direct manual operation, e.g. by tassels, by            |
|           | screens; Mesh windows for other purposes {(screens  | 3,70      | handles   |
|           | A47G 5/00)}   | 2009/785  | • • {by belts, straps, bands, tapes, cords, tassels}            |
| 9/521     | • • {Frameless fly screens; Tensioning means  | 9/80      | Safety measures against dropping or unauthorised                |
|           | therefor (E06B 9/54 takes precedence)}  | 2/00      | opening; Braking or immobilising devices;                       |
| 9/522     | • • {Dimensionally adjustable fly screens (E06B 9/54  |           | Devices for limiting unrolling (securing devices                |
|           | and E06B 9/521 take precedence)}  |           | or arrangements for direct manual operation                     |
| 2009/524  | • • {Mesh details}  |           | E06B 9/78)  |
| 2009/525  | • • {Patches for mesh repair or decoration}   | 2009/801  | {Locking arrangements}  |
| 2009/527  | • • {Mounting of screens to window or door}   | 2009/802  | • • • {located in or close to shutter box}                      |
| 2009/528  | Screens extending between movable wing and  | 2009/804  | {acting directly on the shutter}                                |
| 2007/320  | fixed frame of window or door}  | 2009/805  | {located on or in the guides}                                   |
| 9/54      | Roller fly screens (operating, guiding or securing)   | 2009/807  | {Brakes preventing fast screen movement}                        |
| 7/54      | devices therefor <u>E06B 9/56</u> )   | 2009/807  | {Fluid brakes}  |
| 2009/543  | {Horizontally moving screens}   |           |   |
| 2009/546  | • • {connected to end- or bottom-bar of roller  | 9/82      | • • automatic   |
| 2007/340  | shutter}  | 9/84      | against dropping  |
| 9/56      | Operating, guiding or securing devices or   | 9/86      | against unauthorised opening                                    |
| 7/30      | arrangements for roll-type closures; Spring drums;  | 9/88      | for limiting unrolling  |
|           | Tape drums; Counterweighting arrangements   | 2009/885  | <b>Braking mechanism activated by the</b>                       |
|           | therefor (devices of general interest specially   | 0/00      | bottom bar}   |
|           | adapted or mounted for storing and repeatedly   | 9/90      | for immobilising the closure member in                          |
|           | paying-out and re-storing lengths of material   | 2000/005  | various chosen positions  |
|           | <u>B65H 75/34</u> )   | 2009/905  | {using wrap spring clutches}                                    |
| 9/58      | Guiding devices   | 9/92      | Means allowing the closures to be shifted out of                |
| 9/581     | • • • {Means to prevent or induce disengagement of  |           | the plane of the opening  |
|           | shutter from side rails}  | 11/00     | Means for allowing passage through fences,                      |
| 9/582     | • • • {Means to increase gliss, light, sound or   |           | barriers or the like, e.g. stiles (general features             |
|           | thermal insulation}   |           | of doors <u>E06B 1/00</u> - <u>E06B 9/00</u> ; {cattle grids    |
| 2009/583  | • • • {Cords or cables}   |           | A01K 3/002; features peculiar to electrified wire               |
| 2009/585  | {Emergency release to prevent damage of   |           | fencing <u>A01K 3/005</u> })                                    |
|           | shutter or guiding device}  | 11/02     | . Gates; Doors  |
| 2009/586  | • • • { with heating to prevent frost or condensate }   | 11/021    | • • {Wire gates, e.g. traction gates; Fastenings                |
| 2009/587  | • • • {Mounting of guiding devices to supporting  |           | therefor (insulators, poles, handles, or the like, in           |
|           | structure}  |           | electric fences H01B 17/145)}                                   |
| 2009/588  | • • • {Sealings for guides}   | 11/022    | • • {characterised by the manner of movement}                   |
| 9/60      | Spring drums operated only by closure members   | 11/023    | • • • {where the gate opens within the plane of the             |
| 9/62      | • Counterweighting arrangements (E06B 9/60 takes  |           | gate}   |
|           | precedence)   | 11/025    | • • • {vertically}  |
| 9/64      | • • with lowerable roller   | 11/026    | • • • {horizontally}  |
| 9/66      | • • with a roller situated at the bottom  | 11/027    | • • • {where the gate rotates around a horizontal axis          |
| 9/68      | Operating devices or mechanisms, e.g. with  |           | parallel to the plane of the gate}                              |
|           | electric drive  | 11/028    | • • {with posts connected underground}                          |
| 2009/6809 | {Control}   | 11/04     | • characterised by the kind of suspension                       |
| 2009/6818 | • • • {using sensors}   |           | (suspensions per se E05D)                                       |
| 2009/6827 | • • • • {sensing light}   | 11/045    | • • • {exclusively for horizontally sliding gates}              |
| 2009/6836 | • • • • {sensing obstacle}  | 11/08     | . Turnstiles; {Gates for control of entry or exit of            |
| 2009/6845 | {sensing position}  |           | persons, e.g. in supermarkets} (control gates on                |
| 2009/6854 | • • • • (sensing position) • • • • (sensing torque)   |           | vehicles <u>B60N 5/00</u> ; {bank protection devices            |
| 2009/6863 | • • • • {sensing wind speed}  |           | <u>E05G 5/00</u> }; with registering means <u>G07C 9/02</u> ;   |
|           |   |           | {coin-freed facilities for turnstiles G07F 17/14})              |

# E06B

11/085 . {non-rotary or with a limited angle of rotation, e.g.  $90^{\circ}\}$