CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINES OR PUMPS

- F03 MACHINES OR ENGINES FOR LIQUIDS; WIND, SPRING, OR WEIGHT MOTORS; PRODUCING MECHANICAL POWER OR A REACTIVE PROPULSIVE THRUST, NOT OTHERWISE PROVIDED FOR
- **F03C POSITIVE-DISPLACEMENT ENGINES DRIVEN BY LIQUIDS** (positive- displacement engines for liquids and elastic fluids <u>F01</u>; positive- displacement machines for liquids <u>F04</u>; fluid-pressure actuators <u>F15B</u>; fluid gearing <u>F16H</u>)

NOTE

Attention is drawn to the notes preceding class <u>F01</u>, especially as regards the meanings of "positive displacement", "rotary-piston machines", "oscillating-piston machines", "rotary-piston", "co-operating members", "movement of co-operating members", "teeth or tooth-equivalents", and "internal axis".

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

F03C 1/253	covered by	<u>F03C 1/06</u>
F03C 1/28	covered by	F03C 1/0406, F03C 1/0605
F03C 1/30	covered by	F03C 1/0409, F03C 1/0631, F03C 1/0668
F03C 1/32	covered by	F03C 1/0415, F03C 1/0626, F03C 1/0652
F03C 1/34	covered by	F03C 1/0435, F03C 1/0615, F03C 1/0655
F03C 1/36	covered by	F03C 1/0435, F03C 1/0615, F03C 1/0655
F03C 1/38	covered by	F03C 1/0435, F03C 1/0615, F03C 1/0655
F03C 1/40	covered by	F03C 1/0447, F03C 1/0678

2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Reciprocating-piston liquid engines	1/035	• • • { one single-acting piston being always under
1/001	• {the movement in two directions being obtained by		the influence of the liquid under pressure}
	two or more double-acting piston liquid motors}	1/04	with cylinders in star or fan arrangement
1/002	• {details; components parts}		$\{(\underline{\text{F03C }1/22} \text{ takes precedence})\}$
1/003	• {controlling}	1/0403	• • • {Details, component parts specially adapted of
1/004	• • {speed-control}		such engines}
1/005	• • {motor piston stroke control}	1/0406	• • • • {Pistons}
1/007	 with single cylinder, double-acting piston 	1/0409	{Cams}
1/0073	• • {one side of the double-acting piston being always under the influence of the liquid under	1/0412	• • • • {consisting of several cylindrical elements, e.g. rollers}
	pressure}	1/0415	{Cylinders}
1/0076	{the liquid under pressure being continuously	1/0419	{Arrangements for pressing or connecting
	delivered to one cylinder chamber through		the pistons against the actuated cam}
	a valve in the piston for actuating the return	1/0422	• • • • {hydraulically}
	stroke}	1/0425	• • • {Disconnecting the pistons from the actuated
1/013	 with single cylinder, single-acting piston 		cam (in general <u>F01B 31/24</u>)}
1/0135	• • {with actuation of the return stroke by gravity}	1/0428	• • • • {Supporting and guiding means for the
1/02	. with multiple-cylinders, characterised by the		pistons}
	number or arrangement of cylinders (with movable cylinders <u>F03C 1/22</u> ; of flexible-wall type	1/0431	• • • • {Draining of the engine housing; arrangements dealing with leakage fluid}
	<u>F03C 7/00</u>)	1/0435	• • • • {Particularities relating to the distribution
1/03	with movement in two directions being obtained		members (F03C 1/0472, F03C 1/0531, and
	by two single-acting piston liquid engines, each		<u>F03C 1/0538</u> take precedence)}
	acting in one direction	1/0438	• • • • {to cylindrical distribution members}
		1/0441	• • • • {to conical distribution members}

CPC - 2025.08

1/0444	• • • • {to plate-like distribution members}	1/0657 {Cylindrical valve means}
1/0447	{Controlling}	1/066 {Conical valve means}
1/045	• • • • {by using a valve in a system with several	1/0663 {Casings, housings}
	pump or motor chambers, wherein the flow	1/0665 {Cylinder barrel bearing means}
	path through the chambers can be changed,	1/0668 {Swash or actuated plate}
1/0454	e.g. series-parallel} {by changing the effective cross sectional	1/0671 {Swash or actuated plate bearing means or driven axis bearing means}
	piston working surface}	1/0673 {Connection between rotating cylinder and
1/0457	• • • {by changing the effective piston stroke}	rotating inclined swash plate}
1/046	• • • • {by changing the excentricity of one element relative to another element}	1/0676 {Arrangement for pressing the cylinder barrel against the valve plate}
1/0463	• • • {by changing the phase relationship between	1/0678 {Control}
	two actuated cams}	1/0681 {using a valve in a system with several motor
1/0466	• • • • {by changing the phase relationship between the actuated cam and the distributing means}	chambers, wherein the flow path through the chambers can be changed}
1/047	• • • the pistons co-operating with an actuated	1/0684 { using a by-pass valve}
	element at the outer ends of the cylinders	1/0686 {by changing the inclination of the swash
1/0472	• • • { with cam-actuated distribution members }	plate}
1/0474	• • • { with two or more radial piston/cylinder	1/0689 {using wedges}
	units in series}	1/0692 {by changing the phase relationship between
1/0476	• • • • { directly located side by side }	the actuated element and the distribution
1/0478	• • • • {having several cylinder barrels coupled together}	means, e.g. turning the valve plate; turning the swash plate}
1/053	the pistons co-operating with an actuated	1/0694 {by changing the inclination of the axis of
	element at the inner ends of the cylinders	the cylinder barrel in relation to the axis of
1/0531	• • • { with cam-actuated distribution members }	the actuated element}
1/0533	• • • • { each piston being provided with channels	1/0697 {responsive to the speed}
	coacting with the cylinder and being used	1/08 • Distributing valve-gear peculiar thereto (for engines
	as a distribution member for another	with positive-displacement in general <u>F01L</u> ;
	cylinder}	$\{\underline{\text{F03C }1/06}\text{ takes precedence}\}\)$
1/0535	• • • { with two or more radial piston/cylinder	1/10 actuated by piston or piston-rod
	units in series}	1/12 mechanically
1/0536	• • • • { directly located side by side }	1/14 by driving liquid of engine
1/0538	• • • { the piston-driven cams being provided with	1/16 Speed controlling, equalising or cushioning
	inlets or outlets}	1/20 specially adapted for engines generating vibration
1/06	with cylinder axes generally coaxial with, or	only
	parallel or inclined to, main shaft axis	1/22 • with movable cylinders {or cylinder}
1/0602	{Component parts, details}	1/223 {having cylinders in star or fan arrangement,
1/0605	• • • • {Adaptations of pistons (pump pistons <u>F04B 1/124</u> , <u>F04B 53/14</u>)}	the connection of the pistons with an actuated element being at the inner ends of the cylinders}
1/0607	• • • {Driven means}	1/226 • • • { with cam actuated distribution members }
1/061	• • • {having stationary cylinders}	1/24 in which the liquid exclusively displaces one or
1/0613	{having two or more sets of cylinders or	more pistons reciprocating in rotary cylinders
	pistons}	$\{(\underline{\text{F03C }1/0636} \text{ takes precedence})\}$
1/0615	{distributing members}	1/2407 {having cylinders in star or fan arrangement,
1/0618	• • • • {cylindrical distribution members}	the connection of the pistons with an actuated
1/0621	• • • • {conical distribution members}	element being at the outer ends of the
1/0623	• • • {Details, component parts}	cylinders}
1/0626	{Cylinders}	1/2415 (cylinder block and actuated cam both
1/0628	{Casings, housings}	rotating (<u>F03C 1/2431</u> and <u>F03C 1/2446</u> take
1/0631	• • • {Wobbler or actuated element}	precedence)}
1/0634	{Actuated element bearing means or	1/2423 • • • { with two or more series radial piston-
1/0054	driven axis bearing means}	cylinder units}
1/0636	• • {having rotary cylinder block}	1/2431 {cylinder block and actuated cam both
1/0639	• • • {having rotary eyminder brock} • • • {having two or more sets of cylinders or	rotating (<u>F03C 1/2446</u> takes precedence)}
1/0037	pistons}	1/2438 {directly located side by side}
1/0642	• • • • {inclined on main shaft axis}	1/2446 {cylinder block and actuated cam both
1/0642	{Component parts}	rotating}
		1/2454 {having cylinders in star or fan arrangement,
1/0647	• • • • {Particularities in the contacting area between cylinder barrel and valve plate}	the connection of the pistons with an actuated
1/06/10		element being at the inner ends of the
1/0649	{Bearing means}	cylinders}
1/0652	{Cylinders}	1/2462 {the rotary cylinder being provided with only
1/0655	· · · · {Valve means}	one piston reciprocating within this cylinder}

CPC - 2025.08

1/247	 with cylinders in star- or fan-arrangement {, the connection of the pistons with an actuated element being at the outer ends of the cylinders}
1/26	adapted for special use or combined with apparatus driven thereby
2/00	Rotary-piston engines (in which the liquid exclusively displaces one or more piston reciprocating in rotary cylinders <u>F03C 1/24</u>)
	NOTE
	Group <u>F03C 2/30</u> takes precedence over groups <u>F03C 2/02</u> - <u>F03C 2/24</u> .
2/02	 of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents
2/08	 of intermeshing-engagement type, i.e. with engagement of co- operating members similar to that of toothed gearing
2/22	 of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth- equivalents than the outer member
2/24	 of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions
2/30	 having the characteristics covered by two or more of groups F03C 2/02, F03C 2/08, F03C 2/22, F03C 2/24 or having the characteristics covered by one of these groups together with some other type of movement between co-operating members
2/302	• • {having both the movements defined in sub- groups <u>F03C 2/02</u> and relative reciprocation between members}
2/304	• • {having both the movements defined in sub- group <u>F03C 2/08</u> or <u>F03C 2/22</u> and relative reciprocation between members}
2/306	• • {having both the movements defined in subgroups F03C 2/22 and F03C 2/24}
2/308	• • {having the movement defined in <u>F03C 2/08</u> and having a hinged member}
4/00	Oscillating-piston engines
7/00	Engines of flexible-wall type
99/00	Subject matter not provided for in other groups of this subclass
99/005	• {Free-piston type engines}

CPC - 2025.08