CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F17 STORING OR DISTRIBUTING GASES OR LIQUIDS

F17B GAS-HOLDERS OF VARIABLE CAPACITY (self-acting gas cut-off devices <u>A47J 27/62</u>, <u>G05D</u>; flame traps <u>A62C 4/00</u>; gas mixers <u>B01F</u>, <u>F16K 11/00</u>, <u>G05D 11/00</u>; construction or assembling of bulk storage containers employing civil-engineering techniques <u>E04H 7/00</u>, gas compressors <u>F04</u>; valves <u>F16K</u>; damping pulsations in valves or pipes <u>F16K</u>, <u>F16L</u>; pipes <u>F16L</u>; stopping devices for gas mains <u>F16L 55/10</u>; vessels adapted for storing compressed, liquefied, or solidified gases <u>F17C</u>; gas distribution systems <u>F17D 1/04</u>; detecting leakage <u>F17D 5/02</u>, <u>G01M</u>; supervising or alarm devices <u>F17D 5/02</u>, <u>G08B</u>; control of combustion in burners <u>F23N</u>; gas flow or pressure regulators <u>G05D</u>)

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Gas-holders of variable capacity (large containers
	in general <u>B65D 88/00;</u> storing fluids in natural or
	artificial cavities or chambers in the earth B65G 5/00)
1/007	 with telescopically movable ring-shaped parts
	(F17B 1/10 takes precedence; sealing of rings
	<u>F17B 1/04</u>)
1/013	• with movables discs (<u>F17B 1/10</u> takes precedence;
	sealing of discs F17B 1/04)
1/02	• Details
1/04	• • Sealing devices for sliding parts (in general
	<u>F16J 15/00</u>)
1/06	• • • using sealing liquids
1/08	• • • using resilient materials for packing, e.g.
	leather
1/10	Guiding moving parts
1/12	Gas admission or discharge arrangements
1/14	Safety devices, e.g. prevention of excess pressure
1/16	• of wet type
1/18	• • bell-shaped
1/20	• • telescopic
1/22	spirally-guided
1/24	• of dry type
1/26	• with flexible walls, e.g. bellows (connection of
	valves to inflatable elastic bodies B60C 29/00)