

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

LIGHTING; HEATING

F24 HEATING; RANGES; VENTILATING (NOTE omitted)

F24F AIR-CONDITIONING; AIR-HUMIDIFICATION; VENTILATION; USE OF AIR CURRENTS FOR SCREENING (removing dirt or fumes from areas where they are produced [B08B 15/00](#); vertical ducts for carrying away waste gases from buildings [E04F 17/02](#); tops for chimneys or ventilating shafts, terminals for flues [F23L 17/02](#))

NOTES

1. This subclass covers treatment, e.g. purification, of air supplied to human living or working spaces in air conditioning systems or in room units.
2. In this subclass:
 - air-humidification as auxiliary treatment in air-conditioning, i.e. in units wherein the air is also either cooled or heated, is covered by groups [F24F 1/00](#) or [F24F 3/14](#);
 - air-humidification per se, e.g. "room humidifiers", is covered by group [F24F 6/00](#).
3. In this subclass, the following terms or expressions are used with the meanings indicated:
 - "air-conditioning" means the supply of air to or the treatment of air in rooms or spaces by means of cooling or a combination of cooling and a further kind of air treatment, e.g. humidification, heating or air purification;
 - "ventilation" means the supply of air to, or its extraction from, rooms or spaces, and systems for circulating air within rooms or spaces, but does not cover the mere treatment of air being supplied to, extracted from, or circulated within, rooms or spaces.
4. In this subclass, control or safety arrangements are classified in group [F24F 11/00](#). In order to indicate the type of air-treatment system in which these arrangements are used, further classification may be made in groups [F24F 1/00](#) - [F24F 9/00](#).

1/00	Room units for air-conditioning, e.g. separate or self-contained units or units receiving primary air from a central station	1/0047	. . . mounted in the ceiling or at the ceiling
		1/005	. . . mounted on the floor; standing on the floor
1/0003	. characterised by a split arrangement, wherein parts of the air-conditioning system, e.g. evaporator and condenser, are in separately located units	1/0053	. . . mounted at least partially below the floor; with air distribution below the floor
1/0007	. Indoor units, e.g. fan coil units (self-contained units F24F 1/02)	1/0057	. . . mounted in or on a wall
1/00073	. . {comprising a compressor in the indoor unit housing}	1/0059	. . characterised by heat exchangers
1/00075	. . {receiving air from a central station}	1/0063	. . . by the mounting or arrangement of the heat exchangers
1/00077	. . {receiving heat exchange fluid entering and leaving the unit as a liquid}	1/0067	. . . by the shape of the heat exchangers or of parts thereof, e.g. of their fins
1/0011	. . characterised by air outlets	1/0068	. . characterised by the arrangement of refrigerant piping outside the heat exchanger within the unit casing
1/0014	. . . having two or more outlet openings	1/0071	. . with means for purifying supplied air (perfuming or deodorising means F24F 1/008)
1/0018	. . characterised by fans (with secondary air induced by injector action of the primary air F24F 1/01)	1/0073	. . . characterised by the mounting or arrangement of filters
1/0022	. . . Centrifugal or radial fans	1/0076	. . . by electric means, e.g. ionisers or electrostatic separators
1/0025	. . . Cross-flow or tangential fans	1/008	. . with perfuming or deodorising means
1/0029	. . . Axial fans	1/0083	. . with dehumidification means
1/0033	. . . having two or more fans	1/0087	. . with humidification means
1/0035	. . characterised by introduction of outside air to the room	1/009	. . characterised by heating arrangements (characterised by heat exchangers F24F 1/0059)
1/0038	. . . in combination with simultaneous exhaustion of inside air	1/0093	. . . with additional radiant heat-discharging elements, e.g. electric heaters
1/0041	. . characterised by exhaustion of inside air from the room (in combination with simultaneous introduction of outside air F24F 1/0038)	1/0097	. . . using thermoelectric or thermomagnetic means, e.g. Peltier elements
1/0043	. . characterised by mounting arrangements		

- | | | | |
|--------|---|-------------|--|
| 1/01 | • in which secondary air is induced by injector action of the primary air | 1/20 | • • Electric components for separate outdoor units |
| 1/02 | • Self-contained room units for air-conditioning, i.e. with all apparatus for treatment installed in a common casing | 1/22 | • • • Arrangement or mounting thereof |
| 1/022 | • • comprising a compressor cycle | 1/24 | • • • Cooling of electric components |
| 1/027 | • • • mounted in wall openings, e.g. in windows | 1/26 | • • Refrigerant piping |
| 1/028 | • • characterised by air supply means, e.g. fan casings, internal dampers or ducts (with secondary air induced by injector action of the primary air F24F 1/01) | 1/28 | • • • for connecting several separate outdoor units |
| 1/0284 | • • • with horizontally arranged fan axis | 1/30 | • • • for use inside the separate outdoor units |
| 1/0287 | • • • with vertically arranged fan axis | 1/32 | • • • for connecting the separate outdoor units to indoor units |
| 1/029 | • • characterised by the layout or mutual arrangement of components, e.g. of compressors or fans | 1/34 | • • • Protection means thereof, e.g. covers for refrigerant pipes |
| 1/03 | • • characterised by mounting arrangements | 1/36 | • • Drip trays for outdoor units |
| 1/031 | • • • penetrating a wall or window | 1/38 | • • Fan details of outdoor units, e.g. bell-mouth shaped inlets or fan mountings |
| 1/0314 | • • • mounted on a wall | 1/40 | • • Vibration or noise prevention at outdoor units (for outdoor units compressors F24F 1/12) |
| 1/0317 | • • • suspended from the ceiling | 1/42 | • • characterised by the use of the condensate, e.g. for enhanced cooling |
| 1/032 | • • characterised by heat exchangers | 1/44 | • • characterised by the use of internal combustion engines |
| 1/0323 | • • • by the mounting or arrangement of the heat exchangers | 1/46 | • • Component arrangements in separate outdoor units |
| 1/0325 | • • • by the shape of the heat exchangers or of parts thereof, e.g. of their fins | 1/48 | • • • characterised by air airflow, e.g. inlet or outlet airflow |
| 1/0326 | • • characterised by the arrangement of refrigerant piping outside the heat exchanger within the unit casing | 1/50 | • • • • with outlet air in upward direction |
| 1/0328 | • • with means for purifying supplied air (perfuming or deodorising means F24F 1/0355) | 1/52 | • • • • with inlet and outlet arranged on the same side, e.g. for mounting in a wall opening |
| 1/035 | • • • characterised by the mounting or arrangement of filters | 1/54 | • • • • Inlet and outlet arranged on opposite sides |
| 1/0353 | • • • by electric means, e.g. ionisers or electrostatic separators | 1/56 | • • Casing or covers of separate outdoor units, e.g. fan guards |
| 1/0355 | • • with perfuming or deodorising means | 1/58 | • • • Separate protective covers for outdoor units, e.g. solar guards, snow shields or camouflage |
| 1/0358 | • • with dehumidification means | 1/60 | • • Arrangement or mounting of the outdoor unit |
| 1/037 | • • with humidification means | 1/62 | • • • Wall-mounted |
| 1/0373 | • • characterised by heating arrangements (characterised by heat exchangers F24F 1/032) | 1/64 | • • • Ceiling-mounted, e.g. below a balcony |
| 1/0375 | • • • with additional radiant heat-discharging elements, e.g. electric heaters | 1/66 | • • • under the floor level |
| 1/0378 | • • • using thermoelectric or thermomagnetic means, e.g. Peltier elements | 1/68 | • • • Arrangement of multiple separate outdoor units |
| 1/039 | • • using water to enhance cooling, e.g. spraying onto condensers | 3/00 | Air-conditioning systems in which conditioned primary air is supplied from one or more central stations to distributing units in the rooms or spaces where it may receive secondary treatment; Apparatus specially designed for such systems (room units F24F 1/00) |
| 1/04 | • • Arrangements for portability | 3/001 | • {in which the air treatment in the central station takes place by means of a heat-pump or by means of a reversible cycle (reversible cycle for humidifying and drying air F24F 3/147)} |
| 1/06 | • Separate outdoor units, e.g. outdoor unit to be linked to a separate room comprising a compressor and a heat exchanger | 2003/003 | • {with primary air treatment in the central station and subsequent secondary air treatment in air treatment units located in or near the rooms} |
| | NOTE | 2003/005 | • • {with a single air duct for transporting treated primary air from the central station to air treatment units located in or near the rooms} |
| | In this group, the first place priority rule is applied, i.e. at each hierarchical level, in the absence of an indication to the contrary, classification is made in the first appropriate place. | 2003/006 | • • {with two air ducts for separately transporting treated hot and cold primary air from the central station to air treatment units located in or near the rooms} |
| 1/08 | • • Compressors specially adapted for separate outdoor units | 2003/008 | • {Supplying highly filtered air to a room or to a limited area within a room} |
| 1/10 | • • • Arrangement or mounting thereof | 3/02 | • characterised by the pressure or velocity of the primary air |
| 1/12 | • • • Vibration or noise prevention thereof | 3/04 | • • operating with high pressure or high velocity |
| 1/14 | • • Heat exchangers specially adapted for separate outdoor units | 3/044 | • Systems in which all treatment is given in the central station, i.e. all-air systems |
| 1/16 | • • • Arrangement or mounting thereof | | |
| 1/18 | • • • characterised by their shape | | |

- 3/0442 . . {with volume control at a constant temperature}
- 3/0444 . . . {in which two airstreams are conducted from the central station via independent conduits to the space to be treated, of which one has a constant volume and a season-adapted temperature, while the other one is always cold and varies in volume}
- 2003/0446 . . {with a single air duct for transporting treated air from the central station to the rooms}
- 2003/0448 . . {with two air ducts for separately transporting treated hot and cold air from the central station to the rooms}
- 3/048 . . with temperature control at constant rate of air-flow
- 3/052 . . . Multiple duct systems, e.g. systems in which hot and cold air are supplied by separate circuits from the central station to mixing chambers in the spaces to be conditioned
- 3/0522 {in which warm or cold air from the central station is delivered via individual pipes to mixing chambers in the space to be treated, the cold air/warm air ratio being controlled by a thermostat in the space concerned, i.e. so-called Dual-duct System}
- 3/0525 {in which the air treated in the central station is reheated}
- 3/0527 {in which treated air having differing temperatures is conducted through independent conduits from the central station to various spaces to be treated, i.e. so-called "multi-Zone" systems (F24F 3/0525 takes precedence)}
- 3/056 . . the air at least partially flowing over lighting fixtures, the heat of which is dissipated or used (outlets for directing or distributing air into rooms or spaces combined with lighting fixtures F24F 13/078)
- 3/06 . . characterised by the arrangements for the supply of heat-exchange fluid for the subsequent treatment of primary air in the room units
- 3/065 . . {with a plurality of evaporators or condensers}
- 3/08 . . with separate supply and return lines for hot and cold heat-exchange fluids {i.e. so-called "4-conduit" system}
- 3/10 . . with separate supply lines and common return line for hot and cold heat-exchange fluids {i.e. so-called "3-conduit" system}
- 3/12 . . characterised by the treatment of the air otherwise than by heating and cooling
- 3/14 . . by humidification; by dehumidification
- 3/1405 . . . {in which the humidity of the air is exclusively affected by contact with the evaporator of a closed-circuit cooling system or heat pump circuit}
- 3/1411 . . . {by absorbing or adsorbing water, e.g. using an hygroscopic desiccant}
- 3/1417 {with liquid hygroscopic desiccants}
- 3/1423 {with a moving bed of solid desiccants, e.g. a rotary wheel supporting solid desiccants}
- 3/1429 {alternatively operating a heat exchanger in an absorbing/adsorbing mode and a heat exchanger in a regeneration mode}
- 2003/1435 . . . {comprising semi-permeable membrane}
- 2003/144 . . . {by dehumidification only}
- 2003/1446 {by condensing}
- 2003/1452 {heat extracted from the humid air for condensing is returned to the dried air}
- 2003/1458 . . . {using regenerators}
- 2003/1464 {using rotating regenerators}
- 3/147 . . . with both heat and humidity transfer between supplied and exhausted air
- 3/153 . . . with subsequent heating, i.e. with the air, given the required humidity in the central station, passing a heating element to achieve the required temperature
- 3/16 . . by purification, e.g. by filtering; by sterilisation; by ozonisation
- 3/163 . . . Clean air work stations, i.e. selected areas within a space which filtered air is passed
- 3/167 . . . Clean rooms, i.e. enclosed spaces in which a uniform flow of filtered air is distributed (air distribution by perforated walls F24F 7/10)
- 5/00 Air-conditioning systems or apparatus not covered by F24F 1/00 or F24F 3/00 {, e.g. using solar heat or combined with household units such as an oven or water heater}**
- 5/0003 . {Exclusively-fluid systems}
- 5/0007 . {cooling apparatus specially adapted for use in air-conditioning (F24F 5/0046 takes precedence)}
- 5/001 . . {Compression cycle type}
- 5/0014 . . {using absorption or desorption}
- 5/0017 . . {using cold storage bodies, e.g. ice}
- 5/0021 . . . {using phase change material [PCM] for storage}
- 2005/0025 . . . {using heat exchange fluid storage tanks}
- 2005/0028 . . . {using hydridable metals as energy storage media}
- 2005/0032 . . . {Systems storing energy during the night}
- 5/0035 . . {using evaporation}
- 2005/0039 . . {using a cryogen, e.g. CO₂ liquid or N₂ liquid}
- 5/0042 . {characterised by the application of thermo-electric units or the Peltier effect}
- 5/0046 . {using natural energy, e.g. solar energy, energy from the ground}
- 5/005 . . {using energy from the ground by air circulation, e.g. "Canadian well"}
- 2005/0053 . . {receiving heat-exchange fluid from a well}
- 2005/0057 . . {receiving heat-exchange fluid from a closed circuit in the ground}
- 2005/006 . . {receiving heat-exchange fluid from the drinking or sanitary water supply circuit}
- 2005/0064 . . {using solar energy}
- 2005/0067 . . . {with photovoltaic panels}
- 5/0071 . {adapted for use in covered swimming pools}
- 5/0075 . {Systems using thermal walls, e.g. double window}
- 2005/0078 . . {Double windows}
- 2005/0082 . . {Facades}
- 5/0085 . {Systems using a compressed air circuit}
- 5/0089 . {Systems using radiation from walls or panels}
- 5/0092 . . {ceilings, e.g. cool ceilings}
- 5/0096 . {combined with domestic apparatus}
- 6/00 Air-humidification {, e.g. cooling by humidification}**
- 2006/001 . {using a water curtain}
- 2006/003 . {using a decorative fountain}
- 2006/005 . {using plants}
- 2006/006 . {with water treatment}

- 2006/008 . {Air-humidifier with water reservoir}
- 6/02 . by evaporation of water in the air
- 6/025 . . {using electrical heating means ([F24F 6/105 takes precedence](#))}
- 6/04 . . using stationary unheated wet elements
- 6/043 . . . {with self-sucking action, e.g. wicks}
- 2006/046 . . . {with a water pump}
- 6/06 . . using moving unheated wet elements
- 2006/065 . . . {using slowly rotating discs for evaporation}
- 6/08 . . using heated wet elements
- 6/10 . . . heated electrically
- 6/105 {using the heat of lamps}
- 6/12 . by forming water dispersions in the air
- 6/14 . . using nozzles
- 2006/143 . . . {using pressurised air for spraying}
- 2006/146 . . . {using pressurised water for spraying}
- 6/16 . . using rotating elements
- 6/18 . by injection of steam into the air
- 7/00 Ventilation**
- 2007/001 . {with exhausting air ducts}
- 2007/002 . . {Junction box, e.g. for ducts from kitchen, toilet or bathroom}
- 2007/0025 . {using vent ports in a wall}
- 7/003 . in combination with air cleaning
- 2007/004 . {Natural ventilation using convection}
- 2007/005 . {Cyclic ventilation, e.g. alternating air supply volume or reversing flow direction}
- 7/007 . with forced flow ([using ducting systems F24F 7/06](#))
- 7/013 . . using wall or window fans, displacing air through the wall or window
- 7/02 . Roof ventilation ([ventilation of roof coverings E04D](#))
- 7/025 . . {with forced air circulation by means of a built-in ventilator}
- 7/04 . with ducting systems {, e.g. by double walls; with natural circulation ([F24F 7/02 takes precedence](#))}
- 7/06 . . with forced air circulation, e.g. by fan {positioning of a ventilator in or against a conduit}
- 7/065 . . . {fan combined with single duct; mounting arrangements of a fan in a duct}
- 7/08 . . . with separate ducts for supplied and exhausted air {with provisions for reversal of the input and output systems}
- 7/10 . . . with air supply, or exhaust, through perforated wall, floor or ceiling ([outlet members for directing or distributing air {into rooms or spaces, e.g. ceiling air-diffusers} F24F 13/06](#))
- 8/00 Treatment, e.g. purification, of air supplied to human living or working spaces otherwise than by heating, cooling, humidifying or drying**
- 8/10 . by separation, e.g. by filtering
- 8/108 . . using dry filter elements
- 8/117 . . using wet filtering
- 8/125 . . . using wet filter elements
- 8/133 . . . by direct contact with liquid, e.g. with sprayed liquid
- 8/142 . . . Treatment of used liquid, e.g. cleaning for recycling
- 8/15 . . by chemical means
- 8/158 . . . using active carbon
- 8/167 . . . using catalytic reactions
- 8/175 . . using biological materials, plants or microorganisms
- 8/183 . . by centrifugal separation, e.g. using vortices
- 8/192 . . by electrical means, e.g. by applying electrostatic fields or high voltages
- 8/194 . . . {by filtering using high voltage}
- 8/20 . by sterilisation
- 8/22 . . using UV light
- 8/24 . . using sterilising media
- 8/26 . . . using ozone
- 8/28 . . specially adapted for combatting or avoiding Legionella bacteria
- 8/30 . by ionisation
- 8/40 . by ozonisation ([for sterilisation F24F 8/26](#))
- 8/50 . by odourisation
- 8/60 . by adding oxygen
- 8/70 . by removing radon
- 8/80 . Self-contained air purifiers
- 8/90 . Cleaning of purification apparatus
- 8/95 . specially adapted for specific purposes
- 8/96 . . for removing pollen
- 8/97 . . for removing tobacco smoke
- 8/98 . . for removing ozone
- 8/99 . . for treating air sourced from urban areas, e.g. from streets
- 9/00 Use of air currents for screening, e.g. air curtains**
- 2009/002 . {Room dividers}
- 2009/005 . {combined with a door}
- 2009/007 . {using more than one jet or band in the air curtain}
- 11/00 Control or safety arrangements**
- NOTE**
- In this group, it is desirable to add the indexing codes of groups [F24F 2110/00](#) – [F24F 2140/00](#).
- 11/0001 . {for ventilation ([F24F 11/30 takes precedence](#))}
- 2011/0002 . . {for admittance of outside air}
- 2011/0004 . . . {to create overpressure in a room}
- 2011/0005 . . . {to create underpressure in a room, keeping contamination inside}
- 2011/0006 . . {using low temperature external supply air to assist cooling}
- 11/0008 . {for air-humidification ([F24F 11/30 takes precedence](#))}
- 11/30 . for purposes related to the operation of the system, e.g. for safety or monitoring
- 11/32 . . Responding to malfunctions or emergencies
- 11/33 . . . to fire, excessive heat or smoke
- 11/34 by opening air passages
- 11/35 by closing air passages
- 11/36 . . . to leakage of heat-exchange fluid
- 11/37 . . . Resuming operation, e.g. after power outages; Emergency starting
- 11/38 . . . Failure diagnosis
- 11/39 . . . Monitoring filter performance
- 11/41 . . Defrosting; Preventing freezing
- 11/42 . . . of outdoor units
- 11/43 . . . of indoor units
- 11/46 . . Improving electric energy efficiency or saving
- 11/47 . . . Responding to energy costs
- 11/48 . . prior to normal operation, e.g. pre-heating or pre-cooling

- 11/49 . . ensuring correct operation, e.g. by trial operation or configuration checks
- 11/50 . characterised by user interfaces or communication
- 11/52 . . Indication arrangements, e.g. displays
- 11/523 . . . for displaying temperature data
- 11/526 . . . giving audible indications
- 11/54 . . using one central controller connected to several sub-controllers
- 11/56 . . Remote control
- 11/57 . . . using telephone networks
- 11/58 . . . using Internet communication
- 11/59 . . . for presetting
- 11/61 . . using timers
- 11/62 . characterised by the type of control or by internal processing, e.g. using fuzzy logic, adaptive control or estimation of values
- 11/63 . . Electronic processing
- 11/64 . . . using pre-stored data
- 11/65 . . . for selecting an operating mode
- 11/66 Sleep mode
- 11/67 Switching between heating and cooling modes
- 11/70 . Control systems characterised by their outputs; Constructional details thereof
- 11/72 . . for controlling the supply of treated air, e.g. its pressure
- 11/74 . . . for controlling air flow rate or air velocity
- 11/745 {the air flow rate increasing with an increase of air-current or wind pressure}
- 11/75 for maintaining constant air flow rate or air velocity
- 11/755 for cyclical variation of air flow rate or air velocity
- 11/76 by means responsive to temperature, e.g. bimetal springs
- 11/77 by controlling the speed of ventilators
- 11/79 . . . for controlling the direction of the supplied air
- 11/80 . . for controlling the temperature of the supplied air
- 11/81 . . . by controlling the air supply to heat-exchangers or bypass channels
- 11/83 . . . by controlling the supply of heat-exchange fluids to heat-exchangers
- 11/84 using valves
- 11/85 using variable-flow pumps
- 11/86 . . . by controlling compressors within refrigeration or heat pump circuits
- 11/87 . . . by controlling absorption or discharge of heat in outdoor units
- 11/871 by controlling outdoor fans
- 11/873 . . . by controlling refrigerant heaters
- 11/875 . . . by controlling heat-storage apparatus
- 11/88 . Electrical aspects, e.g. circuits
- 11/89 . Arrangement or mounting of control or safety devices
- 12/00 Use of energy recovery systems in air conditioning, ventilation or screening (with both heat and humidity transfer between supplied and exhausted air F24F 3/147)**
- 12/001 . {with heat-exchange between supplied and exhausted air}
- 12/002 . . {using an intermediate heat-transfer fluid}
- 12/003 . . . {using a heat pump}
- 2012/005 . . . {using heat pipes}
- 12/006 . . {using an air-to-air heat exchanger (F24F 12/002 takes precedence)}
- 2012/007 . . {using a by-pass for bypassing the heat-exchanger}
- 2012/008 . . {cyclic routing supply and exhaust air}
- 13/00 Details common to, or for air-conditioning, air-humidification, ventilation or use of air currents for screening**
- 13/02 . Ducting arrangements
- 13/0209 . . {characterised by their connecting means, e.g. flanges}
- 13/0218 . . {Flexible soft ducts, e.g. ducts made of permeable textiles}
- 13/0227 . . {using parts of the building, e.g. air ducts inside the floor, walls or ceiling of a building}
- 13/0236 . . {with ducts including air distributors, e.g. air collecting boxes with at least three openings}
- 13/0245 . . {Manufacturing or assembly of air ducts; Methods therefor}
- 13/0254 . . {characterised by their mounting means, e.g. supports}
- 13/0263 . . {Insulation for air ducts}
- 13/0272 . . {Modules for easy installation or transport}
- 13/0281 . . {Multilayer duct}
- 13/029 . . {Duct comprising an opening for inspection, e.g. manhole}
- 13/04 . . Air-mixing units (F24F 13/06 takes precedence)
- 13/06 . . Outlets for directing or distributing air into rooms or spaces, e.g. ceiling air diffuser
- 13/0604 . . . {integrated in or forming part of furniture}
- 2013/0608 . . . {Perforated ducts}
- 2013/0612 . . . {Induction nozzles without swirl means}
- 2013/0616 . . . {Outlets that have intake openings}
- 13/062 . . . having one or more bowls or cones diverging in the flow direction
- 13/065 . . . formed as cylindrical or spherical bodies which are rotatable
- 13/068 . . . formed as perforated walls, ceilings or floors (F24F 13/078 takes precedence)
- 13/072 . . . of elongated shape, e.g. between ceiling panels
- 13/075 . . . having parallel rods or lamellae directing the outflow, e.g. the rods or lamellae being individually adjustable (F24F 13/072 takes precedence)
- 13/078 . . . combined with lighting fixtures
- 13/08 . Air-flow control members, e.g. louvres, grilles, flaps or guide plates (F24F 7/013, F24F 13/06 take precedence)
- 13/081 . . {for guiding air around a curve}
- 13/082 . . {Grilles, registers or guards}
- 13/084 . . . {with mounting arrangements, e.g. snap fasteners for mounting to the wall or duct}
- 13/085 . . . {including an air filter}
- 2013/087 . . . {using inflatable bellows}
- 2013/088 . . . {Air-flow straightener}
- 13/10 . . movable, e.g. dampers
- 13/105 . . . {composed of diaphragms or segments}
- 13/12 . . . built up of sliding members
- 13/14 . . . built up of tilting members, e.g. louvre
- 13/1406 {characterised by sealing means}

F24F

- 13/1413 {using more than one tilting member, e.g. with several pivoting blades (F24F 13/15 takes precedence)}
- 13/142 {using pivoting blades with intersecting axles}
- 13/1426 {characterised by actuating means}
- 2013/1433 {with electric motors}
- 2013/144 {with thermoactuators}
- 2013/1446 {with gearings}
- 2013/1453 {with cables, e.g. bowden cables}
- 2013/146 {with springs}
- 2013/1466 {with pneumatic means}
- 2013/1473 {with cams or levers}
- 2013/148 {with magnets}
- 13/1486 {characterised by bearings, pivots or hinges}
- 2013/1493 {using an elastic membrane}
- 13/15 with parallel simultaneously tiltable lamellae
- 13/16 built up of parallelly-movable plates
- 13/18 specially adapted for insertion in flat panels, e.g. in door or window-pane
- 13/20 Casings or covers
- 2013/202 {Mounting a compressor unit therein}
- 2013/205 {Mounting a ventilator fan therein}
- 2013/207 {with control knobs; Mounting controlling members or control units therein}
- 13/22 Means for preventing condensation or evacuating condensate
- 2013/221 {to avoid the formation of condensate, e.g. dew}
- 13/222 {for evacuating condensate}
- 13/224 {in a window-type room air conditioner}
- 2013/225 {by evaporating the condensate in the cooling medium, e.g. in air flow from the condenser}
- 2013/227 {Condensate pipe for drainage of condensate from the evaporator}
- 2013/228 {Treatment of condensate, e.g. sterilising}
- 13/24 Means for preventing or suppressing noise
- 2013/242 {Sound-absorbing material}
- 2013/245 {using resonance}
- 2013/247 {Active noise-suppression}
- 13/26 Arrangements for air-circulation by means of induction, e.g. by fluid coupling or thermal effect
- 13/28 Arrangement or mounting of filters
- 13/30 Arrangement or mounting of heat-exchangers
- 13/32 Supports for air-conditioning, air-humidification or ventilation units

Indexing scheme associated with group F24F 11/00, relating to control inputs, e.g. measured or estimated values or parameters

- 2110/00 Control inputs relating to air properties**
- 2110/10 Temperature
- 2110/12 of the outside air
- 2110/20 Humidity
- 2110/22 of the outside air
- 2110/30 Velocity
- 2110/32 of the outside air
- 2110/40 Pressure, e.g. wind pressure
- 2110/50 Air quality properties
- 2110/52 of the outside air
- 2110/60 Odour
- 2110/62 Tobacco smoke
- 2110/64 Airborne particle content

- 2110/65 Concentration of specific substances or contaminants
- 2110/66 Volatile organic compounds [VOC]
- 2110/68 Radon
- 2110/70 Carbon dioxide
- 2110/72 Carbon monoxide
- 2110/74 Ozone
- 2110/76 Oxygen
- 2110/80 Electric charge

2120/00 Control inputs relating to users or occupants

- 2120/10 Occupancy
- 2120/12 Position of occupants
- 2120/14 Activity of occupants
- 2120/20 Feedback from users

2130/00 Control inputs relating to environmental factors not covered by group F24F 2110/00

- 2130/10 Weather information or forecasts
- 2130/20 Sunlight
- 2130/30 Artificial light
- 2130/40 Noise

2140/00 Control inputs relating to system states

- 2140/10 Pressure
- 2140/12 Heat-exchange fluid pressure
- 2140/20 Heat-exchange fluid temperature
- 2140/30 Condensation of water from cooled air
- 2140/40 Damper positions, e.g. open or closed
- 2140/50 Load
- 2140/60 Energy consumption

2203/00 Devices or apparatus used for air treatment

- 2203/02 System or Device comprising a heat pump as a subsystem, e.g. combined with humidification/dehumidification, heating, natural energy or with hybrid system
- 2203/021 Compression cycle
- 2203/023 with turbine used for expansion
- 2203/025 with turbine for compression
- 2203/026 Absorption - desorption cycle
- 2203/028 using a solid absorbing medium
- 2203/10 Rotary wheel
- 2203/1004 Bearings or driving means
- 2203/1008 comprising a by-pass channel
- 2203/1012 Details of the casing or cover
- 2203/1016 combined with another type of cooling principle, e.g. compression cycle
- 2203/102 combined with a heat pipe
- 2203/1024 combined with a humidifier
- 2203/1028 combined with a spraying device
- 2203/1032 Desiccant wheel
- 2203/1036 Details
- 2203/104 Heat exchanger wheel
- 2203/1044 performing other movements, e.g. sliding
- 2203/1048 Geometric details
- 2203/1052 comprising a non-axial air flow
- 2203/1056 comprising a reheater
- 2203/106 Electrical reheater
- 2203/1064 Gas fired reheater
- 2203/1068 comprising one rotor
- 2203/1072 comprising two rotors

F24F

- 2203/1076 . . comprising three rotors
- 2203/108 . . comprising rotor parts shaped in sector form
- 2203/1084 . . comprising two flow rotor segments
- 2203/1088 . . comprising three flow rotor segments
- 2203/1092 . . comprising four flow rotor segments
- 2203/1096 . . comprising sealing means
- 2203/12 . Dehumidifying or humidifying belt type

Air-conditioning

2221/00 Details or features not otherwise provided for

- 2221/02 . combined with lighting fixtures
- 2221/08 . Installation or apparatus for use in sport halls, e.g. swimming pools, ice rings
- 2221/10 . combined with, or integrated in, furniture
- 2221/12 . transportable
- 2221/125 . . mounted on wheels
- 2221/14 . mounted on the ceiling
- 2221/16 . mounted on the roof
- 2221/17 . mounted in a wall
- 2221/18 . combined with domestic apparatus
- 2221/183 . . combined with a hot-water boiler
- 2221/186 . . combined with a fireplace
- 2221/20 . mounted in or close to a window
- 2221/22 . Cleaning ducts or apparatus
- 2221/225 . . using a liquid
- 2221/26 . improving the aesthetic appearance
- 2221/28 . using the Coanda effect
- 2221/30 . comprising fireproof material
- 2221/32 . preventing human errors during the installation, use or maintenance, e.g. goofy proof
- 2221/34 . Heater, e.g. gas burner, electric air heater
- 2221/36 . Modules, e.g. for an easy mounting or transport
- 2221/38 . Personalised air distribution
- 2221/40 . HVAC with raised floors
- 2221/42 . Mobile autonomous air conditioner, e.g. robots
- 2221/44 . Protection from terrorism or theft
- 2221/46 . Air flow forming a vortex
- 2221/48 . HVAC for a wine cellar
- 2221/50 . HVAC for high buildings, e.g. thermal or pressure differences
- 2221/52 . Weather protecting means, e.g. against wind, rain or snow
- 2221/54 . Heating and cooling, simultaneously or alternatively
- 2221/56 . Cooling being a secondary aspect