

CPC**COOPERATIVE PATENT CLASSIFICATION****F04D****NON-POSITIVE DISPLACEMENT PUMPS****NOTE**

This subclass covers non-positive-displacement pumps for liquids, for elastic fluids, or for liquids and elastic fluids whether rotary or not having pure rotation.

This subclass does not cover combinations of non-positive-displacement pumps with other pumps, which are covered by subclass [F04B](#), except that the use of such other pumps for priming or boosting non-positive-displacement is covered by this subclass.

Attention is drawn to the Notes preceding class [F01](#), especially as regards the definition of "pump".

Guidance heading: **Pumping liquids, or liquids and elastic fluids, by rotary pumps**([pumping liquids and elastic fluids at the same time F04D 31/00](#))

F04D 1/00

Radial-flow pumps, e.g. centrifugal pumps; Helico-centrifugal pumps([adapted for pumping specific fluids F04D 7/00](#) ; [priming or boosting F04D 9/00](#))

F04D 1/003

- . {Having contrarotating parts}

F04D 1/006

- . {double suction pumps}

F04D 1/02

- . having non-centrifugal stages, e.g. centripetal

F04D 1/025

- .. {Comprising axial and radial stages}

F04D 1/04

- . Helico-centrifugal pumps

F04D 1/06

- . Multi-stage pumps([F04D 1/02](#) , [F04D 13/10](#) take precedence)

F04D 1/063

- .. {of the vertically split casing type}

F04D 1/066

- ... {the casing consisting of a plurality of annuli bolted together}

F04D 1/08

- .. the stages being situated concentrically

F04D 1/10

- .. with means for changing the flow-path through the stages, e.g. series-parallel, e.g. side loads

F04D 1/12

- . Pumps with scoops or like paring members protruding in the fluid circulating in a bowl

F04D 1/14

- . Pumps raising fluids by centrifugal force within a conical rotary bowl with vertical axis

F04D 3/00

Axial-flow pumps([priming or boosting F04D 9/00](#))

F04D 3/005

- . {with a conventional single stage rotor}

F04D 3/02

- . of screw type

F04D 5/00

Pumps with circumferential or transverse flow{([control thereof F04D 15/005](#))}

F04D 5/001

- . {Shear force pumps}

F04D 5/002

- . {Regenerative pumps(for elastic fluids [F04D 23/008](#))}

F04D 5/003

- .. {of multistage type}

F04D 5/005

- ... {the stages being radially offset}

F04D 5/006	... {the stages being axially offset}
F04D 5/007	.. {Details of the inlet or outlet}
F04D 5/008	.. {Details of the stator, e.g. channel shape}
F04D 7/00	Pumps adapted for handling specific fluids, e.g. by selection of specific materials for pumps or pump parts(F04D 11/005 , F04D 29/22 take precedence)
F04D 7/02	. of centrifugal type
F04D 7/04	.. the fluids being viscous or non-homogenous
F04D 7/045	... {with means for comminuting, mixing stirring or otherwise treating}
F04D 7/06	.. the fluids being hot or corrosive, e.g. liquid metals
F04D 7/065	... {for liquid metal}
F04D 7/08	.. the fluids being radioactive
F04D 9/00	Priming; Preventing vapour lock
F04D 9/001	. {Preventing vapour lock(F04D 9/041 takes precedence)}
F04D 9/002	.. {by means in the very pump(F04D 9/041 takes precedence)}
F04D 9/003	... {separating and removing the vapour}
F04D 9/004	. {Priming of not self-priming pumps}
F04D 9/005	.. {by adducting or recycling liquid(F04D 9/006 takes precedence)}
F04D 9/006	.. {by venting gas or using gas valves}
F04D 9/007	. {Preventing loss of prime, siphon breakers(stopping of pumps F04D 15/02)}
F04D 9/008	.. {by means in the suction mouth, e.g. foot valves}
F04D 9/02	. Self-priming pumps
F04D 9/04	. Using priming pumps; Using booster pumps to prevent vapour-lock
F04D 9/041	.. {the priming pump having evacuating action(F04D 9/043 and F04D 9/06 take precedence)}
F04D 9/042	... {and means for rendering its in operative}
F04D 9/043	.. {the priming pump being hand operated or of the reciprocating type}
F04D 9/044	.. {Means for rendering the priming pump inoperative}
F04D 9/045	... {the means being liquid level sensors}
F04D 9/046 {the means being floats}
F04D 9/047	... {the means being flow sensors}
F04D 9/048	... {the means being outlet pressure sensors}
F04D 9/049	... {by operator interventions}
F04D 9/06	.. of jet type
F04D 9/065	... {the driving fluid being a gas or vapour, e.g. exhaust of a combustion engine}
F04D 11/00	Other rotary non-positive-displacement pumps(pumping installations or systems F04D 13/00)
F04D 11/005	. {Swash-type impeller pumps}
F04D 13/00	Pumping installations or systems(controlling F04D 15/00)

- F04D 13/02 . Units comprising pumps and their driving means([predominant aspects of the driving means, see the relevant classes for such means](#))
 - F04D 13/021 .. {containing a coupling}
 - F04D 13/022 ... {a coupling allowing slip, e.g. torque converter}
 - F04D 13/023 {for reducing start torque}
 - F04D 13/024 ... {a magnetic coupling}
 - F04D 13/025 {Details of the can separating the pump and drive area}
 - F04D 13/026 {Details of the bearings}
 - F04D 13/027 {Details of the magnetic circuit}
 - F04D 13/028 .. {the driving means being a planetary gear}
 - F04D 13/04 .. the pump being fluid driven
 - F04D 13/043 ... {the pump wheel carrying the fluid driving means}
 - F04D 13/046 ... {the fluid driving means being a hydraulic motor of the positive displacement type}
 - F04D 13/06 .. the pump being electrically driven
 - F04D 13/0606 ... {Canned motor pumps}
 - F04D 13/0613 {Special connection between the rotor compartments}
 - F04D 13/062 {pressure compensation between motor- and pump- compartment}
 - F04D 13/0626 {Details of the can}
 - F04D 13/0633 {Details of the bearings}
 - F04D 13/064 {Details of the magnetic circuit}
 - F04D 13/0646 ... {the hollow pump or motor shaft being the conduit for the working fluid}
 - F04D 13/0653 ... {the motor being flooded}
 - F04D 13/066 ... {Floating-units}
 - F04D 13/0666 ... {the motor being of the plane gap type}
 - F04D 13/0673 ... {the motor being of the inside-out type}
 - F04D 13/068 ... {Battery powered}
 - F04D 13/0686 ... {Mechanical details of the pump control unit([pump control F04D 15/00](#))}
 - F04D 13/0693 ... {Details or arrangements of the wiring}
 - F04D 13/08 ... for submerged use
 - F04D 13/083 {and protected by a gas-bell}
 - F04D 13/086 {the pump and drive motor are both submerged}
 - F04D 13/10 adapted for use in mining bore holes
 - F04D 13/12 . Combinations of two or more pumps([combinations with priming pumps or booster pumps to counteract vapour-lock F04D 9/04](#))
 - F04D 13/14 .. the pumps being all of centrifugal type{([deviation valves F04D 15/0016](#))}
 - F04D 13/16 . with storage reservoirs
- F04D 15/00 Control, e.g. regulation, of pumps, pumping installations or systems**
 - F04D 15/0005 . {by using valves}
 - F04D 15/0011 .. {by-pass valves}

- F04D 15/0016 . . {mixing-reversing- or deviation valves}
- F04D 15/0022 . . {throttling valves or valves varying the pump inlet opening or the outlet opening}
- F04D 15/0027 . {Varying behaviour or the very pump([F04D 15/0055](#) and [F04D 29/46](#) take precedence)}
- F04D 15/0033 . . {By-passing by increasing clearance between impeller and its casing}
- F04D 15/0038 . . {by varying the effective cross-sectional area of flow through the rotor}
- F04D 15/0044 . . {by introducing a gas}
- F04D 15/005 . . {the pumps being of the circumferential flow type}
- F04D 15/0055 . {Rotors with adjustable blades}
- F04D 15/0061 . . {responsive to temperature}
- F04D 15/0066 . {by changing the speed, e.g. of the driving engine}
- F04D 15/0072 . {Installation or systems with two or more pumps, wherein the flow path through the stages can be changed, e.g. series-parallel}
- F04D 15/0077 . {Safety measures([F04D 15/02](#) takes precedence)}
- F04D 15/0083 . . {Protection against sudden pressure change, e.g. check valves}
- F04D 15/0088 . {Testing machines}
- F04D 15/0094 . {Indicators of rotational movement}
- F04D 15/02 . Stopping of pumps, or operating valves, on occurrence of unwanted conditions
- F04D 15/0209 . . {responsive to a condition of the working fluid([F04D 15/029](#) takes precedence)}
- F04D 15/0218 . . . {the condition being a liquid level or a lack of liquid supply}
- F04D 15/0227 {Lack of liquid level being detected using a flow transducer}
- F04D 15/0236 {Lack of liquid level being detected by analysing the parameters of the electric drive, e.g. current or power consumption}
- F04D 15/0245 . . {responsive to a condition of the pump}
- F04D 15/0254 . . . {the condition being speed or load}
- F04D 15/0263 . . . {the condition being temperature, ingress of humidity or leakage}
- F04D 15/0272 . . . {the condition being wear or a position}
- F04D 15/0281 . . {responsive to a condition not otherwise provided for}
- F04D 15/029 . . {for pumps operating in parallel}

Guidance heading: Pumping elastic fluids by rotary pumps

- F04D 17/00** **Radial-flow pumps e.g. centrifugal pumps; Helico-centrifugal pumps([F04D 21/00](#) takes precedence)**
- F04D 17/02 . having non-centrifugal stages, e.g. centripetal
- F04D 17/025 . . {comprising axial flow and radial flow stages}
- F04D 17/04 . . of transverse-flow type
- F04D 17/06 . Helico-centrifugal pumps
- F04D 17/08 . Centrifugal pumps
- F04D 17/10 . . for compressing or evacuating
- F04D 17/105 . . . {with double suction}

- F04D 17/12 . . . Multi-stage pumps
- F04D 17/122 {the individual rotor discs being, one for each stage, on a common shaft and axially spaced, e.g. conventional centrifugal multi- stage compressors}
- F04D 17/125 {the casing being vertically split}
- F04D 17/127 {with radially spaced stages, e.g. for contrarotating type}
- F04D 17/14 with means for changing the flow-path through the stages, e.g. series-parallel, e.g. side-loads, ([surge control F04D 27/02](#))
- F04D 17/16 . . for displacing without appreciable compression
- F04D 17/161 . . . {Shear force pumps}
- F04D 17/162 . . . {Double suction pumps}
- F04D 17/164 . . . {Multi-stage fans, e.g. for vacuum cleaners}
- F04D 17/165 . . . {Axial entry and discharge}
- F04D 17/167 . . . {Operating by means of fibrous or porous elements([suction filters F04D 29/701](#)); e.g. with sponge rotors}
- F04D 17/168 . . . {Pumps specially adapted to produce a vacuum}
- F04D 17/18 . . characterised by use of centrifugal force of liquids entrained in pumps{ e.g. by means of an auxiliary liquid; fluid ring compressors [F04C 19/00](#) }

F04D 19/00 **Axial-flow pumps([F04D 21/00](#) takes precedence);{ pump comprising axial flow and radial flow stages [F04D 17/025](#) }**

- F04D 19/002 . {Axial flow fans}
- F04D 19/005 . . {reversible fans}
- F04D 19/007 . {multistage fans}
- F04D 19/02 . Multi-stage pumps
- F04D 19/022 . . {with concentric rows of vanes;}
- F04D 19/024 . . {with contrarotating parts}
- F04D 19/026 . . {with a plurality of shafts rotating at different speeds([F04D 19/022](#) takes precedence)}
- F04D 19/028 . . {Layout of fluid flow through the stages}
- F04D 19/04 . . specially adapted to the production of a high vacuum, e.g. molecular pumps
- F04D 19/042 . . . {Turbomolecular vacuum pumps}
- F04D 19/044 . . . {Holweck-type pumps}
- F04D 19/046 . . . {Combinations of two or more different types of pumps}
- F04D 19/048 . . . {comprising magnetic bearings}

F04D 21/00 **Pump involving supersonic speed of pumped fluids**

F04D 23/00 **Other rotary non-positive-displacement pumps([pumping installations or systems F04D 25/00](#))**

- F04D 23/001 . {Pumps adapted for conveying materials or for handling specific elastic fluids}
- F04D 23/003 . . {of radial-flow type}
- F04D 23/005 . . {of axial-flow type}
- F04D 23/006 . {Creating a pulsating flow}

F04D 23/008	. {Regenerative pumps(for liquids or for liquids and elastic fluids F04D 5/002)}
F04D 25/00	Pumping installations or systems(controlling F04D 27/00)
F04D 25/02	. Units comprising pumps and their driving means(predominant aspect of the driving means, see the relevant classes for such means)
F04D 25/022	.. {comprising a yielding coupling, e.g. hydraulic(a magnetic coupling F04D 25/026)}
F04D 25/024	.. {the driving means being assisted by a power recovery turbine}
F04D 25/026	.. {with a magnetic coupling}
F04D 25/028	.. {the driving means being a planetary gear}
F04D 25/04	.. the pump being fluid-driven{(pumps driven by exhaust gases F02B 37/00 , F02B 39/00 ; turbochargers F02C 6/12)}
F04D 25/045	... {the pump wheel carrying the fluid driving means, e.g. turbine blades}
F04D 25/06	.. the pump being electrically driven(F04D 25/08 takes precedence)
F04D 25/0606	... {the electric motor being specially adapted for integration in the pump}
F04D 25/0613 {the electric motor being of the inside-out type, i.e. the rotor is arranged radially outside a central stator}
F04D 25/062 {Details of the bearings}
F04D 25/0626 {Details of the lubrication}
F04D 25/0633 {Details of the magnetic circuit}
F04D 25/064 {Details of the rotor}
F04D 25/0646 {Details of the stator}
F04D 25/0653 {the motor having a plane air gap, e.g. disc-type}
F04D 25/066 {Linear Motors}
F04D 25/0666 {a sensor is integrated into the pump/motor design}
F04D 25/0673	... {Battery powered}
F04D 25/068	... {Mechanical details of the pump control unit(pump control details F04D 27/00)}
F04D 25/0686	... {specially adapted for submerged use}
F04D 25/0693	... {Details or arrangements of the wiring}
F04D 25/08	.. the working fluid being air, e.g. for ventilation
F04D 25/082	... {the unit having provision for cooling the motor}
F04D 25/084	... {hand fans}
F04D 25/086 {hand operated}
F04D 25/088	... {Ceiling fans}
F04D 25/10	... the unit having provisions for automatically changing direction of output air
F04D 25/105 {by changing rotor axis direction, e.g. oscillating fans(interconnecting rotary motion and oscillating motion F16H)}
F04D 25/12	... the unit being adapted for mounting in apertures
F04D 25/14 and having shutters, e.g. automatically closed when not in use
F04D 25/16	. Combinations of two or more pumps{Producing two or more separate gas flows}
F04D 25/163	.. {driven by a common gearing arrangement}
F04D 25/166	.. {using fans}

F04D 27/00 Control, e.g. regulation, of pumps, pumping installations or systems**WARNING**

This group is not complete pending a reorganisation. See also group [F04D 27/02](#) which covers also control in general not focussing on surge control

- F04D 27/001 . {Testing thereof; Determination or simulation of flow characteristics; Stall or surge detection, e.g. condition monitoring}

- F04D 27/002 . {by varying geometry within the pumps, e.g. by adjusting vanes}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0246](#)

- F04D 27/003 . {by throttling([F04D 27/002](#) takes precedence)}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0253](#))

- F04D 27/004 . {by varying driving speed}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0261](#)

- F04D 27/005 . {by changing flow path between different stages or between a plurality of compressors; Load distribution between compressors}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0269](#)]

- F04D 27/006 . {by influencing fluid temperatures}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0276](#)

- F04D 27/007 . {Conjoint control of two or more different functions}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0284](#)

- F04D 27/008 . {Stop safety or alarm devices, e.g. stop-and-go control; Disposition of check-valves}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0292](#)

- F04D 27/009 . {by bleeding, by passing or recycling fluid}

WARNING

This group is not complete pending a reorganisation. See also group [F04D 27/0207](#)

- F04D 27/02 . Surge control{(surge detection [F04D 27/001](#))}
- F04D 27/0207 . . {by bleeding, bypassing or recycling fluids}{ influencing the boundary layer by an uncontrolled bleeding of the working fluid [F04D 29/681](#))}
- F04D 27/0215 . . . {Arrangements therefor, e.g. bleed or by-pass valves}
- F04D 27/0223 . . . {Control schemes therefor}
- F04D 27/023 . . . {Details or means for fluid extraction}
- F04D 27/0238 . . . {Details or means for fluid reinjection}
- F04D 27/0246 . . {by varying geometry within the pumps, e.g. by adjusting vanes}
- F04D 27/0253 . . {by throttling([F04D 27/0246](#) takes precedence)}
- F04D 27/0261 . . {by varying driving speed}
- F04D 27/0269 . . {by changing flow path between different stages or between a plurality of compressors; load distribution between compressors}
- F04D 27/0276 . . {by influencing fluid temperature}
- F04D 27/0284 . . {Conjoint control of two or more different functions}
- F04D 27/0292 . . {Stop safety or alarm devices, e.g. stop-and-go control; Disposition of check-valves}

F04D 29/00 Details, component parts, or accessories(machine elements in general [F16](#))

- F04D 29/002 . {especially adapted for elastic fluid pumps}
- F04D 29/005 . {Decorative aspects, i.e. features which have no effect on the functioning of the pump}
- F04D 29/007 . {especially adapted for liquid pumps}
- F04D 29/02 . Selection of particular materials(for handling specific liquids [F04D 7/00](#) { [F04D 23/001](#) })
- F04D 29/023 . . {especially adapted for elastic fluid pumps}
- F04D 29/026 . . {especially adapted for liquid pumps}
- F04D 29/04 . Shafts or bearings, or assemblies thereof(specially adapted for elastic fluid pumps [F04D 29/05](#))
- F04D 29/0405 . . {joining shafts, e.g. rigid couplings, quill shafts}{ **WARNING:** The group [F04D 29/0405](#) is no longer used for the classification of new documents as from July 1st, 2007. The backlog of this group is being continuously reclassified to [F04D 29/044](#) and [F04D 29/054](#) }
- F04D 29/041 . . Axial thrust balancing

F04D 29/0413	...	{hydrostatic; hydrodynamic thrust bearings}
F04D 29/0416	...	{balancing pistons}
F04D 29/042	..	Axially shiftable rotors F04D 29/041 takes precedence { control by creating a by-pass F04D 15/0027 }
F04D 29/043	..	Shafts
F04D 29/044	...	Arrangements for joining or assembling shafts
F04D 29/046	..	Bearings
F04D 29/0462	...	{Bearing cartridges}
F04D 29/0465	...	{Ceramic bearing designs}
F04D 29/0467	...	{Spherical bearings}
F04D 29/047	...	hydrostatic; hydrodynamic
F04D 29/0473	{for radial pumps}
F04D 29/0476	{for axial pumps}
F04D 29/048	...	magnetic; electromagnetic
F04D 29/049	...	Roller bearings
F04D 29/05	.	Shafts or bearings, or assemblies thereof, specially adapted for elastic fluid pumps
F04D 29/051	..	Axial thrust balancing
F04D 29/0513	...	{hydrostatic; hydrodynamic thrust bearings}
F04D 29/0516	...	{balancing pistons}
F04D 29/052	..	Axially shiftable rotors F04D 29/051 takes precedence { control by creating a by-pass F04D 27/0246 }
F04D 29/053	..	Shafts
F04D 29/054	...	Arrangements for joining or assembling shafts
F04D 29/056	..	Bearings
F04D 29/0563	...	{Bearings cartridges}
F04D 29/0566	...	{Ceramic bearing designs}
F04D 29/057	...	hydrostatic; hydrodynamic
F04D 29/058	...	magnetic; electromagnetic
F04D 29/059	...	Roller bearings
F04D 29/06	.	Lubrication{(F04D 13/0606 , F04D 13/0646 , F04D 13/0653 take precedence)}
F04D 29/061	..	{especially adapted for liquid pumps}
F04D 29/063	..	especially adapted for elastic fluid pumps
F04D 29/08	.	Sealings
F04D 29/083	..	{especially adapted for elastic fluid pumps}
F04D 29/086	..	{especially adapted for liquid pumps}
F04D 29/10	..	Shaft sealings
F04D 29/102	...	{especially adapted for elastic fluid pumps}
F04D 29/104	{the sealing fluid being other than the working fluid or being the working fluid treated}
F04D 29/106	...	{especially adapted for liquid pumps}

F04D 29/108	{the sealing fluid being other than the working liquid or being the working liquid treated}
F04D 29/12	...	using sealing-rings
F04D 29/122	{especially adapted for elastic fluid pumps}
F04D 29/124	{with special means for adducting cooling or sealing fluid}
F04D 29/126	{especially adapted for liquid pumps}
F04D 29/128	{with special means for adducting cooling or sealing fluid}
F04D 29/14	...	operative only when pump is inoperative
F04D 29/143	{especially adapted for elastic fluid pumps}
F04D 29/146	{especially adapted for liquid pumps}
F04D 29/16	..	between pressure and suction sides
F04D 29/161	...	{especially adapted for elastic fluid pumps}
F04D 29/162	{of a centrifugal flow wheel}
F04D 29/164	{of an axial flow wheel}
F04D 29/165	...	{especially adapted for liquid pumps}
F04D 29/167	{of a centrifugal flow wheel}
F04D 29/168	{of an axial flow wheel}
F04D 29/18	.	Rotors(specially for elastic fluids F04D 29/26)
F04D 29/181	..	{Axial flow rotors(F04D 29/185 take precedence)}
F04D 29/183	...	{Semi axial flow rotors}
F04D 29/185	..	{Rotors consisting of a plurality of wheels}
F04D 29/186	..	{Shaftless rotors(F04D 13/024 takes precedence)}
F04D 29/188	..	{specially for regenerative pumps}
F04D 29/20	..	Mounting rotors on shafts
F04D 29/22	..	specially for centrifugal pumps
F04D 29/2205	...	{Conventional flow pattern(F04D 29/18 takes precedence)}
F04D 29/2211	{More than one set of flow passages}
F04D 29/2216	{Shape, geometry(F04D 29/2211 takes precedence)}
F04D 29/2222	{Construction and assembly(F04D 29/2211 takes precedence)}
F04D 29/2227	{for special materials}
F04D 29/2233	{entirely open or stamped from one sheet}
F04D 29/2238	...	{Special flow patterns(F04D 11/005 takes precedence)}
F04D 29/2244	{Free vortex}
F04D 29/225	{Channel wheels, e.g. one blade or one flow channel}
F04D 29/2255	{flow-channels with a special cross-section contour, e.g. ejecting, throttling or diffusing effect}
F04D 29/2261	...	{with special measures}
F04D 29/2266	{for sealing or thrust balance(F04D 29/04 and F04D 29/16 take precedence)}
F04D 29/2272	{for influencing flow or boundary layer}
F04D 29/2277	{for increasing NPSH or dealing with liquids near boiling-point}

F04D 29/2283	{for reverse pumping action}
F04D 29/2288	{for comminuting, mixing or separating}
F04D 29/2294	{for protection, e.g. against abrasion}
F04D 29/24	...	Vanes
F04D 29/242	{Geometry, shape}
F04D 29/245	{for special effects}
F04D 29/247	{elastic or self-adjusting}
F04D 29/26	.	Rotors specially for elastic fluids
F04D 29/263	..	{mounting fan or blower rotors on shafts}
F04D 29/266	..	{mounting compressor rotors on shafts}
F04D 29/28	..	for centrifugal or helico-centrifugal pumps{for radial-flow or helico-centrifugal pumps}
F04D 29/281	...	{for fans or blowers}
F04D 29/282	{the leading edge of each vane being substantially parallel to the rotation axis}
F04D 29/283	{rotors of the squirrel-cage type}
F04D 29/284	...	{for compressors}
F04D 29/285	{the compressor wheel comprising a pair of rotatable bladed hub portions axially aligned and clamped together}
F04D 29/286	{multi-stage rotors}
F04D 29/287	...	{with adjusting means}
F04D 29/288	...	{Part of the wheel having an ejecting effect e.g. being bladeless diffuser}
F04D 29/289	...	{having provision against erosion or for dust-separation}
F04D 29/30	...	Vanes
F04D 29/305	{Flexible vanes}
F04D 29/32	..	for axial flow pumps{ multistage rotors F01D 5/00 }
F04D 29/321	...	{for axial flow compressors}
F04D 29/322	{blade mountings(F01D 5/30 takes precedence)}
F04D 29/323	{adjustable}
F04D 29/324	{blades(F01D 5/282 takes precedence)}
F04D 29/325	...	{for axial flow fans(blade mountings F04D 29/34 , blades F04D 29/38)}
F04D 29/326	{comprising a rotating shroud}
F04D 29/327	{with non identical blades}
F04D 29/328	{with unequal distribution of blades around the hub}
F04D 29/329	{Details of the hub}
F04D 29/34	...	Blade mountings{ for axial flow compressors F04D 29/322 }
F04D 29/36	adjustable{ flexible blades F04D 29/382 }
F04D 29/362	{during rotation}
F04D 29/364	{The blades having only a predetermined number of possible positions}
F04D 29/366	{Adjustment by interaction of inertia and lift}

F04D 29/368	{Adjustment by differences of temperature}
F04D 29/38	...	Blades{(for axial flow compressors F04D 29/324)}
F04D 29/382	{Flexible blades}
F04D 29/384	{characterised by form}
F04D 29/386	{Skewed blades}
F04D 29/388	{characterised by construction}
F04D 29/40	.	Casings; Connections of working fluid{ bleed or by-pass valves F04D 15/0011 , F04D 27/0215 }
F04D 29/403	..	{especially adapted for elastic fluid pumps}
F04D 29/406	..	{especially adapted for liquid pumps}
F04D 29/42	..	for radial or helico-centrifugal pumps
F04D 29/4206	...	{especially adapted for elastic fluid pumps}
F04D 29/4213	{suction ports}
F04D 29/422	{Discharge tongues(F04D 17/04 takes precedence)}
F04D 29/4226	{Fan casings}
F04D 29/4233	{with volutes extending mainly in axial or radially inward direction}
F04D 29/424	{Double entry casings}
F04D 29/4246	{comprising more than one outlet}
F04D 29/4253	{with axial entry and discharge}
F04D 29/426	...	{especially adapted for liquid pumps}
F04D 29/4266	{made of sheet metal}
F04D 29/4273	{suction eyes}
F04D 29/428	{Discharge tongues(F04D 17/04 takes precedence)}
F04D 29/4286	{inside lining e.g. rubber}
F04D 29/4293	{Details of fluid inlet or outlet}
F04D 29/44	...	Fluid-guiding means, e.g. diffusers
F04D 29/441	{especially adapted for elastic fluid pumps}
F04D 29/442	{rotating diffusers}
F04D 29/444	{Bladed diffusers}
F04D 29/445	{especially adapted for liquid pumps}
F04D 29/447	{rotating diffusers}
F04D 29/448	{bladed diffusers}
F04D 29/46	adjustable
F04D 29/462	{especially adapted for elastic fluid pumps}
F04D 29/464	{adjusting flow cross-section, otherwise than by using adjustable stator blades}
F04D 29/466	{especially adapted for liquid fluid pumps}
F04D 29/468	{adjusting flow cross-section, otherwise than by using adjustable stator blades}
F04D 29/48	for unidirectional fluid flow in reversible pumps{ rotors for reverse action F04D 29/2283 }

F04D 29/483	{especially adapted for elastic fluid pumps}
F04D 29/486	{especially adapted for liquid pumps}
F04D 29/50	for reversing fluid flow{ rotors for reverse action F04D 29/2283 }
F04D 29/503	{especially adapted for elastic fluid pumps}
F04D 29/506	{especially adapted for liquid pumps}
F04D 29/52	..	for axial pumps
F04D 29/522	...	{especially adapted for elastic fluid pumps}
F04D 29/524	{shiftable members for obturating part of the flow path}
F04D 29/526	{Details of the casing section radially opposing blade tips(ducts F04D 29/545)}
F04D 29/528	...	{especially adapted for liquid pumps}
F04D 29/54	...	Fluid-guiding means, e.g. diffusers
F04D 29/541	{Specially adapted for elastic fluid pumps(F04D 29/56 takes precedence)}
F04D 29/542	{Bladed diffusers(fixing blades to stators F01D 9/042)}
F04D 29/544	{Blade shapes}
F04D 29/545	{Ducts}
F04D 29/547	{having a special shape in order to influence fluid flow}
F04D 29/548	{Specially adapted for liquid pumps(F04D 29/56 takes precedence)}
F04D 29/56	adjustable
F04D 29/563	{especially adapted for elastic fluid pumps}
F04D 29/566	{especially adapted for liquid pumps}
F04D 29/58	.	Cooling(of machines or engines in general F01P); Heating; Diminishing heat transfer{ for the motor of air-pump units F04D 25/082 ; cooling of shafts or bearings F04D 29/04 }
F04D 29/5806	..	{Cooling the drive system}
F04D 29/5813	..	{Cooling the control unit}
F04D 29/582	..	{specially adapted for elastic fluid pumps}
F04D 29/5826	...	{Cooling at least part of the working fluid in a heat exchanger}
F04D 29/5833	{flow schemes and regulation thereto}
F04D 29/584	...	{cooling or heating the machine(F04D 29/5846 , F04D 29/5853 take precedence)}
F04D 29/5846	...	{cooling by injection}
F04D 29/5853	...	{heat insulation or conduction}
F04D 29/586	..	{specially adapted for liquid pumps}
F04D 29/5866	...	{Cooling at last part of the working fluid in a heat exchanger}
F04D 29/5873	{flow schemes and regulation thereto}
F04D 29/588	...	{cooling or heating the machine(F04D 29/5886 , F04D 29/5893 take precedence)}
F04D 29/5886	...	{cooling by injection}
F04D 29/5893	...	{heat insulation or conduction}
F04D 29/60	.	Mounting; Assembling; Disassembling{ F04D 13/10 takes precedence }

F04D 29/601	..	{specially adapted for elastic fluid pumps}
F04D 29/602	...	{Mounting in cavities}
F04D 29/603	{means for positioning from outside}
F04D 29/604	{means for removing without depressurising the cavity}
F04D 29/605	..	{specially adapted for liquid pumps}
F04D 29/606	...	{Mounting in cavities}
F04D 29/607	{means for positioning from outside}
F04D 29/608	{means for removing without depressurizing the cavity}
F04D 29/62	..	of radial or helico-centrifugal pumps
F04D 29/622	...	{Adjusting the clearances between rotary and stationary parts}
F04D 29/624	...	{especially adapted for elastic fluid pumps}
F04D 29/626	{Mounting or removal of fans}
F04D 29/628	...	{especially adapted for liquid pumps}
F04D 29/64	..	of axial pumps
F04D 29/642	...	{by adjusting the clearances between rotary and stationary parts}
F04D 29/644	...	{especially adapted for elastic fluid pumps}
F04D 29/646	{Mounting or removal of fans}
F04D 29/648	...	{especially adapted for liquid pumps}
F04D 29/66	.	Combating cavitation, whirls, noise, vibration or the like(gas-flow silencers for machines or engines in general F01N); Balancing(surge control F04D 27/02)
F04D 29/661	..	{especially adapted for elastic fluid pumps}
F04D 29/662	...	{Balancing of rotors(compensating unbalance G01M 1/36)}
F04D 29/663	...	{Sound attenuation}
F04D 29/664	{by means of sound absorbing material}
F04D 29/665	{by means of resonance chambers or interference}
F04D 29/666	...	{by means of rotor construction or layout, e.g. unequal distribution of blades or vanes}
F04D 29/667	...	{by influencing the flow pattern, e.g. suppression of turbulence}
F04D 29/668	...	{damping or preventing mechanical vibrations}
F04D 29/669	..	{especially adapted for liquid pumps(F04D 29/18 takes precedence)}
F04D 29/68	..	by influencing boundary layers{(by bleeding elastic fluid F04D 27/0215)}
F04D 29/681	...	{especially adapted for elastic fluid pumps}
F04D 29/682	{by fluid extraction}
F04D 29/684	{by fluid injection}
F04D 29/685	{Inducing localised fluid recirculation in the stator-rotor interface}
F04D 29/687	{Plasma actuators therefore}
F04D 29/688	...	{especially adapted for liquid pumps}
F04D 29/70	.	Suction grids; Strainers; Dust separation; Cleaning
F04D 29/701	..	{especially adapted for elastic fluid pumps}
F04D 29/703	...	{specially for fans, e.g. fan guards}

F04D 29/705 . . . {Adding liquids}
F04D 29/706 . . . {Humidity separation}
F04D 29/708 . . {specially for liquid pumps}

Guidance heading: Other non-positive-displacement pumps

F04D 31/00 Pumping liquids and elastic fluids at the same time

F04D 33/00 Non-positive-displacement pumps with other than pure rotation, e.g. of oscillating type([F04D 35/00](#) takes precedence; hand-held fans [A45B](#))

F04D 35/00 Pumps producing waves in liquids, i.e. wave.producers(for bath tubs [A47K 3/10](#))