

CPC**COOPERATIVE PATENT CLASSIFICATION****Y10T****TECHNICAL SUBJECTS COVERED BY FORMER US CLASSIFICATION****NOTE**

This subclass has been introduced in January 2015 in view of the CPC to accommodate for technical subjects formerly covered by USPC

Former US Class 16 series

Y10T 16/00	Miscellaneous hardware [e.g., bushing, carpet fastener, caster, door closer, panel hanger, attachable or adjunct handle, hinge, window sash balance, etc.]
Y10T 16/05	. Bushing
Y10T 16/063	. . Providing a restricted or insulated environment [i.e., sealable] for internal elements
Y10T 16/075	. . Bung or tap
Y10T 16/082	. . . Threaded
Y10T 16/088	. . Providing strain relief
Y10T 16/10	. Carpet fasteners
Y10T 16/104	. . Combined fasteners and stretchers
Y10T 16/109	. . Hook
Y10T 16/113	. . Moldings
Y10T 16/118	. . Rug
Y10T 16/122	. . Stair
Y10T 16/124	. . . Risers
Y10T 16/125	. . . Rods
Y10T 16/126 Catches
Y10T 16/1263 Sliding
Y10T 16/1267 Swinging
Y10T 16/127	. . Sliding
Y10T 16/131	. . Strips
Y10T 16/134	. . Swinging
Y10T 16/14	. Carpet stiffener or anti-slip device, per se
Y10T 16/18	. Casters
Y10T 16/182	. . Adjustable
Y10T 16/184	. . Wheels
Y10T 16/1847	. . . Antifrictionally mounted
Y10T 16/1853	. . . Multiple
Y10T 16/1857 Antifrictionally swivelled

Y10T 16/186	. .	Antifrictionally swivelled
Y10T 16/1867	. . .	Ball
Y10T 16/1873	. . .	Cylinder
Y10T 16/1877	Pivoted
Y10T 16/188	. .	Ball
Y10T 16/1887	. . .	Antifrictionally mounted
Y10T 16/1889	Ball
Y10T 16/1891	Cylinder
Y10T 16/1893	. . .	Pivoted
Y10T 16/19	. .	Bracket supports
Y10T 16/191	. .	Detachable
Y10T 16/193	. .	Leg elevators
Y10T 16/1937	. . .	Sliding
Y10T 16/1943	. . .	Swinging
Y10T 16/195	. .	Locked
Y10T 16/196	. . .	Shimmy dampening
Y10T 16/197	. .	Lubricators
Y10T 16/199	. .	Pintles
Y10T 16/201	. .	Pintle retainers
Y10T 16/202	. . .	Frame
Y10T 16/203	. .	Frame
Y10T 16/204	. . .	Single leg frame or fork
Y10T 16/205	. .	Rigid wheel supports
Y10T 16/207	. .	Scrapers
Y10T 16/209	. .	Sliding
Y10T 16/21	. . .	for tubular leg
Y10T 16/211	. .	Sockets
Y10T 16/212	. .	Spring supported
Y10T 16/214	. .	Inclined axle
Y10T 16/216	. .	Caster guard
Y10T 16/218	. .	Obstruction climbing aid
Y10T 16/22	. .	Thermally released check or closer
Y10T 16/27	. .	Checks and closers
Y10T 16/276	. .	Liquid
Y10T 16/2766	. . .	Concentric spring chamber
Y10T 16/2769	Cam
Y10T 16/2771	. . .	Hinge
Y10T 16/2774	Floor pivot
Y10T 16/2777	. . .	Multiple piston
Y10T 16/2782	. . .	Oscillating cylinder

Y10T 16/2788	. . . Oscillating piston
Y10T 16/2793	. . . Side spring chamber
Y10T 16/2796 Cam
Y10T 16/2799	. . . Spring and flexible link
Y10T 16/2804	. . . Spring and gear
Y10T 16/281	. . Pneumatic
Y10T 16/282	. . . Flexible link
Y10T 16/283	. . . Hinge
Y10T 16/285	. . . Spring and gear
Y10T 16/286	. . . Spring and lever
Y10T 16/287	. . Spring and flexible link
Y10T 16/293	. . Spring and gear
Y10T 16/299	. . Spring and lever
Y10T 16/304	. . Hinge
Y10T 16/31	. Gate hangers
Y10T 16/33	. . Sliding and swinging
Y10T 16/35	. Panel hangers, travelers and/or tracks
Y10T 16/353	. . with flexible panel attaching means
Y10T 16/354	. . . Covered, hollow or slotted track
Y10T 16/3543 with antifriction means
Y10T 16/3545 Wood track
Y10T 16/3547 Wood track
Y10T 16/355	. . . with antifriction means
Y10T 16/356	. . Ball
Y10T 16/359	. . Cylinder
Y10T 16/361	. . Guide brackets
Y10T 16/364	. . Guide rollers
Y10T 16/367	. . Link and lever
Y10T 16/37	. . Sliding shoe
Y10T 16/372	. . . Drapery supports
Y10T 16/373	. . Track and bracket
Y10T 16/375	. . . Drapery supports
Y10T 16/376	. . Covered, hollow or slotted track
Y10T 16/377	. . . Wood
Y10T 16/378	. . . Drapery supports
Y10T 16/3785 Wood
Y10T 16/379	. . Tracks
Y10T 16/3797	. . . Drapery supports
Y10T 16/3803	. . . Laminated
Y10T 16/381	. . Wheel mounts

Y10T 16/3813	. . .	Antifrictionally mounted wheels
Y10T 16/3816	. . .	Door elevating
Y10T 16/3819	. . .	Floor
Y10T 16/3822	. . .	Reciprocating track
Y10T 16/3825	. . .	Traveling wheel
Y10T 16/3828	. . .	Swinging
Y10T 16/3831	. . .	Swiveling
Y10T 16/3834	. . .	Vertically adjustable
Y10T 16/3837	. . .	Wheel and guide roller
Y10T 16/384	. .	Wheels
Y10T 16/387	. .	Overlapping doors, common track
Y10T 16/39	. .	Ferrules, rings, and thimbles
Y10T 16/42	. .	Ring ferrules
Y10T 16/44	. .	Handle, handle component, or handle adjunct
Y10T 16/444	. .	having receptacle within
Y10T 16/447	. .	for plow
Y10T 16/451	. .	Length adjustable pull handle for luggage or luggage cart [e.g., wheeled suitcase handle, etc.]
Y10T 16/455	. .	Luggage-type [loop style] handgrip for carrying [e.g., suitcase, handbag, briefcase, shopping bag, package, etc.]
Y10T 16/4554	. . .	Extensible handle
Y10T 16/4559	. . .	Detachable handle
Y10T 16/4563	. . .	Welded or adhesively attached handle
Y10T 16/4567	. . .	Swinging handle
Y10T 16/4569	with means permanently connecting the handle to a carried article
Y10T 16/4571	. . .	with means permanently connecting the handle to a carried article
Y10T 16/4576	. . .	with carrier handle including a user enhanced grip attachment
Y10T 16/458	. .	Door handle
Y10T 16/459	. . .	Detachable handle
Y10T 16/46	. . .	Knob type
Y10T 16/462	. .	Drawer pull
Y10T 16/4628	. . .	Lift
Y10T 16/4636	. . .	Knob type
Y10T 16/464	Swinging
Y10T 16/4644	. . .	Loop type
Y10T 16/4652	. . .	Ring type
Y10T 16/466	. .	Handle having mounted grip means [e.g., bicycle handlebar grips, etc.]
Y10T 16/469	. .	Detachable handle
Y10T 16/4696	. . .	for battery
Y10T 16/4701	. . .	for casket

Y10T 16/4707	. . . for container
Y10T 16/4713	. . . Auxiliary handle
Y10T 16/4719	. . . Extension
Y10T 16/4724	. . . Cord or rope related
Y10T 16/473	. . Extensible handle
Y10T 16/476	. . Handle with ergonomic structure [e.g., finger engagement structure such as indents, grooves, etc.] and handle user-interaction [human engineering] enhancements such as improved handle dimensions and handle positioning
Y10T 16/48	. Insulated handle
Y10T 16/484	. . Handwheel
Y10T 16/487	. . Knob type
Y10T 16/491	. . Wire type
Y10T 16/495	. . Unshaped or unattached pad
Y10T 16/498	. . Bar-type handle
Y10T 16/499	. . . for lawnmower
Y10T 16/50	. . . Swinging
Y10T 16/501 Casket handle
Y10T 16/502	. . Braced handle
Y10T 16/506	. . Knob-type handle
Y10T 16/508	. . . with flexible suspending means
Y10T 16/509	. . Lift
Y10T 16/513	. . Loop-type handle
Y10T 16/515	. . . Swinging
Y10T 16/516	. . Ring-type handle
Y10T 16/52	. Hinge
Y10T 16/521	. . including frangible or fusible portion
Y10T 16/522	. . with diverse art portion or attachment
Y10T 16/524	. . Ball and socket
Y10T 16/525	. . Pliant or elastic hinge
Y10T 16/5253	. . . Metallic
Y10T 16/5257	. . . Snap or X hinge
Y10T 16/526	. . Eyeglass hinge
Y10T 16/527	. . Retractable pintle
Y10T 16/5275	. . . Latch hinge
Y10T 16/528	. . Latch hinge
Y10T 16/5285	. . . Resilient securing means
Y10T 16/529	. . including lever for shifting one member of hinge relative to another
Y10T 16/531	. . having staggered leaves
Y10T 16/532	. . including adjustment for changing relative orientation of hinged members
Y10T 16/5321	. . . having plural independent adjustments

Y10T 16/5322 All rectilinear
Y10T 16/53225 including screw-operated means to move hinged members
Y10T 16/5323	. . . Pivotal adjustment
Y10T 16/53235 including screw-operated means to move hinged members
Y10T 16/53238 About hinge axis
Y10T 16/5324	. . . including means to move hinged members
Y10T 16/53247 Along or parallel to hinge axis
Y10T 16/5325 including threaded hinge pin
Y10T 16/53253 Screw-operated
Y10T 16/53257 to shift plate toward or away from hinged member
Y10T 16/5326	. . . having adjustable spacer between leaf and hinged member [e.g., shim]
Y10T 16/5327	. . . Adjustable along or parallel to hinge axis
Y10T 16/5329	. . . having interdigitated surfaces or slot for hinge-to-member fastener
Y10T 16/533	. . having cover
Y10T 16/5335	. . . Leaf cover
Y10T 16/534	. . having clamp for attaching hinge to hinged member
Y10T 16/5345	. . . Circumferential clamp
Y10T 16/535	. . having means to facilitate assembly and disassembly of hinge sections to join or disjoin hinged members
Y10T 16/5353	. . . Resiliently biased hinge
Y10T 16/5355 having helical spring along hinge axis
Y10T 16/5357	. . . Resiliently biased retaining means
Y10T 16/5358 having discrete latch and spring to slide or pivot latch
Y10T 16/5359 Discrete retaining means for pivotal contacting surfaces
Y10T 16/536	. . . Separation of pivotal contacting surfaces
Y10T 16/53605 having movable or removable connector
Y10T 16/53607 Pintle removable from remainder of hinge
Y10T 16/536075 and additional connector for pintle or separate pintle sections
Y10T 16/53608 Screw-threaded connector
Y10T 16/5361 Axially shifting hinge sections
Y10T 16/53613 At specific angular orientation of hinge sections
Y10T 16/53615 Hook and pin
Y10T 16/5362 Hook in aperture
Y10T 16/53625 Hook to hook
Y10T 16/5363	. . . and discrete movable or removable connector to fasten one hinge section to another
Y10T 16/5367	. . . by relatively sliding connection [e.g., dovetail]
Y10T 16/5369 including receiving connector attachable to hinged member
Y10T 16/537	. . having means to reduce friction between hinge parts
Y10T 16/5373	. . . by fluid lubricant

Y10T 16/5377	. . .	Ball or roller bearing
Y10T 16/5379	Circularly distributed balls or rollers
Y10T 16/538	. .	Resiliently biased hinge
Y10T 16/5381	. . .	including means to render spring ineffective through all or a portion of swing
Y10T 16/53815	comprising manipulatable element or portion
Y10T 16/5382	. . .	Biased from either direction toward neutral position [e.g., double acting]
Y10T 16/53822	Helical spring transverse to hinge axis
Y10T 16/53824	Plural hinge axes [e.g., multiple pintle]
Y10T 16/53825	and barrels for helical springs on separate axes
Y10T 16/53826	Resiliently biased rolling or sliding cam surface
Y10T 16/53828	by helical spring along hinge axis
Y10T 16/5383	. . .	having transverse helical spring or elastic strip
Y10T 16/53832	Plural hinge axes [e.g., multiple pintle]
Y10T 16/53833	Four or more axes
Y10T 16/53834	to counterbalance weight of hinged member [e.g., closure biased to open position]
Y10T 16/53835	including pivoted coaxial spring retaining bar
Y10T 16/53836	Over-center spring or linkage travel [e.g., "holdback hinge"]
Y10T 16/53838	having means to hold hinged members against pivotal movement about hinge axis [i.e., catch]
Y10T 16/5384	. . .	Over-center spring or linkage travel [e.g., "holdback hinge"]
Y10T 16/53843	Plural hinge axes
Y10T 16/53845	Coil spring having axis along or parallel to hinge axis
Y10T 16/53848	including camming or sliding surface to deflect spring perpendicularly to the hinge axis
Y10T 16/5385	. . .	having means to hold hinged members against pivotal movement about hinge axis [e.g., catch]
Y10T 16/5386	. . .	having force adjustment
Y10T 16/53862	Rotatable spring-engaging collar
Y10T 16/538627	having detention aperture or protuberance
Y10T 16/538633	having tool-receiving aperture
Y10T 16/53864	. . .	Plural hinge axes [e.g., multiple pintle]
Y10T 16/5387	. . .	having axially biased camming surface
Y10T 16/5388	. . .	Coil
Y10T 16/53883	Plural coils
Y10T 16/53885	to counterbalance weight of hinged member [e.g., horizontal closure biased to open position]
Y10T 16/53888	On pintle
Y10T 16/5389	. . .	torsion spring
Y10T 16/539	. .	Gravitating hinge having vertical axis
Y10T 16/5393	. . .	having lift rod

Y10T 16/5395	. . .	having plural spaced hinge axes
Y10T 16/5398	. . .	including cam surface and follower
Y10T 16/53984	and rolling element
Y10T 16/53985	Between opposing surfaces
Y10T 16/53987	and detent in cam surface
Y10T 16/53988	On axially twisted or helically fluted element
Y10T 16/53992	including means to hold hinged members against pivotal movement
Y10T 16/53996	having aperture for slidably receiving pintle [e.g., camming knuckle]
Y10T 16/54	. .	including means to hold or retard hinged members against pivotal movement [e.g., catch]
Y10T 16/5401	. . .	Magnetic
Y10T 16/5402	. . .	Resiliently biased catch
Y10T 16/54021	having spring force adjustment
Y10T 16/54023	including toggle linkage
Y10T 16/54024	having discrete manipulatable release means [e.g., lever]
Y10T 16/540243	including cam or eccentric
Y10T 16/540247	Sliding release means or lever-actuated sliding catch
Y10T 16/54025	Sliding
Y10T 16/540253	Movement along or parallel to hinge axis
Y10T 16/540254	Interdigitated or plural sockets
Y10T 16/540255	Opposed interdigitated sliding collars on hinge axis
Y10T 16/540256	and catch receiving socket
Y10T 16/540257	and catch receiving socket
Y10T 16/54026	Pivoted
Y10T 16/54028	Plural alternately useable detents
Y10T 16/54029	Spring arm
Y10T 16/540295	Plural opposed arms
Y10T 16/5403	. . .	by friction
Y10T 16/54033	Screw-threaded adjustment
Y10T 16/54034	Along or parallel to hinge axis
Y10T 16/540345	Threaded pintle
Y10T 16/54035	Cam or wedge actuator
Y10T 16/54038	On hinge pin or between surfaces surrounding hinge axis
Y10T 16/5404	. . .	Pivoted
Y10T 16/54044	Plural alternately useable detents
Y10T 16/54048	and sliding
Y10T 16/54052	Serially connected pivoted arms between leaves [e.g., brace]
Y10T 16/54056	About axis along or parallel to hinge axis
Y10T 16/5406	. . .	by transversely moving pin in slot
Y10T 16/5407	. . .	having discrete manipulatable release means [e.g., lever operated]

Y10T 16/5408	. . . by shifting hinged members
Y10T 16/54085 Along hinge axis
Y10T 16/5409	. . . Sliding
Y10T 16/54095 Along or parallel to hinge axis
Y10T 16/541	. . including toothed gear
Y10T 16/542	. . comprising nested open curved portions attached to hinged members
Y10T 16/543	. . . including hinge pin
Y10T 16/544	. . including transversely moving pin in slot
Y10T 16/5443	. . . Plural noncollinear pins and slots
Y10T 16/5444 Parallel slots
Y10T 16/5445	. . . having pin fixed to pivoted arm or plate
Y10T 16/5448	. . . Hinge pin movable along slot
Y10T 16/545	. . including sliding surfaces to permit relative translation of hinged members
Y10T 16/5453	. . . and stop or abutment for pivotal movement
Y10T 16/5457	. . . Movement transverse to hinge axis
Y10T 16/546	. . Three-hinged members
Y10T 16/547	. . having plural hinge axes [e.g., multiple pintle]
Y10T 16/5472	. . . having transverse or skewed axes
Y10T 16/5474	. . . Connected by serially arranged pivoted links between hinged members
Y10T 16/5475 Plural sets of serially arranged pivoted links
Y10T 16/5476	. . . Four or more axes
Y10T 16/5478	. . . including stop or latch
Y10T 16/548	. . including laminated leaf
Y10T 16/549	. . Wire hinge
Y10T 16/551	. . having stop or abutment
Y10T 16/5513	. . . Adjustable or resilient
Y10T 16/5515	. . . comprising relieved axially opposed relatively rotating surfaces
Y10T 16/5518	. . . comprising platelike bearing portion curved about hinge axis
Y10T 16/552	. . Hinge axis passes through hinged member [e.g., floor hinge]
Y10T 16/5525	. . . Pintle or pivot concealed in hinged member
Y10T 16/553	. . including means to retain pintle in hinge [e.g., tamper proof, nonrising pintle, etc.]
Y10T 16/5535	. . . Threaded or slotted pintle or knuckle
Y10T 16/554	. . including means to fasten leaf to member
Y10T 16/5543	. . . by expandable connector
Y10T 16/5547	. . . Self-penetrating fastener
Y10T 16/555	. . Specified material
Y10T 16/557	. . Specific pintle structure
Y10T 16/558	. . Specific leaf structure
Y10T 16/559	. . having prongs or cooperating structure on leaf
Y10T 16/5595	. . . Angular leaf sections

Y10T 16/55963 Parallel sections
Y10T 16/55975 Coplanar sections
Y10T 16/55988 including planar section perpendicular to hinge axis
Y10T 16/56	. Closers
Y10T 16/568	. . Spring and flexible link
Y10T 16/577	. . Spring and gear
Y10T 16/585	. . Spring and lever
Y10T 16/593	. . Spring
Y10T 16/595	. . . Bow
Y10T 16/597	. . . Rubber
Y10T 16/599	. . . torsional
Y10T 16/5995 Coil
Y10T 16/60	. . . Volute
Y10T 16/602	. . Weight
Y10T 16/61	. Closure checks
Y10T 16/615	. . Inertia
Y10T 16/62	. . Pneumatic
Y10T 16/625	. . Spring
Y10T 16/628	. . . Rubber
Y10T 16/6285 Rubber cushioned
Y10T 16/629 Multiple or opposed buffer surfaces
Y10T 16/6295 Link type
Y10T 16/6298	. Sash balances
Y10T 16/63	. . Cord and counterweight
Y10T 16/635	. . Sash and cord
Y10T 16/64	. . Spring
Y10T 16/641	. . . Drum and cord
Y10T 16/642	. . . Friction roller
Y10T 16/643	. . . Lever
Y10T 16/644	. . . Rack and pinion
Y10T 16/645	. . Rack and pinion
Y10T 16/65	. Sash-cord fasteners
Y10T 16/655	. . Bendable
Y10T 16/66	. . Chain
Y10T 16/665	. . Clamps
Y10T 16/67	. . Hooks
Y10T 16/675	. . Knot
Y10T 16/68	. . Slack-cord holders
Y10T 16/685	. . Weight
Y10T 16/69	. Sash-cord guides

Y10T 16/698	. . Wheel and casing
Y10T 16/706	. . Casings
Y10T 16/71	. . . Sheet metal, single piece
Y10T 16/714	. . Multiple wheel
Y10T 16/722	. . Sliding
Y10T 16/73	. Sash weights
Y10T 16/743	. . Composite
Y10T 16/755	. . Sectional
Y10T 16/767	. . Weight and wheel
Y10T 16/78	. Window-bead fasteners
Y10T 16/82	. Counterbalance device, per se
Y10T 16/84	. . Spring
Y10T 16/86	. Door escutcheon or similar element
Y10T 16/90	. Paper weight
Y10T 16/95	. Miscellaneous element or attachment

Former US Class 24 series

Y10T 24/00	Buckles, buttons, clasps, etc.
Y10T 24/10	. Miscellaneous
Y10T 24/11	. Album fasteners
Y10T 24/12	. Gun band type
Y10T 24/13	. Article holder attachable to apparel or body
Y10T 24/1303	. . Chatelaine safety hooks
Y10T 24/1306	. . Flower
Y10T 24/1309	. . . Pin attached
Y10T 24/1312	. . Napkin
Y10T 24/1315	. . . Hook
Y10T 24/1318	. . . Neck enclosing
Y10T 24/1321	. . Pencil
Y10T 24/1324	. . . Clasp attached
Y10T 24/1326 Finger ear, belt attached pencil holder
Y10T 24/1329 Pencil holder with paper clip
Y10T 24/1332 Combined and convertible pencil holder
Y10T 24/1335 Container type pencil holder
Y10T 24/1338 Separate pencil holder and pocket engaging clip
Y10T 24/1341 Sliding jaw pencil holding clip
Y10T 24/1344 Wire pencil holder
Y10T 24/1347 Flexible shank pencil holder
Y10T 24/135 with movable catch [e.g., pin pivoted lever, roller, etc.]

Y10T 24/1353 Pivoted jaw pencil holder
Y10T 24/1356	. . . Pin attached
Y10T 24/1359	. . . Rule holder
Y10T 24/1362	. . Sleeve holder [e.g., for inner coat]
Y10T 24/1365	. . Pin attached
Y10T 24/1368	. . Arm or leg carried holder
Y10T 24/1371	. . Eyeglass holder including retaining means
Y10T 24/1374	. . Neck supported holder
Y10T 24/1376	. . Holder contains pocket engager [e.g., antitheft device, wallet protector]
Y10T 24/1379	. . Key ring holder
Y10T 24/1382	. . Receptacle type holder
Y10T 24/1385	. . . Eyeglass or spectacle case
Y10T 24/1388	. . Open-ended holster type holder
Y10T 24/1391	. . Article held by clip with spring [e.g., leaf, coil] member
Y10T 24/1394	. . Article held by clip
Y10T 24/1397	. . Article held by flexible connector [e.g., chain]
Y10T 24/14	. Bale and package ties, hose clamps
Y10T 24/1402	. . Packet holders
Y10T 24/1404	. . . Cord
Y10T 24/1406	. . . Adjustable bands
Y10T 24/1408	. . . Closed loops
Y10T 24/141	. . . Plastic bands
Y10T 24/1412	. . with tighteners
Y10T 24/1414	. . . Wedge
Y10T 24/1416	. . . Winder
Y10T 24/1418	. . . Self-locking [dead center or snap action]
Y10T 24/142 Adjustable girth
Y10T 24/1422 Rack bar
Y10T 24/1424	. . . Lever
Y10T 24/1427	. . . Worm and tooth
Y10T 24/1429 Pivotal worm band clamp
Y10T 24/1431 Radial worm band clamp
Y10T 24/1433	. . . Integral thread
Y10T 24/1435 External thread
Y10T 24/1437 Both ends threaded
Y10T 24/1439	. . . Radial screw
Y10T 24/1441	. . . Tangential screw
Y10T 24/1443 Adjustable girth
Y10T 24/1445 Step adjustment
Y10T 24/1447 Plural separable parts

Y10T 24/1449 Wire
Y10T 24/1451 Plural separable parts
Y10T 24/1453 Pivotal strap parts
Y10T 24/1455 Plural wrap
Y10T 24/1457	. . Metal bands
Y10T 24/1459	. . . Separate connections
Y10T 24/1461 One piece
Y10T 24/1463 Sheet metal
Y10T 24/1465 Buckle band connection
Y10T 24/1467 Swedged sheet metal band connection
Y10T 24/1469 End-to-end integral with band connecting means
Y10T 24/1471 Pivoted parts
Y10T 24/1473 Wedging parts
Y10T 24/1476 Wire
Y10T 24/1478	. . . Circumferentially swagged band clamp
Y10T 24/148	. . . End-to-end integral band end connection
Y10T 24/1482	. . . Ratchet and tool tightened band clamp
Y10T 24/1484	. . . Spring closed band clamp
Y10T 24/1486	. . . Screw locked band clamp
Y10T 24/1488	. . . Swedged to lock band ends
Y10T 24/149	. . Wire
Y10T 24/1492	. . . Separate connections
Y10T 24/1494 Wire
Y10T 24/1496	. . Wooden bands
Y10T 24/1498	. . Plastic band
Y10T 24/15	. Bag fasteners
Y10T 24/152	. . Swedged bag tie
Y10T 24/153	. . Plastic band bag tie
Y10T 24/155	. . Resilient slot bag tie
Y10T 24/157	. . Twist-to-close bag tie
Y10T 24/158	. . Slides to lock bag end within housing
Y10T 24/16	. Belt fasteners
Y10T 24/1604	. . Tighteners
Y10T 24/1608	. . Hinged
Y10T 24/1612	. . . Ring connected belt ends
Y10T 24/1616	. . . Bent over flanged ends
Y10T 24/162	. . . Pintle pin connected belt ends
Y10T 24/1624	. . . V and round belts
Y10T 24/1628	. . . Overlapped belt ends
Y10T 24/1632	. . . Sheet metal knuckles, common pintle

Y10T 24/1636	. . . Wire knuckles, common pintle
Y10T 24/164	. . . Knuckle integral with belt material
Y10T 24/1644	. . . Multiple pintles interconnected V-belt type
Y10T 24/1648	. . Lacing
Y10T 24/1652	. . One piece
Y10T 24/1656	. . . Deflecting prong
Y10T 24/166	. . Screw clamp
Y10T 24/1664	. . Splices
Y10T 24/1668	. . Wire
Y10T 24/1672	. . Butt connected belt ends
Y10T 24/1676	. . V, round, trapezoidal belts
Y10T 24/168	. . Flanged belt ends, connector hold ends
Y10T 24/1684	. . Lapped ends of endless belts
Y10T 24/1688	. . Hinged ends of endless belts
Y10T 24/1692	. . Wire strands reinforce belts
Y10T 24/1696	. . Hook and loop type fastener and zipper belt end connection
Y10T 24/17	. Buttoners
Y10T 24/18	. Cuff holder
Y10T 24/181	. . Adjustable
Y10T 24/183	. . Sleeve clasp and button for cuff
Y10T 24/184	. . Sleeve clasp and clasp for cuff
Y10T 24/185	. . Sleeve clasp and hook for cuff
Y10T 24/186	. . Sleeve clasp and pin for cuff
Y10T 24/188	. . Sleeve pin and button for cuff
Y10T 24/189	. . Pin fastener
Y10T 24/19	. Necktie fastener
Y10T 24/1903	. . Bands
Y10T 24/1907	. . . End-securing pin
Y10T 24/191	. . . Gripping
Y10T 24/1914	. . . Depressors
Y10T 24/1917 Button engaging
Y10T 24/1921 Pin or spur
Y10T 24/1924	. . Button engaging
Y10T 24/1928	. . . Adjustable
Y10T 24/1931	. . . Cord loop
Y10T 24/1934	. . . Pivoted or sliding jaw
Y10T 24/1938	. . . Pin attached
Y10T 24/1941	. . Collar button combined
Y10T 24/1945	. . . Clasp attached
Y10T 24/1948	. . . Pin attached

Y10T 24/1952	. . . Separable fastener
Y10T 24/1955	. . Tie, attached hook
Y10T 24/1959	. . Magnetic, adhesive, or snap type fastener connects tie to shirt
Y10T 24/1962	. . Tie engaging loop with shirt engaging fastener
Y10T 24/1966	. . Tie knot engaging and collar attaching
Y10T 24/1969	. . Tie clip and shirt clasp attaching
Y10T 24/1972	. . Tie clip and fastening pin
Y10T 24/1976	. . Tie pin with shirt fastener
Y10T 24/1979	. . Tie stiffener with shirt fastener
Y10T 24/1983	. . with pivotal jaws having spring means
Y10T 24/1986	. . Slider
Y10T 24/199	. . Ornamental
Y10T 24/1993	. . . Key shaped
Y10T 24/1997	. . Resilient clasp
Y10T 24/20	. Paper fastener
Y10T 24/201	. . with screw threaded or notch engaging securing means
Y10T 24/202	. . Resiliently biased
Y10T 24/203	. . . including means to open or close fastener
Y10T 24/204 Pivotaly mounted on pintle
Y10T 24/205	. . . One piece
Y10T 24/206 Mounted on support means
Y10T 24/207	. . Adhesive
Y10T 24/208	. . Corner fastened
Y10T 24/209	. . Paper-penetrating
Y10T 24/21	. Strap tighteners
Y10T 24/2102	. . Cam lever and loop
Y10T 24/2104	. . . Step adjusted
Y10T 24/2106 Ski boot and garment fasteners
Y10T 24/2108 Split ring tightener
Y10T 24/2109 Chain and rope tighteners
Y10T 24/2111 Tire chain tighteners
Y10T 24/2113 Strap tighteners
Y10T 24/2115 Jewelry
Y10T 24/2117	. . . Strap tighteners
Y10T 24/2119	. . . Tie chain tighteners
Y10T 24/2121	. . . Cargo tie down
Y10T 24/2123	. . . Cover fasteners
Y10T 24/2125	. . . Chain tighteners
Y10T 24/2126	. . . Strap tightener machine
Y10T 24/2128	. . . toggle actuated sliding jaw

Y10T 24/213	. . . Jewelry
Y10T 24/2132	. . . Split ring with tightener
Y10T 24/2134	. . . Concrete form panels
Y10T 24/2136	. . . Seat belt buckles
Y10T 24/2138	. . . Chain, cable, wire tighteners, and anchors
Y10T 24/214	. . . Envelope fasteners
Y10T 24/2142	. . . Ski boot and garment fasteners
Y10T 24/2143	. . Strap-attached folding lever
Y10T 24/2145	. . . toggle latch
Y10T 24/2147	. . . Strap tightener
Y10T 24/2149	. . . Tire antiskid strap tightener
Y10T 24/2151	. . . Seat belts
Y10T 24/2153	. . . Split ring fasteners
Y10T 24/2155	. . . Jewelry-watch straps
Y10T 24/2157	. . . Tie downs [covers, articles]
Y10T 24/2158	. . . Cable, wire, rope tightener
Y10T 24/216	. . . Ski boot and garment fasteners
Y10T 24/2162	. . . Dress hem raisers
Y10T 24/2164	. . Midline
Y10T 24/2166	. . Jewelry
Y10T 24/2168	. . Seat belt
Y10T 24/217	. . Accordion straps
Y10T 24/2172	. . Parallel poles clamp
Y10T 24/2174	. . form panels for walls
Y10T 24/2175	. . Cargo tie down
Y10T 24/2177	. . Chain tighteners
Y10T 24/2179	. . Split band with tightener
Y10T 24/2181	. . Tire chain tighteners
Y10T 24/2183	. . Ski, boot, and shoe fasteners
Y10T 24/2185	. . Fixed jaw with sliding or pivoted jaw
Y10T 24/2187	. . Rack and pinion and circular tighteners
Y10T 24/2189	. . Circular flange container clamp
Y10T 24/2191	. . Strap stretching tools, tighteners, and sealers
Y10T 24/2192	. . Buckle type
Y10T 24/2194	. . Integral piece
Y10T 24/2196	. . toggle
Y10T 24/2198	. . Stocking top
Y10T 24/22	. Trouser guards, clips, straps [e.g., above shoetops]
Y10T 24/23	. Bedclothes holders
Y10T 24/24	. T-head nongripping, fabric engaging type

Y10T 24/25	. Zipper or required component thereof
Y10T 24/2502	. . Plural zippers
Y10T 24/2504	. . . Zipper chain
Y10T 24/2505	. . . having surface sealing structure
Y10T 24/2507	. . having slider or interconnected sliders with access opening for diverse-art member
Y10T 24/2509	. . Plural independently movable sliders
Y10T 24/2511	. . with distinct, stationary means for anchoring slider
Y10T 24/2513	. . . and for aligning surfaces or obstructing slider movement
Y10T 24/2514	. . with distinct member for sealing surfaces
Y10T 24/2516	. . with distinct separable-fastener
Y10T 24/2518	. . having coiled or bent continuous wire interlocking surface
Y10T 24/252	. . . with stringer tape interwoven or knitted therewith
Y10T 24/2521	. . . with stringer tape having specific weave or knit pattern
Y10T 24/2523	. . . with core encircled by coils or bends
Y10T 24/2525	. . . with mounting portion having structural formations complementary to stitching
Y10T 24/2527	. . . Attached by stitching
Y10T 24/2529 String or stringer tape having distinctive property [e.g., heat sensitive]
Y10T 24/253	. . . with stringer tape having distinctive property [e.g., heat sensitive]
Y10T 24/2532	. . having interlocking surface with continuous cross section
Y10T 24/2534	. . . Opposed interlocking surface having dissimilar cross section
Y10T 24/2536	. . having interlocking surface formed from single member with varying cross section
Y10T 24/2538	. . . Opposed surface having dissimilar cross section
Y10T 24/2539	. . Interlocking surface constructed from plural elements in series
Y10T 24/2541	. . . having either noninterlocking element in, interrupted, or unequal length series
Y10T 24/2543	. . . with element structural feature unrelated to interlocking or securing portion
Y10T 24/2545	. . . Dissimilar opposed elements
Y10T 24/2546	. . . Wire element
Y10T 24/2548	. . . Preattached to mounting cord
Y10T 24/255	. . . having interlocking portion with specific shape
Y10T 24/2552 including symmetrical formations on opposite walls for engaging mating elements
Y10T 24/2554 including complementary formations on opposite walls for engaging mating elements
Y10T 24/2555 Mating elements having reversed orientation of formations
Y10T 24/2557	. . . having mounting portion with specific shape or structure
Y10T 24/2559 including embracing jaws
Y10T 24/2561	. . Slider having specific configuration, construction, adaptation, or material
Y10T 24/2563	. . . including relatively movable spaced wings [i.e., restraining walls]
Y10T 24/2564	. . . including converging channel and relatively movable separator island
Y10T 24/2566	. . . including position locking-means attached thereto

- Y10T 24/2568 Protrusion on pull tab directly engaging interlocking surfaces
- Y10T 24/257 having surface engaging element shifted by reorientation of pull tab
- Y10T 24/2571 Resilient or spring biased element
- Y10T 24/2573 Selectively shifted by either of two pull tabs
- Y10T 24/2575 with relatively movable link
- Y10T 24/2577 Biased by distinct spring
- Y10T 24/2579 having aperture cooperating with guide post
- Y10T 24/258 . . . including means preventing bunching of structure-to-be-secured or stringer
- Y10T 24/2582 . . . having specific contour or arrangement of converging channel, separator island, or wing
- Y10T 24/2584 Spaced segments of each wall of channel supported by different wings
- Y10T 24/2586 . . . including pull tab attaching means
- Y10T 24/2588 . . . including means for attaching components of slider together
- Y10T 24/2589 . . . with ornamental slider
- Y10T 24/2591 . . with means for concealing surfaces
- Y10T 24/2593 . . including complementary, aligning means attached to ends of interlocking surfaces
- Y10T 24/2595 . . . having specific mounting connection or reinforcing structure at connection
- Y10T 24/2596 . . including means attaching interlocking surfaces together
- Y10T 24/2598 . . including means for obstructing movement of slider
- Y10T 24/26 . . Slit closing means including guides on opposite edges of slit and slidable bridging component
- Y10T 24/262 . . with hand-actuated lever for shifting bridging component
- Y10T 24/264 . . including structure linking and allowing variations in separation between opposite-guide-contacting portions of component
- Y10T 24/266 . . having bridging components attached in series along carrying element
- Y10T 24/268 . . having separate, independently movable, bridging components
- Y10T 24/27 . . including readily dissociable fastener having numerous, protruding, unitary filaments randomly interlocking with, and simultaneously moving towards, mating structure [e.g., hook-loop type fastener]
- Y10T 24/2708 . . Combined with diverse fastener
- Y10T 24/2717 . . with distinct structure for sealing securement joint
- Y10T 24/2725 . . with feature facilitating, enhancing, or causing attachment of filament mounting surface to support therefor
- Y10T 24/2733 . . having filaments formed from continuous element interwoven or knitted into distinct, mounting surface fabric
- Y10T 24/2742 . . having filaments of varied shape or size on same mounting surface
- Y10T 24/275 . . with feature facilitating or causing attachment of filaments to mounting surface
- Y10T 24/2758 . . . Thermal or adhesive
- Y10T 24/2767 . . having several, repeating, interlocking formations along length of filaments
- Y10T 24/2775 . . having opposed structure formed from distinct filaments of diverse shape to those mating therewith
- Y10T 24/2783 . . having filaments constructed from coated, laminated, or composite material

Y10T 24/2792	. . having mounting surface and filaments constructed from common piece of material
Y10T 24/28	. Freight container to freight container fastener
Y10T 24/29	. Drum or can spacer fastener
Y10T 24/30	. Trim molding fastener
Y10T 24/301	. . having externally threaded attaching means
Y10T 24/302	. . . and laterally extending biasing appendage
Y10T 24/303	. . having laterally extending biasing appendage
Y10T 24/304	. . Resilient metal type
Y10T 24/306	. . . Strip formed
Y10T 24/307	. . . Sheet metal formed
Y10T 24/308	. . . Wire formed
Y10T 24/309	. . Plastic type
Y10T 24/31	. Plural fasteners having intermediate flaccid connector
Y10T 24/312	. . Chain connector
Y10T 24/314	. . Elastic connector
Y10T 24/316	. . . Strap connector
Y10T 24/318	. . Strap connector
Y10T 24/32	. having magnetic fastener
Y10T 24/33	. having adhesive fastener
Y10T 24/34	. Combined diverse multipart fasteners
Y10T 24/3401	. . Buckle
Y10T 24/3403	. . . and buckles
Y10T 24/3404 having separate material adjustment means
Y10T 24/3405 having separate disconnect means
Y10T 24/3407 Pivotal lever type
Y10T 24/3408 having disconnect structure
Y10T 24/3409 Resilient cooperating means
Y10T 24/3411 and pin
Y10T 24/3412 Crossed belt accommodating
Y10T 24/3413	. . . and clasp
Y10T 24/3415	. . . and pin
Y10T 24/3416	. . . and hook
Y10T 24/3417 having disconnect means
Y10T 24/3419 having penetrating prong
Y10T 24/342 Buckle having plural receiving slots
Y10T 24/3421	. . . including a button fastening element
Y10T 24/3423	. . . and separable fastening means for attached fastener
Y10T 24/3424 Snap fastener
Y10T 24/3425	. . . having roller means
Y10T 24/3427	. . Clasp

Y10T 24/3428	. . .	having pivoted members
Y10T 24/3429	Cam type member
Y10T 24/3431	Plural clasps
Y10T 24/3432	and toggle operator
Y10T 24/3433	Spring biased
Y10T 24/3435	Coil
Y10T 24/3436	and cam
Y10T 24/3437	Coil spring biased
Y10T 24/3439	. . .	Plural clasps
Y10T 24/344	Resilient type clasp
Y10T 24/3441	and cam
Y10T 24/3443	Spring biased jaw
Y10T 24/3444	Circular work engageable
Y10T 24/3445	and pin attachment
Y10T 24/3447	and disconnect means
Y10T 24/3448	. . .	including a button fastening element
Y10T 24/3449	. . .	and hook
Y10T 24/3451	having intermediate connector allowing movement
Y10T 24/3452	and adjustment means
Y10T 24/3453	having gripping configuration on clasp jaw
Y10T 24/3455	Penetrating type
Y10T 24/3456	having cam
Y10T 24/3457	having separable jaws
Y10T 24/3459	. . .	and penetrating prong
Y10T 24/346	. . .	and pin
Y10T 24/3461	having separate pin loss prevention means
Y10T 24/3463	Pin coextensive, coplanar, and contiguous with clasp jaw
Y10T 24/3464	Pin coextensive, coplanar, and contiguous with clasp jaw
Y10T 24/3465	Pin forms part of clasp jaw
Y10T 24/3467	. .	Pin
Y10T 24/3468	. . .	and pin
Y10T 24/3469	and disconnect means
Y10T 24/3471	Hook and eye type
Y10T 24/3472	and hook
Y10T 24/3473	having connector allowing movement
Y10T 24/3475	having intermediate connector allowing movement
Y10T 24/3476	. . .	and hook
Y10T 24/3477	having intermediate connector allowing movement
Y10T 24/3479	and adjustment means
Y10T 24/348	Hook having locking means

Y10T 24/3481	. . . including a button fastening element
Y10T 24/3483	. . . and penetrating prong
Y10T 24/3484	. . Hook
Y10T 24/3485	. . . and hook
Y10T 24/3487 having biasing spring
Y10T 24/3488 Separately connected
Y10T 24/3489 having securing means
Y10T 24/3491 Sliding
Y10T 24/3492 Snap type
Y10T 24/3493 Pivoted
Y10T 24/3495	. . . having penetrating prong
Y10T 24/3496	. . . including a button fastening element
Y10T 24/3497	. . Button fastening element including another fastener element
Y10T 24/3499	. . Penetrating prong
Y10T 24/35	. Interchangeable button loop and pin
Y10T 24/36	. Button with fastener
Y10T 24/3602	. . Loss-preventing devices
Y10T 24/3604	. . Adjustable
Y10T 24/3606	. . Cloth shanks and covers
Y10T 24/3609	. . Multiple attachment
Y10T 24/3611	. . Deflecting prong or rivet
Y10T 24/3613	. . . Anvil or plate
Y10T 24/3615	. . . Integral
Y10T 24/3617	. . Hinged leaf
Y10T 24/3619	. . . Axially rotating
Y10T 24/3621	. . . Double
Y10T 24/3623	. . . Sliding
Y10T 24/3626	. . Sliding bar
Y10T 24/3628	. . Integral or rigid stud
Y10T 24/363	. . . Bent sheet metal [integral]
Y10T 24/3632	. . Link
Y10T 24/3634	. . . Integral rubber button, extendable shank
Y10T 24/3636	. . . Extendably connected
Y10T 24/3638	. . . Pivoted leaf
Y10T 24/364	. . . Releasably locked
Y10T 24/3643	. . . French cuff
Y10T 24/3645	. . . Tufting
Y10T 24/3647	. . . Integral piece
Y10T 24/3649	. . Pin attached
Y10T 24/3651	. . Separable

Y10T 24/3653	. . . Screw
Y10T 24/3655	. . . Spring
Y10T 24/3657 Resilient head
Y10T 24/366 Resilient socket
Y10T 24/3662 Rotating head
Y10T 24/3664 with operating devices
Y10T 24/3666	. . Separate thread bar
Y10T 24/3668	. . Spiral fastener
Y10T 24/367	. . Covers
Y10T 24/3672	. . . Metal or plastic caps
Y10T 24/3674	. . Pads
Y10T 24/3677	. . Flexible button
Y10T 24/3679	. . Swivel button
Y10T 24/3681	. . Tufting type
Y10T 24/3683	. . Button with cavity for friction grip fastener
Y10T 24/3685	. . Button with shank for friction grip fastener
Y10T 24/3687	. . Heat or adhesive secured type
Y10T 24/3689	. . Thread or wire through apertured button
Y10T 24/3691	. . Eye shank type button
Y10T 24/3694	. . Ornamental type
Y10T 24/3696	. . for cuff or collar
Y10T 24/3698	. . Fabric embracing
Y10T 24/37	. Drawstring, laced-fastener, or separate essential cooperating device therefor
Y10T 24/3703	. . Includes separate device for holding drawn portion of lacing
Y10T 24/3705	. . . Device engages tie in lacing
Y10T 24/3708 and fully covers tie
Y10T 24/3711	. . . Device engages element or formation on lacing
Y10T 24/3713	. . . having relatively movable holding components or surfaces
Y10T 24/3716 with pivotal connection therebetween
Y10T 24/3718 with integral resilient linking structure therebetween
Y10T 24/3721 formed from wire
Y10T 24/3724	. . . having lacing wound thereabout or wedged therein
Y10T 24/3726	. . with holding means fixedly mounted on lacing
Y10T 24/3729	. . . and forming lacing tips
Y10T 24/3732	. . Includes lacing holding structure within directing means therefor
Y10T 24/3734	. . having diverse shaped directing means for lacing
Y10T 24/3737	. . having lacing directing means in particular pattern
Y10T 24/3739	. . Includes lacing guiding roller within directing means
Y10T 24/3742	. . having eyelet type directing means
Y10T 24/3745	. . . with permanently deformed mounting structure

Y10T 24/3747 Mounting structure formed from different material than directing passage
Y10T 24/375	. . having hook shaped directing means
Y10T 24/3753	. . . and movable component or surface for closing throat
Y10T 24/3755	. . . Mounted by structure allowing bodily movement thereof
Y10T 24/3758	. . . formed from wire
Y10T 24/3761	. . . with mounting structure formed from different material
Y10T 24/3763	. . . with permanently deformed mounting structure
Y10T 24/3766 Expanding stud
Y10T 24/3768	. . having loop or sleeve shaped directing means
Y10T 24/3771	. . . Entirely formed from flaccid material
Y10T 24/3774	. . . Mounted by structure allowing bodily movement thereof
Y10T 24/3776	. . . formed from wire
Y10T 24/3779	. . . with permanently deformed mounting structure
Y10T 24/3782 Loop or sleeve closed when mounted
Y10T 24/3784 Expanding stud
Y10T 24/3787	. . having elastic segment in lacing
Y10T 24/3789	. . having means covering tip of lacing
Y10T 24/3792	. . . Tasseled
Y10T 24/3795	. . . with plural components
Y10T 24/3797	. . . with permanently deformed mounting structure
Y10T 24/38	. Strap cable or pipe button
Y10T 24/39	. Cord and rope holders
Y10T 24/3902	. . Chain
Y10T 24/3904	. . . Bead chain fasteners
Y10T 24/3907	. . Sheathed strand
Y10T 24/3909	. . Plural-strand cord or rope
Y10T 24/3911	. . Friction disk
Y10T 24/3913	. . Knot engaging
Y10T 24/3916	. . One-piece
Y10T 24/3918	. . . Wedge slot
Y10T 24/392	. . . Wire
Y10T 24/3922 Cord runs through center of coil
Y10T 24/3924	. . . Sheet material
Y10T 24/3927	. . . Slack adjuster
Y10T 24/3929	. . . Rubber
Y10T 24/3931	. . . Wire
Y10T 24/3933	. . . Swagged, deformable
Y10T 24/3936	. . Pivoted part
Y10T 24/3938	. . . Lever tension
Y10T 24/394	. . . Cam lever

Y10T 24/3942 Laterally shifted rope
Y10T 24/3944 Cam engaging or disengaging
Y10T 24/3947 Fixed and movable jaws, movable jaw pulled
Y10T 24/3949 Link-connected parallel jaws
Y10T 24/3951 Dual cam
Y10T 24/3953	. . . Pivotal means with plate aperture
Y10T 24/3956	. . . Jaws locked together by cam, wedge, lever, or screw
Y10T 24/3958	. . Screw clamp
Y10T 24/396	. . . Screw clamp with snubber
Y10T 24/3962	. . . Tangential bolt
Y10T 24/3964	. . . J-shaped bolt
Y10T 24/3967	. . . Bolt perpendicular to cable axis
Y10T 24/3969	. . Sliding part or wedge
Y10T 24/3971	. . . Rope looped about movable member
Y10T 24/3973	. . . Rope clamped between cone and socket
Y10T 24/3976	. . . Sliding ball
Y10T 24/3978	. . . Screw actuated
Y10T 24/398	. . Bendable, ductible
Y10T 24/3982	. . Safety release
Y10T 24/3984	. . Alignable aperture and spring pressed moving element
Y10T 24/3987	. . Loop, adjustable
Y10T 24/3989	. . Snubbers, cleats by dielectric loss
Y10T 24/3991	. . Loop engaging
Y10T 24/3993	. . Ball or roller
Y10T 24/3996	. . Sliding wedge
Y10T 24/3998	. . Helical preform
Y10T 24/40	. Buckles
Y10T 24/4002	. . Harness
Y10T 24/4005	. . . Combined buckles and snap hooks
Y10T 24/4007	. . . Lock
Y10T 24/4009 Key
Y10T 24/4012	. . . Clamping
Y10T 24/4014 One-piece
Y10T 24/4016 Pivoted part or lever
Y10T 24/4019 Sliding part or wedge
Y10T 24/4021	. . . Cross bails
Y10T 24/4023 Pivoted stud plate
Y10T 24/4026 Rigid stud
Y10T 24/4028	. . . Penetrating tongue
Y10T 24/403 Guarded

Y10T 24/4033 One-piece
Y10T 24/4035 Multiple
Y10T 24/4037 Pivoted
Y10T 24/404 Lever actuated
Y10T 24/4042 Stud
Y10T 24/4044 Sliding part or wedge
Y10T 24/4047	. . . Strap loops and attaching devices
Y10T 24/4049	. . . Loop shields
Y10T 24/4051	. . Garment shielded
Y10T 24/4053	. . Combined pressure bar and guard
Y10T 24/4056	. . . Hook attached
Y10T 24/4058	. . Penetrating prong
Y10T 24/406	. . . One-piece
Y10T 24/4063 Hook attached
Y10T 24/4065	. . . Pivoted
Y10T 24/4067 Hook attached
Y10T 24/407	. . . Slide
Y10T 24/4072	. . Pivoted lever
Y10T 24/4074	. . . Hook attached
Y10T 24/4077	. . . Looped strap
Y10T 24/4079	. . Sliding part of wedge
Y10T 24/4081	. . . Hook attached
Y10T 24/4084	. . . Looped strap
Y10T 24/4086	. . Looped strap
Y10T 24/4088	. . One-piece
Y10T 24/4091	. . . Hook attached
Y10T 24/4093	. . . Looped strap
Y10T 24/4095	. . Fabric covered
Y10T 24/4098	. . Ornamental and/or object supported
Y10T 24/41	. Pierced earring fastener
Y10T 24/42	. Independent, headed, aperture pass-through fastener
Y10T 24/43	. Fastener with revolving component wrapping structure-to-be-secured about fastener
Y10T 24/44	. Clasp, clip, support-clamp, or required component thereof
Y10T 24/44009	. . Gripping member adapted for tool actuation or release
Y10T 24/44017	. . with specific mounting means for attaching to rigid or semirigid supporting structure or structure-to-be-secured
Y10T 24/44026	. . . for cooperating with aperture in supporting structure or structure-to-be-secured
Y10T 24/44034	. . Dissociable gripping members
Y10T 24/44043	. . . Channel and inserted bar
Y10T 24/44051 having operator or locking means

Y10T 24/4406 Resilient channel or bar
Y10T 24/44068	. . having gripping member actuated by fluid force
Y10T 24/44077	. . having inserted and receiving interlocking members connected by bendable, nonbiasing strap
Y10T 24/44085	. . . Discrete flaccid strap
Y10T 24/44094 with distinct means for preventing separation of members
Y10T 24/44103 Slidably mounted
Y10T 24/44111 with separate flaccid flap or pocket for protecting structure-to-be-secured
Y10T 24/4412 with separate, cavity-blocking gate on receiving member
Y10T 24/44128 Resilient inserted or receiving member
Y10T 24/44137 Inserted or receiving member substantially covered or coated for protection or to promote gripping
Y10T 24/44145 Resilient inserted member
Y10T 24/44154 having engaging face formed from nonmetallic material
Y10T 24/44162 having head and neck type engaging face
Y10T 24/44171 having internal supporting or reinforcing element
Y10T 24/44179 Circular head or neck
Y10T 24/44188 having wedge shaped, inserted and receiving members
Y10T 24/44197 with specific means for attaching to flaccid strap or supporting strap
Y10T 24/44205 On the inserted member
Y10T 24/44214 having necked button sliding along length of closed, variable width loop
Y10T 24/44222	. . having flaccid gripping member
Y10T 24/44231	. . . formed from elastic material
Y10T 24/44239	. . Encircling gripping member including semirigid band and operator for tightening
Y10T 24/44248	. . Encircling gripping member including semirigid band and means for adjusting girth
Y10T 24/44256	. . with specifically shaped, nongripping, rigid structure for connecting independently operable clasps, clips, or support-clamps
Y10T 24/44265	. . Gripping member face integral with or rigidly affixed to screw-driving portion
Y10T 24/44274	. . having either discrete flaccid or thin, nonbiasing, integral, connecting hinge
Y10T 24/44282	. . having equally spaced or continual gripping faces revolving about central axis
Y10T 24/44291	. . including pivoted gripping member
Y10T 24/44299	. . . Pivoted member also slides
Y10T 24/44308 Tapered face
Y10T 24/44316	. . . Pivoting gripping member either supports or coacts with sliding engaging face
Y10T 24/44325	. . . having three or more pivotally connected gripping members
Y10T 24/44333	. . . having toggle operator for moving
Y10T 24/44342	. . . having rigid linking arm pivotally connected to each gripping member
Y10T 24/4435 with extended lever portion
Y10T 24/44359 having lever end modified for attachment to support
Y10T 24/44368	. . . Pivoted gripping member applies camming force
Y10T 24/44376	. . . Spring or resiliently biased about pivot

Y10T 24/44385 Distinct spring
Y10T 24/44393 Attached solely by spring
Y10T 24/44402 with operator for moving pivoted member
Y10T 24/4441 Camming or wedging element
Y10T 24/44419 Pivoted or rotated element
Y10T 24/44427 with position locking-means for gripping members
Y10T 24/44436 including pivoted arm
Y10T 24/44444 having specific surface material or irregularity on or along engaging face
Y10T 24/44453 having specific handle structure
Y10T 24/44462 Coil spring
Y10T 24/4447 having coil portion coaxial or parallel with pivotal axis
Y10T 24/44479 Flat or leaf spring
Y10T 24/44487	. . . Closed by gravity or weight of structure-to-be-secured
Y10T 24/44496	. . . with operator means for moving pivoted member
Y10T 24/44504 Threaded cylindrical rod and mating cavity
Y10T 24/44513 Camming or wedging element
Y10T 24/44521 Pivoted or rotated element
Y10T 24/4453	. . . with position locking-means for gripping members
Y10T 24/44538 Integral locking-means
Y10T 24/44547	. . . having inserted and receiving interlocking engaging faces
Y10T 24/44556 Resilient gripping member
Y10T 24/44564	. . . having specific surface material or irregularity on or along engaging face
Y10T 24/44573	. . including track or way guided and retained gripping member
Y10T 24/44581	. . . Biased by distinct spring
Y10T 24/4459	. . . with operator for moving guided member
Y10T 24/44598 Threaded cylindrical rod and mating cavity
Y10T 24/44607	. . . Track or way oblique to path of gripping member
Y10T 24/44615	. . . with position locking-means for gripping members
Y10T 24/44624 Integral locking-means
Y10T 24/44632	. . . with specific mounting means for attaching to flaccid supporting structure or structure-to-be-secured
Y10T 24/44641	. . having gripping member formed from, biased by, or mounted on resilient member
Y10T 24/4465	. . . Integrally combined, independently operable, diverse clasps, clips, or support-clamps
Y10T 24/44658	. . . with specific means for mounting to flaccid supporting structure or structure-to-be-secured
Y10T 24/44667 Mounting means made entirely from integral wire portion of resilient gripping member
Y10T 24/44675 Wire coiled about flaccid supporting structure
Y10T 24/44684	. . . with operator for moving biased engaging face
Y10T 24/44692 Camming or wedging element

Y10T 24/44701	Encircling sleeve type element
Y10T 24/44709	Pivoted or rotated element
Y10T 24/44718	Element pivots or rotates in plane parallel to plane bisecting opposed engaging faces
Y10T 24/44726	Elongated element with pivot between cam and handle portions
Y10T 24/44735	for moving engaging face of U-shaped gripping member
Y10T 24/44744	with position locking-means for engaging faces
Y10T 24/44752	Integral locking-means
Y10T 24/44761	Pivoted lock member
Y10T 24/44769	Opposed engaging faces on gripping member formed from single piece of resilient material
Y10T 24/44778	Piece totally forms clasp, clip, or support-clamp and has shaped, wirelike, or bandlike configuration with uniform cross section throughout its length
Y10T 24/44786	Opposed faces located in and bias towards common plane in nonuse position
Y10T 24/44795	Resilient gripping member having tightly twisted portion
Y10T 24/44803	Resilient gripping member having coiled portion
Y10T 24/44812	Convolutions of coil form faces
Y10T 24/44821	Relatively movable segments of resilient gripping member contact and cross in nonuse position
Y10T 24/44829	Segments form opposed engaging faces
Y10T 24/44838	having specific handle structure
Y10T 24/44846	having specific handle structure
Y10T 24/44855	Terminal end of resilient member having engagement or disengagement enhancing structural modifications
Y10T 24/44863	having specific surface irregularity on or along engaging face
Y10T 24/44872	having specific handle structure
Y10T 24/4488	Movably attached to gripping member
Y10T 24/44889	Interlocking faces
Y10T 24/44897	with reinforcing member
Y10T 24/44906	having specific surface irregularity on or along engaging face
Y10T 24/44915	Corrugated or toothed face
Y10T 24/44923	Clasp, clip, or support-clamp cut or shaped from a single sheet of resilient, uniformly thick, planar material
Y10T 24/44932	having specific surface material or irregularity on or along engaging face
Y10T 24/4494	having specific handle structure
Y10T 24/44949	including resilient biasing wire
Y10T 24/44957	Coiled wire
Y10T 24/44966	having gripping member shifted by operator
Y10T 24/44974	Threaded cylindrical rod and mating cavity
Y10T 24/44983	formed from single rigid piece of material
Y10T 24/44991	having specific surface irregularity on or along engaging face

Y10T 24/45	. Separable-fastener or required component thereof [e.g., projection and cavity to complete interlock]
Y10T 24/45005	. . with third detached member completing interlock [e.g., hook type]
Y10T 24/4501	. . . Quick connect or release [e.g., spring and detent]
Y10T 24/45016	. . . for jewelry
Y10T 24/45021	. . . including eyelet [e.g., shoes]
Y10T 24/45026	. . . for key holder
Y10T 24/45031	. . . for tire chain, strap, etc. [e.g., rotatable or sliding spring gate]
Y10T 24/45037	. . . for apparel and related accessories
Y10T 24/45042 Button, button related
Y10T 24/45047 Snap [e.g., key hole type]
Y10T 24/45052 Post and receiver [e.g., pin and slot]
Y10T 24/45058 Hook [e.g., within cavity]
Y10T 24/45063 Belt, strap, etc. [e.g., buckle or snap fastener]
Y10T 24/45068 Glove
Y10T 24/45073 Purse, wallet, etc.
Y10T 24/45079 Belt, strap, harness, etc.
Y10T 24/45084 for safety belt buckle, strap, harness, etc.
Y10T 24/45089 Sliding or rotating element
Y10T 24/45094 Element having key slot
Y10T 24/45099 Resilient element [e.g., snap type]
Y10T 24/45105 for upholstery, panel, trim strip, etc. [e.g., spring biased]
Y10T 24/4511 Link with pivoted gate
Y10T 24/45115 Hook
Y10T 24/4512 Snap with spring bias [e.g., gate]
Y10T 24/45126 for connecting chains [e.g., opposed pivoted hook]
Y10T 24/45131 for heavy load bearing device [e.g., chain, rope, cable, etc.]
Y10T 24/45136 Haim, harness, whiffletree, rein, etc.
Y10T 24/45141 for chain, rope, cable, etc.
Y10T 24/45147 Coupler with sliding socket to complete interlock
Y10T 24/45152	. . Each mating member having similarly shaped, sized, and operated interlocking or intermeshable face
Y10T 24/45157	. . . Zipper-type [e.g., slider]
Y10T 24/45162 for garment [e.g., with ribs and grooves interlocking elements]
Y10T 24/45168 for container [e.g., bag]
Y10T 24/45173	. . . Resilient element
Y10T 24/45178 Snap [e.g., identical elements]
Y10T 24/45183	. . . Clasp [e.g., spring type]
Y10T 24/45188 for jewelry [e.g., buckle type]
Y10T 24/45194 for belt or strap

Y10T 24/45199	. . .	Hook
Y10T 24/45204	for belt, strap, etc. [e.g., with pivoted gate locking member]
Y10T 24/45209	for apparel
Y10T 24/45215	. . .	Slot and tab or tongue
Y10T 24/4522	. . .	Sliding or rotating element
Y10T 24/45225	. .	including member having distinct formations and mating member selectively interlocking therewith
Y10T 24/4523	. . .	Hook
Y10T 24/45236	Multiple catch [e.g., with pivoted gate]
Y10T 24/45241	. . .	Slot and tab or tongue
Y10T 24/45246	having teeth or serrations [e.g., sliding with respect to each other]
Y10T 24/45251	. . .	Resilient element [e.g., with spring]
Y10T 24/45257	Snap with cavity
Y10T 24/45262	. . .	Pin, post and receiver
Y10T 24/45267	. . .	Notched clasp [e.g., with receiving slot]
Y10T 24/45272	. . .	Projection passes through cavity then moves toward noninserted portion of its member to complete interlock [e.g., snap hook]
Y10T 24/45277	Entire projection member forms loop or ring when interlocked
Y10T 24/45283	Includes slidable gate closing entrance throat
Y10T 24/45288	Hook type projection member
Y10T 24/45293	Plural hooks entering opposite sides of same cavity
Y10T 24/45298	Hooks formed solely from wire
Y10T 24/45304	Noninserted portion of projection member includes movably connected gate for closing access throat
Y10T 24/45309	Threaded gate
Y10T 24/45314	Revolvably mounted disc shaped gate
Y10T 24/45319	Pivotally connected gate
Y10T 24/45325	Gate swings transversely to plane of hook
Y10T 24/4533	Gate also slides relative to pivot
Y10T 24/45335	having means biasing gate about pivot
Y10T 24/4534	and position locking-means for gate
Y10T 24/45346	Includes distinct biasing spring
Y10T 24/45351	Coil type spring
Y10T 24/45356	Coiled about pivotal axis of gate
Y10T 24/45361	having position locking-means for gate
Y10T 24/45366	Locking-means pivotally connected
Y10T 24/45372	Locking-means slidably mounted
Y10T 24/45377	Gate closes when structure-to-be-secured is tensioned
Y10T 24/45382	Track or way guided gate
Y10T 24/45387	having means biasing gate
Y10T 24/45393	Guide of gate encircles shank

Y10T 24/45398	Cavity in shank forms track or way
Y10T 24/45403	with position locking-means for gate
Y10T 24/45408	Resilient, self-biased gate
Y10T 24/45414	with position locking-means for gate
Y10T 24/45419	Gate and hook formed from plastic
Y10T 24/45424	Gate and hook formed solely from wire
Y10T 24/45429	Gate and hook formed from single piece of sheet metal
Y10T 24/45435	Projection pivotally attached to shank or mounting structure
Y10T 24/4544	Projection slidably mounted to shank or mounting structure
Y10T 24/45445	Projection self-biased towards shank or mounting structure
Y10T 24/4545	and formed solely from wire
Y10T 24/45455	Cooperating with relatively stationary wire gate
Y10T 24/45461	. . .	Interlocking portion actuated or released responsive to preselected condition [e.g., heat, pressure]
Y10T 24/45466	. . .	having electric or fluid powered, actuation or release, of interlock
Y10T 24/45471	. . .	Projection having movable connection between components thereof or variable configuration
Y10T 24/45476	with additional, similar projection for engaging different cavity
Y10T 24/45482	and operator therefor
Y10T 24/45487	including camming or wedging element on projection member
Y10T 24/45492	Pivotally attached element
Y10T 24/45497	including pivotal connection between projection components
Y10T 24/45503	Component slides relative to connection
Y10T 24/45508	and spring or resilient extension biasing about pivot
Y10T 24/45513	including slidably guided connection between nonself-biasing projection components
Y10T 24/45518	and distinct spring biasing component
Y10T 24/45524	including resiliently biased projection component or surface segment
Y10T 24/45529	Requiring manual force applied against bias to interlock or disengage
Y10T 24/45534	having connected leading edge and separated trailing arms
Y10T 24/45539	Cooperating with cavity having side walls and axially biased component capping end
Y10T 24/45545	forming total external surface of projection
Y10T 24/4555	and encircling hollow central area
Y10T 24/45555	having separate mounting means inserted into area
Y10T 24/4556	Plastic deformation of means or surface required for mounting
Y10T 24/45565	having separate mounting means encompassing cross section of projection
Y10T 24/45571	having dome-shaped head and expansion slit along side
Y10T 24/45576	and connected surface at tip of head
Y10T 24/45581	having inserted end formed by oppositely biased surface segments

Y10T 24/45586	Constructed from wire
Y10T 24/45592	having both resiliently biased and rigid components forming external surface of projection
Y10T 24/45597	. . .	Projection member including noninserted spring for engaging and pushing against receiving member
Y10T 24/45602	. . .	Receiving member includes either movable connection between interlocking components or variable configuration cavity
Y10T 24/45607	with additional cavity for engaging different projection
Y10T 24/45613	having common means actuating or releasing interlocking components or surfaces
Y10T 24/45618	and interlocking with independently associated or dissociated projection members
Y10T 24/45623	and operator therefor
Y10T 24/45628	for plural, oppositely shifting, similar interlocking components or segments
Y10T 24/45634	Operator includes camming or wedging element
Y10T 24/45639	including pivotally connected element on receiving member
Y10T 24/45644	for shifting pivotally connected interlocking component
Y10T 24/45649 Element and component pivot about same axis
Y10T 24/45654	for shifting slidably connected and guided, nonself-biasing interlocking component
Y10T 24/4566	including slidably connected and guided element on receiving member
Y10T 24/45665	for shifting pivotally connected interlocking component
Y10T 24/4567	for shifting slidably connected and guided, nonself-biasing, interlocking component
Y10T 24/45675	having pivotally connected interlocking component
Y10T 24/45681	Blocking removal of formation on projection from complementary formation on side wall of cavity
Y10T 24/45686	and position locking-means therefor
Y10T 24/45691	and relatively movable handle therefor
Y10T 24/45696	Requiring manual force thereon to interlock or disengage
Y10T 24/45702	Plural, oppositely shifting, similar interlocking components
Y10T 24/45707	having aperture therein alignable with parallel access opening
Y10T 24/45712	having interlocking portion thereof housed continuously within cavity
Y10T 24/45717	having cavity with side walls and axially biased component capping end
Y10T 24/45723	having slidably connected, nonself-biasing interlocking component
Y10T 24/45728	Blocking removal of formation on projection from complementary formation on side wall of cavity
Y10T 24/45733	and position locking-means therefor
Y10T 24/45738	and relatively movable handle therefor
Y10T 24/45743	Requiring manual force thereon to interlock or disengage
Y10T 24/45749	Plural, oppositely shifting, similar interlocking components

Y10T 24/45754	having closed aperture therethrough alignable with parallel access opening
Y10T 24/45759	having flaccid component defining access opening of cavity
Y10T 24/45764	Component formed solely by flaccid cord
Y10T 24/4577	with nonflaccid component
Y10T 24/45775	having resiliently biased interlocking component or segment
Y10T 24/4578	Cavity or projection rotates about axis of cavity to dissociate
Y10T 24/45785	Requiring manual force applied against bias to interlock or disengage
Y10T 24/45791	and partially blocking separate, nonresilient access opening of cavity
Y10T 24/45796	and closed elongated access opening for guiding transverse projection travel after insertion
Y10T 24/45801	Nonresilient walls define opening
Y10T 24/45806	formed from wire
Y10T 24/45812	and access opening with gapped perimeter for allowing movement of noninserted projection support therepast
Y10T 24/45817	Cavity constructed solely from wire
Y10T 24/45822	Partially blocking separate, nonresilient, access opening of cavity
Y10T 24/45827	and bodily shifted into or out of interlock location by manual force thereon
Y10T 24/45832	formed from wire
Y10T 24/45838	having curved or bent engaging section conforming to contour of projection
Y10T 24/45843	Similar, distinct sections
Y10T 24/45848	having distinct sections engaging projection at spaced points
Y10T 24/45853	including separate, nonprojection-engaging spring for biasing
Y10T 24/45859	Biased component or segment entirely formed from wire
Y10T 24/45864	having portion of cavity deformed during mounting
Y10T 24/45869	and cooperating with separate mounting component
Y10T 24/45874	having axially extending expansion slit along side of cavity
Y10T 24/4588	Means for mounting projection or cavity portion
Y10T 24/45885	Allows bodily movement facilitating interlock
Y10T 24/4589	About pivotal connection
Y10T 24/45895	Includes resilient component separate from portion
Y10T 24/45901	Allows relocation of portion
Y10T 24/45906	having component of means permanently deformed during mounting operation
Y10T 24/45911	and formed from or fixedly attached to projection or cavity portion
Y10T 24/45916	Cooperates with detached component of means
Y10T 24/45921	having shape facilitating impaling of mounting surface
Y10T 24/45927	and inserted into or through cavity or projection
Y10T 24/45932	and encircling cavity or projection
Y10T 24/45937	Consisting of thermally fusible substance

Y10T 24/45942	having threaded formation
Y10T 24/45948	having specific structure for cooperating with stitching
Y10T 24/45953	having shape facilitating impaling of mounting surface
Y10T 24/45958	. . .	Plural distinct cavities or projections
Y10T 24/45963	Hook type
Y10T 24/45969	. . .	Hook-shaped projection member passing through cavity
Y10T 24/45974	formed from single piece of sheet metal
Y10T 24/45979	formed solely from wire
Y10T 24/45984	. . .	Cavity having specific shape
Y10T 24/4599	including closed elongated access opening for guiding transverse projection travel after insertion
Y10T 24/45995	having access opening with gapped perimeter for allowing movement of noninserted projection support therepast
Y10T 24/46	. .	Pin or separate essential cooperating device therefor
Y10T 24/4602	. .	with separately operable, manually releasable, nonpenetrating means for mounting [e.g., drapery hook]
Y10T 24/4604	. .	having distinct guiding, holding, or protecting means for penetrated portion
Y10T 24/4605	. . .	Means detachable from or flaccidly connected to pin [e.g., hatpin type]
Y10T 24/4607	for pin having plural penetrating portions
Y10T 24/4609	including relatively movable guiding, holding, or protecting components or surfaces
Y10T 24/4611	having operator for moving holding component or surface
Y10T 24/4613	Moves pivoting holding component
Y10T 24/4614	Moves slidably guided, nonself-biasing, holding component
Y10T 24/4616	having pierceable [e.g., cork] or naturally resilient [e.g., rubber] surfaces
Y10T 24/4618	with pivotal connection therebetween
Y10T 24/462	with slidable connection between nonself-biasing components
Y10T 24/4621	having resiliently biased component or surface
Y10T 24/4623	Coiled about longitudinal axis of held portion
Y10T 24/4625	and aperture therein alignable with another spaced aperture of means
Y10T 24/4627	and nonresilient structure for guiding portion thereto
Y10T 24/4629	including structure for cooperating with formation [e.g., cavity] formed on penetrating portion
Y10T 24/463	. . .	for pin having plural penetrating portions
Y10T 24/4632	Each independently movable towards and into cooperation with means
Y10T 24/4634	. . .	including relatively movable guiding, holding, or protecting components or surfaces
Y10T 24/4636	with connection allowing component to revolve about axis of held penetrating portion
Y10T 24/4638	with pivotal connection therebetween
Y10T 24/4639	having position locking means therefor
Y10T 24/4641	Spring or resiliently biased

Y10T 24/4643 with slidable connection between nonself-biasing components
Y10T 24/4645 Component slides parallel to axis of held penetrating portion
Y10T 24/4646 Means engages formation formed on penetrating portion
Y10T 24/4648 having nonresilient and resilient components
Y10T 24/465 Means formed from single resilient wire
Y10T 24/4652 Means formed from resilient sheet metal
Y10T 24/4654	. . . with independent, spaced, intermediate connections, or formations [e.g., coils], about which portion or means move
Y10T 24/4655 Includes slidable connection
Y10T 24/4657	. . . with pivotal connection between penetrating portion and means
Y10T 24/4659 Connection also permits sliding movement
Y10T 24/4661 Resiliently biased about connection
Y10T 24/4663	. . . with slidable connection intermediate penetrating portion and means
Y10T 24/4664	. . . having resilient bridging structure between portion and means
Y10T 24/4666 Means includes structure for cooperating with formation [e.g., cavity] formed on portion
Y10T 24/4668 and penetrating portion formed from wire
Y10T 24/467 Bridging structure includes elongated nonwire element
Y10T 24/4671 Wire also forms coiled bridging structure about which portion moves
Y10T 24/4673 including distinct device for cooperating with coil
Y10T 24/4675 having means also formed from same wire
Y10T 24/4677	. . with cavity for guiding structure-to-be-secured towards penetrating portion [e.g., stocking support]
Y10T 24/4679	. . having penetrating portion retractable or of changeable length
Y10T 24/468	. . having interconnected distinct penetrating portions
Y10T 24/4682	. . . Connection allows movement therebetween
Y10T 24/4684 Slidable connection
Y10T 24/4686 Resilient connection
Y10T 24/4688	. . . formed from common wire
Y10T 24/4689 and pointing in same direction
Y10T 24/4691	. . Penetrating portion includes relatively movable structure for resisting extraction
Y10T 24/4693	. . having specific wire penetrating portion
Y10T 24/4695	. . . Wire curved or bent
Y10T 24/4696	. . having distinct head structure
Y10T 24/4698	. . . Movably connected to penetrating portion
Y10T 24/47	. Strap-end-attaching devices
Y10T 24/4709	. . Bendable sheet material
Y10T 24/4718	. . Watch pintle connected
Y10T 24/4727	. . Webbing to tube [lawn chair]
Y10T 24/4736	. . Buckle connected
Y10T 24/4745	. . End clasp

Y10T 24/4755	. . Hook
Y10T 24/4764	. . Ring-loop
Y10T 24/4773	. . Cargo tiedown
Y10T 24/4782	. . Watch strap
Y10T 24/4791	. . Enlarged end epoxy
Y10T 24/48	. Pivoted edge stays
Y10T 24/49	. Fastener destructively secured by reshaping distortion force [e.g., ductile fastener]
Y10T 24/492	. . Distorted structure having shape facilitating impaling
Y10T 24/493	. . . and distinct fastener structure cooperating with impaled structure
Y10T 24/495 Detached cooperating structure
Y10T 24/497	. . . including plural impaling elements
Y10T 24/498 Elements form single aperture [e.g., split shank type]
Y10T 24/50	. Readily interlocking, two-part fastener requiring either destructive or tool disengagement
Y10T 24/505	. . including additional fastener structure linking parts
Y10T 24/51	. Hanger on portable article support for manual attachment thereof to overhead support [e.g., drapery hook]

Former US Class 29 Series

Y10T 29/00	Metal working
Y10T 29/10	. Battery-grid making
Y10T 29/11	. Bias [i.e. , helically] cutting of tubular stock
Y10T 29/1106	. . including orbital cutter
Y10T 29/1113	. . . within stock support
Y10T 29/1119	. . . with orbiting strip accumulator
Y10T 29/1125	. . including means to inflate stock
Y10T 29/1131	. . with means to feed stock along support or mandrel
Y10T 29/1138	. . . Single means produces compound motion
Y10T 29/1144 Endless belt drive means
Y10T 29/115	. . . Axially
Y10T 29/1156	. . . Rotatably
Y10T 29/1163	. . with means to rotate and store stock supply
Y10T 29/1169	. . . Axis of rotation parallel to support or mandrel
Y10T 29/1175	. . with means for arcuate shift of mandrel
Y10T 29/1181	. . including means to handle produced strip or web
Y10T 29/1188	. . . with common adjustment for cutter
Y10T 29/1194	. . Method
Y10T 29/12	. Buckle making
Y10T 29/13	. Button-fastener making
Y10T 29/14	. Shredding metal or metal wool article making

Y10T 29/142	. . Metal wool making
Y10T 29/143	. . . Shaving or longitudinal cutting
Y10T 29/145 Soap-pad making
Y10T 29/147	. . Metal wool bundling
Y10T 29/148	. . . Soap-pad making
Y10T 29/15	. Cord heddle making
Y10T 29/16	. Cotter-pin making
Y10T 29/17	. Crankshaft making apparatus
Y10T 29/18	. Expanded metal making
Y10T 29/185	. . by use of reciprocating perforator
Y10T 29/19	. Eyebolt or hook making
Y10T 29/20	. Fence barb making
Y10T 29/203	. . by use of reciprocating cutter or die
Y10T 29/207	. . by use of rotary cutter or die
Y10T 29/21	. Finger-ring forming or sizing
Y10T 29/22	. Fishhook making
Y10T 29/23	. Gem and jewel setting
Y10T 29/24	. Hinge making or assembling
Y10T 29/25	. Lacing-stud making
Y10T 29/26	. Paper-fastener making
Y10T 29/27	. Plow or cultivator iron making
Y10T 29/28	. Puddlers balls making
Y10T 29/29	. Railway-chair making
Y10T 29/30	. Foil or other thin sheet-metal making or treating
Y10T 29/301	. . Method
Y10T 29/302	. . . Clad or other composite foil or thin metal making
Y10T 29/303	. . . with assembling or disassembling of a pack
Y10T 29/304 Using transitory solid cover material
Y10T 29/305 including bond prevention treatment
Y10T 29/306 Disassembling of a pack
Y10T 29/307	. . . by shaving or longitudinal cutting
Y10T 29/308	. . . Using transitory material
Y10T 29/309	. . Means for opening or separating a pack
Y10T 29/31	. Spectacle-frame making
Y10T 29/32	. Spiral cutting of flat stock
Y10T 29/33	. Stereotype-plate finishing
Y10T 29/34	. Means for forming clench-tongue [eg, for tieband]
Y10T 29/35	. Tire upsetting, with cutting, punching, etc.
Y10T 29/36	. toothed-cylinder making apparatus [e.g. , texture working cylinder]
Y10T 29/37	. Impeller making apparatus

Y10T 29/38	. Type finishing and grooving
Y10T 29/39	. Venetian blind assembling
Y10T 29/40	. Umbrella-frame making
Y10T 29/41	. Barrier layer or semiconductor device making
Y10T 29/413	. . Barrier layer device making
Y10T 29/417	. . . Electrolytic device making [e.g., capacitor]
Y10T 29/42	. Piezoelectric device making
Y10T 29/43	. Electric condenser making
Y10T 29/435	. . Solid dielectric type
Y10T 29/44	. Filing
Y10T 29/442	. . of key article
Y10T 29/444	. . Continuous band type
Y10T 29/446	. . Reciprocating type
Y10T 29/448	. . File-blank stripper
Y10T 29/45	. Scale remover or preventor
Y10T 29/4506	. . for hollow workpiece
Y10T 29/4511	. . . Interior surface
Y10T 29/4517	. . Rolling deformation or deflection
Y10T 29/4522	. . . for wire or rod
Y10T 29/4528	. . with rotary head
Y10T 29/4533	. . Fluid impingement
Y10T 29/4539	. . . with heater
Y10T 29/4544	. . . Liquid jet
Y10T 29/455	. . . Airblast
Y10T 29/4556	. . Chainer
Y10T 29/4561	. . Scraper or scalper
Y10T 29/4567	. . Brush type
Y10T 29/4572	. . Mechanically powered operator
Y10T 29/4578	. . . Tack or needle type
Y10T 29/4583	. . . Hammer
Y10T 29/4589	. . . Blade or chisel
Y10T 29/4594	. . Hand tool
Y10T 29/46	. Burning in, wearing in, or oil burnishing
Y10T 29/47	. Burnishing
Y10T 29/471	. . of water laid fibrous article [e.g., paper]
Y10T 29/473	. . . Heated burnishing member
Y10T 29/474 Burnishing tool reciprocates across work surface
Y10T 29/476	. . Continuous feed
Y10T 29/477	. . of gear article
Y10T 29/479	. . by shot peening or blasting

Y10T 29/48	. Upholstered article making
Y10T 29/481	. . Method
Y10T 29/482	. . Tufting
Y10T 29/483	. . . with means to clench fastener
Y10T 29/484	. . . with means to insert guide pin or fastener
Y10T 29/486	. . Cover stretching
Y10T 29/487	. . Edge-roll forming
Y10T 29/488	. . form or holder
Y10T 29/489	. . . with follower
Y10T 29/49	. Method of mechanical manufacture
Y10T 29/49002	. . Electrical device making
Y10T 29/49004	. . . including measuring or testing of device or component part
Y10T 29/49005	. . . Acoustic transducer
Y10T 29/49007	. . . Indicating transducer
Y10T 29/49009	. . . Dynamoelectric machine
Y10T 29/49011 Commutator or slip ring assembly
Y10T 29/49012 Rotor
Y10T 29/49014	. . . Superconductor
Y10T 29/49016	. . . Antenna or wave energy "plumbing" making
Y10T 29/49018 with other electrical component
Y10T 29/4902	. . . Electromagnet, transformer or inductor
Y10T 29/49021 Magnetic recording reproducing transducer [e.g., tape head, core, etc.]
Y10T 29/49023 including disassembly step
Y10T 29/49025 Making disc drive
Y10T 29/49027 Mounting preformed head/core onto other structure
Y10T 29/49028 Mounting multitrack head
Y10T 29/4903 with bonding
Y10T 29/49032 Fabricating head structure or component thereof
Y10T 29/49034 Treating to affect magnetic properties
Y10T 29/49036 including measuring or testing
Y10T 29/49037 Using reference point/surface to facilitate measuring
Y10T 29/49039 with dual gap materials
Y10T 29/49041 with significant slider/housing shaping or treating
Y10T 29/49043 Depositing magnetic layer or coating
Y10T 29/49044 Plural magnetic deposition layers
Y10T 29/49046 with etching or machining of magnetic material
Y10T 29/49048 Machining magnetic material [e.g., grinding, etching, polishing]
Y10T 29/4905 Employing workholding means
Y10T 29/49052 by etching
Y10T 29/49053 Multitrack heads having integral holding means

Y10T 29/49055	with bond/laminating preformed parts, at least two magnetic
Y10T 29/49057	Using glass bonding material
Y10T 29/49059	with work positioning means
Y10T 29/4906	Providing winding
Y10T 29/49062	Multilayered winding
Y10T 29/49064	by coating
Y10T 29/49066	Preformed winding
Y10T 29/49067	Specified diverse magnetic materials
Y10T 29/49069	Data storage inductor or core
Y10T 29/49071	by winding or coiling
Y10T 29/49073	by assembling coil and core
Y10T 29/49075	including permanent magnet or core
Y10T 29/49076	From comminuted material
Y10T 29/49078	Laminated
Y10T 29/4908	Acoustic transducer
Y10T 29/49082	Resistor making
Y10T 29/49083	Heater type
Y10T 29/49085	Thermally variable
Y10T 29/49087	with envelope or housing
Y10T 29/49089	Filling with powdered insulation
Y10T 29/49091	with direct compression of powdered insulation
Y10T 29/49092	Powdering the insulation
Y10T 29/49094	by oxidation
Y10T 29/49096	with winding
Y10T 29/49098	Applying terminal
Y10T 29/49099	Coating resistive material on a base
Y10T 29/49101	Applying terminal
Y10T 29/49103	Strain gauge making
Y10T 29/49105	Switch making
Y10T 29/49107	Fuse making
Y10T 29/49108	Electric battery cell making
Y10T 29/4911	including sealing
Y10T 29/49112	including laminating of indefinite length material
Y10T 29/49114	including adhesively bonding
Y10T 29/49115	including coating or impregnating
Y10T 29/49117	Conductor or circuit manufacturing
Y10T 29/49119	Brush
Y10T 29/49121	Beam lead frame or beam lead device
Y10T 29/49123	Co-axial cable
Y10T 29/49124	On flat or curved insulated base, e.g., printed circuit, etc.

Y10T 29/49126	Assembling bases
Y10T 29/49128	Assembling formed circuit to base
Y10T 29/4913	Assembling to base an electrical component, e.g., capacitor, etc.
Y10T 29/49131	by utilizing optical sighting device
Y10T 29/49133	with component orienting
Y10T 29/49135	and shaping, e.g., cutting or bending, etc.
Y10T 29/49137	Different components
Y10T 29/49139	by inserting component lead or terminal into base aperture
Y10T 29/4914	with deforming of lead or terminal
Y10T 29/49142	including metal fusion
Y10T 29/49144	by metal fusion
Y10T 29/49146	with encapsulating, e.g., potting, etc.
Y10T 29/49147	Assembling terminal to base
Y10T 29/49149	by metal fusion bonding
Y10T 29/49151	by deforming or shaping
Y10T 29/49153	with shaping or forcing terminal into base aperture
Y10T 29/49155	Manufacturing circuit on or in base
Y10T 29/49156	with selective destruction of conductive paths
Y10T 29/49158	with molding of insulated base
Y10T 29/4916	Simultaneous circuit manufacturing
Y10T 29/49162	by using wire as conductive path
Y10T 29/49163	with sintering of base
Y10T 29/49165	by forming conductive walled aperture in base
Y10T 29/49167	with deforming of conductive path
Y10T 29/49169	Assembling electrical component directly to terminal or elongated conductor
Y10T 29/49171	with encapsulating
Y10T 29/49172	by molding of insulating material
Y10T 29/49174	Assembling terminal to elongated conductor
Y10T 29/49176	with molding of electrically insulating material
Y10T 29/49178	by shrinking of cover
Y10T 29/49179	by metal fusion bonding
Y10T 29/49181	by deforming
Y10T 29/49183	of ferrule about conductor and terminal
Y10T 29/49185	of terminal
Y10T 29/49187	with forming eyelet from elongated conductor
Y10T 29/49188	with penetrating portion
Y10T 29/4919	Through insulation
Y10T 29/49192	with insulation removal
Y10T 29/49194	Assembling elongated conductors, e.g., splicing, etc.
Y10T 29/49195	with end-to-end orienting

Y10T 29/49197	including fluid evacuating or pressurizing
Y10T 29/49199	including deforming of joining bridge
Y10T 29/49201	with overlapping orienting
Y10T 29/49202	including oppositely facing end orienting
Y10T 29/49204	Contact or terminal manufacturing
Y10T 29/49206	by powder metallurgy
Y10T 29/49208	by assembling plural parts
Y10T 29/4921	with bonding
Y10T 29/49211	of fused material
Y10T 29/49213	Metal
Y10T 29/49215	by impregnating a porous mass
Y10T 29/49217	by elastic joining
Y10T 29/49218	with deforming
Y10T 29/4922	with molding of insulation
Y10T 29/49222	forming array of contacts or terminals
Y10T 29/49224	with coating
Y10T 29/49226	Electret making
Y10T 29/49227	Insulator making
Y10T 29/49229	Prime mover or fluid pump making
Y10T 29/49231	I.C. [internal combustion] engine making
Y10T 29/49233	Repairing, converting, servicing or salvaging
Y10T 29/49234	Rotary or radial engine making
Y10T 29/49236	Fluid pump or compressor making
Y10T 29/49238	Repairing, converting, servicing or salvaging
Y10T 29/4924	Scroll or peristaltic type
Y10T 29/49242	Screw or gear type, e.g., Moineau type
Y10T 29/49243	Centrifugal type
Y10T 29/49245	Vane type or other rotary, e.g., fan
Y10T 29/49247	Valve lifter making
Y10T 29/49249	Piston making
Y10T 29/4925	Repairing, converting, servicing or salvaging
Y10T 29/49252	Multi-element piston making
Y10T 29/49254	Utilizing a high energy beam, e.g., laser, electron beam
Y10T 29/49256	with assembly or composite article making
Y10T 29/49258	with thermal barrier or heat flow provision
Y10T 29/49259	with fiber reinforced structure
Y10T 29/49261	by composite casting or molding
Y10T 29/49263	by coating or cladding
Y10T 29/49265	Ring groove forming or finishing
Y10T 29/49266	Gudgeon pin, wrist pin, piston pin, or boss therefor

Y10T 29/49268	with other attaching provision for connecting rod
Y10T 29/4927	. . .	Cylinder, cylinder head or engine valve sleeve making
Y10T 29/49272	with liner, coating, or sleeve
Y10T 29/49274	. . .	Piston ring or piston packing making
Y10T 29/49275	including forging or hammering
Y10T 29/49277	including casting or molding
Y10T 29/49279	including rolling or die forming, e.g., drawing, punching
Y10T 29/49281	including coating or plating
Y10T 29/49282	including grinding or honing
Y10T 29/49284	including machining or angular cutting
Y10T 29/49286	. . .	Crankshaft making
Y10T 29/49288	. . .	Connecting rod making
Y10T 29/4929	including metallurgical bonding
Y10T 29/49291	including metal forging or die shaping
Y10T 29/49293	. . .	Camshaft making
Y10T 29/49295	. . .	Push rod or rocker arm making
Y10T 29/49297	. . .	Seal or packing making
Y10T 29/49298	. . .	Poppet or I.C. engine valve or valve seat making
Y10T 29/493	Valve guide making
Y10T 29/49302	Repairing, converting, servicing or salvaging
Y10T 29/49304	Valve tappet making
Y10T 29/49306	Valve seat making
Y10T 29/49307	Composite or hollow valve stem or head making
Y10T 29/49309	including forging
Y10T 29/49311	including extruding
Y10T 29/49313	including casting
Y10T 29/49314	with assembly or composite article making
Y10T 29/49316	. .	Impeller making
Y10T 29/49318	. . .	Repairing or disassembling
Y10T 29/4932	. . .	Turbomachine making
Y10T 29/49321	Assembling individual fluid flow interacting members, e.g., blades, vanes, buckets, on rotary support member
Y10T 29/49323	Assembling fluid flow directing devices, e.g., stators, diaphragms, nozzles
Y10T 29/49325	Shaping integrally bladed rotor
Y10T 29/49327	. . .	Axial blower or fan
Y10T 29/49329	. . .	Centrifugal blower or fan
Y10T 29/4933	. . .	Fluid coupling device
Y10T 29/49332	. . .	Propeller making
Y10T 29/49334	Utilizing hollow tube blank
Y10T 29/49336	. . .	Blade making

Y10T 29/49337 Composite blade
Y10T 29/49339 Hollow blade
Y10T 29/49341 with cooling passage
Y10T 29/49343 Passage contains tubular insert
Y10T 29/49345	. . Catalytic device making
Y10T 29/49346	. . Rocket or jet device making
Y10T 29/49348	. . Burner, torch or metallurgical lance making
Y10T 29/4935	. . Heat exchanger or boiler making
Y10T 29/49352	. . . Repairing, converting, servicing or salvaging
Y10T 29/49353	. . . Heat pipe device making
Y10T 29/49355	. . . Solar energy device making
Y10T 29/49357	. . . Regenerator or recuperator making
Y10T 29/49359	. . . Cooling apparatus making, e.g., air conditioner, refrigerator
Y10T 29/49361	. . . Tube inside tube
Y10T 29/49362	. . . Tube wound about tube
Y10T 29/49364	. . . Tube joined to flat sheet longitudinally, i.e., tube sheet
Y10T 29/49366	. . . Sheet joined to sheet
Y10T 29/49368 with inserted tubes
Y10T 29/49369 Utilizing bond inhibiting material
Y10T 29/49371 with subsequent fluid expansion
Y10T 29/49373	. . . Tube joint and tube plate structure
Y10T 29/49375 including conduit expansion or inflation
Y10T 29/49377	. . . Tube with heat transfer means
Y10T 29/49378 Finned tube
Y10T 29/4938 Common fin traverses plurality of tubes
Y10T 29/49382 Helically finned
Y10T 29/49384 Internally finned
Y10T 29/49385 Made from unitary workpiece, i.e., no assembly
Y10T 29/49387	. . . Boiler making
Y10T 29/49389	. . . Header or manifold making
Y10T 29/49391	. . . Tube making or reforming
Y10T 29/49393	. . . with metallurgical bonding
Y10T 29/49394	. . Accumulator making
Y10T 29/49396	. . Condenser, evaporator or vaporizer making
Y10T 29/49398	. . Muffler, manifold or exhaust pipe making
Y10T 29/494	. . Fluidic or fluid actuated device making
Y10T 29/49401	. . Fluid pattern dispersing device making, e.g., ink jet
Y10T 29/49403	. . Tapping device making
Y10T 29/49405	. . Valve or choke making
Y10T 29/49407	. . . Repairing, converting, servicing or salvaging

Y10T 29/49409	. . .	Valve seat forming
Y10T 29/4941	. . .	Valve stem or tire valve making
Y10T 29/49412	. . .	with assembly, disassembly or composite article making
Y10T 29/49414	Joining plural semi-circular components
Y10T 29/49416	with material shaping or cutting
Y10T 29/49417	including molding or casting
Y10T 29/49419	including machining or drilling
Y10T 29/49421	including metallurgical bonding
Y10T 29/49423	including metal deforming
Y10T 29/49425	including metallurgical bonding
Y10T 29/49426	. . .	including metal shaping and diverse operation
Y10T 29/49428	. .	Gas and water specific plumbing component making
Y10T 29/4943	. . .	Plumbing fixture making
Y10T 29/49432	. . .	Nozzle making
Y10T 29/49433	Sprayer
Y10T 29/49435	. . .	Flexible conduit or fitting therefor
Y10T 29/49437	. . .	Flue connector device making
Y10T 29/49439	. . .	Trap making
Y10T 29/4944	. . .	Return connector device making
Y10T 29/49442	. . .	T-shaped fitting making
Y10T 29/49444	. . .	Elbow or L-shaped fitting making
Y10T 29/49446	. . .	Ferrule making or reforming
Y10T 29/49448	. .	Agricultural device making
Y10T 29/49449	. . .	Traction apparatus, e.g., for tractor
Y10T 29/49451	. . .	Harvester guard
Y10T 29/49453	. .	Pulley making
Y10T 29/49455	. . .	Assembly
Y10T 29/49456	with shaping
Y10T 29/49458	. . .	Disc splitting to form pulley rim groove
Y10T 29/4946	. . .	Groove forming in sheet metal pulley rim
Y10T 29/49462	. .	Gear making
Y10T 29/49464	. . .	Assembling of gear into force transmitting device
Y10T 29/49465	. . .	Gear mounting
Y10T 29/49467	. . .	Gear shaping
Y10T 29/49469	Worm gear
Y10T 29/49471	Roll forming
Y10T 29/49472	Punching or stamping
Y10T 29/49474	Die-press shaping
Y10T 29/49476	Gear tooth cutting
Y10T 29/49478	Gear blank making

Y10T 29/4948 with specific gear material
Y10T 29/49481	. . Wheel making
Y10T 29/49483	. . . Railway or trolley wheel making
Y10T 29/49485 Multiple part or composite
Y10T 29/49487 with axle or hub
Y10T 29/49488	. . . Steering wheel
Y10T 29/4949	. . . Material winding, e.g., reel, spool
Y10T 29/49492	. . . Land wheel
Y10T 29/49494 Assembling tire to wheel body
Y10T 29/49496 Disc type wheel
Y10T 29/49497 Assembling wheel disc to rim and hub
Y10T 29/49499 Assembling wheel disc to rim
Y10T 29/49501 with disc shaping
Y10T 29/49503 Integral rim and disc making
Y10T 29/49504 Disc shaping
Y10T 29/49506 Tensioned spoke type wheel making
Y10T 29/49508 Tensioning all spokes simultaneously
Y10T 29/4951 Tensioning spokes in series
Y10T 29/49512 Tensioning spokes individually
Y10T 29/49513 Compression, e.g., nontension, spoke type wheel making
Y10T 29/49515 Joining spokes to rim and hub
Y10T 29/49517 Joining spokes to rim
Y10T 29/49519 Joining spokes to hub
Y10T 29/4952 Making plural spokes from a single blank
Y10T 29/49522 Individual spoke making
Y10T 29/49524 Rim making
Y10T 29/49526 with assembling
Y10T 29/49528 Demountable rim making
Y10T 29/49529 Die-press shaping
Y10T 29/49531 Roller forming
Y10T 29/49533 Hub making
Y10T 29/49535 with assembling
Y10T 29/49536 Hub shaping
Y10T 29/49538 Tire making
Y10T 29/4954 Wheel trim making, e.g., wheel cover, hubcap
Y10T 29/49542 with means for retaining trim member on wheel
Y10T 29/49544	. . Roller making
Y10T 29/49545	. . . Repairing or servicing
Y10T 29/49547	. . . Assembling preformed components
Y10T 29/49549 Work contacting surface element assembled to core

Y10T 29/49551	Work contacting surface wound about core
Y10T 29/49552	with prestressing of component by heat differential, e.g., shrink, fit
Y10T 29/49554	Work contacting surface having annular axial sections
Y10T 29/49556	Work contacting surface element assembled to end support members
Y10T 29/49558	Includes securing removable cover on roller
Y10T 29/4956	Fabricating and shaping roller work contacting surface element
Y10T 29/49561	toothed roller
Y10T 29/49563	with coating or casting about a core
Y10T 29/49565	One-piece roller making
Y10T 29/49567	Dental appliance making
Y10T 29/49568	Orthodontic device making
Y10T 29/4957	Sound device making
Y10T 29/49572	Hearing aid component making
Y10T 29/49574	Musical instrument or tuning fork making
Y10T 29/49575	including diaphragm or support therefor
Y10T 29/49577	Phonograph component making
Y10T 29/49579	Watch or clock making
Y10T 29/49581	having arbor, pinion, or balance
Y10T 29/49583	having indicia, face, or dial
Y10T 29/49584	having case, cover, or back
Y10T 29/49586	having crown, stem, or pendent
Y10T 29/49588	Jewelry or locket making
Y10T 29/4959	Human adornment device making
Y10T 29/49591	Bracelet making
Y10T 29/49593	Finger ring making
Y10T 29/49595	Latch, clasp, or fastener component making
Y10T 29/49597	Ornamental stock making
Y10T 29/49599	Knob or knob shank making
Y10T 29/496	Multiperforated metal article making
Y10T 29/49602	Coil wound wall screen
Y10T 29/49604	Filter
Y10T 29/49606	Turnbuckle making
Y10T 29/49607	Spring-head clip making
Y10T 29/49609	Spring making
Y10T 29/49611	for vehicle or clutch
Y10T 29/49613	for human comfort
Y10T 29/49615	Resilient shock or vibration absorber utility
Y10T 29/49616	Structural member making
Y10T 29/49618	Restoring existing member, e.g., reinforcing, repairing
Y10T 29/4962	Grille making

Y10T 29/49622	. . .	Vehicular structural member making
Y10T 29/49623	. . .	Static structure, e.g., a building component
Y10T 29/49625	Openwork, e.g., a truss, joist, frame, lattice-type or box beam
Y10T 29/49627	Frame component
Y10T 29/49629	Panel
Y10T 29/49631	Columnar member
Y10T 29/49632	Metal reinforcement member for nonmetallic, e.g., concrete, structural element
Y10T 29/49634	Beam or girder
Y10T 29/49636	. .	Process for making bearing or component thereof
Y10T 29/49638	. . .	Repairing
Y10T 29/49639	. . .	Fluid bearing
Y10T 29/49641	. . .	Linear bearing
Y10T 29/49643	. . .	Rotary bearing
Y10T 29/49645	Thrust bearing
Y10T 29/49647	Plain bearing
Y10T 29/49648	Self-adjusting or self-aligning, including ball and socket type, bearing and component making
Y10T 29/4965	Deforming socket to secure ball
Y10T 29/49652	Die-press shaping
Y10T 29/49654	having liner
Y10T 29/49655	having liner
Y10T 29/49657	Socket making
Y10T 29/49659	by molding or casting
Y10T 29/49661	Nonmetallic socket
Y10T 29/49663	by assembling
Y10T 29/49664	Ball making
Y10T 29/49666	with metallurgical bonding
Y10T 29/49668	Sleeve or bushing making
Y10T 29/4967	Nonmetallic
Y10T 29/49671	Strip or blank material shaping
Y10T 29/49673	Die-press shaping
Y10T 29/49675	having inner lining layer
Y10T 29/49677	having liner
Y10T 29/49679	Anti-friction bearing or component thereof
Y10T 29/4968	Assembling of race, cage, and rolling anti-friction members
Y10T 29/49682	Assembling of race and rolling anti-friction members
Y10T 29/49684	with race making
Y10T 29/49686	Assembling of cage and rolling anti-friction members
Y10T 29/49687	with cage making

Y10T 29/49689	Race making
Y10T 29/49691	Cage making
Y10T 29/49693	Roller making
Y10T 29/49694	Ball making
Y10T 29/49696	. . .	Mounting
Y10T 29/49698	. . .	Demounting
Y10T 29/497	. . .	Pre-usage process, e.g., preloading, aligning
Y10T 29/49702	. . .	Lubricating
Y10T 29/49703	. . .	Sealing
Y10T 29/49705	. . .	Coating or casting
Y10T 29/49707	. . .	Bearing surface treatment
Y10T 29/49709	. . .	Specific metallic composition
Y10T 29/4971	. . .	Nonmetallic bearing element
Y10T 29/49712	. .	Ball making
Y10T 29/49714	. . .	Hollow ball
Y10T 29/49716	. .	Converting
Y10T 29/49718	. .	Repairing
Y10T 29/49719	. . .	Seal or element thereof
Y10T 29/49721	. . .	with disassembling
Y10T 29/49723	including reconditioning of part
Y10T 29/49725	by shaping
Y10T 29/49726	Removing material
Y10T 29/49728	and by a metallurgical operation, e.g., welding, diffusion bonding, casting
Y10T 29/4973	Replacing of defective part
Y10T 29/49732	. . .	by attaching repair preform, e.g., remaking, restoring, or patching
Y10T 29/49734	and removing damaged material
Y10T 29/49735	Mechanically attaching preform with separate fastener
Y10T 29/49737	Metallurgically attaching preform
Y10T 29/49739	Mechanically attaching preform by separate fastener
Y10T 29/49741	Screw threaded fastener
Y10T 29/49742	Metallurgically attaching preform
Y10T 29/49744	Screw threaded preform
Y10T 29/49746	. . .	by applying fluent material, e.g., coating, casting
Y10T 29/49748	. . .	by shaping, e.g., bending, extruding, turning, etc.
Y10T 29/4975	including heating
Y10T 29/49751	. .	Scrap recovering or utilizing
Y10T 29/49753	. . .	Metalworking to consolidate scrap
Y10T 29/49755	. . .	Separating one material from another
Y10T 29/49757	by burning or heating

Y10T 29/49758	. . .	During simulated operation or operating conditions
Y10T 29/4976	. . .	Temperature
Y10T 29/49762	. . .	Center locating and shaping
Y10T 29/49764	. . .	with testing or indicating
Y10T 29/49766	. . .	torquing threaded assemblage or determining torque herein
Y10T 29/49767	Determining relative number of threaded member rotations
Y10T 29/49769	. . .	Using optical instrument [excludes mere human eyeballing]
Y10T 29/49771	. . .	Quantitative measuring or gauging
Y10T 29/49773	by radioactive tracing
Y10T 29/49774	by vibratory or oscillatory movement
Y10T 29/49776	Pressure, force, or weight determining
Y10T 29/49778	. . .	with aligning, guiding, or instruction
Y10T 29/4978	Assisting assembly or disassembly
Y10T 29/49782	. . .	of a slide fastener
Y10T 29/49783	. . .	of slider
Y10T 29/49785	. . .	of interlocking element
Y10T 29/49787	. . .	Obtaining plural composite product pieces from preassembled workpieces
Y10T 29/49789	. . .	Obtaining plural product pieces from unitary workpiece
Y10T 29/4979	. . .	Breaking through weakened portion
Y10T 29/49792	. . .	Dividing through modified portion
Y10T 29/49794	. . .	Dividing on common outline
Y10T 29/49796	. . .	Coacting pieces
Y10T 29/49798	. . .	Dividing sequentially from leading end, e.g., by cutting or breaking
Y10T 29/49799	. . .	Providing transitory integral holding or handling portion
Y10T 29/49801	. . .	Shaping fiber or fibered material
Y10T 29/49803	. . .	Magnetically shaping
Y10T 29/49805	. . .	Shaping by direct application of fluent pressure
Y10T 29/49806	. . .	Explosively shaping
Y10T 29/49808	. . .	Shaping container end to encapsulate material
Y10T 29/4981	. . .	Utilizing transitory attached element or associated separate material
Y10T 29/49812	. . .	Temporary protective coating, impregnation, or cast layer
Y10T 29/49813	. . .	Shaping mating parts for reassembly in different positions
Y10T 29/49815	. . .	Disassembling
Y10T 29/49817	. . .	with other than ancillary treating or assembling
Y10T 29/49819	. . .	with conveying of work or disassembled work part
Y10T 29/49821	. . .	by altering or destroying work part or connector
Y10T 29/49822	. . .	by applying force
Y10T 29/49824	to elastically deform work part or connector
Y10T 29/49826	. . .	Assembling or joining
Y10T 29/49828	. . .	Progressively advancing of work assembly station or assembled portion of work

Y10T 29/49829	Advancing work to successive stations [i.e., assembly line]
Y10T 29/49831	Advancing station
Y10T 29/49833	. . .	Punching, piercing or reaming part by surface of second part
Y10T 29/49835	with shaping
Y10T 29/49837	of first part
Y10T 29/49838	. . .	by stringing
Y10T 29/4984	. . .	Retaining clearance for motion between assembled parts
Y10T 29/49842	Between tube-forming helical coils
Y10T 29/49844	Through resilient media
Y10T 29/49845	by deforming interlock
Y10T 29/49847	by folding part into plural ears
Y10T 29/49849	by wrapping around
Y10T 29/49851	of link closure
Y10T 29/49853	of sphere, i.e., ball, in socket
Y10T 29/49854	Ball point pen making
Y10T 29/49856	Allowing assembled sphere to move in single plane only
Y10T 29/49858	of flange into tubular socket
Y10T 29/4986	Outwardly deforming internally fitted rod
Y10T 29/49861	. . .	Sizing mating parts during final positional association
Y10T 29/49863	. . .	with prestressing of part
Y10T 29/49865	by temperature differential [e.g., shrink fit]
Y10T 29/49867	of skin on frame member
Y10T 29/49869	by flexing
Y10T 29/4987	Elastic joining of parts
Y10T 29/49872	Confining elastic part in socket
Y10T 29/49874	Prestressing rod, filament or strand
Y10T 29/49876	by snap fit
Y10T 29/49877	. . .	of flexible wall, expansible chamber devices [e.g., bellows]
Y10T 29/49879	. . .	Spaced wall tube or receptacle
Y10T 29/49881	. . .	of separate helix [e.g., screw thread]
Y10T 29/49883	. . .	Ribbing
Y10T 29/49885	. . .	with coating before or during assembling
Y10T 29/49886	to roughen surface
Y10T 29/49888	. . .	Subsequently coating
Y10T 29/4989	. . .	with spreading of cable strands
Y10T 29/49892	. . .	Joining plate edge perpendicularly to frame
Y10T 29/49893	. . .	Peripheral joining of opposed mirror image parts to form a hollow body
Y10T 29/49895	. . .	Associating parts by use of aligning means [e.g., use of a drift pin or a "fixture"]
Y10T 29/49897	Registering mating opposed tool parts [e.g., registering a punch and a cooperating die]

Y10T 29/49899	by multiple cooperating aligning means
Y10T 29/49901	Sequentially associating parts on stationary aligning means
Y10T 29/49902	by manipulating aligning means
Y10T 29/49904	. . .	Assembling a subassembly, then assembling with a second subassembly
Y10T 29/49906	. . .	Metal deforming with nonmetallic bonding
Y10T 29/49908	. . .	Joining by deforming
Y10T 29/49909	Securing cup or tube between axially extending concentric annuli
Y10T 29/49911	by expanding inner annulus
Y10T 29/49913	by constricting outer annulus
Y10T 29/49915	Overedge assembling of seated part
Y10T 29/49917	by necking in cup or tube wall
Y10T 29/49918	At cup or tube end
Y10T 29/4992	by flaring inserted cup or tube end
Y10T 29/49922	by bending over projecting prongs
Y10T 29/49924	of parallel side-by-side elongated members
Y10T 29/49925	Inward deformation of aperture or hollow body wall
Y10T 29/49927	Hollow body is axially joined cup or tube
Y10T 29/49929	Joined to rod
Y10T 29/49931	Joined to overlapping ends of plural rods
Y10T 29/49933	After thinning
Y10T 29/49934	by axially applying force
Y10T 29/49936	Surface interlocking
Y10T 29/49938	Radially expanding part in cavity, aperture, or hollow body
Y10T 29/4994	Radially expanding internal tube
Y10T 29/49941	Peripheral edge joining of abutting plates
Y10T 29/49943	Riveting
Y10T 29/49945	. . .	by driven force fit
Y10T 29/49947	. . .	by applying separate fastener
Y10T 29/49948	Multipart cooperating fastener [e.g., bolt and nut]
Y10T 29/4995	Nonthreaded
Y10T 29/49952	At least one part is nonmetallic
Y10T 29/49954	Fastener deformed after application
Y10T 29/49956	Riveting
Y10T 29/49957	At least one part nonmetallic
Y10T 29/49959	Nonresilient fastener
Y10T 29/49961	At least one part nonmetallic
Y10T 29/49963	Threaded fastener
Y10T 29/49964	At least one part nonmetallic
Y10T 29/49966	with supplemental joining
Y10T 29/49968	Metal fusion joining

Y10T 29/4997 At least one part nonmetallic
Y10T 29/49972	. . with separating, localizing, or eliminating of as-cast defects from a metal casting [e.g., anti-pipe]
Y10T 29/49973	. . . Compressing ingot while still partially molten
Y10T 29/49975	. . . Removing defects
Y10T 29/49977 From center of ingot to leave hollow blank
Y10T 29/49979 After deforming
Y10T 29/4998	. . Combined manufacture including applying or shaping of fluent material
Y10T 29/49982	. . . Coating
Y10T 29/49984 and casting
Y10T 29/49986 Subsequent to metal working
Y10T 29/49988	. . . Metal casting
Y10T 29/49989 Followed by cutting or removing material
Y10T 29/49991 Combined with rolling
Y10T 29/49993	. . . Filling of opening
Y10T 29/49995	. . Shaping one-piece blank by removing material
Y10T 29/49996	. . . Successive distinct removal operations
Y10T 29/49998	. . Work holding
Y10T 29/50	. Convertible metal working machine
Y10T 29/505	. . Vise type
Y10T 29/51	. Plural diverse manufacturing apparatus including means for metal shaping or assembling
Y10T 29/5101	. . Slide fastener or slide fastener element
Y10T 29/5102	. . Binding or covering and cutting
Y10T 29/5103	. . . Cutting covering material only
Y10T 29/5104	. . Type of machine
Y10T 29/5105	. . . Drill press
Y10T 29/5107 Drilling and other
Y10T 29/5108 Portable
Y10T 29/5109	. . . Lathe
Y10T 29/511 Grinding attachment
Y10T 29/5111 Pulley or wheel
Y10T 29/5112 Convertible
Y10T 29/5113 Commutator
Y10T 29/5114 Lathe and tool
Y10T 29/5115	. . . Planer
Y10T 29/5116	. . forging and bending, cutting or punching
Y10T 29/5117	. . . Fastener [zipper]
Y10T 29/5118	. . . Riveting
Y10T 29/512	. . . Ball making

Y10T 29/5121	. . . Wire working
Y10T 29/5122	. . with means to feed work during tool contact
Y10T 29/5123	. . . including nonrotary flying tool
Y10T 29/5124	. . with means to feed work intermittently from one tool station to another
Y10T 29/5125	. . . Stock turret
Y10T 29/5126 Swiss type
Y10T 29/5127	. . . Blank turret
Y10T 29/5128 Rotary work - vertical axis
Y10T 29/5129 Rotary work - horizontal axis
Y10T 29/513 Stationary work
Y10T 29/5132 Belt drive
Y10T 29/5133 Crankshaft
Y10T 29/5134 Collapsible tube
Y10T 29/5135	. . . Endless belt
Y10T 29/5136	. . Separate tool stations for selective or successive operation on work
Y10T 29/5137	. . . including assembling or disassembling station
Y10T 29/5138 and means to machine work part to fit cooperating work part
Y10T 29/5139 and means to sever work prior to disassembling
Y10T 29/514 comprising means to strip insulation from wire
Y10T 29/5141 and means to stake electric wire to commutator or armature in assembling of electric motor or generator
Y10T 29/5142 and means to sever work from supply
Y10T 29/5143 and means to machine product
Y10T 29/5145 to sever product to length
Y10T 29/5146	. . Common reciprocating support for spaced tools
Y10T 29/5147	. . including composite tool
Y10T 29/5148	. . . including severing means
Y10T 29/5149 to sever electric terminal from supply strip
Y10T 29/515 to trim electric component
Y10T 29/5151 Means comprising hand-manipulatable implement
Y10T 29/5152	. . with turret mechanism
Y10T 29/5153	. . . Multiple turret
Y10T 29/5154	. . . tool turret
Y10T 29/5155 Rotary tool holder
Y10T 29/5157 Sliding tool holder
Y10T 29/5158 Fluid operated
Y10T 29/5159 Cam operated
Y10T 29/516 Longitudinal turret axis
Y10T 29/5161 Transverse turret axis
Y10T 29/5162 Lever operated

Y10T 29/5163 Rack-and-pinion operated
Y10T 29/5164 Screw operated
Y10T 29/5165	. . . including rotating and/or locking means
Y10T 29/5166 Frictional and positive
Y10T 29/5167 Lock means for tool or work turrets
Y10T 29/5168	. . Multiple-tool holder
Y10T 29/517	. . . Laterally movable stock holder
Y10T 29/5171	. . . Axial tool and transversely movable slide rest
Y10T 29/5172 Rotary tool spindle
Y10T 29/5173	. . . Longitudinally and transversely movable
Y10T 29/5174 Rotary tool spindle
Y10T 29/5175	. . . Oscillating tool
Y10T 29/5176	. . including machining means
Y10T 29/5177	. . . and work-holder for assembly
Y10T 29/5178	. . Attachment
Y10T 29/5179	. . Speed controller
Y10T 29/518	. . Carriage stop mechanism
Y10T 29/5182	. . Flash remover
Y10T 29/5183	. . Welding strip ends
Y10T 29/5184	. . Casting and working
Y10T 29/5185	. . Tube making
Y10T 29/5186	. . Covering
Y10T 29/5187	. . Wire working
Y10T 29/5188	. . Radiator making
Y10T 29/5189	. . Printing plate
Y10T 29/519	. . Turret
Y10T 29/5191	. . Assembly
Y10T 29/5192	. . Armature
Y10T 29/5193	. . Electrical connector or terminal
Y10T 29/5195	. . Tire valve or spark plug
Y10T 29/5196	. . Multiple station with conveyor
Y10T 29/5197	. . Multiple stations working strip material
Y10T 29/5198	. . Continuous strip
Y10T 29/5199	. . Work on tubes
Y10T 29/52	. Plural diverse manufacturing apparatus
Y10T 29/53	. Means to assemble or disassemble
Y10T 29/53004	. . with means to regulate operation by use of templet, tape, card or other replaceable information supply
Y10T 29/53009	. . . with comparator
Y10T 29/53013 Computer input

Y10T 29/53017	. . . Web or strand-carried information supply
Y10T 29/53022	. . with means to test work or product
Y10T 29/53026	. . with randomly actuated stopping or disabling means
Y10T 29/5303	. . . Responsive to condition of work or product
Y10T 29/53035	. . . Responsive to operative [e.g., safety device, etc.]
Y10T 29/53039	. . with control means energized in response to activator stimulated by condition sensor
Y10T 29/53043	. . . including means to divert defective work part
Y10T 29/53048	. . . Multiple station assembly or disassembly apparatus
Y10T 29/53052 including position sensor
Y10T 29/53057	. . . Responsive to timer
Y10T 29/53061	. . . Responsive to work or work-related machine element
Y10T 29/53065 with means to fasten by deformation
Y10T 29/5307 Self-piercing work part
Y10T 29/53074 with means to fasten by elastic joining
Y10T 29/53078 with means to fasten by frictional fitting
Y10T 29/53083 including means to apply magnetic force directly to position or hold work
Y10T 29/53087	. . with signal, scale, illuminator, or optical viewer
Y10T 29/53091	. . . for work-holder for assembly or disassembly
Y10T 29/53096	. . including means to provide a controlled environment
Y10T 29/531	. . Nuclear device
Y10T 29/53104	. . Roller or ball bearing
Y10T 29/53109	. . . including deforming means
Y10T 29/53113	. . Heat exchanger
Y10T 29/53117	. . . including means to manipulate heat exchanger tube bundle
Y10T 29/53122	. . . including deforming means
Y10T 29/53126	. . Means to place sheath on running-length core
Y10T 29/5313	. . Means to assemble electrical device
Y10T 29/53135	. . . Storage cell or battery
Y10T 29/53139 including deforming means
Y10T 29/53143	. . . Motor or generator
Y10T 29/53148 Means to assemble commutator
Y10T 29/53152 Means to position insulation
Y10T 29/53157 Means to stake wire to commutator or armature
Y10T 29/53161 including deforming means
Y10T 29/53165	. . . Magnetic memory device
Y10T 29/5317	. . . Laminated device
Y10T 29/53174	. . . Means to fasten electrical component to wiring board, base, or substrate
Y10T 29/53178 Chip component
Y10T 29/53183 Multilead component

Y10T 29/53187	. . .	Multiple station assembly apparatus
Y10T 29/53191	. . .	Means to apply vacuum directly to position or hold work part
Y10T 29/53196	. . .	Means to apply magnetic force directly to position or hold work part
Y10T 29/532	. . .	Conductor
Y10T 29/53204	Electrode
Y10T 29/53209	Terminal or connector
Y10T 29/53213	Assembled to wire-type conductor
Y10T 29/53217	Means to simultaneously assemble multiple, independent conductors to terminal
Y10T 29/53222	Means comprising hand-manipulatable implement
Y10T 29/53226	Fastening by deformation
Y10T 29/5323	Fastening by elastic joining
Y10T 29/53235	Means to fasten by deformation
Y10T 29/53239	Means to fasten by elastic joining
Y10T 29/53243	Multiple, independent conductors
Y10T 29/53248	Switch or fuse
Y10T 29/53252	. . .	Means to simultaneously fasten three or more parts
Y10T 29/53257	. . .	Means comprising hand-manipulatable implement
Y10T 29/53261	. . .	Means to align and advance work part
Y10T 29/53265	. . .	with work-holder for assembly
Y10T 29/5327	. . .	Means to fasten by deforming
Y10T 29/53274	. .	Means to disassemble electrical device
Y10T 29/53278	. . .	Storage cell or battery
Y10T 29/53283	. . .	Means comprising hand-manipulatable implement
Y10T 29/53287	. .	Means to place traveler on ring or ring on bobbin of a textile machine
Y10T 29/53291	. .	Slide fastener
Y10T 29/53296	. . .	Means to assemble stop onto stringer
Y10T 29/533	. . .	Means to assemble slider onto stringer
Y10T 29/53304	. . .	Means to assemble teeth onto stringer
Y10T 29/53309	. . .	Disassembly means
Y10T 29/53313	. .	Means to interrelatedly feed plural work parts from plural sources without manual intervention
Y10T 29/53317	. . .	Box or pallet assembly means
Y10T 29/53322	. . .	Means to assemble container
Y10T 29/53326	Handle to container
Y10T 29/5333	Label to container
Y10T 29/53335	Pressurized dispensing container
Y10T 29/53339	Hypodermic syringe
Y10T 29/53343	including fluid component
Y10T 29/53348	. . .	Running-length work

Y10T 29/53352	Means including orbiting running-length work supply
Y10T 29/53357	Pipe section
Y10T 29/53361	Assembled to article
Y10T 29/53365	Multiple station assembly apparatus
Y10T 29/5337	including assembly pallet
Y10T 29/53374	including turret-type conveyer
Y10T 29/53378	including converging conveyers
Y10T 29/53383	and means to fasten work parts together
Y10T 29/53387	by deforming
Y10T 29/53391	by elastic joining
Y10T 29/53396	by friction fit
Y10T 29/534	Multiple station assembly or disassembly apparatus
Y10T 29/53404	including turret-type conveyer
Y10T 29/53409	including converging conveyers
Y10T 29/53413	and primary central conveyer
Y10T 29/53417	Means to fasten work parts together
Y10T 29/53422	by deforming
Y10T 29/53426	by elastic joining
Y10T 29/5343	Means to drive self-piercing work part
Y10T 29/53435	including assembly pallet
Y10T 29/53439	including provision to utilize thermal expansion of work
Y10T 29/53443	Means to assemble or disassemble container and fluid component
Y10T 29/53448	Vehicle wheel
Y10T 29/53452	Railway wheel
Y10T 29/53457	Tumbler lock
Y10T 29/53461	toy doll
Y10T 29/53465	Film or tape cartridge
Y10T 29/5347	Crystal to watch or clock
Y10T 29/53474	Means to insert or extract pen point
Y10T 29/53478	with magazine supply
Y10T 29/53483	and magnetic work-holder or positioner
Y10T 29/53487	Assembling means comprising hand-manipulatable implement
Y10T 29/53491	One work part comprising living tissue
Y10T 29/53496	comprising driver for snap-off-mandrel fastener; e.g., Pop [TM] riveter
Y10T 29/535	One work part comprising nut or screw
Y10T 29/53504	One work part comprising paper clip
Y10T 29/53509	Means to assemble tire stud into tire tread
Y10T 29/53513	Means to fasten by deforming
Y10T 29/53517	Fastening sinker to fishing line
Y10T 29/53522	Means to fasten by deforming

Y10T 29/53526	. .	Running-length work
Y10T 29/5353	. . .	Assembled on core
Y10T 29/53535	. .	including means to vibrate work
Y10T 29/53539	. .	including work conveyer
Y10T 29/53543	. . .	including transporting track
Y10T 29/53548	and work carrying vehicle
Y10T 29/53552	. .	Valve applying or removing
Y10T 29/53557	. . .	Engine valve unit puller or applier
Y10T 29/53561	. . .	Engine valve spring compressor [only]
Y10T 29/53565	Plural spring engagement
Y10T 29/5357	Screw operated
Y10T 29/53574	Parallel or tong type, side entrance
Y10T 29/53578	Lever operated
Y10T 29/53583	Single jaw or valve engagement
Y10T 29/53587	Plier type
Y10T 29/53591	. . .	to or from wheel rim of resilient tire or tube
Y10T 29/53596	. . .	Removal tool
Y10T 29/536	. .	Piston ring inserter or remover
Y10T 29/53604	. . .	Plier-type operation
Y10T 29/53609	with ring encirclement
Y10T 29/53613	. .	Spring applier or remover
Y10T 29/53617	. . .	Transmission spring
Y10T 29/53622	. . .	Helical spring
Y10T 29/53626	. . .	Flat spiral spring [e.g., watch or clock type]
Y10T 29/5363	. . .	Circular spring
Y10T 29/53635	. . .	Leaf spring
Y10T 29/53639	. .	Means to stake watch or clock
Y10T 29/53643	. . .	Plier type
Y10T 29/53648	. .	Brake lining to brake shoe
Y10T 29/53652	. .	Tube and coextensive core
Y10T 29/53657	. .	to apply or remove a resilient article [e.g., tube, sleeve, etc.]
Y10T 29/53661	. . .	Nipple to nursing bottle
Y10T 29/53665	. . .	Well protector to sucker rod
Y10T 29/5367	. .	Coupling to conduit
Y10T 29/53674	. .	Loose-leaf sheet binder
Y10T 29/53678	. .	Compressing parts together face to face
Y10T 29/53683	. .	Spreading parts apart or separating them from face to face engagement
Y10T 29/53687	. .	by rotation of work part
Y10T 29/53691	. . .	Means to insert or remove helix
Y10T 29/53696	. .	Means to string

Y10T 29/537	. . . tool handle and tool
Y10T 29/53704	. . . tool chuck and tool
Y10T 29/53709	. . . Overedge assembling means
Y10T 29/53713 Belt-hook attacher
Y10T 29/53717 Annular work
Y10T 29/53722 with radially acting tool inside annular work
Y10T 29/53726 with second workpiece inside annular work one workpiece moved to shape the other
Y10T 29/5373 comprising driver for snap-off-mandrel fastener; e.g., Pop [TM] riveter
Y10T 29/53735 including near side fastener shaping tool
Y10T 29/53739 Pneumatic- or fluid-actuated tool
Y10T 29/53743 Liquid
Y10T 29/53748 and gas
Y10T 29/53752 having rotary drive mechanism
Y10T 29/53757 having allochiral actuating handles
Y10T 29/53761 having repositionable annulus engaging tool
Y10T 29/53765 including near side fastener shaping tool
Y10T 29/5377 Riveter
Y10T 29/53774 Single header
Y10T 29/53778 Pipe joiner
Y10T 29/53783 Clip applier
Y10T 29/53787 Binding or covering
Y10T 29/53791 Edge binding
Y10T 29/53796	. . . Puller or pusher means, contained force multiplying operator
Y10T 29/538 Hubcap and hub
Y10T 29/53804 Battery post and terminal
Y10T 29/53809 Cotter pin and cooperating member
Y10T 29/53813 Plier type means
Y10T 29/53817 Valve stem pin or key and another member
Y10T 29/53822 Machine key and another member
Y10T 29/53826 Arbor-type press means
Y10T 29/5383 having fluid operator
Y10T 29/53835 having wedge operator
Y10T 29/53839 having percussion or explosive operator
Y10T 29/53843 Tube, sleeve, or ferrule inserting or removing
Y10T 29/53848 having screw operator
Y10T 29/53852 C-frame
Y10T 29/53857 Central screw, work-engagers around screw
Y10T 29/53861 Work-engager arms along or parallel to screw
Y10T 29/53865 with arm connecting engaging means

Y10T 29/5387 Pivotal arms
Y10T 29/53874 Pivotal grippers on screw
Y10T 29/53878 Tubular or tube segment forms work-engager
Y10T 29/53883 Screw threaded work-engager
Y10T 29/53887 Movable grippers on screw
Y10T 29/53891 Plate or bar forms work-engager
Y10T 29/53896	. . . having lever operator
Y10T 29/539 Plier type means
Y10T 29/53904	. . Means comprising piston ring group contractor or holder
Y10T 29/53909	. . Means comprising hand manipulatable tool
Y10T 29/53913	. . . Aligner or center
Y10T 29/53917 Tube with tube
Y10T 29/53922 Auto wheel with auto chassis
Y10T 29/53926 Clutch plates
Y10T 29/5393	. . . Means comprising impact receiving tool
Y10T 29/53935 C-frame
Y10T 29/53939 Thread protector [e.g., wheel axle type]
Y10T 29/53943	. . . Hand gripper for direct push or pull
Y10T 29/53948 Centrifugal separator
Y10T 29/53952 Tube sleeve or ferrule applying or removing
Y10T 29/53957 Thread-tapping grip
Y10T 29/53961	. . with work-holder for assembly
Y10T 29/53965	. . . for assembling a luminescent mantle
Y10T 29/5397	. . . and assembling press [e.g., truss assembling means, etc.]
Y10T 29/53974	. . . having means to permit support movement while work is thereon
Y10T 29/53978	. . including means to relatively position plural work parts
Y10T 29/53983	. . Work-supported apparatus
Y10T 29/53987	. . Tube, sleeve or ferrule
Y10T 29/53991	. . Work gripper, anvil, or element
Y10T 29/53996	. . by deforming
Y10T 29/54	. Miscellaneous apparatus

Former US Class 70 series

Y10T 70/00	Locks
Y10T 70/10	. Miscellaneous
Y10T 70/20	. Attack-actuated defeating mechanisms
Y10T 70/25	. . With reset mechanisms
Y10T 70/30	. Hasp
Y10T 70/308	. . Combination lock

Y10T 70/317	. . .	Hasp-carried
Y10T 70/325	. . .	Keeper-carried
Y10T 70/333	. .	Key lock
Y10T 70/342	. . .	Hasp-carried
Y10T 70/35	Keeper-encasing
Y10T 70/358	Dead bolt
Y10T 70/367	Latching bolt
Y10T 70/375	Dead bolt
Y10T 70/383	Latching bolt
Y10T 70/392	. . .	Keeper-carried
Y10T 70/40	. .	Portable
Y10T 70/402	. .	Fetters
Y10T 70/404	. . .	Manacles and cuffs
Y10T 70/407	Nippers
Y10T 70/409	. . .	Shackles
Y10T 70/411	. .	Clamps
Y10T 70/413	. .	Padlocks
Y10T 70/415	. . .	Combination and/or key-controlled
Y10T 70/417	. . .	Combination-controlled
Y10T 70/42	Non-shackle type
Y10T 70/422	Rigid shackle
Y10T 70/424	Sliding
Y10T 70/426	Removable
Y10T 70/428	Pivoted
Y10T 70/43	Sliding detent
Y10T 70/433	Swinging detent
Y10T 70/435	Flexible shackle
Y10T 70/437	. . .	Key-controlled
Y10T 70/439	Non-shackle type
Y10T 70/441	Housing extension and cooperating detent
Y10T 70/443	Single stem or shank
Y10T 70/446	Rigid shackle
Y10T 70/448	Divided shackle
Y10T 70/45	Divided jaw type
Y10T 70/452	Sliding
Y10T 70/454	Removable
Y10T 70/457	Arcuate locus
Y10T 70/459	Both legs engaged
Y10T 70/461	Short leg engaged
Y10T 70/463	Long leg engaged

Y10T 70/465 Pivoted
Y10T 70/467 Sliding detent
Y10T 70/47 Free end only engaged
Y10T 70/472 Pivoted end only engaged
Y10T 70/474 Swinging detent
Y10T 70/476 Free end only engaged
Y10T 70/478 Pivoted end only engaged
Y10T 70/48 Arcuate locus
Y10T 70/483 Flexible shackle
Y10T 70/485	. . . With seal
Y10T 70/487	. . . Parts, accessories, attachments and adjuncts
Y10T 70/489 Housings
Y10T 70/491 Shackles
Y10T 70/493 Protectors
Y10T 70/496 Sheaths
Y10T 70/498 Shields or canopies
Y10T 70/50	. Special application
Y10T 70/5004	. . For antitheft signaling device on protected article
Y10T 70/5009	. . For portable articles
Y10T 70/5013	. . . Canes, umbrellas, apparel
Y10T 70/5018	. . . Robes
Y10T 70/5022	. . . Tools
Y10T 70/5027	. . . Supporting stands
Y10T 70/5031	. . . Receptacle
Y10T 70/5035 Bag
Y10T 70/504 Collapsible throat
Y10T 70/5044 Pivoted rigid jaw
Y10T 70/5049 Attache or briefcase, portfolio
Y10T 70/5053 Interengageable slide fastener type
Y10T 70/5058 Trunk and/or suitcase
Y10T 70/5062 Projecting fixed or movable lug type
Y10T 70/5066 Bolt type
Y10T 70/5071 Hasp controlled
Y10T 70/5075 Link and lever of hasp type
Y10T 70/508 Hasp type
Y10T 70/5084 Hasp-carried lock
Y10T 70/5089 Loop type
Y10T 70/5093	. . For closures
Y10T 70/5097	. . . Cabinet
Y10T 70/5102 Projecting lug type

Y10T 70/5106	External catch
Y10T 70/5111	Projectable bolt
Y10T 70/5115	Multiple bolts
Y10T 70/5119	Multidirectional displacement
Y10T 70/5124	Swinging and hooked end
Y10T 70/5128	Drawer
Y10T 70/5133	Dead bolt
Y10T 70/5137	Till
Y10T 70/5142	Combination
Y10T 70/5146	Window
Y10T 70/515	Sliding sash
Y10T 70/5155	Door
Y10T 70/5159	Emergency exit
Y10T 70/5164	Links to limit opening
Y10T 70/5168	Braces
Y10T 70/5173	Sliding door
Y10T 70/5177	Extending keeper
Y10T 70/5181	Rigid or fixed
Y10T 70/5186	Extensible
Y10T 70/519	Projecting or extending bolt
Y10T 70/5195	Projectable bolt
Y10T 70/5199	Swinging door
Y10T 70/5204	Interfitting lock housing and keeper
Y10T 70/5208	Multiple dead bolts
Y10T 70/5212	Sliding dead bolt
Y10T 70/5217	Swinging dead bolt
Y10T 70/5221	Locking latch bolt, biased
Y10T 70/5226	Combined dead bolt and latching bolt
Y10T 70/523	Multiple dead bolts
Y10T 70/5235	Multiple latch bolts
Y10T 70/5239	Dead bolt, dogged latch bolt
Y10T 70/5243	Manually dogged latch bolt
Y10T 70/5246	Dead bolts
Y10T 70/5248	Multiple
Y10T 70/5252	Sliding and swinging
Y10T 70/5257	Combination operable only
Y10T 70/5261	Key operable only
Y10T 70/5265	Sliding and rotary
Y10T 70/527	Sliding
Y10T 70/5274	Combination operable only

Y10T 70/5279	Key operable only
Y10T 70/5283	Swinging
Y10T 70/5288	Combination operable only
Y10T 70/5292	Key operable only
Y10T 70/5296	Single
Y10T 70/5301	Sliding and swinging
Y10T 70/5305	Combination operable only
Y10T 70/531	Key operable only
Y10T 70/5314	Sliding and rotary
Y10T 70/5319	Sliding
Y10T 70/5323	Multidirectional displacement
Y10T 70/5327	Keeper interlocking
Y10T 70/5332	Curved
Y10T 70/5336	Combination operable only
Y10T 70/5341	Key operable only
Y10T 70/5345	Swinging
Y10T 70/535	Keeper and housing interlocking
Y10T 70/5354	With hooked end
Y10T 70/5358	Combination operable only
Y10T 70/5363	Key operable only
Y10T 70/5367	Screw
Y10T 70/5372	Locking latch bolts, biased
Y10T 70/5376	Keeper interlocking
Y10T 70/5381	Projectable beyond normal biased position
Y10T 70/5385	Spring projected
Y10T 70/5389	Manually operable
Y10T 70/5394	Directly acting dog for exterior, manual, bolt manipulator
Y10T 70/5398	Related dog for interior, manual, bolt manipulator
Y10T 70/5403	Dog having a dog
Y10T 70/5407	Related dogging means for latch-bolt
Y10T 70/5412	Dog and dog actuator always interconnected
Y10T 70/5416	Exterior manipulator declutched from bolt when dogged
Y10T 70/542	Manual dog-controller concentric with bolt manipulator
Y10T 70/5425	Shiftable rollback serves as dog
Y10T 70/5429	Additional dog-controller key actuated for dogging and undogging
Y10T 70/5434	Dog-controller axially slidable and axially rotatable
Y10T 70/5438	Dog-controller rotatable
Y10T 70/5442	Key-actuated lock releases dog
Y10T 70/5447	Manual bolt-manipulator operation releases dog

Y10T 70/5451	Manual bolt-manipulator operation releases dog
Y10T 70/5456	Interior manual bolt-manipulator serves as dog-controller
Y10T 70/546	For both dogging and undogging
Y10T 70/5465	Manual dog-controller
Y10T 70/5469	With additional lock actuated dog-controller
Y10T 70/5473	Additional dog-controller controls both dogging and undogging
Y10T 70/5478	Accessible at door edge
Y10T 70/5482	Slidable only
Y10T 70/5487	Manual bolt-manipulator is slidable only
Y10T 70/5491	Manual bolt-manipulator is lever
Y10T 70/5496	Freely movable external manipulator
Y10T 70/55	Dogged bolt or connections
Y10T 70/5504	Automatic
Y10T 70/5509	Snub bolt
Y10T 70/5513	By manipulator
Y10T 70/5518	Connections only
Y10T 70/5522	Gravity projected
Y10T 70/5527	Projecting mechanism is lock controlled
Y10T 70/5531	Combination and/or key operable
Y10T 70/5535	Trip release
Y10T 70/554	Cover, lid, cap, encasing shield
Y10T 70/5544	Pivoted
Y10T 70/5549	Cover-carried lock
Y10T 70/5553	Dead bolt
Y10T 70/5558	Latching bolt
Y10T 70/5562	Removable
Y10T 70/5566	External locking devices
Y10T 70/5571	Freely movable when locked
Y10T 70/5575	Directly seating
Y10T 70/558	Cover-carried lock
Y10T 70/5584	Dead bolt
Y10T 70/5589	Latching bolt
Y10T 70/5593	Movably seating
Y10T 70/5597	Cover-carried lock
Y10T 70/5602	Dead bolt
Y10T 70/5606	Latching bolt
Y10T 70/5611	For control and machine elements
Y10T 70/5615	Valve
Y10T 70/5619	Locked stationary

Y10T 70/5624	Externally mounted locking device
Y10T 70/5628	Valve encasing
Y10T 70/5633	Housing-carried lock
Y10T 70/5637	With padlock
Y10T 70/5642	Rod
Y10T 70/5646	Rotary shaft
Y10T 70/565	Locked stationary
Y10T 70/5655	Housing-carried lock
Y10T 70/5659	Dead bolt
Y10T 70/5664	Latching bolt
Y10T 70/5668	Shaft-carried lock
Y10T 70/5673	Freely movable when locked
Y10T 70/5677	Shaft-carried clutch
Y10T 70/5681	Gear
Y10T 70/5686	Planetary
Y10T 70/569	Lever
Y10T 70/5695	Guide
Y10T 70/5699	Quadrant
Y10T 70/5704	Lever-carried lock
Y10T 70/5708	Fixed lever-receiving keeper
Y10T 70/5712	Lever-carried lock
Y10T 70/5717	Multiple
Y10T 70/5721	Externally mounted locking device
Y10T 70/5726	With padlock
Y10T 70/573	Single
Y10T 70/5735	Externally mounted locking device
Y10T 70/5739	With padlock
Y10T 70/5743	Disconnectable
Y10T 70/5748	Foldable
Y10T 70/5752	Universal mounting
Y10T 70/5757	Handle, handwheel or knob
Y10T 70/5761	Retractable or flush handle
Y10T 70/5765	Rotary or swinging
Y10T 70/577	Locked stationary
Y10T 70/5774	Externally mounted locking device
Y10T 70/5779	With padlock
Y10T 70/5783	Combination lock
Y10T 70/5788	Push pin or button
Y10T 70/5792	Handle-carried key lock
Y10T 70/5796	Coaxially mounted

Y10T 70/5801	Axially movable bolt
Y10T 70/5805	Freely movable when locked
Y10T 70/581	Combination lock
Y10T 70/5814	Push pin or button
Y10T 70/5819	Handle-carried key lock
Y10T 70/5823	Coaxial clutch connection
Y10T 70/5827	Axially movable clutch
Y10T 70/5832	Lock and handle assembly
Y10T 70/5836	Wheel
Y10T 70/5841	Rotation blocking
Y10T 70/5845	Spoke gap traversing type
Y10T 70/585	Brake type
Y10T 70/5854	Bolt, nut, stud, stud-cap
Y10T 70/5858	Locked stationary
Y10T 70/5863	Freely movable when locked
Y10T 70/5867	Encased
Y10T 70/5872	For cycles
Y10T 70/5876	Anchors
Y10T 70/5881	Stands
Y10T 70/5885	Drive
Y10T 70/5889	For automotive vehicles
Y10T 70/5894	Plural point
Y10T 70/5898	With switch
Y10T 70/5903	Hood
Y10T 70/5907	With switch
Y10T 70/5912	Fuel valve
Y10T 70/5916	With switch
Y10T 70/592	Cap combined
Y10T 70/5925	Transmission
Y10T 70/5929	Cover combined
Y10T 70/5934	Selective-type shift rod, fork or block
Y10T 70/5938	With switch
Y10T 70/5942	Planetary type
Y10T 70/5947	With switch
Y10T 70/5951	With switch
Y10T 70/5956	Steering mechanism with switch
Y10T 70/596	Pilot wheel control or linkage
Y10T 70/5965	Control levers with switch
Y10T 70/5969	Other element with switch
Y10T 70/5973	Remote control

Y10T 70/5978 With switch
Y10T 70/5982	. . . Accessories
Y10T 70/5987 Spare or mounted wheel or tire
Y10T 70/5991 Tire or rim only
Y10T 70/5996	. . For seats
Y10T 70/60	. Systems
Y10T 70/625	. . Operation and control
Y10T 70/65	. . . Central control
Y10T 70/675	. . . Serially operable
Y10T 70/70	. Operating mechanism
Y10T 70/7006	. . Predetermined time interval controlled
Y10T 70/7011	. . . Positively initiated delay interval
Y10T 70/7017 Interval terminating
Y10T 70/7023 Repeating interval
Y10T 70/7028	. . . Electric
Y10T 70/7034	. . . Clockwork control
Y10T 70/704 Continuously operating once initiated
Y10T 70/7045 Emergency release
Y10T 70/7051	. . Using a powered device [e.g., motor]
Y10T 70/7057	. . . Permanent magnet
Y10T 70/7062	. . . Electrical type [e.g., solenoid]
Y10T 70/7068 Actuated after correct combination recognized [e.g., numerical, alphabetical, or magnet[s] pattern]
Y10T 70/7073 Including use of a key
Y10T 70/7079 Key rotated [e.g., Eurocylinder]
Y10T 70/7085 Using a dial having indicia or pointer and indicia
Y10T 70/709 Plural interdependent or plural independently operable tumbler sets
Y10T 70/7096 With mechanism having rocker arm or linked bars
Y10T 70/7102 And details of blocking system [e.g., linkage, latch, pawl, spring]
Y10T 70/7107 And alternately mechanically actuated by a key, dial, etc.
Y10T 70/7113 Projected and retracted electrically
Y10T 70/7119 Projected electrically only
Y10T 70/7124 Retracted electrically only
Y10T 70/713 Dogging manual operator
Y10T 70/7136 Key initiated actuation of device
Y10T 70/7141	. . Combination and key
Y10T 70/7147	. . Combination or key
Y10T 70/7153	. . Combination
Y10T 70/7158	. . . Individual blocking elements
Y10T 70/7164 Selectively operable

Y10T 70/7169	. . .	Complex movement or puzzle type
Y10T 70/7175	Labyrinthian passage
Y10T 70/7181	. . .	Tumbler type
Y10T 70/7186	Plural interdependent sets
Y10T 70/7192	Plural independently operable sets
Y10T 70/7198	Single tumbler set
Y10T 70/7203	With ball or roller
Y10T 70/7209	Intersect sliding tumblers
Y10T 70/7215	Individually set sliding tumblers
Y10T 70/722	Manually operable
Y10T 70/7226	Associated movable operator
Y10T 70/7232	Removable
Y10T 70/7237	Rotary or swinging tumblers
Y10T 70/7243	Intersect tumblers
Y10T 70/7249	Tumblers released
Y10T 70/7254	Fence held spaced from tumblers
Y10T 70/726	Individually set
Y10T 70/7266	Movable selector
Y10T 70/7271	Associated movable operator
Y10T 70/7277	Removable
Y10T 70/7282	Pin or rod and slot
Y10T 70/7288	Spindle operator
Y10T 70/7294	Concentric spindles
Y10T 70/7299	Axially shiftable spindle
Y10T 70/7305	Manually operable
Y10T 70/7311	. . .	Step-by-step
Y10T 70/7316	. . .	Combination upsetting
Y10T 70/7322	. . .	Permutation
Y10T 70/7328	Compound tumblers
Y10T 70/7333	With fastener or holder
Y10T 70/7339	Pin and socket
Y10T 70/7345	Removable change element
Y10T 70/735	. . .	Operating elements
Y10T 70/7356	Fences
Y10T 70/7362	Bolt or lock housing supported
Y10T 70/7367	Tumbler structure and position
Y10T 70/7373	Nested
Y10T 70/7379	Variant diameter
Y10T 70/7384	Mounts
Y10T 70/739	Motion-restraining means

Y10T 70/7395	Friction holder
Y10T 70/7401	Spindles
Y10T 70/7407	Operating indicators
Y10T 70/7412	Portable combination setting guide
Y10T 70/7418	Dials
Y10T 70/7424	Tampering prevention or attach defeating
Y10T 70/7429	Resonance type
Y10T 70/7435	Hidden or covered dial
Y10T 70/7441	Key
Y10T 70/7446	Multiple keys
Y10T 70/7452	Selective shutout type
Y10T 70/7458	Interdependent
Y10T 70/7463	Master- and change-key
Y10T 70/7469	Change-key shutout
Y10T 70/7475	Submaster- and change-key
Y10T 70/748	Change-key shutout
Y10T 70/7486	Single key
Y10T 70/7492	Tumblerless push or pull key
Y10T 70/7497	Tumblerless warded
Y10T 70/7503	Tumbler and ward type
Y10T 70/7508	Tumbler type
Y10T 70/7514	Sliding and rotary or swinging tumblers
Y10T 70/752	Sliding tumblers
Y10T 70/7525	Longitudinal
Y10T 70/7531	Transverse
Y10T 70/7537	Rotary or swinging tumblers
Y10T 70/7542	Single set
Y10T 70/7548	Directly key engaged
Y10T 70/7554	Cylinder type with auxiliary tumblers or wards
Y10T 70/7559	Cylinder type
Y10T 70/7565	Plural tumbler sets
Y10T 70/7571	Concentric tumblers
Y10T 70/7576	Sliding and rotary plug
Y10T 70/7582	Sliding plug
Y10T 70/7588	Rotary plug
Y10T 70/7593	Sliding tumblers
Y10T 70/7599	Transverse of plug
Y10T 70/7605	Pin tumblers
Y10T 70/761	Rotatable pins [e.g., MEDECO lock]
Y10T 70/7616	Including sidebar

Y10T 70/7621	Including sidebar
Y10T 70/7627	Rotary or swinging tumblers
Y10T 70/7633	Transverse of plug
Y10T 70/7638	Cylinder and plug assembly
Y10T 70/7644	Key- and tool-controlled
Y10T 70/765	Key only controlled
Y10T 70/7655	Cylinder attaching or mounting means
Y10T 70/7661	Detachable or removable cylinder
Y10T 70/7667	Operating elements, parts and adjuncts
Y10T 70/7672	Cylinder
Y10T 70/7678	Adjustable
Y10T 70/7684	Plug
Y10T 70/7689	Tumblers
Y10T 70/7695	Plate
Y10T 70/7701	Pin
Y10T 70/7706	Operating connections
Y10T 70/7712	Rollbacks
Y10T 70/7718	Intermediate
Y10T 70/7723	Cylinder rings
Y10T 70/7729	. . .	Permutation
Y10T 70/7734	Automatically key set combinations
Y10T 70/774	Adjustable tumblers
Y10T 70/7746	Removable change element
Y10T 70/7751	. . .	With ball or roller
Y10T 70/7757	. . .	Push or pull key operation
Y10T 70/7763	. . .	Key ejecting
Y10T 70/7768	. . .	Key-removal preventing
Y10T 70/7774	. . .	False or picking key trapping
Y10T 70/778	. . .	Operating elements
Y10T 70/7785	Tumblers
Y10T 70/7791	Keys
Y10T 70/7797	Picking
Y10T 70/7802	Multi-part structures
Y10T 70/7808	With foldable shank or stem
Y10T 70/7814	With extensible shank or stem
Y10T 70/7819	With slidable bit portion
Y10T 70/7825	With pivoted or swinging bit portion
Y10T 70/7831	Nested second key
Y10T 70/7836	Plural shanks, stems or bit wings
Y10T 70/7842	Single shank or stem

Y10T 70/7847	Round rigid
Y10T 70/7853	Tubular
Y10T 70/7859	Flat rigid
Y10T 70/7864	Cylinder lock type
Y10T 70/787	Irregular nonplanar or undulated
Y10T 70/7876	Bow or head
Y10T 70/7881	Bitting
Y10T 70/7887	Frangible
Y10T 70/7893	Permutation
Y10T 70/7898	Threaded
Y10T 70/7904	Magnetic features
Y10T 70/791	Ejecting feature
Y10T 70/7915	. . .	Tampering prevention or attack defeating
Y10T 70/7921	Armoring
Y10T 70/7927	Anti-jimmy
Y10T 70/7932	Anti-pick
Y10T 70/7938	Guard ward
Y10T 70/7944	Guard tumbler
Y10T 70/7949	Yielding or frangible connections
Y10T 70/7955	Keyhole guards
Y10T 70/796	Portable
Y10T 70/7966	Combination-controlled
Y10T 70/7972	Portable
Y10T 70/7977	Key-controlled
Y10T 70/7983	Portable
Y10T 70/7989	Key securers, fasteners or retainers
Y10T 70/7994	Portable
Y10T 70/80	. .	Parts, attachments, accessories and adjuncts
Y10T 70/8027	. .	Condition indicators
Y10T 70/8054	. . .	With recorder
Y10T 70/8081	Electric
Y10T 70/8108	Padlock
Y10T 70/8135	. . .	With register
Y10T 70/8162	Padlock
Y10T 70/8189	. . .	Contactual feeler
Y10T 70/8216	. . .	Tampering detector
Y10T 70/8243	With seal
Y10T 70/827	. . .	Attention-directing
Y10T 70/8297	. .	For combination-operated mechanism
Y10T 70/8324	. . .	Housings

Y10T 70/8351	. . .	Operating attachments
Y10T 70/8378	. . .	Knobs, hand grips, etc.
Y10T 70/8405	. . .	Combination finders
Y10T 70/8432	. .	For key-operated mechanism
Y10T 70/8459	. . .	Housings
Y10T 70/8486	Cylindrical
Y10T 70/8514	Face plate
Y10T 70/8541	Mounting arrangements
Y10T 70/8568	. . .	Escutcheons
Y10T 70/8595	. . .	Key guides, internal
Y10T 70/8622	. . .	Key insertion guides
Y10T 70/8649	. . .	Keyhole covers
Y10T 70/8676	. . .	Key holders
Y10T 70/8703	Flexible
Y10T 70/873	One-piece
Y10T 70/8757	Releasable catches
Y10T 70/8784	Parallel key loops, coaxially mounted, individually movable
Y10T 70/8811	. . .	Key identification
Y10T 70/8838	. .	Adjustment provisions
Y10T 70/8865	. .	Reversible structures
Y10T 70/8892	. .	Silencers or mufflers
Y10T 70/8919	. .	Antifriction provisions
Y10T 70/8946	. .	Emergency unlocking or release arrangements
Y10T 70/8973	. .	Mounting aids, guides and assistors

Former US Class 74 Series

Y10T 74/00	Machine element or mechanism
Y10T 74/10	. High frequency vibratory devices
Y10T 74/11	. Tripping mechanism
Y10T 74/111	. . Speed controlled
Y10T 74/113	. . . Valve gear trips [e.g., steam engine "Corliss" type]
Y10T 74/114	. . Retarded
Y10T 74/115	. . . Plural, sequential, trip actuations
Y10T 74/116	. . . Clock train
Y10T 74/118 Winding knob trip [e.g., alarm mechanism]
Y10T 74/119	. . Hit and miss
Y10T 74/12	. Gyroscopes
Y10T 74/1204	. . with caging or parking means
Y10T 74/1207	. . . Rotor spin and cage release type

Y10T 74/1211	. . . and resetting means
Y10T 74/1214	. . with gimbal lock preventing means
Y10T 74/1218	. . Combined
Y10T 74/1221	. . Multiple gyroscopes
Y10T 74/1225	. . . with rotor drives
Y10T 74/1229	. . Gyroscope control
Y10T 74/1232	. . . Erecting
Y10T 74/1236 by plural diverse forces
Y10T 74/1239 by jet
Y10T 74/1243 by weight
Y10T 74/1246 by friction
Y10T 74/125 by magnetic field
Y10T 74/1254 by motor torque
Y10T 74/1257	. . . Damping
Y10T 74/1261	. . with pick off
Y10T 74/1264	. . . Optical
Y10T 74/1268	. . . Pneumatic
Y10T 74/1271	. . . Conducting liquid
Y10T 74/1275	. . . Electrical
Y10T 74/1279	. . . Electrical and magnetic
Y10T 74/1282	. . with rotor drive
Y10T 74/1286	. . Vertical gyroscopes
Y10T 74/1289	. . Horizontal gyroscopes
Y10T 74/1293	. . Flexure hinges for gyros
Y10T 74/1296	. . Flywheel structure
Y10T 74/13	. Machine starters
Y10T 74/131	. . Automatic
Y10T 74/132	. . . Separate power mesher
Y10T 74/133	. . . Holders
Y10T 74/134	. . . Clutch connection
Y10T 74/136	. . . Worm and wheel
Y10T 74/137	. . . Reduction gearing
Y10T 74/138	. . Radial meshing
Y10T 74/139	. . Cam operated
Y10T 74/14	. Rotary member or shaft indexing, e.g., tool or work turret
Y10T 74/1406	. . with safety device or drive disconnect
Y10T 74/1412	. . with locating point adjusting
Y10T 74/1418	. . Preselected indexed position
Y10T 74/1424	. . . Sequential
Y10T 74/1429 Skip position

Y10T 74/1435 Held by torque
Y10T 74/1441 Geneva or mutilated gear drive
Y10T 74/1447 Velocity control
Y10T 74/1453 Interlocked rotator and brake
Y10T 74/1459 Diverse-type brakes
Y10T 74/1465 with axially acting friction brake
Y10T 74/1471	. . Plural operators or input drives
Y10T 74/1476	. . with means to axially shift shaft
Y10T 74/1482	. . Single revolution input effects desired fractional output
Y10T 74/1488	. . Control means
Y10T 74/1494	. . Locking means
Y10T 74/15	. Intermittent grip type mechanical movement
Y10T 74/1502	. . Escapement
Y10T 74/1503	. . Rotary to intermittent unidirectional motion
Y10T 74/1505	. . . Automatically controlled
Y10T 74/1506 Speed
Y10T 74/1508	. . . Rotary crank or eccentric drive
Y10T 74/151 Adjustable
Y10T 74/1511 Lever transmitter
Y10T 74/1513 Adjustable leverage
Y10T 74/1515 Rack and pinion transmitter
Y10T 74/1516 Adjustable throw
Y10T 74/1518 Rotary cam drive
Y10T 74/1519 Adjustable throw
Y10T 74/1521 Radial cam
Y10T 74/1523 Radial cam
Y10T 74/1524	. . . Intermittently engaged clutch
Y10T 74/1526	. . Oscillation or reciprocation to intermittent unidirectional motion
Y10T 74/1527	. . . Screw and nut devices
Y10T 74/1529	. . . Slide actuator
Y10T 74/1531 Multiple acting
Y10T 74/1532	. . . Rack actuator
Y10T 74/1534 Multiple acting
Y10T 74/1535 Inwardly facing racks
Y10T 74/1537 Oscillating
Y10T 74/1539 Multiple acting
Y10T 74/154 Inwardly facing racks
Y10T 74/1542	. . . Strap actuator
Y10T 74/1544 Multiple acting
Y10T 74/1545 Spring or weight return

Y10T 74/1547 Single acting
Y10T 74/1548 Engine starter type
Y10T 74/155 Spring or weight return
Y10T 74/1552 Spring or weight return
Y10T 74/1553 Lever actuator
Y10T 74/1555 Rotary driven element
Y10T 74/1556 Multiple acting
Y10T 74/1558	. . . Grip units and features
Y10T 74/156 Compound movement handle
Y10T 74/1561 Reversible
Y10T 74/1563 Transverse pivots
Y10T 74/1565 Gripper releasing devices
Y10T 74/1566 Power pawl lifter
Y10T 74/1568 Automatic
Y10T 74/1569 Idle stroke
Y10T 74/1571 Cooperating holding pawl
Y10T 74/1573 Power stroke
Y10T 74/1574 Cooperating holding pawl
Y10T 74/1576 Holding pawl lifter
Y10T 74/1577 Gripper mountings, lever
Y10T 74/1579 Reversible
Y10T 74/1581 Multiple acting
Y10T 74/1582 Single ratchet or clutch
Y10T 74/1584 Gripper mountings, slide
Y10T 74/1585 Multiple acting
Y10T 74/1587 Grip features
Y10T 74/1589 Driving band
Y10T 74/159 Clamping
Y10T 74/1592 Driven band and gripper
Y10T 74/1594 Positive grip
Y10T 74/1595 Driving ratchet-bar or rack
Y10T 74/1597 Multiple acting
Y10T 74/1598 Driven ratchet-bar and power dog
Y10T 74/16	. Alternating-motion driven device with means during operation to adjust stroke
Y10T 74/1608	. . . Constant length stroke with means to displace end limits
Y10T 74/1616	. . . Cyclical displacement responsive to the alternating-motion
Y10T 74/1625	. . . Stroke adjustable to zero and/or reversible in phasing
Y10T 74/1633	. . . Plural driving means to jointly drive the driven device
Y10T 74/1642	. . . Device driven from selected points on oscillating link
Y10T 74/165	. . . Driving lever with adjustable pivot point

Y10T 74/1658	. . . Eccentric and strap drive, shiftable eccentric
Y10T 74/1667 Changing the extent of eccentricity
Y10T 74/1675	. . . Crank pin drive, shiftable pin
Y10T 74/1683	. . . Cam and follower drive
Y10T 74/1692 Axial-type cam [e.g., wabblor type]
Y10T 74/17	. Rotary driven device adjustable during operation relative to its supporting structure
Y10T 74/173	. . Screw and nut adjusting means
Y10T 74/177	. . Rack and pinion adjusting means
Y10T 74/18	. Mechanical movements
Y10T 74/18008	. . Oscillating to reciprocating and alternating rotary
Y10T 74/18016	. . Oscillating to reciprocating and intermittent rotary
Y10T 74/18024	. . Rotary to reciprocating and rotary
Y10T 74/18032	. . . Rotary to reciprocating or rotary
Y10T 74/1804	. . Rotary to reciprocating and alternating rotary
Y10T 74/18048	. . Rotary to reciprocating and intermittent rotary
Y10T 74/18056	. . Rotary to or from reciprocating or oscillating
Y10T 74/18064	. . . Head motions
Y10T 74/18072	. . . Reciprocating carriage motions
Y10T 74/1808 Phonograph type
Y10T 74/18088	. . . Rack and pinion type
Y10T 74/18096 Shifting rack
Y10T 74/18104 Shiftable pinion
Y10T 74/18112 Segmental pinion
Y10T 74/1812 Alternately rotated pinion
Y10T 74/18128 Clutchable gears
Y10T 74/18136 Bevel
Y10T 74/18144	. . . Overcoming dead center
Y10T 74/18152	. . . Belt or chain carried member
Y10T 74/1816	. . . Crank, lever, toggle, and slide
Y10T 74/18168	. . . Crank, lazy-tong, and slide
Y10T 74/18176	. . . Crank, pitman, lever, and slide
Y10T 74/18182 Pump jack type
Y10T 74/18184	. . . Crank, pitman, and lever
Y10T 74/182 Multiple levers
Y10T 74/18208	. . . Crank, pitman, and slide
Y10T 74/18216	. . . Crank, lever, and slide
Y10T 74/18224 Rack connections
Y10T 74/18232	. . . Crank and lever
Y10T 74/1824 Slidable connections
Y10T 74/18248	. . . Crank and slide

Y10T 74/18256	Slidable connections [e.g., scotch yoke]
Y10T 74/18264	. . .	Crank and multiple pitmans
Y10T 74/18272	. . .	Planetary gearing and slide
Y10T 74/1828	. . .	Cam, lever, and slide
Y10T 74/18288	. . .	Cam and lever
Y10T 74/18296	. . .	Cam and slide
Y10T 74/18304	Axial cam
Y10T 74/18312	Grooved
Y10T 74/1832	Multiple screw
Y10T 74/18328	Alternately rotated screw
Y10T 74/18336	Wabblers type
Y10T 74/18344	. . .	Unbalanced weights
Y10T 74/18352	. . .	Trammel-pitman
Y10T 74/1836	. .	Rotary to rotary
Y10T 74/18368	. . .	Inertia or centrifugal transmitters
Y10T 74/18376	. . .	Crank, pitman, lever, and crank
Y10T 74/18384	. . .	Crank, lever, and crank
Y10T 74/18392	. . .	Crank, pitman, and crank
Y10T 74/184	. . .	Cranks, link connected
Y10T 74/18408	. . .	Cranks, slidable connections
Y10T 74/18416	. .	Rotary to alternating rotary
Y10T 74/18424	. . .	Mangle connections
Y10T 74/18432	Shiftable driven gear
Y10T 74/1844	Central teeth
Y10T 74/18448	Mutilated gearing connections
Y10T 74/18456	. . .	Crank, pitman, and lever
Y10T 74/18464	. . .	Reciprocating rack connections
Y10T 74/18472	Crank and pitman actuator
Y10T 74/1848	Simple crank actuator
Y10T 74/18488	. . .	Oscillating rack connections
Y10T 74/18496	Mangle actuated
Y10T 74/18504	Crank and pitman actuator
Y10T 74/18512	. . .	Flexible connector type
Y10T 74/1852	. . .	Associated inertia devices
Y10T 74/18528	. .	Rotary to intermittent unidirectional motion
Y10T 74/18536	. . .	Space machines
Y10T 74/18544	. .	Rotary to gyratory
Y10T 74/18552	. . .	Unbalanced weight
Y10T 74/1856	. .	Reciprocating or oscillating to intermittent unidirectional motion
Y10T 74/18568	. .	Reciprocating or oscillating to or from alternating rotary

Y10T 74/18576	. . .	including screw and nut
Y10T 74/18584	Shaft shorter than nut
Y10T 74/18592	Auxiliary drive [e.g., fluid piston, etc.] for load
Y10T 74/186	Alternate power path operable on failure of primary
Y10T 74/18608	Single input split into two intermediate outputs that are subsequently superposed into a single output
Y10T 74/18616	Single input, plural outputs
Y10T 74/18624	Plural inputs, single output
Y10T 74/18632	Plural nuts driving shaft
Y10T 74/1864	Shaft and nut driven
Y10T 74/18648	Carriage surrounding, guided by, and primarily supported by member other than screw [e.g., linear guide, etc.]
Y10T 74/18656	Carriage surrounded, guided, and primarily supported by member other than screw [e.g., linear guide, etc.]
Y10T 74/18664	Shaft moves through rotary drive means
Y10T 74/18672	Plural screws in series [e.g., telescoping, etc.]
Y10T 74/1868	Deflection related
Y10T 74/18688	Limit stop
Y10T 74/18696	including means to selectively transmit power [e.g., clutch, etc.]
Y10T 74/18704	Means to selectively lock or retard screw or nut
Y10T 74/18712	Contamination related
Y10T 74/1872	Imperforate enclosure
Y10T 74/18728	Backlash
Y10T 74/18736	Pressurized fluid introduced between nut and screw
Y10T 74/18744	Lubrication
Y10T 74/18752	Manually driven
Y10T 74/1876	. . .	including inertia device
Y10T 74/18768	with rack and pinion
Y10T 74/18776	Rectilinear rack
Y10T 74/18784	. . .	including bevel gears
Y10T 74/18792	. . .	including worm
Y10T 74/188	. . .	including spur gear
Y10T 74/18808	with rack
Y10T 74/18816	Curvilinear rack
Y10T 74/18824	with biasing means
Y10T 74/18832	. . .	including flexible drive connector [e.g., belt, chain, strand, etc.]
Y10T 74/1884	with sprocket wheel
Y10T 74/18848	with pulley
Y10T 74/18856	. .	Oscillating to oscillating
Y10T 74/18864	. . .	Snap action
Y10T 74/18872	Plate spring

Y10T 74/1888	. . . Geared connections
Y10T 74/18888	. . Reciprocating to or from oscillating
Y10T 74/18896	. . . Snap action
Y10T 74/18904 Plate spring
Y10T 74/18912	. . . Compound lever and slide
Y10T 74/1892	. . . Lever and slide
Y10T 74/18928 Straight line motions
Y10T 74/18936 Slidable connections
Y10T 74/18944 Link connections
Y10T 74/18952 toggle transmissions
Y10T 74/1896 Cam connections
Y10T 74/18968 Flexible connections
Y10T 74/18976	. . . Rack and pinion
Y10T 74/18984	. . . Inclined ramp
Y10T 74/18992	. . Reciprocating to reciprocating
Y10T 74/19	. Gearing
Y10T 74/19005	. . Nonplanetary gearing differential type [e.g., gearless differentials]
Y10T 74/19009	. . Single gearing unit includes fluid drive
Y10T 74/19014	. . Plural prime movers selectively coupled to common output
Y10T 74/19019	. . Plural power paths from prime mover
Y10T 74/19023	. . Plural power paths to and/or from gearing
Y10T 74/19028	. . . Alternate input connections single hand crank
Y10T 74/19033	. . . Fluid drive divides or combines alternate paths
Y10T 74/19037	. . . One path includes fluid drive
Y10T 74/19042	. . . Friction-type gearing
Y10T 74/19047	. . . Worm-type gearing
Y10T 74/19051	. . . Single driven plural drives
Y10T 74/19056 Parallel
Y10T 74/1906 Nonparallel
Y10T 74/19065 Aligned
Y10T 74/1907 Parallel and aligned
Y10T 74/19074	. . . Single drive plural driven
Y10T 74/19079 Parallel
Y10T 74/19084 Spur
Y10T 74/19088 Bevel
Y10T 74/19093 Spur and bevel
Y10T 74/19098 Helical
Y10T 74/19102 Belt or chain
Y10T 74/19107 Nonparallel
Y10T 74/19112 Aligned

Y10T 74/19116 Vehicle
Y10T 74/19121 Concentric
Y10T 74/19126 Plural drivers plural driven
Y10T 74/1913 Bevel
Y10T 74/19135 Spur
Y10T 74/1914 Alternate drivers and driven
Y10T 74/19144 Miscellaneous [plural power paths]
Y10T 74/19149 with fluid drive
Y10T 74/19153 Condition responsive control
Y10T 74/19158 with one or more controllers for gearing, fluid drive, or clutch
Y10T 74/19163 with interrelated controls
Y10T 74/19167 In series plural interchangeably locked nonplanetary units
Y10T 74/19172 Reversal of direction of power flow changes power transmission to alternate path
Y10T 74/19177 Input and output exchange functions
Y10T 74/19181 toothed gear and recirculated unconnected elements
Y10T 74/19186 Alternating rotary or continuous
Y10T 74/19191 Alternating rotary
Y10T 74/19195 Progressive
Y10T 74/192 Shiftable and/or slidable gears
Y10T 74/19205 Clutchable gears
Y10T 74/1921 On single driven member
Y10T 74/19214 On single driving member
Y10T 74/19219 Interchangeably locked
Y10T 74/19223 Disconnectable counter shaft
Y10T 74/19228 Multiple concentric clutch shafts
Y10T 74/19233 Plurality of counter shafts
Y10T 74/19237 Internal-external gears
Y10T 74/19242 Combined gear and clutch
Y10T 74/19247 Preselector
Y10T 74/19251 Control mechanism
Y10T 74/19256 Automatic
Y10T 74/1926 Speed responsive
Y10T 74/19265 Governor
Y10T 74/1927 with belt gearing
Y10T 74/19274 torque responsive
Y10T 74/19279 Cam operated
Y10T 74/19284 Meshing assisters
Y10T 74/19288 Double clutch and interposed transmission
Y10T 74/19293 Longitudinally slidable
Y10T 74/19298 Multiple spur gears

Y10T 74/19302	with tumbler gear
Y10T 74/19307	Selective
Y10T 74/19312	Direct clutch and drive
Y10T 74/19316	Progressive
Y10T 74/19321	Direct clutch and drive
Y10T 74/19326	Fluid operated
Y10T 74/1933	Multiple bevel gears
Y10T 74/19335	Single spur gear
Y10T 74/1934	Tumbler and cone
Y10T 74/19344	Multiple cone
Y10T 74/19349	Single bevel gear
Y10T 74/19353	Pin or crown gears
Y10T 74/19358	Laterally slidable gears
Y10T 74/19363	Rotary carriage
Y10T 74/19367	Swinging carriage
Y10T 74/19372	Single forward and reverse speeds
Y10T 74/19377	Slidable keys or clutches
Y10T 74/19381	Alternative clutch shaft
Y10T 74/19386	Multiple clutch shafts
Y10T 74/19391	Progressive
Y10T 74/19395	Keys simultaneously slidable
Y10T 74/194	Selective
Y10T 74/19405	Multiple forward and reverse
Y10T 74/19409	Single forward and reverse
Y10T 74/19414	Single clutch shaft
Y10T 74/19419	Progressive
Y10T 74/19423	Multiple key
Y10T 74/19428	Spur
Y10T 74/19433	Fluid operated
Y10T 74/19437	Electrically operated
Y10T 74/19442	Single key
Y10T 74/19447	Clutch and ratchet
Y10T 74/19451	Spur gears
Y10T 74/19456	Intermediate clutch
Y10T 74/1946	Sliding clutch carrier
Y10T 74/19465	Sliding clutch operator
Y10T 74/1947	Selective
Y10T 74/19474	Multiple key
Y10T 74/19479	Spur gears
Y10T 74/19484	Single speed forward and reverse

Y10T 74/19488	Spur gears
Y10T 74/19493	Bevel gears
Y10T 74/19498	Bevel and idler gears
Y10T 74/19502	. . .	Pivotally supported
Y10T 74/19507	. . .	Windmill turntable
Y10T 74/19512	. . .	Screw
Y10T 74/19516	. . .	Spur
Y10T 74/19521	. . .	Bevel
Y10T 74/19526	Wheel type
Y10T 74/1953	Wringer type
Y10T 74/19535	. . .	Follow-up mechanism
Y10T 74/1954	. . .	Eccentric driving shaft and axle
Y10T 74/19545	. . .	Central driving shaft in axle
Y10T 74/1955	. . .	Parallel shafts, adjustable gear mesh
Y10T 74/19555	. . .	Varying speed ratio
Y10T 74/1956	. . .	Adjustable
Y10T 74/19565	Relative movable axes
Y10T 74/1957	Parallel shafts
Y10T 74/19575	Automatic control
Y10T 74/1958	Parallel shafts
Y10T 74/19585	Fixed axes
Y10T 74/1959	Parallel shafts
Y10T 74/19595	Automatic control
Y10T 74/196	Parallel shafts
Y10T 74/19605	. . .	Reversing means
Y10T 74/19609	. . .	Governor control
Y10T 74/19614	. . .	Disconnecting means
Y10T 74/19619	. . .	Displaceable elements
Y10T 74/19623	. . .	Backlash take-up
Y10T 74/19628	. . .	Pressure distributing
Y10T 74/19633	. . .	Yieldability in gear trains
Y10T 74/19637	. . .	with brake means for gearing
Y10T 74/19642	. . .	Directly cooperating gears
Y10T 74/19647	Parallel axes or shafts
Y10T 74/19651	External type
Y10T 74/19656	Pin teeth
Y10T 74/1966	Intersecting axes
Y10T 74/19665	Bevel gear type
Y10T 74/1967	Rack and pinion
Y10T 74/19674	Spur and bevel

Y10T 74/19679	. . .	Spur
Y10T 74/19684	Motor and gearing
Y10T 74/19688	. . .	Bevel
Y10T 74/19693	Motor vehicle drive
Y10T 74/19698	. . .	Spiral
Y10T 74/19702	Screw and nut
Y10T 74/19707	Plural longitudinally variably spaced nuts
Y10T 74/19712	Threadless
Y10T 74/19716	Non-linear screw
Y10T 74/19721	Thread geometry
Y10T 74/19726	Thread pitch varies over axial length
Y10T 74/1973	Shaft thread is spirally wound wire
Y10T 74/19735	Nut disengageable from screw
Y10T 74/1974	Nut segments hinged parallel to shaft [e.g., clam shell-type, etc.]
Y10T 74/19744	Rolling element engaging thread
Y10T 74/19749	Recirculating rolling elements
Y10T 74/19753	Plural independent recirculating element paths
Y10T 74/19758	Single thread common to plural paths
Y10T 74/19763	Roller return path in shaft
Y10T 74/19767	Return path geometry
Y10T 74/19772	Rolling element deflector
Y10T 74/19777	Interconnected or cooperating rollers or roller structure
Y10T 74/19781	Non-recirculating rolling elements
Y10T 74/19786	Captured sphere
Y10T 74/19791	Cylindrical or quasi-cylindrical roller element [e.g., inclined roller, etc.]
Y10T 74/19795	Parallel to shaft
Y10T 74/198	Perpendicular to shaft
Y10T 74/19805	Less than 360 degrees of contact between nut and screw
Y10T 74/19809	Independent nut segments
Y10T 74/19814	Integral deformable tangs engaging screw
Y10T 74/19819	Driven rack or shaft
Y10T 74/19823	Screw
Y10T 74/19828	Worm
Y10T 74/19833	Variable speed
Y10T 74/19837	Intermittent motion
Y10T 74/19842	Distribution of pressure
Y10T 74/19847	. . .	torque actuated safety devices
Y10T 74/19851	. .	Gear and rotary bodies
Y10T 74/19856	. . .	Laterally-spaced wheels

Y10T 74/1986	. . .	Radially-spaced wheels
Y10T 74/19865	. . .	with flywheel
Y10T 74/1987	. .	Rotary bodies
Y10T 74/19874	. . .	Mutilated
Y10T 74/19879	. . .	Geneva
Y10T 74/19884	. . .	Irregular teeth and bodies
Y10T 74/19888	. . .	External and internal teeth
Y10T 74/19893	. . .	Sectional
Y10T 74/19898	Backlash take-up
Y10T 74/19902	Screw and nut
Y10T 74/19907	Sound deadening
Y10T 74/19912	Differential disks
Y10T 74/19916	Multiple disks
Y10T 74/19921	Separate rim
Y10T 74/19926	Detachable
Y10T 74/1993	Segmental rim
Y10T 74/19935	Sheet metal
Y10T 74/1994	Diametrically split
Y10T 74/19944	Shaft-admitting insert
Y10T 74/19949	. .	Teeth
Y10T 74/19953	. . .	Worm and helical
Y10T 74/19958	. . .	Bevel
Y10T 74/19963	. . .	Spur
Y10T 74/19967	Yieldable
Y10T 74/19972	form
Y10T 74/19977	Antifriction
Y10T 74/19981	Roller
Y10T 74/19986	Twisted
Y10T 74/19991	. .	Lubrication
Y10T 74/19995	. . .	Teeth
Y10T 74/20	. .	Control lever and linkage systems
Y10T 74/20006	. .	Resilient connections
Y10T 74/20012	. .	Multiple controlled elements
Y10T 74/20018	. . .	Transmission control
Y10T 74/20024	Fluid actuator
Y10T 74/2003	Electrical actuator
Y10T 74/20037	Occupant propelled vehicle
Y10T 74/20043	Transmission controlled by flexible cable
Y10T 74/20049	Transmission controlled by flexible cable
Y10T 74/20055	Foot operated

Y10T 74/20061	Multiple foot-operated controls
Y10T 74/20067	Control convertible between automatic and manual operation
Y10T 74/20073	Control of plural mechanisms [e.g., control of transmission and control of 4 - wheel drive]
Y10T 74/20079	Separate control levers
Y10T 74/20085	Restriction of shift, gear selection, or gear engagement
Y10T 74/20091	Prevention of reverse shift
Y10T 74/20098	Separate actuator to disengage restrictor
Y10T 74/20104	Shift element interlock
Y10T 74/2011	with detent, recess, notch, or groove
Y10T 74/20116	Resiliently biased interlock
Y10T 74/20122	Spherical restrictor
Y10T 74/20128	Resiliently biased restrictor
Y10T 74/20134	having vibration damper
Y10T 74/2014	Manually operated selector [e.g., remotely controlled device, lever, push button, rotary dial, etc.]
Y10T 74/20146	Control lever on steering column
Y10T 74/20152	Control lever movable through plural planes
Y10T 74/20159	Control lever movable through plural planes
Y10T 74/20165	Spherical mount [e.g., ball and socket]
Y10T 74/20171	Resiliently biased control lever
Y10T 74/20177	Particular element [e.g., shift fork, template, etc.]
Y10T 74/20183	Shift fork structure
Y10T 74/20189	Foot operated
Y10T 74/20195	Offset extension
Y10T 74/20201	Control moves in two planes
Y10T 74/20207	Multiple controlling elements for single controlled element
Y10T 74/20213	Interconnected
Y10T 74/2022	Hand and foot
Y10T 74/20226	Accelerator
Y10T 74/20232	Marine
Y10T 74/20238	Interlocked
Y10T 74/20244	Push button
Y10T 74/2025	Rod blocks actuation of rotary member
Y10T 74/20256	Steering and controls assemblies
Y10T 74/20262	Rotary control shaft
Y10T 74/20268	Reciprocating control elements
Y10T 74/20274	Flexible
Y10T 74/2028	Handle bar type
Y10T 74/20287	Flexible control element

Y10T 74/20293	with horn control
Y10T 74/20299	. . .	Antirattling elements
Y10T 74/20305	. . .	Robotic arm
Y10T 74/20311	including power cable or connector
Y10T 74/20317	including electric motor
Y10T 74/20323	including flaccid drive element
Y10T 74/20329	Joint between elements
Y10T 74/20335	Wrist
Y10T 74/20341	. . .	Power elements as controlling elements
Y10T 74/20348	Planar surface with orthogonal movement and rotation
Y10T 74/20354	Planar surface with orthogonal movement only
Y10T 74/2036	Pair of power elements
Y10T 74/20366	. . .	Power and manual controlling elements
Y10T 74/20372	. . .	Manual controlling elements
Y10T 74/20378	Planar surface with orthogonal movement or rotation
Y10T 74/20384	Levers
Y10T 74/2039	Pair of levers
Y10T 74/20396	. .	Hand operated
Y10T 74/20402	. . .	Flexible transmitter [e.g., Bowden cable]
Y10T 74/20408	Constant tension sustaining
Y10T 74/20414	Hydraulic control
Y10T 74/2042	and hand operator
Y10T 74/20426	Slidable
Y10T 74/20432	for moving a mirror
Y10T 74/20438	Single rotatable lever [e.g., for bicycle brake or derailleur]
Y10T 74/20444	including rolling antifriction elements
Y10T 74/2045	and sheath support, connector, or anchor
Y10T 74/20456	Specific cable or sheath structure
Y10T 74/20462	Specific cable connector or guide
Y10T 74/20468	. . .	Sliding rod
Y10T 74/20474	. . .	Rotatable rod, shaft, or post
Y10T 74/2048	Gear, drum, and cable
Y10T 74/20486	Drum and cable
Y10T 74/20492	Gear
Y10T 74/20498	Variable ratio
Y10T 74/20504	Screw and nut
Y10T 74/2051	Adjustable
Y10T 74/20516	Mountings
Y10T 74/20522	Antenna
Y10T 74/20528	. .	Foot operated

Y10T 74/20534	. . .	Accelerator
Y10T 74/2054	. . .	Signal
Y10T 74/20546	. .	Knee operated
Y10T 74/20552	. . .	Elbow
Y10T 74/20558	. .	Variable output force
Y10T 74/20564	. . .	Flexible
Y10T 74/2057	. . .	Variable input leverage
Y10T 74/20576	. .	Elements
Y10T 74/20582	. . .	Levers
Y10T 74/20588	toggle
Y10T 74/20594	Lazy tongs
Y10T 74/206	Adjustable
Y10T 74/20606	Swing posts
Y10T 74/20612	Hand
Y10T 74/20618	Jointed
Y10T 74/20624	Adjustable
Y10T 74/2063	Stops
Y10T 74/20636	Detents
Y10T 74/20642	Hand crank
Y10T 74/20648	Interrelated lever release
Y10T 74/20654	Gear
Y10T 74/2066	Friction
Y10T 74/20666	Lever engaging
Y10T 74/20672	Lever engaging rack
Y10T 74/20678	Pivoted
Y10T 74/20684	Lever carried pawl
Y10T 74/2069	Handle release
Y10T 74/20696	Finger lever release
Y10T 74/20702	Slidable
Y10T 74/20708	Pedal controlled
Y10T 74/20714	Lever carried rack
Y10T 74/2072	Pivoted
Y10T 74/20726	Pedal controlled
Y10T 74/20732	. . .	Handles
Y10T 74/20738	Extension
Y10T 74/20744	Hand crank
Y10T 74/2075	Extensible
Y10T 74/20756	Collapsible
Y10T 74/20762	Shaft connections
Y10T 74/20768	Engine starter type

Y10T 74/20774	Holders
Y10T 74/2078	Handle bars
Y10T 74/20786	Spring biased or supported
Y10T 74/20792	Folding or adjustable
Y10T 74/20798	Sectional
Y10T 74/20804	Simultaneously movable
Y10T 74/2081	Continuous
Y10T 74/20816	with handle latch
Y10T 74/20822	Attachments and accessories
Y10T 74/20828	Handholds and grips
Y10T 74/20834	Hand wheels
Y10T 74/2084	Knob or dial
Y10T 74/20846	Slidable
Y10T 74/20852	Pivoted
Y10T 74/20858	Releasable
Y10T 74/20864	Handles
Y10T 74/2087	Rim grips and covers
Y10T 74/20876	Caps and covers
Y10T 74/20882	Rocker arms
Y10T 74/20888	Pedals
Y10T 74/20894	Treadles
Y10T 74/209	Extension
Y10T 74/20906	Offset
Y10T 74/20912	Pads and covers
Y10T 74/20918	Foot rests
Y10T 74/20924	Controller checks
Y10T 74/2093	Slot closers and lever guards
Y10T 74/21	Elements
Y10T 74/2101	Cams
Y10T 74/2102	Adjustable
Y10T 74/2104	Flexible strip
Y10T 74/2105	Memory devices
Y10T 74/2106	Timer devices
Y10T 74/2107	Follower
Y10T 74/2109	Balancing for drum, e.g., washing machine or arm-type structure, etc., centrifuge, etc.
Y10T 74/211	Eccentric
Y10T 74/2111	Plural, movable relative to each other [including ball[s]]
Y10T 74/2112	Concentric
Y10T 74/2114	Adjustable

Y10T 74/2115 Radially
Y10T 74/2116	. . . having anti-friction means, e.g., roller bearing, lubrication, etc.
Y10T 74/2117	. . Power generating-type flywheel
Y10T 74/2119	. . . Structural detail, e.g., material, configuration, superconductor, discs, laminated, etc.
Y10T 74/212 Containing fiber or filament
Y10T 74/2121	. . Flywheel, motion smoothing-type
Y10T 74/2122	. . . with fluid balancing means
Y10T 74/2123 and pressure compensation
Y10T 74/2125 and elastic device
Y10T 74/2126 and bearings
Y10T 74/2127	. . . with electrical or magnetic damping
Y10T 74/2128	. . . Damping using swinging masses, e.g., pendulum type, etc.
Y10T 74/213	. . . Damping by increasing frictional force
Y10T 74/2131	. . . Damping by absorbing vibration force [via rubber, elastomeric material, etc.]
Y10T 74/2132	. . . Structural detail, e.g., fiber, held by magnet, etc.
Y10T 74/2133	. . Pawls and ratchets
Y10T 74/2135	. . . Noiseless
Y10T 74/2136	. . . Pivoted pawls
Y10T 74/2137 Single tooth
Y10T 74/2138 Flexible single tooth
Y10T 74/214 Multiple tooth
Y10T 74/2141	. . . Sliding pawls
Y10T 74/2142	. . Pitmans and connecting rods
Y10T 74/2143	. . . Radial
Y10T 74/2144	. . . Yieldable
Y10T 74/2146 Longitudinal springs
Y10T 74/2147 Fluid cushion
Y10T 74/2148 Automatic release
Y10T 74/2149 toggle link type
Y10T 74/2151	. . . Longitudinally adjustable
Y10T 74/2152	. . . Hollow rod, lubricated
Y10T 74/2153	. . . Sheet metal type
Y10T 74/2154	. . . Counterbalanced
Y10T 74/2156 Weight type
Y10T 74/2157 Rotating
Y10T 74/2158 Spring
Y10T 74/2159	. . . Section coupled
Y10T 74/216	. . . Bearings, adjustable
Y10T 74/2162	. . . Engine type

Y10T 74/2163	. . . Idler arm
Y10T 74/2164	. . Cranks and pedals
Y10T 74/2165	. . . with attached gear
Y10T 74/2167	. . . Variable
Y10T 74/2168	. . . Pedals
Y10T 74/2169 Counterbalanced
Y10T 74/217 with toe or shoe clips
Y10T 74/2172 Adjustable or folding
Y10T 74/2173	. . Cranks and wrist pins
Y10T 74/2174	. . . Multiple throw
Y10T 74/2175 Sectional
Y10T 74/2177	. . . Sectional
Y10T 74/2178	. . . Yieldable
Y10T 74/2179	. . . Adjustable
Y10T 74/218 Automatically
Y10T 74/2181	. . . Variable
Y10T 74/2183	. . . Counterbalanced
Y10T 74/2184 Vibration dampers
Y10T 74/2185	. . . Lubricated
Y10T 74/2186	. . Gear casings
Y10T 74/2188	. . . Axle and torque tubes
Y10T 74/2189	. . . Cooling
Y10T 74/219	. . Guards
Y10T 74/2191	. . . for rotary member
Y10T 74/2193	. . Guard mechanisms
Y10T 74/2194	. . . Automatic
Y10T 74/2195 Oscillating member actuator
Y10T 74/2196 Reciprocating member actuator
Y10T 74/2198	. . . Operator controlled
Y10T 74/2199	. . . Set screw
Y10T 74/22	. Miscellaneous

Former US Class 82 Series

Y10T 82/00	Turning
Y10T 82/10	. Process of turning
Y10T 82/11	. Talking machine tablet
Y10T 82/12	. Radially moving rotating tool inside bore
Y10T 82/122	. . Forming non-circular bore
Y10T 82/125	. . Tool simultaneously moving axially

Y10T 82/128	. . . Pivoted to tool-carrier
Y10T 82/13	. Pattern section
Y10T 82/135	. . Cam-controlled cutter
Y10T 82/14	. Axial pattern
Y10T 82/141	. . having transverse tool and templet guide
Y10T 82/142	. . . with workpiece gauge
Y10T 82/143	. . . having electrical actuator
Y10T 82/145 And hydraulic actuator
Y10T 82/147	. . . having hydraulic actuator
Y10T 82/148	. . Pivoted tool rest
Y10T 82/149	. . Profiled cutter
Y10T 82/15	. Tapers
Y10T 82/152	. . Offset work axis
Y10T 82/154	. . Transversely shifted cutter
Y10T 82/156	. . . Templet controlled
Y10T 82/158	. . . Gear controlled
Y10T 82/16	. Severing or cut-off
Y10T 82/16016	. . Processes
Y10T 82/16032	. . Automatic and/or triggered control
Y10T 82/16049	. . Combined with means to sharpen tool[s]
Y10T 82/16065	. . Combined with means to apply fluid
Y10T 82/16081	. . Combined with means to heat tool and/or work
Y10T 82/16098	. . with dust or chip handling
Y10T 82/16114	. . including scrap cutting means
Y10T 82/16131	. . Flying cutter type
Y10T 82/16147	. . Cutting couple straddling work
Y10T 82/16163	. . . with pattern, guide or cam means [noncircular product]
Y10T 82/16181	. . . Plural cutting means [pairs, or pair, plus single]
Y10T 82/16196	. . . Rotary shear pair
Y10T 82/16213 Tool axes parallel to axis of work rotation
Y10T 82/16229	. . Interrelated means for tool infeed and circumrotation
Y10T 82/16245	. . . Dependent upon reaction to work
Y10T 82/16262	. . . Infeed cam disk rotation geared to tool holder rotation
Y10T 82/16278 Axial infeed cam
Y10T 82/16295 including centrifugal balancing means
Y10T 82/16311 Scroll plate infeed cam
Y10T 82/16327	. . . Infeed cam plate braked with respect to tool[s] carrier plate
Y10T 82/16344	. . . Orbital cogwheel and fixed detent
Y10T 82/16361	. . . Common gear means
Y10T 82/16377 including adjustable means to vary gear speed

Y10T 82/16393 with manual disconnect lever
Y10T 82/16409	. . . with means to feed work
Y10T 82/16426	. . Infeed means
Y10T 82/16442	. . . with means to circumrotate tool[s] about work
Y10T 82/16459 Fluid means for relative tool actuation
Y10T 82/16475 Gear means for tool actuation
Y10T 82/16491 including axial cam
Y10T 82/16508 with indicator
Y10T 82/16524 Bell crank linkage for tool[s] holder
Y10T 82/16541 Resilient means for tool actuation
Y10T 82/16557 with means for manual retraction
Y10T 82/16573	. . . Hand crank for tool holder
Y10T 82/16591	. . . Power driven eccentric
Y10T 82/16606 Fluid motor
Y10T 82/16622 Plural tools
Y10T 82/16639	. . . Tool within work
Y10T 82/16655	. . . with means to rotate tool[s]
Y10T 82/16672 including rotatable cutters supporting work
Y10T 82/16688 Planetating work mandrels
Y10T 82/16704 Pivoted tool carriage
Y10T 82/16721 with adjustable work stops
Y10T 82/16737 Eccentric periphery rotary tool
Y10T 82/16754 Means to feed work axially
Y10T 82/16771 Translatable work support carriage
Y10T 82/16786 with tool groove in support roll[s]
Y10T 82/16803	. . . Rotatable tool[s] driven by contact with work
Y10T 82/16819 Axially movable tool support
Y10T 82/16836 Freely floating parallel to axis
Y10T 82/16852 with supplemental nonrotative tool
Y10T 82/16868 including clutch control for work rotation
Y10T 82/16885 including resilient means urging work against rotary support
Y10T 82/16901	. . . Separate means for plural tools
Y10T 82/16918	. . . Spring urged
Y10T 82/16934 For window shade
Y10T 82/16951	. . . Tool adjustment and/or stop
Y10T 82/16967	. . . with means to support and/or rotate work
Y10T 82/16983	. . . with means to feed work
Y10T 82/17	. Lathe for pulley
Y10T 82/18	. Lathe for wheel or axle
Y10T 82/185	. . In situ lathe for railroad wheel

Y10T 82/19	. Lathe for crank or crank pin
Y10T 82/192	. . Portable lathe for crank pin
Y10T 82/195	. . having work oscillator
Y10T 82/198	. . . having work driver
Y10T 82/20	. Lathe for screw cutting
Y10T 82/205	. . having swinging feed nut and tool bar
Y10T 82/21	. Portable lathe for brake drum, disc, or shoe
Y10T 82/22	. Portable lathe for pipe turning
Y10T 82/23	. Portable lathe for piston grooving
Y10T 82/24	. Bench lathe
Y10T 82/245	. . Watchmaker's lathe
Y10T 82/25	. Lathe
Y10T 82/2502	. . with program control
Y10T 82/2504	. . . And transmission
Y10T 82/2506	. . . And tool turret
Y10T 82/2508	. . with tool turret
Y10T 82/2511	. . Vertical
Y10T 82/2512	. . having facing tool fed transverse to work
Y10T 82/2514	. . with work feeder or remover
Y10T 82/2516	. . . Magazine type
Y10T 82/2518 Bar feeder
Y10T 82/2521	. . . Bar feeder
Y10T 82/2522	. . Portable
Y10T 82/2524	. . Multiple
Y10T 82/2527	. . having hollow cutter head
Y10T 82/2529	. . Revolvable cutter heads
Y10T 82/2531	. . Carriage feed
Y10T 82/2533	. . . Control
Y10T 82/2535 Electrical type
Y10T 82/2537	. . . Apron mechanism
Y10T 82/2539 Feednut control
Y10T 82/2541	. . . Slide rest
Y10T 82/2543 Multiple tool support
Y10T 82/2545 Tool relief
Y10T 82/2547	. . . Change gears
Y10T 82/2549	. . . Feedscrews and rods
Y10T 82/2552	. . Headstock
Y10T 82/2554	. . . Speed changing gear
Y10T 82/2556 Speed change gears for maintaining constant cutting speed
Y10T 82/2558	. . . Spindle reverser

Y10T 82/2561	. . . Spindle or work angler
Y10T 82/2562	. . . Spindle and bearings
Y10T 82/2564	. . Tailstock
Y10T 82/2566	. . Bed
Y10T 82/2568	. . Center
Y10T 82/2571	. . . Alignment adjuster
Y10T 82/2572	. . Attachment
Y10T 82/2574	. . . Stop [e.g., carriage, tool, work, etc.]
Y10T 82/2577 Tool slide
Y10T 82/2579 Collet or spindle
Y10T 82/2581 Indexible [e.g., roll type, etc.]
Y10T 82/2583	. . Tool and work rest
Y10T 82/2585	. . Tool rest
Y10T 82/2587	. . . Turret type holder [e.g., multiple tools, etc.]
Y10T 82/2589	. . . Quick release tool or holder clamp
Y10T 82/2591	. . . Tool post
Y10T 82/2593	. . Work rest
Y10T 82/2595	. . . with noise or vibration dampener
Y10T 82/2597	. . . Center rest
Y10T 82/26	. Work driver
Y10T 82/262	. . Lathe dog
Y10T 82/264	. . . Cam grip
Y10T 82/266	. . Mandrel
Y10T 82/268	. . . Expansible
Y10T 82/27	. Centerer
Y10T 82/28	. Drill press attachment for turning
Y10T 82/29	. Attachment for cutting a valve
Y10T 82/30	. Miscellaneous

Former US Class 83 series

Y10T 83/00	Cutting
Y10T 83/02	. Other than completely through work thickness
Y10T 83/0207	. . or through work presented
Y10T 83/0215	. . . Including use of rotary scoring blade
Y10T 83/0222 Plural independent rotary scoring blades
Y10T 83/023	. . . With infeeding of work
Y10T 83/0237	. . Pricking
Y10T 83/0244	. . . Including use of orbiting tool carrier
Y10T 83/0252	. . . With infeeding of tool

Y10T 83/0259	. . Edge trimming [e.g., chamfering, etc.]
Y10T 83/0267	. . Splitting
Y10T 83/0274	. . . By use of endless band or chain knife
Y10T 83/0281	. . . By use of rotary blade
Y10T 83/0289 Plural independent rotary blades
Y10T 83/0296	. . . With infeeding of work
Y10T 83/0304	. . Grooving
Y10T 83/0311	. . . By use of plural independent rotary blades
Y10T 83/0319 Forming common groove
Y10T 83/0326 Blades turning about perpendicular axes
Y10T 83/0333	. . Scoring
Y10T 83/0341	. . . Processes
Y10T 83/0348	. . . Active means to control depth of score
Y10T 83/0356	. . . Serially
Y10T 83/0363	. . . Plural independent scoring blades
Y10T 83/037 Rotary scoring blades
Y10T 83/0378 On opposite sides of work
Y10T 83/0385	. . . Rotary scoring blade
Y10T 83/0393 With means to rotate blade
Y10T 83/04	. Processes
Y10T 83/0405	. . With preparatory or simultaneous ancillary treatment of work
Y10T 83/041	. . . By heating or cooling
Y10T 83/0414 At localized area [e.g., line of separation]
Y10T 83/0419	. . . By distorting within elastic limit
Y10T 83/0424 By stretching
Y10T 83/0429 By compressing
Y10T 83/0433 By flexing around or by tool
Y10T 83/0438 To conform to shape of tool
Y10T 83/0443	. . . By fluid application
Y10T 83/0448	. . With subsequent handling [i.e., of product]
Y10T 83/0453	. . . By fluid application
Y10T 83/0457	. . . By retaining or reinserting product in workpiece
Y10T 83/0462	. . . By accelerating travel
Y10T 83/0467	. . . By separating products from each other
Y10T 83/0472	. . . By moving work support to which a tacky product is adhered
Y10T 83/0476	. . Including stacking of plural workpieces
Y10T 83/0481	. . Puncturing
Y10T 83/0486	. . With manipulation of tool protective strip [e.g., backing strip]
Y10T 83/0491	. . Cutting of interdigitating products
Y10T 83/0495	. . Making and using a registration cut

Y10T 83/05	. . With reorientation of tool between cuts
Y10T 83/0505	. . With reorientation of work between cuts
Y10T 83/051	. . . Relative to same tool
Y10T 83/0515	. . During movement of work past flying cutter
Y10T 83/0519	. . . Cyclically varying rate of tool or work movement
Y10T 83/0524	. . Plural cutting steps
Y10T 83/0529	. . . Blanking and cutting
Y10T 83/0534 Cutting to join blanked holes
Y10T 83/0538	. . . Repetitive transverse severing from leading edge of work
Y10T 83/0543 Alternately forming products of less than total width of work
Y10T 83/0548 With longitudinal severing
Y10T 83/0553 Effected by plural steps
Y10T 83/0558 Along zigzag or undulant line or cut
Y10T 83/0562 Prior to transverse severing
Y10T 83/0567 Nonrectilinear cutting
Y10T 83/0572	. . . Plural cutting steps effect progressive cut
Y10T 83/0577	. . . Repetitive blanking
Y10T 83/0581	. . Cutting part way through from opposite sides of work
Y10T 83/0586	. . Effecting diverse or sequential cuts in same cutting step
Y10T 83/0591	. . Cutting by direct application of fluent pressure to work
Y10T 83/0596	. . Cutting wall of hollow work
Y10T 83/06	. . Blanking
Y10T 83/0605	. . Cut advances across work surface
Y10T 83/061	. With manually actuated means to disturb cyclic operation
Y10T 83/081	. With randomly actuated stopping means
Y10T 83/083	. . With means to permit subsequent hand operation
Y10T 83/084	. . With stop-signal-responsive means to actuate auxiliary cutter
Y10T 83/086	. . With sensing of product or product handling means
Y10T 83/088	. . Responsive to tool detector or work-feed-means detector
Y10T 83/089	. . . Responsive to tool characteristic
Y10T 83/091	. . Responsive to work sensing means
Y10T 83/093	. . . Of buckled work
Y10T 83/094 Running loop
Y10T 83/096	. . . Detector supported on or urged against work
Y10T 83/098 Resiliently biased
Y10T 83/099	. . Manually operated
Y10T 83/101	. With stopping means effective on completion of predetermined number of tool cycles
Y10T 83/121	. With means to accomplish delayed stopping after cessation of cyclic operation
Y10T 83/141	. With means to monitor and control operation [e.g., self-regulating means]
Y10T 83/145	. . Including means to monitor product

Y10T 83/148	. . Including means to correct the sensed operation
Y10T 83/152	. . . And modify another operation
Y10T 83/155	. . . Optimizing product from unique workpiece
Y10T 83/159	. . Including means to compensate tool speed for work-feed variations
Y10T 83/162	. With control means responsive to replaceable or selectable information program
Y10T 83/164	. . For cutting component of animal; e.g., hair clipper
Y10T 83/166	. . Removable element carries program
Y10T 83/169	. . . Indeterminate length, web or strand
Y10T 83/171 Magnetic
Y10T 83/173	. . Arithmetically determined program
Y10T 83/175	. . . With condition sensor
Y10T 83/178 Responsive to work
Y10T 83/18	. . . With operator input means
Y10T 83/182	. With means to weigh product
Y10T 83/202	. With product handling means
Y10T 83/2022	. . Initiated by means responsive to product or work
Y10T 83/2024	. . . Responsive to work
Y10T 83/2027	. . Initiated by means directly responsive to tool movement
Y10T 83/2029	. . . In return motion of tool
Y10T 83/2031	. . Including means to drape the product
Y10T 83/2033	. . Including means to form or hold pile of product pieces
Y10T 83/2035	. . . In nested relation
Y10T 83/2037	. . . In stacked or packed relation
Y10T 83/204 Stacker sweeps along product support
Y10T 83/2042 Including cut pieces overlapped on delivery means
Y10T 83/2044 And means to separate product portions
Y10T 83/2046 Including means to move stack bodily
Y10T 83/2048 By movement of stack holder
Y10T 83/205 By timed relocation of holder along path of stack gscheme-change-itemth
Y10T 83/2053 Interrelated adjustment of holder movement and work-feeder
Y10T 83/2055 And means to resist stack movement
Y10T 83/2057 Including means to deliver individual pieces to a stack holder
Y10T 83/2059 With spindle to enter a hole or to make hole in product
Y10T 83/2061 By face-engaging means to push product broadside into stacked relation
Y10T 83/2063 Upon emergence from hollow cutter
Y10T 83/2066	. . By fluid current
Y10T 83/2068	. . . Plural blasts directed against plural product pieces
Y10T 83/207	. . . By suction means
Y10T 83/2072	. . By brush means

Y10T 83/2074	. .	Including means to divert one portion of product from another
Y10T 83/2077	. . .	By kerf entering guide
Y10T 83/2079	. . .	Remaining or re-inserted product portion from base material
Y10T 83/2081	. . .	Gravity type
Y10T 83/2083	. . .	Deflecting guide
Y10T 83/2085	Positionable gate in product flow path
Y10T 83/2087	. . .	Diverging product movers
Y10T 83/209	. .	Including means to replace product in base material after cutting
Y10T 83/2092	. .	Means to move, guide, or permit free fall or flight of product
Y10T 83/2094	. . .	Means to move product at speed different from work speed
Y10T 83/2096	. . .	Means to move product out of contact with tool
Y10T 83/2098	With means to effect subsequent conveying or guiding
Y10T 83/21	Out of contact with a rotary tool
Y10T 83/2103	Mover surrounds axis of tool rotation
Y10T 83/2105	Mover mounted on rotary tool
Y10T 83/2107	For radial movement of product
Y10T 83/2109	Resiliently mounted
Y10T 83/2111	Mover is resiliently mounted
Y10T 83/2113	Pivoted mover
Y10T 83/2116	And plural rotating tools
Y10T 83/2118	Stationary mover
Y10T 83/212	And plural rotating tools
Y10T 83/2122	By ejector within a hollow cutter
Y10T 83/2124	And means to strip the outer surface of a cutter
Y10T 83/2127	Ejector operated with return stroke of cutter
Y10T 83/2129	By means carried by cooperating cutter
Y10T 83/2131	By cam-operated ejector
Y10T 83/2133	By resiliently biased ejector
Y10T 83/2135	Moving stripper timed with tool stroke
Y10T 83/2137	And alternatively movable to or from operating position
Y10T 83/214	Latched stripper released by tool return
Y10T 83/2142	Plural strippers operative upon plural tools
Y10T 83/2144	Single stripper operative upon plural tools
Y10T 83/2146	Spring arm stripper
Y10T 83/2148	Linkage actuated
Y10T 83/215	Carried by moving tool element or its support
Y10T 83/2153	Fluid pressure actuated stripper
Y10T 83/2155	Stripper biased against product
Y10T 83/2157	Elastomeric stripper contacting product
Y10T 83/2159	By spring means

Y10T 83/2161 By free weight of stripper
Y10T 83/2163 Stripper biased against product
Y10T 83/2166 Spring biased stripper
Y10T 83/2168 Manually operated stripper
Y10T 83/217 Stationary stripper
Y10T 83/2172 Stripper encircles moving tool
Y10T 83/2174 Blockable exit port
Y10T 83/2177 Tool conforming member interposed between tool and work
Y10T 83/2179 Including means to move, or resist movement of, cut pieces along delivery chute
Y10T 83/2181 Active delivery means mounted on tool support
Y10T 83/2183 Product mover including gripper means
Y10T 83/2185 Suction gripper
Y10T 83/2187 Reciprocating product handler
Y10T 83/219 Rotating or oscillating product handler
Y10T 83/2192 Endless conveyor
Y10T 83/2194 And means to remove product therefrom
Y10T 83/2196 Roller[s]
Y10T 83/2198 Tiltable or withdrawable support
Y10T 83/22 Means to move product laterally
Y10T 83/2203 Oscillating means
Y10T 83/2205 Reciprocating means
Y10T 83/2207 Means to move product in a nonrectilinear path
Y10T 83/2209 Guide
Y10T 83/2211 Abutment in path of product being moved by work feeder
Y10T 83/2213 Product-diverting conduit in or from hollow tool
Y10T 83/2216 Inclined conduit, chute or plane
Y10T 83/2218 Abutment interposed in path of free fall or flight of product
Y10T 83/222 With receptacle or support for cut product
Y10T 83/242 With means to clean work or tool
Y10T 83/263 With means to apply transient nonpropellant fluent material to tool or work
Y10T 83/283 With means to control or modify temperature of apparatus or work
Y10T 83/293 Of tool
Y10T 83/303 With tool sharpener or smoother
Y10T 83/313 Spatially fixed tool
Y10T 83/323 With means to stretch work temporarily
Y10T 83/343 With means to deform work temporarily
Y10T 83/364 By fluid blast and/or suction
Y10T 83/384 By tool inside hollow work
Y10T 83/385 Work pre-packed with internal tool[s]

Y10T 83/386	. . . With expanding mandrel
Y10T 83/387	. . . Interrelated tool feed means and means to actuate work immobilizer
Y10T 83/388 Actuated clamp element and work holder coact to position work
Y10T 83/39	. . . Synchronized tool and work feeding means
Y10T 83/391	. . . With means to position tool[s] for cutting
Y10T 83/392	. . . One tool [either internal or external] having compound motion
Y10T 83/393 Annulus and disc-type tool pair
Y10T 83/394	. . . One tool having unidirectional rotary motion
Y10T 83/395	. . . One tool having only rectilinear motion[s]
Y10T 83/396 Annulus and disc-type tool pair
Y10T 83/397 A tool has a sequence of motion in plural paths
Y10T 83/398 Internal tool is an active cutter
Y10T 83/40 Multiple external active tools
Y10T 83/401 Tools operate in a substantially common transverse plane of cut
Y10T 83/402 With tool actuating cams on a common support
Y10T 83/403	. . . With manually actuated means to position or facilitate positioning of work
Y10T 83/404	. . By means to misalign aligned apertured tools
Y10T 83/408	. . . Combined with another type tool of the class
Y10T 83/412	. . . Rectilinear relative movement only
Y10T 83/416	. . . Rotary relative movement solely about a single pivot
Y10T 83/42 With plural apertures in one or both carriers
Y10T 83/424	. . By increased tensioning of work-enclosing wire
Y10T 83/444	. . Tool engages work during dwell of intermittent workfeed
Y10T 83/4443	. . . Unicyclic
Y10T 83/4445 Convertible to and from unicyclic
Y10T 83/4448 Controlled by mechanical means
Y10T 83/445	. . . With work-moving clamp jaw
Y10T 83/4453	. . . Work moved solely by movable abutment
Y10T 83/4455	. . . Operation initiated by work-driven detector means to measure work length
Y10T 83/4458	. . . Work-sensing means to control work-moving or work-stopping means
Y10T 83/446 With means to initiate tool feed by same control impulse
Y10T 83/4463	. . . Work-sensing means to initiate tool feed
Y10T 83/4465 With work-stopping abutment in sensing means
Y10T 83/4468	. . . Plural tools at same station, one positioned for continuous engagement with work
Y10T 83/447	. . . Plural tools successively actuated at same station
Y10T 83/4473 During one dwell period
Y10T 83/4475	. . . Tool has motion additional to cutting stroke during tool cycle
Y10T 83/4478 Tool has additional motion during work dwell
Y10T 83/448 Included in plural cutting cycles
Y10T 83/4483 Tool has work-feeding motion

- Y10T 83/4486 . . . With variable direction of work-feed from cycle to cycle
- Y10T 83/4488 In one of certain selected directions
- Y10T 83/4491 . . . Interlock between tool actuating and work feed means
- Y10T 83/4493 . . . Tool motion initiates work feed and vice versa
- Y10T 83/4496 . . . Stored energy means for moving work or tool, loaded by tool or work
- Y10T 83/4498 Work feed means actuates energy storage device for tool
- Y10T 83/4501 . . . Work feed means controlled by means mounted on tool or tool support
- Y10T 83/4503 Such means drives the work feed means
- Y10T 83/4506 Work feed means carried by tool or tool support
- Y10T 83/4508 With supplemental work feed means
- Y10T 83/4511 On return stroke of tool
- Y10T 83/4513 Work feed means halted by means on tool or tool support
- Y10T 83/4516 . . . Work-feed mechanism in nonfeed motion effects or initiates tool actuation
- Y10T 83/4518 By striking tool actuator
- Y10T 83/4521 Nonfeed motion is reverse to feed motion
- Y10T 83/4523 . . . With means to vary number of work-feed increments between tool strokes
- Y10T 83/4526 . . . Dwell caused by imposing reverse motion on portion of flexible moving work
- Y10T 83/4529 . . . With uninterrupted flow of work from supply source
- Y10T 83/4531 . . . Work feed increment shorter than longitudinal tool field
- Y10T 83/4534 . . . Unequal work feed increments in recurring series
- Y10T 83/4536 Work carriage carries ratchet means to determine increments
- Y10T 83/4539 . . . Means to change tool position, or length or datum position of work- or tool-feed increment
- Y10T 83/4541 With means to vary magnitude of work-feed increment
- Y10T 83/4544 Multi-increment type [e.g., ticket issuing]
- Y10T 83/4546 Length selector initiates machine operation
- Y10T 83/4549 By change in length of one member of feed-driving linkage
- Y10T 83/4551 Rotating member
- Y10T 83/4554 By change of effective shape of driving or driven surface of element of work-feed mechanism
- Y10T 83/4556 By adjustment of fixed stop
- Y10T 83/4559 With means to vary magnitude or base position of tool stroke
- Y10T 83/4561 . . . With means to facilitate manual repositioning [shift] of work
- Y10T 83/4564 . . . With means to produce plurality of work-feed increments per tool cycle
- Y10T 83/4567 Including supplemental work-feed means
- Y10T 83/4569 Manual
- Y10T 83/4572 With stop adapted to engage abutment surface on work
- Y10T 83/4574 Plurality of work stops successively effective
- Y10T 83/4577 . . . Work fed successively to plural tools
- Y10T 83/4579 With change of direction between tools

- Y10T 83/4582 . . Work advance occurs during return stroke of tool
- Y10T 83/4584 . . Dwell defined only by "dead-center" of rotating crank
- Y10T 83/4587 . . Dwell initiated by disengagement of surface of moving frictional feed means from work
- Y10T 83/4589 . . . Feed means has interrupted frictional surface
- Y10T 83/4592 . . . Feed means has rotary motion
- Y10T 83/4594 . . Dwell caused by clamping or blocking work during continuous operation of feed means
- Y10T 83/4597 . . With means to control magnitude of work-feed increment or work acceleration
- Y10T 83/4599 . . . Means to prevent random or excessive work feeds
- Y10T 83/4602 . . . Full stroke required of feed means
- Y10T 83/4604 . . Work feed functions as tool support
- Y10T 83/4607 . . With rotary work-carrier
- Y10T 83/461 . . With abutment to position work being fed with respect to cutter
- Y10T 83/4612 . . . With slip between positioned work and feed means
- Y10T 83/4615 . . Work guide and feed means have open side
- Y10T 83/4617 . . Work feed means modified to maintain clearance from tool
- Y10T 83/462 . . Plurality of work feed means in separate paths
- Y10T 83/4622 . . Intermittent drive type of gearing for work-feed means
- Y10T 83/4625 . . . Gearing modified to lock the work-feed means
- Y10T 83/4627 . . . Mutilated gear in mesh with gear driving work-feed means
- Y10T 83/463 . . Work-feed element contacts and moves with work
- Y10T 83/4632 . . . Comprises a work-moving gripper
- Y10T 83/4635 . . . Comprises element entering aperture in, or engaging abutment surface on, work
- Y10T 83/4637 . . With means to guide, position, or present work to work-feed means
- Y10T 83/464 . . . Means to transport work to work-feed means
- Y10T 83/4642 Including means to pick articles from pack or stack
- Y10T 83/4645 . . With means to clamp work during dwell
- Y10T 83/4647 . . One-revolution clutch in tool drive
- Y10T 83/465 . . Cutting motion of tool has component in direction of moving work
- Y10T 83/4653 . . With means to initiate intermittent tool action
- Y10T 83/4656 . . . Tool moved in response to work-sensing means
- Y10T 83/4659 With means to vary "length" of product
- Y10T 83/4662 To vary an end-product "length" [e.g., "crop cut"]
- Y10T 83/4664 With photo-electric work-sensing means
- Y10T 83/4667 With trip-switch work-sensing means
- Y10T 83/467 To initiate feed movement of tool
- Y10T 83/4673 And to initiate flying movement of tool
- Y10T 83/4676 With work-responsive means to initiate flying movement of tool
- Y10T 83/4679 With flying work-gripper means related to tool carrier

Y10T 83/4682 With means controlling flying speed dependent on work speed
Y10T 83/4685	. . . With means to vary frequency of initiation
Y10T 83/4688 By orbitally traveling trigger pin[s]
Y10T 83/4691	. . Interrelated control of tool and work-feed drives
Y10T 83/4693	. . With means to concurrently adjust flying frequency and retain flying speed of tool
Y10T 83/4696	. . Plural diverse flying cutters
Y10T 83/4699	. . Combined with other type cutter
Y10T 83/4702	. . . With slitter
Y10T 83/4705	. . Plural separately mounted flying cutters
Y10T 83/4708	. . With means to render cutter pass[es] ineffective
Y10T 83/4711	. . . With means to produce "mis-cut"
Y10T 83/4714	. . Oscillating work shifter adjacent cutter
Y10T 83/4717	. . . Work actuated senser initiates shifter
Y10T 83/472	. . Wire tool
Y10T 83/4722	. . . On tool support having reciprocation parallel to direction of work-feed
Y10T 83/4725 And rotation about axis parallel to direction of work-feed
Y10T 83/4728	. . Tool flies by engagement with the work
Y10T 83/4731	. . . Tool merely flexes with moving work
Y10T 83/4734	. . Flying support or guide for work
Y10T 83/4737	. . With tool speed regulator
Y10T 83/474	. . With work feed speed regulator
Y10T 83/4743	. . . With means to vary cyclically speed of work
Y10T 83/4746	. . Spring return of tool in counterfly direction
Y10T 83/4749	. . Tool mounted on oscillating standard
Y10T 83/4751	. . . Both tools of couple on single standard
Y10T 83/4754 One tool swings out of work path on return stroke
Y10T 83/4757	. . Tool carrier shuttles rectilinearly parallel to direction of work feed
Y10T 83/476	. . . Including means to secure work to carrier
Y10T 83/4763	. . . Both members of cutting pair on same carrier
Y10T 83/4766	. . Orbital motion of cutting blade
Y10T 83/4769	. . . Work feeder mounted on tool support
Y10T 83/4772 Gripper-type feeder
Y10T 83/4775	. . . Tool speed varied within each orbital cycle
Y10T 83/4778	. . . Work feed gripper carried on endless belt
Y10T 83/478	. . . Endless belt or chain tool carrier
Y10T 83/4783	. . . Constantly oriented tool with arcuate cutting path
Y10T 83/4786 Cutting couple type
Y10T 83/4789	. . . Rotatable disc-type tool on orbiting axis
Y10T 83/4792 Idling disc
Y10T 83/4795	. . . Rotary tool

Y10T 83/4798	Segmented disc slitting or slotting tool
Y10T 83/4801	With undulant cutting edge [e.g., "pinking" tool]
Y10T 83/4804	Single tool action drive
Y10T 83/4807	With one-revolution drive
Y10T 83/4809	With loop former preceding tool
Y10T 83/4812	Compound movement of tool during tool cycle
Y10T 83/4815	Axial reciprocation of tool
Y10T 83/4818	Interconnected work feeder and tool driver
Y10T 83/4821	Side cutting helical blade
Y10T 83/4824	With means to cause progressive transverse cutting
Y10T 83/4827	With helical cutter blade
Y10T 83/483	With cooperating rotary cutter or backup
Y10T 83/4833	Cooperating tool axes adjustable relative to each other
Y10T 83/4836	With radial overlap of the cutting members
Y10T 83/4838	With anvil backup
Y10T 83/4841	With resilient anvil surface
Y10T 83/4844	Resiliently urged cutter or anvil member
Y10T 83/4847	With cooperating stationary tool
Y10T 83/485	Cutter with timed stroke relative to moving work
Y10T 83/487	Work swings about progressively cutting tool during tool stroke
Y10T 83/489	Tool actuated by movable work support
Y10T 83/49	Traveling cutter
Y10T 83/492	With means to vary timing of tool feed
Y10T 83/494	Uniform periodic tool actuation
Y10T 83/496	With periodic lateral feed of tool or work
Y10T 83/498	With plural tool stations
Y10T 83/50	Reciprocating tool
Y10T 83/501	With plural tools on a single tool support
Y10T 83/503	With plural tool stations
Y10T 83/505	Operation controlled by means responsive to product
Y10T 83/515	Actuation of tool controlled
Y10T 83/525	Operation controlled by detector means responsive to work
Y10T 83/527	With means to control work-responsive signal system
Y10T 83/528	To delay response to work-senser
Y10T 83/53	To change length of product
Y10T 83/531	With plural work-sensing means
Y10T 83/533	With photo-electric work-sensing means
Y10T 83/535	Release of interlock controlled
Y10T 83/536	Movement of work controlled
Y10T 83/538	Positioning of tool controlled

- Y10T 83/54 . . . Actuation of tool controlled by work-driven means to measure work length
- Y10T 83/541 . . . Actuation of tool controlled in response to work-sensing means
- Y10T 83/543 Sensing means responsive to work indicium or irregularity
- Y10T 83/544 With trip-switch in work-sensing mechanism
- Y10T 83/546 . . . Interrelated tool actuating and work guide moving means
- Y10T 83/566 . . . Interrelated tool actuating means and means to actuate work immobilizer
- Y10T 83/5669 . . . Work clamp
- Y10T 83/5678 Tool deflected by guide on tightened clamp
- Y10T 83/5687 With means to control clamping force
- Y10T 83/5696 Clamp driven by reaction from tool force
- Y10T 83/5705 With means providing for plural steps in clamping stroke
- Y10T 83/5715 With sequencing means
- Y10T 83/5724 With provision for manual control of clamp
- Y10T 83/5733 Tool or tool support on movable clamp jaw
- Y10T 83/5742 Clamp moved by direct impact of tool or tool support
- Y10T 83/5751 Clamp retracted by impact of tool or tool support
- Y10T 83/576 Clamp actuating means driven by tool or tool support
- Y10T 83/5769 Clamp yieldably driven by tool or tool support
- Y10T 83/5778 With resilient drive element
- Y10T 83/5787 Clamp driven by yieldable means
- Y10T 83/5796 Drive means is resilient
- Y10T 83/5805 Fluid pressure yieldable drive means
- Y10T 83/5815 . . . Work-stop abutment
- Y10T 83/5824 Oppositely effective abutments
- Y10T 83/5833 With cyclic means to alter work-stopping position
- Y10T 83/5842 Stop partakes of tool motion
- Y10T 83/5851 Carried by tool or tool support
- Y10T 83/586 . . . Interrelated tool actuating means and means to actuate work-mover stop
- Y10T 83/606 . . . Interrelated tool actuating means and guard means
- Y10T 83/613 . . . Work guard
- Y10T 83/619 . . . Cutter guide slot closer
- Y10T 83/626 . . . Operation of member controlled by means responsive to position of element remote from member [e.g., interlock]
- Y10T 83/637 With means to initiate operation of member
- Y10T 83/647 . . . With means to convey work relative to tool station
- Y10T 83/6472 . . . By fluid current
- Y10T 83/6473 . . . Centrifugal feed to tangential tool [e.g., "Beria" type]
- Y10T 83/6475 . . . With means to regulate work-feed speed
- Y10T 83/6476 . . . Including means to move work from one tool station to another
- Y10T 83/6478 Tool stations angularly related

Y10T 83/648	Work manipulated between tool stations
Y10T 83/6481	With static tool
Y10T 83/6483	. . .	Tool stations staggered relative to one another
Y10T 83/6484	. . .	Punch or die station
Y10T 83/6486	. . .	Notcher or pinker station
Y10T 83/6488	. . .	Work reciprocated past double-edged knife
Y10T 83/6489	. . .	Slitter station
Y10T 83/6491	And transverse cutter station
Y10T 83/6492	. .	Plural passes of diminishing work piece through tool station
Y10T 83/6494	. . .	Work alternately, angularly re-oriented relative to tool station
Y10T 83/6496	By additional means to engage work and orient it relative to tool station
Y10T 83/6497	By roller or roll-like element
Y10T 83/6499	. . .	Work rectilinearly reciprocated through tool station
Y10T 83/65	With means to cause or permit angular re-orientation of work about axis parallel to plane of cut
Y10T 83/6502	By endless member having work-engaging teeth
Y10T 83/6504	By member having work-engaging tooth
Y10T 83/6505	Including plural work-engaging teeth
Y10T 83/6507	Fluid operated
Y10T 83/6508	With means to cause movement of work transversely toward plane of cut
Y10T 83/651	By means to cause movement toward and away from plane of cut
Y10T 83/6512	Actuated by movement of a member on reciprocating means
Y10T 83/6513	Actuated by passive means which is external to reciprocating means
Y10T 83/6515	By means to define increment of movement toward plane of cut
Y10T 83/6516	Interrelated with movement of reciprocating means
Y10T 83/6518	By pusher mechanism
Y10T 83/652	With additional work holding or positioning means
Y10T 83/6521	Work holding means includes actuator
Y10T 83/6523	Including plural, simultaneously acting pusher elements
Y10T 83/6524	Independently adjustable
Y10T 83/6526	With additional means to retract elements
Y10T 83/6528	Power derived from movement of reciprocating means
Y10T 83/6529	Power derived from fluid pressure means
Y10T 83/6531	Movement by screw means
Y10T 83/6532	Movement by rack and pinion or pawl
Y10T 83/6534	With handle
Y10T 83/6536	By carriage
Y10T 83/6537	By cable or belt drive
Y10T 83/6539	. .	With means for transverse positioning of work on a moving conveyor
Y10T 83/654	. .	With work-constraining means on work conveyor [i.e., "work-carrier"]

Y10T 83/6542	. . .	Plural means to constrain plural work pieces
Y10T 83/6544	End of work protrudes through aperture in carrier
Y10T 83/6545	. . .	With means to guide work-carrier in nonrectilinear path
Y10T 83/6547	About axis fixed relative to tool station
Y10T 83/6548	Infeed
Y10T 83/655	About vertical axis
Y10T 83/6552	Cut normal to axis
Y10T 83/6553	Work-guide tube
Y10T 83/6555	Cut normal to axis
Y10T 83/6556	Oscillating work-carrier
Y10T 83/6558	Multiple cutters
Y10T 83/656	Coaxial rotary cutters
Y10T 83/6561	Work stationary during cut
Y10T 83/6563	. . .	With means to orient or position work carrier relative to tool station
Y10T 83/6564	By pattern or templet
Y10T 83/6566	By indexing means
Y10T 83/6568	. . .	With additional work-locating means on work-carrier
Y10T 83/6569	. .	With means to stop work conveyor
Y10T 83/6571	. .	With means to store work articles
Y10T 83/6572	. .	With additional means to engage work and orient it relative to tool station
Y10T 83/6574	. . .	By work-stopping abutment
Y10T 83/6576	. . .	By opposed lateral guide means
Y10T 83/6577	. . .	With means to adjust additional means
Y10T 83/6579	. .	With means to press work to work-carrier
Y10T 83/658	. .	With projections on work-carrier [e.g., pin wheel]
Y10T 83/6582	. .	Tool between tandem arranged work carrying means
Y10T 83/6584	. .	Cut made parallel to direction of and during work movement
Y10T 83/6585	. . .	Including nonconcurrently acting tool
Y10T 83/6587	. . .	Including plural, laterally spaced tools
Y10T 83/6588	Tools mounted on common tool support
Y10T 83/659	Tools axially shiftable on support
Y10T 83/6592	. . .	Interrelated work-conveying and tool-moving means
Y10T 83/6593	With reciprocating tool [e.g., "jigsaw" type]
Y10T 83/6595	With means to move tool laterally of feed direction during cutting
Y10T 83/6596	With means to effect difference between work speed and tool speed
Y10T 83/6598	Tool co-axial with work-conveying means
Y10T 83/66	. . .	With means to press work to tool
Y10T 83/6601	. . .	Bevel cutting tool
Y10T 83/6603	. . .	Tool shiftable relative to work-conveying means
Y10T 83/6604	. . .	Tool in contact with surface of work-conveying means

Y10T 83/6606	. . .	Tool between laterally spaced work-conveying means
Y10T 83/6608	. . .	By rectilinearly moving work carriage
Y10T 83/6609	Angularly adjustable
Y10T 83/6611	Having positive adjustment stop; e.g., link
Y10T 83/6612	Having position indicating means
Y10T 83/6614	Pusher engaging rear surface of work
Y10T 83/6616	Having means to actuate pusher
Y10T 83/6617	Hydraulic or pneumatic means
Y10T 83/6619	Gear or pulley actuated pusher
Y10T 83/662	Lever, cam, or link actuated pusher
Y10T 83/6622	Having means to actuate carriage
Y10T 83/6624	Hydraulic or pneumatic means
Y10T 83/6625	Gear or pulley
Y10T 83/6627	Adapted to place tension on flacid member
Y10T 83/6628	Lever, cam, or link means
Y10T 83/663	On or attached to vehicle
Y10T 83/6632	Supported for movement at one side of tool only
Y10T 83/6633	. . .	By work moving flexible chain or conveyor
Y10T 83/6635	. . .	By feed roller
Y10T 83/6636	Pinch rollers
Y10T 83/6638	. . .	Unattached manual work pusher
Y10T 83/664	. .	Roller
Y10T 83/6641	. . .	Plural independent rollers for feed of plural distinct work
Y10T 83/6643	. . .	Shaped to conform to work
Y10T 83/6644	. . .	With work-supplying reel
Y10T 83/6646	And provision for selecting feed length
Y10T 83/6648	. . .	Continuous conveying during , cutting; e.g., straw cutting
Y10T 83/6649	. . .	Supporting work at cutting station
Y10T 83/6651	Comprising part of cutting station
Y10T 83/6652	. . .	Tool and feed roller actuated by common handle
Y10T 83/6654	. . .	Tool and roller on common movable support
Y10T 83/6656	. .	Rectilinear movement only
Y10T 83/6657	. . .	Tool opposing pusher
Y10T 83/6659	Hydraulically or pneumatically actuated
Y10T 83/666	Screw actuated
Y10T 83/6662	Gear or pulley actuated
Y10T 83/6664	Lever, cam, or link actuated
Y10T 83/6665	Spring or gravity urged
Y10T 83/6667	. .	Work carrier rotates about axis fixed relative to tool station
Y10T 83/6668	. .	Interrelated work-feeding means and tool-moving means

- Y10T 83/667 . Tool carrier or guide affixed to work during cutting
- Y10T 83/674 . . By flexible work-engaging member
- Y10T 83/68 . . Entirely work supported
- Y10T 83/687 . By tool reciprocable along elongated edge
- Y10T 83/6875 . . With means permitting tool to be rotatably adjusted about its cutting edge during cutting
- Y10T 83/688 . . With dynamic balancing or shock absorbing means
- Y10T 83/6885 . . With tool of another type
- Y10T 83/689 . . With means to change to other type tool
- Y10T 83/6895 . . Plural reciprocable tools
- Y10T 83/69 . . Stored energy furnishes drive in one direction
- Y10T 83/6905 . . With tool in-feed
- Y10T 83/691 . . . And auxiliary means for promoting or retarding tool in-feed
- Y10T 83/6915 By yieldable means
- Y10T 83/692 And means to vary tool in-feed speed
- Y10T 83/6925 With interrelated tool actuating and in-feed means
- Y10T 83/693 . . . Of rectilinearly reciprocating tool
- Y10T 83/6935 With in-feed by pivoting carrier
- Y10T 83/694 . . . And means to prevent tool in-feed
- Y10T 83/6945 . . . With passive means to guide tool directly
- Y10T 83/695 By plural opposed guide surfaces
- Y10T 83/6955 Having relative adjustment between guide surfaces
- Y10T 83/696 With relative adjustment between guide and work or work-support
- Y10T 83/6965 By or with additional movable work-support portion
- Y10T 83/697 By rotation about an axis parallel to the work-support surface
- Y10T 83/6975 By rotation about an axis perpendicular to the work-support surface
- Y10T 83/698 . . . Including means to cause nonrectilinear tool infeed
- Y10T 83/6985 . . . Of arcuately oscillating tool
- Y10T 83/699 . . . Of tool carrier on single moving pivot
- Y10T 83/6995 Pivot moves in closed loop
- Y10T 83/70 Pivot moves to and fro in arcuate path
- Y10T 83/7005 Axis of arcuate path moves during cutting
- Y10T 83/701 Pivot moves to and fro in rectilinear path
- Y10T 83/7015 . . Having uniplanar compound motion
- Y10T 83/702 . . . By plural arcuately oscillating carrier
- Y10T 83/7025 . . . Constantly oriented tool travelling in orbit
- Y10T 83/703 . . . Tool rocks cutting reciprocations
- Y10T 83/7035 One tool reciprocates along fixed guide element
- Y10T 83/704 . . With work-support and means to vary relationship between tool and work support
- Y10T 83/7045 . . Arcuately oscillating tool carried on single pivot

Y10T 83/705	. . With means to support tool at opposite ends
Y10T 83/7055	. . . And apply drive force to both ends of tool
Y10T 83/706 By flexible drive means
Y10T 83/7065 By reciprocating rigid support
Y10T 83/707	. By endless band or chain knife
Y10T 83/7076	. . With programming means
Y10T 83/7083	. . With cutter other than endlessly orbiting type
Y10T 83/7089	. . Including contiguous oppositely moving knife portions
Y10T 83/7095	. . With means to change to non-endlessly orbiting cutter
Y10T 83/7101	. . With tool in-feed
Y10T 83/7108	. . . Including ground-traversing vehicle
Y10T 83/7114	. . . Including means to permit arcuate in-feed motion
Y10T 83/712 Including means to relocate path of in-feed motion
Y10T 83/7126 Angular relative previous path
Y10T 83/7133	. . . By gravity
Y10T 83/7139 With fluid in-feed regulating means
Y10T 83/7145	. . . By motor-driven mechanism
Y10T 83/7151	. . With scale or indicator
Y10T 83/7158	. . Including plural cutting zones
Y10T 83/7164	. . . With adjustment of separation between zones
Y10T 83/717 By lever means
Y10T 83/7176 By screw-threaded means
Y10T 83/7183	. . . Including "figure-8" band
Y10T 83/7189	. . . Comprising plural bands
Y10T 83/7195	. . Including means to adjust relationship between band and work-support surface
Y10T 83/7201	. . . By varying angle between band and work-support surface
Y10T 83/7208 By tilting band carrier
Y10T 83/7214 About point of intersection of cutting span and work-support surface
Y10T 83/722	. . . By varying distance between band and work-support surface
Y10T 83/7226	. . With means to guard the tension
Y10T 83/7233	. . . Including means to retard undriven pulley or sprocket
Y10T 83/7239	. . . With means to vary distance between pulley or sprocket axes
Y10T 83/7245 And angular relationship of axes
Y10T 83/7251 Including means to yieldably bias pulley
Y10T 83/7258 By fluid means
Y10T 83/7264	. . With special blade guide means
Y10T 83/727	. With means to guide moving work
Y10T 83/728	. . In pivotal or arcuate movement
Y10T 83/73	. . Guide fixed to or integral with stationary tool element
Y10T 83/731	. . . Tool element cooperates with a second tool

Y10T 83/732	. . With guard
Y10T 83/734	. . With attachment or operative connection to tool carrier
Y10T 83/735	. . With attachment or operative connection to passive tool guide
Y10T 83/736	. . Guide cooperates with template or straight edge secured to work
Y10T 83/738	. . Curved or deflecting guide
Y10T 83/739	. . Positively confines or otherwise determines path of work
Y10T 83/74	. . Adapted to permit maneuvering of work at tool zone
Y10T 83/741	. . With movable or yieldable guide element
Y10T 83/743	. . . Opposed to work-supporting surface
Y10T 83/744	. . Plural guide elements
Y10T 83/745	. . . Opposed
Y10T 83/747	. . Opposed to work-supporting surface
Y10T 83/748	. With work immobilizer
Y10T 83/7487	. . Means to clamp work
Y10T 83/7493	. . . Combined with, peculiarly related to, other element
Y10T 83/75 With or to tool guide
Y10T 83/7507 Guide for traveling cutter
Y10T 83/7513 Tool or tool support on movable clamp jaw
Y10T 83/752	. . . With means providing for plural steps in clamping stroke
Y10T 83/7527	. . . With equalizer or self-aligning jaw
Y10T 83/7533	. . . With biasing or counterbalancing means
Y10T 83/754	. . . Clamp driven by yieldable means
Y10T 83/7547	. . . Liquid pressure actuating means
Y10T 83/7553	. . . Including means to retain clamp jaw in position
Y10T 83/756	. . . Self-locking drive means
Y10T 83/7567	. . . Manually actuated drive means
Y10T 83/7573	. . . Including clamping face of specific structure
Y10T 83/758	. . . With means to adjust clamp position or stroke
Y10T 83/7587	. . Gapped work-constrainer
Y10T 83/7593	. . Work-stop abutment
Y10T 83/76	. . . With scale or indicator
Y10T 83/7607	. . . Normal to plane of cut
Y10T 83/7613 Adjustable
Y10T 83/762 Angularly relative to plane of cut; e.g., miter
Y10T 83/7627 With traversing cutter guide; e.g., cut-off saw
Y10T 83/7633	. . . Collapsible
Y10T 83/764	. . . Retractable
Y10T 83/7647	. . . Adjustable
Y10T 83/7653 Having curved cutting edge to make arcuate cut, plural nonaligned intersecting cutting edges, or spaced punches

Y10T 83/766 Spaced edges
Y10T 83/7667	. . . Having curved cutting edge to make arcuate cut, plural nonaligned intersecting cutting edges, or spaced punches
Y10T 83/7673 Spaced edges
Y10T 83/768	. Rotatable disc tool pair or tool and carrier
Y10T 83/7684	. . With means to support work relative to tool[s]
Y10T 83/7688	. . . Plural tool elements successively actuated at same station
Y10T 83/7693	. . . Tool moved relative to work-support during cutting
Y10T 83/7697 Tool angularly adjustable relative to work-support
Y10T 83/7701	. . . Supporting surface and tool axis angularly related
Y10T 83/7705 Adjustable angular relationship
Y10T 83/7709	. . . Unidirectionally movable work support
Y10T 83/7713 With opposed work-presser
Y10T 83/7718 Presser co-axial with tool
Y10T 83/7722	. . . Support and tool relatively adjustable
Y10T 83/7726 By movement of the tool
Y10T 83/773	. . . Work-support includes passageway for tool [e.g., slotted table]
Y10T 83/7734	. . With guard for tool
Y10T 83/7738	. . Optional tool pairs alternatively operative
Y10T 83/7743	. . . One element of tool pairs common to all pairs
Y10T 83/7747	. . With means to permit replacement of tool
Y10T 83/7751	. . Means to separate elements of tool pair
Y10T 83/7755	. . Carrier for rotatable tool movable during cutting
Y10T 83/7759	. . . Unicyclic movement
Y10T 83/7763	. . . Tool carrier reciprocable rectilinearly
Y10T 83/7768 With means to adjust path of reciprocation
Y10T 83/7772 Angular relative to previous path
Y10T 83/7776 With means to reciprocate carrier
Y10T 83/778 And means to rotate tool
Y10T 83/7784 With means to rotate tool
Y10T 83/7788	. . . Tool carrier oscillated or rotated
Y10T 83/7793	. . Means to rotate or oscillate tool
Y10T 83/7797	. . . Including means to rotate both elements of tool pair
Y10T 83/7801 Including means to rotate both elements at different speeds
Y10T 83/7805 And means to change speed of rotation
Y10T 83/7809	. . Tool pair comprises rotatable tools
Y10T 83/7813	. . . Tool pair elements angularly related
Y10T 83/7818 Elements of tool pair angularly adjustable relative to each other
Y10T 83/7822	. . . Tool pair axially shiftable
Y10T 83/7826 With shifting mechanism for at least one element of tool pair

Y10T 83/783	. . . Tool pair comprises contacting overlapped discs
Y10T 83/7834 With means to effect axial pressure on pair
Y10T 83/7838 With means to change axial pressure
Y10T 83/7843 With means to change overlap of discs
Y10T 83/7847	. . . Tool element axially shiftable
Y10T 83/7851	. . . Tool pair comprises disc and cylindrical anvil
Y10T 83/7855 With adjustable means to urge tool elements together
Y10T 83/7859	. . . Elements of tool pair adjustably spaced
Y10T 83/7863	. . Tool pair comprises rotatable tool and nonrotatable tool
Y10T 83/7868	. . Tool element selectively operative
Y10T 83/7872	. . Tool element mounted for adjustment
Y10T 83/7876	. . . Plural, axially spaced tool elements
Y10T 83/788	. Tool pair comprises rotatable anvil and fixed-type tool
Y10T 83/793	. . Anvil has motion in addition to rotation [i.e., traveling anvil]
Y10T 83/798	. . . Additional motion is along fixed arcuate path
Y10T 83/803	. . . With plural anvils
Y10T 83/808	. Two tool pairs, driver for one pair moves relative to driver for other pair
Y10T 83/811	. . One tool support acts as driver for other
Y10T 83/814	. . . Punch and shear
Y10T 83/817	. . With variable spacing between tool pairs
Y10T 83/819	. . . With intermediate work support
Y10T 83/822	. . Punch and shear
Y10T 83/825	. . Successively acting
Y10T 83/828	. With illuminating or viewing means for work
Y10T 83/839	. . Mirror or lens
Y10T 83/849	. With signal, scale, or indicator
Y10T 83/85	. . Signal; e.g., alarm
Y10T 83/851	. . Indicator comprising work or product
Y10T 83/852	. . Responsive to force
Y10T 83/853	. . Indicates tool position
Y10T 83/855	. . . Relative to another element
Y10T 83/856 To work-engaging member
Y10T 83/857 Calibrated scale or indicator
Y10T 83/858 Indicates dimension of work being cut
Y10T 83/859 Dynamic indicator
Y10T 83/86 To another tool assembly
Y10T 83/861 To cooperating tool
Y10T 83/862 To another component of tool assembly
Y10T 83/863 Adjustable guide for traversing tool; e.g., radial saw guide or miter saw guide
Y10T 83/865	. . Indicates work characteristic

Y10T 83/866	. . Indicates wear
Y10T 83/867	. . Bubble level
Y10T 83/868	. . Counter
Y10T 83/869	. Means to drive or to guide tool
Y10T 83/8691	. . Unicyclic
Y10T 83/8693	. . . With adjustable stopping point or tool
Y10T 83/8694	. . . With brake or blocking means
Y10T 83/8696	. . Means to change datum plane of tool or tool presser stroke
Y10T 83/8697	. . . For disabling of continuously actuated cutter
Y10T 83/8699	. . . With adjustable stop
Y10T 83/87	. . . By varying length of tool stroke
Y10T 83/8702	. . Clicker die press
Y10T 83/8703	. . . With die handling attachment
Y10T 83/8704	. . . With reciprocating presser
Y10T 83/8706 Laterally movable to selective operative positions
Y10T 83/8707 Pivotal or revolving only
Y10T 83/8709 With means to impart, limit, or control pivotal motion of presser
Y10T 83/871 Interrelated with presser reciprocating means
Y10T 83/8712 With means to mount presser for oscillation about column
Y10T 83/8713 With adjustable bed block
Y10T 83/8714 Including presser member reinforcing, or flexure compensating, means
Y10T 83/8716 With manually actuated control apparatus for reciprocation of presser member
Y10T 83/8717	. . By deforming resilient tool or tool support
Y10T 83/8719	. . With transmission yieldable on overload
Y10T 83/872	. . With guard means
Y10T 83/8722	. . . Static
Y10T 83/8723 Adjustable
Y10T 83/8725	. . Including movable, tool protecting, cushioning sheet
Y10T 83/8726	. . Single tool with plural selective driving means
Y10T 83/8727	. . Plural tools selectively engageable with single drive
Y10T 83/8729	. . . Predetermined sequence of selection
Y10T 83/873 Of paired tools
Y10T 83/8732	. . . Turret of tools
Y10T 83/8733	. . Tool movable to cooperate selectively with one of a plurality of mating tools
Y10T 83/8735	. . With means providing for plural steps in tool stroke
Y10T 83/8736	. . Sequential cutting motions
Y10T 83/8737	. . With tool positioning means synchronized with cutting stroke
Y10T 83/8739	. . . Anvil moves into and out of operative position
Y10T 83/874	. . . Straight line positioning

Y10T 83/8742	. . . Tool pair positionable as a unit
Y10T 83/8743 Straight line positioning
Y10T 83/8745	. . . Tool and anvil relatively positionable
Y10T 83/8746 Straight line
Y10T 83/8748	. . . Tool displaceable to inactive position [e.g., for work loading]
Y10T 83/8749 By pivotal motion
Y10T 83/875	. . . With templet surface following tool
Y10T 83/8752	. . . Tool moves work to and against cooperating tool
Y10T 83/8753 With means to clamp or bind work to moving tool
Y10T 83/8755 One tool resiliently mounted or biased
Y10T 83/8756 Work forced through tool aperture or between spaced cooperating tools
Y10T 83/8758 Manually actuated work-moving tool
Y10T 83/8759	. . . With means to connect or disconnect tool and its drive
Y10T 83/8761 Continuously moving drive means [e.g., "gag"]
Y10T 83/8762 Hand actuated connecting means
Y10T 83/8763	. . . Convertible from tool path to another or from implement to machine
Y10T 83/8765	. . . Magnet- or solenoid-actuated tool
Y10T 83/8766 Tool movement modifies actuating circuit
Y10T 83/8768 Solenoid core is tool or tool support
Y10T 83/8769	. . . Cutting tool operative in opposite directions of travel
Y10T 83/8771	. . . Motion direction of tool influenced by resistance of work
Y10T 83/8772	. . . One tool edge of tool pair encompasses work [e.g., wire cutter]
Y10T 83/8773	. . . Bevel or miter cut
Y10T 83/8775	. . . With tool tensioning means
Y10T 83/8776	. . . Constantly urged tool or tool support [e.g., spring biased]
Y10T 83/8778 Ledger blade
Y10T 83/8779 Oscillating tool urged axially
Y10T 83/8781 And urged about pivotal axis
Y10T 83/8782 Stored energy furnishes cutting force
Y10T 83/8784 With reset
Y10T 83/8785 Through return [noncutting] stroke
Y10T 83/8786 Oscillating tool
Y10T 83/8788	. . . Tool return mechanism separate from tool advance mechanism
Y10T 83/8789	. . . With simple revolving motion only
Y10T 83/8791 Tool mounted on radial face of rotor
Y10T 83/8792 Variable speed during one revolution [e.g., intermittent]
Y10T 83/8794 Revolving tool moves through recess in work holder or cooperating tool
Y10T 83/8795 Progressively cutting
Y10T 83/8796 Progressively cutting
Y10T 83/8798	. . . With simple oscillating motion only

Y10T 83/8799	. . .	Plural tool pairs
Y10T 83/8801	Plural tools on single oscillating arm [i.e., tool holder]
Y10T 83/8802	. . .	And means to move cooperating cutter member
Y10T 83/8804	. . .	Tool driver movable relative to tool support
Y10T 83/8805	Cam or eccentric revolving about fixed axis
Y10T 83/8807	Gear or ratchet pawl drives toothed tool support
Y10T 83/8808	Toggle links, one link pivoted to tool support
Y10T 83/8809	Fixed axis lever
Y10T 83/8811	Adjustable mechanical advantage
Y10T 83/8812	. . .	Cutting edge in radial plane
Y10T 83/8814	Adjustable
Y10T 83/8815	With guide means for the cutting member
Y10T 83/8817	. . .	Axially extending cutting edge
Y10T 83/8818	Axially progressing cut
Y10T 83/882	Adjustable
Y10T 83/8821	. .	With simple rectilinear reciprocating motion only
Y10T 83/8822	. . .	Edge-to-edge of sheet or web [e.g., traveling cutter]
Y10T 83/8824	. . .	With provision for dynamic balance
Y10T 83/8825	. . .	With lost motion in tool drive
Y10T 83/8827	. . .	Means to vary force on, or speed of, tool during stroke
Y10T 83/8828	. . .	Plural tools with same drive means
Y10T 83/883	Tools positioned by template
Y10T 83/8831	Plural distinct cutting edges on same support
Y10T 83/8832	Concentrically mounted
Y10T 83/8834	Successively acting
Y10T 83/8835	. . .	And means to move cooperating cutting member
Y10T 83/8837	. . .	With application of force to opposite ends of tool supporting crosshead
Y10T 83/8838	By relatively movable fixed axis levers
Y10T 83/884	By connecting rod articulated with tool support
Y10T 83/8841	. . .	Tool driver movable relative to tool support
Y10T 83/8843	Cam or eccentric revolving about fixed axis
Y10T 83/8844	Gear actuated tool support
Y10T 83/8845	Toggle links, one link pivoted to tool support
Y10T 83/8847	Screw actuated tool support
Y10T 83/8848	Connecting rod articulated with tool support
Y10T 83/885	Fixed axis lever
Y10T 83/8851	Adjustable mechanical advantage
Y10T 83/8853	Including details of guide for tool or tool support
Y10T 83/8854	. . .	Progressively cutting
Y10T 83/8855	. . .	With spaced guide pins [e.g., die set leader pins]

Y10T 83/8857	. . . With inclined guides
Y10T 83/8858	. . . Fluid pressure actuated
Y10T 83/886 Utilizing fluid amplifier
Y10T 83/8861 Diaphragm
Y10T 83/8863 Explosive fluid
Y10T 83/8864 Plural cylinders
Y10T 83/8866 Offset cutter
Y10T 83/8867	. . . With means to adjust tool position on tool holder
Y10T 83/8868 Adjustably mounted cooperating tool
Y10T 83/887	. . Parallel draw-cut [e.g., translatable]
Y10T 83/8871	. . . Link suspension
Y10T 83/8873	. . Straight line motion combined with tilting in plane of stroke
Y10T 83/8874	. . Uniplanar compound motion
Y10T 83/8876	. . . Reciprocating plus work approach [e.g., saw type]
Y10T 83/8877	. . . With gyratory drive
Y10T 83/8878	. . Guide
Y10T 83/888	. . . With nonrigidly positioned member
Y10T 83/8881	. . . With anti-friction means
Y10T 83/8883 Roller with peripheral flange or groove
Y10T 83/8884 Disc
Y10T 83/8886	. . . With means to vary space between opposed members
Y10T 83/8887 By rectilinear movement of member
Y10T 83/8889	. . . With means to adjust position
Y10T 83/889	. Tool with either work holder or means to hold work supply
Y10T 83/896	. . Rotatable wound package supply
Y10T 83/902	. . . Plural supply sources
Y10T 83/909	. Cutter assemblage or cutter element therefor [e.g., chain saw chain]
Y10T 83/913	. . With means permitting removal of cutter element
Y10T 83/917	. . Having diverse cutting elements
Y10T 83/921	. . . And noncutting depth gauge
Y10T 83/925	. . Having noncutting depth gauge
Y10T 83/929	. Tool or tool with support
Y10T 83/9292	. . Wire tool
Y10T 83/9295	. . Work supported tool [e.g., clicker die]
Y10T 83/9297	. . . With product ejection facilitator
Y10T 83/93	. . . With tool manipulating portion
Y10T 83/9302	. . . With tool positioning abutment
Y10T 83/9304	. . . To sever article from work and cut within article
Y10T 83/9307	. . . With tool contour adjusting means
Y10T 83/9309	. . Anvil

Y10T 83/9312	. . .	Rotatable type
Y10T 83/9314	. .	Pointed perforators
Y10T 83/9317	. .	Endless band or belt type
Y10T 83/9319	. .	Toothed blade or tooth therefor
Y10T 83/9321	. . .	With means to vary tooth position
Y10T 83/9324	. . .	With additional cutting means
Y10T 83/9326	. . .	Plural separable sections
Y10T 83/9329	Tooth separable from blade
Y10T 83/9331	By independent connecting element
Y10T 83/9333	Transversely movable
Y10T 83/9336	Arcuately movable
Y10T 83/9338	With additional element to prevent movement of connecting element
Y10T 83/9341	Rectilinearly movable
Y10T 83/9343	By deformation
Y10T 83/9346	. . .	Uniformly varying teeth or tooth spacing
Y10T 83/9348	. . .	Undulating tooth arrangement
Y10T 83/935	. . .	Plural tooth groups
Y10T 83/9353	Including raker tooth group
Y10T 83/9355	Including intermediate raker tooth
Y10T 83/9358	. . .	Series of dissimilar teeth
Y10T 83/936	. . .	Series of allochiral teeth
Y10T 83/9362	. . .	Teeth having transversely curved cutting edge
Y10T 83/9365	. . .	Teeth having cutting edge parallel to blade surface
Y10T 83/9367	. . .	Teeth having cutting edge perpendicular to blade surface
Y10T 83/937	. .	Tool mounted by and between spaced arms
Y10T 83/9372	. .	Rotatable type
Y10T 83/9374	. . .	With spacer interposed between shaft-mounted tools
Y10T 83/9377	. . .	Mounting of tool about rod-type shaft
Y10T 83/9379	At end of shaft
Y10T 83/9382	. . .	Punching plus nonpunching tool
Y10T 83/9384	. . .	Notching plus nonnotching tool
Y10T 83/9387	. . .	Punching tool
Y10T 83/9389	Shear type
Y10T 83/9391	. . .	Notching tool
Y10T 83/9394	. . .	Helical tool
Y10T 83/9396	. . .	Shear type
Y10T 83/9399	Cutting edge wholly parallel to axis of rotation
Y10T 83/9401	Cutting edge wholly normal to axis of rotation
Y10T 83/9403	. . .	Disc type

Y10T 83/9406	. . .	Radially adjustable tool
Y10T 83/9408	. . .	Spaced cut forming tool
Y10T 83/9411	. .	Cutting couple type
Y10T 83/9413	. . .	Spiral type cutter
Y10T 83/9416	. . .	To punch and cut punched article
Y10T 83/9418	. . .	Punching plus nonpunching tool
Y10T 83/942	. . .	Notching plus nonnotching tool
Y10T 83/9423	. . .	Punching tool
Y10T 83/9425	Tool pair
Y10T 83/9428	Shear-type male tool
Y10T 83/943	Multiple punchings
Y10T 83/9432	Plural spaced successively operative shearing portions
Y10T 83/9435	Progressive cutting
Y10T 83/9437	Shear-type female tool
Y10T 83/944	Multiple punchings
Y10T 83/9442	. . .	Notching tool
Y10T 83/9444	Shear type
Y10T 83/9447	. . .	Shear type
Y10T 83/9449	. . .	Spaced cut forming tool
Y10T 83/9452	. . .	With tool contour adjusting means
Y10T 83/9454	. .	Reciprocable type
Y10T 83/9457	. .	Joint or connection
Y10T 83/9459	. . .	Magnetic connection
Y10T 83/9461	. . .	Resiliently biased connection
Y10T 83/9464	. . .	For rotary tool
Y10T 83/9466	Flexible sleevelike tool
Y10T 83/9469	Adjustable
Y10T 83/9471	Rectilinearly
Y10T 83/9473	. . .	For rectilinearly reciprocating tool
Y10T 83/9476	Tool is single element with continuous cutting edge [e.g., punch, etc.]
Y10T 83/9478	Tool is single element reciprocable generally perpendicularly to elongate cutting edge [e.g., shear, etc.]
Y10T 83/9481	Tool is single element reciprocable along elongate cutting edge [e.g., saw blade, etc.]
Y10T 83/9483	Adjustable
Y10T 83/9486	Rectilinearly
Y10T 83/9488	. . .	Adjustable
Y10T 83/949	Rectilinearly
Y10T 83/9493	. .	Stationary cutter
Y10T 83/9495	. . .	Nonparallel cutting edges

- Y10T 83/9498 . . . Parallel cutting edges
- Y10T 83/95 . Machine frame
- Y10T 83/96 . . Guard
- Y10T 83/97 . Miscellaneous

Former US Class 117 Series

- Y10T 117/00** **Single-crystal, oriented-crystal, and epitaxy growth processes; non-coating apparatus therefor**
- Y10T 117/10 . Apparatus
- Y10T 117/1004 . . with means for measuring, testing, or sensing
- Y10T 117/1008 . . . with responsive control means
- Y10T 117/1012 . . . with a window or port for visual observation or examination
- Y10T 117/1016 . . with means for treating single-crystal [e.g., heat treating]
- Y10T 117/102 . . for forming a platelet shape or a small diameter, elongate, generally cylindrical shape [e.g., whisker, fiber, needle, filament]
- Y10T 117/1024 . . for crystallization from liquid or supercritical state
- Y10T 117/1028 . . . Crucibleless apparatus having means providing movement of discrete droplets or solid particles to thin-film precursor [e.g., Verneuil method]
- Y10T 117/1032 . . . Seed pulling
- Y10T 117/1036 including solid member shaping means other than seed or product [e.g., EDFG die]
- Y10T 117/104 Means for forming a hollow structure [e.g., tube, polygon]
- Y10T 117/1044 including means forming a flat shape [e.g., ribbon]
- Y10T 117/1048 Pulling includes a horizontal component
- Y10T 117/1052 including a sectioned crucible [e.g., double crucible, baffle]
- Y10T 117/1056 including details of precursor replenishment
- Y10T 117/106 including sealing means details
- Y10T 117/1064 including a fully-sealed or vacuum-maintained crystallization chamber [e.g., ampoule]
- Y10T 117/1068 including heating or cooling details [e.g., shield configuration]
- Y10T 117/1072 including details of means providing product movement [e.g., shaft guides, servo means]
- Y10T 117/1076 . . . having means for producing a moving solid-liquid-solid zone
- Y10T 117/108 Including a solid member other than seed or product contacting the liquid [e.g., crucible, immersed heating element]
- Y10T 117/1084 having details of a stabilizing feature
- Y10T 117/1088 including heating or cooling details
- Y10T 117/1092 . . . Shape defined by a solid member other than seed or product [e.g., Bridgman-Stockbarger]
- Y10T 117/1096 . . . including pressurized crystallization means [e.g., hydrothermal]

Former US Class 137 series**Y10T 137/00****Fluid handling**

- Y10T 137/0318 . Processes
- Y10T 137/0324 . . With control of flow by a condition or characteristic of a fluid
- Y10T 137/0329 . . . Mixing of plural fluids of diverse characteristics or conditions
- Y10T 137/0335 Controlled by consistency of mixture
- Y10T 137/034 Controlled by conductivity of mixture
- Y10T 137/0346 Controlled by heat of combustion of mixture
- Y10T 137/0352 Controlled by pressure
- Y10T 137/0357 . . . For producing uniform flow
- Y10T 137/0363 . . . For producing proportionate flow
- Y10T 137/0368 . . . By speed of fluid
- Y10T 137/0374 . . . For regulating boiler feed water level
- Y10T 137/0379 . . . By fluid pressure
- Y10T 137/0385 . . Carbonated beverage handling processes
- Y10T 137/0391 . . Affecting flow by the addition of material or energy
- Y10T 137/0396 . . Involving pressure control
- Y10T 137/0402 . . Cleaning, repairing, or assembling
- Y10T 137/0407 . . . Repairing or assembling hydrant [e.g., fireplug, etc.]
- Y10T 137/0413 . . . Gas or water meter repairing or assembling
- Y10T 137/0419 . . . Fluid cleaning or flushing
- Y10T 137/0424 Liquid cleaning or flushing
- Y10T 137/043 Valve or valve seat cleaning
- Y10T 137/0435 Mechanical cleaning [e.g., pig, etc.]
- Y10T 137/0441 Repairing, securing, replacing, or servicing pipe joint, valve, or tank
- Y10T 137/0447 Including joint or coupling
- Y10T 137/0452 Detecting or repairing leak
- Y10T 137/0458 Tapping pipe, keg, or tank
- Y10T 137/0463 Particular aperture forming means
- Y10T 137/0469 Cutter or cutting tool
- Y10T 137/0475 Having deformable or inflatable means
- Y10T 137/048 With content loading or unloading [e.g., dispensing, discharge assistant, etc.]
- Y10T 137/0486 Specific valve or valve element mounting or repairing
- Y10T 137/0491 Valve or valve element assembling, disassembling, or replacing
- Y10T 137/0497 Fluid actuated or retarded
- Y10T 137/0502 Multi way valve
- Y10T 137/0508 Ball valve or rotary ball valve
- Y10T 137/0514 Gate valve

Y10T 137/0519 Plug valve
Y10T 137/0525 Butterfly valve
Y10T 137/053 Float valve
Y10T 137/0536	. Highspeed fluid intake means [e.g., jet engine intake]
Y10T 137/0645	. . With condition responsive control means
Y10T 137/0753	. Control by change of position or inertia of system
Y10T 137/0777	. . With second control
Y10T 137/0801	. . Position relative body of water [e.g., marine governors]
Y10T 137/0826	. . . Float controlled
Y10T 137/085	. . . Pressure or head controlled
Y10T 137/0874	. . Vent opening or closing on tipping container
Y10T 137/0898	. . By shifting of liquid level
Y10T 137/0923	. . By pendulum or swinging member
Y10T 137/0947	. . . With servo connection to valve
Y10T 137/0971	. Speed responsive valve control
Y10T 137/0989	. . Acceleration responsive valve control
Y10T 137/1007	. . With manual valve control
Y10T 137/1026	. . Speed change and excess speed valve control
Y10T 137/1044	. . With other condition responsive valve control
Y10T 137/1062	. . . Governor drive failure responsive
Y10T 137/108	. . Centrifugal mass type [exclusive of liquid]
Y10T 137/1098	. . . With multiple valves
Y10T 137/1116	. . . Periodically actuated valve
Y10T 137/1135	. . . Rotating valve and rotating governor
Y10T 137/1153	. . . Excess speed responsive
Y10T 137/1171	. . . With fluid servo-motor
Y10T 137/1189	. Freeze condition responsive safety systems
Y10T 137/1244	. . With freeze waste
Y10T 137/1298	. . Stop and waste
Y10T 137/1353	. . Low temperature responsive drains
Y10T 137/1407	. Combustion failure responsive fuel safety cut-off for burners
Y10T 137/1516	. . Thermo-electric
Y10T 137/1624	. Destructible or deformable element controlled
Y10T 137/1632	. . Destructible element
Y10T 137/1639	. . . Combined destructible and fusible element
Y10T 137/1647	. . . Explosive actuation
Y10T 137/1654	. . . Separable valve coupling or conduit
Y10T 137/1662 Tensile or sheer pin or bolt
Y10T 137/1669	. . . Tensile or sheer pin or bolt
Y10T 137/1677 Pressure causes pin or bolt to destruct

Y10T 137/1684	. . . With alarm or indicator
Y10T 137/1692	. . . Rupture disc
Y10T 137/1699 Means for holding entire disc after rupture
Y10T 137/1707 Disc burst after destruction of additional element
Y10T 137/1714 Direct pressure causes disc to burst
Y10T 137/1722 Two-way rupture disc
Y10T 137/1729 Dome shape
Y10T 137/1737 Reverse buckling
Y10T 137/1744 Specific weakening point
Y10T 137/1752 Integral disc assembly
Y10T 137/1759 Knife or cutter causes disc to break
Y10T 137/1767 Movable knife or cutter
Y10T 137/1774	. . . With counterbalancing element
Y10T 137/1782	. . . Frangible element returns pressure responsive valve
Y10T 137/1789	. . . Having pressure responsive valve
Y10T 137/1797	. . Heat destructible or fusible
Y10T 137/1804	. . . With second sensing means
Y10T 137/1812	. . . In fluid flow path
Y10T 137/1819	. . . Safety cut-off
Y10T 137/1827 With heater for destructible or fusible element
Y10T 137/1834 With external closing means
Y10T 137/1842	. Ambient condition change responsive
Y10T 137/1866	. . For controlling soil irrigation
Y10T 137/189	. . . Soil moisture sensing
Y10T 137/1915	. . Burner gas cutoff
Y10T 137/1939	. . Atmospheric
Y10T 137/1963	. . . Temperature
Y10T 137/1987 With additional diverse control
Y10T 137/2012	. . . Pressure
Y10T 137/2036	. . Underwater
Y10T 137/206	. Flow affected by fluid contact, energy field or coanda effect [e.g., pure fluid device or system]
Y10T 137/2065	. . Responsive to condition external of system
Y10T 137/2071	. . . And causing change or correction of sensed condition
Y10T 137/2076	. . Utilizing diverse fluids
Y10T 137/2082	. . Utilizing particular fluid
Y10T 137/2087	. . Means to cause rotational flow of fluid [e.g., vortex generator]
Y10T 137/2093	. . . Plural vortex generators
Y10T 137/2098	. . . Vortex generator as control for system
Y10T 137/2104	. . . Vortex generator in interaction chamber of device

Y10T 137/2109	. . . By tangential input to axial output [e.g., vortex amplifier]
Y10T 137/2115 With means to vary input or output of device
Y10T 137/212	. . System comprising plural fluidic devices or stages
Y10T 137/2125	. . . Plural power inputs [e.g., parallel inputs]
Y10T 137/2131 Variable or different-value power inputs
Y10T 137/2136 Pulsating power input and continuous-flow power input
Y10T 137/2142 With variable or selectable source of control-input signal
Y10T 137/2147 To cascaded plural devices
Y10T 137/2153 With feedback passage[s] between devices of cascade
Y10T 137/2158 With pulsed control-input signal
Y10T 137/2164	. . Plural power inputs to single device
Y10T 137/2169	. . . Intersecting at interaction region [e.g., comparator]
Y10T 137/2174 Co-lineal, oppositely-directed power inputs [e.g., impact modulator]
Y10T 137/218	. . Means to regulate or vary operation of device
Y10T 137/2185	. . . To vary frequency of pulses or oscillations
Y10T 137/2191	. . . By non-fluid energy field affecting input [e.g., transducer]
Y10T 137/2196 Acoustical or thermal energy
Y10T 137/2202	. . . By movable element
Y10T 137/2207 Operating at timed intervals [e.g., to produce pulses]
Y10T 137/2213 Electrically-actuated element [e.g., electro-mechanical transducer]
Y10T 137/2218 Means [e.g., valve] in control input
Y10T 137/2224	. . Structure of body of device
Y10T 137/2229	. . Device including passages having V over T configuration
Y10T 137/2234	. . . And feedback passage[s] or path[s]
Y10T 137/224	. . . With particular characteristics of control input
Y10T 137/2245 Multiple control-input passages
Y10T 137/2251	. . . And multiple or joined power-outlet passages
Y10T 137/2256	. . . And enlarged interaction chamber
Y10T 137/2262	. . . And vent passage[s]
Y10T 137/2267	. . Device including passages having V over gamma configuration
Y10T 137/2273	. . Device including linearly-aligned power stream emitter and power stream collector
Y10T 137/2278	. Pressure modulating relays or followers
Y10T 137/2322	. . Jet control type
Y10T 137/2365	. . Plural series units
Y10T 137/2409	. . With counter-balancing pressure feedback to the modulating device
Y10T 137/2452	. . . With counter-counter balancing pressure feedback
Y10T 137/2496	. Self-proportioning or correlating systems
Y10T 137/2499	. . Mixture condition maintaining or sensing
Y10T 137/2501	. . . Dividing and recombining flow
Y10T 137/2504	. . . By specific gravity

Y10T 137/2506	. . .	By viscosity or consistency
Y10T 137/2509	. . .	By optical or chemical property
Y10T 137/2511	. .	Fuel controlled by boiler or water system condition
Y10T 137/2514	. .	Self-proportioning flow systems
Y10T 137/2516	. . .	Interconnected flow displacement elements
Y10T 137/2519	Movable trap chamber
Y10T 137/2521	. . .	Flow comparison or differential response
Y10T 137/2524	Flow dividers [e.g., reversely acting controls]
Y10T 137/2526	Main line flow displaces or entrains material from reservoir
Y10T 137/2529	With electrical controller
Y10T 137/2531	. . .	Flow displacement element actuates electrical controller
Y10T 137/2534	. . .	Liquid level response
Y10T 137/2536	Float controlled weir or valve
Y10T 137/2539	Swinging outlet pipe controller
Y10T 137/2541	. . .	With measuring type discharge assistant
Y10T 137/2544	. .	Supply and exhaust type
Y10T 137/2546	. . .	Vacuum or suction pulsator type [e.g., milking machine]
Y10T 137/2549	With trip linkage or snap action
Y10T 137/2552	With pulsation responsive pilot valve
Y10T 137/2554	. . .	Reversing or 4-way valve systems
Y10T 137/2557	. . .	Waste responsive to flow stoppage
Y10T 137/2559	. .	Self-controlled branched flow systems
Y10T 137/2562	. . .	Dividing and recombining
Y10T 137/2564	. . .	Plural inflows
Y10T 137/2567	Alternate or successive inflows
Y10T 137/2569	Control by depletion of source
Y10T 137/2572	One inflow supplements another
Y10T 137/2574	. . .	Bypass or relief controlled by main line fluid condition
Y10T 137/2577	Liquid level responsive
Y10T 137/2579	Flow rate responsive
Y10T 137/2582	Including controlling main line flow
Y10T 137/2584	Relief or bypass closes as main opens
Y10T 137/2587	Bypass or relief valve biased open
Y10T 137/2589	Pilot valve operated
Y10T 137/2592	Carried choke
Y10T 137/2594	Choke
Y10T 137/2597	Variable choke resistance
Y10T 137/2599	Venturi
Y10T 137/2602	Flapper
Y10T 137/2605	Pressure responsive

Y10T 137/2607	With pressure reducing inlet valve
Y10T 137/261	Relief port through common sensing means
Y10T 137/2612	Common sensor for both bypass or relief valve and other branch valve
Y10T 137/2615	Bypass or relief valve opens as other branch valve closes
Y10T 137/2617	Bypass or relief valve biased open
Y10T 137/262	Increasing pressure progressively closes then reopens by-pass or relief valve
Y10T 137/2622	Bypass or relief valve responsive to pressure downstream of outlet valve
Y10T 137/2625	Pilot valve
Y10T 137/2627	Outlet valve carried by bypass or relief valve
Y10T 137/263	Plural sensors for single bypass or relief valve
Y10T 137/2632	Sensors interconnected by timing or restrictive orifice
Y10T 137/2635	Pilot valve operated
Y10T 137/2637	Mechanical movement between sensor and valve
Y10T 137/264	Electrical control
Y10T 137/2642	Sensor rigid with valve
Y10T 137/2645	Flexible sensor
Y10T 137/2647	Pressure responsive outlet valve
Y10T 137/265	Plural outflows
Y10T 137/2652	Single actuator operates plural outlets simultaneously
Y10T 137/2655	Biased open isolation valve
Y10T 137/2657	Flow rate responsive
Y10T 137/266	Primer valve
Y10T 137/2663	Pressure responsive
Y10T 137/2665	With external control for correlating valve [e.g., manual]
Y10T 137/2668	Alternately or successively substituted outflow
Y10T 137/267	Control by filling auxiliary gravitating or float operating tank
Y10T 137/2673	Control by filling outlet tank or receiver
Y10T 137/2675	Float controlled
Y10T 137/2678	Four port reversing valve
Y10T 137/268	Responsive to pressure or flow interruption
Y10T 137/2683	Plural outlets control with automatic reset
Y10T 137/2685	Manually set to a single outflow position
Y10T 137/2688	Flow rate responsive
Y10T 137/269	Flow sensing turbine
Y10T 137/2693	Pressure responsive
Y10T 137/2695	Responsive to outlet pressure
Y10T 137/2698	Electrical control
Y10T 137/27	Liquid level responsive
Y10T 137/2703	Flow rate responsive

Y10T 137/2705	. . . Pressure differential
Y10T 137/2708	. . Plural sensors
Y10T 137/271	. . . For single valve
Y10T 137/2713	. Siphons
Y10T 137/272	. . Plural
Y10T 137/2727	. . . Tank truck mounted
Y10T 137/2733	. . . Sequentially discharging in parallel
Y10T 137/274 From plural tanks
Y10T 137/2747	. . . Main siphon with auxiliary starting, stopping or resetting siphon
Y10T 137/2754 Sinking or bucket-type float operated main siphon, float emptying auxiliary siphon
Y10T 137/2761	. . With discharge-controlling receiver
Y10T 137/2768	. . . With float
Y10T 137/2774	. . Periodic or accumulation responsive discharge
Y10T 137/2781	. . . With manual control
Y10T 137/2788	. . . Control by filling auxiliary tank
Y10T 137/2795	. . . Float-operated inlet to siphon
Y10T 137/2802	. . . Release of trapped air
Y10T 137/2808 Through float-operated vent
Y10T 137/2815 Through liquid trap seal
Y10T 137/2822 Auxiliary liquid trap seal
Y10T 137/2829	. . With strainer, filter, separator or sediment trap
Y10T 137/2836	. . With recorder, register, signal, indicator or inspection window
Y10T 137/2842	. . With flow starting, stopping or maintaining means
Y10T 137/2849	. . . Siphon venting or breaking
Y10T 137/2856	. . . With leakage or entrained air removal
Y10T 137/2863	. . . Pressure applied to liquid in supply chamber
Y10T 137/287	. . . Plunge or immersion starting
Y10T 137/2877	. . . Pump or liquid displacement device for flow passage
Y10T 137/2883 Piston
Y10T 137/289 Co-axial within flow passage
Y10T 137/2897 Collapsible bulb
Y10T 137/2904	. . . Siphon inlet movable to and from seat
Y10T 137/2911	. . . With valve or closure in-flow passage
Y10T 137/2917	. . With means for mounting and/or positioning relative to siphon chamber
Y10T 137/2924	. . Elements
Y10T 137/2931	. Diverse fluid containing pressure systems
Y10T 137/2934	. . Gas lift valves for wells
Y10T 137/2937	. . Gas pressure discharge of liquids feed traps [e.g., to boiler]
Y10T 137/294	. . . Gas pressure controlled by amount of liquids in boiler or discharge receiver

Y10T 137/2943	Pressure connection at liquid level in boiler or discharge receiver
Y10T 137/2947	. . .	Gas pressure controlled by amount of liquid in trap
Y10T 137/295	Plural trap chambers
Y10T 137/2953	Gravitating
Y10T 137/2956	Gravitating vessel
Y10T 137/2959	Sinking or bucket type float
Y10T 137/2962	Pivoted vessel with fluid passage through pivot
Y10T 137/2965	Float responsive
Y10T 137/2968	Liquid control valve positively actuated
Y10T 137/2971	Gas condensing type
Y10T 137/2975	Gas inlet and outlet valves unitary
Y10T 137/2978	. . .	Gas pressure controlled by manual or cyclic means
Y10T 137/2981	Movable trap chamber
Y10T 137/2984	. .	Foam control in gas charged liquids
Y10T 137/2987	. . .	Level or pressure responsive
Y10T 137/299	. . .	Separate handling of foam
Y10T 137/2993	. . .	With conditioning trap or chamber
Y10T 137/2996	Recarbonation
Y10T 137/30	With trap or chamber by-pass
Y10T 137/3003	. .	Fluid separating traps or vents
Y10T 137/3006	. . .	Liquids separated from liquid
Y10T 137/3009	. . .	Plural discriminating outlets for diverse fluids
Y10T 137/3012	Common actuator for control valves
Y10T 137/3015	Choke or restricted passage gas bleed
Y10T 137/3018	From above liquid level
Y10T 137/3021	. . .	Discriminating outlet for liquid
Y10T 137/3024	With alternately operated inlet and outlet valves
Y10T 137/3028	With non-discriminating gas vent or liquid discharge
Y10T 137/3031	Abnormal pressure responsive liquid blow-off or drain
Y10T 137/3034	Manual control
Y10T 137/3037	With auxiliary inlet or by-pass valve
Y10T 137/304	With fluid responsive valve
Y10T 137/3043	Successively opened valves
Y10T 137/3046	Gas collecting float [e.g., inverted bucket]
Y10T 137/3049	Downstream from valve
Y10T 137/3052	Level responsive
Y10T 137/3056	Weight or pressure
Y10T 137/3059	Gravitating vessel
Y10T 137/3062	Sinking or bucket type float
Y10T 137/3065	Servo-control

Y10T 137/3068 Float
Y10T 137/3071 With main line gas outlet from trap chamber
Y10T 137/3074 With outlet extending above liquid in trap
Y10T 137/3077 Servo-control
Y10T 137/308 With pressure balanced outlet valve
Y10T 137/3084	. . . Discriminating outlet for gas
Y10T 137/3087 With reverse flow stop or pressure regulating valve
Y10T 137/309 Fluid sensing valve
Y10T 137/3093 With vaporized liquid stop
Y10T 137/3096 With separate return for condensate
Y10T 137/3099 Float responsive
Y10T 137/3102	. . . With liquid emptying means
Y10T 137/3105 Self-emptying
Y10T 137/3109	. . Liquid filling by evacuating container
Y10T 137/3112	. . Main line flow displaces additive from shunt reservoir
Y10T 137/3115	. . Gas pressure storage over or displacement of liquid
Y10T 137/3118	. . . Surge suppression
Y10T 137/3121	. . . With return of liquid to supply
Y10T 137/3124	. . . Plural units
Y10T 137/3127	. . . With gas maintenance or application
Y10T 137/313 Gas carried by or evolved from liquid
Y10T 137/3133 Gas injectors
Y10T 137/3137 Gas injected by liquid pressure or flow
Y10T 137/314 Unitary mounting for gas pressure inlet and liquid outlet
Y10T 137/3143	. . . With liquid level responsive gas vent or whistle
Y10T 137/3146 Combined high and low level responsive
Y10T 137/3149	. Back flow prevention by vacuum breaking [e.g., anti-siphon devices]
Y10T 137/3185	. . Air vent in liquid flow line
Y10T 137/3222	. . . With liquid seal in liquid flow line
Y10T 137/3258 Automatic valve in vent line
Y10T 137/3294	. . . Valved
Y10T 137/3331 With co-acting valve in liquid flow path
Y10T 137/3367	. Larner-Johnson type valves; i.e., telescoping internal valve in expanded flow line section
Y10T 137/3421	. . Line condition change responsive
Y10T 137/3476	. . Internal servo-motor with internal pilot valve
Y10T 137/353	. . . Pilot controlled passage in nose or needle
Y10T 137/3584	. Inflatable article [e.g., tire filling chuck and/or stem]
Y10T 137/36	. . With pressure-responsive pressure-control means
Y10T 137/3615	. . . Pulsating

Y10T 137/3631	. . .	Diaphragm, bellows or expansible tube
Y10T 137/3646	. . .	Co-axial inflation and relief valves
Y10T 137/3662	. .	With gauge or indicator
Y10T 137/3677	. . .	With deflating means
Y10T 137/3693	. . .	Selectively connected
Y10T 137/3709	. .	Stem attached relief valve
Y10T 137/3724	. .	With coupling means
Y10T 137/374	. .	With cap
Y10T 137/3755	. . .	Valve actuating, assembling or locking means on cap
Y10T 137/3771	Valve manually seated
Y10T 137/3786	. .	Removable valve head and seat unit [valve insides]
Y10T 137/3802	. .	With vehicle guide or support, e.g., service station
Y10T 137/402	. .	Distribution systems involving geographic features
Y10T 137/4238	. .	With cleaner, lubrication added to fluid or liquid sealing at valve interface
Y10T 137/4245	. .	Cleaning or steam sterilizing
Y10T 137/4252	. . .	Reverse fluid flow
Y10T 137/4259	. . .	With separate material addition
Y10T 137/4266	. . .	Steam sterilizing
Y10T 137/4273	. . .	Mechanical cleaning
Y10T 137/428	Valve grinding motion of valve on seat
Y10T 137/4287	Concentric stem
Y10T 137/4294	Spring pressed
Y10T 137/4301	Lost motion permits grinding
Y10T 137/4308	With swivel-preventing means
Y10T 137/4315	Nut releasable from body and/or stem
Y10T 137/4322	With independent grinding actuator
Y10T 137/4329	Separable
Y10T 137/4336	Cleaning member reciprocates in passage
Y10T 137/4343	By-pass cleaning
Y10T 137/4351	Independent actuation
Y10T 137/4358	. .	Liquid supplied at valve interface
Y10T 137/4365	. . .	Plural feed
Y10T 137/4372	. . .	Line pressure feed
Y10T 137/4379	. . .	Feed by or with actuation
Y10T 137/4386	. . .	Loss control
Y10T 137/4393	. . .	Screw feed
Y10T 137/44	With check valve
Y10T 137/4407	Excess relief
Y10T 137/4414	Jacking
Y10T 137/4421	Jacking

Y10T 137/4428 Seating
Y10T 137/4435	. . . Spring biased piston feed
Y10T 137/4442	. . . External pressure
Y10T 137/4449	. . . Gravity or capillary feed
Y10T 137/4456	. With liquid valves or liquid trap seals
Y10T 137/4463	. . Liquid seal in liquid flow line; flow liquid forms seal
Y10T 137/4471	. . . Valves
Y10T 137/4478 Line condition change responsive
Y10T 137/4486 Plural valves or valve seats
Y10T 137/4493 Pivoted valve
Y10T 137/4501 Ball valve
Y10T 137/4508 Seats vertically up
Y10T 137/4516	. . . Seal replenishers
Y10T 137/4523	. . . Plural inlet
Y10T 137/4531	. . . Divided and recombined passages
Y10T 137/4538	. . . Tangential inlet flow
Y10T 137/4546	. . . Downward partition encircles projecting outlet
Y10T 137/4553	. . . Submerged inlet pipe end
Y10T 137/4561 Hinged seal bowl
Y10T 137/4568 Distinct seal bowl in flow line connected casing
Y10T 137/4576	. . . U-seals
Y10T 137/4583 Topside access beneath cover plate closed floor opening
Y10T 137/4591 Enlarged upflow leg
Y10T 137/4598 Topside access opening
Y10T 137/4606 Even diameter legs
Y10T 137/4613 Access opening
Y10T 137/4621	. . Seal for relatively movable valving parts
Y10T 137/4628	. . . Horizontally moving valve
Y10T 137/4636 Rotary
Y10T 137/4643	. . Liquid valves
Y10T 137/4651	. . . Branched passage for sealing liquid
Y10T 137/4658	. . . With auxiliary means for varying liquid level
Y10T 137/4666	. . . With baffle
Y10T 137/4673	. Plural tanks or compartments with parallel flow
Y10T 137/469	. . Sequentially filled and emptied [e.g., holding type]
Y10T 137/4707	. . . With relative rotation of tank group and filling head
Y10T 137/4723 With rotary filling and emptying head
Y10T 137/474	. . With housings, supports or stacking arrangements
Y10T 137/4757	. . Battery or electrolytic cell replenishment
Y10T 137/4774	. . . Barometric supply

Y10T 137/479	. . Flow dividing compartments
Y10T 137/4807	. . Tank type manifold [i.e., one tank supplies or receives from at least two others]
Y10T 137/4824	. . Tank within tank
Y10T 137/4841	. . With cross connecting passage
Y10T 137/4857	. . With manifold or grouped outlets
Y10T 137/4874	. . . Tank truck type
Y10T 137/4891	. With holder for solid, flaky or pulverized material to be dissolved or entrained
Y10T 137/5109	. Convertible
Y10T 137/5153	. . Reversible check
Y10T 137/5196	. . Unit orientable in a single location between plural positions
Y10T 137/524	. . . Reversible stop and vent or waste
Y10T 137/5283	. . Units interchangeable between alternate locations
Y10T 137/5327	. Hydrant type
Y10T 137/5333	. . Water crane type
Y10T 137/5339	. . . Spout operated valve
Y10T 137/5345	. . . Rotating riser
Y10T 137/535 Spout articulated to riser
Y10T 137/5356 Vertically movable riser
Y10T 137/5362	. . . Extensible spout
Y10T 137/5368	. . . Spout articulated to riser
Y10T 137/5374	. . Plural riser
Y10T 137/538	. . Expansible chamber operated by valve actuator for draining riser
Y10T 137/5386	. . With pump or ejector
Y10T 137/5392	. . Removable valve and valve seat
Y10T 137/5397	. . . With extension to facilitate removal
Y10T 137/5403	. . Removable valve with supplemental check valve
Y10T 137/5409	. . Movable riser actuated valve
Y10T 137/5415	. . . Reciprocating riser
Y10T 137/5421 Piston type valve
Y10T 137/5427	. . Balanced valve
Y10T 137/5433	. . Valve actuator extends laterally from bottom of riser
Y10T 137/5438	. . Valve actuator outside riser
Y10T 137/5444	. . . Lever actuator
Y10T 137/545	. . . With casing, flush with ground or pavement surface
Y10T 137/5456	. . With casing
Y10T 137/5462	. . . Flush with ground or pavement surface
Y10T 137/5468	. . . Cap, cover or hood
Y10T 137/5474	. . . With heater
Y10T 137/5479	. . With actuator lubricating means
Y10T 137/5485	. . With valve at outlet

Y10T 137/5491	. . With supplemental valve
Y10T 137/5497	. . Protection against freezing
Y10T 137/5503	. . . Stop and waste
Y10T 137/5509 With disabling means
Y10T 137/5515 Separate relatively movable valves with single actuator
Y10T 137/5521 Unidirectional abutting connection between main valve or actuator and waste valve
Y10T 137/5526 With screw or gear in actuating mechanism
Y10T 137/5532 Reciprocating relatively fixed valves
Y10T 137/5538 Waste through lower valve guide
Y10T 137/5544	. Reversing valves - regenerative furnace type
Y10T 137/5617	. . With cooling
Y10T 137/5689	. . Rotary reversing valve
Y10T 137/5762	. With leakage or drip collecting
Y10T 137/5835	. . Relatively movable receptacle or drain pipe and outlet
Y10T 137/5907	. . Collector for waste liquid derived from solid, gas or vapor
Y10T 137/598	. With repair, tapping, assembly, or disassembly means
Y10T 137/5983	. . Blow out preventer or choke valve device [e.g., oil well flow controlling device, etc.]
Y10T 137/5987	. . Solenoid or electromagnetically operated valve
Y10T 137/599	. . Pressure regulating type valve
Y10T 137/5994	. . . Diaphragm type
Y10T 137/5997	. . Gas or water meter replacing
Y10T 137/60	. . Assembling or disassembling flexible tube or sleeve type valve
Y10T 137/6004	. . Assembling or disassembling float or float valve
Y10T 137/6007	. . Assembling or disassembling multi way valve
Y10T 137/6011	. . Assembling, disassembling, or removing cartridge type valve [e.g., insertable and removable as a unit, etc.]
Y10T 137/6014	. . . Faucet type [e.g., domestic water use, etc.]
Y10T 137/6017 Including removable valve head and seat unit
Y10T 137/6021 Including mechanical movement actuator
Y10T 137/6024 Particular handle or handle fastening means
Y10T 137/6028	. . Assembling or disassembling pivoted valve
Y10T 137/6031	. . Assembling or disassembling rotary valve
Y10T 137/6035	. . . Rotary ball valve
Y10T 137/6038 Particular valve seat or interface seal
Y10T 137/6041 Replaceable
Y10T 137/6045 With top entry valve
Y10T 137/6048	. . . Butterfly valve
Y10T 137/6052 Having valve head or seat packing
Y10T 137/6055 With head and stem collections

Y10T 137/6058	. . . Plug valve
Y10T 137/6062 Having retainer at actuator end
Y10T 137/6065	. . Assembling or disassembling reciprocating valve
Y10T 137/6069	. . . Having particularly packed or sealed mechanical movement actuator
Y10T 137/6072	. . . Gate valve
Y10T 137/6075 Bifaced
Y10T 137/6079 Having particular valve seat
Y10T 137/6082 Including seal
Y10T 137/6086	. . Assembling or disassembling check valve
Y10T 137/6089	. . With mechanical movement between actuator and valve
Y10T 137/6092	. . . Plural motions of valve
Y10T 137/6096	. . . Lever type
Y10T 137/6099	. . . Gear type
Y10T 137/6103	. . . Cam type
Y10T 137/6106	. . . Screw type
Y10T 137/6109	. . Tool for applying or removing valve or valve member
Y10T 137/6113	. . . Including sealing feature
Y10T 137/6116	. . With holding means functioning only during transportation assembly or disassembly
Y10T 137/612	. . Tapping a pipe, keg, or apertured tank under pressure
Y10T 137/6123	. . . With aperture forming means
Y10T 137/6126	. . . Imperforate closure removing and holding tap
Y10T 137/613	. . . With valved closure or bung
Y10T 137/6133 Combined rotary and longitudinal movement of valve
Y10T 137/6137 Longitudinal movement of valve
Y10T 137/614 Rotary movement of valve
Y10T 137/6144	. . . With core ejectors
Y10T 137/6147 Impact operated
Y10T 137/615	. . Foot valve extraction from top of enclosure
Y10T 137/6154	. . With disassembly tool engaging feature
Y10T 137/6157	. . . Wrench engaging lugs
Y10T 137/6161	. . With provision of alternate wear parts
Y10T 137/6164	. . . Valve heads and/or seats
Y10T 137/6167 Opposite duplicate surfaces of unitary structure
Y10T 137/6171 Homogeneous material
Y10T 137/6174 Valve heads
Y10T 137/6178 Different portions of continuous surfaces
Y10T 137/6181 Successively used adjacent independent elements
Y10T 137/6184	. . Removable valve with normally disabled supplemental check valve
Y10T 137/6188	. . . Check valve disabled by normally movable main valve part

Y10T 137/6191 Ball check
Y10T 137/6195 Spring bias
Y10T 137/6198	. Non-valving motion of the valve or valve seat
Y10T 137/6253	. . Rotary motion of a reciprocating valve
Y10T 137/6307	. . . Turbine on valve
Y10T 137/6362	. . . Manual rotating means
Y10T 137/6416	. With heating or cooling of the system
Y10T 137/6443	. . With burner
Y10T 137/647	. . . Flue extending through fluid
Y10T 137/6497	. . Hot and cold water system having a connection from the hot to the cold channel
Y10T 137/6525	. . Air heated or cooled [fan, fins, or channels]
Y10T 137/6552	. . With diversion of part of fluid to heat or cool the device or its contents
Y10T 137/6579	. . Circulating fluid in heat exchange relationship
Y10T 137/6606	. . With electric heating element
Y10T 137/6633	. With fluid system support for workman or non-system material
Y10T 137/6851	. With casing, support, protector or static constructional installations
Y10T 137/6855	. . Vehicle
Y10T 137/6858	. . . Locomotive
Y10T 137/6862 Boiler or steam dome
Y10T 137/6866	. . . Railway car
Y10T 137/6869 Car frame
Y10T 137/6873 End of car
Y10T 137/6877 Roof, wall or floor
Y10T 137/6881	. . . Automotive
Y10T 137/6884 Steering post or wheel
Y10T 137/6888 Dash
Y10T 137/6892 Floor or frame
Y10T 137/6895 Fender or running board
Y10T 137/6899	. . . With hose reel storage means
Y10T 137/6903	. . . Guided by means of track or guideway
Y10T 137/6906	. . . Aerial or water-supported [e.g., airplane or ship, etc.]
Y10T 137/691	. . . With retractable or nonuse-positionable support wheel
Y10T 137/6914	. . . Vehicle supports fluid compressor and compressed fluid storage tank
Y10T 137/6918	. . With hose storage or retrieval means
Y10T 137/6921	. . . With means for plural hoses
Y10T 137/6925	. . . With flow regulation responsive to hose movement
Y10T 137/6929 Reel type
Y10T 137/6932	. . . With retrieval means
Y10T 137/6936 Power stop or brake
Y10T 137/694 Responsive to position of hose in casing

Y10T 137/6943	Biased to retracted position
Y10T 137/6947	Boom type
Y10T 137/6951	Weighted
Y10T 137/6954	. . .	Reel with support therefor
Y10T 137/6958	Ground supported
Y10T 137/6962	. . .	Basket or holder for folded coiled hose
Y10T 137/6966	. .	Static constructional installations
Y10T 137/6969	. . .	Buildings
Y10T 137/6973	Outside access to portions of the system
Y10T 137/6977	Escutcheon type support
Y10T 137/698	Wall
Y10T 137/6984	Recessed gas outlet box
Y10T 137/6988	Floor installation
Y10T 137/6991	. . .	Ground supporting enclosure
Y10T 137/6995	Valve and meter wells
Y10T 137/6999	With means to center well on valve
Y10T 137/7002	Detachable base plate
Y10T 137/7006	Vertical casing aligned by valve casing
Y10T 137/701	Combined with actuator
Y10T 137/7014	Telescopic well casing
Y10T 137/7017	Telescopic well casing
Y10T 137/7021	Covers
Y10T 137/7025	Pipe line transport
Y10T 137/7028	. . .	Tapering or tower type
Y10T 137/7032	. .	Furniture and housing furnishings
Y10T 137/7036	. .	Jacketed
Y10T 137/7039	. .	Tank supports
Y10T 137/7043	. .	Guards and shields
Y10T 137/7047	. . .	Resilient abutment for preventing breakage
Y10T 137/7051	. . .	Nozzle abutment for scratch or damage prevention
Y10T 137/7054	. . .	Cover for beer cooler aperture for faucet
Y10T 137/7058	. . .	Sanitary covers or shields
Y10T 137/7062	. . .	Valve guards
Y10T 137/7065	With means for accommodating a detachable actuator
Y10T 137/7069	. .	With lock or seal
Y10T 137/71	. .	With seal
Y10T 137/7131	. .	Common lock and valve actuator
Y10T 137/7162	. . .	Combination lock
Y10T 137/7194	. . .	Biased valve
Y10T 137/7225	. . .	Mechanical movement between lock and valve

Y10T 137/7256	. . Locks against rotary motion
Y10T 137/7287	. Liquid level responsive or maintaining systems
Y10T 137/729	. . Washing machine cycle control
Y10T 137/7293	. . Liquid excluding devices for gas inlet or outlets
Y10T 137/7297	. . With second diverse control
Y10T 137/73	. . . Manual control
Y10T 137/7303	. . Control of both inflow and outflow of tank
Y10T 137/7306	. . Electrical characteristic sensing
Y10T 137/731	. . With control fluid connection at desired liquid level
Y10T 137/7313	. . Control of outflow from tank
Y10T 137/7316	. . . Self-emptying tanks
Y10T 137/7319 By float
Y10T 137/7323	. . . By float
Y10T 137/7326 Low level safety cut-off
Y10T 137/7329	. . With supplemental or safety closing means or bias
Y10T 137/7332	. . . Sinking or bucket type float
Y10T 137/7336	. . . Gravitating tank
Y10T 137/7339	. . By weight of accumulated fluid
Y10T 137/7342	. . . In sinking or bucket type float
Y10T 137/7345	. . . Oil burner fuel overflow preventing safety cut-offs
Y10T 137/7349	. . . In communicating measuring vessel
Y10T 137/7352 Top and bottom connections
Y10T 137/7355	. . . In gravitating tank
Y10T 137/7358	. . By float controlled valve
Y10T 137/7361	. . . Valve opened by external means, closing or closing control by float
Y10T 137/7365	. . . Single float controls plural valves
Y10T 137/7368	. . . Servo relay operation of control
Y10T 137/7371 Fluid pressure
Y10T 137/7374 Flexible diaphragm valve
Y10T 137/7378 From tank
Y10T 137/7381	. . . Quick acting
Y10T 137/7384 Pilot float released
Y10T 137/7387 Over center mechanism
Y10T 137/7391 Shifting weight
Y10T 137/7394 Trip mechanism
Y10T 137/7397 Weight or spring bias
Y10T 137/74 Lost motion mechanism
Y10T 137/7404	. . . Plural floats
Y10T 137/7407	. . . With counter-balance
Y10T 137/741 Within tank

Y10T 137/7413	. . .	Level adjustment or selection means
Y10T 137/7417	. . .	With float leakage disposal
Y10T 137/742	. . .	In separate communicating float chamber
Y10T 137/7423	. . .	Rectilinearly traveling float
Y10T 137/7426	Float co-axial with valve or port
Y10T 137/743	Float is spreader or anti-splash means
Y10T 137/7433	Float surrounds inlet pipe
Y10T 137/7436	Float rigid with valve
Y10T 137/7439	. . .	Float arm operated valve
Y10T 137/7442	With valve retarder or cushion means
Y10T 137/7446	With flow guide or restrictor
Y10T 137/7449	External hood or deflector or annular outlet surrounding the inlet pipe
Y10T 137/7452	Movable nozzle or inlet terminal
Y10T 137/7455	Valve removable from outside container
Y10T 137/7459	With U-shaped inlet pipe having terminal valve
Y10T 137/7462	With refill pipe
Y10T 137/7465	Assembly mounted on and having reciprocating valve element coaxial with inlet pipe
Y10T 137/7468	Horizontal or side entering pipe
Y10T 137/7472	Vertical inlet riser
Y10T 137/7475	With toggle or second lever connected to valve
Y10T 137/7478	With interposed cam, gear or threaded connection
Y10T 137/7481	Rotary valve element
Y10T 137/7485	Pivoted valve
Y10T 137/7488	Ball valves
Y10T 137/7491	Balanced valves
Y10T 137/7494	Flexible valve
Y10T 137/7498	. .	Barometric
Y10T 137/7501	. . .	With shut-off between supply tank and receiver
Y10T 137/7504	. .	Removable valve head and seat unit
Y10T 137/7559	. .	Pump type
Y10T 137/7613	. .	Threaded into valve casing
Y10T 137/7668	. .	Retained by bonnet or closure
Y10T 137/7722	. .	Line condition change responsive valves
Y10T 137/7723	. .	Safety cut-off requiring reset
Y10T 137/7724	. . .	Thermal
Y10T 137/7725	. . .	Responsive to both high and low pressure or velocity
Y10T 137/7726	. . .	Responsive to change in rate of flow
Y10T 137/7727	Excessive flow cut-off
Y10T 137/7728	. . .	High pressure cut-off

Y10T 137/7729	. . .	Reset by pressure equalization valve or by-pass
Y10T 137/773	. . .	Fluid released trip
Y10T 137/7731	. . .	Fluid counter-biased or unseated valve
Y10T 137/7732	With mechanical stop against reopening
Y10T 137/7733	With fluid pressure seating of valve
Y10T 137/7734	. .	Fluid opened valve requiring reset
Y10T 137/7736	. .	Consistency responsive
Y10T 137/7737	. .	Thermal responsive
Y10T 137/7738	. .	Pop valves
Y10T 137/7739	. . .	Pop closing valves
Y10T 137/774	. . .	Pop pressure reactor in inflow to valve
Y10T 137/7741	. . .	Pop pressure reactor in branched released path
Y10T 137/7742	Separate relief valves or valves for each branch
Y10T 137/7743	. . .	Lost motion between pop pressure reactor and valve
Y10T 137/7744	. . .	Adjustable choke
Y10T 137/7745	Annular lip or baffle
Y10T 137/7746	On movable valve part
Y10T 137/7747	Screw threaded
Y10T 137/7748	. .	Combustion engine induction type
Y10T 137/7749	. . .	Valve in auxiliary inlet to induction line
Y10T 137/775	. . .	With manual modifier
Y10T 137/7751	. . .	With suction compensator
Y10T 137/7752	. . .	With separate reactor surface
Y10T 137/7753	. . .	Unbalanced pivoted valve [e.g., unbalanced butterfly type]
Y10T 137/7754	. .	Line flow effect assisted
Y10T 137/7755	. . .	Reactor surface normal to flow
Y10T 137/7756	. . .	Reactor surface separated from flow by apertured partition
Y10T 137/7757	Through separate aperture
Y10T 137/7758	. .	Pilot or servo controlled
Y10T 137/7759	. . .	Responsive to change in rate of fluid flow
Y10T 137/776	Control by pressures across flow line valve
Y10T 137/7761	. . .	Electrically actuated valve
Y10T 137/7762	. . .	Fluid pressure type
Y10T 137/7764	Choked or throttled pressure type
Y10T 137/7765	Pilot valve within main valve head
Y10T 137/7766	Choked passage through main valve head
Y10T 137/7767	Loose fitting piston
Y10T 137/7768	Pilot controls supply to pressure chamber
Y10T 137/7769	Single acting fluid servo
Y10T 137/777	Spring biased

Y10T 137/7771	. .	Bi-directional flow valves
Y10T 137/7772	. . .	One head and seat carried by head of another
Y10T 137/7773	Supporting valve only spring biased
Y10T 137/7774	Supporting valve spring carried by supporting valve
Y10T 137/7775	Spring stop on supported valve stem
Y10T 137/7776	Spring abuts guide for supported valve stem
Y10T 137/7777	Both valves spring biased
Y10T 137/7778	. . .	Axes of ports perpendicular
Y10T 137/7779	. . .	Axes of ports parallel
Y10T 137/778	. . .	Axes of ports co-axial
Y10T 137/7781	. .	With separate connected fluid reactor surface
Y10T 137/7782	. . .	With manual or external control for line valve
Y10T 137/7783	. . .	Valve closes in responses to reverse flow
Y10T 137/7784	. . .	Responsive to change in rate of fluid flow
Y10T 137/7785	Valve closes in response to excessive flow
Y10T 137/7786	Turbine or swinging vane type reactor
Y10T 137/7787	Expansible chamber subject to differential pressures
Y10T 137/7788	Pressures across fixed choke
Y10T 137/7789	With Venturi tube having a connection to throat
Y10T 137/7791	Pressures across flow line valve
Y10T 137/7792	Movable deflector or choke
Y10T 137/7793	. . .	With opening bias [e.g., pressure regulator]
Y10T 137/7794	With relief valve
Y10T 137/7795	Multi-stage
Y10T 137/7796	Senses inlet pressure
Y10T 137/7797	Bias variable during operation
Y10T 137/7798	Ancillary reactor surface responds to inlet pressure
Y10T 137/7799	Liquid transfer
Y10T 137/78	Weight
Y10T 137/7801	Balanced valve
Y10T 137/7802	Liquid level responsive gas flow control
Y10T 137/7803	With protective separator
Y10T 137/7804	Main flow through isolated reactor chamber
Y10T 137/7805	Through external pipe
Y10T 137/7806	Modified valve casing
Y10T 137/7807	Adjustable external lever
Y10T 137/7808	Apertured reactor surface surrounds flow line
Y10T 137/7809	Reactor surface separated by apertured partition
Y10T 137/781	In valve stem
Y10T 137/7811	Also through reactor surface

Y10T 137/7812	Valve stem passes through the aperture
Y10T 137/7813	Plural reactor surfaces
Y10T 137/7814	Reactor is an inverted cup having liquid seal
Y10T 137/7815	With movement dampener
Y10T 137/7816	Valve head in inlet chamber
Y10T 137/7818	Valve head in inlet chamber
Y10T 137/7819	Rectilinear valve stem rigid with reactor surface
Y10T 137/782	Reactor surface is diaphragm
Y10T 137/7821	With valve closing bias
Y10T 137/7822	Reactor surface closes chamber
Y10T 137/7823	Valve head in inlet chamber
Y10T 137/7824	Reactor surface is inverted cup [float]
Y10T 137/7825	Rectilinear valve stem rigid with reactor surface
Y10T 137/7826	With valve closing bias
Y10T 137/7827	In reactor chamber
Y10T 137/7828	Valve head on yoke
Y10T 137/7829	Yoke has valve closing bias
Y10T 137/783	Reactor operatively connected to valve by mechanical movement
Y10T 137/7831	With mechanical movement between actuator and valve
Y10T 137/7832	Plural valves biased closed
Y10T 137/7833	With means for mounting or connecting to system
Y10T 137/7834	Valve seat or external sleeve moves to open valve
Y10T 137/7835	Valve seating in direction of flow
Y10T 137/7836	Flexible diaphragm or bellows reactor
Y10T 137/7837	Direct response valves [i.e., check valve type]
Y10T 137/7838	Plural
Y10T 137/7839	Dividing and recombining in a single flow path
Y10T 137/784	Integral resilient member forms plural valves
Y10T 137/7841	One valve carries head and seat for second valve
Y10T 137/7842	Diverse types
Y10T 137/7843	Integral resilient member forms plural valves
Y10T 137/7845	With common biasing means
Y10T 137/7846	Mechanically interconnected
Y10T 137/7847	With leak passage
Y10T 137/7848	Permits flow at valve interface
Y10T 137/7849	Bypass in valve casing
Y10T 137/785	With retarder or dashpot
Y10T 137/7851	End of valve forms dashpot chamber
Y10T 137/7852	End of valve moves inside dashpot chamber
Y10T 137/7853	Enlarged piston on end of valve stem

Y10T 137/7854	. . .	In couplings for coaxial conduits, e.g., drill pipe check valves
Y10T 137/7855	Valve seat threaded into a coupling element
Y10T 137/7856	Valve seat formed on or carried by a coupling element
Y10T 137/7857	Valve seat clamped between coupling elements
Y10T 137/7858	. . .	With means for selecting area of valve or seat
Y10T 137/7859	. . .	Single head, plural ports in parallel
Y10T 137/786	Concentric ports
Y10T 137/7861	Annular head
Y10T 137/7862	Central post on seat
Y10T 137/7863	Stop
Y10T 137/7864	With guide
Y10T 137/7865	Guide
Y10T 137/7866	. . .	Plural seating
Y10T 137/7867	Sequential
Y10T 137/7868	Resilient gasket
Y10T 137/7869	. . .	Biased open
Y10T 137/787	Oppositely swinging vanes
Y10T 137/7871	Weight biased
Y10T 137/7873	Ball valves
Y10T 137/7874	Edge pivoted valve
Y10T 137/7875	Pivoted valves
Y10T 137/7876	. . .	With external means for opposing bias
Y10T 137/7877	With means for retaining external means in bias opposing position
Y10T 137/7878	. . .	With bias adjustment indicator
Y10T 137/7879	. . .	Resilient material valve
Y10T 137/788	Having expansible port
Y10T 137/7881	Apertured plate
Y10T 137/7882	Having exit lip
Y10T 137/7883	With biasing means
Y10T 137/7884	Side vent
Y10T 137/7885	Multiple slit
Y10T 137/7886	Internally extending mount
Y10T 137/7887	Center flexing strip
Y10T 137/7888	With valve member flexing about securement
Y10T 137/7889	Sleeve
Y10T 137/789	Central mount
Y10T 137/7891	Flap or reed
Y10T 137/7892	With stop
Y10T 137/7893	With spring
Y10T 137/7894	With weight

Y10T 137/7895	Peripherally secured diaphragm
Y10T 137/7896	Annulus
Y10T 137/7897	Vacuum relief type
Y10T 137/7898	Pivoted valves
Y10T 137/79	Head retained by removable closure
Y10T 137/7901	Valve head movably connected for accommodation to seat
Y10T 137/7902	Valve mounted on end of pipe
Y10T 137/7903	Weight biased
Y10T 137/7904	Reciprocating valves
Y10T 137/7905	Plural biasing means
Y10T 137/7906	Cam means for adjusting and fixing bias
Y10T 137/7907	Varying effective lever arm
Y10T 137/7908	Weight biased
Y10T 137/7909	Valve body is the weight
Y10T 137/791	Ball valves
Y10T 137/7911	Removable cage
Y10T 137/7912	Separable seat
Y10T 137/7913	Guided head
Y10T 137/7914	Cage
Y10T 137/7915	Guide stem
Y10T 137/7916	With closing stop
Y10T 137/7917	Oppositely disposed
Y10T 137/7918	Head slidable on guide rod
Y10T 137/7919	Guide and seat integral unit
Y10T 137/792	Guide and closure integral unit
Y10T 137/7921	Weight coaxial with valve
Y10T 137/7922	Spring biased
Y10T 137/7923	With means to protect spring from fluid
Y10T 137/7924	Spring under tension
Y10T 137/7925	Piston-type valves
Y10T 137/7927	Ball valves
Y10T 137/7928	With follower
Y10T 137/7929	Spring coaxial with valve
Y10T 137/793	Broken valve parts retainer
Y10T 137/7931	Spring in inlet
Y10T 137/7932	Valve stem extends through fixed spring abutment
Y10T 137/7933	Yoke or cage-type support for valve stem
Y10T 137/7934	Spring abuts removable valve stem guide
Y10T 137/7935	Head slides on guide-rod concentric with spring
Y10T 137/7936	Spring guides valve head

Y10T 137/7937	Cage-type guide for stemless valves
Y10T 137/7938	Guide means integral and coplanar with valve disk
Y10T 137/7939	Head between spring and guide
Y10T 137/794	With means for separating solid material from the fluid
Y10T 137/7976	Plural separating elements
Y10T 137/8013	Sediment chamber
Y10T 137/8049	Movable strainer
Y10T 137/8085	Hollow strainer, fluid inlet and outlet perpendicular to each other
Y10T 137/8122	Planar strainer normal to flow path
Y10T 137/8158	With indicator, register, recorder, alarm or inspection means
Y10T 137/8175	Plural
Y10T 137/8192	Unobvious - "combination lock" type
Y10T 137/8208	Time
Y10T 137/8225	Position or extent of motion indicator
Y10T 137/8242	Electrical
Y10T 137/8259	Selection from plural branches
Y10T 137/8275	Indicator element rigidly carried by the movable element whose position is indicated
Y10T 137/8292	Movable indicator element is a pointer
Y10T 137/8309	Pointer integral with handle
Y10T 137/8326	Fluid pressure responsive indicator, recorder or alarm
Y10T 137/8342	Liquid level responsive indicator, recorder or alarm
Y10T 137/8359	Inspection means
Y10T 137/8376	Combined
Y10T 137/8593	Systems
Y10T 137/85938	Non-valved flow dividers
Y10T 137/85946	Faucet connected, sink drained
Y10T 137/85954	Closed circulating system
Y10T 137/85962	With thermal circulating means [thermo-siphons]
Y10T 137/8597	Main line as motive fluid for follower-type feeder
Y10T 137/85978	With pump
Y10T 137/85986	Pumped fluid control
Y10T 137/85994	Manual
Y10T 137/86002	Fluid pressure responsive
Y10T 137/8601	And pilot valve
Y10T 137/86019	Direct response valve
Y10T 137/86027	Electric
Y10T 137/86035	Combined with fluid receiver
Y10T 137/86043	Reserve or surge receiver
Y10T 137/86051	Compressed air supply unit

Y10T 137/86059	Hydraulic power unit
Y10T 137/86067	Fluid sump
Y10T 137/86075	. . .	And jet-aspiration type pump
Y10T 137/86083	. . .	Vacuum pump
Y10T 137/86091	. . .	Resiliently mounted pump
Y10T 137/86099	. . .	Hand pump
Y10T 137/86107	. . .	Multiple inlet with multiple outlet
Y10T 137/86115	. . .	Downstream cyclic distributor
Y10T 137/86123	Distributor part unitary with movable pump part
Y10T 137/86131	. . .	Plural
Y10T 137/86139	Serial
Y10T 137/86147	With single motive input
Y10T 137/86155	One pump driven by motive fluid from the other
Y10T 137/86163	Parallel
Y10T 137/86171	. . .	With pump bypass
Y10T 137/86179	. . .	Drain valve actuator mounted on pump
Y10T 137/86187	. .	Plural tanks or compartments connected for serial flow
Y10T 137/86196	. . .	Separable with valved-connecting passage
Y10T 137/86204	. . .	Fluid progresses by zigzag flow
Y10T 137/86212	. . .	Plural compartments formed by baffles
Y10T 137/8622	. . .	Plural top-to-bottom connected tanks
Y10T 137/86228	. . .	With communicating opening in common walls of tanks or compartments
Y10T 137/86236	. .	Tank with movable or adjustable outlet or overflow pipe
Y10T 137/86244	. . .	Horizontally traversing outlet
Y10T 137/86252	. . .	Float-supported outlet
Y10T 137/8626	. . .	Swinging outlet pipe or spout
Y10T 137/86268	. .	With running joint between movable parts of system
Y10T 137/86276	. .	Movable tank
Y10T 137/86284	. .	With antisplash means not in flow passage
Y10T 137/86292	. .	System with plural openings, one a gas vent or access opening
Y10T 137/863	. . .	Access and outlet
Y10T 137/86308	Tank access opening and bottom outlet
Y10T 137/86316	Access opening interlock or telltale on outlet valve actuator
Y10T 137/86324	. . .	Tank with gas vent and inlet or outlet
Y10T 137/86332	Vent and inlet or outlet in unitary mounting
Y10T 137/8634	. . .	With vented outlet
Y10T 137/86348	. .	Tank with internally extending flow guide, pipe or conduit
Y10T 137/86356	. . .	Nondraining overflow type
Y10T 137/86364	. . .	Inverted "U" passage
Y10T 137/86372	. . .	Inlet internally extending

Y10T 137/86381	. .	Head-establishing standpipe or expansion chamber [e.g., surge tanks]
Y10T 137/86389	. .	Programmer or timer
Y10T 137/86397	. . .	With independent valve controller
Y10T 137/86405	. . .	Repeating cycle
Y10T 137/86413	Self-cycling
Y10T 137/86421	Variable
Y10T 137/86429	Attachable and removable element
Y10T 137/86437	Adjustable cam
Y10T 137/86445	. . .	Plural, sequential, valve actuations
Y10T 137/86453	Plural trips or trip actuations
Y10T 137/86461	Variable cycle
Y10T 137/86469	. . .	Clock alarm mechanism controlled
Y10T 137/86477	. . .	Biased latch, cam operated
Y10T 137/86485	. .	Line condition change responsive release of valve
Y10T 137/86493	. .	Multi-way valve unit
Y10T 137/86501	. . .	Sequential distributor or collector type
Y10T 137/86509	. . .	Sequentially progressive opening or closing of plural ports
Y10T 137/86517	With subsequent closing of first port
Y10T 137/86525	Flow combining with flow dividing
Y10T 137/86533	Rotary
Y10T 137/86541	Plug
Y10T 137/86549	. . .	Selective reciprocation or rotation
Y10T 137/86558	. . .	Plural noncommunicating flow paths
Y10T 137/86566	Rotary plug
Y10T 137/86574	. . .	Supply and exhaust
Y10T 137/86582	Pilot-actuated
Y10T 137/8659	Variable orifice-type modulator
Y10T 137/86598	Opposed orifices; interposed modulator
Y10T 137/86606	Common to plural valve motor chambers
Y10T 137/86614	Electric
Y10T 137/86622	Motor-operated
Y10T 137/8663	Fluid motor
Y10T 137/86638	Rotary valve
Y10T 137/86646	Plug type
Y10T 137/86654	For plural lines
Y10T 137/86662	Axial and radial flow
Y10T 137/8667	Reciprocating valve
Y10T 137/86678	Combined disk or plug and gate or piston
Y10T 137/86686	Plural disk or plug
Y10T 137/86694	Piston valve

Y10T 137/86702	With internal flow passage
Y10T 137/8671	With annular passage [e.g., spool]
Y10T 137/86718	. . .	Dividing into parallel flow paths with recombining
Y10T 137/86726	Valve with bypass connections
Y10T 137/86734	With metering feature
Y10T 137/86743	Rotary
Y10T 137/86751	Plug
Y10T 137/86759	Reciprocating
Y10T 137/86767	Spool
Y10T 137/86775	With internal passage
Y10T 137/86783	Unequal heads
Y10T 137/86791	Piston
Y10T 137/86799	With internal flow passage
Y10T 137/86807	Sequential opening or closing of serial ports in single flow line
Y10T 137/86815	. . .	Multiple inlet with single outlet
Y10T 137/86823	Rotary valve
Y10T 137/86831	. . .	Selective opening of plural ports
Y10T 137/86839	. . .	Four port reversing valves
Y10T 137/86847	. . .	Pivoted valve unit
Y10T 137/86855	Gate
Y10T 137/86863	. . .	Rotary valve unit
Y10T 137/86871	Plug
Y10T 137/86879	. . .	Reciprocating valve unit
Y10T 137/86887	Combined disk or plug and gate or piston
Y10T 137/86895	Plural disk or plug
Y10T 137/86903	. .	Plural petcocks
Y10T 137/86911	. .	Sequential distributor or collector type
Y10T 137/86919	. .	Sequentially closing and opening alternately seating flow controllers
Y10T 137/86928	. .	Sequentially progressive opening or closing of plural valves
Y10T 137/86936	. . .	Pressure equalizing or auxiliary shunt flow
Y10T 137/86944	One valve seats against other valve [e.g., concentric valves]
Y10T 137/86952	Locomotive throttle
Y10T 137/8696	Gate
Y10T 137/86968	With balancing chamber
Y10T 137/86976	First valve moves second valve
Y10T 137/86984	Actuator moves both valves
Y10T 137/86992	. . .	With subsequent closing of first opened port
Y10T 137/87	Simultaneously moved port controllers
Y10T 137/87008	. . .	Screw-actuated differential valves
Y10T 137/87016	. . .	Lost motion

Y10T 137/87024	Cam determines sequence
Y10T 137/87032	Rotary concentric valves
Y10T 137/8704	First valve actuates second valve
Y10T 137/87048	. .	With preselecting means for plural valve actuator
Y10T 137/87056	. .	With selective motion for plural valve actuator
Y10T 137/87064	. . .	Oppositely movable cam surfaces
Y10T 137/87072	. . .	Rotation about either of two pivotal axes
Y10T 137/8708	. . .	Rotation of actuator arm about its pivot and its axis
Y10T 137/87088	. . .	Reciprocation along and rotation about same axis
Y10T 137/87096	. .	Valves with separate, correlated, actuators
Y10T 137/87105	. . .	Correlated across separable flow path joint
Y10T 137/87113	. . .	Interlocked
Y10T 137/87121	. . .	Coaxial stems
Y10T 137/87129	Rotary
Y10T 137/87137	And reciprocating
Y10T 137/87145	Concentric, central valve removable
Y10T 137/87153	. .	Plural noncommunicating flow paths
Y10T 137/87161	. . .	With common valve operator
Y10T 137/87169	. .	Supply and exhaust
Y10T 137/87177	. . .	With bypass
Y10T 137/87185	Controlled by supply or exhaust valve
Y10T 137/87193	. . .	Pilot-actuated
Y10T 137/87201	Common to plural valve motor chambers
Y10T 137/87209	Electric
Y10T 137/87217	. . .	Motor
Y10T 137/87225	Fluid motor
Y10T 137/87233	. . .	Biased exhaust valve
Y10T 137/87241	Biased closed
Y10T 137/87249	. .	Multiple inlet with multiple outlet
Y10T 137/87257	. .	Hydraulic brake line [e.g., hill holders]
Y10T 137/87265	. .	Dividing into parallel flow paths with recombining
Y10T 137/87273	. . .	With fluid coupling [e.g., railway car hose coupling, truck-trailer oil system coupling, etc.]
Y10T 137/87281	. . .	System having plural inlets
Y10T 137/8729	Having digital flow controller
Y10T 137/87298	. . .	Having digital flow controller
Y10T 137/87306	Having plural branches under common control for separate valve actuators
Y10T 137/87314	Electromagnetic or electric control [e.g., digital control, bistable electro control, etc.]
Y10T 137/87322	. . .	With multi way valve having serial valve in at least one branch

Y10T 137/8733	. . .	Fluid pressure regulator in at least one branch
Y10T 137/87338	. . .	Flow passage with bypass
Y10T 137/87346	Including mixing feature
Y10T 137/87354	Including flowmeter
Y10T 137/87362	Including cleaning, treating, or heat transfer feature
Y10T 137/8737	Water treatment feature
Y10T 137/87378	. . .	Second valve assembly carried by first valve head
Y10T 137/87386	With rotary plug having variable restrictor
Y10T 137/87394	Carried valve is direct response valve [e.g., check valve, etc.]
Y10T 137/87402	. . .	With foam controlling means [e.g., beer, soda faucets]
Y10T 137/8741	. . .	With common operator
Y10T 137/87418	Balanced valve
Y10T 137/87426	Single resilient member actuates or forms plural passages
Y10T 137/87434	Valves deform to close passage
Y10T 137/87442	Rotary valve
Y10T 137/8745	Including rigid plate with flexible or resilient seal
Y10T 137/87458	Axes of rotation of valves intersect at point
Y10T 137/87467	Axes of rotation parallel
Y10T 137/87475	Adjacent plate valves always parallel
Y10T 137/87483	Adjacent plate valves counter rotate
Y10T 137/87491	Mechanical movement between actuator and non-rotary valve
Y10T 137/87499	. . .	Fluid actuated or retarded
Y10T 137/87507	. . .	Electrical actuator
Y10T 137/87515	. . .	Mechanical movement between actuator and valve
Y10T 137/87523	. . .	Rotary valve
Y10T 137/87531	Butterfly valve
Y10T 137/87539	. . .	Having guide or restrictor
Y10T 137/87547	Manually variable
Y10T 137/87555	. . .	Having direct response valve [e.g., check valve, etc.]
Y10T 137/87563	With reverse flow direction
Y10T 137/87571	. .	Multiple inlet with single outlet
Y10T 137/87579	. . .	Faucet attachment
Y10T 137/87587	. . .	Combining by aspiration
Y10T 137/87595	Combining of three or more diverse fluids
Y10T 137/87603	Plural motivating fluid jets
Y10T 137/87611	Flow control by varying position of a fluid inlet relative to entrainment chamber
Y10T 137/87619	With selectively operated flow control means in inlet
Y10T 137/87627	Flow control means is located in aspirated fluid inlet

Y10T 137/87635	Single actuator operates flow control means located in both motivating fluid and aspirated fluid inlets
Y10T 137/87643	With condition responsive valve
Y10T 137/87652	. . .	With means to promote mixing or combining of plural fluids
Y10T 137/8766	With selectively operated flow control means
Y10T 137/87668	Single actuator operates plural flow control means
Y10T 137/87676	. . .	With flow control
Y10T 137/87684	Valve in each inlet
Y10T 137/87692	With common valve operator
Y10T 137/877	. .	With flow control means for branched passages
Y10T 137/87708	. . .	With common valve operator
Y10T 137/87716	For valve having a flexible diaphragm valving member
Y10T 137/87724	For valve having a ball head
Y10T 137/87732	With gearing
Y10T 137/8774	Threaded actuator
Y10T 137/87748	Pivoted or rotary motion converted to reciprocating valve head motion
Y10T 137/87756	Spring biased
Y10T 137/87764	Having fluid actuator
Y10T 137/87772	With electrical actuation
Y10T 137/8778	Spring biased
Y10T 137/87788	. . .	With valve or movable deflector at junction
Y10T 137/87796	Movable deflector spout in lateral port
Y10T 137/87804	Valve or deflector is tubular passageway
Y10T 137/87812	Pivoted valve or deflector
Y10T 137/8782	Rotary valve or deflector
Y10T 137/87829	. . .	Biased valve
Y10T 137/87837	Spring bias
Y10T 137/87845	For valve having a ball head
Y10T 137/87853	With threaded actuator
Y10T 137/87861	Spring coaxial with valve
Y10T 137/87869	Biased open
Y10T 137/87877	. . .	Single inlet with multiple distinctly valved outlets
Y10T 137/87885	. . .	Sectional block structure
Y10T 137/87893	. . .	With fluid actuator
Y10T 137/87901	. . .	With threaded actuator
Y10T 137/87909	. . .	Containing rotary valve
Y10T 137/87917	. .	Flow path with serial valves and/or closures
Y10T 137/87925	. . .	Separable flow path section, valve or closure in each
Y10T 137/87933	Common joint and valve seat faces, or sections joined by closing members
Y10T 137/87941	Each valve and/or closure operated by coupling motion

Y10T 137/87949	Linear motion of flow path sections operates both
Y10T 137/87957	Valves actuate each other
Y10T 137/87965	Valve- or closure-operated by coupling motion
Y10T 137/87973	Coupling interlocked with valve, or closure or actuator
Y10T 137/87981	Common actuator
Y10T 137/87989	Delivery cock with terminal valve
Y10T 137/87997	Alternately seating
Y10T 137/88005	Biased valve
Y10T 137/88014	Opposed screw
Y10T 137/88022	One valve head provides seat for other head
Y10T 137/8803	Also carries head of other valve
Y10T 137/88038	One valve head carries other valve head
Y10T 137/88046	Biased valve with external operator
Y10T 137/88054	Direct response normally closed valve limits direction of flow
Y10T 137/88062	Coaxial oppositely directed seats
Y10T 137/8807	Articulated or swinging flow conduit
Y10T 137/88078	Actuates valve
Y10T 137/88086	Plural motions of valve
Y10T 137/88094	Reciprocating valve
Y10T 137/88102	Rotary valve
Y10T 137/8811	Frangible
Y10T 137/9029	With coupling
Y10T 137/9138	Flexible
Y10T 137/9247	With closure
Y10T 137/9464	Faucets and spouts
Y10T 137/9682	Miscellaneous

Former US Class 152 Series

Y10T 152/00	Resilient tires and wheels
Y10T 152/10	. Tires, resilient
Y10T 152/10009	. . Emergency
Y10T 152/10018	. . with splash guards
Y10T 152/10027	. . with wear indicating feature
Y10T 152/10036	. . Cushion and pneumatic combined
Y10T 152/10045	. . . Metallic spring cushion
Y10T 152/10054	. . . Enclosed cushion
Y10T 152/10063	. . . Superimposed
Y10T 152/10072 Plungers
Y10T 152/10081 Edge-secured cushion

Y10T 152/1009	Guide flanges
Y10T 152/10099	Radial stops
Y10T 152/10108	Bolts or studs
Y10T 152/10117	. . .	Integral
Y10T 152/10126	with removable inner tube
Y10T 152/10135	. .	Armored
Y10T 152/10144	. . .	Single tube tires internal
Y10T 152/10153	Metal
Y10T 152/10162	Plates
Y10T 152/10171	. . .	Casing construction
Y10T 152/1018	Embedded
Y10T 152/10189	Metal
Y10T 152/10198	Plates
Y10T 152/10207	Annular
Y10T 152/10216	Linked mat
Y10T 152/10225	Woven
Y10T 152/10234	. . .	Interliners
Y10T 152/10243	Cotton, fabric, or rubber
Y10T 152/10252	Metal
Y10T 152/10261	Scale armor
Y10T 152/1027	Annular
Y10T 152/10279	. .	Cushion
Y10T 152/10288	. . .	Sectional
Y10T 152/10297	Annular
Y10T 152/10306	Superimposed
Y10T 152/10315	Superimposed
Y10T 152/10324	with apertured external binders
Y10T 152/10333	Radial bolt secured
Y10T 152/10342	Abutting sections
Y10T 152/10351	with annular internal binders
Y10T 152/1036	Interfitting
Y10T 152/10369	Indented at joints
Y10T 152/10378	. . .	Casing enclosed core
Y10T 152/10387	Separate core
Y10T 152/10396	Removable
Y10T 152/10405	Sponge rubber
Y10T 152/10414	with core compression
Y10T 152/10423	Superimposed rings
Y10T 152/10432	Sectional transversely
Y10T 152/10441	Balls

Y10T 152/1045	Integral structure
Y10T 152/10459	Recessed
Y10T 152/10468	Chambered
Y10T 152/10477	Perforated
Y10T 152/10486	Chambered
Y10T 152/10495	. .	Pneumatic tire or inner tube
Y10T 152/10504	. . .	Asymmetric tire
Y10T 152/10513	. . .	Tire reinforcement material characterized by short length fibers or the like
Y10T 152/10522	. . .	Multiple chamber
Y10T 152/10531	Cylinder and piston
Y10T 152/1054	Mutually free walls
Y10T 152/10549	Interfitting
Y10T 152/10558	Balls
Y10T 152/10567	with simultaneous inflating means
Y10T 152/10576	Annular chambers
Y10T 152/10585	with simultaneous inflating means
Y10T 152/10594	Mutually free walls
Y10T 152/10603	with simultaneous inflating means
Y10T 152/10612	with simultaneous inflating means
Y10T 152/10621	. . .	Sectional casings
Y10T 152/1063	Circumferential
Y10T 152/10639	Rigid inner sections
Y10T 152/10648	. . .	with means restricting relative movement between tire and inner tube [e.g., anti-creep feature, etc.]
Y10T 152/10657	. . .	with means to protect inner tube from rim
Y10T 152/10666	. . .	Automatic sealing of punctures [e.g., self-healing, etc.]
Y10T 152/10675	Using flowable coating or composition
Y10T 152/10684	On inner surface of tubeless tire
Y10T 152/10693	Sealant in plural layers or plural pockets
Y10T 152/10702	within or part of construction of inflating inner tube
Y10T 152/10711	Sealant in plural layers or plural pockets
Y10T 152/1072	by compression
Y10T 152/10729	with reinflating means
Y10T 152/10738	. . .	with means to protect tire from rim
Y10T 152/10747	. . .	Means other than rim closing the tire opening
Y10T 152/10756	Positive casing closure
Y10T 152/10765	. . .	Characterized by belt or breaker structure
Y10T 152/10774	Consisting of only one ply
Y10T 152/10783	Reinforcing plies made up from wound narrow ribbons

Y10T 152/10792	Structure where each bias angle reinforcing cord ply has no opposingly angled ply
Y10T 152/10801	Structure made up of two or more sets of plies wherein the reinforcing cords in one set lie in a different angular position relative to those in other sets
Y10T 152/1081	Breaker or belt characterized by the chemical composition or physical properties of elastomer or the like
Y10T 152/10819	Characterized by the structure of the bead portion of the tire
Y10T 152/10828	Chafer or sealing strips
Y10T 152/10837	Bead characterized by the radial extent of apex, flipper or chafer into tire sidewall
Y10T 152/10846	Bead characterized by the chemical composition and or physical properties of elastomers or the like
Y10T 152/10855	Characterized by the carcass, carcass material, or physical arrangement of the carcass materials
Y10T 152/10864	Sidewall stiffening or reinforcing means other than main carcass plies or foldups thereof about beads
Y10T 152/10873	with two or more differing cord materials
Y10T 152/10882	Patches
Y10T 152/10891	Mechanically secured
Y10T 152/109	Inside and outside, bolt connected
Y10T 152/10909	with plugs
Y10T 152/10918	Bandages
Y10T 152/10927	Mechanically secured
Y10T 152/10936	to felly or rim

Former US Class 156 Series

Y10T 156/00	Adhesive bonding and miscellaneous chemical manufacture	
Y10T 156/10	Methods of surface bonding and/or assembly therefor
Y10T 156/1002	with permanent bending or reshaping or surface deformation of self sustaining lamina
Y10T 156/1003	by separating laminae between spaced secured areas [e.g., honeycomb expanding]
Y10T 156/1005	by inward collapsing of portion of hollow body
Y10T 156/1007	Running or continuous length work
Y10T 156/1008	Longitudinal bending
Y10T 156/101	Prior to or during assembly with additional lamina
Y10T 156/1011	Overedge bending or overedge folding
Y10T 156/1013	and edge-joining of one piece blank to form tube
Y10T 156/1015	Folding
Y10T 156/1016	Transverse corrugating
Y10T 156/1018	Subsequent to assembly of laminae
Y10T 156/102	with deformation or cutting of corrugated lamina

Y10T 156/1021	Treating material of corrugated lamina or dry adhesive thereon to render tacky
Y10T 156/1023	Surface deformation only [e.g., embossing]
Y10T 156/1025	to form undulated to corrugated sheet and securing to base with parts of shaped areas out of contact
Y10T 156/1026	with slitting or removal of material at reshaping area prior to reshaping
Y10T 156/1028	by bending, drawing or stretch forming sheet to assume shape of configured lamina while in contact therewith
Y10T 156/103	Encasing or enveloping the configured lamina
Y10T 156/1031	with preshaping of lamina
Y10T 156/1033	Flexible sheet to cylinder lamina
Y10T 156/1034	Overedge bending of lamina about edges of sheetlike base
Y10T 156/1036	Bending of one piece blank and joining edges to form article
Y10T 156/1038	Hollow cylinder article
Y10T 156/1039	Surface deformation only of sandwich or lamina [e.g., embossed panels]
Y10T 156/1041	Subsequent to lamination
Y10T 156/1043	Subsequent to assembly
Y10T 156/1044	of parallel stacked sheets only
Y10T 156/1046	Bending of one lamina only
Y10T 156/1048	to form dished or receptacle-like product
Y10T 156/1049	Folding only
Y10T 156/1051	by folding
Y10T 156/1052	with cutting, punching, tearing or severing
Y10T 156/1054	and simultaneously bonding [e.g., cut-seaming]
Y10T 156/1056	Perforating lamina
Y10T 156/1057	Subsequent to assembly of laminae
Y10T 156/1059	Splitting sheet lamina in plane intermediate of faces
Y10T 156/1061	Spiral peeling
Y10T 156/1062	Prior to assembly
Y10T 156/1064	Partial cutting [e.g., grooving or incising]
Y10T 156/1066	Cutting to shape joining edge surfaces only
Y10T 156/1067	Continuous longitudinal slitting
Y10T 156/1069	Bonding face to face of laminae cut from single sheet
Y10T 156/107	Punching and bonding pressure application by punch
Y10T 156/1072	Closure cap liner applying type
Y10T 156/1074	Separate cutting of separate sheets or webs
Y10T 156/1075	of plural laminae from single stock and assembling to each other or to additional lamina
Y10T 156/1077	Applying plural cut laminae to single face of additional lamina
Y10T 156/1079	Joining of cut laminae end-to-end
Y10T 156/108	Flash, trim or excess removal

Y10T 156/1082	. . . Partial cutting bonded sandwich [e.g., grooving or incising]
Y10T 156/1084	. . . of continuous or running length bonded web
Y10T 156/1085 One web only
Y10T 156/1087 Continuous longitudinal slitting
Y10T 156/1089	. . of discrete laminae to single face of additional lamina
Y10T 156/109	. . . Embedding of laminae within face of additional laminae
Y10T 156/1092	. . . All laminae planar and face to face
Y10T 156/1093 with covering of discrete laminae with additional lamina
Y10T 156/1095 Opposed laminae are running length webs
Y10T 156/1097 Lamina is running length web
Y10T 156/1098 Feeding of discrete laminae from separate sources
Y10T 156/11	. Methods of delaminating, per se; i.e. , separating at bonding face
Y10T 156/1105	. . Delaminating process responsive to feed or shape at delamination
Y10T 156/1111	. . Using solvent during delaminating [e.g., water dissolving adhesive at bonding face during delamination, etc.]
Y10T 156/1116	. . . Using specified organic delamination solvent
Y10T 156/1121	. . Using vibration during delaminating
Y10T 156/1126	. . Using direct fluid current against work during delaminating
Y10T 156/1132	. . . Using vacuum directly against work during delaminating
Y10T 156/1137	. . . Using air blast directly against work during delaminating
Y10T 156/1142	. . Changing dimension during delaminating [e.g., crushing, expanding, warping, etc.]
Y10T 156/1147	. . . Using shrinking or swelling agent during delaminating
Y10T 156/1153	. . Temperature change for delamination [e.g., heating during delaminating, etc.]
Y10T 156/1158	. . . Electromagnetic radiation applied to work for delamination [e.g., microwave, uv, ir, etc.]
Y10T 156/1163	. . . Sintering for delamination
Y10T 156/1168	. . Gripping and pulling work apart during delaminating
Y10T 156/1174	. . . Using roller for delamination [e.g., roller pairs operating at differing speeds or directions, etc.]
Y10T 156/1179	. . . with poking during delaminating [e.g., jabbing, etc.]
Y10T 156/1184 Piercing layer during delaminating [e.g., cutting, etc.]
Y10T 156/1189	. . . with shearing during delaminating
Y10T 156/1195	. . . Delaminating from release surface
Y10T 156/12	. Surface bonding means and/or assembly means with cutting, punching, piercing, severing or tearing
Y10T 156/125	. . Plural severing means each acting on a different work piece
Y10T 156/13	. . Severing followed by associating with part from same source
Y10T 156/1304	. . Means making hole or aperture in part to be laminated
Y10T 156/1309	. . . and securing separate part over hole or aperture
Y10T 156/1313	. . Cutting element simultaneously bonds [e.g., cut seaming]
Y10T 156/1317	. . Means feeding plural workpieces to be joined

Y10T 156/1322	. . . Severing before bonding or assembling of parts
Y10T 156/1326 Severing means or member secured thereto also bonds
Y10T 156/133 Delivering cut part to indefinite or running length web
Y10T 156/1335 Cutter also delivers cut piece
Y10T 156/1339 Delivering cut part in sequence to serially conveyed articles
Y10T 156/1343	. . . Cutting indefinite length web after assembly with discrete article
Y10T 156/1348	. . Work traversing type
Y10T 156/1352	. . . with liquid applying means
Y10T 156/1357 Slitting and severing
Y10T 156/1361 Cutting after bonding
Y10T 156/1365	. . . Fixed cutter
Y10T 156/137	. . Stamp from multiple row sheet type
Y10T 156/1374	. . with means projecting fluid against work
Y10T 156/1378	. . Cutter actuated by or secured to bonding element
Y10T 156/1383	. . . with liquid applicator
Y10T 156/1387 Common actuator for bonding and liquid applying means
Y10T 156/1391 Liquid applied to web before cutting
Y10T 156/1396 Roller applicator
Y10T 156/14	. Surface bonding means and/or assembly means with shaping, scarifying, or cleaning joining surface only
Y10T 156/15	. Combined or convertible surface bonding means and/or assembly means
Y10T 156/16	. Surface bonding means and/or assembly means with bond interfering means [slip sheet, etc.]
Y10T 156/17	. Surface bonding means and/or assembly means with work feeding or handling means
Y10T 156/1702	. . For plural parts or plural areas of single part
Y10T 156/1705	. . . Lamina transferred to base from adhered flexible web or sheet type carrier
Y10T 156/1707 Discrete spaced laminae on adhered carrier
Y10T 156/171 Means serially presenting discrete base articles or separate portions of a single article
Y10T 156/1712	. . . Indefinite or running length work
Y10T 156/1715 Means joining indefinite length work edge to edge
Y10T 156/1717 Means applying adhesively secured tape to seam
Y10T 156/172 Means applying fluid adhesive to work edge
Y10T 156/1722 Means applying fluent adhesive or adhesive activator material between layers
Y10T 156/1724 At spaced areas
Y10T 156/1727 Plural indefinite length or running length workpieces
Y10T 156/1729 Fluid applied to nip between indefinite length webs
Y10T 156/1732 Fluid applied to plural workpieces
Y10T 156/1734 Means bringing articles into association with web
Y10T 156/1737 Discontinuous, spaced area, and/or patterned pressing

Y10T 156/1739 Webs of different width, longitudinally aligned
Y10T 156/1741 Progressive continuous bonding press [e.g., roll couples]
Y10T 156/1744	. . . Means bringing discrete articles into assembled relationship
Y10T 156/1746 Plural lines and/or separate means assembling separate sandwiches
Y10T 156/1749 All articles from single source only
Y10T 156/1751 At least three articles
Y10T 156/1754 At least two applied side by side to common base
Y10T 156/1756 Plural ranks
Y10T 156/1759 Sheet form common base
Y10T 156/1761 Stacked serially
Y10T 156/1763 Magazine stack directly contacting separate work
Y10T 156/1766 Magazine movable to work
Y10T 156/1768 Means simultaneously conveying plural articles from a single source and serially presenting them to an assembly station
Y10T 156/1771 Turret or rotary drum-type conveyer
Y10T 156/1773 For flexible sheets
Y10T 156/1776 Means separating articles from bulk source
Y10T 156/1778 Stacked sheet source
Y10T 156/178 Rotary or pivoted picker
Y10T 156/1783 Translating picker
Y10T 156/1785	. . Magazine stack directly contacting work
Y10T 156/1788	. . Work traversing type and/or means applying work to wall or static structure
Y10T 156/179	. . . with liquid applying means
Y10T 156/1793	. . . Grip or clamp for web end
Y10T 156/1795	. . . Implement carried web supply
Y10T 156/1798	. . with liquid adhesive or adhesive activator applying means
Y10T 156/18	. Surface bonding means and/or assembly means with handle or handgrip
Y10T 156/19	. Delaminating means
Y10T 156/1906	. . Delaminating means responsive to feed or shape at delamination
Y10T 156/1911	. . Heating or cooling delaminating means [e.g., melting means, freezing means, etc.]
Y10T 156/1917	. . . Electromagnetic radiation delaminating means [e.g., microwave, uv, ir, etc.]
Y10T 156/1922	. . Vibrating delaminating means
Y10T 156/1928	. . Differential fluid pressure delaminating means
Y10T 156/1933	. . . Spraying delaminating means [e.g., atomizer, etc.]
Y10T 156/1939 Air blasting delaminating means]
Y10T 156/1944	. . . Vacuum delaminating means [e.g., vacuum chamber, etc.]
Y10T 156/195	. . Delaminating roller means
Y10T 156/1956	. . . Roller pair delaminating means
Y10T 156/1961	. . Severing delaminating means [e.g., chisel, etc.]
Y10T 156/1967	. . . Cutting delaminating means

Y10T 156/1972 Shearing delaminating means
Y10T 156/1978	. . Delaminating bending means
Y10T 156/1983	. . . Poking delaminating means
Y10T 156/1989	. . . Corner edge bending delaminating means
Y10T 156/1994	. . Means for delaminating from release surface

Former US Class 225 series

Y10T 225/00	Severing by tearing or breaking
Y10T 225/10	. Methods
Y10T 225/12	. . With preliminary weakening
Y10T 225/14	. . Longitudinally of direction of feed
Y10T 225/16	. . Transversely of continuously fed work
Y10T 225/18	. . . Progressively to or from one side edge
Y10T 225/20	. Severing by manually forcing against fixed edge
Y10T 225/201	. . With other type severing means
Y10T 225/202	. . With timer-released means for preventing work feed-out
Y10T 225/203	. . Including means to effect bias cut
Y10T 225/205	. . With feed-out of predetermined length from work supply
Y10T 225/206	. . . Including means to select or adjust feed-out length
Y10T 225/207	. . . Including feed-out stop for manually pulled work
Y10T 225/208 Stop abuts work edge or work-mounted article
Y10T 225/209 With feed-out of lead-end to aid initial grasping
Y10T 225/21	. . . Merely to provide lead-end for manual grasping
Y10T 225/211	. . . Manually operated feed-out mechanism
Y10T 225/213	. . With indicator
Y10T 225/214	. . . Indicates length to be severed from supply
Y10T 225/215	. . With blade-edge guard
Y10T 225/216	. . . Movable
Y10T 225/217	. . Work stripped from blade by relatively movable means
Y10T 225/218	. . . Including movable blade
Y10T 225/22	. . With means to move work toward or into severing position
Y10T 225/221	. . . With means to strip adhering work therefrom
Y10T 225/222	. . With work-immobilizing pasteur surface
Y10T 225/223	. . . With finger-access opening
Y10T 225/224	. . With means to hold pad or stack of individual sheets
Y10T 225/225	. . . With means to separate severed end of stub from supply package
Y10T 225/226	. . . With changeable blade-edge contour
Y10T 225/228 Slidable notcher
Y10T 225/229	. . . Blade slidable along plane of work surface

Y10T 225/23	. . .	Zigzag-folded supply package
Y10T 225/231	. . .	Separate blades usable alternatively or sequentially on same work supply
Y10T 225/232	. . .	Plural supply sources
Y10T 225/233	On turret-type support with single blade
Y10T 225/234	With movable blade registrable selectively with each source
Y10T 225/236	With plural blades
Y10T 225/237	With individual blade for each source
Y10T 225/238	. . .	With housing for work supply
Y10T 225/239	Liquid-, gas-, or light-tight work passage
Y10T 225/24	With inspection window or transparent panel
Y10T 225/241	With mounting means for housing
Y10T 225/243	Blade on pivoted closure for housing
Y10T 225/244	Sectional telescoping housing
Y10T 225/245	Including removable cap or sleeve enclosure for spooled work supply
Y10T 225/246	Including special support for wound supply package
Y10T 225/247	Bearing or trunnions to engage package core
Y10T 225/248	Single blank container
Y10T 225/249	Blade unitary with container
Y10T 225/251	With closure fastener
Y10T 225/252	With brake or tensioner
Y10T 225/253	Restricted or restrictable work outlet
Y10T 225/254	With finger-access opening to facilitate work feed-out
Y10T 225/255	With internal guide
Y10T 225/256	. . .	Blade carrier bodily and slidably supported on running length work
Y10T 225/257	. . .	Blade mounted on hand-held wound package
Y10T 225/259	With lead-end stripper for tacky adhesive work
Y10T 225/26	By resiliently embracing outer circumference of package
Y10T 225/261	Work supply nonrotatably wound on flanged spool
Y10T 225/262	Circumferentially movable blade radially retained by beaded or grooved flanges
Y10T 225/263	Blade carrier supports hollow spool for rotation
Y10T 225/264	Flange edge notched to provide or coact with cutter
Y10T 225/266	With clamp for lead-end of strand-type work
Y10T 225/267	Strand clamped against flange
Y10T 225/268	By resiliently engaging package ends or interior of core
Y10T 225/269	Blade carrier supports package for rotation
Y10T 225/27	. . .	Movable blade continually biased toward wound web supply package
Y10T 225/271	Including temporary bias-disabling means
Y10T 225/272	Including stripper to separate lead-end from package
Y10T 225/274	Weight of bodily movable package contributes to blade-biasing force

Y10T 225/275	. . . Blade slidably guided
Y10T 225/276	. . Blade movable to severing position by moving work
Y10T 225/277	. . . With simultaneous application of brake or clamp
Y10T 225/278 Applied to running length work
Y10T 225/279 Opposed movable jaws
Y10T 225/28	. . Wound package bodily biased toward fixed blade
Y10T 225/282	. . With fixed blade and support for wound package
Y10T 225/283	. . . Body- or belt-attached
Y10T 225/284	. . . With brake applied to supply package
Y10T 225/285	. . . With guide spaced from blade edge to provide lead-end therebetween
Y10T 225/286	. . With work-abutment stop
Y10T 225/287	. . With brake or clamp
Y10T 225/289	. . . Thread cutter and clamp attachment for sewing machine presser foot
Y10T 225/29	. . . Applied to running length work
Y10T 225/291 Spaced from blade edge to provide lead-end therebetween
Y10T 225/292 Blade manually movable to expose lead-end
Y10T 225/293	. . . Manually applied, spring returned
Y10T 225/294	. . With guide for running length work
Y10T 225/295	. . Blade manually movable to or from severing position
Y10T 225/297	. . With means to facilitate lead-end grasping
Y10T 225/298	. . Blades or severing devices
Y10T 225/299	. . . Adjustable blade-edge contour
Y10T 225/30	. Breaking or tearing apparatus
Y10T 225/304	. . Including means to apply thermal shock to work
Y10T 225/307	. . Combined with preliminary weakener or with nonbreaking cutter
Y10T 225/314	. . . Successively actuated sharp and dull tools
Y10T 225/321	. . . Preliminary weakener
Y10T 225/325 With means to apply moment of force to weakened work
Y10T 225/329	. . Plural breakers
Y10T 225/336	. . Conveyer diverter for moving work
Y10T 225/343	. . . Plural divergent work paths
Y10T 225/35	. . Work-parting pullers [burststers]
Y10T 225/357	. . . Relatively movable clamps
Y10T 225/364	. . Axial twisters
Y10T 225/371	. . Movable breaking tool
Y10T 225/379	. . . Breaking tool intermediate spaced work supports
Y10T 225/386 Clamping supports
Y10T 225/393	. . Web restrainer

Former US Class 279 Series**Y10T 279/00****Chucks or sockets**

- Y10T 279/10 . Expanding
- Y10T 279/1004 . . Collet type
- Y10T 279/1008 . . . Fixed jaws and moving cam
- Y10T 279/1012 . . . Fixed cam and moving jaws
- Y10T 279/1016 . . Jaws mounted on flexible member; i.e., diaphragm
- Y10T 279/1021 . . Fluid-pressure actuator
- Y10T 279/1024 . . . Directly expanding jaws
- Y10T 279/1029 Jaw is expansible chamber; i.e., bladder type
- Y10T 279/1033 . . . Expanding jaws via mechanical connection
- Y10T 279/1037 . . Axially moving actuator
- Y10T 279/1041 . . . Wedge
- Y10T 279/1045 Internal cone
- Y10T 279/1049 with jaw positively interlocked with wedge; e.g., dovetail or T-slot
- Y10T 279/1054 with resilient means contacting nonresilient jaw
- Y10T 279/1058 Constricting band, annulus, or clip
- Y10T 279/1062 . . . Toggle
- Y10T 279/1066 . . . Axially compressible element expands radially
- Y10T 279/1071 . . . Lever
- Y10T 279/1074 . . Rotary actuator
- Y10T 279/1079 . . . Clutch or self-actuating type
- Y10T 279/1083 . . Jaw structure
- Y10T 279/1087 . . . Resilient
- Y10T 279/1091 . . . Ball or roller
- Y10T 279/1095 . . . Pivoted
- Y10T 279/11 . Vacuum
- Y10T 279/12 . with fluid-pressure actuator
- Y10T 279/1208 . . with measuring, indicating or control means
- Y10T 279/1216 . . Jaw is expansible chamber; i.e., bladder type
- Y10T 279/1224 . . Pneumatic type
- Y10T 279/1233 . . Jaws mounted on flexible member; i.e., diaphragm
- Y10T 279/1241 . . Socket type
- Y10T 279/1249 . . . Collet
- Y10T 279/1258 Fixed cam and moving jaws
- Y10T 279/1266 Moving cam and fixed jaws
- Y10T 279/1274 . . Radially reciprocating jaws
- Y10T 279/1283 . . . Fluid pressure directly moves jaws

Y10T 279/1291	. . . Fluid pressure moves jaws via mechanical connection
Y10T 279/13	. Angularly adjustable or indexing
Y10T 279/14	. Eccentric
Y10T 279/15	. Threaded grip
Y10T 279/16	. Longitudinal screw clamp
Y10T 279/17	. Socket type
Y10T 279/17008	. . Multiple alternative
Y10T 279/17017	. . Self-centering of floating
Y10T 279/17025	. . . Radially reciprocating jaws
Y10T 279/17034	. . . Transverse holder and setscrew
Y10T 279/17042	. . Lost motion
Y10T 279/17051	. . . Swinging external yoke or detent
Y10T 279/17059 Rotary socket
Y10T 279/17068	. . . Rotary socket
Y10T 279/17076	. . . Spreading elements
Y10T 279/17085	. . . Key retainer
Y10T 279/17094	. . . Sleeve type retainer
Y10T 279/17102 Sleeve in socket
Y10T 279/17111	. . Fluid-conduit drill holding
Y10T 279/17119	. . Feed type
Y10T 279/17128	. . Self-grasping
Y10T 279/17136	. . . Yielding grasping jaws
Y10T 279/17145 Ball or roller
Y10T 279/17153 Spring jaws
Y10T 279/17162	. . . Yielding detent
Y10T 279/17171	. . . One-way-clutch type
Y10T 279/17179 Wedge
Y10T 279/17188 Side detent
Y10T 279/17196 Ball or roller
Y10T 279/17205	. . Conical clamp threaded in socket
Y10T 279/17213	. . Transversely oscillating jaws
Y10T 279/17222	. . . Screw actuated
Y10T 279/17231	. . Pivoted jaws
Y10T 279/17239	. . . Moving-cam actuator
Y10T 279/17247 Threaded cam sleeve
Y10T 279/17256 Reciprocating cam sleeve
Y10T 279/17264	. . . Fixed cam and moving jaws
Y10T 279/17273 Axial screw actuator
Y10T 279/17282 Threaded-sleeve actuator
Y10T 279/17291	. . Resilient split socket

Y10T 279/17299	. . .	Threaded cam sleeve
Y10T 279/17307	. . .	Reciprocating cam sleeve
Y10T 279/17316	. . .	Unitary
Y10T 279/17324	Split at one end only
Y10T 279/17333	Transverse screw actuator
Y10T 279/17341	Cam actuator
Y10T 279/17351	Split end to end
Y10T 279/17358	with jaw pads or insert
Y10T 279/17367	. . .	Nonresilient member biased by a resilient member
Y10T 279/17376	. . .	Resilient member reinforced by another resilient member
Y10T 279/17384	. .	with means to exclude contaminants; e.g., seal, shield
Y10T 279/17393	. .	One movable side
Y10T 279/17401	. . .	Sleeved
Y10T 279/17411	. .	Spring biased jaws
Y10T 279/17418	. . .	Unitary
Y10T 279/17427	Split at one end only
Y10T 279/17435	Split at both ends
Y10T 279/17444	Split end to end
Y10T 279/17452	with jaw pads or insert
Y10T 279/17461	. . .	Nonresilient member biased by a resilient member
Y10T 279/17471	. . .	Resilient member reinforced by another resilient member
Y10T 279/17478	. . .	with means to exclude contaminants; e.g., seal, shield
Y10T 279/17487	. . .	Moving-cam actuator
Y10T 279/17495	Threaded sleeve and wedge
Y10T 279/17504	Threaded cam sleeve
Y10T 279/17512	Loose jaws
Y10T 279/17521	Reciprocating cam sleeve
Y10T 279/17529	. . .	Fixed cam and moving jaws
Y10T 279/17538	Threaded-sleeve actuator
Y10T 279/17547	Axial screw actuator
Y10T 279/17555	. . .	Loose jaws
Y10T 279/17564	. .	Loose jaws
Y10T 279/17572	. . .	Moving-cam actuator
Y10T 279/17581	Threaded cam sleeve
Y10T 279/17589	Reciprocating cam sleeve
Y10T 279/17598	. . .	Fixed cam and moving jaws
Y10T 279/17606	Threaded sleeve and body
Y10T 279/17615	. .	Obliquely guided reciprocating jaws
Y10T 279/17623	. . .	Threaded sleeve and jaw
Y10T 279/17632	Conical sleeve

Y10T 279/17641	. . .	Threaded central cone and jaw
Y10T 279/17649	. . .	Threaded sleeve and body
Y10T 279/17658	. . .	Reciprocating jaw advancing sleeve
Y10T 279/17666	. .	Radially reciprocating jaws
Y10T 279/17675	. . .	Transverse-screw actuated
Y10T 279/17683	Interlaced jaws
Y10T 279/17692	. . .	Moving-cam actuator
Y10T 279/17701	Threaded cam sleeve
Y10T 279/17709	Threaded sleeve and wedge
Y10T 279/17717	Rotary eccentric-cam sleeve
Y10T 279/17726	Roller and rocking jaw
Y10T 279/17735	Worm actuated
Y10T 279/17743	Reciprocating cam sleeve
Y10T 279/17752	Ball or roller jaws
Y10T 279/17761	. .	Side detent
Y10T 279/17769	. . .	Pivoted or rotary
Y10T 279/17777	Sleeved
Y10T 279/17786	. . .	Spring
Y10T 279/17794	Sleeved
Y10T 279/17803	. . .	Rotary cam sleeve
Y10T 279/17811	. . .	Reciprocating sleeve
Y10T 279/17821	. . .	Set screw
Y10T 279/17829	. . .	U-clamp
Y10T 279/17837	. . .	Plural bolt
Y10T 279/17846	. . .	Single transverse bolt
Y10T 279/17854	. . .	Longitudinal clamping wedge
Y10T 279/17863	. .	Shouldered-tang holding
Y10T 279/17871	. . .	Cap
Y10T 279/17881	Screw
Y10T 279/17888	. .	Tang offset within socket
Y10T 279/17897	. .	Tang offset without socket
Y10T 279/17905	. .	Bottomless
Y10T 279/17914	. . .	Friction grip
Y10T 279/17923	. .	Transverse pin
Y10T 279/17931	. .	Screw threaded
Y10T 279/17941	. . .	Nut lock
Y10T 279/17948	Threaded sleeve
Y10T 279/17957	. .	Friction grip
Y10T 279/17965	. . .	Drill type
Y10T 279/17974	. .	Barbed or pronged tang

Y10T 279/17982	. . Molded or cast-in tang
Y10T 279/17991	. . Adjustable length or size
Y10T 279/18	. Pivoted jaw
Y10T 279/182	. . Cam-sleeve actuated
Y10T 279/185	. . Internal-cone actuated
Y10T 279/188	. . Toggle actuated
Y10T 279/19	. Radially reciprocating jaws
Y10T 279/1906	. . with indicator
Y10T 279/1913	. . Transverse-screw actuated
Y10T 279/1921	. . . Annular rack
Y10T 279/1926	. . Spiral cam or scroll actuated
Y10T 279/1933	. . . Worm
Y10T 279/1941	. . . Bevel pinion
Y10T 279/1946	. . Rack-and-pinion actuated
Y10T 279/1953	. . Toggle actuated
Y10T 279/1961	. . Lever actuated
Y10T 279/1966	. . . Internal cone
Y10T 279/1973	. . Wedge actuated
Y10T 279/1981	. . External-cone actuated
Y10T 279/1986	. . Jaws
Y10T 279/1993	. . . with means to facilitate jaw removal
Y10T 279/20	. with safety feature
Y10T 279/21	. with measuring, indicating or control means
Y10T 279/22	. Double acting
Y10T 279/23	. with magnetic or electrostatic means
Y10T 279/24	. by centrifugal force
Y10T 279/243	. . to counterbalance jaws
Y10T 279/247	. . to grip tool or workpiece
Y10T 279/25	. Compensation for eccentricity
Y10T 279/26	. with centering means
Y10T 279/27	. Separate chuck-actuating power source
Y10T 279/275	. . Self-contained
Y10T 279/28	. for gear or spline molding
Y10T 279/29	. More than one set of gripping means
Y10T 279/30	. Torsion mandrel
Y10T 279/31	. Jaws mounted on flexible member; i.e. , diaphragm
Y10T 279/32	. Means to prevent jaw loosening
Y10T 279/33	. Member applies axial force component
Y10T 279/34	. Accessory or component
Y10T 279/3406	. . Adapter

Y10T 279/3412	. . . Drive conversion
Y10T 279/3418	. . . for particular tool or workpiece
Y10T 279/3425	. . Sliding cam chuck actuator
Y10T 279/3431	. . Chuck key
Y10T 279/3437	. . . Safety feature; e.g., ejector, interlock
Y10T 279/3443	. . . Key holding or attaching means
Y10T 279/3451	. . . Nonseparable or built-in
Y10T 279/3456	. . Padded or cushioned jaw
Y10T 279/3462	. . Jaw insert
Y10T 279/3468	. . . Machinable jaw
Y10T 279/3475 Locking or positioning means
Y10T 279/3481	. . Tool or workpiece ejector
Y10T 279/3487	. . Tool or work stop or locator
Y10T 279/3493	. . Protection means; e.g., cover, seal, overstress prevention, air blast
Y10T 279/35	. Miscellaneous

Former US Class 292 series

Y10T 292/00	Closure fasteners
Y10T 292/03	. Miscellaneous
Y10T 292/06	. Adjustable backset
Y10T 292/08	. Bolts
Y10T 292/0801	. . Multiple
Y10T 292/0802	. . . Sliding and rotary
Y10T 292/0803	. . . Sliding and swinging
Y10T 292/0805 Combined motion
Y10T 292/0806 Lever-operating means
Y10T 292/0807	. . . Sliding and hooked end
Y10T 292/0808	. . . Sliding and roller
Y10T 292/0809	. . . Sliding and spring arm
Y10T 292/081	. . . Swinging and hooked end
Y10T 292/0811	. . . Swinging and roller
Y10T 292/0813	. . . Swinging and spring arm
Y10T 292/0814	. . . Double acting
Y10T 292/0815 Roller
Y10T 292/0816 Sliding
Y10T 292/0817 Spring arm
Y10T 292/0818 Swinging
Y10T 292/082	. . . Spring arm
Y10T 292/0821 Combined motion

Y10T 292/0822	. . .	Emergency operating means
Y10T 292/0823	. . .	Gear
Y10T 292/0824	. . .	Roller
Y10T 292/0825	. . .	Hooked end
Y10T 292/0826	Operating means
Y10T 292/0828	Link and lever
Y10T 292/0829	Cam
Y10T 292/083	Flexible
Y10T 292/0831	Lever
Y10T 292/0832	Push or pull rod
Y10T 292/0833	Rigid
Y10T 292/0834	. . .	Sliding
Y10T 292/0836	Operating means
Y10T 292/0837	Cam and lever
Y10T 292/0838	Lever and push or pull rod
Y10T 292/0839	Link and lever
Y10T 292/084	Cam
Y10T 292/0841	Flexible
Y10T 292/0843	Gear
Y10T 292/0844	Lever
Y10T 292/0845	Push or pull rod
Y10T 292/0846	Rigid
Y10T 292/0847	Screw
Y10T 292/0848	. . .	Swinging
Y10T 292/0849	Operating means
Y10T 292/0851	Cam and lever
Y10T 292/0852	Link and cam
Y10T 292/0853	Link and lever
Y10T 292/0854	Cam
Y10T 292/0855	Flexible
Y10T 292/0856	Gear
Y10T 292/0857	Lever
Y10T 292/0859	Push or pull rod
Y10T 292/086	Rigid
Y10T 292/0861	Screw
Y10T 292/0862	. .	Swinging and hooked end, multiple head
Y10T 292/0863	. .	Sliding and rotary
Y10T 292/0864	. . .	Combined motion
Y10T 292/0866	. . .	Multiple head
Y10T 292/0867	. . .	Spring projected

Y10T 292/0868 Combined motion
Y10T 292/0869	. . . Spring retracted
Y10T 292/087	. . Loops
Y10T 292/0871	. . . Sliding and swinging, lever-operating means
Y10T 292/0872	. . . Sliding catch
Y10T 292/0874	. . . Spring-arm catch
Y10T 292/0875	. . . Swinging catch
Y10T 292/0876	. . Double acting
Y10T 292/0877	. . . Sliding and swinging
Y10T 292/0878	. . . Sliding
Y10T 292/0879 Roller
Y10T 292/088	. . . Spring arm
Y10T 292/0882 Roller
Y10T 292/0883	. . . Swinging
Y10T 292/0884 Roller
Y10T 292/0885	. . . Roller
Y10T 292/0886	. . Sliding and swinging
Y10T 292/0887	. . . Operating means
Y10T 292/0889 Cam
Y10T 292/089 Lever
Y10T 292/0891 Rigid
Y10T 292/0892	. . . Multiple head
Y10T 292/0893	. . . Spring retracted
Y10T 292/0894	. . Spring arm
Y10T 292/0895	. . . Operating means
Y10T 292/0897 Link and lever
Y10T 292/0898 Cam
Y10T 292/0899 Flexible
Y10T 292/09 Lever
Y10T 292/0901 Push or pull rod
Y10T 292/0902 Rigid
Y10T 292/0903 Seal catch
Y10T 292/0905 Swinging catch
Y10T 292/0906 Screw
Y10T 292/0907	. . . Multiple head
Y10T 292/0908	. . Emergency operating means
Y10T 292/0909	. . . Panel
Y10T 292/091	. . . Platform
Y10T 292/0911	. . Hooked end
Y10T 292/0913	. . . Sliding and swinging

Y10T 292/0914	Operating means
Y10T 292/0915	Cam
Y10T 292/0916	Gear
Y10T 292/0917	Lever
Y10T 292/0918	Rigid
Y10T 292/092	Screw
Y10T 292/0921	Multiple head
Y10T 292/0922	Operating means
Y10T 292/0923	Lever
Y10T 292/0924	Push or pull rod
Y10T 292/0925	Rigid
Y10T 292/0926	Spring projected
Y10T 292/0928	Operating means
Y10T 292/0929	Link and lever
Y10T 292/093	Cam
Y10T 292/0931	Flexible
Y10T 292/0932	Lever
Y10T 292/0933	Push or pull rod
Y10T 292/0934	Rigid
Y10T 292/0936	Spring retracted
Y10T 292/0937	Gravity actuated
Y10T 292/0938	Operating means
Y10T 292/0939	Cam
Y10T 292/094	Flexible
Y10T 292/0941	Lever
Y10T 292/0943	Push or pull rod
Y10T 292/0944	Rigid
Y10T 292/0945	Operating means
Y10T 292/0946	Link and lever
Y10T 292/0947	Cam
Y10T 292/0948	Closure
Y10T 292/0949	Lever
Y10T 292/0951	Rigid
Y10T 292/0952	Closure catch
Y10T 292/0953	Friction catch
Y10T 292/0954	Padlock or seal catch
Y10T 292/0955	Screw catch
Y10T 292/0956	Sliding catch
Y10T 292/0957	Spring-arm catch
Y10T 292/0959	Swinging catch

Y10T 292/096	. . . Sliding
Y10T 292/0961 Multiple head
Y10T 292/0962 Operating means
Y10T 292/0963 Link and lever
Y10T 292/0964 Cam
Y10T 292/0966 Gear
Y10T 292/0967 Lever
Y10T 292/0968 Rigid
Y10T 292/0969 Spring projected
Y10T 292/097 Operating means
Y10T 292/0971 Cam and lever
Y10T 292/0972 Lever and push or pull rod
Y10T 292/0974 Link and lever
Y10T 292/0975 Link and push or pull rod
Y10T 292/0976 Sliding cam
Y10T 292/0977 Cam
Y10T 292/0978 Specifically related to vehicle closure
Y10T 292/0979 Bolt disabled by contraretractive movement of inside handle
Y10T 292/098 Auxiliary bolt
Y10T 292/0982 Bolt blocking or disabling means
Y10T 292/0983 Involves rollback
Y10T 292/0984 Rollback members located on separate spindles
Y10T 292/0985 Discrete pivotable or rotatable actuator
Y10T 292/0986 Discrete push or pull actuator
Y10T 292/0987 Bolt has ancillary projection spring
Y10T 292/0989 Plural rollback elements directionally selectively effective
Y10T 292/099 On separate spindles
Y10T 292/0991 On a tubular member
Y10T 292/0992 Flexible
Y10T 292/0993 Gear
Y10T 292/0994 Lever
Y10T 292/0995 Push or pull rod
Y10T 292/0997 Rigid
Y10T 292/0998 Screw
Y10T 292/0999 Spring retracted
Y10T 292/10 Friction catch
Y10T 292/1001 Sliding catch
Y10T 292/1002 Spring-arm catch
Y10T 292/1003 Swinging catch
Y10T 292/1005 Cam-operating means

Y10T 292/1006	. . .	Gravity actuated
Y10T 292/1007	Operating means
Y10T 292/1008	Cam and lever
Y10T 292/1009	Link and lever
Y10T 292/101	Cam
Y10T 292/1011	Lever
Y10T 292/1013	Rigid
Y10T 292/1014	. . .	Operating means
Y10T 292/1015	Link and lever
Y10T 292/1016	Cam
Y10T 292/1017	Flexible
Y10T 292/1018	Gear
Y10T 292/102	Lever
Y10T 292/1021	Motor
Y10T 292/1022	Rigid
Y10T 292/1023	Closure catch
Y10T 292/1024	Friction catch
Y10T 292/1025	Padlock or seal catch
Y10T 292/1026	Screw catch
Y10T 292/1028	Sliding catch
Y10T 292/1029	Seal
Y10T 292/103	Spring-arm catch
Y10T 292/1031	Swinging catch
Y10T 292/1032	Seal
Y10T 292/1033	Screw
Y10T 292/1034	. . .	Curved
Y10T 292/1036	. . .	End lever
Y10T 292/1037	. . .	Pivoted end
Y10T 292/1038	. . .	Roller
Y10T 292/1039	. .	Swinging and camming
Y10T 292/10395	. . .	Spring projected
Y10T 292/104	Rigid operating means
Y10T 292/1041	. . .	Rigid operating means
Y10T 292/1043	. .	Swinging
Y10T 292/1044	. . .	Multiple head
Y10T 292/1045	Operating means
Y10T 292/1046	Cam
Y10T 292/1047	Closure
Y10T 292/1048	Lever
Y10T 292/1049	Rigid

Y10T 292/1051	. . .	Spring projected
Y10T 292/1052	Operating means
Y10T 292/1053	Lever and push or pull rod
Y10T 292/1054	Link and cam
Y10T 292/1055	Link and lever
Y10T 292/1056	Cam
Y10T 292/1057	Flexible
Y10T 292/1059	Lever
Y10T 292/106	Push or pull rod
Y10T 292/1061	Rigid
Y10T 292/1062	. . .	Spring retracted
Y10T 292/1063	. . .	Gravity actuated
Y10T 292/1064	Operating means
Y10T 292/1066	Cam and lever
Y10T 292/1067	Link and lever
Y10T 292/1068	Cam
Y10T 292/1069	Flexible
Y10T 292/107	Lever
Y10T 292/1071	Push or pull rod
Y10T 292/1072	Rigid
Y10T 292/1074	Roller
Y10T 292/1075	. . .	Operating means
Y10T 292/1076	Link and lever
Y10T 292/1077	Cam
Y10T 292/1078	Closure
Y10T 292/1079	Gear
Y10T 292/108	Lever
Y10T 292/1082	Motor
Y10T 292/1083	Rigid
Y10T 292/1084	Closure catch
Y10T 292/1085	Friction catch
Y10T 292/1086	Padlock or seal catch
Y10T 292/1087	Screw catch
Y10T 292/1089	Sliding catch
Y10T 292/109	Seal
Y10T 292/1091	Spring-arm catch
Y10T 292/1092	Swinging catch
Y10T 292/1093	Seal
Y10T 292/1094	Screw
Y10T 292/1095	. .	Seal-rupturing devices

Y10T 292/1097	. . Reversible
Y10T 292/1098	. . . Cam and lever operating means
Y10T 292/1099	. . Screw
Y10T 292/11	. Magnetic
Y10T 292/14	. Ball
Y10T 292/17	. Bendable securers
Y10T 292/175	. Bolt releasers
Y10T 292/18	. . Free-end-engaging means
Y10T 292/19	. . Foot operated
Y10T 292/20	. Clamps
Y10T 292/202	. . Hatch fastener
Y10T 292/205	. . Ring
Y10T 292/207	. . . Permanently deformed
Y10T 292/209	. . . Resilient wedge
Y10T 292/212	. . . With expanding or contracting means
Y10T 292/214 Screw
Y10T 292/216 Toggle lever
Y10T 292/218	. . Screw against closure
Y10T 292/221	. . Screw and nut
Y10T 292/223	. . . Swingable
Y10T 292/225	. . Cam-operating means
Y10T 292/228	. . Portable
Y10T 292/23	. Cross bars
Y10T 292/237	. . Screw-operating means
Y10T 292/243	. . Vehicle door latches
Y10T 292/25	. Cylinder
Y10T 292/28	. Extension link
Y10T 292/282	. . Multiple
Y10T 292/283	. . Chain
Y10T 292/285	. . Notched bar
Y10T 292/286	. . . Sliding catch
Y10T 292/288	. . . Swinging catch
Y10T 292/289	. . Slotted bar
Y10T 292/291	. . . Sliding catch
Y10T 292/293	. . . Swinging catch
Y10T 292/2935	. . Slotted or notched keeper
Y10T 292/294	. . . Sliding catch
Y10T 292/296	. . . Swinging catch
Y10T 292/297	. . Notched keeper
Y10T 292/299	. . Slotted keeper

Y10T 292/301	. . Friction catch
Y10T 292/302	. . Screw catch
Y10T 292/304	. . Sliding catch
Y10T 292/305	. . Swinging catch
Y10T 292/306	. Gear
Y10T 292/307	. . Sliding catch
Y10T 292/308	. . Swinging catch
Y10T 292/31	. Hasps
Y10T 292/314	. . Sliding catch
Y10T 292/319	. . . Seal
Y10T 292/323	. . Swinging catch
Y10T 292/327	. . . Seal
Y10T 292/331	. . Seal catch
Y10T 292/336	. . Seal-rupturing devices
Y10T 292/34	. Portable
Y10T 292/37	. Portable securer plate or bar
Y10T 292/373	. . Sliding and swinging holding member
Y10T 292/376	. . Screw-holding member
Y10T 292/379	. . Sliding holding member
Y10T 292/382	. . . Screw-operating means
Y10T 292/385	. . . Screw catch
Y10T 292/388	. . . Sliding catch
Y10T 292/391	. . . Swinging catch
Y10T 292/394	. . Swinging holding member
Y10T 292/397	. . . Catch devices
Y10T 292/40	. Rings
Y10T 292/42	. Rigid engaging means
Y10T 292/426	. . Screw catch
Y10T 292/432	. . Sliding catch
Y10T 292/438	. . Spring-arm catch
Y10T 292/444	. . Swinging catch
Y10T 292/45	. Rod clamps
Y10T 292/47	. . Friction-plate catch
Y10T 292/48	. Seals
Y10T 292/481	. . Compressible disk
Y10T 292/483	. . . Reinforced
Y10T 292/484	. . . Multiple
Y10T 292/485 Sheet metal
Y10T 292/487 Hard and soft metal
Y10T 292/488	. . . Sheet metal

Y10T 292/49	. . Compressible rivets and eyelets
Y10T 292/491	. . Distorted shackle
Y10T 292/492	. . Driving
Y10T 292/494	. . Interengaging shackle ends, inclosing housing
Y10T 292/4945	. . Rigid shackle ends
Y10T 292/495	. . . Resilient and rigid engaging means
Y10T 292/496	. . . Resilient engaging means
Y10T 292/497	. . Resilient shackle ends
Y10T 292/498	. . . Rigid engaging means
Y10T 292/499	. . . Resilient engaging means
Y10T 292/50	. . Single piece, spring catch
Y10T 292/502	. . Shiftable catch shackle operated
Y10T 292/503	. . Split-ring catch, shackle operated
Y10T 292/505	. . Strap-end fasteners
Y10T 292/506	. . Rigid disk, distorted shackle
Y10T 292/507	. . Tag type
Y10T 292/509	. . Encasing
Y10T 292/51	. Seal bolts
Y10T 292/513	. Shackles
Y10T 292/516	. . Sliding catch, seal
Y10T 292/522	. . Swinging catch, seal
Y10T 292/528	. . Seal catch
Y10T 292/534	. . Seal-rupturing devices
Y10T 292/54	. Trippers
Y10T 292/546	. . Sliding detent
Y10T 292/552	. . Spring-arm detent
Y10T 292/558	. . Sliding bolt, swinging detent
Y10T 292/564	. . Swinging bolt, swinging detent
Y10T 292/57	. Operators with knobs or handles
Y10T 292/59	. Rollback and spindle connection
Y10T 292/62	. Bolt casings
Y10T 292/65	. Braces
Y10T 292/67	. . Portable
Y10T 292/68	. Keepers
Y10T 292/683	. . Segment
Y10T 292/685	. . With anti-friction means
Y10T 292/688	. . With silencing or anti-rattle means
Y10T 292/691	. . . Take-up
Y10T 292/694	. . Covers
Y10T 292/696	. . With movable dog, catch or striker

Y10T 292/699	. . . Motor controlled
Y10T 292/702	. . . Pivoted or swinging
Y10T 292/705	. . Adjustable
Y10T 292/707	. . . Vertically
Y10T 292/71	. Wedges
Y10T 292/73	. . Portable
Y10T 292/74	. Weights
Y10T 292/76	. Blind-slat holders
Y10T 292/79	. Bolt guards
Y10T 292/82	. Knobs
Y10T 292/85	. Knob-attaching devices
Y10T 292/854	. . Friction
Y10T 292/858	. . Screw
Y10T 292/861	. . . Guards
Y10T 292/865	. . Sliding
Y10T 292/869	. . Spring arm
Y10T 292/873	. . Swinging
Y10T 292/876	. . Wedge
Y10T 292/88	. Knob bearings
Y10T 292/91	. Knob rose plates
Y10T 292/93	. Latch spindles
Y10T 292/96	. Latch-spindle catches

Former US Class 307 series

Y10T 307/00	Electrical transmission or interconnection systems
Y10T 307/25	. Plural load circuit systems
Y10T 307/258	. . Common conductor or return type
Y10T 307/266	. . . Polyphase
Y10T 307/273 Phase balancing
Y10T 307/281	. . . Voltage divider type
Y10T 307/289	. . . Plural output generators
Y10T 307/297	. . Transformer connections
Y10T 307/305	. . Plural sources of supply
Y10T 307/313	. . . Interconnected for energy transfer
Y10T 307/32 With control of magnitude of energy transfer
Y10T 307/328 Diverse sources
Y10T 307/336 AC and DC
Y10T 307/344	. . . Substitute or alternate source
Y10T 307/352	. . . With control of magnitude of current or power

Y10T 307/359	. . . Diverse sources
Y10T 307/367 AC and DC
Y10T 307/375 Different frequencies
Y10T 307/383 Different voltages
Y10T 307/391	. . . Selectively connected loads and/or sources
Y10T 307/398	. . Anticoupling of load circuits through same source
Y10T 307/406	. . Control of current or power
Y10T 307/414	. . . Load current proportioning or dividing
Y10T 307/422	. . . Constant magnitude control
Y10T 307/43 By control of one or more load circuits
Y10T 307/438	. . . Limit control
Y10T 307/445	. . Serially connected load circuits
Y10T 307/453	. . . Selective series-parallel connections
Y10T 307/461	. . Selectively connected or controlled load circuits
Y10T 307/469	. . . Condition responsive
Y10T 307/477	. . . Code-controlled
Y10T 307/484	. . . Sequential or alternating
Y10T 307/492	. . Circuit arrangements or layouts
Y10T 307/50	. Plural supply circuits or sources
Y10T 307/505	. . One source floats across or compensates for other source
Y10T 307/511	. . . With intervening converter
Y10T 307/516 Storage battery or accumulator-type source
Y10T 307/522	. . . Dynamoelectric-type source
Y10T 307/527	. . . Storage battery or accumulator-type source
Y10T 307/533 With series-connected auxiliary source
Y10T 307/538 Tap-changing or variable number of cells
Y10T 307/544	. . Circulating- or inter-current control or prevention
Y10T 307/549	. . Load current control
Y10T 307/555	. . . Load current division
Y10T 307/56 Serially connected sources
Y10T 307/565 Fixed or predetermined ratio
Y10T 307/571 Diverse-or unlike-type sources
Y10T 307/576 Plural generators
Y10T 307/582 Plural converters
Y10T 307/587 Peak or excess load
Y10T 307/593	. . . Constant load or current
Y10T 307/598 Serially connected sources
Y10T 307/604	. . . Load-limiting
Y10T 307/609	. . . Serially connected sources
Y10T 307/615	. . Substitute or emergency source

Y10T 307/62	. . . Plural substitute sources
Y10T 307/625	. . . Storage battery or accumulator
Y10T 307/631 With intervening dynamoelectric machine
Y10T 307/636	. . . Dynamoelectric
Y10T 307/642	. . Sources distributed along load circuit
Y10T 307/647	. . Load transfer without paralleling sources
Y10T 307/653	. . Series-parallel connection of sources
Y10T 307/658	. . Diverse or unlike electrical characteristics
Y10T 307/664	. . . Differing frequencies
Y10T 307/669	. . . Differing capacities
Y10T 307/675	. . . Differing voltages
Y10T 307/68 Generator sources
Y10T 307/685	. . Series-connected sources
Y10T 307/691	. . . Generator sources
Y10T 307/696	. . Selective or optional sources
Y10T 307/702	. . . Predetermined sequence
Y10T 307/707	. . Plural converters
Y10T 307/713	. . Plural transformers
Y10T 307/718	. . Plural generators
Y10T 307/724	. . Connecting or disconnecting
Y10T 307/729	. . . Condition responsive
Y10T 307/735 Attainment of voltage, frequency or phase relationship
Y10T 307/74	. Switching systems
Y10T 307/747	. . Plural switches
Y10T 307/753	. . . Lazy-man switch type
Y10T 307/76	. . . Selectively actuated
Y10T 307/766	. . Condition responsive
Y10T 307/773	. . . Light, heat, vibratory or radiant energy
Y10T 307/779	. . . Fluid pressure, density, level, velocity or humidity
Y10T 307/786	. . . Mechanical force
Y10T 307/793 Speed, centrifugal or kinetic force
Y10T 307/799 Inertia or acceleration
Y10T 307/806 Direction of rotation
Y10T 307/812 Differential speed between two bodies
Y10T 307/819 Torque
Y10T 307/826	. . . Electrical
Y10T 307/832 Power or energy
Y10T 307/839 Polarity, phase sequence or reverse flow
Y10T 307/845 AC or DC discriminating
Y10T 307/852 Frequency

Y10T 307/858 Voltage
Y10T 307/865 Current
Y10T 307/872	. . Repetitive make and break
Y10T 307/878	. . . Electronically controlled relay
Y10T 307/885 Responsive to physical condition
Y10T 307/891	. . . Thermal relay
Y10T 307/898	. . . Vibrating relay
Y10T 307/904	. . . Miscellaneous
Y10T 307/911	. . With operation facilitating feature
Y10T 307/918	. . . Preliminary reduction in current or voltage of system
Y10T 307/924	. . . Switch contact conditioning
Y10T 307/931 Polarity reversing
Y10T 307/937	. . Switch actuation
Y10T 307/944	. . . Power circuit controlled
Y10T 307/951	. . . With time delay or retardation means
Y10T 307/957 Electrically initiated
Y10T 307/964 Series connected switches
Y10T 307/97	. . . With locking, holding or braking means
Y10T 307/977	. . . Electrical actuator
Y10T 307/983	. . . Fluid-pressure actuator

Former US Class 403 Series

Y10T 403/00	Joints and connections
Y10T 403/10	. Selectively engageable hub to shaft connection
Y10T 403/11	. including frangible component
Y10T 403/12	. Selectively assembled, e.g. , convertible, etc.
Y10T 403/125	. . Selective orientation
Y10T 403/13	. Inflatable connector
Y10T 403/14	. with opening for access to connector or operator
Y10T 403/142	. . to threaded component
Y10T 403/145	. . . Transverse to thread axis
Y10T 403/148	. . to biased component
Y10T 403/15	. Closure or plug spaced from joint
Y10T 403/16	. with adjunctive protector, broken parts retainer, repair, assembly or disassembly feature
Y10T 403/1608	. . Holding means or protector functioning only during transportation, assembly or disassembly
Y10T 403/1616	. . Position or guide means
Y10T 403/1624	. . . Related to joint component
Y10T 403/1633	. . Utilizing fluid pressure

Y10T 403/1641	. . Back-off means, e.g., separator, etc.
Y10T 403/1649	. . Handle or handwheel
Y10T 403/1658	. . . Actuates retainer or blocker
Y10T 403/1666	. . tool-engaging or accommodating means or with tool
Y10T 403/1674	. . . for latch or retainer
Y10T 403/1683	. . Releasably captive nut or bolt
Y10T 403/1691	. . Means to lock bolt or nut when other is turned
Y10T 403/17	. with adjunctive shield
Y10T 403/18	. Structurally installed in diverse art device
Y10T 403/185	. . Head or base
Y10T 403/19	. Coupling supported by independent bearing
Y10T 403/20	. with indicator or inspection means
Y10T 403/21	. Utilizing thermal characteristic, e.g. , expansion or contraction, etc.
Y10T 403/213	. . Interposed material of intermediate coefficient of expansion
Y10T 403/217	. . Members having different coefficients of expansion
Y10T 403/22	. with fluid pressure responsive component
Y10T 403/23	. with ambient condition responsive control means
Y10T 403/24	. with independent handle or operator
Y10T 403/25	. with distinct fluid or article handling or directing feature
Y10T 403/251	. . External reservoir
Y10T 403/253	. . Pressure fitting
Y10T 403/255	. . including port or reservoir communicating with joint
Y10T 403/257	. . . Articulated member
Y10T 403/259 At joint interface
Y10T 403/26	. Non-adhering fluent material at joint
Y10T 403/27	. with strain-limiting means
Y10T 403/28	. Combined
Y10T 403/29	. Rotarily connected, differentially translatable members, e.g. , turn-buckle, etc.
Y10T 403/291	. . having tool-engaging means or operating handle
Y10T 403/293	. . having operating mechanism
Y10T 403/295	. . having locking means
Y10T 403/297	. . Differential pitch, similar hand
Y10T 403/299	. . Externally threaded actuator
Y10T 403/30	. Laterally related members connected by latch means, e.g. , scaffold connectors
Y10T 403/31	. Flexible diaphragm or bellows
Y10T 403/315	. . with additional connection or packing
Y10T 403/32	. Articulated members
Y10T 403/32008	. . Plural distinct articulation axes
Y10T 403/32016	. . . Three or more parallel axes
Y10T 403/32024	. . . Single adjustment for plural axes

Y10T 403/32032	. . .	Plural ball and socket
Y10T 403/32041	. . .	Universal
Y10T 403/32049	Non-coplanar axes
Y10T 403/32057	. . .	Angular and linear
Y10T 403/32065	Screw and swivel
Y10T 403/32073	Pivot stud slidable in elongated opening
Y10T 403/32081	. . .	Parallel rotary
Y10T 403/32091	. . .	Plural translating connections
Y10T 403/32098	. .	Branched
Y10T 403/32106	. .	Member pivoted at rigid corner
Y10T 403/32114	. .	including static joint
Y10T 403/32122	. . .	Trunnion assembly to side of rod
Y10T 403/32131	. . .	One member is plate or side
Y10T 403/32139	Secant, i.e., rod extending through plate
Y10T 403/32147	Plate or side forms bearing surface
Y10T 403/32155	Bearing component clamped to plate or side, e.g., bolted, etc.
Y10T 403/32163	. . .	Articulate joint intermediate end joints
Y10T 403/32172	Variable angle
Y10T 403/32181	Universal
Y10T 403/32188	. . .	Angled or offset members
Y10T 403/32196	. . .	Articulate joint is ball and socket
Y10T 403/32204	with threaded joint
Y10T 403/32213	. . .	Articulate joint is a swivel
Y10T 403/32221	. . .	Articulate joint comprises pivoted clevis or channel bar
Y10T 403/32229	. . .	Articulate joint is a slide
Y10T 403/32237	. .	including operator
Y10T 403/32245	. .	Arcuate shank moves in complementary guide
Y10T 403/32254	. .	Lockable at fixed position
Y10T 403/32262	. . .	At selected angle
Y10T 403/32271	Movable brace between members
Y10T 403/32278	Members rotatable about oblique axes
Y10T 403/32286	Clamping screw traverses sliding complementary arcuate bearing surfaces
Y10T 403/32295	Securing yoke or ring spaced radially from locking means
Y10T 403/32303	Eyebolt
Y10T 403/32311	Ball and socket
Y10T 403/32319	including pivot stud
Y10T 403/32327	including radially spaced detent or latch component
Y10T 403/32336	Engaging notch or recess in outer periphery of component
Y10T 403/32344	Side of rod engages recess in radial face
Y10T 403/32352	Pivoted detent

Y10T 403/32361	Engaging recess in radial face
Y10T 403/32368	including radial interengaging tongue and slot or serrations
Y10T 403/32377	Radially spaced arcuate slot engages fastener
Y10T 403/32385	Locked by plural motions of one member
Y10T 403/32393	including bridging keeper
Y10T 403/32401	Locked by nesting parts
Y10T 403/32409	Members locked in axial alignment
Y10T 403/32418	Plural distinct positions
Y10T 403/32426	Plural distinct positions
Y10T 403/32434	Unidirectional movement, e.g., ratchet, etc.
Y10T 403/32442	At least one discrete position
Y10T 403/32451	Step-by-step adjustment
Y10T 403/32459	Retainer extends through aligned recesses
Y10T 403/32467	Telescoping members
Y10T 403/32475	having detent
Y10T 403/32483	Spring biased
Y10T 403/32491	Threaded
Y10T 403/32501	Cam or wedge
Y10T 403/32508	having transverse pin
Y10T 403/32516	Remotely actuated
Y10T 403/32524	Self-locking
Y10T 403/32532	Clamped members
Y10T 403/32541	Rotatable members resiliently biased to one position
Y10T 403/32549	including limit means
Y10T 403/32557	for pivotal motion
Y10T 403/32565	Ball and socket with restricted movement about one axis
Y10T 403/32573	Ball stud passes through confining opening
Y10T 403/32581	Pin and slot
Y10T 403/32591	Opposed stops on one member
Y10T 403/32598	Threaded interface
Y10T 403/32606	Pivoted
Y10T 403/32614	including circumferential biasing or damping means
Y10T 403/32622	Rocking or rolling contact
Y10T 403/32631	Universal ball and socket
Y10T 403/32639	including internal tie means
Y10T 403/32647	Plural concave surfaces with diverse curvature
Y10T 403/32655	Interposed concavo-convex component
Y10T 403/32663	Outer surfaces
Y10T 403/32672	Swiveled ball parts or seat
Y10T 403/32681	Composite ball

Y10T 403/32688	Spring biased segments
Y10T 403/32696	Nonmetallic part
Y10T 403/32704	Stud extends into ball
Y10T 403/32713	Elastomerically biased or backed components
Y10T 403/32721	Elastomeric seat
Y10T 403/32729	Externally packed
Y10T 403/32737	including liner, shim, or discrete seat
Y10T 403/32745	Spring acts through wedging surfaces
Y10T 403/32754	Variably preloaded
Y10T 403/32762	Spring-biased seat opposite ball stud
Y10T 403/32771	Porous
Y10T 403/32778	Completely spacing the members
Y10T 403/32786	Divided socket-type coupling
Y10T 403/32795	Bifurcated socket
Y10T 403/32803	Separable socket sections
Y10T 403/32811	Spring-biased
Y10T 403/32819	including tension or take-up means
Y10T 403/32827	Interposed spring means coaxial with pivot
Y10T 403/32836	Acting through tapered surface on bearing component
Y10T 403/32844	Manually variable
Y10T 403/32852	External of bearing assembly, e.g., antirattler, etc.
Y10T 403/32861	T-pivot, e.g., wrist pin, etc.
Y10T 403/32868	Floating pin
Y10T 403/32877	Pin is integral with or secured to inner member
Y10T 403/32885	Expanded pin or end
Y10T 403/32893	including distinct pin retainer
Y10T 403/32901	Unitary clip or plug
Y10T 403/32909	Threaded pin end
Y10T 403/32918	fork and tongue
Y10T 403/32926	with interposed antifriction means
Y10T 403/32934	Oppositely laterally movable tines
Y10T 403/32942	On oblique interface
Y10T 403/32951	Transverse pin or stud
Y10T 403/32959	Traverses interposed facing component
Y10T 403/32967	Attached to or integral with one member
Y10T 403/32975	Rotatable
Y10T 403/32983	Rod in socket
Y10T 403/32991	Axially spring-biased coaxial members
Y10T 403/33	Transverse rod to spaced plate surfaces
Y10T 403/335	Retainer utilizes or abuts plural plates

Y10T 403/34	. Branched
Y10T 403/341	. . Three or more radiating members
Y10T 403/342	. . . Polyhedral
Y10T 403/343 Unilateral of plane
Y10T 403/344	. . . Plural pairs of axially aligned members
Y10T 403/345	. . . Coplanar
Y10T 403/346 Additional rod held by encompassing means
Y10T 403/347	. . Polyhedral
Y10T 403/348	. . Parallel rods
Y10T 403/349	. . Coplanar
Y10T 403/35	. Diverse material coupling member
Y10T 403/36	. Three or more serial joints, at least one diverse
Y10T 403/362	. . Nonaligned axes
Y10T 403/364	. . Separable intermediate joint
Y10T 403/366	. . . Axially acting connector
Y10T 403/368	. . . Screw or cam
Y10T 403/37	. Joint involving plural layers of single rod
Y10T 403/38	. Laterally related rods independently joined to transverse surface
Y10T 403/39	. Rod to member to side, e.g. , plate, rod side, etc.
Y10T 403/3906	. . Rod side to member to side
Y10T 403/3913	. . Unilateral of side
Y10T 403/3921	. . Arcuate or multiplanar side
Y10T 403/3926	. . . Encompassed side
Y10T 403/3933	. . Intermediate member includes tubular part
Y10T 403/3941	. . . Side or tubular part deformed in situ
Y10T 403/3946	. . . Intermediate member extends through side
Y10T 403/3953 Split or divided tubular part and coacting compressor
Y10T 403/3961 Transverse clamp secures rod and tubular part
Y10T 403/3966 Rod also extends through side
Y10T 403/3973	. . . Oblique rod
Y10T 403/3981	. . . Intermediate member secured to side by radial flange
Y10T 403/3986	. . . Internally threaded tubular part
Y10T 403/3993	. . Intermediate member extends completely through side
Y10T 403/40	. Radially spaced members joined by independent coupling
Y10T 403/405	. . Flexible intermediate member
Y10T 403/41	. Coacting connection between inner member and plural parts of outer member
Y10T 403/42	. Rigid angle coupling, e.g. , elbow or u, etc.
Y10T 403/43	. Axially curved or bent portion of rod is joint component
Y10T 403/4309	. . Interfitted crossing rods
Y10T 403/4318	. . Joined to laterally related transverse surface at axially spaced points

Y10T 403/4327	. . Reversely bent portion
Y10T 403/4336	. . . Around eye-forming thimble
Y10T 403/4345	. . . with wedge clamp
Y10T 403/4354	. . . Held by crimped collar
Y10T 403/4363	. . . Open U
Y10T 403/4372	. . Intertwisted ends
Y10T 403/4381	. . End of rod is deflected laterally within connector
Y10T 403/4391	. . Plural rods distorted by single component
Y10T 403/44	. Three or more members connected at single locus
Y10T 403/443	. . All encompassed
Y10T 403/447	. . Mutually contacting
Y10T 403/45	. Flexibly connected rigid members
Y10T 403/451	. . Rigid sleeve encompasses flexible bushing
Y10T 403/452	. . . Longitudinally divided sleeve
Y10T 403/453	. . Flexible sleeve-type coupling
Y10T 403/454	. . Connecting pin traverses radially interposed elastomer
Y10T 403/455	. . Elastomer interposed between radially spaced members
Y10T 403/456	. . . Elastomer encompasses shoulder on inner member
Y10T 403/457	. . . including axially acting compressing means
Y10T 403/458	. . . Composite bushing with elastomeric component
Y10T 403/459	. . Helical spring type coupling
Y10T 403/46	. Rod end to transverse side of member
Y10T 403/4602	. . Corner joint
Y10T 403/4605	. . Stirrup
Y10T 403/4608	. . Structure attached to rod end encompasses side
Y10T 403/4611	. . . Clamped saddle
Y10T 403/4614	. . . Yoke or ring
Y10T 403/4617 having radial screw at bight
Y10T 403/4621	. . including saddle
Y10T 403/4622	. . Gland type
Y10T 403/4625	. . . Rod and side gripped simultaneously by single actuation
Y10T 403/4628	. . Rod clamped to hole edge
Y10T 403/4631	. . Rod to open edge of side, e.g., wrap-around connection
Y10T 403/4634	. . Rod and side deformingly interlocked
Y10T 403/4637	. . Radially interposed, side-engaging shim or bushing
Y10T 403/4641	. . Socket formed by shaping or deforming side
Y10T 403/4642	. . Integral transverse projection on side, e.g., necked, etc.
Y10T 403/4645	. . . From rod side
Y10T 403/4648	. . Utilizing opposite sides of member
Y10T 403/4651	. . . Rod is expanded by component inserted from distal side

Y10T 403/4654 Separate and deformable component
Y10T 403/4657 Plural contacting components
Y10T 403/4661 Barbed component
Y10T 403/4662 Inserted, blind-side-engaging, retaining portion on rod
Y10T 403/4665 Stepped or tapered recess in side
Y10T 403/4668 Terminal, rod-attached retainer engages distal side
Y10T 403/4671 Inserted into rod
Y10T 403/4674 Clamped member
Y10T 403/4677 Clamping component engages recessed side
Y10T 403/4681 Bolted to rod
Y10T 403/4682 Between rod shoulder and terminal nut
Y10T 403/4685 Bolted through member
Y10T 403/4688 Coaxial collar or shoulder or rod is clamp element
Y10T 403/4691	. . Flange on rod bolted to side
Y10T 403/4694	. . Rod received in recessed side, e.g., socket or tapered opening, etc.
Y10T 403/4697	. . Utilizing internal rod structure
Y10T 403/47	. Molded joint
Y10T 403/471	. . And independent connection
Y10T 403/472	. . including mechanical interlock
Y10T 403/473	. . Socket or open cup for bonding material
Y10T 403/475	. . Member cast in situ
Y10T 403/477	. . Fusion bond, e.g., weld, etc.
Y10T 403/478	. . . Metallic fusion material
Y10T 403/479 Added bonding material, e.g., solder, braze, etc.
Y10T 403/48	. Shrunken fit
Y10T 403/49	. Member deformed in situ
Y10T 403/4908	. . Separating element between strands of member
Y10T 403/4916	. . Interposed deforming element contacts socket bottom
Y10T 403/4924	. . Inner member is expanded by longitudinally inserted element
Y10T 403/4933	. . by separate, deformable element
Y10T 403/4941	. . Deformation occurs simultaneously with action of separate, diverse function, joint component
Y10T 403/4949	. . Deforming component is inserted section
Y10T 403/4958	. . Separate deforming means remains with joint assembly
Y10T 403/4966	. . Deformation occurs simultaneously with assembly
Y10T 403/4974	. . by piercing
Y10T 403/4983	. . Diverse resistance to lateral deforming force
Y10T 403/4991	. . Both members deformed
Y10T 403/50	. Bridged by diverse connector
Y10T 403/51	. including spaced, diverse connections

Y10T 403/52	. including distinct packing
Y10T 403/53	. Split end with laterally movable opposed portions
Y10T 403/535	. . with separate force-applying means
Y10T 403/54	. Flexible member is joint component
Y10T 403/55	. Member ends joined by inserted section
Y10T 403/551	. . Externally bridged
Y10T 403/553	. . Laterally inserted section
Y10T 403/555	. . Angle section
Y10T 403/556	. . Section threaded to member
Y10T 403/557	. . Expansible section
Y10T 403/559	. . Fluted or splined section
Y10T 403/56	. Thread adaptor
Y10T 403/57	. Distinct end coupler
Y10T 403/5706	. . Diverse serial connections
Y10T 403/5713	. . . Axially cleft coupler
Y10T 403/5721	. . Single actuator for plural connections
Y10T 403/5726	. . . Axially biased end portions
Y10T 403/5733	. . Plural opposed sockets
Y10T 403/5741	. . Separate screw or pin-type connections
Y10T 403/5746	. . Continuous thread
Y10T 403/5753	. . having separable end caps or plugs
Y10T 403/5761	. . Interrupted periphery, e.g., split or segmental, etc.
Y10T 403/5766	. . . Axially divided segments
Y10T 403/5773 Interfitting
Y10T 403/5781 Bolted
Y10T 403/5786	. . . Split
Y10T 403/5793	. . including member wedging or camming means
Y10T 403/58	. including ancillary means blocking disconnection of joint
Y10T 403/581	. . Blocker for assembled joint retainer
Y10T 403/583	. . . Blocker keeper
Y10T 403/585	. . . Blocked key
Y10T 403/587	. . Blocker is catch or key
Y10T 403/589	. . Cam or thread lock
Y10T 403/59	. Manually releaseable latch type
Y10T 403/591	. . having operating mechanism
Y10T 403/592	. . . Ball detent
Y10T 403/593	. . . Remotely actuated
Y10T 403/595	. . . Lever
Y10T 403/597	. . Swiveled bolt
Y10T 403/598	. . Transversely sliding pin

Y10T 403/599	. . Spring biased manipulator
Y10T 403/60	. Biased catch or latch
Y10T 403/602	. . by separate spring
Y10T 403/604	. . . Radially sliding catch
Y10T 403/606	. . Leaf spring
Y10T 403/608	. . Pivoted
Y10T 403/61	. Side slide: elongated co-linear members
Y10T 403/62	. Annular recess is joint component
Y10T 403/63	. Convergent interface
Y10T 403/635	. . Tapered
Y10T 403/64	. Interconnected flanges or shoulders
Y10T 403/642	. . Separate flange or shoulder
Y10T 403/645	. . Axially bolted or riveted
Y10T 403/648	. . Clamped
Y10T 403/65	. Scarf
Y10T 403/655	. . Mirror images
Y10T 403/66	. Interfitted members with external bridging piece
Y10T 403/67	. Thimble: screw or cam
Y10T 403/68	. Screw or cam
Y10T 403/69	. Axially split or separable member
Y10T 403/70	. Interfitted members
Y10T 403/7001	. . Crossed rods
Y10T 403/7003	. . . One rod is encompassed by the other
Y10T 403/7005	. . Lugged member, rotary engagement
Y10T 403/7007	. . . Bayonet joint
Y10T 403/7009	. . Rotary binding cam or wedge
Y10T 403/7011	. . . Radially interposed shim or bushing
Y10T 403/7013 Arcuate slip
Y10T 403/7015	. . Assembled by plural manipulations of member
Y10T 403/7016	. . Diametric end slot is joint component
Y10T 403/7018	. . including separably interposed key
Y10T 403/7021	. . . Axially extending
Y10T 403/7022 Resilient
Y10T 403/7024 Longitudinally stepped or tapered
Y10T 403/7026	. . Longitudinally splined or fluted rod
Y10T 403/7028	. . . Splayed or having a cam surface for anti-backlash
Y10T 403/7031	. . . Rod designed to be manipulable, e.g., twistable, within coupling for quick disconnect
Y10T 403/7032	. . . including a means, e.g., spring biased portion, for misalignment correction
Y10T 403/7033	. . . including a lock or retainer

Y10T 403/7035	. . . Specific angle or shape of rib, key, groove, or shoulder
Y10T 403/7037	. . Externally shouldered or headed rod
Y10T 403/7039	. . Socket
Y10T 403/7041	. . including set screw
Y10T 403/7043	. . Interfitted angle or channel bars
Y10T 403/7045	. . Interdigitated ends
Y10T 403/7047	. . Radially interposed shim or bushing
Y10T 403/7049	. . . Biased by distinct radially acting means
Y10T 403/7051	. . . Wedging or camming
Y10T 403/7052 Engaged by axial movement
Y10T 403/7054 Plural, circumferentially related shims between members
Y10T 403/7056 Threaded actuator
Y10T 403/7058 Split or slotted bushing
Y10T 403/7061	. . . Resilient
Y10T 403/7062	. . Clamped members
Y10T 403/7064	. . . by wedge or cam
Y10T 403/7066 having actuator
Y10T 403/7067 Threaded actuator
Y10T 403/7069 Axially oriented
Y10T 403/7071 Lever actuator
Y10T 403/7073	. . Peripheral enlargement, depression, or slot on one member is joint component
Y10T 403/7075	. . including discrete retainer
Y10T 403/7077	. . . for telescoping members
Y10T 403/7079 Transverse pin
Y10T 403/7081 Multiple retainers
Y10T 403/7083 having means to prevent removal of retainer
Y10T 403/7084 Bolt, rivet, or screw
Y10T 403/7086 Wedge pin
Y10T 403/7088 Sliding pin
Y10T 403/7091 Expansible retainer
Y10T 403/7092	. . . for interfitted side faces
Y10T 403/7094	. . Enlarged head in complementary recess, e.g., dovetail, etc.
Y10T 403/7096	. . Rigid angle
Y10T 403/7098	. . Non-circular rod section is joint component
Y10T 403/71	. Rod side to plate or side
Y10T 403/7105	. . Connected by double clamp
Y10T 403/7111	. . Shackle is integral with or independently attached to proximate side of plate or other side
Y10T 403/7117	. . Flanged or grooved rod
Y10T 403/7123	. . Traversed by connector

Y10T 403/7129	. . Laterally spaced rods
Y10T 403/7135	. . . by separable shim or bushing in connector
Y10T 403/7141	. . . Plural channels in connector
Y10T 403/7147	. . Connected by flexible tie
Y10T 403/7152	. . Lapped rod ends
Y10T 403/7158	. . Diagonal connector
Y10T 403/7164	. . One rod held between bight and other rod extending through aperture in leg of connector
Y10T 403/7171	. . Two rods encompassed by single connector
Y10T 403/7176	. . Resilient clip
Y10T 403/7182	. . Yoke or ring-type connector
Y10T 403/7188	. . . Rod received in open channel
Y10T 403/7194	. . Crossed rods
Y10T 403/72	. Miter joint
Y10T 403/725	. . Connector bridges inner or outer periphery
Y10T 403/73	. Rigid angle
Y10T 403/74	. Particular configuration or material of member
Y10T 403/75	. having a joining piece extending through aligned openings in plural members
Y10T 403/76	. having a cam, wedge, or tapered portion
Y10T 403/77	. Miscellaneous

Former US Class 407 Series

Y10T 407/00	Cutters, for shaping
Y10T 407/10	. including noncutting work modifying means
Y10T 407/11	. including chip breaker, guide or deflector detachable from tool and tool holder
Y10T 407/112	. . Adjustable relative to cutting edge
Y10T 407/114	. . . including adjusting means
Y10T 407/116	. . Attached to or integral with tool clamping jaw
Y10T 407/118	. . Chip breaker
Y10T 407/12	. Freely movable cutting edge
Y10T 407/13	. Yieldable tool
Y10T 407/134	. . Resiliently mounted tool
Y10T 407/137	. . . including yield stress or flexure limit adjusting means
Y10T 407/14	. with means to apply fluid to cutting tool
Y10T 407/15	. Rotary broach
Y10T 407/16	. Rectilinear broach
Y10T 407/1614	. . Hollow tool for surrounding workpiece
Y10T 407/1628	. . including holder having seat for inserted tool
Y10T 407/1642	. . . Annular tool

Y10T 407/1657	. . . including single tooth
Y10T 407/1671	. . Plural tooth groups
Y10T 407/1685	. . including sequentially acting teeth of stepped cutting width
Y10T 407/17	. Gear cutting tool
Y10T 407/1705	. . Face mill gear cutting tool
Y10T 407/171	. . . Adjustable teeth
Y10T 407/1715	. . Hob
Y10T 407/172	. . . Thread cutting
Y10T 407/1725	. . . including holder having seat for inserted tool
Y10T 407/173	. . . for cutting involute gear tooth
Y10T 407/1735	. . Rotary, gear shaving cutting tool
Y10T 407/174	. . Gear generating, revolving shaper cutting tool
Y10T 407/1745	. . Rotary, tooth form cutting tool
Y10T 407/18	. File or rasp
Y10T 407/1805	. . Flexible blade or carrier therefor
Y10T 407/181	. . Tire rasp
Y10T 407/1815	. . Rotary file or round disc
Y10T 407/182	. . Composite, diverse sector, or assembled
Y10T 407/1825	. . Handle or holder, per se
Y10T 407/19	. Rotary cutting tool
Y10T 407/1902	. . Gang
Y10T 407/1904	. . Composite body of diverse material
Y10T 407/1906	. . including holder [i.e., head] having seat for inserted tool
Y10T 407/1908	. . . Face or end mill
Y10T 407/191 Plural simultaneously usable separable tools in common seat or common clamp actuator for plural simultaneously usable tools
Y10T 407/1912 Tool adjustable relative to holder
Y10T 407/1914 Radially
Y10T 407/1916 And axially
Y10T 407/1918 Selectively
Y10T 407/192 with separate means to fasten tool to holder
Y10T 407/1922 Wedge clamp element
Y10T 407/1924 Specified tool shape
Y10T 407/1926	. . . Plural simultaneously usable separable tools in common seat or common clamp actuator for plural simultaneously usable tools
Y10T 407/1928	. . . Tool adjustable relative to holder
Y10T 407/193 Radially
Y10T 407/1932	. . . with means to fasten tool seat to holder
Y10T 407/1934	. . . with separate means to fasten tool to holder
Y10T 407/1936 Apertured tool

Y10T 407/1938 Wedge clamp element
Y10T 407/194 Resilient clamp jaw
Y10T 407/1942	. . . Peripherally spaced tools
Y10T 407/1944 Sectional support
Y10T 407/1946	. . Face or end mill
Y10T 407/1948	. . . with cutting edge entirely across end of tool [e.g., router bit, end mill, etc.]
Y10T 407/195	. . Compound tooth arrangement
Y10T 407/1952	. . Having peripherally spaced teeth
Y10T 407/1954	. . . Axially tapering tool
Y10T 407/1956	. . . Circumferentially staggered
Y10T 407/1958 Plural teeth spaced about a helix
Y10T 407/196	. . . Varying in cutting edge profile
Y10T 407/1962	. . . Specified tooth shape or spacing
Y10T 407/1964 Arcuate cutting edge
Y10T 407/1966 Helical tooth
Y10T 407/20	. Profiled circular tool
Y10T 407/21	. Arc segment tool
Y10T 407/22	. including holder having seat for inserted tool
Y10T 407/2202	. . Plural spaced seats and common holder
Y10T 407/2204	. . . Relatively adjustable seats
Y10T 407/2206	. . . Simultaneously usable
Y10T 407/2208	. . Plural simultaneously usable separable tools in common seat or common clamp actuator for plural simultaneously usable tools
Y10T 407/221	. . . Adjustable tool
Y10T 407/2212	. . with tool ejector
Y10T 407/2214	. . with separate means to adjust tool to and fro relative to holder
Y10T 407/2216	. . . with indicator
Y10T 407/2218	. . . Plural provisions for adjustment
Y10T 407/222	. . . by moving tool seat
Y10T 407/2222	. . Tool adjustable relative to holder
Y10T 407/2224	. . . with indicator
Y10T 407/2226	. . . Plural provisions for adjustment
Y10T 407/2228 Plural interfering seats
Y10T 407/223 including pivotable seat or tool
Y10T 407/2232 with detent
Y10T 407/2234 Pivoted seat
Y10T 407/2236 And pivotable tool
Y10T 407/2238	. . . by adjustable or replaceable stop
Y10T 407/224 Adjustable
Y10T 407/2242 Screw

Y10T 407/2244	. . .	by movement of seat relative to holder
Y10T 407/2246	Pivoted seat
Y10T 407/2248	. . .	Pivoted tool
Y10T 407/225	. . .	Resiliently biased tool clamping jaw
Y10T 407/2252	. . .	Rectilinearly
Y10T 407/2254	including rotatable cam clamp element
Y10T 407/2256	including wedge clamp element
Y10T 407/2258	And guide or detent
Y10T 407/226	including detent
Y10T 407/2262	Tool gripped directly by set screw
Y10T 407/2264	Slidable jaw
Y10T 407/2266	. .	Holder adapted for tools of different shape
Y10T 407/2268	. .	with chip breaker, guide or deflector
Y10T 407/227	. .	with separate means to fasten tool seat to holder
Y10T 407/2272	. .	with separate means to fasten tool to holder
Y10T 407/2274	. . .	Apertured tool
Y10T 407/2276	with means projecting through aperture to force tool laterally against reaction surface
Y10T 407/2278	Tilting clamp element and separate means to tilt same
Y10T 407/228	. . .	Rotatable cam clamp element
Y10T 407/2282	. . .	including tool holding clamp and clamp actuator
Y10T 407/2284	Wedge clamp element
Y10T 407/2286	Resiliently biased clamp jaw
Y10T 407/2288	Integral with holder
Y10T 407/229	Pivoted jaw
Y10T 407/2292	Slidable jaw
Y10T 407/23	. .	including tool having plural alternatively usable cutting edges
Y10T 407/235	. .	with integral chip breaker, guide or deflector
Y10T 407/24	. .	with chip breaker, guide or deflector
Y10T 407/245	. .	comprising concave surface in cutting face of tool
Y10T 407/25	. .	including cut off tool
Y10T 407/26	. .	comprising cutting edge bonded to tool shank
Y10T 407/27	. .	comprising tool of specific chemical composition
Y10T 407/28	. .	Miscellaneous

Former US Class 408 Series

Y10T 408/00	Cutting by use of rotating axially moving tool
Y10T 408/03	. Processes
Y10T 408/04	. . Bit detachable

Y10T 408/05	. with means to weigh or test work or product
Y10T 408/08	. with means to regulate operation by use of templet, tape, card, or other replaceable information supply
Y10T 408/10	. with interlock between machine elements
Y10T 408/13	. with randomly-actuated stopping means
Y10T 408/14	. . Responsive to condition of Tool or tool-drive
Y10T 408/15	. . Responsive to condition of work or product
Y10T 408/16	. with control means energized in response to activator stimulated by condition sensor
Y10T 408/165	. . to control Tool rotation
Y10T 408/17	. . to control infeed
Y10T 408/172	. . . Responsive to Tool
Y10T 408/173	. . . Responsive to work
Y10T 408/175	. . to control relative positioning of Tool and work
Y10T 408/18	. with stopping upon completion of prescribed operation
Y10T 408/20	. . Responsive to condition of work or product
Y10T 408/21	. with signal, indicator, illuminator or optical means
Y10T 408/23	. including means to cause Tool to progressively vibrate toward work
Y10T 408/26	. with means to condition tool
Y10T 408/29	. with means to deForm work temporarily
Y10T 408/31	. Convertible cutting means
Y10T 408/33	. . Utilizing common cutting Tool
Y10T 408/34	. Combined cutting means
Y10T 408/344	. . including Tool operating on rotating work
Y10T 408/348	. . Plural other type cutting means
Y10T 408/35	. . . including plural rotating tools
Y10T 408/352	. . including rotating cutter other than rotating, axially moving Tool
Y10T 408/353	. . . Crystalline cutter
Y10T 408/355	. . . Utilized in cutting work or product to length
Y10T 408/3555 Adapted to cut entire thickness of work at one pass
Y10T 408/356	. . including plunging [single stroke] cutter
Y10T 408/36	. Machine including plural tools
Y10T 408/365	. . Axes of tools moving with work during operation
Y10T 408/367	. . . including means to infeed Tool and means to infeed work or including coaxial tools
Y10T 408/368	. . . Plural work stations
Y10T 408/37	. . Turret of tools
Y10T 408/375	. . Coaxial tools
Y10T 408/378	. . . Coaxial, opposed tools
Y10T 408/3784 with additional, converging Tool
Y10T 408/3788 Plural pairs of coaxial, opposed tools

Y10T 408/3792 with means to sequentially feed tools toward work
Y10T 408/3796 with interconnected means to simultaneously feed tools
Y10T 408/38	. . Plural, simultaneously operational tools
Y10T 408/3806	. . . with plural simultaneously operational work stations
Y10T 408/3809 Successively acting on workpiece
Y10T 408/381 Pivotaly mounted, work-advancing, work-supporting means, pivot-axis parallel to tool-axis
Y10T 408/3811	. . . with provision for adjustment of relationship of axes
Y10T 408/3817	. . . at least one Tool driven by orbiting wrist plate
Y10T 408/3822	. . . at least one Tool including flexible drive connection
Y10T 408/3828	. . . with work-infeed
Y10T 408/3833	. . . with means to advance work relative to Tool
Y10T 408/3839	. . . with presser-foot
Y10T 408/3844	. . . with tool-opposing, work-engaging surface
Y10T 408/385	. . Rotatable about parallel axes
Y10T 408/39	. with radially outer limit of cutting edge moving to define cylinder partially, but not entirely encircled by work
Y10T 408/42	. Axis of Tool moving with work during operation
Y10T 408/44	. with means to apply transient, fluent medium to work or product
Y10T 408/45	. . including Tool with duct
Y10T 408/453	. . . and means to move gaseous fluid by application of vacuum
Y10T 408/455	. . . Conducting channel extending to end of Tool
Y10T 408/458	. . . including nozzle
Y10T 408/46	. . including nozzle
Y10T 408/47	. with work-infeed means
Y10T 408/476	. . Driven by fluid motor
Y10T 408/482	. . Driven by means having sliding engagement therewith
Y10T 408/488	. . Driven by lever or connecting link
Y10T 408/494	. . and gear to drive infeed means
Y10T 408/50	. with product handling or receiving means
Y10T 408/51	. . Ejector
Y10T 408/52	. with work advancing or guiding means
Y10T 408/54	. . Means to intermittently advance work
Y10T 408/545	. . . Rotary, work-supporting means
Y10T 408/55	. with work-engaging structure other than Tool or tool-support
Y10T 408/551	. . with means actuated by work to release Tool from fixed position in Tool support
Y10T 408/552	. . . Adapted to engage work at tool-axis
Y10T 408/553	. . Centering means adapted to be replaced by Tool
Y10T 408/554	. . Magnetic or suction means
Y10T 408/556	. . Tool supporting wheel

Y10T 408/5565	. . .	Wheel-axis parallel to tool-axis
Y10T 408/557	. .	Frictionally engaging sides of opening in work
Y10T 408/558	. . .	Opening coaxial with Tool
Y10T 408/5583	Engaging sides of opening being enlarged by Tool
Y10T 408/5584	Engaging surface axially advanced of tool-action
Y10T 408/5586	Engaging surface subsequent to tool-action on that surface
Y10T 408/5587	Valve fitting
Y10T 408/559	. .	Funnel like work-engaging surface cooperating with protuberance on work
Y10T 408/56	. .	Adapted to "form" recession in work
Y10T 408/5605	. . .	Recession at tool-axis
Y10T 408/561	. .	Having tool-opposing, work-engaging surface
Y10T 408/5612	. . .	Tool having shiftable tool-axis
Y10T 408/5614	. . .	Angularly adjustable surface
Y10T 408/5616	Adjustable about axis that is parallel to tool-axis
Y10T 408/5617	. . .	Laterally adjustable surface
Y10T 408/5619	. . .	Flexible or concatenated member
Y10T 408/5621	. . .	Connected to Tool through opening being enlarged by Tool
Y10T 408/5622	Plural, coaxially opposing, work-engaging means
Y10T 408/5623	. . .	with presser foot
Y10T 408/56238	Encompassed by Tool during cut
Y10T 408/56245	including tool-guide [or bushing]
Y10T 408/56253	Base supported machine
Y10T 408/5626	. . .	with means to move Tool relative to other work-engaging structure along tool-axis
Y10T 408/5627	Having sliding engagement therewith
Y10T 408/56275	Screw coaxial with Tool
Y10T 408/5628	. . .	Tool having screw-thread engaging frame to cause infeed
Y10T 408/563	. .	Work-gripping clamp
Y10T 408/5633	. . .	Adapted to coaxially grip round work
Y10T 408/56337	Oppositely moving lateral clamps
Y10T 408/5634	Three or more moving clamps
Y10T 408/56343	Base supported clamp
Y10T 408/5635	. . .	Oppositely moving lateral clamps
Y10T 408/5638	. . .	Adjustable relative to tool-axis
Y10T 408/564	. .	Movable relative to Tool along tool-axis
Y10T 408/5647	. . .	including means to move Tool
Y10T 408/5653	. . .	with means to bias Tool away from work
Y10T 408/566	. .	Axially fixed to Tool
Y10T 408/5665	. . .	Work-engaging surface parallel to tool-axis
Y10T 408/567	. .	Adjustable, tool-guiding jig

Y10T 408/568	. . . Guide bushing
Y10T 408/569	. . Bushing
Y10T 408/57	. Tool-support with means to receive tool-position indicator
Y10T 408/60	. Plural tool-assemblages
Y10T 408/62	. . Coaxial
Y10T 408/625	. . . Spring biased
Y10T 408/63	. Tool or tool-support with torque-applying ratchet
Y10T 408/637	. . with thrust applying means
Y10T 408/639	. . . Reversible ratchet
Y10T 408/641	. . . Double-acting ratchet
Y10T 408/643	. . Reversible ratchet
Y10T 408/65	. Means to drive tool
Y10T 408/655	. . with specific Tool structure
Y10T 408/66	. . Friction gearing
Y10T 408/665	. . Universal or flexible drive connection to rotate Tool
Y10T 408/67	. . Belt and pulley
Y10T 408/675	. . including means to move Tool along tool-axis
Y10T 408/6757	. . . Fluid means
Y10T 408/6764	. . . Laterally adjustable Tool
Y10T 408/6771	. . . with clutch means
Y10T 408/6774 including plural speed drive
Y10T 408/6776 Actuated by Tool movement
Y10T 408/6779	. . . Rack and pinion
Y10T 408/6786	. . . Manually moved lever
Y10T 408/6793	. . . Screw coaxial with Tool
Y10T 408/68	. Tool or tool-support with thrust-applying machine-engaging screw
Y10T 408/70	. Tool or tool-support with torque-applying clutch
Y10T 408/72	. . Friction clutch
Y10T 408/73	. Tool or tool-support with torque-applying spline
Y10T 408/75	. . Relative motion of splined shaft and tool-support causing release of Tool from operating position
Y10T 408/76	. Tool-carrier with vibration-damping means
Y10T 408/78	. Tool of specific diverse material
Y10T 408/81	. Tool having crystalline cutting edge
Y10T 408/83	. Tool-support with means to move Tool relative to tool-support
Y10T 408/85	. . to move radially
Y10T 408/852	. . . with Tool releasing trigger
Y10T 408/853 and separate Tool setting means
Y10T 408/854	. . . to move eccentrically mounted Tool
Y10T 408/855 Tool-support including plural, adjustable sections

Y10T 408/856	. . .	Moving means including pinion engaging rack-like surface of Tool
Y10T 408/858	. . .	Moving means including wedge, screw or cam
Y10T 408/8583	with resiliently urged Tool
Y10T 408/85837	with spring retainer
Y10T 408/85843	Resilient Tool or tool-support
Y10T 408/8585	including oppositely moving, diverging tools
Y10T 408/8588	Axially slidable moving-means
Y10T 408/85884	Tool pivotally mounted on support
Y10T 408/85888	Having axially spaced shoulders
Y10T 408/85892	Screw driven wedge or cam
Y10T 408/85893	Screw with axis radially spaced from tool-axis
Y10T 408/85894	Annular wedge-collar
Y10T 408/858945	Axially spaced tool-retaining collars
Y10T 408/858946	with travelling wedge
Y10T 408/858948	Tool having axially facing, collar-receiving groove
Y10T 408/858949	including two-piece collar
Y10T 408/85895	Traveling wedge
Y10T 408/858953	Interfitting, tool-retaining wedge
Y10T 408/858955	including separable interfitting element
Y10T 408/858957	Having externally threaded shank connected to tool-support
Y10T 408/85896	Annular wedge-collar
Y10T 408/859	Rotary cam
Y10T 408/8591	Scroll plate
Y10T 408/85913	Volute scroll
Y10T 408/85915	with means to rotate scroll
Y10T 408/85918	with adjustable means to limit scroll movement
Y10T 408/8592	Coaxial with tool-axis
Y10T 408/8593	Wedge moving perpendicular to tool-axis
Y10T 408/8595	Pivotable tool-support
Y10T 408/8598	Screw extending perpendicular to tool-axis
Y10T 408/85985	Plural tools moved by diametrically opposed screws
Y10T 408/85988	Screws mounted on common shaft
Y10T 408/8599	Tool having pitch-stabilizing ridge
Y10T 408/85995	with tool-holding clamp and clamp actuator
Y10T 408/86	Tool-support with means to permit positioning of the Tool relative to support
Y10T 408/865	Pivotable Tool
Y10T 408/868	with multiple cutting positions
Y10T 408/87	Tool having stepped cutting edges
Y10T 408/8713	including means to permit both radial and axial positioning of edge
Y10T 408/8725	including means to permit relative axial positioning of edges

Y10T 408/8729 with work-engaging structure other than cutting edge
Y10T 408/8734 including central Tool axially movable relative to support
Y10T 408/8738	. . . including inverse cutting edge
Y10T 408/875	. . including means to "form" depression in work
Y10T 408/88	. . including central-lead
Y10T 408/885	. . including tool-holding clamp and clamp actuator
Y10T 408/888	. . . Movable along tool-axis
Y10T 408/89	. Tool or Tool with support
Y10T 408/892	. . with work-engaging structure detachable from cutting edge
Y10T 408/8923	. . . Removable central lead
Y10T 408/8925	. . . Depth-limiting member
Y10T 408/8928	. . . Adjustable
Y10T 408/893	. . Hollow milling Tool
Y10T 408/895	. . Having axial, core-receiving central portion
Y10T 408/8953	. . . with lateral outlet
Y10T 408/8957	. . . and having stepped cutting edges
Y10T 408/896	. . Having product-receiving chamber
Y10T 408/8967	. . . and central lead-screw
Y10T 408/8973	. . . and central lead
Y10T 408/898	. . Helical ribbon Tool
Y10T 408/899	. . Having inversely angled cutting edge
Y10T 408/90	. . . and axially extending peripheral cutting spur
Y10T 408/901	. . Having axially extending peripheral cutting spur
Y10T 408/902	. . Having central lead-screw
Y10T 408/904	. . with pitch-stabilizing ridge
Y10T 408/9042	. . . and radially spaced cutting edge
Y10T 408/9044	. . . including cutting teeth of different width
Y10T 408/9045 and different root circles
Y10T 408/9046	. . . including tapered section
Y10T 408/90467 and relieved cutting edge
Y10T 408/90473 including work-embracing cutting edges
Y10T 408/9048	. . . Extending outwardly from tool-axis
Y10T 408/905	. . Having stepped cutting edges
Y10T 408/906	. . . Axially spaced
Y10T 408/9065 with central lead
Y10T 408/907	. . including detailed shank
Y10T 408/909	. . Having peripherally spaced cutting edges
Y10T 408/9093	. . . Each formed by a pair of axially facing facets
Y10T 408/9095	. . . with axially extending relief channel
Y10T 408/9097 Spiral channel

Y10T 408/9098	. . . with means to retain Tool to support
Y10T 408/90987 Wedge means
Y10T 408/90993 Screw driven means
Y10T 408/91	. Machine frame
Y10T 408/92	. . with counterweight mechanism
Y10T 408/93	. . including pivotally mounted tool-carrier
Y10T 408/935	. . . including laterally movable tool-carrier
Y10T 408/94	. Tool-support
Y10T 408/95	. . with tool-retaining means
Y10T 408/953	. . . Clamping jaws
Y10T 408/957	. . . Tool adapter
Y10T 408/96	. Miscellaneous
Y10T 408/97	. . Drill bushings
Y10T 408/98	. . Drill guide
Y10T 408/99	. . Adjustable stop

Former US Class 409 Series

Y10T 409/00	Gear cutting, milling, or planing
Y10T 409/10	. Gear cutting
Y10T 409/100159	. . with regulation of operation by use of templet, card, or other replaceable information supply
Y10T 409/100318	. . . including follower for templet
Y10T 409/100477	. . and burnishing simultaneously
Y10T 409/100636	. . with compensation for backlash in drive means
Y10T 409/100795	. . with work or product advancing
Y10T 409/100954	. . . Utilizing transfer arm
Y10T 409/101113	. . Gear chamfering or deburring
Y10T 409/101272	. . . Using relatively reciprocating or oscillating cutter
Y10T 409/101431	. . Gear tooth shape generating
Y10T 409/10159	. . . Hobbing
Y10T 409/101749 Process
Y10T 409/101908 Generating tooth for bevel gear
Y10T 409/102067 including means to shift hob between cutting passes
Y10T 409/102226 with control means energized in response to activator stimulated by condition sensor
Y10T 409/102385 Plural hobs
Y10T 409/102544 including infeed means
Y10T 409/102703 to infeed along axis of work rotation
Y10T 409/102862 Infeed of cutter
Y10T 409/103021 and infeed radially of axis of work rotation

Y10T 409/10318	Vertically
Y10T 409/103339	to infeed radially of axis of work rotation
Y10T 409/103498	Infeed of cutter
Y10T 409/103657	and infeed tangentially of work axis
Y10T 409/103816	Milling with radial faced tool
Y10T 409/103975	Process
Y10T 409/104134	Adapted to cut bevel gear
Y10T 409/104293	with means to continuously rotate work and means to co-form all teeth of gear
Y10T 409/104452	Bevel gear having nonparallel opposing tooth flanks
Y10T 409/104611	including rotary cutter cradle
Y10T 409/10477	by relative axial movement between synchronously indexing or rotating work and cutter
Y10T 409/104929	Crowning
Y10T 409/105088	Displacing cutter axially relative to work [e.g., gear shaving, etc.]
Y10T 409/105247	Using gear shaper-cutter
Y10T 409/105406	Plural distinct cutting edges
Y10T 409/105565	Cutting rotating work, the axis of which lies in a plane intersecting the cutter axis
Y10T 409/105724	Gear shaving
Y10T 409/105883	Using rotary cutter
Y10T 409/106042	having axially directed cutting edge
Y10T 409/106201	Plural rotary cutters
Y10T 409/10636	On reciprocating carriage
Y10T 409/106519	Using reciprocating or oscillating cutter
Y10T 409/106678	Bevel gear cutting
Y10T 409/106837	Dual cutters
Y10T 409/106996	Double acting cutter
Y10T 409/107155	Rectilinearly reciprocating cutter
Y10T 409/107314	Cutter comprising a rack
Y10T 409/107473	Making a noncircular gear, worm, rotor, or a planar-faced gear
Y10T 409/107632	Gear shaving
Y10T 409/107791	Using rotary cutter
Y10T 409/10795	Process
Y10T 409/108109	End mill
Y10T 409/108268	Radially faced
Y10T 409/108427	Using plural, selectively usable tools
Y10T 409/108586	Plural rotary cutters
Y10T 409/108745	Cutting action along work axis
Y10T 409/108904	Cutting action intersecting work axis
Y10T 409/109063	Using reciprocating or oscillating cutter

Y10T 409/109222	. . .	Broach
Y10T 409/109381	. . .	including circumferentially disposed cutting edges
Y10T 409/10954	. .	Work dividing or checking of work position or division
Y10T 409/109699	. .	with work clamping
Y10T 409/20	.	with refurbishing of cutter
Y10T 409/30	.	Milling
Y10T 409/300056	. .	Thread or helix generating
Y10T 409/300112	. . .	Process
Y10T 409/300168	. . .	with means to regulate operation by use of templet, card, or other replaceable information supply
Y10T 409/300224	Complete cycle
Y10T 409/30028	to regulate cutting depth [e.g., relief, taper, etc.]
Y10T 409/300336	to regulate rate of motion [e.g., stopping, etc.]
Y10T 409/300392	. . .	with nonthread or nonhelix generating, milling cutter
Y10T 409/300448	. . .	with means to advance work or product
Y10T 409/300504	. . .	Plural cutters or work holders
Y10T 409/30056	. . .	with planetary cutter
Y10T 409/300616	. . .	Work means to move work axially and means to interrelate work movement with cutter rotation
Y10T 409/300672	. . .	with means to rotate work and means to interrelatedly infeed the work relative to the cutter
Y10T 409/300728	Means to infeed the cutter
Y10T 409/300784	. . .	with means to circumferentially adjust the position of the cutter with respect to the work
Y10T 409/30084	. .	with regulation of operation by templet, card, or other replaceable information supply
Y10T 409/300896	. . .	with sensing of numerical information and regulation without mechanical connection between sensing means and regulated means [i.e., numerical control]
Y10T 409/300952	. . .	to cut lock key
Y10T 409/301008	Using templet other than a key
Y10T 409/301064	Complete cycle
Y10T 409/30112	. . .	Process
Y10T 409/301176	. . .	Reproducing means
Y10T 409/301232	including pantograph cutter-carrier
Y10T 409/301288	and means to move work at work station
Y10T 409/301344	About work axis
Y10T 409/3014	Pivotaly supported for vertical movement
Y10T 409/301456	and means to counterbalance carrier
Y10T 409/301512	including plural cutters
Y10T 409/301568	by use of pivotaly supported tracer
Y10T 409/301624	Duplicating means

Y10T 409/30168	with means for operation without manual intervention
Y10T 409/301736	to make a double curvature foil
Y10T 409/301792	including means to sense optical or magnetic image
Y10T 409/301848	with means to support templet above or under work
Y10T 409/301904	including tracer adapted to trigger electrical energy
Y10T 409/30196	to actuate electrically driven work or tool moving means
Y10T 409/302016	to actuate fluid driven work or tool moving means
Y10T 409/302072	including tracer adapted to trigger fluid energy
Y10T 409/302128	to actuate fluid driven work or tool moving means
Y10T 409/302184	including cutter and tracer fixed to move laterally together
Y10T 409/30224	and provision for circumferential relative movement of cutter and work
Y10T 409/302296	including plural cutters
Y10T 409/302352	including plural cutters
Y10T 409/302408	including cross-slide tool carrier
Y10T 409/302464	including plural cutters
Y10T 409/30252	including cross-slide tool carrier
Y10T 409/302576	with means to support templet above or under work
Y10T 409/302632	with provision for circumferential relative movement of cutter and work
Y10T 409/302688	with provision for circumferential relative movement of cutter and work
Y10T 409/302744	and means for operation without manual intervention
Y10T 409/3028	including tracer adapted to trigger electrical or fluid energy
Y10T 409/302856	For using planar templet in cutting profile [e.g., contour map from planar map, etc.]
Y10T 409/302912	including means for operation without manual intervention
Y10T 409/302968	including means for operation without manual intervention
Y10T 409/303024	including simultaneously usable plural tracers or including tracer adapted to simultaneously use plural templates
Y10T 409/30308	to make a double curvature foil
Y10T 409/303136	to make a double curvature foil
Y10T 409/303192	including cutter and tracer fixed to move together
Y10T 409/303248	with provision for circumferential relative movement of cutter and work
Y10T 409/303304	and provision for circumferential relative movement of cutter and work
Y10T 409/30336	including cutter and tracer fixed to move together
Y10T 409/303416	Templet, tracer, or cutter
Y10T 409/303472	Tracer
Y10T 409/303528	Adapted to trigger electrical energy
Y10T 409/303584	Photocell
Y10T 409/30364	Adapted to trigger fluid energy
Y10T 409/303696	Templet
Y10T 409/303752	Process

Y10T 409/303808	. . .	including infeeding
Y10T 409/303864	. .	with means to weigh or test work or product
Y10T 409/30392	. .	with means to protect operative or machine [e.g., guard, safety device, etc.]
Y10T 409/303976	. .	with means to control temperature or lubricate
Y10T 409/304032	. . .	Cutter or work
Y10T 409/304088	. .	with means to remove chip
Y10T 409/304144	. .	Means to trim edge
Y10T 409/3042	. .	Means to remove scale or raised surface imperfection
Y10T 409/304256	. . .	Means to remove flash or burr
Y10T 409/304312	. .	with means to dampen vibration
Y10T 409/304368	. .	Means to mill epitrochoidal shape
Y10T 409/304424	. .	Means for internal milling
Y10T 409/30448	. .	with detachable or auxiliary cutter support to convert cutting action
Y10T 409/304536	. .	including means to infeed work to cutter
Y10T 409/304592	. . .	with compensation for backlash in drive means
Y10T 409/304648	. . .	with control means energized in response to activator stimulated by condition sensor
Y10T 409/304704	In response to cutter or cutter carriage
Y10T 409/30476	In response to work or work carriage
Y10T 409/304816	to control rate of infeed or return
Y10T 409/304872	to control limit of infeed
Y10T 409/304928	Adapted to hydraulically or pneumatically stimulate control
Y10T 409/304984	Adapted to electrically stimulate control
Y10T 409/30504	to control rate of infeed or return
Y10T 409/305096	to effect stopping of infeed
Y10T 409/305152	. . .	with means to change rate of infeed
Y10T 409/305208	. . .	Means to mill indeterminate length work
Y10T 409/305264	. . .	Multiple work stations
Y10T 409/30532	. . .	with means to advance work or product
Y10T 409/305376	Vertically
Y10T 409/305432	Endless or orbital work or product advancing means
Y10T 409/305488	. . .	to reciprocate or oscillate work
Y10T 409/305544	. . .	with work holder
Y10T 409/3056	and means to selectively position work
Y10T 409/305656	including means to support work for rotation during operation
Y10T 409/305712	and including means to infeed cutter toward work axis
Y10T 409/305768	with linear movement of work
Y10T 409/305824	with angular movement of work
Y10T 409/30588	. . .	including friction gearing drive
Y10T 409/305936	. . .	including fluid drive

Y10T 409/305992	. .	with means to effect stopping upon completion of operation
Y10T 409/306048	. .	with means to advance work or product
Y10T 409/306104	. . .	Endless or orbital work or product advancing means
Y10T 409/30616	. .	with means to precisely reposition work
Y10T 409/306216	. .	Randomly manipulated, work supported, or work following device
Y10T 409/306272	. . .	For machining commutator
Y10T 409/306328	. . .	For cutting longitudinal groove in shaft [e.g., keyway, etc.]
Y10T 409/306384	. . .	with work supported guide means
Y10T 409/30644	to guide tool to move in arcuate path
Y10T 409/306496	. . .	with work follower
Y10T 409/306552	. . .	Randomly manipulated
Y10T 409/306608	End mill [e.g., router, etc.]
Y10T 409/306664	. .	including means to infeed rotary cutter toward work
Y10T 409/30672	. . .	with means to limit penetration into work
Y10T 409/306776	. . .	Axially
Y10T 409/306832	with infeed control means energized in response to activator stimulated by condition sensor
Y10T 409/306888	In response to cutter condition
Y10T 409/306944	In response to work condition
Y10T 409/307	with work holder
Y10T 409/307056	and laterally
Y10T 409/307112	Simultaneously
Y10T 409/307168	Plural cutters
Y10T 409/307224	. . .	with infeed control means energized in response to activator stimulated by condition sensor
Y10T 409/30728	In response to cutter condition
Y10T 409/307336	In response to work condition
Y10T 409/307392	. . .	with means to change rate of infeed
Y10T 409/307448	. . .	with work holder
Y10T 409/307504	Indexable
Y10T 409/30756	. . .	Machining arcuate surface
Y10T 409/307616	with means to move cutter eccentrically
Y10T 409/307672	. . .	Angularly adjustable cutter head
Y10T 409/307728	. . .	including gantry-type cutter-carrier
Y10T 409/307784	. . .	Plural cutters
Y10T 409/30784	. .	including means to adjustably position cutter
Y10T 409/307896	. . .	with work holder or guide
Y10T 409/307952	. . .	Linear adjustment
Y10T 409/308008	with control for adjustment means responsive to activator stimulated by condition sensor
Y10T 409/308064	Responsive to position of cutter

Y10T 409/30812	and means to clamp cutter support in adjusted position
Y10T 409/308176	with position indicator or limit means
Y10T 409/308232	and angular adjustment
Y10T 409/308288	including gantry-type cutter-carrier
Y10T 409/308344	Plural cutters
Y10T 409/3084	with position indicator or limit means
Y10T 409/308456	with right angle cutter drive
Y10T 409/308512	Compound angular adjustment
Y10T 409/308568	Plural cutters
Y10T 409/308624	with limit means to aid in positioning of cutter bit or work [e.g., gauge, stop, etc.]
Y10T 409/30868	Work support
Y10T 409/308736	with position indicator or stop
Y10T 409/308792	Indexable
Y10T 409/308848	including dividing head
Y10T 409/308904	Multiple row dividing head
Y10T 409/30896	with angular adjustment
Y10T 409/309016	with work holder or guide
Y10T 409/309072	including cutter limited to rotary motion
Y10T 409/309128	with means to adjust work support vertically
Y10T 409/309184	including cutter limited to rotary motion
Y10T 409/30924	Cutter turning about vertical axis
Y10T 409/309296	Detachable or repositionable tool head
Y10T 409/309352	Cutter spindle or spindle support
Y10T 409/309408	with cutter holder
Y10T 409/309464	and draw bar
Y10T 409/30952	with cutter holder
Y10T 409/309576	Machine frame
Y10T 409/309632	Overarm harness structure
Y10T 409/309688	including counterbalancing means
Y10T 409/309744	including means to compensate for deformation
Y10T 409/3098	Deflection of cutter spindle
Y10T 409/309856	Convertible from lathe
Y10T 409/309912	including relatively movable components and means to relatively immobilize these components
Y10T 409/309968	Tailstock
Y10T 409/40	Broaching
Y10T 409/400175	Process
Y10T 409/40035	with control means energized in response to activator stimulated by condition sensor
Y10T 409/400525	Responsive to condition of work or product

Y10T 409/4007	. .	with means to distribute cutter infeed force
Y10T 409/400875	. .	with means to select cutter or to select or modify cutter drive
Y10T 409/40105	. .	with means to clean, lubricate, or modify temperature of work or cutter
Y10T 409/401225	. .	with product handling means
Y10T 409/4014	. . .	Between plural broaching stations
Y10T 409/401575	. . .	Means to eject broached product
Y10T 409/40175	. . .	Chip removal means
Y10T 409/401925	. .	with means to protect operative or machine [e.g., guard, safety device, etc.]
Y10T 409/4021	. . .	with safety means for overload or safety interlock
Y10T 409/402275	. .	with work immobilizer and means to activate work immobilizer interrelated with cutter infeed, work infeed, or work advance
Y10T 409/40245	. .	with work infeed or advancing means and means to clamp the work thereto, which clamping means is interrelated with work or cutter infeed
Y10T 409/402625	. .	Means to remove flash or burr
Y10T 409/4028	. .	Means for cutting groove
Y10T 409/402975	. . .	Arcuate groove in cylindrical surface
Y10T 409/40315	Rifling
Y10T 409/403325	. .	Orbital carrier for cutter
Y10T 409/4035	. .	Orbital carrier for work
Y10T 409/403675	. .	with means to cyclically manipulate cutter or cutter support
Y10T 409/40385	. . .	to reorient, introduce, or remove cutter
Y10T 409/404025	. . .	Cutter released to interim support at termination of cutting stroke
Y10T 409/4042	. . .	to remove and return cutter to cutter support
Y10T 409/404375	. .	with plural cutters
Y10T 409/40455	. .	with means to advance, infeed, or manipulate work
Y10T 409/404725	. . .	Interrelated with cutter infeed
Y10T 409/4049	including means supporting work and additional means opposing infeed force
Y10T 409/405075	including work indexing means for sequential cutting of different surfaces of a single workpiece
Y10T 409/40525	including work indexing means for sequential cutting of surfaces of different workpieces
Y10T 409/405425	with means to retract work from path of tool's idle return stroke
Y10T 409/4056	. . .	to infeed work past cutter
Y10T 409/405775	. .	with means to hold work during cutting
Y10T 409/40595	. . .	including work clamping means
Y10T 409/406125	. . .	with means to adjust or facilitate adjustment of work or work holder
Y10T 409/4063	. . .	with means on work or work holder to guide cutter during infeed
Y10T 409/406475	. .	Cutter infeed means
Y10T 409/40665	. . .	Imparting rectilinear motion to cutter
Y10T 409/406825	and rotary motion to cutter

Y10T 409/407	Fluid powered means
Y10T 409/407175	Rack means
Y10T 409/40735	Screw means
Y10T 409/407525	. .	Machine frame
Y10T 409/4077	. .	Cutter support or guide
Y10T 409/50	. .	Planing
Y10T 409/500164	. .	with regulation of operation by templet, card, or other replaceable information supply
Y10T 409/500328	. . .	including use of tracer adapted to trigger electrical or fluid energy
Y10T 409/500492	including provision for circumferential relative movement of cutter and work
Y10T 409/500656	. . .	including provision for circumferential relative movement of cutter and work
Y10T 409/50082	. .	Process
Y10T 409/500984	. .	with means to lubricate
Y10T 409/501148	. .	with product handling means
Y10T 409/501312	. .	Randomly manipulated, work supported, or work following device
Y10T 409/501476	. .	Means to remove flash or burr
Y10T 409/50164	. . .	Elongated work
Y10T 409/501804	Flash or burr inside hollow work
Y10T 409/501968	Transverse burr
Y10T 409/502132	. . .	Flat work
Y10T 409/502296	. .	of commutator
Y10T 409/50246	. .	Means for trimming edge [e.g., chamfering, scarfing, etc.]
Y10T 409/502624	. .	Means for cutting groove
Y10T 409/502788	. . .	Arcuate groove
Y10T 409/502952	For rifling
Y10T 409/503116	. . .	Inside hollow work
Y10T 409/50328	. .	Means for shaving by blade spanning work surface
Y10T 409/503444	. . .	Concave work surface [e.g., bearing, stereotype printing plate, etc.]
Y10T 409/503608	. . .	Circumferential surface
Y10T 409/503772	. . .	including rack driven infeed means
Y10T 409/503936	. . .	including roller infeed means
Y10T 409/5041	. .	Means for cutting arcuate surface
Y10T 409/504264	. . .	Cycloidal surface
Y10T 409/504428	. . .	with work infeed and means to arcuately reposition the cutter
Y10T 409/504592	. . .	with work infeed and means to arcuately reposition the work
Y10T 409/504756	. .	with means to relatively infeed cutter and work
Y10T 409/50492	. . .	and means to rotate work and cutter at same rate about converging axes
Y10T 409/505084	. . .	with plural sequentially acting cutters or with double acting cutter
Y10T 409/505248	. . .	and means to vary rate of infeed
Y10T 409/505412	. . .	Reciprocating work infeed means

Y10T 409/505576	with fluid-driven bed
Y10T 409/50574	with rack-driven bed
Y10T 409/505904	with screw-driven bed
Y10T 409/506068	and means to permit repositioning of cutter laterally
Y10T 409/506232	. . .	Reciprocating cutter infeed means
Y10T 409/506396	Reciprocating cutter horizontally
Y10T 409/50656	with work support and lead screw to reposition work support
Y10T 409/506724	with fluid-powered means to drive cutter
Y10T 409/506888	with pivoting link to drive cutter
Y10T 409/507052	Link driven by crank
Y10T 409/507216	with rack to drive cutter
Y10T 409/50738	with screw to drive cutter
Y10T 409/507544	with link or cam to drive cutter
Y10T 409/507708	with rack to drive cutter
Y10T 409/507872	. . .	including means causing return stroke
Y10T 409/508036	. .	Machine frame
Y10T 409/5082	. . .	Means to permit repositioning of cutter
Y10T 409/508364	Laterally
Y10T 409/508528	Plural independently positioned cutters
Y10T 409/508692	including clutch
Y10T 409/508856	including repositioning means and means to effect stopping thereof
Y10T 409/50902	. . .	including relatively movable components and means to relatively immobilize these components
Y10T 409/509184	. . .	Work table
Y10T 409/509348	. .	Tool head
Y10T 409/509512	. . .	with selectively usable cutting edges
Y10T 409/509676	. . .	with means to permit repositioning of cutting for idle return stroke
Y10T 409/50984	comprising pivotable cutter or cutter support

Former US Class 428 Series

Y10T 428/00	Stock material or miscellaneous articles
Y10T 428/10	. Liquid crystal optical display having layer of specified composition
Y10T 428/1005	. . Alignment layer of specified composition
Y10T 428/1009	. . . Alignment layer is inorganic
Y10T 428/1014	. . . Silicon compound [i.e., organosilicon]
Y10T 428/1018	. . . Polyamide
Y10T 428/1023	. . . Polyimide
Y10T 428/1027 Polyimidfluoride
Y10T 428/1032 Polyimidmetalo

Y10T 428/1036	. . with viewing layer of specified composition
Y10T 428/1041	. . . Polarizer or dye containing viewing layer
Y10T 428/1045	. . . Silicon compound [e.g., glass, organosilicon, etc.]
Y10T 428/105	. . . Ester [e.g., polycarbonate, polyacrylate, etc.]
Y10T 428/1055	. . with charge transferring layer of specified composition
Y10T 428/1059	. . with bonding or intermediate layer of specified composition [e.g., sealant, space, etc.]
Y10T 428/1064	. . . Inorganic layer
Y10T 428/1068	. . . Silicon compound [i.e., organosilicon]
Y10T 428/1073	. . . Epoxy
Y10T 428/1077	. . . Ester
Y10T 428/1082	. . . Unsaturated aliphatic polymer [e.g., vinyl, etc.]
Y10T 428/1086	. . with substrate layer of specified composition
Y10T 428/1091	. . . Releasable substrate layer to expose adhesive
Y10T 428/1095	. . . Inorganic substrate layer [e.g., ceramic, metallic, glass, etc.]
Y10T 428/11	. Magnetic recording head
Y10T 428/1107	. . Magnetoresistive
Y10T 428/1114	. . . having tunnel junction effect
Y10T 428/1121	. . . Multilayer
Y10T 428/1129 Super lattice [e.g., giant magneto resistance [GMR] or colossal magneto resistance [CMR], etc.]
Y10T 428/1136	. . . Single film
Y10T 428/1143	. . . with defined structural feature
Y10T 428/115	. . Magnetic layer composition
Y10T 428/1157	. . Substrate composition
Y10T 428/1164	. . with protective film
Y10T 428/1171	. . with defined laminate structural detail
Y10T 428/1179	. . . Head with slider structure
Y10T 428/1186	. . . with head pole component
Y10T 428/1193	. . with interlaminar component [e.g., adhesion layer, etc.]
Y10T 428/12	. All metal or with adjacent metals
Y10T 428/12007	. . Component of composite having metal continuous phase interengaged with nonmetal continuous phase
Y10T 428/12014	. . having metal particles
Y10T 428/12021	. . . having composition or density gradient or differential porosity
Y10T 428/12028	. . . Composite; i.e., plural, adjacent, spatially distinct metal components [e.g., layers, etc.]
Y10T 428/12035 Fiber, asbestos, or cellulose in or next to particulate component
Y10T 428/12042 Porous component
Y10T 428/12049 Nonmetal component
Y10T 428/12056 Entirely inorganic

Y10T 428/12063	Nonparticulate metal component
Y10T 428/12069	Plural nonparticulate metal components
Y10T 428/12076	Next to each other
Y10T 428/12083	Nonmetal in particulate component
Y10T 428/1209	Plural particulate metal components
Y10T 428/12097	Nonparticulate component encloses particles
Y10T 428/12104	Particles discontinuous
Y10T 428/12111	Separated by nonmetal matrix or binder [e.g., welding electrode, etc.]
Y10T 428/12118	Nonparticulate component has Ni-, Cu-, or Zn-base
Y10T 428/12125	Nonparticulate component has Fe-base
Y10T 428/12132	Next to Fe-containing particles
Y10T 428/12139	Nonmetal particles in particulate component
Y10T 428/12146	Nonmetal particles in a component
Y10T 428/12153	Interconnected void structure [e.g., permeable, etc.]
Y10T 428/1216	Continuous interengaged phases of plural metals, or oriented fiber containing
Y10T 428/12167	Nonmetal containing
Y10T 428/12174	Mo or W containing
Y10T 428/12181	Composite powder [e.g., coated, etc.]
Y10T 428/12188	having marginal feature for indexing or weakened portion for severing
Y10T 428/12194	For severing perpendicular to longitudinal dimension
Y10T 428/12201	Width or thickness variation or marginal cuts repeating longitudinally
Y10T 428/12208	Variation in both width and thickness
Y10T 428/12215	Marginal slots [i.e., deeper than wide]
Y10T 428/12222	Shaped configuration for melting [e.g., package, etc.]
Y10T 428/12229	Intermediate article [e.g., blank, etc.]
Y10T 428/12236	Panel having nonrectangular perimeter
Y10T 428/12243	Disk
Y10T 428/1225	Symmetrical
Y10T 428/12257	Only one plane of symmetry
Y10T 428/12264	having outward flange, gripping means or interlocking feature
Y10T 428/12271	having discrete fastener, marginal fastening, taper, or end structure
Y10T 428/12278	Same structure at both ends of plural taper
Y10T 428/12285	Single taper [e.g., ingot, etc.]
Y10T 428/12292	Workpiece with longitudinal passageway or stopweld material [e.g., for tubular stock, etc.]
Y10T 428/12299	Workpiece mimicking finished stock having nonrectangular or noncircular cross section
Y10T 428/12306	Workpiece of parallel, nonfastened components [e.g., fagot, pile, etc.]
Y10T 428/12313	Arranged to avoid lateral displacement
Y10T 428/12319	Composite

- Y10T 428/12326 . . with provision for limited relative movement between components
- Y10T 428/12333 . . Helical or with helical component
- Y10T 428/1234 . . Honeycomb, or with grain orientation or elongated elements in defined angular relationship in respective components [e.g., parallel, inter- secting, etc.]
- Y10T 428/12347 . . Plural layers discontinuously bonded [e.g., spot-weld, mechanical fastener, etc.]
- Y10T 428/12354 . . Nonplanar, uniform-thickness material having symmetrical channel shape or reverse fold [e.g., making acute angle, etc.]
- Y10T 428/12361 . . having aperture or cut
- Y10T 428/12368 . . . Struck-out portion type
- Y10T 428/12375 . . having member which crosses the plane of another member [e.g., T or X cross section, etc.]
- Y10T 428/12382 . . Defined configuration of both thickness and nonthickness surface or angle therebetween [e.g., rounded corners, etc.]
- Y10T 428/12389 . . having variation in thickness
- Y10T 428/12396 . . . Discontinuous surface component
- Y10T 428/12403 . . . Longitudinally smooth and symmetrical
- Y10T 428/1241 . . Nonplanar uniform thickness or nonlinear uniform diameter [e.g., L-shape]
- Y10T 428/12417 . . . Intersecting corrugating or dimples not in a single line [e.g., waffle form, etc.]
- Y10T 428/12424 . . Mass of only fibers
- Y10T 428/12431 . . Foil or filament smaller than 6 mils
- Y10T 428/12438 . . . Composite
- Y10T 428/12444 . . Embodying fibers interengaged or between layers [e.g., paper, etc.]
- Y10T 428/12451 . . Macroscopically anomalous interface between layers
- Y10T 428/12458 . . having composition, density, or hardness gradient
- Y10T 428/12465 . . having magnetic properties, or preformed fiber orientation coordinate with shape
- Y10T 428/12472 . . Microscopic interfacial wave or roughness
- Y10T 428/12479 . . Porous [e.g., foamed, spongy, cracked, etc.]
- Y10T 428/12486 . . Laterally noncoextensive components [e.g., embedded, etc.]
- Y10T 428/12493 . . Composite; i.e., plural, adjacent, spatially distinct metal components [e.g., layers, joint, etc.]
- Y10T 428/125 . . . Deflectable by temperature change [e.g., thermostat element]
- Y10T 428/12507 More than two components
- Y10T 428/12514 One component Cu-based
- Y10T 428/12521 Both components Fe-based with more than 10% Ni
- Y10T 428/12528 Semiconductor component
- Y10T 428/12535 with additional, spatially distinct nonmetal component
- Y10T 428/12542 More than one such component
- Y10T 428/12549 Adjacent to each other
- Y10T 428/12556 Organic component
- Y10T 428/12562 Elastomer
- Y10T 428/12569 Synthetic resin

Y10T 428/12576	Boride, carbide or nitride component
Y10T 428/12583	Component contains compound of adjacent metal
Y10T 428/1259	Oxide
Y10T 428/12597	Noncrystalline silica or noncrystalline plural-oxide component [e.g., glass, etc.]
Y10T 428/12604	Film [e.g., glaze, etc.]
Y10T 428/12611	Oxide-containing component
Y10T 428/12618	Plural oxides
Y10T 428/12625	Free carbon containing component
Y10T 428/12632	. . .	Four or more distinct components with alternate recurrence of each type component
Y10T 428/12639	. . .	Adjacent, identical composition, components
Y10T 428/12646	Group VIII or IB metal-base
Y10T 428/12653	Fe, containing 0.01-1.7% carbon [i.e., steel]
Y10T 428/1266	O, S, or organic compound in metal component
Y10T 428/12667	Oxide of transition metal or Al
Y10T 428/12674	Ge- or Si-base component
Y10T 428/12681	Ga-, In-, Tl- or Group VA metal-base component
Y10T 428/12687	Pb- and Sn-base components: alternative to or next to each other
Y10T 428/12694	and next to Cu- or Fe-base component
Y10T 428/12701	Pb-base component
Y10T 428/12708	Sn-base component
Y10T 428/12715	Next to Group IB metal-base component
Y10T 428/12722	Next to Group VIII metal-base component
Y10T 428/12729	Group IIA metal-base component
Y10T 428/12736	Al-base component
Y10T 428/12743	Next to refractory [Group IVB, VB, or VIB] metal-base component
Y10T 428/1275	Next to Group VIII or IB metal-base component
Y10T 428/12757	Fe
Y10T 428/12764	Next to Al-base component
Y10T 428/12771	Transition metal-base component
Y10T 428/12778	Alternative base metals from diverse categories
Y10T 428/12785	Group IIB metal-base component
Y10T 428/12792	Zn-base component
Y10T 428/12799	Next to Fe-base component [e.g., galvanized]
Y10T 428/12806	Refractory [Group IVB, VB, or VIB] metal-base component
Y10T 428/12812	Diverse refractory group metal-base components: alternative to or next to each other
Y10T 428/12819	Group VB metal-base component
Y10T 428/12826	Group VIB metal-base component
Y10T 428/12833	Alternative to or next to each other

Y10T 428/1284	W-base component
Y10T 428/12847	Cr-base component
Y10T 428/12854	Next to Co-, Fe-, or Ni-base component
Y10T 428/12861	Group VIII or IB metal-base component
Y10T 428/12868	Group IB metal-base component alternative to platinum group metal-base component [e.g., precious metal, etc.]
Y10T 428/12875	Platinum group metal-base component
Y10T 428/12882	Cu-base component alternative to Ag-, Au-, or Ni-base component
Y10T 428/12889	Au-base component
Y10T 428/12896	Ag-base component
Y10T 428/12903	Cu-base component
Y10T 428/1291	Next to Co-, Cu-, or Ni-base component
Y10T 428/12917	Next to Fe-base component
Y10T 428/12924	Fe-base has 0.01-1.7% carbon [i.e., steel]
Y10T 428/12931	Co-, Fe-, or Ni-base components, alternative to each other
Y10T 428/12937	Co- or Ni-base component next to Fe-base component
Y10T 428/12944	Ni-base component
Y10T 428/12951	Fe-base component
Y10T 428/12958	Next to Fe-base component
Y10T 428/12965	Both containing 0.01-1.7% carbon [i.e., steel]
Y10T 428/12972	Containing 0.01-1.7% carbon [i.e., steel]
Y10T 428/12979	Containing more than 10% nonferrous elements [e.g., high alloy, stainless]
Y10T 428/12986	. . .	Adjacent functionally defined components
Y10T 428/12993	. .	Surface feature [e.g., rough, mirror]
Y10T 428/13	. .	Hollow or container type article [e.g., tube, vase, etc.]
Y10T 428/1303	. .	Paper containing [e.g., paperboard, cardboard, fiberboard, etc.]
Y10T 428/1307	. . .	Bag or tubular film [e.g., pouch, flexible food casing, envelope, etc.]
Y10T 428/131	. .	Glass, ceramic, or sintered, fused, fired, or calcined metal oxide or metal carbide containing [e.g., porcelain, brick, cement, etc.]
Y10T 428/1314	. . .	Contains fabric, fiber particle, or filament made of glass, ceramic, or sintered, fused, fired, or calcined metal oxide, or metal carbide or other inorganic compound [e.g., fiber glass, mineral fiber, sand, etc.]
Y10T 428/1317	. . .	Multilayer [continuous layer]
Y10T 428/1321	Polymer or resin containing [i.e., natural or synthetic]
Y10T 428/1324	. .	Flexible food casing [e.g., sausage type, etc.]
Y10T 428/1328	. .	Shrinkable or shrunk [e.g., due to heat, solvent, volatile agent, restraint removal, etc.]
Y10T 428/1331	. . .	Single layer [continuous layer]
Y10T 428/1334	. .	Nonself-supporting tubular film or bag [e.g., pouch, envelope, packet, etc.]
Y10T 428/1338	. . .	Elemental metal containing

Y10T 428/1341	. . .	Contains vapor or gas barrier, polymer derived from vinyl chloride or vinylidene chloride, or polymer containing a vinyl alcohol unit
Y10T 428/1345	. . .	Single layer [continuous layer]
Y10T 428/1348	. .	Cellular material derived from plant or animal source [e.g., wood, cotton, wool, leather, etc.]
Y10T 428/1352	. .	Polymer or resin containing [i.e., natural or synthetic]
Y10T 428/1355	. . .	Elemental metal containing [e.g., substrate, foil, film, coating, etc.]
Y10T 428/1359	Three or more layers [continuous layer]
Y10T 428/1362	. . .	Textile, fabric, cloth, or pile containing [e.g., web, net, woven, knitted, mesh, nonwoven, matted, etc.]
Y10T 428/1366	Textile, fabric, cloth, or pile is sandwiched between two distinct layers of material unlike the textile, fabric, cloth, or pile layer
Y10T 428/1369	. . .	Fiber or fibers wound around each other or into a self-sustaining shape [e.g., yarn, braid, fibers shaped around a core, etc.]
Y10T 428/1372	. . .	Randomly noninterengaged or randomly contacting fibers, filaments, particles, or flakes
Y10T 428/1376	. . .	Foam or porous material containing
Y10T 428/1379	. . .	Contains vapor or gas barrier, polymer derived from vinyl chloride or vinylidene chloride, or polymer containing a vinyl alcohol unit
Y10T 428/1383	Vapor or gas barrier, polymer derived from vinyl chloride or vinylidene chloride, or polymer containing a vinyl alcohol unit is sandwiched between layers [continuous layer]
Y10T 428/1386	. . .	Natural or synthetic rubber or rubber-like compound containing
Y10T 428/139	. . .	Open-ended, self-supporting conduit, cylinder, or tube-type article
Y10T 428/1393	Multilayer [continuous layer]
Y10T 428/1397	. . .	Single layer [continuous layer]
Y10T 428/14	. .	Layer or component removable to expose adhesive
Y10T 428/1405	. .	Capsule or particulate matter containing [e.g., sphere, flake, microballoon, etc.]
Y10T 428/141	. .	Bituminous
Y10T 428/1414	. .	Ceramic, glass, glasslike, vitreous
Y10T 428/1419	. .	Wax containing
Y10T 428/1424	. .	Halogen containing compound
Y10T 428/1429	. . .	Fluorine
Y10T 428/1433	. . .	Coloring agent containing
Y10T 428/1438	. .	Metal containing
Y10T 428/1443	. . .	Aluminum
Y10T 428/1448	. . .	Coloring agent containing
Y10T 428/1452	. .	Polymer derived only from ethylenically unsaturated monomer
Y10T 428/1457	. . .	Silicon
Y10T 428/1462	. .	Polymer derived from material having at least one acrylic or alkacrylic group or the nitrile or amide derivative thereof [e.g., acrylamide, acrylate ester, etc.]
Y10T 428/1467	. .	Coloring agent
Y10T 428/1471	. .	Protective layer

Y10T 428/1476	. . Release layer
Y10T 428/1481	. . Dissimilar adhesives
Y10T 428/1486	. . Ornamental, decorative, pattern, or indicia
Y10T 428/149	. . Sectional layer removable
Y10T 428/1495	. . . Adhesive is on removable layer
Y10T 428/15	. Sheet, web, or layer weakened to permit separation through thickness
Y10T 428/16	. Two dimensionally sectional layer
Y10T 428/161	. . with frame, casing, or perimeter structure
Y10T 428/162	. . Transparent or translucent layer or section
Y10T 428/163	. . Next to unitary web or sheet of equal or greater extent
Y10T 428/164	. . . Continuous two dimensionally sectional layer
Y10T 428/166 Glass, ceramic, or metal sections [e.g., floor or wall tile, etc.]
Y10T 428/167 Cellulosic sections [e.g., parquet floor, etc.]
Y10T 428/168	. . . Nonrectangular
Y10T 428/169	. . Sections connected flexibly with external fastener
Y10T 428/17	. Three or more coplanar interfitted sections with securing means
Y10T 428/18	. Longitudinally sectional layer of three or more sections
Y10T 428/183	. . Next to unitary sheet of equal or greater extent
Y10T 428/187	. . . Continuous sectional layer
Y10T 428/19	. Sheets or webs edge spliced or joined
Y10T 428/192	. . Sheets or webs coplanar
Y10T 428/193	. . . Double faced corrugated sheets or webs connected
Y10T 428/195	. . . Beveled, stepped, or skived in thickness
Y10T 428/197	. . . with noncoplanar reinforcement
Y10T 428/198 Pile or nap surface sheets connected
Y10T 428/20	. Patched hole or depression
Y10T 428/21	. Circular sheet or circular blank
Y10T 428/211	. . Gear
Y10T 428/213	. . Frictional
Y10T 428/214	. . End closure
Y10T 428/215	. . Seal, gasket, or packing
Y10T 428/216	. . Ornamental, decorative, pattern, or indicia
Y10T 428/218	. . Aperture containing
Y10T 428/219	. . Edge structure
Y10T 428/22	. Nonparticulate element embedded or inlaid in substrate and visible
Y10T 428/23	. Sheet including cover or casing
Y10T 428/231	. . Filled with gas other than air; or under vacuum
Y10T 428/232	. . Encased layer derived from inorganic settable ingredient
Y10T 428/233	. . Foamed or expanded material encased
Y10T 428/234	. . including elements cooperating to form cells

Y10T 428/236	. . . Honeycomb type cells extend perpendicularly to nonthickness layer
Y10T 428/237	. . Noninterengaged fibered material encased [e.g., mat, batt, etc.]
Y10T 428/238	. . . Metal cover or casing
Y10T 428/239	. . Complete cover or casing
Y10T 428/23907	. Pile or nap type surface or component
Y10T 428/23914	. . Interlaminar
Y10T 428/23921	. . With particles
Y10T 428/23929	. . Edge feature or configured or discontinuous surface
Y10T 428/23936	. . . Differential pile length or surface
Y10T 428/23943	. . Flock surface
Y10T 428/2395	. . Nap type surface
Y10T 428/23957	. . Particular shape or structure of pile
Y10T 428/23964	. . . U-, V-, or W-shaped or continuous strand, filamentary material
Y10T 428/23971 Continuous strand with adhesive bond to backing
Y10T 428/23979	. . Particular backing structure or composition
Y10T 428/23986	. . With coating, impregnation, or bond
Y10T 428/23993	. . Composition of pile or adhesive
Y10T 428/24	. Structurally defined web or sheet [e.g., overall dimension, etc.]
Y10T 428/24008	. . including fastener for attaching to external surface
Y10T 428/24017	. . . Hook or barb
Y10T 428/24025	. . Superposed movable attached layers or components
Y10T 428/24033	. . including stitching and discrete fastener[s], coating or bond
Y10T 428/24041	. . . Discontinuous or differential coating, impregnation, or bond
Y10T 428/2405 Coating, impregnation, or bond in stitching zone only
Y10T 428/24058	. . including grain, strips, or filamentary elements in respective layers or components in angular relation
Y10T 428/24066	. . . Wood grain
Y10T 428/24074	. . . Strand or strand-portions
Y10T 428/24083 Nonlinear strands or strand-portions
Y10T 428/24091 with additional layer[s]
Y10T 428/24099 On each side of strands or strand-portions
Y10T 428/24107 including mechanically interengaged strands, strand-portions or strand-like strips
Y10T 428/24116 Oblique to direction of web
Y10T 428/24124	. . . Fibers
Y10T 428/24132	. . including grain, strips, or filamentary elements in different layers or components parallel
Y10T 428/2414	. . including fringe
Y10T 428/24149	. . Honeycomb-like
Y10T 428/24157	. . . Filled honeycomb cells [e.g., solid substance in cavities, etc.]
Y10T 428/24165	. . . Hexagonally shaped cavities

Y10T 428/24174	. .	including sheet or component perpendicular to plane of web or sheet
Y10T 428/24182	. . .	Inward from edge of web or sheet
Y10T 428/2419	. .	Fold at edge
Y10T 428/24198	. . .	Channel-shaped edge component [e.g., binding, etc.]
Y10T 428/24207	. . .	with strand[s] or strand-portion[s] between layers [e.g., upholstery trim, etc.]
Y10T 428/24215	. . .	Acute or reverse fold of exterior component
Y10T 428/24223	Embedded in body of web
Y10T 428/24231	At opposed marginal edges
Y10T 428/2424	Annular cover
Y10T 428/24248	One piece
Y10T 428/24256	Abutted or lapped seam
Y10T 428/24264	. . .	Particular fold structure [e.g., beveled, etc.]
Y10T 428/24273	. .	including aperture
Y10T 428/24281	. . .	Struck out portion type
Y10T 428/24289	Embedded or interlocked
Y10T 428/24298	. . .	Noncircular aperture [e.g., slit, diamond, rectangular, etc.]
Y10T 428/24306	Diamond or hexagonal
Y10T 428/24314	Slit or elongated
Y10T 428/24322	. . .	Composite web or sheet
Y10T 428/24331	including nonapertured component
Y10T 428/24339	Keyed
Y10T 428/24347	From both sides
Y10T 428/24355	. .	Continuous and nonuniform or irregular surface on layer or component [e.g., roofing, etc.]
Y10T 428/24364	. . .	with transparent or protective coating
Y10T 428/24372	. . .	Particulate matter
Y10T 428/2438	Coated
Y10T 428/24388	Silicon containing coating
Y10T 428/24397	Carbohydrate
Y10T 428/24405	Polymer or resin [e.g., natural or synthetic rubber, etc.]
Y10T 428/24413	Metal or metal compound
Y10T 428/24421	Silicon containing
Y10T 428/2443	Sand, clay, or crushed rock or slate
Y10T 428/24438	. . .	Artificial wood or leather grain surface
Y10T 428/24446	. . .	Wrinkled, creased, crinkled or creped
Y10T 428/24455	Paper
Y10T 428/24463	Plural paper components
Y10T 428/24471	. . .	Crackled, crazed or slit
Y10T 428/24479	. .	including variation in thickness
Y10T 428/24488	. . .	Differential nonuniformity at margin

Y10T 428/24496	. . .	Foamed or cellular component
Y10T 428/24504	Component comprises a polymer [e.g., rubber, etc.]
Y10T 428/24512	Polyurethane
Y10T 428/24521	. . .	with component conforming to contour of nonplanar surface
Y10T 428/24529	and conforming component on an opposite nonplanar surface
Y10T 428/24537	Parallel ribs and/or grooves
Y10T 428/24545	Containing metal or metal compound
Y10T 428/24554	including cellulosic or natural rubber component
Y10T 428/24562	. . .	Interlaminar spaces
Y10T 428/2457	. . .	Parallel ribs and/or grooves
Y10T 428/24579	with particulate matter
Y10T 428/24587	Oblique to longitudinal axis of web or sheet
Y10T 428/24595	. . .	and varying density
Y10T 428/24603	Fiber containing component
Y10T 428/24612	. . .	Composite web or sheet
Y10T 428/2462	with partial filling of valleys on outer surface
Y10T 428/24628	. .	Nonplanar uniform thickness material
Y10T 428/24636	. . .	Embodying mechanically interengaged strand[s], strand-portion[s] or strand-like strip[s] [e.g., weave, knit, etc.]
Y10T 428/24645	with folds in parallel planes
Y10T 428/24653	. . .	Differential nonplanarity at margin
Y10T 428/24661	. . .	Forming, or cooperating to form cells
Y10T 428/24669	. . .	Aligned or parallel nonplanarities
Y10T 428/24678	Waffle-form
Y10T 428/24686	Pleats or otherwise parallel adjacent folds
Y10T 428/24694	Parallel corrugations
Y10T 428/24702	with locally deformed crests or intersecting series of corrugations
Y10T 428/24711	Plural corrugated components
Y10T 428/24719	with corrugations of respective components intersecting in plane projection
Y10T 428/24727	with planar component
Y10T 428/24736	. . .	Ornamental design or indicia
Y10T 428/24744	. .	Longitudinal or transverse tubular cavity or cell
Y10T 428/24752	. .	Laterally noncoextensive components
Y10T 428/2476	. . .	Fabric, cloth or textile component
Y10T 428/24769	. . .	Cellulosic
Y10T 428/24777	. .	Edge feature
Y10T 428/24785	. . .	including layer embodying mechanically interengaged strands, strand portions or strand-like strips [e.g., weave, knit, etc.]
Y10T 428/24793	. . .	Comprising discontinuous or differential impregnation or bond

Y10T 428/24802	. .	Discontinuous or differential coating, impregnation or bond [e.g., artwork, printing, retouched photograph, etc.]
Y10T 428/2481	. . .	including layer of mechanically interengaged strands, strand-portions or strand-like strips
Y10T 428/24818	Knitted, with particular or differential bond sites or intersections
Y10T 428/24826	. . .	Spot bonds connect components
Y10T 428/24835	. . .	including developable image or soluble portion in coating or impregnation [e.g., safety paper, etc.]
Y10T 428/24843	. . .	with heat sealable or heat releasable adhesive layer
Y10T 428/24851	. . .	Intermediate layer is discontinuous or differential
Y10T 428/2486	with outer strippable or release layer
Y10T 428/24868	Translucent outer layer
Y10T 428/24876	Intermediate layer contains particulate material [e.g., pigment, etc.]
Y10T 428/24884	Translucent layer comprises natural oil, wax, resin, gum, glue, gelatin
Y10T 428/24893	. . .	including particulate material
Y10T 428/24901	including coloring matter
Y10T 428/24909	Free metal or mineral containing
Y10T 428/24917	. . .	including metal layer
Y10T 428/24926	. . .	including ceramic, glass, porcelain or quartz layer
Y10T 428/24934	. . .	including paper layer
Y10T 428/24942	. .	including components having same physical characteristic in differing degree
Y10T 428/2495	. . .	Thickness [relative or absolute]
Y10T 428/24959	of adhesive layers
Y10T 428/24967	Absolute thicknesses specified
Y10T 428/24975	No layer or component greater than 5 mils thick
Y10T 428/24983	. . .	Hardness
Y10T 428/24992	. . .	Density or compression of components
Y10T 428/249921	. .	Web or sheet containing structurally defined element or component
Y10T 428/249922	. .	Embodying intertwined or helical component[s]
Y10T 428/249923	. .	Including interlaminar mechanical fastener
Y10T 428/249924	. .	Noninterengaged fiber-containing paper-free web or sheet which is not of specified porosity
Y10T 428/249925	. . .	Fiber-containing wood product [e.g., hardboard, lumber, or wood board, etc.]
Y10T 428/249926	. . .	Including paper layer
Y10T 428/249927	. . .	Fiber embedded in a metal matrix
Y10T 428/249928	. . .	Fiber embedded in a ceramic, glass, or carbon matrix
Y10T 428/249929	Fibers are aligned substantially parallel
Y10T 428/24993	Fiber is precoated
Y10T 428/249931	Free metal or alloy fiber
Y10T 428/249932	. . .	Fiber embedded in a layer derived from a water-settable material [e.g., cement, gypsum, etc.]

Y10T 428/249933	.	.	.	Fiber embedded in or on the surface of a natural or synthetic rubber matrix
Y10T 428/249934	.	.	.	Fibers are aligned substantially parallel
Y10T 428/249935	.	.	.	Fiber is nonlinear [e.g., crimped, sinusoidal, etc.]
Y10T 428/249936	.	.	.	Fiber is precoated
Y10T 428/249937	.	.	.	Fiber is precoated
Y10T 428/249938	.	.	.	Composite or conjugate fiber [e.g., fiber contains more than one chemically different material in monofilament or multifilament form, etc.]
Y10T 428/249939	.	.	.	Two or more layers
Y10T 428/24994	.	.	.	Fiber embedded in or on the surface of a polymeric matrix
Y10T 428/249941	.	.	.	Fiber is on the surface of a polymeric matrix having no embedded portion
Y10T 428/249942	.	.	.	Fibers are aligned substantially parallel
Y10T 428/249943	.	.	.	Fiber is nonlinear [e.g., crimped, sinusoidal, etc.]
Y10T 428/249944	.	.	.	Fiber is precoated
Y10T 428/249945	.	.	.	Carbon or carbonaceous fiber
Y10T 428/249946	.	.	.	Glass fiber
Y10T 428/249947	.	.	.	Polymeric fiber
Y10T 428/249948	.	.	.	Fiber is precoated
Y10T 428/249949	.	.	.	Two or more chemically different fibers
Y10T 428/24995	.	.	.	Two or more layers
Y10T 428/249951	.	.	.	Including a free metal or alloy constituent
Y10T 428/249952	.	.	.	At least one thermosetting synthetic polymeric material layer
Y10T 428/249953	.	.	.	Composite having voids in a component [e.g., porous, cellular, etc.]
Y10T 428/249954	.	.	.	With chemically effective material or specified gas other than air, N, or carbon dioxide in void-containing component
Y10T 428/249955	.	.	.	Void-containing component partially impregnated with adjacent component
Y10T 428/249956	.	.	.	Void-containing component is inorganic
Y10T 428/249957	.	.	.	Inorganic impregnant
Y10T 428/249958	.	.	.	Void-containing component is synthetic resin or natural rubbers
Y10T 428/249959	.	.	.	Void-containing component is wood or paper
Y10T 428/24996	.	.	.	With internal element bridging layers, nonplanar interface between layers, or intermediate layer of commingled adjacent foam layers
Y10T 428/249961	.	.	.	With gradual property change within a component
Y10T 428/249962	.	.	.	Void-containing component has a continuous matrix of fibers only [e.g., porous paper, etc.]
Y10T 428/249963	.	.	.	And a force disintegratable component [e.g., stencil sheet, etc.]
Y10T 428/249964	.	.	.	Fibers of defined composition
Y10T 428/249965	.	.	.	Cellulosic
Y10T 428/249966	.	.	.	Plural cellulosic components
Y10T 428/249967	.	.	.	Inorganic matrix in void-containing component
Y10T 428/249968	.	.	.	Of hydraulic-setting material
Y10T 428/249969	.	.	.	Of silicon-containing material [e.g., glass, etc.]

Y10T 428/24997	Of metal-containing material
Y10T 428/249971	. . .	Preformed hollow element-containing
Y10T 428/249972	Resin or rubber element
Y10T 428/249973	Mineral element
Y10T 428/249974	Metal- or silicon-containing element
Y10T 428/249975	. . .	Void shape specified [e.g., crushed, flat, round, etc.]
Y10T 428/249976	. . .	Voids specified as closed
Y10T 428/249977	Specified thickness of void-containing component [absolute or relative], numerical cell dimension or density
Y10T 428/249978	. . .	Voids specified as micro
Y10T 428/249979	Specified thickness of void-containing component [absolute or relative] or numerical cell dimension
Y10T 428/24998	Composite has more than two layers
Y10T 428/249981	. . .	Plural void-containing components
Y10T 428/249982	. . .	With component specified as adhesive or bonding agent
Y10T 428/249983	As outermost component
Y10T 428/249984	Adhesive or bonding component contains voids
Y10T 428/249985	Composition of adhesive or bonding component specified
Y10T 428/249986	. . .	Void-containing component contains also a solid fiber or solid particle
Y10T 428/249987	. . .	With nonvoid component of specified composition
Y10T 428/249988	Of about the same composition as, and adjacent to, the void-containing component
Y10T 428/249989	Integrally formed skin
Y10T 428/24999	Inorganic
Y10T 428/249991	Synthetic resin or natural rubbers
Y10T 428/249992	Linear or thermoplastic
Y10T 428/249993	Hydrocarbon polymer
Y10T 428/249994	. .	Composite having a component wherein a constituent is liquid or is contained within preformed walls [e.g., impregnant-filled, previously void containing component, etc.]
Y10T 428/249995	. . .	Constituent is in liquid form
Y10T 428/249996	Ink in pores
Y10T 428/249997	Encapsulated liquid
Y10T 428/249998	. . .	Indefinite plurality of similar impregnated thin sheets [e.g., "decorative laminate" type, etc.]
Y10T 428/249999	. . .	Differentially filled foam, filled plural layers, or filled layer with coat of filling material
Y10T 428/25	. .	Web or sheet containing structurally defined element or component and including a second component containing structurally defined particles
Y10T 428/251	. .	Mica
Y10T 428/252	. .	Glass or ceramic [i.e., fired or glazed clay, cement, etc.] [porcelain, quartz, etc.]
Y10T 428/253	. .	Cellulosic [e.g., wood, paper, cork, rayon, etc.]

- Y10T 428/254 . . Polymeric or resinous material
- Y10T 428/256 . . Heavy metal or aluminum or compound thereof
- Y10T 428/257 . . . Iron oxide or aluminum oxide
- Y10T 428/258 . . Alkali metal or alkaline earth metal or compound thereof
- Y10T 428/259 . . Silicic material
- Y10T 428/26 . . Web or sheet containing structurally defined element or component, the element or component having a specified physical dimension
- Y10T 428/261 . . In terms of molecular thickness or light wave length
- Y10T 428/263 . . Coating layer not in excess of 5 mils thick or equivalent
- Y10T 428/264 . . . Up to 3 mils
- Y10T 428/265 1 mil or less
- Y10T 428/266 . . of base or substrate
- Y10T 428/268 . . Monolayer with structurally defined element
- Y10T 428/269 . . including synthetic resin or polymer layer or component
- Y10T 428/27 . . Web or sheet containing structurally defined element or component, the element or component having a specified weight per unit area [e.g., gms/sq cm, lbs/sq ft, etc.]
- Y10T 428/273 . . of coating
- Y10T 428/277 . . . Cellulosic substrate
- Y10T 428/28 . . Web or sheet containing structurally defined element or component and having an adhesive outermost layer
- Y10T 428/2804 . . Next to metal
- Y10T 428/2809 . . including irradiated or wave energy treated component
- Y10T 428/2813 . . Heat or solvent activated or sealable
- Y10T 428/2817 . . . Heat sealable
- Y10T 428/2822 Wax containing
- Y10T 428/2826 Synthetic resin or polymer
- Y10T 428/283 . . . Water activated
- Y10T 428/2835 . . including moisture or waterproof component
- Y10T 428/2839 . . with release or antistick coating
- Y10T 428/2843 . . including a primer layer
- Y10T 428/2848 . . Three or more layers
- Y10T 428/2852 . . Adhesive compositions
- Y10T 428/2857 . . . including metal or compound thereof or natural rubber
- Y10T 428/2861 . . . having readily strippable combined with readily readhearable properties [e.g., stick-ons, etc.]
- Y10T 428/2865 . . . including monomer or polymer of carbohydrate [e.g., starch, dextrin, etc.] Or protein [e.g., casein, animal protein, etc.] Or derivative thereof
- Y10T 428/287 . . . including epoxy group or epoxy polymer
- Y10T 428/2874 . . . including aldehyde or ketone condensation polymer [e.g., urea formaldehyde polymer, melamine formaldehyde polymer, etc.]
- Y10T 428/2878 . . . including addition polymer from unsaturated monomer
- Y10T 428/2883 including addition polymer of diene monomer [e.g., SBR, SIS, etc.]

Y10T 428/2887	including nitrogen containing polymer [e.g., polyacrylonitrile, polymethacrylonitrile, etc.]
Y10T 428/2891	including addition polymer from alpha-beta unsaturated carboxylic acid [e.g., acrylic acid, methacrylic acid, etc.] Or derivative thereof
Y10T 428/2896	including nitrogen containing condensation polymer [e.g., polyurethane, polyisocyanate, etc.]
Y10T 428/29	Coated or structually defined flake, particle, cell, strand, strand portion, rod, filament, macroscopic fiber or mass thereof
Y10T 428/2902	Channel shape
Y10T 428/2904	Staple length fiber
Y10T 428/2905	Plural and with bonded intersections only
Y10T 428/2907	with coating or impregnation
Y10T 428/2909	Nonlinear [e.g., crimped, coiled, etc.]
Y10T 428/2911	Mica flake
Y10T 428/2913	Rod, strand, filament or fiber
Y10T 428/2915	including textile, cloth or fabric
Y10T 428/2916	including boron or compound thereof [not as steel]
Y10T 428/2918	including free carbon or carbide or therewith [not as steel]
Y10T 428/292	In coating or impregnation
Y10T 428/2922	Nonlinear [e.g., crimped, coiled, etc.]
Y10T 428/2924	Composite
Y10T 428/2925	Helical or coiled
Y10T 428/2927	including structurally defined particulate matter
Y10T 428/2929	Bicomponent, conjugate, composite or collateral fibers or filaments [i.e., coextruded sheath-core or side-by-side type]
Y10T 428/2931	Fibers or filaments nonconcentric [e.g., side-by-side or eccentric, etc.]
Y10T 428/2933	Coated or with bond, impregnation or core
Y10T 428/2935	Discontinuous or tubular or cellular core
Y10T 428/2936	Wound or wrapped core or coating [i.e., spiral or helical]
Y10T 428/2938	Coating on discrete and individual rods, strands or filaments
Y10T 428/294	including metal or compound thereof [excluding glass, ceramic and asbestos]
Y10T 428/2942	Plural coatings
Y10T 428/2944	Free metal in coating
Y10T 428/2945	Natural rubber in coating
Y10T 428/2947	Synthetic resin or polymer in plural coatings, each of different type
Y10T 428/2949	Glass, ceramic or metal oxide in coating
Y10T 428/2951	Metal with weld modifying or stabilizing coating [e.g., flux, slag, producer, etc.]
Y10T 428/2953	Titanium compound in coating
Y10T 428/2955	Silicic material in coating
Y10T 428/2956	Glass or silicic fiber or filament with metal coating

Y10T 428/2958 Metal or metal compound in coating
Y10T 428/296 Rubber, cellulosic or silicic material in coating
Y10T 428/2962 Silane, silicone or siloxane in coating
Y10T 428/2964 Artificial fiber or filament
Y10T 428/2965 Cellulosic
Y10T 428/2967 Synthetic resin or polymer
Y10T 428/2969 Polyamide, polyimide or polyester
Y10T 428/2971 Impregnation
Y10T 428/2973 Particular cross section
Y10T 428/2975 Tubular or cellular
Y10T 428/2976 Longitudinally varying
Y10T 428/2978 Surface characteristic
Y10T 428/298 Physical dimension
Y10T 428/2982 Particulate matter [e.g., sphere, flake, etc.]
Y10T 428/2984 Microcapsule with fluid core [includes liposome]
Y10T 428/2985 Solid-walled microcapsule from synthetic polymer
Y10T 428/2987 Addition polymer from unsaturated monomers only
Y10T 428/2989 Microcapsule with solid core [includes liposome]
Y10T 428/2991 Coated
Y10T 428/2993 Silicic or refractory material containing [e.g., tungsten oxide, glass, cement, etc.]
Y10T 428/2995 Silane, siloxane or silicone coating
Y10T 428/2996 Glass particles or spheres
Y10T 428/2998 including synthetic resin or polymer
Y10T 428/30 Self-sustaining carbon mass or layer with impregnant or other layer
Y10T 428/31 Surface property or characteristic of web, sheet or block
Y10T 428/315 Surface modified glass [e.g., tempered, strengthened, etc.]
Y10T 428/31504 Composite [nonstructural laminate]
Y10T 428/31507 Of polycarbonate
Y10T 428/31511 Of epoxy ether
Y10T 428/31515 As intermediate layer
Y10T 428/31518 Next to glass or quartz
Y10T 428/31522 Next to metal
Y10T 428/31525 Next to glass or quartz
Y10T 428/31529 Next to metal
Y10T 428/31533 Of polythioether
Y10T 428/31536 Including interfacial reaction product of adjacent layers
Y10T 428/3154 Of fluorinated addition polymer from unsaturated monomers
Y10T 428/31544 Addition polymer is perhalogenated
Y10T 428/31547 Of polyisocyanurate

Y10T 428/31551	. .	Of polyamidoester [polyurethane, polyisocyanate, polycarbamate, etc.]
Y10T 428/31554	. . .	Next to second layer of polyamidoester
Y10T 428/31558	. . .	Next to animal skin or membrane
Y10T 428/31562	. . .	Next to polyamide [nylon, etc.]
Y10T 428/31565	. . .	Next to polyester [polyethylene terephthalate, etc.]
Y10T 428/31569	. . .	Next to natural rubber
Y10T 428/31573	. . .	Next to addition polymer of ethylenically unsaturated monomer
Y10T 428/31576	Ester monomer type [polyvinylacetate, etc.]
Y10T 428/3158	Halide monomer type [polyvinyl chloride, etc.]
Y10T 428/31583	Nitrile monomer type [polyacrylonitrile, etc.]
Y10T 428/31587	Hydrocarbon polymer [polyethylene, polybutadiene, etc.]
Y10T 428/31591	. . .	Next to cellulosic
Y10T 428/31594	. . .	Next to aldehyde or ketone condensation product [phenol-aldehyde, etc.]
Y10T 428/31598	. . .	Next to silicon-containing [silicone, cement, etc.] layer
Y10T 428/31601	Quartz or glass
Y10T 428/31605	. . .	Next to free metal
Y10T 428/31609	. . .	Particulate metal or metal compound-containing
Y10T 428/31612	As silicone, silane or siloxane
Y10T 428/31616	. . .	Next to polyester [e.g., alkyd]
Y10T 428/3162	Cross-linked polyester [e.g., glycerol maleate-styrene, etc.]
Y10T 428/31623	. . .	Next to polyamide or polyimide
Y10T 428/31627	. . .	Next to aldehyde or ketone condensation product
Y10T 428/3163	Next to acetal of polymerized unsaturated alcohol [e.g., formal butyral, etc.]
Y10T 428/31634	. . .	Next to cellulosic
Y10T 428/31638	Cellulosic ester
Y10T 428/31641	. . .	Next to natural rubber, gum, oil, rosin, wax, bituminous or tarry residue
Y10T 428/31645	. . .	Next to addition polymer from unsaturated monomers
Y10T 428/31649	Ester, halide or nitrile of addition polymer
Y10T 428/31652	. .	Of asbestos
Y10T 428/31656	. . .	With metal layer
Y10T 428/31659	. . .	With cellulosic layer
Y10T 428/31663	. . .	As siloxane, silicone or silane
Y10T 428/31667	. . .	Next to addition polymer from unsaturated monomers, or aldehyde or ketone condensation product
Y10T 428/3167	. .	Of cork
Y10T 428/31674	. . .	Including natural oil or gum or rosin [e.g., linoleum, etc.]
Y10T 428/31678	. .	Of metal
Y10T 428/31681	. . .	Next to polyester, polyamide or polyimide [e.g., alkyd, glue, or nylon, etc.]
Y10T 428/31685	Natural source polyamide [e.g., casein, gelatin, etc.]
Y10T 428/31688	. . .	Next to aldehyde or ketone condensation product

Y10T 428/31692	. . .	Next to addition polymer from unsaturated monomers
Y10T 428/31696	Including polyene monomers [e.g., butadiene, etc.]
Y10T 428/31699	Ester, halide or nitrile of addition polymer
Y10T 428/31703	. . .	Next to cellulosic
Y10T 428/31707	. . .	Next to natural rubber
Y10T 428/3171	With natural rubber next to second layer of natural rubber
Y10T 428/31714	. . .	Next to natural gum, natural oil, rosin, lac or wax
Y10T 428/31717	. . .	Next to bituminous or tarry residue
Y10T 428/31721	. .	Of polyimide
Y10T 428/31725	. .	Of polyamide
Y10T 428/31728	. . .	Next to second layer of polyamide
Y10T 428/31732	At least one layer is nylon type
Y10T 428/31736	. . .	Next to polyester
Y10T 428/31739	. . .	Nylon type
Y10T 428/31743	Next to addition polymer from unsaturated monomer[s]
Y10T 428/31746	Polymer of monoethylenically unsaturated hydrocarbon
Y10T 428/3175	. . .	Next to addition polymer from unsaturated monomer[s]
Y10T 428/31754	Natural source-type polyamide
Y10T 428/31757	Polymer of monoethylenically unsaturated hydrocarbon
Y10T 428/31761	. . .	Next to aldehyde or ketone condensation product
Y10T 428/31765	. . .	Inorganic-containing or next to inorganic-containing
Y10T 428/31768	. . .	Natural source-type polyamide [e.g., casein, gelatin, etc.]
Y10T 428/31772	Next to cellulosic
Y10T 428/31775	Paper
Y10T 428/31779	. . .	Next to cellulosic
Y10T 428/31783	Paper or wood
Y10T 428/31786	. .	Of polyester [e.g., alkyd, etc.]
Y10T 428/3179	. . .	Next to cellulosic
Y10T 428/31794	. . .	Of cross-linked polyester
Y10T 428/31797	. . .	Next to addition polymer from unsaturated monomers
Y10T 428/31801	. .	Of wax or waxy material
Y10T 428/31804	. . .	Next to cellulosic
Y10T 428/31808	Cellulosic is paper
Y10T 428/31812	Glassine paper
Y10T 428/31815	. .	Of bituminous or tarry residue
Y10T 428/31819	. . .	Next to cellulosic
Y10T 428/31823	Paper
Y10T 428/31826	. .	Of natural rubber
Y10T 428/3183	. . .	Next to second layer of natural rubber

Y10T 428/31833	. . .	Next to aldehyde or ketone condensation product or addition polymer from unsaturated monomers
Y10T 428/31837	Including polyene monomers
Y10T 428/31841	. . .	Next to cellulosic
Y10T 428/31844	. .	Of natural gum, rosin, natural oil or lac
Y10T 428/31848	. . .	Next to cellulosic
Y10T 428/31851	Natural oil
Y10T 428/31855	. .	Of addition polymer from unsaturated monomers
Y10T 428/31859	. . .	Next to an aldehyde or ketone condensation product
Y10T 428/31862	Melamine-aldehyde
Y10T 428/31866	Impregnated or coated cellulosic material
Y10T 428/3187	Amide-aldehyde
Y10T 428/31873	Urea or modified urea-aldehyde
Y10T 428/31877	Phenol-aldehyde
Y10T 428/3188	. . .	Next to cellulosic
Y10T 428/31884	Regenerated or modified cellulose
Y10T 428/31888	Addition polymer of hydrocarbon[s] only
Y10T 428/31891	Where addition polymer is an ester or halide
Y10T 428/31895	Paper or wood
Y10T 428/31899	Addition polymer of hydrocarbon[s] only
Y10T 428/31902	Monoethylenically unsaturated
Y10T 428/31906	Ester, halide or nitrile of addition polymer
Y10T 428/31909	. . .	Next to second addition polymer from unsaturated monomers
Y10T 428/31913	Monoolefin polymer
Y10T 428/31917	Next to polyene polymer
Y10T 428/3192	Next to vinyl or vinylidene chloride polymer
Y10T 428/31924	Including polyene monomers
Y10T 428/31928	Ester, halide or nitrile of addition polymer
Y10T 428/31931	. . .	Polyene monomer-containing
Y10T 428/31935	. . .	Ester, halide or nitrile of addition polymer
Y10T 428/31938	. . .	Polymer of monoethylenically unsaturated hydrocarbon
Y10T 428/31942	. .	Of aldehyde or ketone condensation product
Y10T 428/31946	. . .	Next to second aldehyde or ketone condensation product
Y10T 428/31949	. . .	Next to cellulosic
Y10T 428/31953	Modified or regenerated cellulose
Y10T 428/31957	Wood
Y10T 428/3196	Phenoplast
Y10T 428/31964	Paper
Y10T 428/31967	Phenoplast
Y10T 428/31971	. .	Of carbohydrate

Y10T 428/31975	. . . Of cellulosic next to another carbohydrate
Y10T 428/31978 Cellulosic next to another cellulosic
Y10T 428/31982 Wood or paper
Y10T 428/31986 Regenerated or modified
Y10T 428/31989	. . . Of wood
Y10T 428/31993	. . . Of paper
Y10T 428/31996 Next to layer of metal salt [e.g., plasterboard, etc.]
Y10T 428/32	. Composite [nonstructural laminate] of inorganic material having metal-compound-containing layer and having defined magnetic layer
Y10T 428/325	. . Magnetic layer next to second metal compound-containing layer
Y10T 428/4935	. Impregnated naturally solid product [e.g., leather, stone, etc.]
Y10T 428/662	. . Wood timber product [e.g., piling, post, veneer, etc.]
Y10T 428/8305	. Miscellaneous [e.g., treated surfaces, etc.]

Former US Class 436 Series

Y10T 436/00

Chemistry: analytical and immunological testing

Y10T 436/10	. Composition for standardization, calibration, simulation, stabilization, preparation or preservation; processes of use in preparation for chemical testing
Y10T 436/100833	. . Simulative of a gaseous composition
Y10T 436/101666	. . Particle count or volume standard or control [e.g., platelet count standards, etc.]
Y10T 436/102499	. . Blood gas standard or control
Y10T 436/103332	. . Bilirubin or uric acid standard or control
Y10T 436/104165	. . Lipid, cholesterol, or triglyceride standard or control
Y10T 436/104998	. . Glucose, ketone, nitrate standard or control
Y10T 436/105831	. . Protein or peptide standard or control [e.g., hemoglobin, etc.]
Y10T 436/106664	. . Blood serum or blood plasma standard or control
Y10T 436/107497	. . Preparation composition [e.g., lysing or precipitation, etc.]
Y10T 436/108331	. . Preservative, buffer, anticoagulant or diluent
Y10T 436/109163	. . Inorganic standards or controls
Y10T 436/11	. Automated chemical analysis
Y10T 436/110833	. . Utilizing a moving indicator strip or tape
Y10T 436/111666	. . Utilizing a centrifuge or compartmented rotor
Y10T 436/112499	. . with sample on test slide
Y10T 436/113332	. . with conveyance of sample along a test line in a container or rack
Y10T 436/114165	. . . with step of insertion or removal from test line
Y10T 436/114998	. . . with treatment or replacement of aspirator element [e.g., cleaning, etc.]
Y10T 436/115831	. . Condition or time responsive
Y10T 436/116664	. . . with automated titrator
Y10T 436/117497	. . with a continuously flowing sample or carrier stream
Y10T 436/118339	. . . with formation of a segmented stream

Y10T 436/119163	. . with aspirator of claimed structure
Y10T 436/12	. Condition responsive control
Y10T 436/13	. Tracers or tags
Y10T 436/14	. Heterocyclic carbon compound [i.e. , O, S, N, Se, Te, as only ring hetero atom]
Y10T 436/141111	. . Diverse hetero atoms in same or different rings [e.g., alkaloids, opiates, etc.]
Y10T 436/142222	. . Hetero-O [e.g., ascorbic acid, etc.]
Y10T 436/143333	. . . Saccharide [e.g., DNA, etc.]
Y10T 436/144444 Glucose
Y10T 436/145555	. . Hetero-N
Y10T 436/146666	. . . Bile pigment
Y10T 436/147777	. . . Plural nitrogen in the same ring [e.g., barbituates, creatinine, etc.]
Y10T 436/148888 Uric acid
Y10T 436/15	. Inorganic acid or base [e.g. , hcl, sulfuric acid, etc.]
Y10T 436/153333	. . Halogen containing
Y10T 436/156666	. . Sulfur containing
Y10T 436/16	. Phosphorus containing
Y10T 436/163333	. . Organic [e.g., chemical warfare agents, insecticides, etc.]
Y10T 436/166666	. . of inorganic phosphorus compound in body fluid
Y10T 436/17	. Nitrogen containing
Y10T 436/170769	. . N-Nitroso containing [e.g., nitrosamine, etc.]
Y10T 436/171538	. . Urea or blood urea nitrogen
Y10T 436/172307	. . Cyanide or isocyanide
Y10T 436/173076	. . Nitrite or nitrate
Y10T 436/173845	. . Amine and quaternary ammonium
Y10T 436/174614	. . . Tertiary amine
Y10T 436/175383	. . . Ammonia
Y10T 436/176152	. . Total nitrogen determined
Y10T 436/176921	. . . As part of an elemental analysis
Y10T 436/177692	. . Oxides of nitrogen
Y10T 436/178459	. . . Only nitrogen dioxide
Y10T 436/179228	. . . Both nitrogen oxide and dioxide
Y10T 436/18	. Sulfur containing
Y10T 436/182	. . Organic or sulfhydryl containing [e.g., mercaptan, hydrogen, sulfide, etc.]
Y10T 436/184	. . . Only hydrogen sulfide
Y10T 436/186	. . Sulfur dioxide
Y10T 436/188	. . Total or elemental sulfur
Y10T 436/19	. Halogen containing
Y10T 436/193333	. . In aqueous solution
Y10T 436/196666	. . Carbon containing compound [e.g., vinylchloride, etc.]
Y10T 436/20	. Oxygen containing

Y10T 436/200833	. . Carbonyl, ether, aldehyde or ketone containing
Y10T 436/201666	. . . Carboxylic acid
Y10T 436/202499	. . . Formaldehyde or acetone
Y10T 436/203332	. . Hydroxyl containing
Y10T 436/204165	. . . Ethanol
Y10T 436/204998	. . Inorganic carbon compounds
Y10T 436/205831	. . . Carbon monoxide only
Y10T 436/206664	. . Ozone or peroxide
Y10T 436/207497	. . Molecular oxygen
Y10T 436/208339	. . . Fuel/air mixture or exhaust gas analysis
Y10T 436/209163	. . . Dissolved or trace oxygen or oxygen content of a sealed environment
Y10T 436/21	. Hydrocarbon
Y10T 436/212	. . Aromatic
Y10T 436/214	. . Acyclic [e.g., methane, octane, isoparaffin, etc.]
Y10T 436/216	. . . Unsaturated [e.g., ethylene, diene, etc.]
Y10T 436/218	. . Total hydrocarbon, flammability, combustibility [e.g., air-fuel mixture, etc.]
Y10T 436/22	. Hydrogen, per se
Y10T 436/23	. Carbon containing
Y10T 436/235	. . In an aqueous solution [e.g., TOC, etc.]
Y10T 436/24	. Nuclear magnetic resonance, electron spin resonance or other spin effects or mass spectrometry
Y10T 436/25	. including sample preparation
Y10T 436/25125	. . Digestion or removing interfering materials
Y10T 436/2525	. . Stabilizing or preserving
Y10T 436/25375	. . Liberation or purification of sample or separation of material from a sample [e.g., filtering, centrifuging, etc.]
Y10T 436/255	. . . including use of a solid sorbent, semipermeable membrane, or liquid extraction
Y10T 436/25625	. . Dilution
Y10T 436/2575	. . Volumetric liquid transfer
Y10T 436/25875	. . Gaseous sample or with change of physical state

Former US Class 442 series

Y10T 442/00	Fabric [woven, knitted, or nonwoven textile or cloth, etc.]
Y10T 442/10	. Scrim [e.g., open net or mesh, gauze, loose or open weave or knit, etc.]
Y10T 442/102	. . Woven scrim
Y10T 442/103	. . . Including a multifilament fiber precoated with other than free metal or alloy prior to weaving
Y10T 442/105	. . . Comprising a composite fiber
Y10T 442/107	. . . Comprising at least two chemically different fibers
Y10T 442/109	. . . Metal or metal-coated fiber-containing scrim

Y10T 442/11	Including an additional free metal or alloy constituent
Y10T 442/112	Particulate free metal or alloy constituent
Y10T 442/114	Including a foam layer
Y10T 442/116	Including a woven fabric which is not a scrim
Y10T 442/117	Including a nonwoven fabric which is not a scrim
Y10T 442/119	Including a paper layer
Y10T 442/121	Including a nonwoven fabric which is not a scrim
Y10T 442/122	Two or more nonwoven fabric layers
Y10T 442/124	Including a natural or synthetic rubber layer
Y10T 442/126	Including a preformed film, foil, or sheet
Y10T 442/128	Including a layer derived from a water-settable material [e.g., cement, gypsum, etc.]
Y10T 442/129	Including a ceramic or glass layer
Y10T 442/131	Including a coating or impregnation of synthetic polymeric material
Y10T 442/133	. . .	Inorganic fiber-containing scrim
Y10T 442/134	Including a carbon or carbonized fiber
Y10T 442/136	Including a foam layer
Y10T 442/138	Including a metal layer
Y10T 442/14	Including an additional scrim layer
Y10T 442/141	Including a woven fabric which is not a scrim
Y10T 442/143	Including a nonwoven fabric which is not a scrim
Y10T 442/145	Including a preformed film, foil, or sheet
Y10T 442/147	Including a mica layer
Y10T 442/148	Including a coating or impregnation containing particulate material other than fiber
Y10T 442/15	. . .	Including a foam layer
Y10T 442/152	. . .	Including a free metal or alloy constituent
Y10T 442/153	. . .	Including an additional scrim layer
Y10T 442/155	. . .	Including a paper layer
Y10T 442/157	Two or more paper layers
Y10T 442/159	. . .	Including a nonwoven fabric which is not a scrim
Y10T 442/16	Two or more nonwoven layers
Y10T 442/162	. . .	Including a natural or synthetic rubber layer
Y10T 442/164	. . .	Including a preformed film, foil, or sheet
Y10T 442/166	Cellulose acetate film or sheet
Y10T 442/167	Fluorinated polyolefin film or sheet
Y10T 442/169	Polyolefin film or sheet
Y10T 442/171	. . .	Including a layer derived from a water-settable material [e.g., cement, gypsum, etc.]
Y10T 442/172	. . .	Coated or impregnated
Y10T 442/174	Including particulate material other than fiber in coating or impregnation

- Y10T 442/176 Three or more layers
- Y10T 442/178 Synthetic polymeric fiber
- Y10T 442/179 Nylon fiber
- Y10T 442/181 Bitumen coating or impregnation
- Y10T 442/183 . . . Synthetic polymeric fiber
- Y10T 442/184 . . Nonwoven scrim
- Y10T 442/186 . . . Comprising a composite fiber
- Y10T 442/188 . . . Metal or metal-coated fiber-containing scrim
- Y10T 442/19 Including a paper layer
- Y10T 442/191 . . . Inorganic fiber-containing scrim
- Y10T 442/193 Including a foam layer
- Y10T 442/195 . . . Including a foam layer
- Y10T 442/197 . . . Including a nonwoven fabric which is not a scrim
- Y10T 442/198 . . . Coated or impregnated
- Y10T 442/20 . Coated or impregnated woven, knit, or nonwoven fabric which is not [a] associated with another preformed layer or fiber layer or, [b] with respect to woven and knit, characterized, respectively, by a particular or differential weave or knit, wherein the coating or impregnation is neither a foamed material nor a free metal or alloy layer
- Y10T 442/2008 . . Fabric composed of a fiber or strand which is of specific structural definition
- Y10T 442/2016 . . Impregnation is confined to a plane disposed between both major fabric surfaces which are essentially free of impregnating material
- Y10T 442/2025 . . Coating produced by extrusion
- Y10T 442/2033 . . Coating or impregnation formed in situ [e.g., by interfacial condensation, coagulation, precipitation, etc.]
- Y10T 442/2041 . . Two or more non-extruded coatings or impregnations
- Y10T 442/2049 . . . Each major face of the fabric has at least one coating or impregnation
- Y10T 442/2057 At least two coatings or impregnations of different chemical composition
- Y10T 442/2066 Different coatings or impregnations on opposite faces of the fabric
- Y10T 442/2074 At least one coating or impregnation contains particulate material
- Y10T 442/2082 At least one coating or impregnation functions to fix pigments or particles on the surface of a coating or impregnation
- Y10T 442/209 At least one coating or impregnation contains particulate material
- Y10T 442/2098 . . . At least two coatings or impregnations of different chemical composition
- Y10T 442/2107 At least one coating or impregnation contains particulate material
- Y10T 442/2115 At least one coating or impregnation functions to fix pigments or particles on the surface of a coating or impregnation
- Y10T 442/2123 . . . At least one coating or impregnation contains particulate material
- Y10T 442/2131 At least one coating or impregnation functions to fix pigments or particles on the surface of a coating or impregnation
- Y10T 442/2139 . . Coating or impregnation specified as porous or permeable to a specific substance [e.g., water vapor, air, etc.]
- Y10T 442/2148 . . . Coating or impregnation is specified as microporous but is not a foam

Y10T 442/2156	. . Coating or impregnation collects radionuclide or heavy metal
Y10T 442/2164	. . Coating or impregnation specified as water repellent
Y10T 442/2172	. . . Also specified as oil repellent
Y10T 442/218	. . . Organosilicon containing
Y10T 442/2189	. . . Fluorocarbon containing
Y10T 442/2197	. . . Nitrogen containing
Y10T 442/2205	. . . Natural oil or wax containing
Y10T 442/2213	. . Coating or impregnation is specified as weather proof, water vapor resistant, or moisture resistant
Y10T 442/2221	. . Coating or impregnation is specified as water proof
Y10T 442/223	. . . Organosilicon containing
Y10T 442/2238	. . . Fluorocarbon containing
Y10T 442/2246	. . . Nitrogen containing
Y10T 442/2254	. . . Natural oil or wax containing
Y10T 442/2262	. . Coating or impregnation is oil repellent but not oil or stain release
Y10T 442/227	. . . Fluorocarbon containing
Y10T 442/2279	. . Coating or impregnation improves soil repellency, soil release, or anti- soil redeposition qualities of fabric
Y10T 442/2287	. . . Fluorocarbon containing
Y10T 442/2295	. . . Linear polyether group chain containing
Y10T 442/2303	. . Coating or impregnation provides a fragrance or releases an odor intended to be perceptible to humans
Y10T 442/2311	. . Coating or impregnation is a lubricant or a surface friction reducing agent other than specified as improving the "hand" of the fabric or increasing the softness thereof
Y10T 442/232	. . . Fluorocarbon containing
Y10T 442/2328	. . . Organosilicon containing
Y10T 442/2336	. . . Natural oil or wax containing
Y10T 442/2344	. . Coating or impregnation is anti-slip or friction-increasing other than specified as an abrasive
Y10T 442/2352	. . Coating or impregnation functions to soften the feel of or improve the "hand" of the fabric
Y10T 442/2361	. . Coating or impregnation improves stiffness of the fabric other than specified as a size
Y10T 442/2369	. . Coating or impregnation improves elasticity, bendability, resiliency, flexibility, or shape retention of the fabric
Y10T 442/2377	. . . Improves elasticity
Y10T 442/2385	. . . Improves shrink resistance
Y10T 442/2393	. . . Coating or impregnation provides crease-resistance or wash and wear characteristics
Y10T 442/2402	. . Coating or impregnation specified as a size
Y10T 442/241	. . Coating or impregnation improves snag or pull resistance of the fabric
Y10T 442/2418	. . Coating or impregnation increases electrical conductivity or anti-static quality

Y10T 442/2426	. . .	Elemental carbon containing
Y10T 442/2434	. . .	Linear polyether group chain containing
Y10T 442/2443	. . .	Nitrogen and phosphorus containing
Y10T 442/2451	. . .	Phosphorus containing
Y10T 442/2459	. . .	Nitrogen containing
Y10T 442/2467	. . .	Sulphur containing
Y10T 442/2475	. .	Coating or impregnation is electrical insulation-providing, -improving, or -increasing, or conductivity-reducing
Y10T 442/2484	. .	Coating or impregnation is water absorbency-increasing or hydrophilicity-increasing or hydrophilicity-imparting
Y10T 442/2492	. . .	Polyether group containing
Y10T 442/25	. .	Coating or impregnation absorbs sound
Y10T 442/2508	. .	Coating or impregnation absorbs chemical material other than water
Y10T 442/2516	. . .	Chemical material is one used in biological or chemical warfare
Y10T 442/2525	. .	Coating or impregnation functions biologically [e.g., insect repellent, antiseptic, insecticide, bactericide, etc.]
Y10T 442/2533	. . .	Inhibits mildew
Y10T 442/2541	. . .	Insect repellent
Y10T 442/2549	. .	Coating or impregnation is chemically inert or of stated nonreactance
Y10T 442/2557	. . .	Oxygen or ozone resistant
Y10T 442/2566	. . .	Organic solvent resistant [e.g., dry cleaning fluid, etc.]
Y10T 442/2574	. . .	Acid or alkali resistant
Y10T 442/2582	. .	Coating or impregnation contains an optical bleach or brightener or functions as an optical bleach or brightener [e.g., it masks fabric yellowing, etc.]
Y10T 442/259	. .	Coating or impregnation provides protection from radiation [e.g., U.V., visible light, I.R., micscheme-change-itemave, high energy particle, etc.] or heat retention thru radiation absorption
Y10T 442/2598	. . .	Radiation reflective
Y10T 442/2607	. . .	Radiation absorptive
Y10T 442/2615	. .	Coating or impregnation is resistant to penetration by solid implements
Y10T 442/2623	. . .	Ballistic resistant
Y10T 442/2631	. .	Coating or impregnation provides heat or fire protection
Y10T 442/2639	. . .	Coated or impregnated asbestos fabric
Y10T 442/2648	. . .	Coating or impregnation is specified as an intumescent material
Y10T 442/2656	. . .	Antimony containing
Y10T 442/2664	. . .	Boron containing
Y10T 442/2672	. . .	Phosphorus containing
Y10T 442/268	Phosphorus and nitrogen containing compound
Y10T 442/2689	A phosphorus containing compound and a nitrogen containing compound
Y10T 442/2697	Phosphorus and halogen containing compound
Y10T 442/2705	A phosphorus containing compound and a halogen containing compound
Y10T 442/2713	. . .	Halogen containing

Y10T 442/2721	. . . Nitrogen containing
Y10T 442/273	. . Coating or impregnation provides wear or abrasion resistance
Y10T 442/2738	. . Coating or impregnation intended to function as an adhesive to solid surfaces subsequently associated therewith
Y10T 442/2746	. . . Heat-activatable adhesive
Y10T 442/2754	. . . Pressure-sensitive adhesive
Y10T 442/2762	. . Coated or impregnated natural fiber fabric [e.g., cotton, wool, silk, linen, etc.]
Y10T 442/277	. . . Coated or impregnated cellulosic fiber fabric
Y10T 442/2779 Coating or impregnation contains an acrylic polymer or copolymer [e.g., polyacrylonitrile, polyacrylic acid, etc.]
Y10T 442/2787 Coating or impregnation contains a vinyl polymer or copolymer
Y10T 442/2795 Coating or impregnation contains an epoxy polymer or copolymer or polyether
Y10T 442/2803 Polymeric coating or impregnation from a silane or siloxane not specified as lubricant or water repellent
Y10T 442/2811 Coating or impregnation contains polyimide or polyamide
Y10T 442/282 Coating or impregnation contains natural gum, rosin, natural oil, or wax
Y10T 442/2828 Coating or impregnation contains aldehyde or ketone condensation product
Y10T 442/2836 Phenol-aldehyde condensate
Y10T 442/2844 Melamine-aldehyde condensate
Y10T 442/2852 Amide-aldehyde condensate [e.g., modified urea-aldehyde condensate, etc.]
Y10T 442/2861	. . Coated or impregnated synthetic organic fiber fabric
Y10T 442/2869	. . . Coated or impregnated regenerated cellulose fiber fabric
Y10T 442/2877	. . . Coated or impregnated polyvinyl alcohol fiber fabric
Y10T 442/2885	. . . Coated or impregnated acrylic fiber fabric
Y10T 442/2893	. . . Coated or impregnated polyamide fiber fabric
Y10T 442/2902 Aromatic polyamide fiber fabric
Y10T 442/291	. . . Coated or impregnated polyolefin fiber fabric
Y10T 442/2918 Polypropylene fiber fabric
Y10T 442/2926	. . Coated or impregnated inorganic fiber fabric
Y10T 442/2934	. . . Coating or impregnation contains vinyl polymer or copolymer
Y10T 442/2943 Vinyl acetate polymer or copolymer
Y10T 442/2951	. . . Coating or impregnation contains epoxy polymer or copolymer or polyether
Y10T 442/2959	. . . Coating or impregnation contains aldehyde or ketone condensation product
Y10T 442/2967 Amide-aldehyde condensate
Y10T 442/2975	. . . Coated or impregnated ceramic fiber fabric
Y10T 442/2984	. . . Coated or impregnated carbon or carbonaceous fiber fabric
Y10T 442/2992	. . . Coated or impregnated glass fiber fabric
Y10T 442/30	. Woven fabric [i.e., woven strand or strip material]
Y10T 442/3008	. . Woven fabric has an elastic quality

Y10T 442/3016	. . .	Including a preformed layer other than the elastic woven fabric [e.g., fabric or film or foil or sheet layer, etc.]
Y10T 442/3024	. . .	Including elastic strand or strip
Y10T 442/3033	. .	Including a strip or ribbon
Y10T 442/3041	. . .	Woven fabric comprises strips or ribbons only
Y10T 442/3049	. .	Including strand precoated with other than free metal or alloy
Y10T 442/3057	. . .	Multiple coatings
Y10T 442/3065	. .	Including strand which is of specific structural definition
Y10T 442/3073	. . .	Strand material is core-spun [not sheath-core bicomponent strand]
Y10T 442/3081	Core is synthetic polymeric material
Y10T 442/3089	. . .	Cross-sectional configuration of strand material is specified
Y10T 442/3098	Cross-sectional configuration varies longitudinally along the strand
Y10T 442/3106	Hollow strand material
Y10T 442/3114	Cross-sectional configuration of the strand material is other than circular
Y10T 442/3122	Cross-sectional configuration is multi-lobal
Y10T 442/313	. . .	Strand material formed of individual filaments having different chemical compositions
Y10T 442/3138	Including inorganic filament
Y10T 442/3146	. .	Strand material is composed of two or more polymeric materials in physically distinct relationship [e.g., sheath-core, side-by-side, islands-in-sea, fibrils-in-matrix, etc.] or composed of physical blend of chemically different polymeric materials or a physical blend of a polymeric material and a filler material
Y10T 442/3154	. . .	Sheath-core multicomponent strand material
Y10T 442/3163	. . .	Islands-in-sea multicomponent strand material
Y10T 442/3171	. . .	Strand material is a blend of polymeric material and a filler material
Y10T 442/3179	. .	Woven fabric is characterized by a particular or differential weave other than fabric in which the strand denier or warp/weft pick count is specified
Y10T 442/3187	. . .	Triaxially woven fabric
Y10T 442/3195	. . .	Three-dimensional weave [e.g., x-y-z planes, multi-planar warps and/or wefts, etc.]
Y10T 442/3203	Multi-planar warp layers
Y10T 442/3211	Multi-planar weft layers
Y10T 442/322	. . .	Warp differs from weft
Y10T 442/3228	Materials differ
Y10T 442/3236	Including inorganic strand material
Y10T 442/3244	Including natural strand material [e.g., cotton, wool, etc.]
Y10T 442/3252	Including synthetic polymeric strand material
Y10T 442/326	Including synthetic polymeric strand material
Y10T 442/3268	Including natural strand material
Y10T 442/3276	Including polyamide strand material
Y10T 442/3285	Including polyester strand material

Y10T 442/3293	. . .	Warp and weft are identical and contain at least two chemically different strand materials
Y10T 442/3301	. . .	Coated, impregnated, or autogenous bonded
Y10T 442/3309	Woven fabric contains inorganic strand material
Y10T 442/3317	Woven fabric contains synthetic polymeric strand material
Y10T 442/3325	. .	Including a foamed layer or component
Y10T 442/3333	. . .	Including a free metal or alloy constituent
Y10T 442/3341	. . .	Plural foam layers
Y10T 442/335	. . .	Plural fabric layers
Y10T 442/3358	Including a nonwoven fabric layer
Y10T 442/3366	. . .	Woven fabric is coated, impregnated, or autogenously bonded
Y10T 442/3374	Coating or impregnation includes particulate material other than fiber
Y10T 442/3382	. .	Including a free metal or alloy constituent
Y10T 442/339	. . .	Metal or metal-coated strand
Y10T 442/3398	. . .	Vapor or sputter deposited metal layer
Y10T 442/3407	. . .	Chemically deposited metal layer [e.g., chemical precipitation or electrochemical deposition or plating, etc.]
Y10T 442/3415	. . .	Preformed metallic film or foil or sheet [film or foil or sheet had structural integrity prior to association with the woven fabric]
Y10T 442/3423	Plural metallic films or foils or sheets
Y10T 442/3431	Plural fabric layers
Y10T 442/3439	Including a nonwoven fabric layer
Y10T 442/3447	Including a preformed synthetic polymeric film or sheet [i.e., film or sheet having structural integrity prior to association with the woven fabric]
Y10T 442/3455	Including particulate material other than fiber
Y10T 442/3463	. . .	Plural fabric layers
Y10T 442/3472	. .	Woven fabric including an additional woven fabric layer
Y10T 442/348	. . .	Mechanically needled or hydroentangled
Y10T 442/3488	Four or more layers
Y10T 442/3496	Coated, impregnated, or autogenously bonded
Y10T 442/3504	. . .	Woven fabric layers comprise chemically different strand material
Y10T 442/3512	Three or more fabric layers
Y10T 442/352	One of which is a nonwoven fabric layer
Y10T 442/3528	. . .	Three or more fabric layers
Y10T 442/3537	One of which is a nonwoven fabric layer
Y10T 442/3545	Woven fabric layers impregnated with a blend of thermosetting and thermoplastic resins
Y10T 442/3553	Woven fabric layers impregnated with an organosilicon resin
Y10T 442/3561	Woven fabric layers impregnated with a natural or synthetic rubber
Y10T 442/3569	Woven fabric layers impregnated with a thermosetting resin
Y10T 442/3577	Phenolic resin

Y10T 442/3585	Epoxy resin
Y10T 442/3594	Woven fabric layers impregnated with a thermoplastic resin [e.g., vinyl polymer, etc.]
Y10T 442/3602	Three or more distinct layers
Y10T 442/361	At least one layer is derived from water-settable material [e.g., cement, gypsum, etc.]
Y10T 442/3618	At least one layer contains wood or cork
Y10T 442/3626	At least one layer contains bituminous material [e.g., tar, pitch, asphalt, etc.]
Y10T 442/3634	At least one layer comprises paper
Y10T 442/3642	At least one layer contains natural or synthetic rubber
Y10T 442/365	At least one layer is a preformed synthetic polymeric film or sheet
Y10T 442/3659	At least one layer comprises ceramic or glass material in other than particulate form
Y10T 442/3667	Composite consisting of at least two woven fabrics bonded by an interposed adhesive layer [but not two woven fabrics bonded together by an impregnation which penetrates through the thickness of at least one of the woven fabric layers]
Y10T 442/3675	Fabric layer contains natural strand material
Y10T 442/3683	Fabric layer contains carbon or carbonaceous strand material
Y10T 442/3691	Fabric layer contains glass strand material
Y10T 442/3699	Including particulate material other than fiber
Y10T 442/3707	Woven fabric including a nonwoven fabric layer other than paper
Y10T 442/3715	Nonwoven fabric layer comprises parallel arrays of strand material
Y10T 442/3724	Needled
Y10T 442/3732	Including an additional nonwoven fabric
Y10T 442/374	Additional nonwoven fabric comprises chemically different strand material than the first nonwoven fabric
Y10T 442/3748	Including inorganic strand material
Y10T 442/3756	Nonwoven fabric layer comprises at least two chemically different fibers
Y10T 442/3764	Coated, impregnated, or autogenously bonded
Y10T 442/3772	Hydroentangled
Y10T 442/378	Coated, impregnated, or autogenously bonded
Y10T 442/3789	Plural nonwoven fabric layers
Y10T 442/3797	Coating or impregnation is derived from a water-settable material [e.g., cement, gypsum, etc.]
Y10T 442/3805	Coating or impregnation contains natural or synthetic rubber
Y10T 442/3813	Coating or impregnation contains synthetic polymeric material
Y10T 442/3821	Coating or impregnation contains bituminous material
Y10T 442/3829	Four or more layers
Y10T 442/3837	Including particulate material other than fiber
Y10T 442/3846	Including particulate material other than fiber
Y10T 442/3854	Woven fabric with a preformed polymeric film or sheet

- Y10T 442/3862 . . . Ester condensation polymer sheet or film [e.g., polyethylene terephthalate, etc.]
- Y10T 442/387 . . . Vinyl polymer or copolymer sheet or film [e.g., polyvinyl chloride, polyvinylidene chloride, polyvinyl acetate, etc.]
- Y10T 442/3878 . . . Fluorinated olefin polymer or copolymer sheet or film [e.g., Teflon®, etc.]
- Y10T 442/3886 . . . Olefin polymer or copolymer sheet or film [e.g., polypropylene, polyethylene, ethylene-butylene copolymer, etc.]
- Y10T 442/3894 . . . Amide condensation polymer sheet or film [e.g., nylon 6, etc.]
- Y10T 442/3902 . . . Polyimide sheet or film
- Y10T 442/3911 . . . Natural or synthetic rubber sheet or film
- Y10T 442/3919 . . . Including particulate material other than fiber
- Y10T 442/3927 . . . Including a paper or wood pulp layer
- Y10T 442/3935 . . . Mica paper layer
- Y10T 442/3943 . . . Plural paper or wood pulp layers
- Y10T 442/3951 . . . Including a bituminous layer
- Y10T 442/3959 . . . Including an outermost adhesive layer
- Y10T 442/3967 . . . Including a natural or synthetic rubber layer
- Y10T 442/3976 . . . Including strand which is stated to have specific attributes [e.g., heat or fire resistance, chemical or solvent resistance, high absorption for aqueous composition, water solubility, heat shrinkability, etc.]
- Y10T 442/3984 . . . Strand is other than glass and is heat or fire resistant
- Y10T 442/3992 . . . Strand is heat shrinkable
- Y10T 442/40 . . . Knit fabric [i.e., knit strand or strip material]
- Y10T 442/406 . . . Including parallel strips
- Y10T 442/413 . . . Including an elastic strand
- Y10T 442/419 . . . Including strand precoated with other than free metal or alloy
- Y10T 442/425 . . . Including strand which is of specific structural definition
- Y10T 442/431 . . . Cross-sectional configuration of strand material is specified
- Y10T 442/438 . . . Strand material formed of individual filaments having different chemical compositions
- Y10T 442/444 . . . Strand is a monofilament composed of two or more polymeric materials in physically distinct relationship [e.g., sheath-core, side-by-side, islands-in-sea, fibrils-in-matrix, etc.] or composed of physical blend of chemically different polymeric materials or a physical blend of a polymeric material and a filler material
- Y10T 442/45 . . . Knit fabric is characterized by a particular or differential knit pattern other than open knit fabric or a fabric in which the strand denier is specified
- Y10T 442/456 . . . Including additional strand inserted within knit fabric
- Y10T 442/463 Warp knit insert strand
- Y10T 442/469 . . . Including a foamed layer or component
- Y10T 442/475 . . . Including a free metal or alloy constituent
- Y10T 442/481 . . . Chemically deposited metal layer [e.g., chemical precipitation or electrochemical deposition or plating, etc.]
- Y10T 442/488 . . . Including an additional knit fabric layer
- Y10T 442/494 . . . Including a nonwoven fabric layer other than paper

Y10T 442/50	. FELT FABRIC
Y10T 442/51	. . From natural organic fiber [e.g., wool, etc.]
Y10T 442/53	. . . Including particulate material other than fiber
Y10T 442/54	. . . At least three layers
Y10T 442/56	. . From synthetic organic fiber
Y10T 442/57	. . Including particulate material other than fiber
Y10T 442/59	. . At least three layers
Y10T 442/60	. Nonwoven fabric [i.e., nonwoven strand or fiber material]
Y10T 442/601	. . Nonwoven fabric has an elastic quality
Y10T 442/602	. . . Nonwoven fabric comprises an elastic strand or fiber material
Y10T 442/603	. . Including strand or fiber material precoated with other than free metal or alloy
Y10T 442/604	. . . Strand or fiber material is glass
Y10T 442/605	. . . Strand or fiber material is inorganic
Y10T 442/607	. . . Strand or fiber material is synthetic polymer
Y10T 442/608	. . Including strand or fiber material which is of specific structural definition
Y10T 442/609	. . . Cross-sectional configuration of strand or fiber material is specified
Y10T 442/61 Cross-sectional configuration varies longitudinally along strand or fiber material
Y10T 442/611 Cross-sectional configuration of strand or fiber material is other than circular
Y10T 442/612 Hollow strand or fiber material
Y10T 442/613 Microcellular strand or fiber material
Y10T 442/614	. . . Strand or fiber material specified as having micro dimensions [i.e., microfiber]
Y10T 442/615 Strand or fiber material is blended with another chemically different microfiber in the same layer
Y10T 442/616 Blend of synthetic polymeric and inorganic microfibers
Y10T 442/618 Blend of chemically different inorganic microfibers
Y10T 442/619 Including other strand or fiber material in the same layer not specified as having micro dimensions
Y10T 442/62 Including another chemically different microfiber in a separate layer
Y10T 442/621 Including other strand or fiber material in a different layer not specified as having micro dimensions
Y10T 442/622 Microfiber is a composite fiber
Y10T 442/623 Microfiber is glass
Y10T 442/624 Microfiber is carbon or carbonaceous
Y10T 442/625 Autogenously bonded
Y10T 442/626 Microfiber is synthetic polymer
Y10T 442/627	. . . Strand or fiber material is specified as non-linear [e.g., crimped, coiled, etc.]
Y10T 442/629 Composite strand or fiber material
Y10T 442/63 Carbon or carbonaceous strand or fiber material
Y10T 442/631 Glass strand or fiber material

Y10T 442/632 A single nonwoven layer comprising non-linear synthetic polymeric strand or fiber material and strand or fiber material not specified as non-linear
Y10T 442/633 Synthetic polymeric strand or fiber material is of staple length
Y10T 442/634 A nonwoven fabric having a layer comprising non-linear synthetic polymeric strand or fiber material and a separate and distinct layer comprising strand or fiber material which is not specified as non-linear
Y10T 442/635 Synthetic polymeric strand or fiber material
Y10T 442/636 Synthetic polymeric strand or fiber material is of staple length
Y10T 442/637	. . Including strand or fiber material which is a monofilament composed of two or more polymeric materials in physically distinct relationship [e.g., sheath-core, side-by-side, islands-in-sea, fibrils-in-matrix, etc.] or composed of physical blend of chemically different polymeric materials or a physical blend of a polymeric material and a filler material
Y10T 442/638	. . . Side-by-side multicomponent strand or fiber material
Y10T 442/64	. . . Islands-in-sea multicomponent strand or fiber material
Y10T 442/641	. . . Sheath-core multicomponent strand or fiber material
Y10T 442/642	. . . Strand or fiber material is a blend of polymeric material and a filler material
Y10T 442/643	. . Including parallel strand or fiber material within the nonwoven fabric
Y10T 442/644	. . . Parallel strand or fiber material is glass
Y10T 442/645	. . . Parallel strand or fiber material is inorganic [e.g., rock wool, mineral wool, etc.]
Y10T 442/646	. . . Parallel strand or fiber material is naturally occurring [e.g., cotton, wool, etc.]
Y10T 442/647	. . Including a foamed layer or component
Y10T 442/648	. . . Including a free metal or alloy constituent
Y10T 442/649	. . . Plural foamed layers
Y10T 442/651	. . . Plural fabric layers
Y10T 442/652	. . . Nonwoven fabric is coated, impregnated, or autogenously bonded
Y10T 442/653 Including particulate material other than fiber
Y10T 442/654	. . Including a free metal or alloy constituent
Y10T 442/655	. . . Metal or metal-coated strand or fiber material
Y10T 442/656	. . . Preformed metallic film or foil or sheet [film or foil or sheet had structural integrity prior to association with the nonwoven fabric]
Y10T 442/657	. . . Vapor, chemical, or spray deposited metal layer
Y10T 442/658	. . . Particulate free metal or alloy constituent
Y10T 442/659	. . Including an additional nonwoven fabric
Y10T 442/66	. . . Additional nonwoven fabric is a spun-bonded fabric
Y10T 442/662 Needled
Y10T 442/663 Hydroentangled
Y10T 442/664	. . . Including a wood fiber containing layer
Y10T 442/665	. . . Including a layer derived from a water-settable material [e.g., cement, gypsum, etc.]
Y10T 442/666	. . . Mechanically interengaged by needling or impingement of fluid [e.g., gas or liquid stream, etc.]
Y10T 442/667 Needled

- Y10T 442/668 . . . Separate nonwoven fabric layers comprise chemically different strand or fiber material
- Y10T 442/669 At least one layer of inorganic strand or fiber material and at least one layer of synthetic polymeric strand or fiber material
- Y10T 442/67 . . . Multiple nonwoven fabric layers composed of the same inorganic strand or fiber material
- Y10T 442/671 . . . Multiple nonwoven fabric layers composed of the same polymeric strand or fiber material
- Y10T 442/673 . . . Including particulate material other than fiber
- Y10T 442/674 . . Nonwoven fabric with a preformed polymeric film or sheet
- Y10T 442/675 . . . Ester condensation polymer sheet or film [e.g., polyethylene terephthalate, etc.]
- Y10T 442/676 . . . Vinyl polymer or copolymer sheet or film [e.g., polyvinyl chloride, polyvinylidene chloride, polyvinyl acetate, etc.]
- Y10T 442/677 . . . Fluorinated olefin polymer or copolymer sheet or film [e.g., TeflonR, etc.]
- Y10T 442/678 . . . Olefin polymer or copolymer sheet or film [e.g., polypropylene, polyethylene, ethylene-butylene copolymer, etc.]
- Y10T 442/679 . . . Natural or synthetic rubber sheet or film
- Y10T 442/68 . . Melt-blown nonwoven fabric
- Y10T 442/681 . . Spun-bonded nonwoven fabric
- Y10T 442/682 . . Needled nonwoven fabric
- Y10T 442/684 . . . Containing at least two chemically different strand or fiber materials
- Y10T 442/685 Containing inorganic and polymeric strand or fiber materials
- Y10T 442/686 Containing polymeric and natural strand or fiber materials
- Y10T 442/687 Containing inorganic strand or fiber material
- Y10T 442/688 Containing polymeric strand or fiber material
- Y10T 442/689 . . Hydroentangled nonwoven fabric
- Y10T 442/69 . . Autogenously bonded nonwoven fabric
- Y10T 442/691 . . . Inorganic strand or fiber material only
- Y10T 442/692 . . . Containing at least two chemically different strand or fiber materials
- Y10T 442/693 . . Including a paper layer
- Y10T 442/695 . . Including a wood containing layer
- Y10T 442/696 . . Including strand or fiber material which is stated to have specific attributes [e.g., heat or fire resistance, chemical or solvent resistance, high absorption for aqueous compositions, water solubility, heat shrinkability, etc.]
- Y10T 442/697 . . Containing at least two chemically different strand or fiber materials
- Y10T 442/698 . . . Containing polymeric and natural strand or fiber materials
- Y10T 442/699 . . Including particulate material other than strand or fiber material

Former US Class 464 Series

- Y10T 464/00 **Rotary shafts, gudgeons, housings, and flexible couplings for rotary shafts**
- Y10T 464/10 . having heating or cooling means

- Y10T 464/20 . with auxilliary indicator or alarm
- Y10T 464/30 . Electrical or magnetic coupling
- Y10T 464/40 . Coupling accommodates drive between members having misaligned or angularly related axes, transmits torque via radially directed pin, and has particular balancing means
- Y10T 464/50 . Shafting having particular vibration dampening or balancing structure

Former US Class 477 Series

- | | |
|--------------------|---|
| Y10T 477/00 | Interrelated power delivery controls, including engine control |
| Y10T 477/10 | . Steering by driving |
| Y10T 477/20 | . Plural engines |
| Y10T 477/23 | . . Electric engine |
| Y10T 477/24 | . . . with brake control |
| Y10T 477/26 | . . . with clutch control |
| Y10T 477/27 | . . with clutch control |
| Y10T 477/30 | . Electric engine |
| Y10T 477/32 | . . with clutch control |
| Y10T 477/322 | . . . with brake control |
| Y10T 477/3225 | Stopped at end of cycle |
| Y10T 477/323 | . . . Engine stopped at end of cycle |
| Y10T 477/325 | . . . Common controller |
| Y10T 477/327 | . . . Electric clutch |
| Y10T 477/328 | . . . Speed responsive |
| Y10T 477/33 | . . with transmission control |
| Y10T 477/333 | . . . Load motion limit control |
| Y10T 477/337 | . . . Transmission change by moving engine |
| Y10T 477/34 | . . . Reversible engine |
| Y10T 477/343 | . . . Engine starting interlock |
| Y10T 477/347 | . . . Condition responsive engine control |
| Y10T 477/35 | . . Brake engaged when engine energy deactivated, brake disengaged when engine energy activated |
| Y10T 477/357 | . . . Cam actuated brake |
| Y10T 477/363 | . . . Electrically actuated brake |
| Y10T 477/37 | . . Brake actuation opens switch to engine |
| Y10T 477/373 | . . . Electrically actuated brake |
| Y10T 477/377 | . . . Fluid actuated brake |
| Y10T 477/38 | . . Control means selectively operates engine energy input and brake |
| Y10T 477/387 | . . . Fluid actuated brake |
| Y10T 477/393 | . . . Electrically actuated brake |
| Y10T 477/40 | . Gas turbine engine |

Y10T 477/45	. . Continuously variable transmission
Y10T 477/50	. with supercharger
Y10T 477/55	. . Manifold pressure control
Y10T 477/60	. Transmission control
Y10T 477/606	. . Differential transmission
Y10T 477/613	. . Plural outputs
Y10T 477/619	. . Continuously variable friction transmission
Y10T 477/6197	. . . with fluid drive
Y10T 477/6203	. . . with clutch control
Y10T 477/621	. . . with brake control
Y10T 477/6217	. . . Interrelated control of diverse transmissions
Y10T 477/6223	. . . Constant speed output
Y10T 477/623	. . . Controlled by engine map
Y10T 477/6237	. . . Belt-type
Y10T 477/624 Fluid pressure control
Y10T 477/6242 Ratio change controlled
Y10T 477/62423 Engine coast braking
Y10T 477/62427 with electric valve control
Y10T 477/62429 Duty ratio control
Y10T 477/6243	. . . Fluid pressure control
Y10T 477/625	. . Fluid resistance inhibits rotation of planetary transmission element
Y10T 477/631	. . including fluid drive
Y10T 477/633	. . . Impeller-turbine-type
Y10T 477/6333 Engine controlled
Y10T 477/6337 with countershaft gearing
Y10T 477/63378 and turbine shaft brake
Y10T 477/63385 and clutch control
Y10T 477/63393 Control of or by fluid drive
Y10T 477/634 with hydrodynamic braking
Y10T 477/6343 with nonratio brake
Y10T 477/6347 Control responsive to fluid drive
Y10T 477/635 with clutch control
Y10T 477/6351 Disengaged during shift
Y10T 477/6352 Speed responsive
Y10T 477/63525 Electrical
Y10T 477/6353 with fluid unit vane control
Y10T 477/6357 Fill and empty-type fluid units
Y10T 477/636	. . . Ratio control
Y10T 477/637 with planetary transmission control
Y10T 477/638	. . with clutch control

Y10T 477/6388	. . .	and brake control
Y10T 477/6389	Temperature responsive control
Y10T 477/639	Engine controlled
Y10T 477/6392	Clutch controlled
Y10T 477/6394	Gearing controlled
Y10T 477/6395	. . .	Temperature responsive control
Y10T 477/6403	. . .	Clutch, engine, and transmission controlled
Y10T 477/6407	Electronic digital control
Y10T 477/641	. . .	Clutch and transmission controlled
Y10T 477/6414	Speed responsive control
Y10T 477/6415	with manual override
Y10T 477/6417	Vacuum actuated clutch
Y10T 477/6418	. . .	Clutch and engine controlled
Y10T 477/6422	Speed responsive control
Y10T 477/6424	Plural speed signals
Y10T 477/6425	. . .	Clutch controlled
Y10T 477/6428	Electric clutch
Y10T 477/643	Vacuum actuated clutch
Y10T 477/6432	Electric control
Y10T 477/6433	. . .	Engine controlled
Y10T 477/6437	Speed responsive
Y10T 477/644	. .	with brake control
Y10T 477/646	. . .	Anti-creep
Y10T 477/647	. . .	Brake controls transmission
Y10T 477/648	Pressure controlled
Y10T 477/649	. . .	One control blocks another
Y10T 477/65	. .	Control by sensed ambient condition, pattern indicia, external signal, or temperature
Y10T 477/653	. . .	Temperature control
Y10T 477/656	. .	Engine starting interlock
Y10T 477/663	. .	Exhaust emission control
Y10T 477/669	. .	Engine ignition control for transmission change
Y10T 477/67	. . .	Ignition advanced or retarded
Y10T 477/671	. . .	Ignition intermitting and safety means limiting duration of intermission
Y10T 477/673	. . .	Ignition intermitting controlled by manifold pressure
Y10T 477/674	. . .	Ignition intermitting initiated by positioning accelerator
Y10T 477/6745	Initiation inhibited by sensed condition
Y10T 477/675	. .	Engine controlled by transmission
Y10T 477/676	. . .	Constant output shaft speed
Y10T 477/677	. . .	Diminution during transmission change

Y10T 477/679	. . .	Responsive to transmission output condition
Y10T 477/68	. . .	Transmission setting contingent
Y10T 477/6805	Change to neutral idles engine
Y10T 477/6808	Engine input variable in neutral
Y10T 477/681	. .	Anticreep
Y10T 477/688	. .	Transmission controlled by engine
Y10T 477/689	. . .	Shift from neutral shock control
Y10T 477/6895	Pressure controlled
Y10T 477/69	. . .	Engine [coast] braking
Y10T 477/691	Electric valve control
Y10T 477/692	. . .	by acceleration
Y10T 477/693	. . .	by input manifold pressure or engine fuel control
Y10T 477/6931	Selector-type
Y10T 477/6933	with positive shift means
Y10T 477/69335	with synchronization
Y10T 477/6934	Prevents unsafe or unintentional shift
Y10T 477/6935	Reverse inhibitor
Y10T 477/6936	Shift valve control
Y10T 477/69362	Hysteresis
Y10T 477/693625	Electric control
Y10T 477/69363	Plural shift valves
Y10T 477/693635	Electric control
Y10T 477/693636	Downshift control
Y10T 477/693637	Kickdown
Y10T 477/693638	Selector valve overrule
Y10T 477/69364	Downshift control
Y10T 477/693643	Kickdown
Y10T 477/693645	Selector valve overrule
Y10T 477/69365	Electric control
Y10T 477/69366	Downshift control
Y10T 477/69367	Downshift control
Y10T 477/693675	Kickdown
Y10T 477/69368	Selector valve overrule
Y10T 477/6937	Servo motor timing
Y10T 477/69373	Downshift
Y10T 477/693738	with fluid accumulator
Y10T 477/693742	Electric valve control
Y10T 477/693746	Double acting servo
Y10T 477/693754	Speed responsive control
Y10T 477/693762	Electric valve control

Y10T 477/69377	with fluid accumulator
Y10T 477/69378	Engine parameter controls back pressure
Y10T 477/69379	Electric valve control
Y10T 477/6938	Double acting servo
Y10T 477/69383	Speed responsive control
Y10T 477/69387	Electric valve control
Y10T 477/6939	Transmission pressure controlled
Y10T 477/69393	Variable capacity pump
Y10T 477/69395	Line pressure controlled
Y10T 477/693958	Responsive to speed
Y10T 477/693962	Electric valve control
Y10T 477/693964	Duty ratio control
Y10T 477/693965	Transmission setting contingent
Y10T 477/693973	Electric valve control
Y10T 477/69398	Electric valve control
Y10T 477/694	. .	Engine control linkage mounted on manual gearshift lever
Y10T 477/70	. .	Clutch control
Y10T 477/71	. .	with starter
Y10T 477/73	. .	with fluid drive
Y10T 477/735	. . .	Speed responsive control
Y10T 477/74	. .	with brake control
Y10T 477/743	. . .	Clutch controlled
Y10T 477/745	and brake controlled
Y10T 477/747	. . .	Engine controlled
Y10T 477/75	. .	Condition responsive control
Y10T 477/753	. . .	Speed responsive
Y10T 477/755	Slip rate control
Y10T 477/757	. . .	Overload release
Y10T 477/759	Engine shut off
Y10T 477/76	. .	Electric clutch
Y10T 477/78	. .	Regulated clutch engagement
Y10T 477/79	. .	Engine controlled by clutch control
Y10T 477/80	. .	Brake control
Y10T 477/81	. .	Sensed condition responsive control of engine of brake
Y10T 477/813	. . .	Brake
Y10T 477/814	and engine
Y10T 477/816	Speed or acceleration responsive
Y10T 477/817	. . .	Speed or acceleration responsive
Y10T 477/82	. .	Plural diverse brake means

- Y10T 477/83 . . Engine energy control having adjusting and holding device, with means on brake control to override holding device
- Y10T 477/833 . . . Holding device engaged by electric means
- Y10T 477/835 Magnetic holding device
- Y10T 477/837 . . . Mechanical holding device engaged by mechanical means
- Y10T 477/839 Device or means including a threaded shaft, rack or ratchet
- Y10T 477/84 . . Brake control having holding device, with means on engine control to override holding device
- Y10T 477/847 . . . Holding device responsive to motion, speed or acceleration
- Y10T 477/85 Holding device comprising brake valve operated by solenoid
- Y10T 477/853 . . . Holding device engaged by electric means
- Y10T 477/857 Holding device comprising brake valve operated by solenoid
- Y10T 477/86 . . Brake engaged when engine energy deactivated, brake disengaged when engine energy is activated
- Y10T 477/865 . . . Internal combustion engine
- Y10T 477/868 Controls brake valve
- Y10T 477/869 Vacuum actuated brake
- Y10T 477/87 . . Brake condition change modifies engine condition
- Y10T 477/873 . . . Brake actuation interrupts ignition circuit of fluid engine
- Y10T 477/877 . . . Brake actuation decreases or eliminates fluid energy input to engine
- Y10T 477/878 by closing throttle valve
- Y10T 477/879 by preventing increasing operation of engine energy control
- Y10T 477/88 . . Decreasing fluid energy input to engine actuates brake
- Y10T 477/89 . . Control means selectively operates engine energy input and brake
- Y10T 477/893 . . . Foot operated control means
- Y10T 477/8936 Engine and brake control including interconnected elements
- Y10T 477/8941 Pivots and translates
- Y10T 477/8944 Pivots about intermediate fulcrum
- Y10T 477/8947 Pivots about two fulcrums
- Y10T 477/8953 Pivots about intermediate fulcrum
- Y10T 477/8959 Lever reciprocates on moveable supports at both ends
- Y10T 477/8964 Pivots for sequential operation
- Y10T 477/897 . . . Control means including fluid passage

Former US Class 483 Series

- Y10T 483/00** **Tool changing**
- Y10T 483/10 . Process
- Y10T 483/11 . with safety means
- Y10T 483/115 . . Guard

- Y10T 483/12 . with means to regulate operation by means of replaceable information supply [e.g. ,
templet, tape, card, etc.]
- Y10T 483/123 . . Replaceable information comprising tool location
- Y10T 483/127 . . . including determining optimum tool access path
- Y10T 483/13 . with control means energized in response to activator stimulated by condition sensor
- Y10T 483/132 . . Responsive to tool identifying information
- Y10T 483/134 . . . Identifying information on tool or tool holder
- Y10T 483/136 . . Responsive to tool
- Y10T 483/138 . . . including means to monitor and control, i.e., adaptive machining
- Y10T 483/14 . with signal or indicator
- Y10T 483/15 . with means to condition or adjust tool or tool support
- Y10T 483/16 . with means to transfer work
- Y10T 483/165 . . Plural machine tools, e.g., flexible manufacturing
- Y10T 483/17 . including machine tool or component
- Y10T 483/1702 . . Rotating work machine tool [e.g., screw machine, lathe, etc.]
- Y10T 483/1705 . . . Tool support comprises rotary spindle
- Y10T 483/1707 . . . Tool having specific mounting or work treating feature
- Y10T 483/171 Workpiece holder [e.g., chuck or chuck jaw, collet, etc.]
- Y10T 483/1712 Turning tool insert changer
- Y10T 483/1714 . . . Tool changer between tool support and matrix
- Y10T 483/1717 Plural matrices
- Y10T 483/1719 Tool support comprises turret
- Y10T 483/1721 Linearly moveable tool changer
- Y10T 483/1724 Linearly moveable tool changer
- Y10T 483/1726 . . . Direct tool exchange between tool support and matrix
- Y10T 483/1729 . . Reciprocating tool machine tool [e.g., broaching machine, shaping machine, etc.]
- Y10T 483/1731 . . . including matrix
- Y10T 483/1733 . . Rotary spindle machine tool [e.g., milling machine, boring, machine, grinding
machine, etc.]
- Y10T 483/1736 . . . Tool having specific mounting or work treating feature
- Y10T 483/1738 Tool head
- Y10T 483/174 Abrading wheel
- Y10T 483/1743 including means for angularly orienting tool and spindle
- Y10T 483/1745 Spindle angularly oriented to align with tool
- Y10T 483/1748 . . . Tool changer between spindle and matrix
- Y10T 483/175 Plural matrices
- Y10T 483/1752 including tool holder pivotable about axis
- Y10T 483/1755 Plural tool holders pivotable about common axis
- Y10T 483/1757 including intermediate tool changer
- Y10T 483/176 Intermediate tool changer includes tool holder pivotable about axis

Y10T 483/1762	Tool holders pivotable with respect to each other
Y10T 483/1764	Tool holders pivotable about plural nonparallel axes
Y10T 483/1767	Linearly movable tool holders
Y10T 483/1769	Extensible tool holders
Y10T 483/1771	Translatable axis
Y10T 483/1774	Distinct tool changer for each tool
Y10T 483/1776	including intermediate tool changer
Y10T 483/1779	Linearly movable tool holder
Y10T 483/1781	Tool holder pivotable about plural nonparallel axes
Y10T 483/1783	including linearly translatable tool changer [e.g., shuttle, ram, etc.]
Y10T 483/1786	Plural tool holders
Y10T 483/1788	Orthogonally translatable
Y10T 483/179	. . .	Direct tool exchange between spindle and matrix
Y10T 483/1793	Spindle comprises tool changer
Y10T 483/1795	Matrix indexes selected tool to transfer position
Y10T 483/1798	including means to project tool from matrix
Y10T 483/18	. . .	Tool transfer to or from matrix
Y10T 483/1809	. . .	Matrix including means to latch tool
Y10T 483/1818	. . .	Matrix including means to project tool for transfer
Y10T 483/1827	. . .	Rectilinear
Y10T 483/1836	. . .	Pivoting
Y10T 483/1845	. . .	Plural matrices
Y10T 483/1855	. . .	including tool replenishing
Y10T 483/1864	. . .	including tool pot or adapter
Y10T 483/1873	. . .	Indexing matrix
Y10T 483/1882	. . .	Rotary disc
Y10T 483/1891	. . .	Chain or belt
Y10T 483/19	. . .	Miscellaneous