

CPC COOPERATIVE PATENT CLASSIFICATION

H ELECTRICITY

(NOTE omitted)

H03 BASIC ELECTRONIC CIRCUITRY

H03L AUTOMATIC CONTROL, STARTING, SYNCHRONISATION, OR STABILISATION OF GENERATORS OF ELECTRONIC OSCILLATIONS OR PULSES (of dynamo-electric generators [H02P](#))

NOTES

1. This subclass covers:
 - automatic control circuits for generators of electronic oscillations or pulses;
 - starting, synchronisation, or stabilisation circuits for generators where the type of generator is irrelevant or unspecified.
2. This subclass does not cover stabilisation or starting circuits specially adapted to only one specific type of generator, which are covered by subclasses [H03B](#), [H03K](#).
3. In this subclass, the following expression is used with the meaning indicated:
 - "automatic control" covers only closed loop systems.

1/00	Stabilisation of generator output against variations of physical values, e.g. power supply (automatic control H03L 5/00, H03L 7/00)	7/07	• . using several loops, e.g. for redundant clock signal generation (for indirect frequency synthesis H03L 7/22)
1/02	• against variations of temperature only	7/08	• . Details of the phase-locked loop
1/021	• . {of generators comprising distributed capacitance and inductance}	7/0802	• . . {the loop being adapted for reducing power consumption (H03L 7/14 takes precedence)}
1/022	• . {by indirect stabilisation, i.e. by generating an electrical correction signal which is a function of the temperature (H03L 1/021 takes precedence)}	7/0805	• . . {the loop being adapted to provide an additional control signal for use outside the loop}
1/023	• . . {by using voltage variable capacitance diodes}	7/0807	• . . {concerning mainly a recovery circuit for the reference signal}
1/025	• . . . {and a memory for digitally storing correction values}	7/081	• . . provided with an additional controlled phase shifter {(H03L 7/0998 takes precedence)}
1/026	• . . {by using a memory for digitally storing correction values (H03L 1/025 takes precedence)}	7/0812	• . . . {and where no voltage or current controlled oscillator is used}
1/027	• . . {by using frequency conversion means which is variable with temperature, e.g. mixer, frequency divider, pulse add/subtract logic circuit (H03L 1/023 , H03L 1/026 take precedence)}	WARNING	
1/028	• . {of generators comprising piezo-electric resonators (H03L 1/021 and H03L 1/022 take precedence; oscillation generators with a piezo-electric resonator per se H03B 5/32)}	Group H03L 7/0812 is impacted by reclassification into groups H03L 7/0816 and H03L 7/0818 .	
1/04	• . Constructional details for maintaining temperature constant	Groups H03L 7/0812 , H03L 7/0816 and H03L 7/0818 should be considered in order to perform a complete search.	
3/00	Starting of generators	7/0814	• {the phase shifting device being digitally controlled}
5/00	Automatic control of voltage, current, or power	WARNING	
5/02	• of power	Group H03L 7/0814 is impacted by reclassification into groups H03L 7/0816 and H03L 7/0818 .	
7/00	Automatic control of frequency or phase; Synchronisation (tuning of resonant circuits in general H03J; synchronising in digital communication systems, see the relevant groups in class H04)	Groups H03L 7/0814 , H03L 7/0816 and H03L 7/0818 should be considered in order to perform a complete search.	
7/02	• using a frequency discriminator comprising a passive frequency-determining element		
7/04	• . wherein the frequency-determining element comprises distributed inductance and capacitance		
7/06	• using a reference signal applied to a frequency- or phase-locked loop		

- 7/0816 {the controlled phase shifter and the frequency- or phase-detection arrangement being connected to a common input}
- WARNING**
- Groups [H03L 7/0816](#) and [H03L 7/0818](#) are incomplete pending reclassification of documents from groups [H03L 7/0812](#) and [H03L 7/0814](#).
- Until reclassification is complete, groups [H03L 7/0816](#), [H03L 7/0818](#), [H03L 7/0812](#) and [H03L 7/0814](#) should be considered in order to perform a complete search.
- 7/0818 {the controlled phase shifter comprising coarse and fine delay or phase-shifting means}
- WARNING**
- Groups [H03L 7/0816](#) and [H03L 7/0818](#) are incomplete pending reclassification of documents from groups [H03L 7/0812](#) and [H03L 7/0814](#).
- Until reclassification is complete, groups [H03L 7/0816](#), [H03L 7/0818](#), [H03L 7/0812](#) and [H03L 7/0814](#) should be considered in order to perform a complete search.
- 7/083 . . . the reference signal being additionally directly applied to the generator ([direct frequency synchronisation without loop H03L 7/24](#))
- 7/085 . . . concerning mainly the frequency- or phase-detection arrangement including the filtering or amplification of its output signal ([H03L 7/10 takes precedence](#); frequency or phase detection comparison in general [H03D 3/00](#), [H03D 13/00](#))
- 7/087 using at least two phase detectors or a frequency and phase detector in the loop
- 7/089 the phase or frequency detector generating up-down pulses ([H03L 7/087 takes precedence](#))
- 7/0891 {the up-down pulses controlling source and sink current generators, e.g. a charge pump}
- 7/0893 {the up-down pulses controlling at least two source current generators or at least two sink current generators connected to different points in the loop}
- 7/0895 {Details of the current generators ([H03L 7/0893 takes precedence](#))}
- 7/0896 {the current generators being controlled by differential up-down pulses}
- 7/0898 {the source or sink current values being variable ([H03L 7/0896 takes precedence](#))}
- 7/091 the phase or frequency detector using a sampling device ([H03L 7/087 takes precedence](#))
- 7/093 using special filtering or amplification characteristics in the loop ([H03L 7/087](#) - [H03L 7/091 take precedence](#))
- 7/095 using a lock detector ([H03L 7/087 takes precedence](#))
- 7/097 using a comparator for comparing the voltages obtained from two frequency to voltage converters
- 7/099 . . . concerning mainly the controlled oscillator of the loop
- 7/0991 {the oscillator being a digital oscillator, e.g. composed of a fixed oscillator followed by a variable frequency divider ([H03L 7/0995 takes precedence](#); fixed oscillators with means for selecting among various phases [H03L 7/0814](#))}
- 7/0992 {comprising a counter or a frequency divider}
- 7/0993 {and a circuit for adding and deleting pulses}
- 7/0994 {comprising an accumulator}
- 7/0995 {the oscillator comprising a ring oscillator}
- 7/0996 {Selecting a signal among the plurality of phase-shifted signals produced by the ring oscillator}
- 7/0997 {Controlling the number of delay elements connected in series in the ring oscillator}
- 7/0998 {using phase interpolation}
- WARNING**
- Not complete, see also [H03L 7/0995](#)
- 7/10 . . . for assuring initial synchronisation or for broadening the capture range
- WARNING**
- Group [H03L 7/10](#) impacted by reclassification into groups [H03L 7/102](#), [H03L 7/103](#), [H03L 7/104](#) and [H03L 7/105](#).
- Groups [H03L 7/10](#), [H03L 7/102](#), [H03L 7/103](#), [H03L 7/104](#) and [H03L 7/105](#) should be considered in order to perform a complete search.
- 7/101 {using an additional control signal to the controlled loop oscillator derived from a signal generated in the loop ([H03L 7/113](#), [H03L 7/187 take precedence](#))}
- 7/102 {the additional signal being directly applied to the controlled loop oscillator}
- WARNING**
- Group [H03L 7/102](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
- Until reclassification is complete, groups [H03L 7/102](#) and [H03L 7/10](#) should be considered in order to perform a complete search.

- 7/103 {the additional signal being a digital signal}
WARNING
 Group [H03L 7/103](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
 Until reclassification is complete, groups [H03L 7/103](#) and [H03L 7/10](#) should be considered in order to perform a complete search.
- 7/104 {using an additional signal from outside the loop for setting or controlling a parameter in the loop ([H03L 7/107](#), [H03L 7/12](#) take precedence)}
WARNING
 Group [H03L 7/104](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
 Until reclassification is complete, groups [H03L 7/104](#) and [H03L 7/10](#) should be considered in order to perform a complete search.
- 7/105 {Resetting the controlled oscillator when its frequency is outside a predetermined limit}
WARNING
 Group [H03L 7/105](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
 Until reclassification is complete, groups [H03L 7/105](#) and [H03L 7/10](#) should be considered in order to perform a complete search.
- 7/107 using a variable transfer function for the loop, e.g. low pass filter having a variable bandwidth
WARNING
 Group [H03L 7/107](#) impacted by reclassification into groups [H03L 7/1072](#), [H03L 7/1075](#) and [H03L 7/1077](#).
 Groups [H03L 7/107](#), [H03L 7/1072](#), [H03L 7/1075](#) and [H03L 7/1077](#) should be considered in order to perform a complete search.
- 7/1072 {by changing characteristics of the charge pump, e.g. changing the gain}
WARNING
 Group [H03L 7/1072](#) is incomplete pending reclassification of documents from group [H03L 7/107](#).
 Until reclassification is complete, groups [H03L 7/1072](#) and [H03L 7/107](#) should be considered in order to perform a complete search.
- 7/1075 {by changing characteristics of the loop filter, e.g. changing the gain, changing the bandwidth ([H03L 7/1072](#) takes precedence)}
WARNING
 Group [H03L 7/1075](#) is incomplete pending reclassification of documents from group [H03L 7/107](#).
 Until reclassification is complete, groups [H03L 7/1075](#) and [H03L 7/107](#) should be considered in order to perform a complete search.
- 7/1077 {by changing characteristics of the phase or frequency detection means ([H03L 7/1072](#) takes precedence)}
WARNING
 Group [H03L 7/1077](#) is incomplete pending reclassification of documents from group [H03L 7/107](#).
 Until reclassification is complete, groups [H03L 7/1077](#) and [H03L 7/107](#) should be considered in order to perform a complete search.
- 7/113 using frequency discriminator
- 7/12 using a scanning signal ([tuning circuits with automatic scanning over a band of frequencies H03J 7/18](#))
- 7/14 for assuring constant frequency when supply or correction voltages fail {or are interrupted}
- 7/141 {the phase-locked loop controlling several oscillators in turn}
- 7/143 {by switching the reference signal of the phase-locked loop}
- 7/145 {the switched reference signal being derived from the controlled oscillator output signal}
- 7/146 {by using digital means for generating the oscillator control signal ([H03L 7/141](#), [H03L 7/143](#) take precedence)}
- 7/148 {said digital means comprising a counter or a divider}
- 7/16 Indirect frequency synthesis, i.e. generating a desired one of a number of predetermined frequencies using a frequency- or phase-locked loop
- 7/18 using a frequency divider or counter in the loop ([H03L 7/20](#), [H03L 7/22](#) take precedence)
- 7/1803 {the counter or frequency divider being connected to a cycle or pulse swallowing circuit}
- 7/1806 {the frequency divider comprising a phase accumulator generating the frequency divided signal}
- 7/181 a numerical count result being used for locking the loop, the counter counting during fixed time intervals {([H03L 7/1806](#) takes precedence)}
- 7/183 a time difference being used for locking the loop, the counter counting between fixed numbers or the frequency divider dividing by a fixed number {([H03L 7/1806](#) takes precedence)}

- 7/185 using a mixer in the loop
([H03L 7/187](#) - [H03L 7/195](#) take precedence)
- 7/187 using means for coarse tuning the voltage controlled oscillator of the loop ([H03L 7/191](#) - [H03L 7/195](#) take precedence)
- 7/189 comprising a D/A converter for generating a coarse tuning voltage
- 7/191 using at least two different signals from the frequency divider or the counter for determining the time difference ([H03L 7/193](#), [H03L 7/195](#) take precedence)
- 7/193 the frequency divider/counter comprising a commutable pre-divider, e.g. a two modulus divider ([pulse counters/frequency dividers H03K 21/00](#) - [H03K 29/00](#))
- 7/195 in which the counter of the loop counts between two different non zero numbers, e.g. for generating an offset frequency ([H03L 7/193](#) takes precedence; [pulse counters for predetermined counting H03K 21/00](#) - [H03K 29/00](#))
- 7/197 a time difference being used for locking the loop, the counter counting between numbers which are variable in time or the frequency divider dividing by a factor variable in time, e.g. for obtaining fractional frequency division { ([H03L 7/1806](#) takes precedence) }
- 7/1972 {for reducing the locking time interval ([H03L 7/1974](#), [H03L 7/199](#) take precedence) }
- 7/1974 {for fractional frequency division }
- 7/1976 {using a phase accumulator for controlling the counter or frequency divider }
- 7/1978 {using a cycle or pulse removing circuit }
- 7/199 with reset of the frequency divider or the counter, e.g. for assuring initial synchronisation
- 7/20 using a harmonic phase-locked loop, i.e. a loop which can be locked to one of a number of harmonically related frequencies applied to it ([H03L 7/22](#) takes precedence)
- 7/22 using more than one loop
- 7/23 with pulse counters or frequency dividers
- 7/235 {[Nested phase locked loops](#) }
- 7/24 using a reference signal directly applied to the generator
- 7/26 using energy levels of molecules, atoms, or subatomic particles as a frequency reference
- 9/00 Automatic control not provided for in other groups of this subclass**
- 2207/00 Indexing scheme relating to automatic control of frequency or phase and to synchronisation**
- 2207/04 Modifications for maintaining constant the phase-locked loop damping factor when other loop parameters change
- 2207/05 Compensating for non-linear characteristics of the controlled oscillator
- 2207/06 Phase locked loops with a controlled oscillator having at least two frequency control terminals
- 2207/08 Modifications of the phase-locked loop for ensuring constant frequency when the power supply fails or is interrupted, e.g. for saving power
- 2207/10 Indirect frequency synthesis using a frequency multiplier in the phase-locked loop or in the reference signal path
- 2207/12 Indirect frequency synthesis using a mixer in the phase-locked loop
- 2207/14 Preventing false-lock or pseudo-lock of the PLL
- 2207/18 Temporarily disabling, deactivating or stopping the frequency counter or divider
- 2207/50 All digital phase-locked loop