

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F16 ENGINEERING ELEMENTS AND UNITS; GENERAL MEASURES FOR PRODUCING AND MAINTAINING EFFECTIVE FUNCTIONING OF MACHINES OR INSTALLATIONS; THERMAL INSULATION IN GENERAL

F16H GEARING

NOTES

- Combinations including mechanical gearings are classified in groups [F16H 37/00](#) or [F16H 47/00](#), unless they are provided for in groups [F16H 1/00](#) - [F16H 35/00](#).
- In this subclass, sets of rigidly-connected members are regarded as single members.
- In this subclass, the following terms or expressions are used with the meanings indicated:
 - "toothed gearing" includes worm gearing and other gearing involving at least one wheel or sector provided with teeth or the equivalent, EXCEPT gearing with chains or toothed belts, which is treated as friction gearing;
 - "conveying motion" includes transmitting energy, and means that the applied and resultant motions are of the same kind, though they may differ in, e.g. speed, direction extent;
 - "rotary" implies that the motion may continue indefinitely;
 - "oscillating" means moving about an axis to an extent which is limited by the construction of the gearing, and which may exceed one revolution, the movement being alternately forwards and backwards during continued operation of the gearing;
 - "reciprocating" means moving substantially in a straight line, the movement being alternately forwards and backwards during continued operation of the gearing;
 - "reversing" or "reversal" means that an applied movement in one direction may produce a resultant movement in either of two opposed directions at will;
 - "central gears" includes any gears whose axis is the main axis of the gearing.
- Attention is drawn to the following places:

A01D 69/06	Gearings in harvesting machines
A63H 31/00	Gearing for toys
B21B 35/12	Toothed-wheel gearing for metal-rolling mills
B60K	Arrangement of transmissions in vehicles
B61C 9/00	Transmissions for railway locomotives
B62D 3/00	Vehicle steering gears
B62M	Transmissions for cycles
B63H 23/00	Transmissions for marine propulsions
B63H 25/00	Marine steering gears
{ B64C 27/12 , B64C 27/58 }	{ Transmissions for helicopters }
{ B64D 35/00 }	{ Transmissions for aircraft }
F01-F04	Machines, engines, pumps
F15B 15/00	Gearings associated with fluid-actuated devices
G01D 5/04	Gearing used in indicating or recording apparatus in connection with measuring devices
H03J 1/00	Driving arrangements for tuning resonant circuits
H04L 13/04	Driving mechanisms for apparatus for transmission of coded digital information.

WARNING

{ In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme. }

Toothed gearings for conveying rotary motion

- | | |
|-------|--|
| 1/00 | Toothed gearings for conveying rotary motion
(specific for conveying rotary motion with variable gear ratio or for reversing rotary motion F16H 3/00) |
| 1/003 | • { Monodirectionally torque-transmitting toothed gearing } |

- | | |
|-------|--|
| 1/006 | • { the driving and driven axes being designed to assume variable positions relative to one another during operation } |
| 1/02 | • without gears having orbital motion |
| 1/04 | • • involving only two intermeshing members |
| 1/06 | • • • with parallel axes |
| 1/08 | • • • • the members having helical, herringbone, or like teeth |

1/10 one of the members being internally toothed	2001/323	. . . {comprising eccentric crankshafts driving or driven by a gearing}
1/12	. . . with non-parallel axes	2001/324	. . . {comprising two axially spaced, rigidly interconnected, orbital gears}
1/125 {comprising spiral gears}	2001/325	. . . {comprising a carrier with pins guiding at least one orbital gear with circular holes}
1/14 comprising conical gears only	2001/326	. . . {comprising a carrier with linear guiding means guiding at least one orbital gear}
1/145 {with offset axes, e.g. hypoid gearings}	2001/327	. . . {with orbital gear sets comprising an internally toothed ring gear}
1/16 comprising worm and worm-wheel	2001/328	. . . {comprising balancing means}
1/163 {with balls between the co-operating parts}	1/34	. . involving gears essentially having intermeshing elements other than involute or cycloidal teeth (in worm gearing F16H 1/30)
1/166 {with members rotating around axes on the worm or worm-wheel}	1/36	. . with two central gears coupled by intermeshing orbital gears
1/18 the members having helical, herringbone, or like teeth (F16H 1/14 takes precedence)	1/46	. . Systems consisting of a plurality of gear trains each with orbital gears, {i.e. systems having three or more central gears}
1/20	. . involving more than two intermeshing members	1/48	. . Special means compensating for misalignment of axes {, e.g. for equalising distribution of load on the face width of the teeth (in combination with distribution of load on the planet-wheels F16H 1/2809)}
1/203	. . . {with non-parallel axes (F16H 1/22 takes precedence)}	3/00	Toothed gearings for conveying rotary motion with variable gear ratio or for reversing rotary motion (speed-changing or reversing mechanisms F16H 59/00 - F16H 63/00)
1/206	. . . {characterised by the driving or driven member being composed of two or more gear wheels}	3/001	. {convertible for varying the gear-ratio, e.g. for selecting one of several shafts as the input shaft}
1/22	. . . with a plurality of driving or driven shafts; with arrangements for dividing torque between two or more intermediate shafts	3/002	. {using gears having teeth movable out of mesh (F16H 3/42 takes precedence)}
1/222 {with non-parallel axes}	3/003	. {the gear-ratio being changed by inversion of torque direction}
1/225 {with two or more worm and worm-wheel gearings}	3/005	. . {for gearings using gears having orbital motion}
1/227 {comprising two or more gearwheels in mesh with the same internally toothed wheel}	3/006	. {power being selectively transmitted by either one of the parallel flow paths}
1/24	. . involving gears essentially having intermeshing elements other than involute or cycloidal teeth (F16H 1/16 takes precedence)	2003/007	. . {with two flow paths, one being directly connected to the input, the other being connected to the input through a clutch}
1/26	. . Special means compensating for misalignment of axes	2003/008	. . {comprising means for selectively driving countershafts}
1/28	. with gears having orbital motion	3/02	. without gears having orbital motion
1/2809	. . {with means for equalising the distribution of load on the planet-wheels}	3/04	. . with internally-toothed gears
1/2818	. . . {by allowing limited movement of the ring gear relative to the casing or shaft}	3/06	. . with worm and worm-wheel or gears essentially having helical or herring-bone teeth
1/2827	. . . {by allowing limited movement of the planet carrier, e.g. relative to its shaft}	3/08	. . exclusively or essentially with continuously meshing gears, that can be disengaged from their shafts
1/2836	. . . {by allowing limited movement of the planets relative to the planet carrier or by using free floating planets}	NOTE	In this group, gears which can be put out of mesh are not taken into consideration if they are used for reversal only.
1/2845	. . . {by allowing limited movement of the sun gear}	2003/0803	. . . {with countershafts coaxial with input or output shaft}
1/2854	. . {involving conical gears}	2003/0807	. . . {with gear ratios in which the power is transferred by axially coupling idle gears}
1/2863	. . {Arrangements for adjusting or for taking-up backlash}	2003/0811	. . . {using unsynchronised clutches}
2001/2872	. . {comprising three central gears, i.e. ring or sun gear, engaged by at least one common orbital gear mounted on an idling carrier}	2003/0815	. . . {using torque sharing, i.e. engaging two gear ratios simultaneously to transfer large torque, e.g. using one slipping clutch}
2001/2881	. . {comprising two axially spaced central gears, i.e. ring or sun gear, engaged by at least one common orbital gear wherein one of the central gears is forming the output}	2003/0818	. . . {comprising means for power-shifting}
2001/289	. . {comprising two or more coaxial and identical sets of orbital gears, e.g. for distributing torque between the coaxial sets}		
1/30	. . in which an orbital gear has an axis crossing the main axes of the gearing and has helical teeth or is a worm		
1/32	. . in which the central axis of the gearing lies inside the periphery of an orbital gear		
1/321	. . . {the orbital gear being nutating}		
2001/322	. . . {comprising at least one universal joint, e.g. a Cardan joint}		

2003/0822	. . . {characterised by the arrangement of at least one reverse gear}	3/20	. . . exclusively or essentially using gears that can be moved out of gear
2003/0826	. . . {wherein at least one gear on the input shaft, or on a countershaft is used for two different forward gear ratios}		NOTE
3/083	. . . with radially acting and axially controlled clutching members, e.g. sliding keys {(clutches with clutching members movable otherwise than only axially F16D 11/12; clutches with wedgeable clutching members F16D 15/00; systems of mechanically actuated clutches F16D 21/04)}	3/22	. . . with gears shiftable only axially
3/085	. . . with more than one output shaft	3/24 with driving and driven shafts coaxial
3/087	. . . characterised by the disposition of the gears (F16H 3/083, F16H 3/085 take precedence)	3/26 and two or more additional shafts
	NOTE	3/28 an additional shaft being coaxial with the main shafts
	When counting the countershafts, the reverse countershaft is not taken into consideration if it is used for reversal only.	3/30 with driving and driven shafts not coaxial
3/089 all of the meshing gears being supported by a pair of parallel shafts, one being the input shaft and the other the output shaft, there being no countershaft involved	3/32 and an additional shaft
3/091 including a single countershaft	3/34	. . . with gears shiftable otherwise than only axially
3/0915 {with coaxial input and output shafts}	3/36	. . . with a single gear meshable with any of a set of coaxial gears of different diameters
3/093 with two or more countershafts	3/363 {the teeth of the set of coaxial gears being arranged on a surface of generally conical shape}
2003/0931 {each countershaft having an output gear meshing with a single common gear on the output shaft}	3/366 {the teeth of the set of coaxial gears being arranged on a generally flat, e.g. disc-type, surface}
2003/0933 {with coaxial countershafts}	3/38	. . . with synchro-meshing
2003/0935 {with multiple countershafts comprising only one idle gear and one gear fixed to the countershaft}	3/385 {with braking means (constructional features of the final output mechanisms for reversing F16H 63/302)}
2003/0936 {with multiple countershafts comprising only two idle gears and one gear fixed to the countershaft}	3/40	. . . Gearings for reversal only
2003/0938 {with multiple gears on the input shaft directly meshing with respective gears on the output shaft}	3/42	. . . with gears having teeth formed or arranged for obtaining multiple gear ratios, e.g. nearly infinitely variable
3/095 with means for ensuring an even distribution of torque between the countershafts	3/423	. . . {the teeth being arranged on a surface of generally conical shape}
3/097 the input and output shafts being aligned on the same axis	3/426	. . . {the teeth being arranged on a generally flat, e.g. disc-type surface}
3/10	. . . with one or more one-way clutches as an essential feature	3/44	. . . using gears having orbital motion {(the gear-ratio being changed by inversion of torque direction F16H 3/005)}
3/12	. . . with means for synchronisation not incorporated in the clutches	2003/442	. . . {comprising two or more sets of orbital gears arranged in a single plane}
2003/123 {using a brake}	2003/445	. . . {without permanent connection between the input and the set of orbital gears}
3/126 {using an electric drive}	2003/447	. . . {without permanent connection between the set of orbital gears and the output}
3/14	. . . Gearings for reversal only	3/46	. . . Gearings having only two central gears, connected by orbital gears (F16H 3/68 - F16H 3/78 take precedence)
3/145 {with a pair of coaxial bevel gears, rotatable in opposite directions}	3/48	. . . with single orbital gears or pairs of rigidly-connected orbital gears
3/16	. . . essentially with both gears that can be put out of gear and continuously-meshing gears that can be disengaged from their shafts	3/50 comprising orbital conical gears
	NOTE	3/52 comprising orbital spur gears
	In this group, gears which can be put out of mesh are not taken into consideration if they are used for reversal only.	3/54 one of the central gears being internally toothed and the other externally toothed
3/18	. . . Gearings for reversal only	3/56 both central gears being sun gears
		3/58	. . . with sets of orbital gears, each consisting of two or more intermeshing orbital gears
		3/60	. . . Gearings for reversal only
		3/62	. . . Gearings having three or more central gears (F16H 3/68 - F16H 3/78 take precedence)
		3/64	. . . composed of a number of gear trains, the drive always passing through all the trains, each train having not more than one connection for driving another train

- 3/66 . . . composed of a number of gear trains without drive passing from one train to another
- 3/663 {with conveying rotary motion between axially spaced orbital gears, e.g. RAVIGNEAUX}
- 3/666 {with compound planetary gear units, e.g. two intermeshing orbital gears ([F16H 3/663](#) takes precedence)}
- 3/68 . . in which an orbital gear has an axis crossing the main axis of the gearing and has helical teeth or is a worm
- 3/70 . . in which the central axis of the gearing lies inside the periphery of an orbital gear
- 3/72 . . with a secondary drive, e.g. regulating motor, in order to vary speed continuously
- 3/721 . . . {with an energy dissipating device, e.g. regulating brake or fluid throttle, in order to vary speed continuously}
- 3/722 {with a fluid throttle}
- 3/724 . . . {using external powered electric machines}
- 3/725 {with means to change ratio in the mechanical gearing}
- 3/727 . . . {with at least two dynamo electric machines for creating an electric power path inside the gearing, e.g. using generator and motor for a variable power torque path ([special adapted for a hybrid electric vehicle B60K 6/20](#))}
- 3/728 {with means to change ratio in the mechanical gearing}
- 3/74 . . Complexes, not using actuable speedchanging or regulating members, e.g. with gear ratio determined by free play of frictional or other forces
- 3/76 . . with an orbital gear having teeth formed or arranged for obtaining multiple gear ratios, e.g. nearly infinitely variable
- 3/78 . . Special adaptation of synchronisation mechanisms to these gearings
- 2007/0812 . . . {Fluid pressure}
- 2007/0814 {with valves opening on surplus pressure}
- 2007/0817 {with means for venting unwanted gas}
- 2007/0819 . . . {Rubber or other elastic materials}
- 2007/0821 . . . {working with gravity}
- 2007/0823 . . . {Electric actuators}
- 2007/0825 . . . {influenced by other actuators of output members}
- 7/0827 . . {for disconnecting the drive}
- 7/0829 . . {with vibration damping means}
- 7/0831 . . . {of the dry friction type}
- 7/0834 . . . {of the viscous friction type, e.g. viscous fluid}
- 7/0836 . . . {of the fluid and restriction type, e.g. dashpot}
- 7/0838 . . . {of the dissipating material type, e.g. elastomeric spring}
- 2007/084 . . . {having vibration damping characteristics dependent on the moving direction of the tensioner}
- 2007/0842 . . {Mounting or support of tensioner}
- 2007/0844 . . . {Mounting elements essentially within boundaries of final output members}
- 2007/0846 . . {comprising a mechanical stopper}
- 7/0848 . . {with means for impeding reverse motion}
- 2007/0851 . . . {Wedges}
- 2007/0853 . . . {Ratchets}
- 2007/0855 {comprising a clip member engaging with the rack teeth}
- 2007/0857 . . . {Screw mechanisms}
- 2007/0859 . . . {Check valves}
- 2007/0861 . . {comprising means for sensing tensioner position}
- 2007/0863 . . {Finally actuated members, e.g. constructional details thereof}
- 2007/0865 . . . {Pulleys}
- 2007/0868 {comprising means for changing working diameter of pulley}
- 2007/087 . . . {Sprockets}
- 2007/0872 . . . {Sliding members}
- 2007/0874 . . . {Two or more finally actuated members}
- 2007/0876 . . {Control or adjustment of actuators}
- 2007/0878 . . . {Disabling during transport}
- 2007/088 . . . {Manual adjustment}
- 2007/0882 . . . {the tension being a function of temperature}
- 2007/0885 . . . {the tension being a function of engine running condition}
- 2007/0887 . . . {the tension being a function of load}
- 2007/0889 . . {Path of movement of the finally actuated member}
- 2007/0891 . . . {Linear path}
- 2007/0893 . . . {Circular path}
- 2007/0895 . . . {Internal to external direction}
- 2007/0897 . . . {External to internal direction}
- 7/10 . . by adjusting the axis of a pulley ([F16H 7/0827](#) takes precedence)}
- 7/12 . . . of an idle pulley
- 7/1209 {with vibration damping means ([vibration damping per se F16F](#))}
- 7/1218 {of the dry friction type}
- 7/1227 {of the viscous friction type, e.g. viscous fluid}
- 7/1236 {of the fluid and restriction type, e.g. dashpot}

Gearing for conveying rotary motion by endless flexible members

- 7/00 Gearings for conveying rotary motion by endless flexible members (specific for conveying rotary motion with variable gear ratio or for reversing rotary motion [F16H 9/00](#) (; chainwheels [F16H 55/30](#))**
- 7/02 . with belts; with V-belts
- 7/023 . . {with belts having a toothed contact surface or regularly spaced bosses or hollows for slipless or nearly slipless meshing with complementary profiled contact surface of a pulley ([toothed belts F16G 1/28, F16G 5/20](#))}
- 2007/026 . . {with belts running in a mist of oil}
- 7/04 . with ropes
- 7/06 . with chains
- 7/08 . Means for varying tension of belts, ropes, or chains (pulleys of adjustable construction [F16H 55/52](#) (; gearings with endless belts [F16H 7/02](#); tensioning for chains or belts specially adapted for cycles [B62M 9/16](#); belt or chain tensioning arrangements for endless conveyors [B65G 23/44](#))}
- 2007/0802 . . {Actuators for final output members}
- 2007/0804 . . . {Leaf springs}
- 2007/0806 . . . {Compression coil springs}
- 2007/0808 . . . {Extension coil springs}
- 2007/081 . . . {Torsion springs}
- 2007/0812 . . . {Fluid pressure}
- 2007/0814 {with valves opening on surplus pressure}
- 2007/0817 {with means for venting unwanted gas}
- 2007/0819 . . . {Rubber or other elastic materials}
- 2007/0821 . . . {working with gravity}
- 2007/0823 . . . {Electric actuators}
- 2007/0825 . . . {influenced by other actuators of output members}
- 7/0827 . . {for disconnecting the drive}
- 7/0829 . . {with vibration damping means}
- 7/0831 . . . {of the dry friction type}
- 7/0834 . . . {of the viscous friction type, e.g. viscous fluid}
- 7/0836 . . . {of the fluid and restriction type, e.g. dashpot}
- 7/0838 . . . {of the dissipating material type, e.g. elastomeric spring}
- 2007/084 . . . {having vibration damping characteristics dependent on the moving direction of the tensioner}
- 2007/0842 . . {Mounting or support of tensioner}
- 2007/0844 . . . {Mounting elements essentially within boundaries of final output members}
- 2007/0846 . . {comprising a mechanical stopper}
- 7/0848 . . {with means for impeding reverse motion}
- 2007/0851 . . . {Wedges}
- 2007/0853 . . . {Ratchets}
- 2007/0855 {comprising a clip member engaging with the rack teeth}
- 2007/0857 . . . {Screw mechanisms}
- 2007/0859 . . . {Check valves}
- 2007/0861 . . {comprising means for sensing tensioner position}
- 2007/0863 . . {Finally actuated members, e.g. constructional details thereof}
- 2007/0865 . . . {Pulleys}
- 2007/0868 {comprising means for changing working diameter of pulley}
- 2007/087 . . . {Sprockets}
- 2007/0872 . . . {Sliding members}
- 2007/0874 . . . {Two or more finally actuated members}
- 2007/0876 . . {Control or adjustment of actuators}
- 2007/0878 . . . {Disabling during transport}
- 2007/088 . . . {Manual adjustment}
- 2007/0882 . . . {the tension being a function of temperature}
- 2007/0885 . . . {the tension being a function of engine running condition}
- 2007/0887 . . . {the tension being a function of load}
- 2007/0889 . . {Path of movement of the finally actuated member}
- 2007/0891 . . . {Linear path}
- 2007/0893 . . . {Circular path}
- 2007/0895 . . . {Internal to external direction}
- 2007/0897 . . . {External to internal direction}
- 7/10 . . by adjusting the axis of a pulley ([F16H 7/0827](#) takes precedence)}
- 7/12 . . . of an idle pulley
- 7/1209 {with vibration damping means ([vibration damping per se F16F](#))}
- 7/1218 {of the dry friction type}
- 7/1227 {of the viscous friction type, e.g. viscous fluid}
- 7/1236 {of the fluid and restriction type, e.g. dashpot}

7/1245 {of the dissipating material type, e.g. elastomeric spring}	2009/245	. . . {with idle wheels to assist ratio change}
7/1254 {without vibration damping means}	9/26	. with members having orbital motion
7/1263 {where the axis of the pulley moves along a substantially straight path}	Other friction gearing for conveying rotary motion	
7/1272 {with means for impeding reverse motion}	13/00	Gearing for conveying rotary motion with constant gear ratio by friction between rotary members {(friction discs F16H 55/32)}
7/1281 {where the axis of the pulley moves along a substantially circular path}	13/02	. without members having orbital motion
7/129 {with means for impeding reverse motion}	13/04	. . with balls or with rollers acting in a similar manner
7/14	. . . of a driving or driven pulley	13/06	. with members having orbital motion
7/16	. . . without adjusting the driving or driven shaft	13/08	. . with balls or with rollers acting in a similar manner
7/18	. Means for guiding or supporting belts, ropes, or chains (construction of pulleys F16H 55/36)	13/10	. Means for influencing the pressure between the members
2007/185	. . {the guiding surface in contact with the belt, rope or chain having particular shapes, structures or materials}	13/12	. . by magnetic forces
7/20	. . Mountings for rollers or pulleys	13/14	. . for automatically varying the pressure mechanically
7/22	. Belt, rope, or chain shifters	15/00	Gearings for conveying rotary motion with variable gear ratio, or for reversing rotary motion, by friction between rotary members ({gearings for reversal only F16H 3/14, F16H 3/60}) ; control of change-speed or reversing-gearings conveying rotary motion F16H 59/00 - F16H 63/00
7/24	. Equipment for mounting belts, ropes, or chains	15/01	. characterised by the use of a magnetisable powder or liquid as friction medium between the rotary members
9/00	Gearings for conveying rotary motion with variable gear ratio, or for reversing rotary motion, by endless flexible members (control of change-speed or reversing-gearings conveying rotary motion F16H 59/00 - F16H 63/00)	15/02	. without members having orbital motion
9/02	. without members having orbital motion	15/04	. . Gearings providing a continuous range of gear ratios
9/04	. . using belts, V-belts, or ropes (with toothed belts F16H 9/24; pulleys of adjustable construction F16H 55/52)	15/06	. . . in which a member A of uniform effective diameter mounted on a shaft may co-operate with different parts of a member B
9/06	. . . engaging a stepped pulley	15/08 in which the member B is a disc with a flat or approximately flat friction surface
9/08	. . . engaging a conical drum (F16H 9/12 takes precedence)	15/10 in which the axes of the two members cross or intersect
9/10	. . . engaging a pulley provided with radially-actuable elements carrying the belt	15/12 in which one or each member is duplicated, e.g. for obtaining better transmission, for lessening the reaction forces on the bearings
9/12	. . . engaging a pulley built-up out of relatively axially-adjustable parts in which the belt engages the opposite flanges of the pulley directly without interposed belt-supporting members	15/14 in which the axes of the members are parallel or approximately parallel
9/125 {characterised by means for controlling the geometrical interrelationship of pulleys and the endless flexible member, e.g. belt alignment or position of the resulting axial pulley force in the plane perpendicular to the pulley axis}	15/16 in which the member B has a conical friction surface
9/14 using only one pulley built-up out of adjustable conical parts	15/18 externally
9/16 using two pulleys, both built-up out of adjustable conical parts	15/20 co-operating with the outer rim of the member A, which is perpendicular or nearly perpendicular to the friction surface of the member B
2009/163 {Arrangements of two or more belt gearings mounted in parallel, e.g. for increasing transmittable torque}	15/22 the axes of the members being parallel or approximately parallel
2009/166 {Arrangements of two or more belt gearings mounted in series, e.g. for increasing ratio coverage}	15/24 internally
9/18 only one flange of each pulley being adjustable	15/26 in which the member B has a spherical friction surface centered on its axis of revolution
9/20 both flanges of the pulleys being adjustable	15/28 with external friction surface
9/22	. . . specially adapted for ropes	15/30 with internal friction surface
9/24	. . using chains or toothed belts, belts in the form of links; Chains or belts specially adapted to such gearing	15/32 in which the member B has a curved friction surface formed as a surface of a body of revolution generated by a curve which is neither a circular arc centered on its axis of revolution nor a straight line

15/34	with convex friction surface	2019/046	. . .	{Facilitating the engagement or stopping of racks}
15/36	with concave friction surface, e.g. a hollow toroid surface	19/06	. .	comprising {flexible members, e.g. an} endless flexible member
15/38	with two members B having hollow toroid surfaces opposite to each other, the member or members A being adjustably mounted between the surfaces	WARNING Groups F16H 19/0604 - F16H 19/0672 are not complete pending reclassification; see also this group		
2015/383	{with two or more sets of toroid gearings arranged in parallel}	19/0604	. . .	{with means to double or half the stroke of the reciprocating member}
2015/386	{with two or more sets of toroid gearings arranged in series}	2019/0609	. . .	{the reciprocating motion being created by at least one drum or pulley with different diameters, using a differential effect}
15/40	. . .	in which two members co-operative by means of balls, or rollers of uniform effective diameter, not mounted on shafts	2019/0613	. . .	{the flexible member being a toothed belt or chain engaging a rack}
15/42	. . .	in which two members co-operate by means of rings or by means of parts of endless flexible members pressed between the first mentioned members	19/0618	. . .	{the flexible member, e.g. cable, being wound on a drum or thread for creating axial movement parallel to the drum}
15/44	. . .	in which two members of non-uniform effective diameter directly co-operate with one another	19/0622	. . .	{for converting reciprocating movement into oscillating movement and <i>vice versa</i> , the reciprocating movement is perpendicular to the axis of oscillation}
15/46	. .	Gearings providing a discontinuous or stepped range of gear ratios	19/0628	{the flexible member, e.g. a cable, being wound with one string to a drum and unwound with the other string to create reciprocating movement of the flexible member}
15/48	. .	with members having orbital motion	19/0636	. . .	{the flexible member being a non-buckling chain}
15/50	. .	Gearings providing a continuous range of gear ratios	19/064	. . .	{the flexible push member uses a bended profile to generate stiffness, e.g. spreading belts}
15/503	. . .	{in which two members co-operate by means of balls or rollers of uniform effective diameter, not mounted on shafts}	19/0645	. . .	{the flexible push or pull member having guiding means, i.e. the flexible member being supported at least partially by a guide to transmit the reciprocating movement (<i>non-buckling chains</i> F16H 19/0636)}
15/506	. . .	{in which two members of non-uniform effective diameter directly co-operate with one another}	19/065	. . .	{with flexible members between discs creating reciprocation by relative rotation of the discs}
15/52	. . .	in which a member of uniform effective diameter mounted on a shaft may co-operate with different parts of another member	19/0654	. . .	{using twisting movement of flexible members to modify the axial length of the mechanism}
15/54	. . .	in which two members co-operate by means of rings or by means of parts of endless flexible members pressed between the first-mentioned members	19/0659	. . .	{combined with means for creating non-linear characteristics, e.g. cams; Means for creating different velocity on forward and reverse stroke}
15/56	. .	Gearings providing a discontinuous or stepped range of gear ratios	19/0663	. . .	{with telescopic means, e.g. for supporting or shielding the reciprocating member}
19/00	Gearings comprising essentially only toothed gears or friction members and not capable of conveying indefinitely-continuing rotary motion (with intermittently-driving members F16H 27/00 - F16H 31/00)		2019/0668	. . .	{with open loop, e.g. with the free ends of the flexible member fixed to the casing, e.g. when the drive means are arranged on the carriage}
19/001	. .	{for conveying reciprocating or limited rotary motion}	19/0672	. . .	{characterised by means for tensioning the flexible member}
19/003	. .	{comprising a flexible member}	2019/0677	. . .	{characterised by the means for fixing the flexible member to a drum}
19/005	. . .	{for conveying oscillating or limited rotary motion}	2019/0681	. . .	{the flexible member forming a closed loop}
19/006	. . .	{for converting reciprocating into an other reciprocating motion}	2019/0686	{the flexible member being directly driven by a pulley or chain wheel}
2019/008	. .	{Facilitating the engagement or stopping of gear sections}	2019/069	. . .	{with means for generating two superposed movements, e.g. for driving a X-Y table}
19/02	. .	for interconverting rotary {or oscillating} motion and reciprocating motion	2019/0695	. . .	{Generating pivoting movement of a joint}
19/025	. .	{comprising a friction shaft}	19/08	. .	for interconverting rotary motion and oscillating motion
19/04	. .	comprising a rack			
19/043	. . .	{for converting reciprocating movement in a continuous rotary movement or <i>vice versa</i> , e.g. by opposite racks engaging intermittently for a part of the stroke}			

2019/085 . . {by using flexible members}

Gearing for conveying or converting motion by means of levers, links, cams or screw-and-nut mechanisms

21/00 Gearings comprising primarily only links or levers, with or without slides

- 21/02 . the movements of two or more independently-moving members being combined into a single movement
- 21/04 . Guiding mechanisms, e.g. for straight-line guidance
- 21/06 . which can be made ineffective when desired
- 21/08 . . by pushing a reciprocating rod out of its operative position
- 21/10 . all movement being in, or parallel to, a single plane
- 21/12 . . for conveying rotary motion
- 21/14 . . . by means of cranks, eccentrics, or like members fixed to one rotary member and guided along tracks on the other
- 21/16 . . for interconverting rotary motion and reciprocating motion
- 21/18 . . . Crank gearings; Eccentric gearings
- 21/20 with adjustment of throw
- 21/22 with one connecting-rod and one guided slide to each crank or eccentric
- 21/24 without further links or guides
- 21/26 with toggle action
- 21/28 with cams or additional guides
- 21/30 with members having rolling contact
- 21/32 with additional members comprising only pivoted links or arms
- 21/34 with two or more connecting-rods to each crank or eccentric
- 21/36 without swinging connecting-rod, e.g. with epicyclic parallel motion, slot-and-crank motion
- 21/365 {with planetary gearing having a ratio of 2:1 between sun gear and planet gear}
- 21/38 with means for temporary energy accumulation, e.g. to overcome dead-centre positions
- 21/40 . . for interconverting rotary motion and oscillating motion
- 21/42 . . . with adjustable throw
- 21/44 . . for conveying or interconverting oscillating or reciprocating motions
- 21/46 . with movements in three dimensions
- 21/48 . . for conveying rotary motions
- 21/50 . . for interconverting rotary motion and reciprocating motion {(F16H 23/00 takes precedence)}
- 21/52 . . for interconverting rotary motion and oscillating motion
- 21/54 . . for conveying or interconverting oscillating or reciprocating motions

23/00 Wobble-plate gearings; Oblique-crank gearings {(conveying rotary motion with toothed nutating gears F16H 1/321)}

- 23/02 . with adjustment of throw by changing the position of the wobble-member (gearings in which the transmission ratio is changed by adjustment of a wobble-plate F16H 29/04; gearings with gyroscopic action, e.g. comprising wobble-plates F16H 33/10)
- 23/04 . with non-rotary wobble-members

- 23/06 . . with sliding members hinged to reciprocating members
- 23/08 . . connected to reciprocating members by connecting-rods
- 23/10 . with rotary wobble-plates with plane surfaces

25/00 Gearings comprising primarily only cams, cam-followers and screw-and-nut mechanisms

- 25/02 . the movements of two or more independently moving members being combined into a single movement
- 25/04 . for conveying rotary motion
- 25/06 . . with intermediate members guided along tracks on both rotary members
- 2025/063 . . . {the intermediate members being balls engaging on opposite cam discs}
- 2025/066 . . . {the intermediate members being rollers supported in a chain}
- 25/08 . for interconverting rotary motion and reciprocating motion (F16H 23/00 takes precedence)
- 25/10 . . with adjustable throw
- 25/12 . . with reciprocation along the axis of rotation, e.g. gearings with helical grooves and automatic reversal {or cams}
- 25/122 . . . {Gearings with helical grooves and automatic reversal}
- 25/125 . . . {having the cam on an end surface of the rotating element}
- 2025/127 . . . {using electric solenoids for generating the reciprocating motion}
- 25/14 . . with reciprocation perpendicular to the axis of rotation (crank or eccentric gearings without swinging connecting-rod F16H 21/36)
- 25/16 . for interconverting rotary motion and oscillating motion
- 25/18 . for conveying or interconverting oscillating or reciprocating motions
- 25/183 . . {conveying only reciprocating motion, e.g. wedges}
- 25/186 . . {with reciprocation along the axis of oscillation}
- 25/20 . . Screw mechanisms (with automatic reversal F16H 25/12)
- 25/2003 . . . {with arrangements for taking up backlash (F16H 25/2209 takes precedence)}
- 25/2006 {with more than one nut or with nuts consisting of more than one bearing part}
- 25/2009 {with radial preloading}
- 2025/2012 {using a spring member creating rotary torque for counter rotating the two nuts, e.g. a torsion bar}
- 25/2015 . . . {Means specially adapted for stopping actuators in the end position; Position sensing means}
- 25/2018 . . . {with both screw and nut being driven, i.e. screw and nut are both rotating}
- 25/2021 . . . {with means for avoiding overloading}
- 25/2025 . . . {with means to disengage the nut or screw from their counterpart; Means for connecting screw and nut for stopping reciprocating movement (F16H 25/2015 takes precedence)}
- 2025/2028 . . . {using screw profiles with high efficiency for converting reciprocating motion into oscillating movement}
- 2025/2031 . . . {Actuator casings}

2025/2034	{Extruded frame casings}	2025/2242	{Thread profile of the screw or nut showing a pointed "gothic" arch in cross-section}
2025/2037	. . .	{Actuator supports or means for fixing piston end, e.g. flanges}	25/2247	{with rollers}
2025/204	. . .	{Axial sliding means, i.e. for rotary support and axial guiding of nut or screw shaft}	25/2252	{Planetary rollers between nut and screw}
2025/2043	. . .	{Screw mechanisms driving an oscillating lever, e.g. lever with perpendicular pivoting axis}	2025/2257	{with means for shifting planetary rollers axially, e.g. into central position}
2025/2046	. . .	{with gears arranged perpendicular to screw shaft axis, e.g. helical gears engaging tangentially the screw shaft}	25/2261	{arranged substantially perpendicular to the screw shaft axis}
25/205	. . .	{comprising alternate power paths, e.g. for fail safe back-up}	25/2266	{arranged substantially in parallel to the screw shaft axis (planetary rollers F16H 25/2252)}
2025/2053	. . .	{Screws in parallel arrangement driven simultaneously with an output member moved by the screws}	2025/2271	{with means for guiding circulating rollers}
25/2056	. . .	{Telescopic screws with at least three screw members in coaxial arrangement}	2025/2276	{using roller spacers, i.e. spacers separating the rollers, e.g. by forming a complete chain}
2025/2059	. . .	{Superposing movement by two screws, e.g. with opposite thread direction (telescopic screws with three screw members F16H 25/2056)}	2025/228	{Screw mechanisms having rollers being supported by the screw shaft and engaging the nut}
2025/2062	. . .	{Arrangements for driving the actuator}	25/2285	{with rings engaging the screw shaft with the inner perimeter, e.g. using inner rings of a ball bearing}
2025/2065	{Manual back-up means for overriding motor control, e.g. hand operation in case of failure}	25/229	{Eccentric rings with their axis arranged substantially parallel to the screw shaft axis}
2025/2068	{Means for returning linear actuator to zero position, e.g. upon occurrence of failure by using a spring}	25/2295	{Rings which are inclined or can pivot around an axis perpendicular to the screw shaft axis}
2025/2071	{Disconnecting drive source from the actuator, e.g. using clutches for release of drive connection during manual control}	25/24	. . .	Elements essential to such mechanisms, e.g. screws, nuts (F16H 25/22 takes precedence)
2025/2075	{Coaxial drive motors}	25/2409	{one of the threads being replaced by elements specially formed for engaging the screw or nut, e.g. pins, racks, toothed belts}
2025/2078	{the rotor being integrated with the nut or screw body}	25/2418	{Screw seals, wipers, scrapers or the like}
2025/2081	{Parallel arrangement of drive motor to screw axis}	25/2427	{one of the threads being replaced by a wire or stripmetal, e.g. spring}
2025/2084	{Perpendicular arrangement of drive motor to screw axis}	2025/2436	{Intermediate screw supports for reducing unsupported length of screw shaft}
2025/2087	{using planetary gears}	2025/2445	{Supports or other means for compensating misalignment or offset between screw and nut}
2025/209	{using worm gears}	25/2454	{Brakes; Rotational locks}
2025/2093	{using conical gears}	2025/2463	{using a wrap spring brake, i.e. a helical wind up spring for braking or locking}
2025/2096	{using endless flexible members}	25/2472	{Safety nuts}
25/22	. . .	with balls, rollers, or similar members between the co-operating parts; Elements essential to the use of such members	2025/2481	{Special features for facilitating the manufacturing of spindles, nuts, or sleeves of screw devices}
25/2204	{with balls}	2025/249	{Special materials or coatings for screws or nuts (lubrication F16H 57/0497)}
25/2209	{with arrangements for taking up backlash}			
25/2214	{with elements for guiding the circulating balls}			
25/2219	{Axially mounted end-deflectors}			
25/2223	{Cross over deflectors between adjacent thread turns, e.g. S-form deflectors connecting neighbouring threads}			
25/2228	{the device for circulation forming a part of the screw member}			
25/2233	{with cages or means to hold the balls in position}			
25/2238	{using ball spacers, i.e. spacers separating the balls, e.g. by forming a chain supporting the balls}			

Gearings with intermittently-driving member

27/00	Step-by-step mechanisms without freewheel members, e.g. Geneva drives
27/02	. with at least one reciprocating or oscillating transmission member (F16H 27/04 takes precedence)
27/04	. for converting continuous rotation into a step-by-step rotary movement
27/045	. {Mechanism comprising a member with partially helical tracks}
27/06	. Mechanisms with driving pins in driven slots, e.g. Geneva drives

- 27/08 . . with driving toothed gears with interrupted toothing
- 27/10 . . obtained by means of disengageable transmission members, combined or not combined with mechanisms according to group [F16H 27/06](#) or [F16H 27/08](#)
- 29/00 Gearings for conveying rotary motion with intermittently-driving members, e.g. with freewheel action** [{\(gearings for converting oscillating or reciprocating movement with freewheeling members or other intermittently-driving members into a rotary movement F16H 31/00\)}](#)
- 29/02 . between one of the shafts and an oscillating or reciprocating intermediate member, not rotating with either of the shafts ([F16H 29/20](#), [F16H 29/22 take precedence](#))
- 29/04 . . in which the transmission ratio is changed by adjustment of a crank, an eccentric, a wobble-plate, or a cam, on one of the shafts
- 29/06 . . . with concentric shafts, an annular intermediate member moving around and being supported on an adjustable crank or eccentric
- 29/08 . . in which the transmission ratio is changed by adjustment of the path of movement, the location of the pivot, or the effective length, of an oscillating connecting member
- 29/10 . . in which the transmission ratio is changed by directly acting on the intermittently driving members
- 29/12 . between rotary driving and driven members ([F16H 29/20](#), [F16H 29/22 take precedence](#))
- 29/14 . . in which the transmission ratio is changed by adjustment of an otherwise stationary guide member for the intermittently-driving members
- 29/16 . . in which the transmission ratio is changed by adjustment of the distance between the axes of the rotary members
- 29/18 . . . in which the intermittently-driving members slide along approximately radial guides while rotating with one of the rotary members
- 29/20 . the intermittently-acting members being shaped as worms, screws, or racks
- 29/22 . with automatic speed change
- 31/00 Other gearings with freewheeling members or other intermittently driving members** ([F16H 21/00](#), [F16H 23/00](#), [F16H 25/00 take precedence](#))
- 31/001 . {Mechanisms with freewheeling members}
- 31/002 . . {Hand-driven ratchets (wrenches of the ratchet type [B25B 13/46](#))}
- 31/003 . {Step-by-step mechanisms for rotary motion}
- 31/004 . . {with pawls driven by a rotary cam}
- 31/005 . . {with pawls driven by a reciprocating or oscillating transmission member ([F16H 31/002](#), [F16H 31/004 take precedence](#))}
- 31/006 . . {with friction means}
- 31/007 . {Step-by-step mechanisms for linear motion}
- 31/008 . . {with friction means}
- 33/00 Gearings based on repeated accumulation and delivery of energy**
- 33/02 . Rotary transmissions with mechanical accumulators, e.g. weights, springs, intermittently-connected flywheels
- 33/04 . . Gearings for conveying rotary motion with variable velocity ratio, in which self-regulation is sought
- 33/06 . . . based essentially on spring action
- 33/08 . . . based essentially on inertia
- 33/10 with gyroscopic action, e.g. comprising wobble-plates, oblique cranks
- 33/12 with a driving member connected differentially with both a driven member and an oscillatory member with large resistance to movement, e.g. Constantinesco gearing
- 33/14 having orbital members influenced by regulating masses
- 33/16 which have their own free motion, or consist of fluid
- 33/18 of which the motion is constrained
- 33/185 {the masses being fixed to the orbital members}
- 33/20 . for interconversion, based essentially on inertia, of rotary motion and reciprocating or oscillating motion [{\(for converting into a linear propulsion force, i.e. inertia motors F03G 3/00\)}](#)
- 35/00 Gearings or mechanisms with other special functional features**
- 2035/001 . {Gearings with eccentric mounted gears, e.g. for cyclically varying ratio}
- 2035/003 . {Gearings comprising pulleys or toothed members of non-circular shape, e.g. elliptical gears (harmonic drives with elliptical wave generators [F16H 49/001](#))}
- 2035/005 . {Gearings or mechanisms preventing back-driving (braking or locking of screw actuators [F16H 25/2454](#))}
- 2035/006 . {Gearings or mechanisms for stopping or limiting movement, e.g. stopping a movement after few turns (for linear screw actuators [F16H 25/2015](#))}
- 35/008 . {for variation of rotational phase relationship, e.g. angular relationship between input and output shaft (couplings [F16D 3/10](#))}
- 35/02 . for conveying rotary motion with cyclically varying velocity ratio
- 35/06 . Gearings designed to allow relative movement between supports thereof without ill effects (special means compensating for misalignment of axes [F16H 1/26](#), [F16H 1/48](#) ; mounting or supporting gearboxes [F16H 57/025](#))}
- 35/08 . for adjustment of members on moving parts from a stationary place
- 35/10 . Arrangements or devices for absorbing overload or preventing damage by overload [{\(for screw mechanisms F16H 25/2021\)}](#)
- 2035/103 . . {with drive interruption by structural failure of overload preventing means, e.g. using shear pins}
- 2035/106 . . {Monitoring of overload}
- 35/12 . Transmitting mechanisms with delayed effect
- 35/14 . Mechanisms with only two stable positions, e.g. acting at definite angular positions
- 35/16 . Mechanisms for movements or movement relations conforming to mathematical formulae
- 35/18 . Turning devices for rotatable members, e.g. shafts

37/00	Combinations of mechanical gearings, not provided for in groups F16H 1/00 - F16H 35/00 (combinations of mechanical gearing with fluid clutches or fluid gearing F16H 47/00)	37/082 {and additional planetary reduction gears}
37/02	. comprising essentially only toothed or friction gearings	37/0826 {with only one output shaft}
37/021	. . {toothed gearing combined with continuous variable friction gearing}	37/0833 {with arrangements for dividing torque between two or more intermediate shafts, i.e. with two or more internal power paths (F16H 3/72 takes precedence)}
37/022	. . . {the toothed gearing having orbital motion}	37/084 {at least one power path being a continuously variable transmission, i.e. CVT}
2037/023	. . . {CVT's provided with at least two forward and one reverse ratio in a serial arranged sub-transmission}	37/0846 {CVT using endless flexible members}
2037/025	. . . {CVT's in which the ratio coverage is used more than once to produce the overall transmission ratio coverage, e.g. by shift to end of range, then change ratio in sub-transmission and shift CVT through range once again}	37/0853 {CVT using friction between rotary members having a first member of uniform effective diameter cooperating with different parts of a second member}
2037/026	. . . {CVT layouts with particular features of reversing gear, e.g. to achieve compact arrangement}	37/086 {CVT using two coaxial friction members cooperating with at least one intermediate friction member}
37/027	. . {toothed gearing combined with a gear using endless flexible members for reversing rotary motion only}	2037/0866 {Power split variators with distributing differentials, with the output of the CVT connected or connectable to the output shaft}
2037/028	. . {having two distinct forward drive ratios and one reverse drive ratio arranged in series with a continuously variable transmission unit}	2037/0873 {with switching, e.g. to change ranges}
37/04	. . Combinations of toothed gearings only (F16H 37/06 takes precedence)	2037/088 {Power split variators with summing differentials, with the input of the CVT connected or connectable to the input shaft}
37/041	. . . {for conveying rotary motion with constant gear ratio}	2037/0886 {with switching means, e.g. to change ranges}
	<u>WARNING</u>	2037/0893 {characterised in the ratio of the continuously variable transmission is different from zero when the output shaft speed is zero}
	This group is not complete pending a reorganisation; see also subgroups of F16H 1/00	37/10 at both ends of intermediate shafts (F16H 37/0806 takes precedence)}
37/042	. . . {change gear transmissions in group arrangement}	2037/101 {Power split variators with one differential at each end of the CVT}
37/043 {without gears having orbital motion}	2037/102 {the input or output shaft of the transmission is connected or connectable to two or more differentials}
2037/044 {comprising a separate gearing unit for shifting between forward or reverse}	2037/103 {Power split variators with each end of the CVT connected or connectable to a Ravigneaux set}
2037/045 {comprising a separate gearing unit for shifting between high and low ratio range}	2037/104 {Power split variators with one end of the CVT connected or connectable to two or more differentials}
37/046 {with an additional planetary gear train, e.g. creep gear, overdrive}	2037/105 {characterised by number of modes or ranges, e.g. for compound gearing}
2037/047	. . . {comprising one or more orbital gear sets coaxial with a first shaft and having more than one drive connection to a second shaft parallel to the first shaft}	2037/106 {with switching means to provide two variator modes or ranges}
2037/048	. . . {Combinations of parallel shaft and orbital motion gearing, wherein the orbital motion gear has more than one connection with the parallel shaft gearing}	2037/107 {with switching means to provide three variator modes or ranges}
2037/049	. . . {Forward-reverse units with forward and reverse gears for achieving multiple forward and reverse gears, e.g. for working machines}	2037/108 {with switching means to provide four or more variator modes or ranges}
37/06	. . with a plurality of driving or driven shafts; with arrangements for dividing torque between two or more intermediate shafts	37/12	. Gearings comprising primarily toothed or friction gearing, links or levers, and cams, or members of at least two of these types (gearings with cranks, eccentrics, or like members fixed to one rotary member and guided along tracks on the other F16H 21/14 ; crank or eccentric gearings with cams or additional guides, or with members having rolling contact F16H 21/28 , F16H 21/30)
37/065	. . . {with a plurality of driving or driven shafts (F16H 37/08 takes precedence)}		
37/08	. . . with differential gearing		
37/0806 {with a plurality of driving or driven shafts}		
37/0813 {with only one input shaft (differentials for four wheel drive vehicles B60K 17/346)}		

- 37/122 . . {for interconverting rotary motion and oscillating motion}
- 37/124 . . {for interconverting rotary motion and reciprocating motion}
- 37/126 . . . {Guiding mechanism using levers combined with gearings for straight line output movement, e.g. by using gears or pulleys with ratio 2:1}
- 2037/128 . . {Generating reciprocating motion by a planetary gear (ratio 2:1) using endless flexible members}
- 37/14 . . the movements of two or more independently-moving members being combined into a single movement {(screw mechanisms with both nut and screw being driven F16H 25/2018)}
- 37/16 . . with a driving or driven member which both rotates or oscillates on its axis and reciprocates

Fluid gearing

- 39/00 Rotary fluid gearing using pumps and motors of the volumetric type, i.e. passing a predetermined volume of fluid per revolution (control of exclusively fluid gearing F16H 61/38)**
- 2039/005 . {comprising arrangements or layout to change the capacity of the motor or pump by moving the hydraulic chamber of the motor or pump}
- 39/01 . Pneumatic gearing; Gearing working with subatmospheric pressure
- 39/02 . with liquid motors at a distance from liquid pumps
- 39/04 . with liquid motor and pump combined in one unit
- 39/06 . . pump and motor being of the same type
- 39/08 . . . each with one main shaft and provided with pistons reciprocating in cylinders
- 39/10 with cylinders arranged around, and parallel or approximately parallel to the main axis of the gearing
- 2039/105 {at least one pair of motors or pumps sharing a common swash plate}
- 39/12 with stationary cylinders
- 39/14 with cylinders carried in rotary cylinder blocks or cylinder-bearing members
- 39/16 with cylinders arranged perpendicular to the main axis of the gearing
- 39/18 the connections of the pistons being at the outer ends of the cylinders
- 39/20 the connections of the pistons being at the inner ends of the cylinders
- 39/22 . . . with liquid chambers shaped as bodies of revolution concentric with the main axis of the gearing
- 39/24 with rotary displacement members, e.g. provided with axially or radially movable vanes passing movable sealing members
- 39/26 . . . with liquid chambers not shaped as bodies of revolution or shaped as bodies of revolution eccentric to the main axis of the gearing
- 39/28 with liquid chambers formed in rotary members
- 39/30 with liquid chambers formed in stationary members
- 39/32 with sliding vanes carried by the rotor
- 39/34 . . . in which a rotor on one shaft co-operates with a rotor on another shaft
- 39/36 toothed-gear type
- 39/38 Displacement screw-pump type

- 39/40 . . . Hydraulic differential gearings, e.g. having a rotary input housing with interconnected liquid chambers for both outputs
- 39/42 . . pump and motor being of different types
- 41/00 Rotary fluid gearing of the hydrokinetic type (control of exclusively fluid gearing F16H 61/38)**
- 41/02 . with pump and turbine connected by conduits or ducts
- 41/04 . Combined pump-turbine units
- 41/22 . . Gearing systems consisting of a plurality of hydrokinetic units operating alternatively, e.g. made effective or ineffective by filling or emptying or by mechanical clutches
- 41/24 . Details
- 2041/243 . . {Connections between pump shell and cover shell of the turbine}
- 2041/246 . . {relating to one way clutch of the stator}
- 41/26 . . Shape of runner blades or channels with respect to function
- 41/28 . . with respect to manufacture, e.g. blade attachment
- 2041/285 . . . {of stator blades}
- 41/30 . . relating to venting, lubrication, cooling, circulation of the cooling medium
- 41/32 . Selection of working fluids
- 43/00 Other fluid gearing, e.g. with oscillating input or output {(generating mechanical vibrations of infrasonic or sonic frequency B06B; percussive tools B25D 9/00; mine roof supports for step by step movement E21D 23/00; reciprocating-piston machines without rotary main shaft F01B 11/08; fluid pressure actuators F15B)}**
- 43/02 . Fluid gearing actuated by pressure waves
- 45/00 Combinations of fluid gearings for conveying rotary motion with couplings or clutches (gearing systems consisting of a plurality of hydrokinetic units operating alternatively F16H 41/22 {, F16H 47/085})**

NOTE

Clutches for varying working conditions in fluid torque-converters are regarded as part of the torque converter

- 2045/002 . {comprising a clutch between prime mover and fluid gearing}
- 2045/005 . {comprising a clutch between fluid gearing and the mechanical gearing unit}
- 2045/007 . {comprising a damper between turbine of the fluid gearing and the mechanical gearing unit}
- 45/02 . with mechanical clutches for bridging a fluid gearing of the hydrokinetic type (control of torque converter lock-up clutches F16H 61/14)
- 2045/0205 . . {two chamber system, i.e. without a separated, closed chamber specially adapted for actuating a lock-up clutch}
- 2045/021 . . {three chamber system, i.e. comprising a separated, closed chamber specially adapted for actuating a lock-up clutch}
- 2045/0215 . . {Details of oil circulation}
- 2045/0221 . . {with damping means}
- 2045/0226 . . . {comprising two or more vibration dampers}
- 2045/0231 {arranged in series}
- 2045/0236 . . . {with axial dampers, e.g. comprising a ramp system}

2045/0242	. . . {with viscous dampers}	2048/087	. . . {characterised by the pinion gears, e.g. their type or arrangement}
2045/0247	. . . {having a turbine with hydrodynamic damping means}	48/10	. . with orbital spur gears
2045/0252	. . . {having a damper arranged on input side of the lock-up clutch}	2048/102	. . . {with spur gears engaging face gears}
2045/0257	. . . {having a pump adapted for use as a secondary mass of the damping system}	2048/104	. . . {characterised by two ring gears}
2045/0263	. . . {the damper comprising a pendulum}	2048/106	. . . {characterised by two sun gears}
2045/0268	. . . {the damper comprising a gearing}	48/11	. . . having intermeshing planet gears
2045/0273	. . {characterised by the type of the friction surface of the lock-up clutch}	48/12	. without gears having orbital motion
2045/0278	. . . {comprising only two co-acting friction surfaces}	48/14	. . with cams
2045/0284	. . . {Multiple disk type lock-up clutch}	48/142	. . . {consisting of linked clutches using axially movable inter-engaging parts}
2045/0289	. . . {Details of friction surfaces of the lock-up clutch}	48/145 {with friction clutching members}
2045/0294	. . . {Single disk type lock-up clutch, i.e. using a single disc engaged between friction members}	48/147	. . . {with driven cam followers or balls engaging two opposite cams}
47/00	Combinations of mechanical gearing with fluid clutches or fluid gearing	48/16	. . with freewheels
47/02	. the fluid gearing being of the volumetric type	48/18	. . with fluid gearing
2047/025	. . {the fluid gearing comprising a plurality of pumps or motors}	48/19	. . consisting of two linked clutches
47/04	. . the mechanical gearing being of the type with members having orbital motion	48/20	. Arrangements for suppressing or influencing the differential action, e.g. locking devices
2047/045	. . . {the fluid gearing comprising a plurality of pumps or motors}	2048/201	. . {with means directly braking the orbital gears}
47/06	. the fluid gearing being of the hydrokinetic type	2048/202	. . {using freewheel clutches}
47/065	. . {the mechanical gearing being of the friction or endless flexible member type}	2048/204	. . {Control of arrangements for suppressing differential actions}
47/07	. . using two or more power-transmitting fluid circuits (F16H 47/065 ,) F16H 47/10 take precedence)	2048/205	. . . {using the steering as a control parameter}
47/08	. . the mechanical gearing being of the type with members having orbital motion (F16H 47/065 takes precedence)}	2048/207	. . . {using torque sensors}
47/085	. . . {with at least two mechanical connections between the hydraulic device and the mechanical transmissions}	2048/208	. . . {using flywheels}
47/10	. . . using two or more power-transmitting fluid circuits	48/22	. . using friction clutches or brakes
47/12	. . . the members with orbital motion having vanes interacting with the fluid	48/24	. . using positive clutches or brakes
48/00	Differential gearings (cooling or lubricating of differential gearing F16H 57/04)	48/26	. . using fluid action, e.g. viscous clutches
	NOTE	2048/265	. . . {with a fluid throttling means}
	When classifying in this main group, in the absence of an indication to the contrary, classification is made in all appropriate places.	48/27	. . using internally-actuatable fluid pressure, e.g. internal pump types
2048/02	. {Transfer gears for influencing drive between outputs}	48/28	. . using self-locking gears or self-braking gears
2048/04	. . {having unequal torque transfer between two outputs}	2048/282	. . . {using the axial movement of axially movable bevel gears}
48/05	. Multiple interconnected differential sets	48/285	. . . with self-braking intermeshing gears having parallel axes and having worms or helical teeth
48/06	. with gears having orbital motion	48/29	. . . with self-braking intermeshing gears having perpendicular arranged axes and having worms or helical teeth
48/08	. . comprising bevel gears	48/295	. . using multiple means for force boosting
2048/082	. . . {characterised by the arrangement of output shafts}	48/30	. . using externally-actuatable means
2048/085	. . . {characterised by shafts or gear carriers for orbital gears}	2048/305	. . . {using manual actuators}
		48/32	. . . using fluid pressure actuators
		48/34	. . . using electromagnetic or electric actuators
		2048/343 {using a rotary motor}
		2048/346 {using a linear motor}
		48/36	. characterised by intentionally generating speed difference between outputs
		2048/362	. . {using a continuously variable transmission}
		2048/364	. . {using electric or hydraulic motors}
		2048/366	. . {using additional non-orbital gears in combination with clutches or brakes}
		2048/368	. . {using additional orbital gears in combination with clutches or brakes}
		48/38	. Constructional details (the outer casing comprising the differential and supporting input and output shafts F16H 57/037)
		2048/382	. . {Methods for manufacturing differential gearings}
		2048/385	. . {of the ring or crown gear}
		2048/387	. . {Shields or washers}
		48/40	. . characterised by features of the rotating cases

2048/405	. . . {characterised by features of the bearing of the rotating case}	55/084	. . . {Non-circular rigid toothed member, e.g. elliptic gear}
48/42	. . characterised by features of the input shafts, e.g. mounting of drive gears thereon	55/0846	. . . {Intersecting-shaft arrangement of the toothed members (F16H 55/0813 , F16H 55/0826 , F16H 55/0833 , F16H 55/084 take precedence)}
2048/423	. . . {characterised by bearing arrangement}	55/0853	. . . {Skewed-shaft arrangement of the toothed members (F16H 55/082 , F16H 55/0826 , F16H 55/0833 , F16H 55/084 take precedence)}
2048/426 {characterised by spigot bearing arrangement, e.g. bearing for supporting the free end of the drive shaft pinion}	2055/086	. . . {Silent gear profiles}
49/00	Other gearings	2055/0866	. . . {Profiles for improving radial engagement of gears, e.g. chamfers on the tips of the teeth}
49/001	. {Wave gearings, e.g. harmonic drive transmissions (harmonic drives specially adapted for positioning programme-controlled manipulators B25J 9/1025)}	55/0873	. . . {for improving axial engagement, e.g. a chamfer at the end of the tooth flank}
2049/003	. . {Features of the flexsplines therefor}	55/088	. . . {with corrections on tip or foot of the teeth, e.g. addendum relief for better approach contact}
49/005	. {Magnetic gearings with physical contact between gears (rotating torque transmitting elements of the permanent-magnet type H02K 49/102)}	55/0886	. . . {with corrections along the width, e.g. flank width crowning for better load distribution}
2049/006	. {Wave generators producing a non-elliptical shape of flexsplines, i.e. with a qualified different shape than elliptical}	2055/0893	. . . {for parallel shaft arrangement of toothed members}
2049/008	. {Linear wave gearings, i.e. harmonic type gearing imposing a strain wave to a straight flexible member engaging a second member with different pitch to generate linear motion thereof}	55/10	. . Constructively simple tooth shapes, e.g. shaped as pins, as balls {(gearwork for clocks and watches G04B 13/00)}
Details of gearing or mechanisms		55/12	. . with body or rim assembled out of detachable parts
51/00	Levers of gearing mechanisms	55/14	. . Construction providing resilience or vibration-damping (F16H 55/06 takes precedence)
51/02	. adjustable	55/16	. . . relating to teeth only
53/00	Cams {; Non-rotary cams;} or cam-followers, e.g. rollers for gearing mechanisms	55/17	. . Toothed wheels (worm wheels F16H 55/22 ; chain wheels F16H 55/30)
53/02	. Single-track cams for single-revolution cycles; Camshafts with such cams	55/171	. . . {Toothed belt pulleys}
53/025	. . {characterised by their construction, e.g. assembling or manufacturing features (grinding of camshafts B24B 19/12)}	2055/173	. . . {Crown gears, i.e. gears have axially arranged teeth}
53/04	. . Adjustable cams	2055/175	. . . {specially adapted for easy repair, e.g. exchange of worn teeth}
53/06	. Cam-followers (F16H 53/08 takes precedence)	2055/176	. . . {Ring gears with inner teeth}
53/08	. Multi-track cams, e.g. for cycles consisting of several revolutions; Cam-followers specially adapted for such cams	2055/178	. . . {combined with clutch means, e.g. gear with integrated synchronizer clutch}
55/00	Elements with teeth or friction surfaces for conveying motion; Worms, pulleys or sheaves for gearing mechanisms (of screw-and-nut gearing F16H 25/00)	55/18	. . . Special devices for taking up backlash {(for gears having orbital motion F16H 1/2863)}
55/02	. Toothed members; Worms	2055/185 {using compound gears with coincident teeth of different material, e.g. laminated construction of metal and elastomeric gear layers, where elastic layer is slightly oversized}
55/06	. . Use of materials; Use of treatments of toothed members or worms to affect their intrinsic material properties {(coatings for lubrication F16H 57/041 ; producing gear wheels from plastics or substances in a plastic state B29D 15/00 ; heat treatment C21D 9/32 ; electrolytic surface treatment C25D ; heating by electromagnetic field H05B 6/00)}	55/20 for bevel gears
2055/065	. . . {Moulded gears, e.g. inserts therefor}	55/22	. . for transmissions with crossing shafts, especially worms, worm-gears
55/08	. . Profiling	55/24	. . . Special devices for taking up backlash
55/0806	. . . {Involute profile}	55/26	. . Racks
55/0813 {Intersecting-shaft arrangement of the toothed members}	55/28	. . . Special devices for taking up backlash
55/082 {Skewed-shaft arrangement of the toothed members, i.e. non-intersecting shafts}	2055/281 {Cylindrical or half-cylindrical bushings around the rack, e.g. using special wedges to reduce play}
55/0826	. . . {Novikov-Wildhaber profile}	55/283 {using pressure yokes}
55/0833	. . . {Flexible toothed member, e.g. harmonic drive}	55/285 {with rollers or balls to reduce friction}
		55/286 {with asymmetric layout of the yoke}
		55/288 {comprising two or more pressure yokes}
		55/30	. . Chain-wheels
		55/303	. . . {for round linked chains, i.e. hoisting chains with identical links}
		2055/306	. . . {with means providing resilience or vibration damping in chain sprocket wheels}
		55/32	. Friction members

- 2055/325 . . {characterized by roughness or hardness of friction surface}
- 55/34 . . Non-adjustable friction discs
- 55/36 . . Pulleys (with features essential for adjustment [F16H 55/52](#))
- 2055/363 . . . {with special means or properties for lateral tracking of the flexible members running on the pulley, e.g. with crowning to keep a belt on track}
- 2055/366 . . . {with means providing resilience or vibration damping}
- 55/38 . . . Means or measures for increasing adhesion
- 55/40 . . . with spokes ([F16H 55/48](#) takes precedence)
- 55/42 . . . Laminated pulleys
- 55/44 . . . Sheet-metal pulleys
- 55/46 . . . Split pulleys
- 55/48 . . . manufactured exclusively or in part of non-metallic material, e.g. plastics ([F16H 55/38](#), [F16H 55/42](#), [F16H 55/46](#) take precedence {; manufacture of wooden wheels [B27H 7/00](#)})
- 55/49 . . . Features essential to V-belts pulleys
- 55/50 . . . Features essential to rope pulleys
- 55/52 . . Pulleys or friction discs of adjustable construction
- 55/54 . . . of which the bearing parts are radially adjustable
- 55/56 . . . of which the bearing parts are relatively axially adjustable
- 55/563 {actuated by centrifugal masses}
- 55/566 {only adjustable when pulley is stationary}
- 57/00** **General details of gearing (of screw-and-nut gearing [F16H 25/00](#); of fluid gearing [F16H 39/00](#) - [F16H 43/00](#))**
- 57/0006 . {Vibration-damping or noise reducing means specially adapted for gearings (devices for varying tension of belts, ropes or chains with damping means [F16H 7/0829](#); toothed members with construction providing vibration damping [F16H 55/14](#); reducing vibrations or noise of the gearbox casing [F16H 57/028](#); suppression of vibrations or noise of gear selectors [F16H 59/0208](#); control of hydrostatic fluid gearing preventing or reducing vibrations or noise [F16H 61/4183](#))}
- 2057/0012 . . {for reducing drive line oscillations}
- 57/0018 . {Shaft assemblies for gearings (camshafts with single track cams [F16H 53/02](#))}
- 57/0025 . . {with gearing elements rigidly connected to a shaft, e.g. securing gears or pulleys by specially adapted splines, keys or methods}
- 57/0031 . . {with gearing elements rotatable supported on the shaft ([F16H 57/021](#) takes precedence)}
- 57/0037 . . {Special features of coaxial shafts, e.g. relative support thereof}
- 2057/0043 . {Mounting or adjusting transmission parts by robots}
- 2057/005 . {Mounting preassembled units, i.e. using pre-mounted structures to speed up final mounting process (mounting of gears or shafts in a gearbox [F16H 57/022](#))}
- 2057/0056 . {Mounting parts arranged in special position or by special sequence, e.g. for keeping particular parts in his position during assembly}
- 2057/0062 . {Tools specially adapted for assembly of transmissions}
- 2057/0068 . {Repairing of transmissions by using repair kits (for gear wheels [F16H 2055/175](#))}
- 2057/0075 . {Modifying standard transmissions from manufacturer, e.g. by adding an extension for additional ratios (for control [F16H 2061/0062](#))}
- 2057/0081 . {Fixing of, or adapting to transmission failure (detecting transmission failures [F16H 2057/018](#))}
- 2057/0087 . {Computer aided design [CAD] specially adapted for gearing features (computer aided design per se [G06F 30/00](#)); Analysis of gear systems}
- 2057/0093 . {Means or measures for transport, shipping or packaging}
- 57/01 . Monitoring wear or stress of gearing elements, e.g. for triggering maintenance
- 2057/012 . . {of gearings}
- 2057/014 . . {of friction elements in transmissions}
- 2057/016 . . {Monitoring of overload conditions}
- 2057/018 . . {Detection of mechanical transmission failures (fixing or adapting to failure [F16H 2057/0081](#); of transmission control [F16H 61/12](#))}
- 57/02 . Gearboxes; Mounting gearing therein
- NOTE**
When classifying in this group, in the absence of an indication to the contrary, classification is made in all appropriate subgroups.
- 57/02004 . . {the gears being positioned relative to one another by rolling members or by specially adapted surfaces on the gears, e.g. by a rolling surface with the diameter of the pitch circle}
- 2057/02008 . . {characterised by specific dividing lines or planes of the gear case}
- 2057/02013 . . {Extension units for gearboxes, e.g. additional units attached to a main gear}
- 2057/02017 . . {characterised by special features related to the manufacturing of the gear case, e.g. special adaptations for casting}
- 2057/02021 . . {with means for adjusting alignment}
- 2057/02026 . . {Connection of auxiliaries with a gear case; Mounting of auxiliaries on the gearbox}
- 2057/0203 . . {the gearbox is associated or combined with a crank case of an engine}
- 2057/02034 . . {Gearboxes combined or connected with electric machines (structural association with electric machines [H02K 7/116](#))}
- 2057/02039 . . {Gearboxes for particular applications}
- 2057/02043 . . . {for vehicle transmissions}
- 2057/02047 {Automatic transmissions}
- 2057/02052 {Axle units; Transfer casings for four wheel drive}
- 2057/02056 {for utility vehicles, e.g. tractors or agricultural machines}
- 2057/0206 {for commercial vehicles, e.g. buses or trucks}
- 2057/02065 {for motorcycles or squads}
- 2057/02069 . . . {for industrial applications}
- 2057/02073 {Reduction gearboxes for industry}
- 2057/02078 . . . {for wind turbines}
- 2057/02082 . . . {for application in vehicles other than propelling, e.g. adjustment of parts}
- 2057/02086 . . {Measures for reducing size of gearbox, e.g. for creating a more compact transmission casing}

- 2057/02091 . . {Measures for reducing weight of gearbox (by using particular materials [F16H 57/032](#))}
- 2057/02095 . . {Measures for reducing number of parts or components}
- 57/021 . . Shaft support structures, e.g. partition walls, bearing eyes, casing walls or covers with bearings
- 2057/0213 . . . {Support of worm gear shafts}
- 2057/0216 . . . {Intermediate shaft supports, e.g. by using a partition wall}
- 57/022 . . . Adjustment of gear shafts or bearings (for compensating misalignment of axes of toothed gearings without orbital motion [F16H 1/26](#); for compensating misalignment of axes of planetary gears [F16H 1/48](#))
- 2057/0221 {Axial adjustment}
- 2057/0222 {Lateral adjustment}
- 2057/0224 {using eccentric bushes}
- 2057/0225 {with means for adjusting alignment}
- 2057/0227 {Assembly method measuring first tolerances or position and selecting mating parts accordingly, e.g. special sized shims for transmission bearings}
- 2057/0228 {Mounting with rough tolerances and fine adjustment after assembly}
- 57/023 . . Mounting or installation of gears or shafts in the gearboxes, e.g. methods or means for assembly
- 2057/0235 . . . {specially adapted to allow easy accessibility and repair (using repair kits [F16H 2057/0068](#))}
- 57/025 . . Support of gearboxes, e.g. torque arms, or attachment to other devices
- 57/027 . . characterised by means for venting gearboxes, e.g. air breathers
- 57/028 . . characterised by means for reducing vibration or noise
- 57/029 . . characterised by means for sealing the gearboxes, e.g. to improve airtightness
- 57/03 . . characterised by means for reinforcing gearboxes, e.g. ribs
- 57/031 . . characterised by covers or lids for gearboxes
- 57/032 . . characterised by the materials used
- 2057/0325 . . {Moulded casings made from plastic}
- 57/033 . . Series gearboxes, e.g. gearboxes based on the same design being available in different sizes or gearboxes using a combination of several standardised units
- 2057/0335 . . . {Series transmissions of modular design, e.g. providing for different transmission ratios or power ranges}
- 57/035 . . Gearboxes for gearing with endless flexible members
- 57/037 . . Gearboxes for accommodating differential gearings (rotating cases for differential gearings [F16H 48/40](#))
- 57/038 . . Gearboxes for accommodating bevel gears ([F16H 57/037](#) takes precedence)
- 57/039 . . Gearboxes for accommodating worm gears
- 57/04 . . Features relating to lubrication or cooling {or heating} ({in hydrokinetic gearing [F16H 41/30](#); } control of lubrication or cooling in hydrostatic gearing [F16H 61/4165](#))
- 57/0401 . . {using different fluids, e.g. a traction fluid for traction gearing and a lubricant for bearings or reduction gears}
- 57/0402 . . {Cleaning of lubricants, e.g. filters or magnets}
- 57/0404 . . . {Lubricant filters}
- 57/0405 . . {Monitoring quality of lubricant or hydraulic fluids}
- 57/0406 . . {Absorption elements for lubricants, e.g. oil felts}
- 57/0408 . . {Exchange, draining or filling of transmission lubricant}
- 57/0409 . . {characterised by the problem to increase efficiency, e.g. by reducing splash losses}
- 57/041 . . {Coatings or solid lubricants, e.g. antiseize layers or pastes}
- 57/0412 . . {Cooling or heating; Control of temperature}
- 57/0413 . . . {Controlled cooling or heating of lubricant; Temperature control therefor}
- 57/0415 . . . {Air cooling or ventilation; Heat exchangers; Thermal insulations}
- 57/0416 {Air cooling or ventilation}
- 57/0417 {Heat exchangers adapted or integrated in the gearing}
- 57/0419 {Thermal insulations}
- 57/042 . . {Guidance of lubricant}
- 57/0421 . . . {on or within the casing, e.g. shields or baffles for collecting lubricant, tubes, pipes, grooves, channels or the like}
- 57/0423 {Lubricant guiding means mounted or supported on the casing, e.g. shields or baffles for collecting lubricant, tubes or pipes (means for guiding lubricant into an axial channel of a shaft [F16H 57/0426](#); lubrication by injection, injection nozzles or tubes therefore [F16H 57/0456](#))}
- 57/0424 {Lubricant guiding means in the wall of or integrated with the casing, e.g. grooves, channels, holes (means for guiding lubricant into an axial channel of a shaft [F16H 57/0426](#))}
- 57/0426 {Means for guiding lubricant into an axial channel of a shaft}
- 57/0427 . . . {on rotary parts, e.g. using baffles for collecting lubricant by centrifugal force}
- 57/0428 {Grooves with pumping effect for supplying lubricants}
- 57/043 . . . {within rotary parts, e.g. axial channels or radial openings in shafts}
- 57/0431 {Means for guiding lubricant directly onto a tooth surface or to foot areas of a gear, e.g. by holes or grooves in a tooth flank}
- 57/0432 . . . {Lubricant guiding means on or inside shift rods or shift forks (shift rods or shift forks to be lubricated, cooled or heated [F16H 57/0468](#))}
- 57/0434 . . {relating to lubrication supply, e.g. pumps (arrangement of pumps [F16H 57/0441](#)); Pressure control (grooves with pumping effect for supplying lubricant [F16H 57/0428](#); generation and variation of line pressure for transmission control [F16H 61/0021](#))}
- 57/0435 . . . {Pressure control for supplying lubricant; Circuits or valves therefor}
- 57/0436 . . . {Pumps}
- 57/0438 {Pumps of jet type, e.g. jet pumps with means to inject high pressure fluid to the suction area thereby supercharging the pump or means reducing cavitations}

- 57/0439 {using multiple pumps with different power sources or a single pump with different power sources, e.g. one and the same pump may selectively be driven by either the engine or an electric motor}
- 57/0441 . . . {Arrangements of pumps}
- 57/0442 . . . {for supply in case of failure, i.e. auxiliary supply}
- 57/0443 . . . {for supply of lubricant during tilt or high acceleration, e.g. problems related to the tilt or extreme acceleration of the transmission casing and the supply of lubricant under these conditions}
- 57/0445 . . . {for supply of different gearbox casings or sections}
- 57/0446 . . . {the supply forming part of the transmission control unit, e.g. for automatic transmissions}
- 57/0447 . . {Control of lubricant levels, e.g. lubricant level control dependent on temperature}
- 57/0449 . . . {Sensors or indicators for controlling the fluid level}
- 57/045 . . {Lubricant storage reservoirs, e.g. reservoirs in addition to a gear sump for collecting lubricant in the upper part of a gear case}
- 57/0452 . . . {Oil pans}
- 57/0453 . . . {Section walls to divide a gear sump}
- 57/0454 . . . {Sealings between different partitions of a gearing or to a reservoir (means for sealing gearboxes F16H 57/029)}
- 57/0456 . . {Lubrication by injection; Injection nozzles or tubes therefor (oil mist or spray lubrication F16H 57/0458)}
- 57/0457 . . {Splash lubrication (characterised by the problem reducing losses, e.g. splash losses F16H 57/0409)}
- 57/0458 . . {Oil-mist or spray lubrication; Means to reduce foam formation (reducing foam formation by venting F16H 57/027)}
- 57/046 . . . {Oil-mist or spray lubrication}
- 57/0461 . . . {Means to reduce foam formation}
- 57/0463 . . {Grease lubrication; Drop-feed lubrication}
- 57/0464 . . . {Grease lubrication}
- 57/0465 . . . {Drop-feed lubrication}
- 57/0467 . . {Elements of gearings to be lubricated, cooled or heated}
- 57/0468 . . . {Shift rods or shift forks}
- 57/0469 . . . {Bearings or seals}
- 57/0471 {Bearing}
- 57/0472 {Seals}
- 57/0473 . . . {Friction devices, e.g. clutches or brakes}
- 57/0475 . . . {Engine and gearing, i.e. joint lubrication or cooling or heating thereof (electric machines and gearing F16H 57/0476)}
- 57/0476 . . . {Electric machines and gearing, i.e. joint lubrication or cooling or heating thereof}
- 57/0478 . . . {Synchromesh devices}
- 57/0479 . . . {Gears or bearings on planet carriers}
- 57/048 . . {Type of gearings to be lubricated, cooled or heated}
- 57/0482 . . . {Gearings with gears having orbital motion}
- 57/0483 {Axle or inter-axle differentials}
- 57/0484 {with variable gear ratio or for reversing rotary motion}
- 57/0486 {with fixed gear ratio (differentials F16H 57/0483)}
- 57/0487 . . . {Friction gearings}
- 57/0489 {with endless flexible members, e.g. belt CVTs}
- 57/049 {of the toroid type}
- 57/0491 {of the cone ring type}
- 57/0493 . . . {Gearings with spur or bevel gears (differentials with spur or bevel gears F16H 57/0483)}
- 57/0494 {with variable gear ratio or for reversing rotary motion}
- 57/0495 {with fixed gear ratio}
- 57/0497 . . . {Screw mechanisms}
- 57/0498 . . . {Worm gearings}
- 57/05 . . of chains
- 57/08 . of gearings with members having orbital motion
- 57/082 . . {Planet carriers}
- 2057/085 . . {Bearings for orbital gears}
- 2057/087 . . {Arrangement and support of friction devices in planetary gearings, e.g. support of clutch drums, stacked arrangements of friction devices (see also arrangements for shifting planetary gears F16H 3/62, F16H 63/3026)}
- 57/10 . . Braking arrangements
- 57/12 . Arrangements for adjusting or for taking-up backlash not provided for elsewhere
- 2057/121 . . {using parallel torque paths and means to twist the two path against each other}
- 2057/122 . . . {by using two independent drive sources, e.g. electric motors}
- 2057/123 . . {using electric control means}
- 2057/125 . . {Adjustment of backlash during mounting or assembly of gearing}
- 2057/126 . . {Self-adjusting during operation, e.g. by a spring}
- 2057/127 . . . {using springs}
- 2057/128 . . {using axial positioning of gear wheel with addendum modification on gear width, i.e. backlash is compensated by axial positioning of a slightly conical gear wheel}

Control of gearings conveying rotary motion

NOTES

1. Attention is drawn to the Notes after the title of subclass [B60W](#).
2. In groups [F16H 59/00](#) - [F16H 63/00](#), clutches positioned within a gearbox are considered as comprising part of the gearings.
3. In groups [F16H 59/00](#) - [F16H 63/00](#), the following terms or expressions are used with the meaning indicated:
 - "final output element" means the final element which is moved to establish a gear ratio, i.e. which achieves the linking between two power transmission means, e.g. reverse idler gear, gear cluster, coupling sleeve, apply piston of a hydraulic clutch;
 - "mechanism" means a kinematic chain consisting either of a single element or alternatively of a series of elements, the position of each point on the kinematic chain being derivable from the position of any other point on the chain, and therefore, for a given position of a point on one of the elements forming the kinematic chain there is only one position for each of the other points on the elements forming the kinematic chain;
 - "final output mechanism" means the mechanism which includes the final output element;

- "actuating mechanism" means the mechanism, the movement of which causes the movement of another mechanism by being in mutual contact;
 - "final actuating mechanism" means the mechanism actuating the final output mechanism.
 - {"mechanical force" means the force transmitted by an actuating mechanism or the human body}
4. Combinations of features individually covered by group [F16H 61/00](#) and one or both of groups [F16H 59/00](#) and [F16H 63/00](#) are classified in group [F16H 61/00](#).
5. Combinations of features individually covered by groups [F16H 59/00](#) and [F16H 63/00](#) are classified in group [F16H 63/00](#).
6. When classifying in groups [F16H 59/00](#) - [F16H 63/00](#), control inputs or types of gearing, which are not identified by the preceding notes concerning combinations, and which are considered to represent information of interest for search, may also be classified. Such non-obligatory classification should be given as "additional information", e.g. selected from subgroup [F16H 61/66](#) relating to the type of gearing controlled or from group [F16H 59/00](#) relating to control inputs

59/00 Control inputs to {control units of} change-speed-, or reversing-gearings for conveying rotary motion

- 2059/003 . . {Detecting or using driving style of a driver, e.g. for adapting shift schedules}
- 2059/006 . . {Overriding automatic control}
- 59/02 . . Selector apparatus

NOTE

Selection apparatus of general applicability or of interest apart from its use in control of gearings conveying rotary motion is also classified in subclass [G05G](#)

- 59/0204 . . {for automatic transmissions with means for range selection and manual shifting, e.g. range selector with tiptronic}
- 59/0208 . . {with means for suppression of vibrations or reduction of noise}
- 59/0213 . . {with sealing means, e.g. against entry of dust}
- 59/0217 . . {with electric switches or sensors not for gear or range selection, e.g. for controlling auxiliary devices (for gear selection [F16H 59/044](#); for range selection [F16H 59/105](#))}
- 2059/0221 . . {for selecting modes, i.e. input device (for selecting between different modes with range selector [F16H 2059/082](#); for conjoint control [B60W 30/182](#))}
- 2059/0226 . . . {for selecting particular shift speeds, e.g. a fast shift speed with aggressive gear change}
- 2059/023 . . {Selectors for gearings using voice control (for vehicle control [B60R 16/0373](#))}
- 2059/0234 . . {Selectors for gearings using foot control}
- 2059/0239 . . {Up- and down-shift or range or mode selection by repeated movement (mechanical step by step selection devices [F16H 63/14](#))}
- 2059/0243 . . . {with push buttons, e.g. shift buttons arranged on steering wheel (range selection with push buttons [F16H 59/12](#))}
- 2059/0247 . . . {with lever or paddle behind steering wheel}
- 2059/0252 . . {with means for initiating skip or double gear shifts, e.g. by moving selection lever beyond a threshold}
- 2059/0256 . . {Levers for forward-reverse selection only, e.g. for working machines having a separate lever for switching between forward and reverse mode}

- 2059/026 . . {Details or special features of the selector casing or lever support (for mechanical gear shifting [F16H 59/042](#))}
- 2059/0265 . . . {Selector lever support with pivot axis offset, e.g. support by four bar linkage to create pivoting centre outside the mechanism}
- 2059/0269 . . . {Ball joints or spherical bearings for supporting the lever}
- 2059/0273 . . . {Cardan or gimbal type joints for supporting the lever}
- 59/0278 . . {Constructional features of the selector lever, e.g. grip parts, mounting or manufacturing}
- 2059/0282 . . . {Lever handles with lock mechanisms, e.g. for allowing selection of reverse gear or releasing lever from park position}
- 2059/0286 . . . {with range or splitter selector on selector lever}
- 2059/0291 . . {comprising safety means for preventing injuries in case of accidents}
- 2059/0295 . . {with mechanisms to return lever to neutral or datum position, e.g. by return springs}
- 59/04 . . Ratio selector apparatus
- 59/041 . . . {consisting of a final output mechanism, e.g. ratio selector being directly linked to a shiftfork}
- 59/042 . . . {comprising a final actuating mechanism (multiple final output mechanism in a gearbox [F16H 63/08](#))}
- 59/044 . . . {consisting of electrical switches or sensors (range selectors with electric switches or sensors [F16H 59/105](#))}
- 59/045 . . . {consisting of fluid valves}
- 2059/047 . . . {with essentially straight linear movement for gear selection, e.g. straight selection movement using detent mechanism for improving feeling (up-down shift by repeated movements [F16H 2059/0239](#))}
- 2059/048 . . . {with means for unlocking select or shift movement to allow access to reverse gear position (particular details of the lever handle [F16H 2059/0282](#))}
- 59/06 . . . the ratio being infinitely variable
- 2059/065 {Inching pedals for setting the ratio of an hydrostatic transmission}
- 59/08 . . Range selector apparatus
- 2059/081 . . . {using knops or discs for rotary range selection}
- 2059/082 . . . {with different modes}
- 2059/083 {Overdrive or overdrive cut-off}
- 2059/084 {Economy mode}
- 2059/085 {Power mode}
- 2059/086 {Adaptive mode, e.g. learning from the driver}
- 2059/087 {Winter mode, e.g. to start on snow or slippery surfaces}
- 2059/088 . . . {Fast forward-reverse-sequence mode}
- 59/10 . . . comprising levers
- 59/105 {consisting of electrical switches or sensors}
- 59/12 . . . comprising push button devices
- 59/14 . . Inputs being a function of torque or torque demand
- 59/141 . . {of rate of change of torque or torque demand}
- 2059/142 . . {of driving resistance calculated from weight, slope, or the like}

2059/144	. . {characterised by change between positive and negative drive line torque, e.g. torque changes when switching between coasting and acceleration}	59/62	. . Atmospheric pressure
2059/145	. . {being a function of power demand of auxiliary devices}	59/64	. . Atmospheric temperature
2059/147	. . {Transmission input torque, e.g. measured or estimated engine torque}	59/66	. . Road conditions, e.g. slope, slippery
2059/148	. . {Transmission output torque, e.g. measured or estimated torque at output drive shaft}	2059/663	. . . {Road slope}
59/16	. . Dynamometric measurement of torque	2059/666	. . . {Determining road conditions by using vehicle location or position, e.g. from global navigation systems [GPS]}
59/18	. . dependent on the position of the accelerator pedal	59/68	. Inputs being a function of gearing status
2059/183	. . . {Rate of change of accelerator position, i.e. pedal or throttle change gradient}	2059/6807	. . {Status of gear-change operation, e.g. clutch fully engaged}
2059/186	. . . {Coasting}	2059/6815	. . {Post shift value of gearing, i.e. calculated or estimated parameters after shift is completed, e.g. estimated output torque after shift is performed}
59/20	. . . Kickdown	2059/6823	. . {Sensing neutral state of the transmission}
59/22	. . . Idle position	2059/683	. . {Sensing pressure in control systems or in fluid controlled devices, e.g. by pressure sensors (for hydrostatic transmissions F16H 2059/6861)}
59/24	. . dependent on the throttle opening	2059/6838	. . {Sensing gearing status of hydrostatic transmissions}
59/26	. . dependent on pressure	2059/6846	. . . {the flow in hydrostatic transmissions circuits, e.g. high, low or differential pressures}
59/28	. . . Gasifier pressure in gas turbines	2059/6853	. . . {the state of the transmission units, i.e. motor or pump capacity, e.g. for controlled shifting of range gear}
59/30	. . . Intake manifold vacuum	2059/6861	. . . {the pressures, e.g. high, low or differential pressures}
59/32	. . . Supercharger pressure in internal combustion engines	2059/6869	. . . {the pump speed}
59/34	. . dependent on fuel feed	2059/6876	. . . {the motor speed}
59/36	. Inputs being a function of speed	2059/6884	. . . {Sensing or calculating the pump torque}
2059/363	. . {Rate of change of input shaft speed, e.g. of engine or motor shaft}	2059/6892	. . . {Sensing or calculating the motor torque}
2059/366	. . {Engine or motor speed}	59/70	. . dependent on the ratio established
59/38	. . of gearing elements	2059/702	. . . {Rate of change of gear ratio, e.g. for triggering clutch engagement}
2059/385	. . . {Turbine speed}	2059/704	. . . {Monitoring gear ratio in CVT's}
59/40	. . . Output shaft speed	2059/706	. . . {Monitoring gear ratio in stepped transmissions, e.g. by calculating the ratio from input and output speed}
2059/405	. . . {Rate of change of output shaft speed or vehicle speed}	2059/708	. . . {Sensing reverse gear, e.g. by a reverse gear switch}
59/42	. . . Input shaft speed	59/72	. . dependent on oil characteristics, e.g. temperature, viscosity
2059/425 {Rate of change of input or turbine shaft speed}	2059/725	. . . {Sensing or calculating temperature of friction devices, e.g. clutches to prevent overheating of friction linings}
59/44	. . dependent on machine speed of the machine, (e.g. the vehicle)	59/74	. Inputs being a function of engine parameters (F16H 59/14 takes precedence)
2059/443	. . . {Detecting travel direction, e.g. the forward or reverse movement of the vehicle}	2059/743	. . {using engine performance or power for control of gearing (transmission input torque F16H 2059/147)}
2059/446	. . . {Detecting vehicle stop, i.e. the vehicle is at stand still, e.g. for engaging parking lock}	2059/746	. . {Engine running state, e.g. on-off of ignition switch}
59/46	. . dependent on a comparison between speeds	59/76	. . Number of cylinders operating
2059/462	. . . {Detecting synchronisation, i.e. speed difference is approaching zero}	59/78	. . Temperature
2059/465	. . . {Detecting slip, e.g. clutch slip ratio}	61/00	Control functions within {control units of} change-speed- or reversing-gearings for conveying rotary motion (; Control of exclusively fluid gearing, friction gearing, gearings with endless flexible members or other particular types of gearing)
2059/467 {of torque converter}	61/0003	. {Arrangement or mounting of elements of the control apparatus, e.g. valve assemblies or snapfittings of valves; Arrangements of the control unit on or in the transmission gearbox}
59/48	. Inputs being a function of acceleration		
59/50	. Inputs being a function of the status of the machine, e.g. position of doors or safety belts		
2059/503	. . {Axle-load distribution}		
2059/506	. . {Wheel slip}		
59/52	. . dependent on the weight of the machine, e.g. change in weight resulting from passengers boarding a bus		
2059/525	. . . {the machine undergoing additional towing load, e.g. by towing a trailer}		
59/54	. . dependent on signals from the brakes, e.g. parking brakes		
59/56	. . dependent on signals from the main clutch		
59/58	. . dependent on signals from the steering		
59/60	. Inputs being a function of ambient conditions		
2059/605	. . {Traffic stagnation information, e.g. traffic jams}		

- 61/0006 . . {Electronic control units for transmission control, e.g. connectors, casings or circuit boards}
 - 61/0009 . . {Hydraulic control units for transmission control, e.g. assembly of valve plates or valve units}
 - 2061/0012 . {Transmission control for optimising power output of driveline}
 - 2061/0015 . {Transmission control for optimising fuel consumptions}
 - 2061/0018 . {Transmission control for optimising exhaust emissions}
 - 61/0021 . {Generation or control of line pressure}
 - 61/0025 . . {Supply of control fluid; Pumps therefore}
 - 61/0028 . . . {using a single pump driven by different power sources}
 - 61/0031 . . . {using auxiliary pumps, e.g. pump driven by a different power source than the engine}
 - 2061/0034 . . {Accumulators for fluid pressure supply; Control thereof}
 - 2061/0037 . . {characterised by controlled fluid supply to lubrication circuits of the gearing (see also lubrication control F16H 57/0446)}
 - 2061/004 . {Venting trapped air from hydraulic systems (venting of hydrostatic transmissions F16H 61/4174; deaeration or removal of unsolved gas F15B 21/044)}
 - 2061/0043 . {Cleaning of hydraulic parts, e.g. removal of an orifice clogging}
 - 2061/0046 . {Details of fluid supply channels, e.g. within shafts, for supplying friction devices or transmission actuators with control fluid}
 - 2061/005 . {Supply of electric power, e.g. batteries for back up supply}
 - 2061/0053 . {Initializing the parameters of the controller}
 - 2061/0056 . {Powering down of the controller}
 - 61/0059 . {Braking of gear output shaft using simultaneous engagement of friction devices applied for different gear ratios}
 - 2061/0062 . {Modifying an existing transmission control from a manufacturer for improvement or adaptation, e.g. by replacing a valve or an electric part}
 - 2061/0065 . {Modifying or tuning an existing transmission control for racing, e.g. adaptation of valves for very fast shifting}
 - 2061/0068 . {Method or means for testing of transmission controls or parts thereof}
 - 2061/0071 . . {Robots or simulators for testing control functions in automatic transmission (testing of transmissions G01M 13/02)}
 - 2061/0075 . {characterised by a particular control method}
 - 2061/0078 . . {Linear control, e.g. PID, state feedback or Kalman}
 - 2061/0081 . . {Fuzzy logic}
 - 2061/0084 . . {Neural networks}
 - 2061/0087 . . {Adaptive control, e.g. the control parameters adapted by learning}
 - 2061/009 . . {using formulas or mathematic relations for calculating parameters}
 - 2061/0093 . . {using models to estimate the state of the controlled object}
 - 2061/0096 . . {using a parameter map}
 - 61/02 . . characterised by the signals used {(for shift actuators F16H 61/28, for continuously variable gearings F16H 61/66)}
- NOTES**
1. Control units where gearshift is controlled by an electric circuit, are classified in F16H 61/0202
 2. Control units where gearshift is controlled by hydraulic signals and a subfunction, e.g. kickdown, is controlled by an electric circuit, are classified in F16H 61/0262 with indexing of the electric features
- 61/0202 . . {the signals being electric (F16H 61/04 takes precedence)}
 - 61/0204 . . . {for gearshift control, e.g. control functions for performing shifting or generation of shift signal}
 - 61/0206 {Layout of electro-hydraulic control circuits, e.g. arrangement of valves (for control of actuators selecting and moving final output members, e.g. shift forks F16H 61/2807)}
 - 2061/0209 {with independent solenoid valves modulating the pressure individually for each clutch or brake}
 - 61/0211 {characterised by low integration or small number of valves}
 - 61/0213 {characterised by the method for generating shift signals}
 - 2061/0216 {Calculation or estimation of post shift values for different gear ratios, e.g. by using engine performance tables}
 - 2061/0218 {Calculation or estimation of the available ratio range, i.e. possible gear ratios, e.g. for prompting a driver with a display}
 - 2061/022 {Calculation or estimation of optimal gear ratio, e.g. best ratio for economy drive or performance according driver preference, or to optimise exhaust emissions}
 - 2061/0223 {Generating of new shift maps, i.e. methods for determining shift points for a schedule by taking into account driveline and vehicle conditions}
 - 2061/0225 {Modifying of shift maps by manual control, e.g. by learning values from the driver during manual shift mode}
 - 2061/0227 {Shift map selection, i.e. methods for controlling selection between different shift maps, e.g. to initiate switch to a map for up-hill driving}
 - 2061/023 {Drive-off gear selection, i.e. optimising gear ratio for drive off of a vehicle}
 - 2061/0232 {Selecting ratios for bringing engine into a particular state, e.g. for fast warming up or for reducing exhaust emissions}
 - 2061/0234 {Adapting the ratios to special vehicle conditions}
 - 2061/0237 {Selecting ratios for providing engine braking}
 - 2061/0239 {Selecting ratios for preventing or cancelling wheel slip}
 - 2061/0241 {Adapting the ratio to special transmission conditions, e.g. shifts during warming up phase of transmission when fluid viscosity is high}

- 2061/0244 {Adapting the automatic ratio to direct driver requests, e.g. manual shift signals or kick down}
- 61/0246 {characterised by initiating reverse gearshift}
- 61/0248 . . . {Control units where shifting is directly initiated by the driver, e.g. semi-automatic transmissions (generation of movements for final actuating mechanisms [F16H 61/28](#))}
- 61/0251 . . . {Elements specially adapted for electric control units, e.g. valves for converting electrical signals to fluid signals}
- 2061/0253 {Details of electro hydraulic valves, e.g. lands, ports, spools or springs}
- 2061/0255 {Solenoid valve using PWM or duty-cycle control}
- 2061/0258 {Proportional solenoid valve}
- 2061/026 {On-off solenoid valve}
- 61/0262 . . {the signals being hydraulic ([F16H 61/04](#) takes precedence)}
- 61/0265 . . . {for gearshift control, e.g. control functions for performing shifting or generation of shift signals}
- 61/0267 {Layout of hydraulic control circuits, e.g. arrangement of valves (for control of actuators selecting and moving final output members, e.g. shift forks [F16H 61/30](#))}
- 61/0269 {characterised by low integration or small number of valves}
- 61/0272 {characterised by initiating reverse gearshift}
- 61/0274 . . . {Control units where shifting is directly initiated by the driver, e.g. semi-automatic transmissions (generation of movements for final actuating mechanisms [F16H 61/28](#))}
- 61/0276 . . . {Elements specially adapted for hydraulic control units, e.g. valves}
- 2061/0279 {Details of hydraulic valves, e.g. lands, ports, spools or springs}
- 2061/0281 {Rotary shift valves, e.g. with a rotary moveable spool for supply of fluid to different channels}
- 61/0283 {Governor valves}
- 61/0286 {Manual valves}
- 2061/0288 {Relay valve, e.g. valve arranged between shift valve and servo}
- 61/029 {Throttle valves}
- 61/0293 . . {the signals being purely mechanical}
- 61/0295 . . . {Automatic gear shift control, e.g. initiating shift by centrifugal forces}
- 61/0297 . . . {Gear shift control where shifting is directly initiated by the driver, e.g. semi-automatic transmissions}
- 61/04 . . Smoothing ratio shift
- 61/0403 . . {Synchronisation before shifting}
- 2061/0407 . . . {by control of clutch in parallel torque path}
- 2061/0411 . . . {by control of shaft brakes}
- 2061/0414 . . . {by retarder control}
- 2061/0418 . . . {by using different synchronisation devices simultaneously, e.g. for faster synchronisation}
- 2061/0422 . . . {by an electric machine, e.g. by accelerating or braking the input shaft}
- 2061/0425 . . {Bridging torque interruption}
- 2061/0429 . . . {by torque supply with a clutch in parallel torque path}
- 2061/0433 . . . {by torque supply with an electric motor}
- 61/0437 . . {by using electrical signals ([F16H 61/0403](#) and [F16H 61/061](#) take precedence)}
- 2061/044 . . . {when a freewheel device is disengaged or bridged}
- 2061/0444 . . . {during fast shifting over two gearsteps, e.g. jumping from fourth to second gear}
- 2061/0448 . . . {using a particular sequence of gear ratios or friction members}
- 2061/0451 . . . {during swap-shifts, i.e. gear shifts between different planetary units, e.g. with double transitions shift involving three or more friction members}
- 2061/0455 . . . {during shifts involving three or more shift members, e.g. release of 3-4 clutch, 2-4 brake and apply of forward clutch C1}
- 2061/0459 . . . {using map for shift parameters, e.g. shift time, slip or pressure gradient, for performing controlled shift transition and adapting shift parameters by learning}
- 2061/0462 . . . {by controlling slip rate during gear shift transition}
- 2061/0466 . . . {Smoothing shift shock by apply or release of band brake servos, e.g. overlap control of band brake and a clutch or *vice versa*}
- 2061/047 . . . {by preventing or solving a tooth butt situation upon engagement failure due to misalignment of teeth}
- 2061/0474 . . . {by smoothing engagement or release of positive clutches; Methods or means for shock free engagement of dog clutches ([for tooth butt situations F16H 2061/047](#))}
- 2061/0477 . . . {by suppression of excessive engine flare or turbine racing during shift transition ([engine flare caused by lock-up release F16H 61/143](#))}
- 2061/0481 . . . {during range shift from drive (D) or reverse (R) to neutral (N)}
- 2061/0485 . . . {during range shift from neutral (N) to reverse (R)}
- 2061/0488 . . . {during range shift from neutral (N) to drive (D)}
- 2061/0492 . . . {for high engine torque, e.g. during acceleration or uphill driving}
- 2061/0496 . . . {for low engine torque, e.g. during coasting, sailing or engine braking}
- 61/06 . . by controlling rate of change of fluid pressure
- 61/061 . . . {using electric control means}
- 2061/062 {for controlling filling of clutches or brake servos, e.g. fill time, fill level or pressure during filling}
- 2061/064 {for calibration of pressure levels for friction members, e.g. by monitoring the speed change of transmission shafts}
- 61/065 . . . {using fluid control means}
- 61/067 {using an accumulator}
- 61/068 {using an orifice control valve ([F16H 61/067](#) takes precedence)}
- 61/08 . . Timing control
- 2061/085 . . . {Timing of auxiliary gear shifts}
- 61/10 . . Controlling shift hysteresis
- 61/12 . . Detecting malfunction or potential malfunction, e.g. fail safe ([in control of hydrostatic gearing F16H 61/4192](#)); {Circumventing or fixing failures}

- 2061/1204 . . {for malfunction caused by simultaneous engagement of different ratios resulting in transmission lock state or tie-up condition ([lock state for braking F16H 61/0059](#))}
 - 2061/1208 . . {with diagnostic check cycles; Monitoring of failures}
 - 2061/1212 . . . {Plausibility checks; Counting means for repeated failures}
 - 2061/1216 . . . {Display or indication of detected failures}
 - 2061/122 . . {Avoiding failures by using redundant parts}
 - 2061/1224 . . {Adapting to failures or work around with other constraints, e.g. circumvention by avoiding use of failed parts}
 - 2061/1228 . . {Fixing failures by repairing failed parts, e.g. loosening a sticking valve}
 - 2061/1232 . . {Bringing the control into a predefined state, e.g. giving priority to particular actuators or gear ratios}
 - 2061/1236 . . . {using fail priority valves}
 - 2061/124 . . {Limiting the input power, torque or speed}
 - 2061/1244 . . {Keeping the current state}
 - 2061/1248 . . {Resuming normal operation}
 - 2061/1252 . . {Fail safe valves ([fail priority valves F16H 2061/1236](#))}
 - 2061/1256 . . {characterised by the parts or units where malfunctioning was assumed or detected}
 - 2061/126 . . . {the failing part is the controller}
 - 2061/1264 {Hydraulic parts of the controller, e.g. a sticking valve or clogged channel}
 - 2061/1268 {Electric parts of the controller, e.g. a defect solenoid, wiring or microprocessor}
 - 2061/1272 . . . {the failing part is a part of the final output mechanism, e.g. shift rods or forks}
 - 2061/1276 . . . {the failing part is a friction device, e.g. clutches or brakes}
 - 2061/128 {the main clutch}
 - 2061/1284 . . . {the failing part is a sensor}
 - 2061/1288 . . . {the failing part is an actuator}
 - 2061/1292 . . . {the failing part is the power supply, e.g. the electric power supply}
 - 2061/1296 . . . {the failing part is an electric machine forming part of the transmission}
 - 61/14 . . Control of torque converter lock-up clutches
 - 61/141 . . {using means only actuated by centrifugal force}
 - 61/142 . . . {the means being hydraulic valves}
 - 61/143 . . {using electric control means}
 - 2061/145 . . . {for controlling slip, e.g. approaching target slip value}
 - 2061/146 . . . {for smoothing gear shift shock}
 - 2061/147 . . . {during engine braking, e.g. to attenuate gear clunk when torque direction is changed}
 - 61/148 . . {using mechanical control means}
 - 61/16 . . Inhibiting {or initiating} shift during unfavourable conditions, {e.g. preventing forward reverse shift at high vehicle speed, preventing engine over speed ([unintentional control input F16H 61/18](#))}
 - 2061/161 . . {by checking feasibility of shifts, i.e. determine if requested shift can be successfully completed and post shift values are in an acceptable range}
 - 2061/163 . . {Holding the gear for delaying gear shifts under unfavorable conditions, e.g. during cornering}
 - 2061/165 . . {Preventing reverse gear shifts if vehicle speed is too high for safe shifting}
 - 2061/166 . . {Preventing or initiating shifts for preventing stall or overspeed of engine}
 - 2061/168 . . {Forced shifts into neutral for safety reasons, e.g. in case of transmission failure or emergency braking}
 - 61/18 . . Preventing unintentional or unsafe shift {, e.g. preventing manual shift from highest gear to reverse gear}
 - 2061/185 . . {Means, e.g. catches or interlocks, for preventing unintended shift into reverse gear}
 - 61/20 . . Preventing gear creeping {; Transmission control during standstill, e.g. hill hold control}
 - 2061/202 . . {Active creep control for slow driving, e.g. by controlling clutch slip}
 - 2061/205 . . {Hill hold control, e.g. with torque converter or a friction device slightly engaged to keep vehicle stationary}
 - 2061/207 . . {by neutral control}
 - 61/21 . . Providing engine brake control
 - 2061/213 . . {for emergency braking, e.g. for increasing brake power in emergency situations}
 - 2061/216 . . {by using exhaust brakes}
 - 61/22 . . Locking {of the control input devices} ([constructional features of locking or disabling mechanisms F16H 63/34](#))
 - 2061/223 . . {Electrical gear shift lock, e.g. locking of lever in park or neutral position by electric means if brake is not applied; Key interlock, i.e. locking the key if lever is not in park position}
 - 2061/226 . . {Manual distress release of the locking means for shift levers, e.g. to allow towing of vehicle in case of breakdown ([for parking locks F16H 63/3491](#))}
 - 61/24 . . Providing feel, e.g. to enable selection
 - 2061/241 . . {Actuators providing feel or simulating a shift gate, i.e. with active force generation for providing counter forces for feed back}
 - 2061/242 . . {Mechanical shift gates or similar guiding means during selection and shifting}
 - 2061/243 . . {Cams or detent arrays for guiding and providing feel}
 - 2061/245 . . {Ramp contours for generating force threshold, e.g. cams or pushers for generating additional resistance for a reverse path}
 - 2061/246 . . {Additional mass or weight on shift linkage for improving feel}
 - 2061/247 . . {Detents for range selectors}
 - 2061/248 . . {with audible signals for providing selection or shift feed back}
 - 61/26 . . Generation or transmission of movements for final actuating mechanisms
- NOTES**
1. The generation or transmission of movements comprising only the selector apparatus, is classified in group [F16H 59/00](#).
 2. The generation or transmission of movements, when part of the final output mechanisms, is classified in group [F16H 63/00](#).
- 61/28 . . with at least one movement of the final actuating mechanism being caused by a non-mechanical force, e.g. power-assisted

61/2807	. . .	{using electric control signals for shift actuators, e.g. electro-hydraulic control therefor (F16H 61/30 , F16H 61/32 take precedence; methods for generating shift signals F16H 61/0213)}	61/4052	by using a variable restriction, e.g. an orifice valve
61/2815	{with a control using only relays and switches}	61/4061	. . .	Control related to directional control valves, e.g. change-over valves, for crossing the feeding conduits
2061/2823	. . .	{Controlling actuator force way characteristic, i.e. controlling force or movement depending on the actuator position, e.g. for adapting force to synchronisation and engagement of gear clutch}	61/4069	. . .	Valves related to the control of neutral, e.g. shut off valves
2061/283	. . .	{Adjustment or calibration of actuator positions, e.g. neutral position}	61/4078	. . .	Fluid exchange between hydrostatic circuits and external sources or consumers
2061/2838	. . .	{Arrangements with single drive motor for selecting and shifting movements, i.e. one motor used for generating both movements}	61/4096	with pressure accumulators
2061/2846	. . .	{Arrangements of actuators for enabling jump shifting for skipping of gear ratios}	61/4104	Flushing, e.g. by using flushing valves or by connection to exhaust
2061/2853	. . .	{Electromagnetic solenoids}	61/4131	Fluid exchange by aspiration from reservoirs, e.g. sump
2061/2861	. . .	{Linear motors}	61/4139	Replenishing or scavenging pumps, e.g. auxiliary charge pumps
2061/2869	. . .	{Cam or crank gearing}	61/4148	. . .	Open loop circuits
2061/2876	. . .	{Racks}	61/4157	. . .	Control of braking, e.g. preventing pump over-speeding when motor acts as a pump
2061/2884	. . .	{Screw-nut devices}	61/4165	. . .	Control of cooling or lubricating
2061/2892	. . .	{other gears, e.g. worm gears, for transmitting rotary motion to the output mechanism}	61/4174	. . .	Control of venting, e.g. removing trapped air
61/30	. . .	Hydraulic {or pneumatic} motors {or related fluid control means} therefor	61/4183	. . .	Preventing or reducing vibrations or noise, e.g. avoiding cavitations
2061/301	{for power assistance, i.e. servos with follow up action}	61/4192	. . .	Detecting malfunction or potential malfunction, e.g. fail safe
2061/302	{with variable force amplification, e.g. force is depending on selected gear or on actuator force (non-linear amplification)}	61/42	. . .	involving adjustment of a pump or motor with adjustable output or capacity (F16H 61/46 takes precedence)}
2061/304	{using telemotors, i.e. systems with master cylinder and linked shift actuator without external pressure source}	61/421	Motor capacity control by electro-hydraulic control means, e.g. using solenoid valves
2061/305	{Accumulators for fluid supply to the servo motors, or control thereof}	61/423	Motor capacity control by fluid pressure control means
2061/307	{Actuators with three or more defined positions, e.g. three position servos}	61/425	Motor capacity control by electric actuators
2061/308	{Modular hydraulic shift units, i.e. preassembled actuator units for select and shift movements adapted for being mounted on transmission casing}	61/427	Motor capacity control by mechanical control means, e.g. by levers or pedals
61/32	. . .	Electric motors {actuators or related electrical control means} therefor	61/431	Pump capacity control by electro-hydraulic control means, e.g. using solenoid valves
2061/323	{for power assistance, i.e. servos with follow up action}	61/433	Pump capacity control by fluid pressure control means
2061/326	{Actuators for range selection, i.e. actuators for controlling the range selector or the manual range valve in the transmission}	61/435	Pump capacity control by electric actuators
61/34	. .	comprising two mechanisms, one for the preselection movement, and one for the shifting movement (F16H 61/36 takes precedence)	61/437	Pump capacity control by mechanical control means, e.g. by levers or pedals
61/36	. .	with at least one movement being transmitted by a cable	61/438	Control of forward-reverse switching, e.g. control of the swash plate causing discharge in two directions
61/38	. .	Control of exclusively fluid gearing	61/439	Control of the neutral position, e.g. by zero tilt rotation holding means
61/40	. .	hydrostatic	61/44	. . .	with more than one pump or motor in operation
61/4008	. . .	Control of circuit pressure	61/444	by changing the number of pump or motor units in operation
61/4017	Control of high pressure, e.g. avoiding excess pressure by a relief valve	61/448	Control circuits for tandem pumps or motors
61/4026	Control of low pressure	61/452	Selectively controlling multiple pumps or motors, e.g. switching between series or parallel
61/4035	. . .	Control of circuit flow	61/456	Control of the balance of torque or speed between pumps or motors
61/4043	. . .	Control of a bypass valve	61/46	. . .	Automatic regulation in accordance with output requirements
			61/461	{not involving a variation of the output capacity of the main pumps or motors}
			61/462	for achieving a target speed ratio
			61/465	for achieving a target input speed
			61/468	for achieving a target input torque
			61/47	for achieving a target output speed

61/472	for achieving a target output torque	2061/66209	{dependent on ambient conditions}
61/475	for achieving a target power, e.g. input power or output power	2061/66213	{dependent on driver's choice}
61/478	for preventing overload, e.g. high pressure limitation	2061/66218	{dependent on control input parameters other than ambient conditions or driver's choice}
61/48	. .	hydrodynamic	2061/66222	{the ratio is varied in order to reduce surface wear of belt or pulley}
61/50	. . .	controlled by changing the flow, force, or reaction of the liquid in the working circuit, while maintaining a completely filled working circuit	61/66227	. . .	{controlling shifting exclusively as a function of speed and torque}
61/52	by altering the position of blades	61/66231	. . .	{controlling shifting exclusively as a function of speed}
61/54	by means of axially-shiftable blade runners	61/66236	{using electrical or electronical sensing or control means}
61/56	to change the blade angle	61/6624	{using only hydraulic and mechanical sensing or control means}
61/58	by change of the mechanical connection of, or between, the runners	61/66245	{using purely mechanical sensing or control means}
61/60	exclusively by the use of freewheel clutches	61/6625	. . .	{controlling shifting exclusively as a function of torque}
61/62	involving use of a speed-changing gearing or of a clutch in the connection between runners (F16H 61/60 takes precedence; combinations of fluid gearings for conveying rotary motion with mechanical clutches for bridging a fluid gearing of the hydrokinetic type F16H 45/02)	61/66254	. . .	{controlling of shifting being influenced by a signal derived from the engine and the main coupling}
61/64	. . .	controlled by changing the amount of liquid in the working circuit	61/66259	{using electrical or electronical sensing or control means}
61/66	. .	specially adapted for continuously variable gearings (control of exclusively fluid gearing F16H 61/38)	61/66263	{using only hydraulic and mechanical sensing or control means}
2061/6601	. .	{with arrangements for dividing torque and shifting between different ranges}	61/66268	{using purely mechanical sensing or control means}
2061/6602	. .	{with at least two dynamo-electric machines for creating an electric power path inside the transmission device, e.g. using generator and motor for a variable power torque path}	61/66272	. . .	{characterised by means for controlling the torque transmitting capability of the gearing}
2061/6603	. . .	{characterised by changing ratio in the mechanical gearing}	2061/66277	{by optimising the clamping force exerted on the endless flexible member}
2061/6604	. .	{Special control features generally applicable to continuously variable gearings}	2061/66281	{by increasing the line pressure at the occurrence of input torque peak}
2061/6605	. . .	{Control for completing downshift at hard braking}	2061/66286	. . .	{Control for optimising pump efficiency}
2061/6607	. . .	{Controls concerning lubrication or cooling (lubrication features of friction gearings F16H 57/0487)}	2061/6629	. . .	{Detection of slip for determining level of wear}
2061/6608	. . .	{Control of clutches, or brakes for forward-reverse shift}	2061/66295	. . .	{characterised by means for controlling the geometrical interrelationship of pulleys and the endless flexible member, e.g. belt alignment or position of the resulting axial pulley force in the plane perpendicular to the pulley axis}
2061/6609	. . .	{Control of clutches or brakes in torque split transmissions}	61/664	. .	Friction gearings
2061/661	. . .	{Conjoint control of CVT and drive clutch}	2061/6641	. . .	{Control for modifying the ratio control characteristic}
2061/6611	. . .	{Control to achieve a particular driver perception, e.g. for generating a shift shock sensation}	2061/6642	{dependent on ambient conditions}
2061/6612	{for engine braking}	2061/6643	{dependent on driver's choice}
2061/6614	. . .	{Control of ratio during dual or multiple pass shifting for enlarged ration coverage}	2061/6644	{dependent on control input parameters other than ambient conditions or driver's choice}
2061/6615	. . .	{Imitating a stepped transmissions}	61/6645	. . .	{controlling shifting exclusively as a function of speed and torque}
2061/6616	{the shifting of the transmission being manually controlled}	61/6646	. . .	{controlling shifting exclusively as a function of speed}
2061/6617	. . .	{Manual control of CVTs while continuously varying the ratio}	61/6647	. . .	{controlling shifting exclusively as a function of torque}
2061/6618	. . .	{Protecting CVTs against overload by limiting clutch capacity, e.g. torque fuse}	61/6648	. . .	{controlling of shifting being influenced by a signal derived from the engine and the main coupling}
61/662	. .	with endless flexible members	61/6649	. . .	{characterised by the means for controlling the torque transmitting capability of the gearing}
2061/66204	. . .	{Control for modifying the ratio control characteristic}	61/68	. .	specially adapted for stepped gearings
			61/682	. .	with interruption of drive
			61/684	. .	without interruption of drive
			61/686	. . .	with orbital gears

- 61/688 . . . with two inputs, e.g. selection of one of two torque-flow paths by clutches
- 61/70 . . specially adapted for change-speed gearing in group arrangement, i.e. with separate change-speed gear trains arranged in series, e.g. range or overdrive-type gearing arrangements
- 61/702 . . {using electric or electrohydraulic control means}
- 61/705 . . {using hydraulic and mechanical control means}
- 61/707 . . {using only mechanical control means}
- 63/00 Control outputs {from the control unit} to change-speed- or reversing-gearings for conveying rotary motion {or to other devices than the final output mechanism}**
- 2063/005 . . {Preassembled gear shift units for mounting on gear case (for hydraulic shift units F16H 2061/308)}
- 63/02 . Final output mechanisms therefor; Actuating means for the final output mechanisms
- 2063/025 . . {Final output mechanisms for double clutch transmissions}
- 63/04 . . a single final output mechanism being moved by a single final actuating mechanism {(constructional features of the final output mechanisms F16H 63/30)}
- 63/06 . . . the final output mechanism having an indefinite number of positions
- 63/062 {electric or electro-mechanical actuating means}
- 63/065 {hydraulic actuating means}
- 63/067 {mechanical actuating means}
- 63/08 . . Multiple final output mechanisms being moved by a single common final actuating mechanism {(constructional features of the final output mechanisms F16H 63/30)}
- 63/10 . . . the final actuating mechanism having a series of independent ways of movement, each way of movement being associated with only one final output mechanism
- 63/12 two or more ways of movement occurring simultaneously
- 63/14 . . . the final output mechanisms being successively actuated by repeated movement of the final actuating mechanism
- 63/16 . . . the final output mechanisms being successively actuated by progressive movement of the final actuating mechanism
- 63/18 the final actuating mechanism comprising cams
- 63/20 . . . with preselection and subsequent movement of each final output mechanism by movement of the final actuating mechanism in two different ways, e.g. guided by a shift gate
- 2063/202 {using cam plates for selection or shifting, e.g. shift plates with recesses or grooves moved by a selector extension}
- 2063/204 {the gear shift lever being the immediate final actuating mechanism, e.g. the shift finger being a part of the gear shift lever}
- 63/206 {the final output mechanisms being mounted coaxially on a single shaft, e.g. mono rail shift mechanism}
- 2063/208 {using two or more selecting fingers}
- 63/22 the final output mechanisms being simultaneously moved by the final actuating mechanism
- 63/24 . . each of the final output mechanisms being moved by only one of the various final actuating mechanisms {(constructional features of the final output mechanisms F16H 63/30)}
- 63/26 . . . some of the movements of the final output mechanisms being caused by another final output mechanism
- 63/28 . . two or more final actuating mechanisms moving the same final output mechanism {(constructional features of the final output mechanisms F16H 63/30)}
- 63/285 . . . {with a first final actuating member applying a force to two or more final output members and a second final actuating member locking in position another final output member}
- 63/30 . . Constructional features of the final output mechanisms
- 63/3003 . . . {Band brake actuating mechanisms}
- 2063/3006 {moved by a non-mechanical force}
- 63/3009 . . . {the final output mechanisms having elements remote from the gearbox}
- 63/3013 . . . {the final output mechanism being characterised by linkages converting movement, e.g. into opposite direction by a pivoting lever linking two shift rods}
- 63/3016 . . . {Final output mechanisms varying the leverage or force ratio}
- 63/302 . . . {Final output mechanisms for reversing}
- 63/3023 . . . {the final output mechanisms comprising elements moved by fluid pressure (band brake actuating mechanisms F16H 63/3003)}
- 63/3026 {comprising friction clutches or brakes (band brake actuating mechanisms F16H 63/3003)}
- 2063/303 {the friction member is actuated and released by applying pressure to different fluid chambers}
- 2063/3033 {the brake is actuated by springs and released by a fluid pressure}
- 2063/3036 {the clutch is actuated by springs and released by a fluid pressure}
- 63/304 . . . {the final output mechanisms comprising elements moved by electrical or magnetic force (band brake actuating mechanisms F16H 63/3003)}
- 63/3043 {comprising friction clutches or brakes}
- 2063/3046 {using electromagnetic clutch for coupling gear wheel to shaft (friction clutches F16H 63/3043)}
- 2063/305 {using electromagnetic solenoids}
- 2063/3053 {using linear motors}
- 2063/3056 {using cam or crank gearing}
- 2063/3059 {using racks}
- 2063/3063 {using screw devices}
- 2063/3066 {using worm gears}
- 63/3069 . . . {Interrelationship between two or more final output mechanisms (interlocking devices F16H 63/36)}
- 2063/3073 {final output mechanisms mounted on a single shaft}
- 2063/3076 . . . {Selector shaft assembly, e.g. supporting, assembly or manufacturing of selector or shift shafts; Special details thereof}

2063/3079	. . .	{Shift rod assembly, e.g. supporting, assembly or manufacturing of shift rails or rods; Special details thereof}	63/48	. .	Signals to a parking brake {or parking lock; Control of parking locks or brakes being part of the transmission}
2063/3083	. . .	{Shift finger arrangements, e.g. shape or attachment of shift fingers}	63/483	. . .	{Circuits for controlling engagement of parking locks or brakes}
2063/3086	. . .	{Shift head arrangements, e.g. forms or arrangements of shift heads for preselection or shifting}	63/486	. . .	{Common control of parking locks or brakes in the transmission and other parking brakes, e.g. wheel brakes}
2063/3089	. . .	{Spring assisted shift, e.g. springs for accumulating energy of shift movement and release it when clutch teeth are aligned}	63/50	. .	Signals to an engine or motor
2063/3093	. . .	{Final output elements, i.e. the final elements to establish gear ratio, e.g. dog clutches or other means establishing coupling to shaft (fluid actuated clutches F16H 63/3026; electromagnetic clutches F16H 2063/3046)}	63/502	. . .	{for smoothing gear shifts}
2063/3096	{Sliding keys as final output elements; Details thereof}	2063/504	. . .	{for bringing engine into special condition by transmission control, e.g. by changing torque converter characteristic to modify engine set point to higher engine speed for better acceleration performance}
63/32	. . .	Gear shift yokes, {e.g. shift forks}	2063/506	. . .	{for engine torque resume after shift transition, e.g. a resume adapted to the driving style}
2063/321	{characterised by the interface between fork body and shift rod, e.g. fixing means, bushes, cams or pins}	2063/508	. . .	{for limiting transmission input torque, e.g. to prevent damage of transmission parts}
2063/322	{characterised by catches or notches for moving the fork}	<hr/>		
2063/324	{characterised by slide shoes, or similar means to transfer shift force to sleeve}	2200/00	Transmissions for multiple ratios	
2063/325	{Rocker or swiveling forks, i.e. the forks are pivoted in the gear case when moving the sleeve}	2200/0004	. .	comprising a power take off shaft
2063/327	{essentially made of sheet metal}	2200/0008	. .	specially adapted for front-wheel-driven vehicles
2063/328	{essentially made of plastics, e.g. injection molded}	2200/0013	. .	specially adapted for rear-wheel-driven vehicles
63/34	. . .	Locking or disabling mechanisms	2200/0017	. .	specially adapted for four-wheel-driven vehicles
63/3408	{the locking mechanism being moved by the final actuating mechanism}	2200/0021	. .	specially adapted for electric vehicles
63/3416	{Parking lock mechanisms or brakes in the transmission}	2200/0026	. .	comprising at least one creep low gear, e.g. additional gear for extra low speed or creeping
63/3425	{characterised by pawls or wheels}	2200/003	. .	characterised by the number of forward speeds
63/3433	{Details of latch mechanisms, e.g. for keeping pawls out of engagement}	2200/0034	. .	the gear ratios comprising two forward speeds
63/3441	{Parking locks engaging axially}	2200/0039	. .	the gear ratios comprising three forward speeds
63/345	{using friction brakes, e.g. a band brakes}	2200/0043	. .	the gear ratios comprising four forward speeds
63/3458	{with electric actuating means, e.g. shift by wire}	2200/0047	. .	the gear ratios comprising five forward speeds
63/3466	{using electric motors}	2200/0052	. .	the gear ratios comprising six forward speeds
63/3475	{using solenoids}	2200/0056	. .	the gear ratios comprising seven forward speeds
63/3483	{with hydraulic actuating means}	2200/006	. .	the gear ratios comprising eight forward speeds
63/3491	{Emergency release or engagement of parking locks or brakes}	2200/0065	. .	the gear ratios comprising nine forward speeds
63/36	Interlocking devices	2200/0069	. .	the gear ratios comprising ten forward speeds
63/38	. . .	Detents {(spring-loaded ball units for holding levers in a limited number of positions G05G 5/065)}	2200/0073	. .	the gear ratios comprising eleven forward speeds
63/40	. .	comprising signals other than signals for actuating the final output mechanisms	2200/0078	. .	the gear ratio comprising twelve or more forward speeds
63/42	. .	Ratio indicator devices	2200/0082	. .	characterised by the number of reverse speeds
2063/423	. . .	{Range indicators for automatic transmissions, e.g. showing selected range or mode}	2200/0086	. .	the gear ratios comprising two reverse speeds
2063/426	. . .	{with means for advising the driver for proper shift action, e.g. prompting the driver with allowable selection range of ratios}	2200/0091	. .	the gear ratios comprising three reverse speeds
63/44	. .	Signals to the control unit of auxiliary gearing	2200/0095	. .	the gear ratios comprising four reverse speeds
63/46	. .	Signals to a clutch outside the gearbox	2200/20	. .	Transmissions using gears with orbital motion
			2200/2002	. .	characterised by the number of sets of orbital gears
			2200/2005	. . .	with one sets of orbital gears
			2200/2007	. . .	with two sets of orbital gears
			2200/201	. . .	with three sets of orbital gears
			2200/2012	. . .	with four sets of orbital gears
			2200/2015	. . .	with five sets of orbital gears
			2200/2017	. . .	with six sets of orbital gears
			2200/202	. .	characterised by the type of Ravigneaux set
			2200/2023	. . .	using a Ravigneaux set with 4 connections
			2200/2025	. . .	using a Ravigneaux set with 5 connections
			2200/2028	. . .	using a Ravigneaux set with 6 connections
			2200/203	. .	characterised by the engaging friction means not of the freewheel type, e.g. friction clutches or brakes

- 2200/2033 . . . with one engaging means
- 2200/2035 . . . with two engaging means
- 2200/2038 . . . with three engaging means
- 2200/2041 . . . with four engaging means
- 2200/2043 . . . with five engaging means
- 2200/2046 . . . with six engaging means
- 2200/2048 . . . with seven engaging means
- 2200/2051 . . . with eight engaging means
- 2200/2053 . . . with nine engaging means
- 2200/2056 . . . with ten engaging means
- 2200/2058 . . . with eleven engaging means
- 2200/2061 . . . with twelve engaging means
- 2200/2064 . . . using at least one positive clutch, e.g. dog clutch
- 2200/2066 . . . using one freewheel mechanism
- 2200/2069 . . . using two freewheel mechanism
- 2200/2071 . . . using three freewheel mechanism
- 2200/2074 . . . using four freewheel mechanism
- 2200/2076 . . . using at least five freewheel mechanism
- 2200/2079 . . . using freewheel type mechanisms, e.g. freewheel clutches
- 2200/2082 . . . one freewheel mechanisms
- 2200/2084 . . . two freewheel mechanisms
- 2200/2087 . . . three freewheel mechanisms
- 2200/2089 . . . four freewheel mechanisms
- 2200/2092 . . . at least five freewheel mechanisms
- 2200/2094 . . . using positive clutches, e.g. dog clutches
- 2200/2097 . . . comprising an orbital gear set member permanently connected to the housing, e.g. a sun wheel permanently connected to the housing
- 2300/00 Determining of new ratio**
- 2300/02 . Computing a new ratio
- 2300/14 . Selecting a state of operation, e.g. depending on two wheel or four wheel drive mode
- 2300/18 . Determining the range
- 2302/00 Determining the way or trajectory to new ratio, e.g. by determining speed, torque or time parameters for shift transition**
- 2302/02 . Optimizing the way to the new ratio
- 2302/04 . Determining a modus for shifting ([selection of shift speed modus F16H 2059/0226](#))
- 2302/06 . Determining timing parameters of shifting, e.g. start of shifting ([for smoothing gear shift F16H 61/08](#))
- 2306/00 Shifting**
- 2306/14 . Skipping gear shift ([for smoothing gear shift F16H 2061/0444](#))
- 2306/18 . Preparing coupling or engaging of future gear
- 2306/20 . Timing of gear shifts ([for smoothing gear shift F16H 61/08](#))
- 2306/21 . . for auxiliary gear shifts ([for smoothing auxiliary gear shifts F16H 2061/085](#))
- 2306/22 . Swap shifting ([for smoothing gear shift F16H 2061/0451](#))
- 2306/24 . Interruption of shift, e.g. if new shift is initiated during ongoing previous shift
- 2306/30 . characterised by the way or trajectory to a new ratio, e.g. by performing shift according to a particular algorithm or function ([determining the way or trajectory to a new ratio F16H 2302/00](#))
- 2306/32 . Preparing the opening or release of the torque transmitting element
- 2306/36 . Filling the dead volume of actuators ([controlling filling of clutches or brake servos F16H 61/62](#))
- 2306/40 . Shifting activities
- 2306/42 . . Changing the input torque to the transmission
- 2306/44 . . Removing torque from current gears
- 2306/46 . . Uncoupling of current gear
- 2306/48 . . Synchronising of new gear
- 2306/50 . . Coupling of new gear
- 2306/52 . . Applying torque to new gears
- 2306/54 . . Synchronizing engine speed to transmission input speed
- 2312/00 Driving activities**
- 2312/02 . Driving off
- 2312/022 . . Preparing to drive off
- 2312/04 . Holding or hillholding
- 2312/06 . Creeping
- 2312/08 . Rocking
- 2312/09 . Switching between forward and reverse ([rocking F16H 2312/08](#))
- 2312/10 . Inching
- 2312/12 . Parking
- 2312/14 . Going to, or coming from standby operation, e.g. for engine start-stop operation at traffic lights
- 2312/16 . Coming to a halt
- 2312/18 . Strong or emergency braking
- 2312/20 . Start-up or shut-down
- 2342/00 Calibrating**
- 2342/02 . Calibrating shift or range movements
- 2342/04 . Calibrating engagement of friction elements
- 2342/042 . . Point of engagement
- 2342/044 . . Torque transmitting capability
- 2342/06 . Determining which part to calibrate or timing of calibrations
- 2342/10 . Calibrating valves
- 2700/00 Transmission housings and mounting of transmission components therein; Cooling; Lubrication; Flexible suspensions, e.g. floating frames**
- 2700/02 . Transmissions, specially for working vehicles
- 2700/04 . . Starting devices or devices to start turning of shafts
- 2700/06 . Protections for shifting mechanical transmissions
- 2702/00 Combinations of two or more transmissions**
- 2702/02 . Mechanical transmissions with planetary gearing combined with one or more other mechanical transmissions
- 2702/04 . . Combinations of a speed-change mechanism without planetary gearing with a differential for driving a vehicle drive axle
- 2702/06 . Combinations of transmissions with parallel force splitting paths having same output
- 2704/00 Control mechanisms and elements applying a mechanical movement**
- 2704/02 . Speed-change devices wherein the control lever actuates directly sliding gears pivoting around two non-parallel axis
- 2704/04 . Speed-change devices with an intermediary mechanism placed between control member and actuator

2706/00	Rotary transmissions with mechanical energy accumulation and recovery without means for automatic selfregulation essentially based on spring action or inertia	2716/00	Control devices for speed-change mechanisms of planetary gearings, with toothed wheels remaining engaged, e.g. also for devices to simplify the control or for synchronising devices combined with control devices
2708/00	Control devices for speed-changing geared mechanisms, e.g. specially adapted couplings for synchronising devices, devices to simplify control, control of auxiliary gearboxes	2716/02	. the control being mechanical
2708/02	. only the toothed wheels remain engaged	2716/04	. the control being hydraulic or pneumatic
2708/04	. . the control being mechanical	2716/06	. . Circuits thereof
2708/06	. . the control being hydraulic or pneumatic	2716/08	. the control being electric
2708/08	. . the control being electric	2716/10	. only the toothed wheels may be disengaged, the control being mechanical
2708/10	. only the toothed wheels may be disengaged	2716/12	. with preselection system, mainly semi-automatic, e.g. with automatic preselection, but controlled at the intended moment, with force amplification
2708/12	. . the control being mechanical	2716/14	. . only with toothed wheels remaining engaged
2708/14	. . the control being hydraulic or pneumatic	2718/00	Mechanisms for speed-change of planetary gearing, the speed change control being dependent on function parameters of the gearing
2708/16	. wherein the gearing is not described or not essential	2718/02	. Control dependent on speed and torque, wherein only the toothed wheels remain engaged
2708/18	. . the control being mechanical	2718/04	. . the control being mechanical
2708/20	. . the control being hydraulic or pneumatic	2718/06	. . the control being hydraulic or pneumatic
2708/22	. . the control being electric	2718/08	. Control dependent on speed
2708/24	. with a preselection system, mainly semi-automatic, e.g. with automatic preselection, but controlled at the intended moment, with force amplification	2718/10	. . only the toothed wheels remain engaged
2708/26	. . only the toothed wheels remain engaged	2718/12	. . . the control being mechanical
2708/28	. . only the toothed wheels may be disengaged	2718/14	. . . the control being hydraulic or pneumatic
2710/00	Control devices for speed-change mechanisms, the speed change control is dependent on function parameters of the gearing	2718/16	. . . the control being electric
2710/02	. Control dependent on speed and torque, wherein only the toothed wheels remain engaged, control being mechanical	2718/18	. Control dependent on torque
2710/04	. Control dependent on speed	2718/20	. . only the toothed wheels remain engaged
2710/06	. . only the toothed wheels remain engaged	2718/22	. . . the control being mechanical
2710/08	. . . the control being mechanical	2718/24	. . . the control being hydraulic or pneumatic
2710/10	. . . the control being hydraulic or pneumatic	2718/26	. . . the control being electric
2710/12	. . . the control being electric	2720/00	Different types of speed-change gear mechanisms
2710/14	. Control dependent on speed, wherein only the toothed wheels may be disengaged, control being mechanical	2720/02	. Gears with a non-circular rolling curve or gears with special teeth
2710/16	. the gearing is not described or not essential	2720/04	. Combining a planetary speed-change gearing with a motor vehicle drive axle differential
2710/18	. . the control being mechanical		
2710/20	. . the control being hydraulic or pneumatic		
2710/22	. . the control being electric		
2710/24	. Control dependent on torque		
2710/26	. . wherein only the toothed wheels remain engaged, the control being mechanical		
2712/00	Mechanisms for changing direction		
2712/02	. Automatic control, e.g. for an alternating movement		
2712/04	. the control being hydraulic or pneumatic		
2712/06	. only with toothed wheels or friction wheels		
2712/08	. . only the toothed wheels may be disengaged		
2712/10	. . with a combination of engaged and disengageable toothed wheels		
2714/00	Different types speed-changing mechanisms for toothed gearing		
2714/02	. only with toothed wheels remaining engaged		
2714/04	. with specially adapted devices		