#### **B60G**

# VEHICLE SUSPENSION ARRANGEMENTS (air-cushion vehicles <u>B60V</u>; {cycle suspensions <u>B62K 25/00</u>})

#### **Definition statement**

This place covers:

Suspension for vehicle with a limitation to the type of vehicle:

Car, truck, agricultural vehicle and their trailers.

#### References

#### Limiting references

This place does not cover:

Rail vehicle suspensions	<u>B61F</u>
Cycle suspensions	B62K 25/00

#### Informative references

Attention is drawn to the following places, which may be of interest for search:

Vehicle wheels; castors; axles; increasing wheel adhession	B60B 1/00 - B60B 39/12
Vehicles adapted for load transportation	B60P 1/00
Conjoint control of vehicle sub-units	<u>B60W</u>
Steering	B62D 1/00 - B62D 7/00
Chassis understructures	<u>B62D 21/00</u> - <u>B62D 67/00</u>
Cycles	<u>B62K</u>
Bearings	<u>F16C</u>
Springs; Shock-absorbers; Means for damping vibration	<u>F16F</u>

#### Special rules of classification

For the whole <u>B60G</u> range, consider the indexing range <u>B60G 1/00</u> - <u>B60G 99/008</u>

#### **B60G 9/00**

Resilient suspensions of a rigid axle or axle housing for two or more wheels {(the axle being a part of a set of tandem axles <u>B60G 5/00-B60G 5/065</u>; with leaf springs <u>B60G 11/02-B60G 11/08</u>)}

#### **Definition statement**

This place covers:

Resilient suspensions of a rigid axle or axle housing for two or more wheels

### References

## Limiting references

This place does not cover:

Twist beam axles or semi-rigid axles	B60G 21/051
--------------------------------------	-------------