

CPC**COOPERATIVE PATENT CLASSIFICATION****F01N**

GAS-FLOW SILENCERS OR EXHAUST APPARATUS FOR MACHINES OR ENGINES IN GENERAL; GAS-FLOW SILENCERS OR EXHAUST APPARATUS FOR INTERNAL COMBUSTION ENGINES ({ evacuation of fumes from the area where they are produced [B08B 15/00](#); arrangement of exhaust or silencing apparatus on percussive tools [B25D 17/12](#)}; arrangements in connection with gas exhaust of propulsion units in vehicles [B60K 13/00](#), { on ships or other waterborne vessels [B63H 21/32](#), on aircraft [B64D 33/04](#); arrangement of exhaust or silencing apparatus on firearms [F41A 21/30](#); ground installations for reducing aircraft engine or jet noise [B64F 1/26](#); silencers specially adapted for steam engines [F01B 31/16](#); air-intake silencers for gas turbine or jet propulsion plants [F02C 7/045](#); jet pipe or nozzles for jet propulsion plants [F02K](#)}; combustion-air intake silencers specially adapted for, or arranged on, internal-combustion engines [F02M 35/00](#); { combating noise or silencing in positive displacement machines or pumps [F04B 39/0027](#), in rotary-piston machines or pumps [F04C 29/06](#), in non-positive displacement pumps [F04D 29/66](#); means in valves for absorbing noise [F16K 47/02](#); noise absorbers in pipe system [F16L 55/02](#); conducting smoke or fumes from various locations to the outside [F23J 11/00](#); means for preventing or suppressing noise in air-conditioning or ventilation systems [F24F 13/24](#)}; protecting against, or damping, noise in general [G10K 11/16](#))

NOTE

Attention is drawn to the notes preceding Class F01, especially as regards Note 2(b).

F01N 1/00

Silencing apparatus characterised by method of silencing {by cooling [F01N 3/02](#); using liquids [F01N 3/04](#)}

F01N 1/003

. {by using dead chambers communicating with gas flow passages (**resonance chambers** [F01N 1/02](#); **chambers containing sound-absorbing materials** [F01N 1/24](#))}

F01N 1/006

.. { comprising at least one perforated tube extending from inlet to outlet of the silencer}

F01N 1/02

. by using resonance

F01N 1/023

.. { Helmholtz resonators}

F01N 1/026

.. { Annular resonance chambers arranged concentrically to an exhaust passage and communicating with it, e.g. via at least one opening in the exhaust passage}

F01N 1/04

.. having sound-absorbing materials in resonance chambers

F01N 1/06

. by using interference effect

F01N 1/065

.. {by using an active noise source, e.g. speakers}

F01N 1/08

. by reducing exhaust energy by throttling or whirling

F01N 1/081

.. {by passing the gases through a mass of particles}

- F01N 1/082 . . {the gases passing through porous members ([F01N 1/081](#) takes precedence)}
- F01N 1/083 . . {using transversal baffles defining a tortuous path for the gases or successively throttling gas flow}
- F01N 1/084 . . {the gases flowing through the silencer two or more times longitudinally in opposite directions, e.g. using parallel or concentric tubes}
- F01N 1/085 . . {using a central core throttling gas passage}
- F01N 1/086 . . {having means to impart whirling motion to the gases (with helically or spirally shaped channels [F01N 1/12](#))}
- F01N 1/087 . . . {using tangential inlets into a circular chamber}
- F01N 1/088 . . . {using vanes arranged on gas flow path or gas flow tubes with tangentially directed apertures}
- F01N 1/089 . . {using two or more expansion chambers in series ([F01N 1/083](#), [F01N 1/084](#), [F01N 1/086](#) take precedence)}
- F01N 1/10 . . in combination with sound-absorbing materials ([F01N 1/125](#) takes precedence)
- F01N 1/12 . . using spirally or helically shaped channels (cyclones [B04C](#))
- F01N 1/125 . . . {in combination with sound-absorbing materials}
- F01N 1/14 . by adding air to exhaust gases {(in tailpipes **F01N 7/08B**, **F01N 7/20**)}
- F01N 1/16 . by using movable parts
- F01N 1/161 . . { for adjusting resonance or dead chambers or passages to resonance or dead chambers}
- F01N 1/163 . . . { by means of valves}
- F01N 1/165 . . {for adjusting flow area}
- F01N 1/166 . . {for changing gas flow path through the silencer or for adjusting the dimensions of a chamber or a pipe ([F01N 1/165](#) takes precedence)}
- F01N 1/168 . . { for controlling or modifying silencing characteristics only}
- F01N 1/18 . . having rotary movement
- F01N 1/20 . . having oscillating or vibrating movement {the parts being resilient walls [F01N 1/22](#)}
- F01N 1/22 . . the parts being resilient walls
- F01N 1/24 . by using sound-absorbing materials ([F01N 1/04](#), [F01N 1/06](#), [F01N 1/10](#), [F01N 1/14](#), [F01N 1/16](#) take precedence)
- F01N 3/00** **Exhaust or silencing apparatus having means for purifying, rendering innocuous, or otherwise treating exhaust** (electric control [F01N 9/00](#); monitoring or diagnostic devices for exhaust-gas treatment apparatus [F01N 11/00](#); {collecting or removing exhaust gases of vehicle engines in workshops [B08B 15/00](#), on highways [E01C 1/005](#)})
- F01N 3/005 . { for draining or otherwise eliminating condensates or moisture accumulating in the apparatus ([F01N 3/02](#) takes precedence)} [c0809]
- F01N 3/01 . by means of electric or electrostatic separators
- F01N 3/02 . for cooling, or for removing solid constituents of, exhaust (by means of electric or electrostatic separators [F01N 3/01](#); {mixing air with exhaust in tailpipes **F01N 7/08B**, **F01N 7/20**})
- F01N 3/0205 . . { using heat exchangers}

F01N 3/021	..	by means of filters
F01N 3/0211	...	{Arrangements for mounting filtering elements in housing, e.g. with means for compensating thermal expansion or vibration}
F01N 3/0212	...	{with one or more perforated tubes surrounded by filtering material, e.g. filter candles}
F01N 3/0214	...	{with filters comprising movable parts, e.g. rotating filters}
F01N 3/0215	...	{ the filtering elements having the form of disks or plates}
F01N 3/0217	...	{ the filtering elements having the form of hollow cylindrical bodies}
F01N 3/0218	...	{ the filtering elements being made from spirally-wound filtering material}
F01N 3/022	...	characterised by specially adapted filtering structure, e.g. honeycomb, mesh or fibrous
F01N 3/0222	{the structure being monolithic, e.g. honeycombs}
F01N 3/0224	{the structure being granular}
F01N 3/0226	{the structure being fibrous}
F01N 3/0228	{the structure being made of foamed rubber or plastics}
F01N 3/023	...	using means for regenerating the filters, e.g. by burning trapped particles (by electrically controlling the supply of combustible mixture or its constituents only F02D 41/0235)
F01N 3/0231	{using special exhaust apparatus upstream of the filter for producing nitrogen dioxide, e.g. for continuous filter regeneration systems (CRT)}
F01N 3/0232	{ removing incombustible material from a particle filter, e.g. ash}
F01N 3/0233	{ periodically cleaning filter by blowing a gas through the filter in a direction opposite to exhaust flow, e.g. exposing filter to engine air intake}
F01N 3/0234	{ using heat exchange means in the exhaust line}
F01N 3/0235	{ using exhaust gas throttling means}
F01N 3/0236	{ using turbine waste gate valve}
F01N 3/0237	{ for regenerating ex situ}
F01N 3/0238	{ for regenerating during engine standstill}
F01N 3/025	using fuel burner or by adding fuel to exhaust
F01N 3/0253	{adding fuel to exhaust gases}
F01N 3/0256	{the fuel being ignited by electrical means}
F01N 3/027	using electric or magnetic heating means
F01N 3/0275	{using electric discharge means}
F01N 3/028	using microwaves
F01N 3/029	by adding non-fuel substances to exhaust
F01N 3/0293	{ injecting substances in exhaust stream}
F01N 3/0296	{ having means for preheating additional substances}
F01N 3/031	...	having means for by-passing filters, e.g. when clogged or during cold engine start
F01N 3/032	during filter regeneration only
F01N 3/033	...	in combination with other devices {with adsorbents or absorbents F01N 3/0821 }
F01N 3/0335	{with exhaust silencers in a single housing}
F01N 3/035	with catalytic reactors, { e.g. catalysed diesel particulate filters }
F01N 3/037	..	by means of inertial or centrifugal separators, e.g. of cyclone type, optionally

- combined or associated with agglomerators
- F01N 3/038 . . by means of perforated plates defining expansion chambers associated with condensation and collection chambers, e.g. for adiabatic expansion of gases and subsequent collection of condensed liquids
- F01N 3/04 . . using liquids
- F01N 3/043 . . . {without contact between liquid and exhaust gases}
- F01N 3/046 {Exhaust manifolds with cooling jacket}
- F01N 3/05 . . by means of air, e.g. by mixing exhaust with air (silencers working by addition of air to exhaust [F01N 1/14](#); arrangements for the supply of additional air for the thermal or catalytic conversion of noxious components of exhaust [F01N 3/30](#); {in tailpipes **F01N 7/08B**})
- F01N 3/055 . . . { without contact between air and exhaust gases}
- F01N 3/06 . for extinguishing sparks
- F01N 3/08 . for rendering innocuous (using electric or electrostatic separators [F01N 3/01](#); chemical aspects [B01D 53/92](#))
- F01N 3/0807 . . {by using absorbents or adsorbents}
- F01N 3/0814 . . . { combined with catalytic converters, e.g. NOx absorption/storage reduction catalysts}
- F01N 3/0821 . . . { combined with particulate filters (catalysed diesel particulate filters [F01N 3/035](#))}
- F01N 3/0828 . . . { characterised by the absorbed or adsorbed substances}
- F01N 3/0835 { Hydrocarbons}
- F01N 3/0842 { Nitrogen oxides}
- F01N 3/085 { Sulfur or sulfur oxides}
- F01N 3/0857 { Carbon oxides}
- F01N 3/0864 { Oxygen}
- F01N 3/0871 . . . {Regulation of absorbents or adsorbents, e.g. purging (by electrically controlling the supply of combustible mixture or its constituents only [F02D 41/0235](#))}
- F01N 3/0878 {Bypassing absorbents or adsorbents}
- F01N 3/0885 {Regeneration of deteriorated absorbents or adsorbents, e.g. desulfurization of NOx traps}
- F01N 3/0892 . . {Electric or magnetic treatment, e.g. dissociation of noxious components (electric filters [F01N 3/01](#); regeneration of exhaust filters [F01N 3/023](#); heating catalytic converters [F01N 3/2006](#))}
- F01N 3/10 . . by thermal or catalytic conversion of noxious components of exhaust (by using other chemical processes, chemical aspects of catalytic conversion, e.g. using specified catalysts, [B01D 53/34](#))

WARNING

[F01N 3/10](#) are not complete pending a reorganisation

- F01N 3/101 . . . { Three-way catalysts}
- F01N 3/103 . . . { Oxidation catalysts for HC and CO only}
- F01N 3/105 . . . { General auxiliary catalysts, e.g. upstream or downstream of the main catalyst}
- F01N 3/106 { Auxiliary oxidation catalysts}

F01N 3/108	{ Auxiliary reduction catalysts}
F01N 3/18	...	characterised by methods of operation; Regulation
F01N 3/20	specialy adapted for catalytic conversion; {Methods of operation or regulation of catalytic converters}(F01N 3/22 takes precedence)
F01N 3/2006	{Periodically heating or cooling catalytic reactors, e.g. at cold starting or overheating (by electrically controlling the supply of combustible mixture or its constituents only F02D 41/0235)}
F01N 3/2013	{using electric or magnetic heating means}
F01N 3/202	{using microwaves}
F01N 3/2026	{directly electrifying the catalyst substrate, i.e. heating the electrically conductive catalyst substrate by joule effect}
F01N 3/2033	{using a fuel burner or introducing fuel into exhaust duct}
F01N 3/204	{using an exhaust gas igniter, e.g. a spark or glow plug, without introducing fuel into exhaust duct}
F01N 3/2046	{ Periodically cooling catalytic reactors}
F01N 3/2053	{By-passing catalytic reactors, e.g. to prevent overheating}
F01N 3/206	{ Adding periodically or continuously substances to exhaust gases for promoting purification, e.g. catalytic material in liquid form, NOx reducing agents (F01N 3/2066 takes precedence)}
F01N 3/2066	{ Selective catalytic reduction (SCR)}

WARNING

[F01N 3/206](#) for documents published before March 2004.

F01N 3/2073	{ with means for generating a reducing substance from the exhaust gases}
F01N 3/208	{ Control of selective catalytic reduction (SCR), e.g. dosing of reducing agent}
F01N 3/2086	{Activating the catalyst by light, photo-catalysts}
F01N 3/2093	{ Periodically blowing a gas through the converter, e.g. in a direction opposite to exhaust gas flow or by reversing exhaust gas flow direction}
F01N 3/22	Regulation of additional air supply only, e.g. using by-passes or variable air pump drives
F01N 3/222	[N: using electric valves only
F01N 3/225	{ Electric control of additional air supply}
F01N 3/227	{ using pneumatically operated valves, e.g. membrane valves}
F01N 3/24	...	characterised by constructional aspects of converting apparatus (filtering in combination with catalytic reactors F01N 3/035)
F01N 3/26	Construction of thermal reactors
F01N 3/28	Construction of catalytic reactors
F01N 3/2803	{characterised by structure, by material or by manufacturing of catalyst support}
F01N 3/2807	{Metal other than sintered metal (F01N 3/2832 and F01N 3/2835 take precedence)}
F01N 3/281	{Metallic honeycomb monoliths made of stacked or rolled sheets, foils or plates}
F01N 3/2814	{all sheets, plates or foils being corrugated}

F01N 3/2817	{only with non-corrugated sheets, plates or foils}
F01N 3/2821	{the support being provided with means to enhance the mixing process inside the converter, e.g. sheets, plates or foils with protrusions or projections to create turbulence}
F01N 3/2825	{Ceramics (F01N 3/2832 , F01N 3/2835 take precedence)}
F01N 3/2828	{Ceramic multi-channel monoliths, e.g. honeycombs}
F01N 3/2832	{granular, e.g. pellets}
F01N 3/2835	{fibrous}
F01N 3/2839	{Arrangements for mounting catalyst support in housing, e.g. with means for compensating thermal expansion or vibration}
F01N 3/2842	{ specially adapted for monolithic supports, e.g. of honeycomb type (F01N 3/2853 to F01N 3/2871 take precedence)}
F01N 3/2846	{specially adapted for granular supports, e.g. pellets}
F01N 3/285	{specially adapted for fibrous supports, e.g. held in place by screens}
F01N 3/2853	{ using mats or gaskets between catalyst body or housing}
F01N 3/2857	{ the mats or gaskets being at least partially made of intumescent material, e.g. unexpanded vermiculite}
F01N 3/286	{ the mats or gaskets having corrugations or cavities}

WARNING[F01N 3/2853](#) and [F01N 3/2857](#)

F01N 3/2864	{ the mats or gaskets comprising two or more insulation layers}
F01N 3/2867	{ the mats or gaskets being placed at the front or end face of catalyst body}

WARNING[F01N 3/2853](#) and [F01N 3/2857](#)

F01N 3/2871	{ the mats or gaskets having an additional, e.g. non-insulating or non-cushioning layer, a metal foil or an adhesive layer}
-------------	-------	---

WARNING[F01N 3/2853](#) and [F01N 3/2857](#)

F01N 3/2875	{ by using elastic means, e.g. spring leaves, for retaining catalyst body in the housing (F01N 3/2853 to F01N 3/2871 take precedence)}
F01N 3/2878	{ by using non-elastic means for retaining catalyst body in the housing, e.g. a metal chamfer, or by corrugation or deformation of the metal housing}
F01N 3/2882	{Catalytic reactors combined or associated with other devices, e.g. exhaust silencers or other exhaust purification devices (combined with absorbents or adsorbents only F01N 3/0814 ; combined with particulate filters F01N 3/035)}
F01N 3/2885	{with exhaust silencers in a single housing}
F01N 3/2889	{with heat exchangers in a single housing}
F01N 3/2892	{Exhaust flow directors or the like, e.g. upstream of catalytic device}

F01N 3/2896	{ Liquid catalyst carrier}
F01N 3/30	Arrangements for supply of additional air (regulation, e.g. using air by-passes or variable air pump drives F01N 3/22)
F01N 3/303	{ Filtering additional air}
F01N 3/306	{ Preheating additional air}
F01N 3/32	using air pump (using jet air pumps F01N 3/34 ; pumps in general F04)
F01N 3/323	{ Electrically driven air pumps}
F01N 3/326	{ Engine-driven air pumps}
F01N 3/34	using air conduits or jet air pumps, e.g. near the engine exhaust port
F01N 3/36	Arrangements for supply of additional fuel
F01N 3/38	Arrangements for igniting

F01N 5/00 Exhaust or silencing apparatus combined or associated with devices profiting by exhaust energy (predominant aspects of such devices, see the relevant classes for the devices; using kinetic or wave energy of exhaust gases in exhaust systems for charging [F02B](#))

NOTE

- in this group the following indexing code is used: [F02M 2700/31](#)

F01N 5/02	.	the devices using heat
F01N 5/025	..	{ the device being thermoelectric generators}

WARNING

[F01N 5/02](#)

F01N 5/04	.	the devices using kinetic energy
-----------	---	----------------------------------

F01N 9/00 Electrical control of exhaust gas treating apparatus (monitoring or diagnostic devices for exhaust-gas treatment apparatus [F01N 11/00](#); {electrical control of supply of combustible mixture or its constituents in relation with the state of the exhaust gas treating apparatus [F02D 41/0235](#)}; controlling combustion engines conjoint electrical control of two or more combustion engine functions [F02D 43/00](#))

F01N 9/002	.	{of filter regeneration, e.g. detection of clogging}
F01N 9/005	.	{ using models instead of sensors to determine operating characteristics of exhaust systems, e.g. calculating catalyst temperature instead of measuring it directly}
F01N 9/007	.	{ Storing data relevant to operation of exhaust systems for later retrieval and analysis, e.g. to research exhaust system malfunctions}

F01N 11/00 Monitoring or diagnostic devices for exhaust-gas treatment apparatus, {e.g. for catalytic activity (safety, indicating or supervising devices for internal combustion engines [F02B 77/08](#); testing of machines [G01M 13/00](#))}

- F01N 11/002 . {the diagnostic devices measuring or estimating temperature or pressure in, or downstream of the exhaust apparatus}
- F01N 11/005 . . {the temperature or pressure being estimated, e.g. by means of a theoretical model}
- F01N 11/007 . {the diagnostic devices measuring oxygen or air concentration downstream of the exhaust apparatus}

- F01N 13/00 Exhaust or silencing apparatus characterised by constructional features; { Exhaust or silencing apparatus, or parts thereof, having pertinent characteristics not provided for in, or of interest apart from, groups [F01N 1/00](#) to [F01N 5/00](#), [F01N 9/00](#), [F01N 11/00](#)}**
- F01N 13/001 . { Gas flow channels or gas chambers being at least partly formed in the structural parts of the engine or machine (using structural parts of the vehicle [B60K 13/06](#))}
- F01N 13/002 . { Apparatus adapted for particular uses, e.g. for portable devices driven by machines or engines}
- F01N 13/004 . { specially adapted for marine propulsion, i.e. for receiving simultaneously engine exhaust gases and engine cooling water (for submerged exhausting [F01N 13/12](#); treating exhaust by using liquids [F01N 3/04](#))}
- F01N 13/005 . . { with parts constructed of non-metallic material, e.g. of rubber}
- F01N 13/007 . { Apparatus used as intake or exhaust silencer (silencing methods [F01N 1/00](#); intake silencers [F02M 35/12](#))}
- F01N 13/008 . { Mounting or arrangement of exhaust sensors in or on exhaust apparatus (sensor arrangements for engine control [F02D 41/1439](#))}
- F01N 13/02 . having two or more separate silencers in series
- F01N 13/04 . having two or more silencers in parallel e.g. having interconnections for multi-cylinder engines
- F01N 13/06 . specially adapted for star-arrangement of cylinders, e.g. exhaust manifolds
- F01N 13/08 . Other arrangements or adaptations of exhaust conduits ({ pipes, joints or supports therefor in general [F16L](#); collecting or removing exhaust gases of vehicle engines in workshops [B08B 15/00](#), on highways [E01C 1/005](#))}
- F01N 13/082 . . { of tailpipe, e.g. with means for mixing air with exhaust for exhaust cooling, dilution or evacuation ([F01N 13/20](#) takes precedence)}
- F01N 13/085 . . { having means preventing foreign matter from entering exhaust conduit}
- F01N 13/087 . . { having valves upstream of silencing apparatus for by-passing at least part of exhaust directly to atmosphere (valves for changing gas flow path through the silencer [F01N 1/166](#))}
- F01N 13/10 . . of exhaust manifolds {(with cooling jacket [F01N 3/046](#))}
- F01N 13/102 . . . { having thermal insulation}
- F01N 13/105 . . . { having the form of a chamber directly connected to the cylinder head, e.g. without having tubes connected between cylinder head and chamber}

- F01N 13/107 ... { More than one exhaust manifold or exhaust collector}
- F01N 13/12 . specially adapted for submerged exhausting
- F01N 13/14 . having thermal insulation {(exhaust manifolds [F01N 13/102](#))}
- F01N 13/141 .. { Double-walled exhaust pipes or housings}
- F01N 13/143 ... { with air filling the space between both walls}
- F01N 13/145 ... { with gas other than air filling the space between both walls}
- F01N 13/146 ... { with vacuum in the space between both walls}
- F01N 13/148 .. { Multiple layers of insulating material}
- F01N 13/16 . Selection of particular materials
- F01N 13/18 . Construction facilitating manufacture, assembly, or disassembly
- F01N 13/1805 .. { Fixing exhaust manifolds, exhaust pipes or pipe sections to each other, to engine or to vehicle body (pipe joints in general [F16L](#); fixing auxiliaries in motor vehicles in general [B60K](#))}
- F01N 13/1811 ... { with means permitting relative movement, e.g. compensation of thermal expansion or vibration}
- F01N 13/1816 { the pipe sections being joined together by flexible tubular elements only, e.g. using bellows or strip-wound pipes}
- F01N 13/1822 { for fixing exhaust pipes or devices to vehicle body}
- F01N 13/1827 ... { Sealings specially adapted for exhaust systems (sealings in general [F16J 15/00](#))}
- F01N 13/1833 .. { specially adapted for small internal combustion engines, e.g. used in model applications}
- F01N 13/1838 .. { characterised by the type of connection between parts of exhaust or silencing apparatus, e.g. between housing and tubes, between tubes and baffles}
- F01N 13/1844 ... { Mechanical joints}
- F01N 13/185 { the connection being realised by deforming housing, tube, baffle, plate, or parts thereof}
- F01N 13/1855 { the connection being realised by using bolts, screws, rivets or the like}
- F01N 13/1861 .. { the assembly using parts formed by casting or moulding}
- F01N 13/1866 ... { the channels or tubes thereof being made integrally with the housing}
- F01N 13/1872 .. { the assembly using stamp-formed parts or otherwise deformed sheet-metal}
- F01N 13/1877 ... { the channels or tubes thereof being made integrally with the housing}
- F01N 13/1883 .. { manufactured by hydroforming}
- F01N 13/1888 .. { the housing of the assembly consisting of two or more parts, e.g. two half-shells}
- F01N 13/1894 ... { the parts being assembled in longitudinal direction}
- F01N 13/20 . having flared outlets, e.g. of fish-tail shape
-
- F01N 2013/00 **Exhaust or silencing apparatus characterised by constructional features;** { Exhaust or silencing apparatus, or parts thereof, having pertinent characteristics not provided for in, or of interest apart from, groups [F01N 1/00](#) to [F01N 5/00](#), [F01N 9/00](#), [F01N 11/00](#)}

- F01N 2013/02 . having two or more separate silencers in series
- [F01N 2013/023](#) . . with two or more of the same type of purifying devices in series
- [F01N 2013/026](#) . . in a single housing
- F01N 2013/04 . having two or more silencers in parallel e.g. having interconnections for multi-cylinder engines
- [F01N 2013/045](#) . . in a single housing

F01N 2210/00 Combination of methods of silencing

- [F01N 2210/02](#) . Resonance and interference
- [F01N 2210/04](#) . Throttling-expansion and resonance
- [F01N 2210/06](#) . Throttling-expansion and interference

F01N 2230/00 Combination of silencers and other devices

- [F01N 2230/02](#) . Exhaust filters
- [F01N 2230/04](#) . Catalytic converters
- [F01N 2230/06](#) . Spark arresters
- [F01N 2230/08](#) . Thermal reactors

F01N 2240/00 Combination or association of two or more different exhaust treating devices, or of at least one such device with an auxiliary device, not covered by indexing codes [F01N 2230/00](#) or [F01N 2250/00](#), one of the devices being

- [F01N 2240/02](#) . a heat exchanger
- [F01N 2240/04](#) . an electric, e.g. electrostatic, device other than a heater
- [F01N 2240/05](#) . a magnetic, e.g. electromagnetic, device other than a valve
- [F01N 2240/06](#) . an inertial, e.g. centrifugal, device
- [F01N 2240/10](#) . a heat accumulator
- [F01N 2240/12](#) . a thermal reactor
- [F01N 2240/14](#) . a fuel burner

- F01N 2240/16 . an electric heater, i.e. a resistance heater
- F01N 2240/18 . an adsorber or absorber
- F01N 2240/20 . a flow director or deflector
- F01N 2240/22 . a condensation chamber
- F01N 2240/25 . an ammonia generator
- F01N 2240/26 . an exhaust gas reservoir, e.g. emission buffer
- F01N 2240/28 . a plasma reactor
- F01N 2240/30 . a fuel reformer
- F01N 2240/32 . a fuel cell
- F01N 2240/34 . an electrolyser
- F01N 2240/36 . an exhaust flap
- F01N 2240/38 . an ozone (O₃) generator, e.g. for adding ozone after generation of ozone from air
- F01N 2240/40 . a hydrolysis catalyst

F01N 2250/00 Combinations of different methods of purification

- F01N 2250/02 . filtering and catalytic conversion
- F01N 2250/04 . afterburning and catalytic conversion
- F01N 2250/06 . afterburning and filtering
- F01N 2250/08 . filtering and inertial particulate separation
- F01N 2250/10 . cooling and filtering
- F01N 2250/12 . absorption or adsorption, and catalytic conversion
- F01N 2250/14 . absorption or adsorption, and filtering

F01N 2260/00 Exhaust treating devices having provisions not otherwise provided for

- F01N 2260/02 . for cooling the device
- F01N 2260/022 . . using air
- F01N 2260/024 . . using a liquid
- F01N 2260/04 . for regeneration or reactivation, e.g. of catalyst

F01N 2260/06	<ul style="list-style-type: none"> for improving exhaust evacuation or circulation, or reducing back-pressure
F01N 2260/08	<ul style="list-style-type: none"> for preventing heat loss or temperature drop, using other means than layers of heat-insulating material
F01N 2260/10	<ul style="list-style-type: none"> for avoiding stress caused by expansions or contractions due to temperature variations
F01N 2260/12	<ul style="list-style-type: none"> for resisting high pressure
F01N 2260/14	<ul style="list-style-type: none"> for modifying or adapting flow area or back-pressure
F01N 2260/16	<ul style="list-style-type: none"> for reducing exhaust flow pulsations
F01N 2260/18	<ul style="list-style-type: none"> for improving rigidity, e.g. by wings, ribs
F01N 2260/20	<ul style="list-style-type: none"> for heat or sound protection, e.g. using a shield or specially shaped outer surface of exhaust device
F01N 2260/22	<ul style="list-style-type: none"> for preventing theft of exhaust parts or devices, e.g. anti-theft arrangements
F01N 2260/24	<ul style="list-style-type: none"> for identifying exhaust parts or devices, e.g. by labels, stickers or directly printing
F01N 2260/26	<ul style="list-style-type: none"> for preventing enter of dirt into the device
F01N 2270/00	Mixing air with exhaust gases
F01N 2270/02	<ul style="list-style-type: none"> for cooling exhaust gases or the apparatus
F01N 2270/04	<ul style="list-style-type: none"> for afterburning
F01N 2270/06	<ul style="list-style-type: none"> for silencing
F01N 2270/08	<ul style="list-style-type: none"> for evacuation of exhaust gases, e.g. in tail-pipes
F01N 2270/10	<ul style="list-style-type: none"> for rendering exhaust innocuous, e.g. by dilution
F01N 2290/00	Movable parts or members in exhaust systems for other than for control purposes
F01N 2290/02	<ul style="list-style-type: none"> with continuous rotary movement
F01N 2290/04	<ul style="list-style-type: none"> .. driven by exhaust gases
F01N 2290/06	<ul style="list-style-type: none"> .. driven by auxiliary drive
F01N 2290/08	<ul style="list-style-type: none"> with oscillating or vibrating movement
F01N 2290/10	<ul style="list-style-type: none"> .. actuated by pressure of exhaust gases, e.g. exhaust pulses
F01N 2310/00	Selection of sound absorbing or insulating material

- F01N 2310/02 . Mineral wool, e.g. glass wool, rock wool, asbestos or the like
- F01N 2310/04 . Metallic wool, e.g. steel wool, copper wool or the like
- F01N 2310/06 . Porous ceramics
- F01N 2310/08 . Exfoliated vermiculite, e.g. zonolite, coke, pumice
- F01N 2310/10 . Plastic foam
- F01N 2310/12 . Granular material
- F01N 2310/14 . Wire mesh fabric, woven glass cloth or the like

F01N 2330/00 Structure of catalyst support or particle filter

- F01N 2330/02 . Metallic plates or honeycombs, e.g. superposed or rolled-up corrugated or otherwise deformed sheet metal
- F01N 2330/04 . . . Methods of manufacturing
- F01N 2330/06 . Ceramic, e.g. monoliths
- F01N 2330/08 . Granular material
- F01N 2330/10 . Fibrous material, e.g. mineral or metallic wool
- F01N 2330/101 . . . using binders, e.g. to form a permeable mat, paper or the like
- F01N 2330/102 fibrous material being fiber reinforced polymer made of plastic matrix reinforced by fine glass or in the form of a loose mass of filaments or fibers
- F01N 2330/12 . Metallic wire mesh fabric or knitting
- F01N 2330/14 . Sintered material
- F01N 2330/18 . Composite material
- F01N 2330/20 . Plastics, e.g. polymers, polyester, polyurethane
- F01N 2330/22 . Metal foam
- F01N 2330/30 . Honeycomb supports characterised by their structural details
- F01N 2330/32 . . . characterised by the shape, form or number of corrugations of plates, sheets or foils
- F01N 2330/321 with two or more different kinds of corrugations in the same substrate
- F01N 2330/322 Corrugations of trapezoidal form
- F01N 2330/323 Corrugations of saw-tooth or triangular form
- F01N 2330/324 Corrugations of rectangular form
- F01N 2330/325 Corrugations of omega form
- F01N 2330/34 . . . with flow channels of polygonal cross section

F01N 2330/36	.. with flow channels formed by tubes
F01N 2330/38	.. flow channels with means to enhance flow mixing, (e.g. protrusions or projections)
F01N 2330/40	.. made of a single sheet, foil or plate
F01N 2330/42	.. made of three or more different sheets, foils or plates stacked one on the other
F01N 2330/44	.. made of stacks of sheets, plates or foils that are folded in S-form
F01N 2330/48	.. characterised by the number of flow passages, e.g. cell density
F01N 2330/60	. Discontinuous, uneven properties of filter material, e.g. different material thickness along the longitudinal direction; Higher filter capacity upstream than downstream in same housing
F01N 2340/00	Dimensional characteristics of the exhaust system, e.g. length, diameter or volume of the apparatus; Spatial arrangements of exhaust apparatuses
F01N 2340/02	. characterised by the distance of the apparatus to the engine, or the distance between two exhaust treating apparatuses
F01N 2340/04	. characterised by the arrangement of an exhaust pipe, manifold or apparatus in relation to vehicle frame or particular vehicle parts
F01N 2340/06	. characterised by the arrangement of the exhaust apparatus relative to the turbine of a turbocharger
F01N 2350/00	Arrangements for fitting catalyst support or particle filter element in the housing
F01N 2350/02	. Fitting ceramic monoliths in a metallic housing
F01N 2350/04	.. with means compensating thermal expansion
F01N 2350/06	.. with means preventing gas flow by-pass or leakage
F01N 2350/08	. with means for compressing granular material
F01N 2370/00	Selection of materials for exhaust purification
F01N 2370/02	. used in catalytic reactors
F01N 2370/04	.. Zeolitic material
F01N 2370/22	. used in non-catalytic purification apparatus
F01N 2370/24	.. Zeolitic material
F01N 2370/30	.. Materials having magnetic properties
F01N 2370/40	. Activated carbon or charcoal
F01N 2390/00	Arrangements for controlling or regulating exhaust apparatus
F01N 2390/02	. using electric components only
F01N 2390/04	. using electropneumatic components

- F01N 2390/06
 - . using pneumatic components only
- F01N 2390/08
 - . using mechanical components only, e.g. actuated manually
- F01N 2410/00**
By-passing, at least partially, exhaust from inlet to outlet of apparatus, to atmosphere or to other device
- F01N 2410/02
 - . in case of high temperature, e.g. overheating of catalytic reactor
- F01N 2410/03
 - . in case of low temperature
- F01N 2410/04
 - . during regeneration period, e.g. of particle filter
- F01N 2410/06
 - . at cold starting
- F01N 2410/08
 - . in case of clogging, e.g. of particle filter
- F01N 2410/10
 - . for reducing flow resistance, e.g. to obtain more engine power
- F01N 2410/12
 - . in case of absorption, adsorption or desorption of exhaust gas constituents
- F01N 2410/14
 - . in case of excessive pressure, e.g. using a safety valve
- F01N 2430/00**
Influencing exhaust purification, e.g. starting of catalytic reaction, filter regeneration, or the like, by controlling engine operating characteristics
- F01N 2430/02
 - . by cutting out a part of engine cylinders
- F01N 2430/04
 - . by adding non-fuel substances to combustion air or fuel, e.g. additives
- F01N 2430/06
 - . by varying fuel-air ratio, e.g. by enriching fuel-air mixture
- F01N 2430/08
 - . by modifying ignition or injection timing
- F01N 2430/085
 - . . at least a part of the injection taking place during expansion or exhaust stroke
- F01N 2430/10
 - . by modifying inlet or exhaust valve timing
- F01N 2450/00**
Methods or apparatus for fitting, inserting or repairing different elements
- F01N 2450/02
 - . Fitting monolithic blocks into the housing
- F01N 2450/04
 - . Filling or emptying a chamber with granular material
- F01N 2450/06
 - . Inserting sound absorbing material into a chamber
- F01N 2450/08
 - . Repairing the housing or pipe-joints
- F01N 2450/10
 - . Fitting temporarily exhaust apparatus on exhaust conduit, e.g. in confined environment, garage or the like

- F01N 2450/16 . by using threaded joints
- F01N 2450/18 . by using quick-active type locking mechanisms, e.g. clips
- F01N 2450/20 . by mechanical joints, e.g. by deforming housing, tube, baffle plate or parts thereof
- F01N 2450/22 . by welding or brazing
- F01N 2450/24 . by bolts, screws, rivets or the like
- F01N 2450/26 . by bayonet fittings
- F01N 2450/28 . by using adhesive material, e.g. cement
- F01N 2450/30 . Removable or rechargeable blocks or cartridges, e.g. for filters
- F01N 2450/40 . Retrofitting exhaust apparatus

- F01N 2470/00 Structure or shape of gas passages, pipes or tubes**

- F01N 2470/02 . Tubes being perforated
- F01N 2470/04 . . characterised by shape, disposition or dimensions of apertures
- F01N 2470/06 . Tubes being formed by assembly of stamped or otherwise deformed sheet-metal
- F01N 2470/08 . Gas passages being formed between the walls of an outer shell and an inner chamber
- F01N 2470/10 . Tubes having non-circular cross section
- F01N 2470/12 . Tubes being corrugated
- F01N 2470/14 . Plurality of outlet tubes, e.g. in parallel or with different length
- F01N 2470/16 . Plurality of inlet tubes, e.g. discharging into different chambers
- F01N 2470/18 . the axis of inlet or outlet tubes being other than the longitudinal axis of apparatus
- F01N 2470/20 . Dimensional characteristics of tubes, e.g. length, diameter
- F01N 2470/22 . Inlet and outlet tubes being positioned on the same side of the apparatus
- F01N 2470/24 . Concentric tubes or tubes being concentric to housing, e.g. telescopically assembled
- F01N 2470/26 . Tubes being formed by extrusion, drawing or rolling
- F01N 2470/28 . Tubes being formed by moulding or casting x
- F01N 2470/30 . Tubes with restrictions, i.e. venturi or the like, e.g. for sucking air or measuring mass flow

F01N 2490/00**Structure, disposition or shape of gas-chambers**

- F01N 2490/02 . Two or more expansion chambers in series connected by means of tubes
- F01N 2490/04 . . the gases flowing longitudinally from inlet to outlet only in one direction
- F01N 2490/06 . . the gases flowing longitudinally from inlet to outlet in opposite directions
- F01N 2490/08 . Two or more expansion chambers in series separated by apertured walls only
- F01N 2490/10 . Two or more expansion chambers in parallel
- F01N 2490/12 . Chambers having variable volumes
- F01N 2490/14 . Dead or resonance chambers connected to gas flow tube by relatively short side-tubes
- F01N 2490/15 . Plurality of resonance or dead chambers
- F01N 2490/155 . . being disposed one after the other in flow direction
- F01N 2490/16 . Chambers with particular shapes, e.g. spherical
- F01N 2490/18 . Dimensional characteristics of gas chambers
- F01N 2490/20 . Chambers being formed inside the exhaust pipe without enlargement of the cross section of the pipe, e.g. resonance chambers

F01N 2510/00**Surface coverings**

- F01N 2510/02 . for thermal insulation
- F01N 2510/04 . for sound absorption
- F01N 2510/06 . for exhaust purification, e.g. catalytic reaction
- F01N 2510/061 . . usable with leaded fuels
- F01N 2510/063 . . zeolites
- F01N 2510/065 . . for reducing soot ignition temperature
- F01N 2510/067 . . usable with sulfurised fuels
- F01N 2510/068 . . characterised by the distribution of the catalytic coatings
- F01N 2510/0682 . . . having a discontinuous, uneven or partially overlapping coating of catalytic material, e.g. higher amount of material upstream than downstream or vice-versa
- F01N 2510/0684 . . . having more than one coating layer, e.g. multi-layered coatings
- F01N 2510/08 . for corrosion prevention
- F01N 2510/10 . for preventing carbon deposits, e.g. chromium
- F01N 2510/12 . for smell removal

F01N 2510/14 . for dehydrating

F01N 2530/00 Selection of materials for tubes, chambers or housings

F01N 2530/02 . Corrosion resistive metals

F01N 2530/04 . . Steel alloys, e.g. stainless steel

F01N 2530/06 . Aluminium or alloys thereof

F01N 2530/18 . Plastics material, e.g. polyester resin

F01N 2530/20 . . reinforced with mineral or metallic fibres

F01N 2530/22 . Flexible elastomeric material

F01N 2530/24 . Sintered porous material, e.g. bronze, aluminium or the like

F01N 2530/26 . Multi-layered walls

F01N 2550/00 Monitoring or diagnosing the deterioration of exhaust systems

F01N 2550/02 . Catalytic activity of catalytic converters

F01N 2550/03 . of sorbing activity of adsorbents or absorbents

F01N 2550/04 . Filtering activity of particulate filters

F01N 2550/05 . Systems for adding substances into exhaust

F01N 2550/06 . By-pass systems

F01N 2550/10 . . of catalytic converters

F01N 2550/12 . . of particulate filters

F01N 2550/14 . Systems for adding secondary air into exhaust

F01N 2550/20 . Monitoring artificially aged exhaust systems

F01N 2550/22 . of electric heaters for exhaust systems or their power supply

F01N 2550/24 . Determining the presence or absence of an exhaust treating device

F01N 2560/00 Exhaust systems with means for detecting or measuring exhaust gas components or characteristics

F01N 2560/02 . the means being an exhaust gas sensor

F01N 2560/021 . . for measuring or detecting ammonia NH₃

F01N 2560/022 . . for measuring or detecting CO or CO₂

F01N 2560/023 . . for measuring or detecting HC

F01N 2560/024	..	for measuring or detecting hydrogen H ₂
F01N 2560/025	..	for measuring or detecting O ₂ , e.g. lambda sensors
F01N 2560/026	..	for measuring or detecting NO _x
F01N 2560/027	..	for measuring or detecting SO _x
F01N 2560/028	..	for measuring or detecting humidity or water
F01N 2560/05	.	the means being a particulate sensor
F01N 2560/06	.	the means being a temperature sensor
F01N 2560/07	.	the means being an exhaust gas flow rate or velocity meter or sensor, intake flow meters only when exclusively used to determine exhaust gas parameters
F01N 2560/08	.	the means being a pressure sensor
F01N 2560/12	.	Other sensor principles, e.g. using electro conductivity of substrate or radio frequency
F01N 2560/14	.	having more than one sensor of one kind
F01N 2560/20	.	Sensor having heating means
F01N 2570/00		Exhaust treating apparatus eliminating, absorbing or adsorbing specific elements or compounds
F01N 2570/02	.	Lead
F01N 2570/04	.	Sulfur or sulfur oxides
F01N 2570/06	.	Zinc
F01N 2570/08	.	Phosphorus
F01N 2570/10	.	Carbon or carbon oxides
F01N 2570/12	.	Hydrocarbons
F01N 2570/14	.	Nitrogen oxides
F01N 2570/145	..	Dinitrogen oxide
F01N 2570/16	.	Oxygen
F01N 2570/18	.	Ammonia
F01N 2570/20	.	Formaldehyde
F01N 2570/22	.	Water or humidity
F01N 2570/24	.	Hydrogen sulfide (H ₂ S)

F01N 2590/00 **Exhaust or silencing apparatus adapted to particular use, e.g. for military applications, airplanes, submarines**

- F01N 2590/02 . for marine vessels or naval applications
- F01N 2590/021 . . for outboard engines
- F01N 2590/022 . . for jetskis
- F01N 2590/04 . for motorcycles
- F01N 2590/06 . for hand-held tools or portables devices
- F01N 2590/08 . for heavy duty applications, e.g. trucks, buses, tractors, locomotives
- F01N 2590/10 . for stationary applications
- F01N 2590/11 . for hybrid vehicles

F01N 2610/00 **Adding substances to exhaust gases**

- F01N 2610/01 . the substance being catalytic material in liquid form
- F01N 2610/02 . the substance being ammonia or urea
- F01N 2610/03 . the substance being hydrocarbons, e.g. engine fuel
- F01N 2610/04 . the substance being hydrogen
- F01N 2610/05 . the substance being carbon monoxide
- F01N 2610/06 . the substance being in the gaseous form
- F01N 2610/08 . with prior mixing of the substances with a gas, e.g. air
- F01N 2610/085 . . Controlling the air supply
- F01N 2610/10 . the substance being heated, e.g. by heating tank or supply line of the added substance
- F01N 2610/102 . . after addition to exhaust gases, e.g. by a passively or actively heated surface in the exhaust conduit
- F01N 2610/105 . . Control thereof
- F01N 2610/107 . . using glow plug heating elements
- F01N 2610/11 . the substance or part of the dosing system being cooled
- F01N 2610/12 . the substance being in solid form, e.g. pellets or powder
- F01N 2610/14 . Arrangements for the supply of substances, e.g. conduits
- F01N 2610/1406 . . Storage means for substances, e.g. tanks or reservoirs
- F01N 2610/1413 . . . Inlet and filling arrangements therefore

F01N 2610/142	...	Controlling the filling of the tank
F01N 2610/1426	..	Filtration means
F01N 2610/1433	..	Pumps
F01N 2610/144	...	Control thereof
F01N 2610/1446	..	Means for damping of pressure fluctuations in the delivery system, e.g. by puffer volumes or throttling
F01N 2610/1453	..	Sprayers or atomisers; Arrangement thereof in the exhaust apparatus
F01N 2610/146	...	Control thereof, e.g. control of injectors or injection valves
F01N 2610/1466	..	Means for venting air out of conduits or tanks
F01N 2610/1473	..	Overflow or return means for the substances, e.g. conduits or valves for the return path
F01N 2610/148	..	Arrangement of sensors
F01N 2610/1486	..	Means to prevent the substance from freezing
F01N 2610/1493	..	Means for prevention of purging or clogging

F01N 2900/00 Details of electrical control or of the monitoring of the exhaust gas treating apparatus

F01N 2900/04	.	Methods of control or diagnosing
F01N 2900/0402	..	using adaptive learning
F01N 2900/0404	..	using a data filter
F01N 2900/0406	..	using a model with a division of the catalyst or filter in several cells
F01N 2900/0408	..	using a feed-back loop
F01N 2900/0411	..	using a feed-forward control
F01N 2900/0412	..	using pre-calibrated maps, tables or charts
F01N 2900/0414	..	using a state observer
F01N 2900/0416	..	using the state of a sensor, e.g. of an exhaust gas sensor
F01N 2900/0418	..	using integration or an accumulated value within an elapsed period
F01N 2900/0421	..	using an increment counter when a predetermined event occurs
F01N 2900/0422	..	measuring the elapsed time
F01N 2900/06	.	Parameters used for exhaust control or diagnosing
F01N 2900/0601	..	being estimated
F01N 2900/0602	..	Electrical exhaust heater signals
F01N 2900/08	..	said parameters being related to the engine
F01N 2900/10	..	said parameters being related to the vehicle or its components
F01N 2900/102	...	Travelling distance
F01N 2900/104	...	Battery status
F01N 2900/12	..	said parameters being related to the vehicle exterior
F01N 2900/14	..	said parameters being related to the exhaust gas
F01N 2900/1402	...	Exhaust gas composition
F01N 2900/1404	...	Exhaust gas temperature

F01N 2900/1406	...	Exhaust gas pressure
F01N 2900/1411	...	Exhaust gas velocity
F01N 2900/16	..	said parameters being related to the exhaust apparatus, e.g. particulate filter or catalyst
F01N 2900/1602	...	Temperature of exhaust gas apparatus
F01N 2900/1606	...	Particle filter loading or soot amount
F01N 2900/1611	...	Particle filter ash amount
F01N 2900/1612	...	SOx amount trapped in catalyst
F01N 2900/1614	...	NOx amount trapped in catalyst
F01N 2900/1616	...	NH3-slip from catalyst
F01N 2900/1618	...	HC-slip from catalyst
F01N 2900/1621	...	Catalyst conversion efficiency
F01N 2900/1622	...	Catalyst reducing agent absorption capacity or consumption amount
F01N 2900/1624	...	Catalyst oxygen storage capacity
F01N 2900/1626	...	Catalyst activation temperature
F01N 2900/1628	...	Moisture amount in exhaust apparatus
F01N 2900/1631	...	Heat amount provided to exhaust apparatus
F01N 2900/18	..	said parameters being related to the system for adding a substance into the exhaust
F01N 2900/1804	...	Properties of secondary air added directly to the exhaust
F01N 2900/1806	...	Properties of reducing agent or dosing system
F01N 2900/1808	Pressure
F01N 2900/1811	Temperature
F01N 2900/1812	Flow rate
F01N 2900/1814	Tank level
F01N 2900/1818	Concentration of the reducing agent
F01N 2900/1821	Injector parameters
F01N 2900/1822	Pump parameters
F01N 2900/1824	Properties of the air to be mixed with added substances, e.g. air pressure or air temperature