

CPC**COOPERATIVE PATENT CLASSIFICATION****H01P**

WAVEGUIDES; RESONATORS, LINES, OR OTHER DEVICES OF THE WAVEGUIDE TYPE (operating at optical frequencies [G02B](#) ; aeriels [H01Q](#) ; {modulating electromagnetic waves in transmission line, waveguide, cavity resonator or radiation field of aerial [H03C 7/02](#) }; networks comprising lumped impedance elements [H03H](#))

NOTE

In this subclass, the following expression is used with the meaning indicated :

- "waveguide type" as applied to transmission lines includes only high-frequency coaxial cables or Lecher lines, and as applied to resonators, delay lines, or other devices includes all devices having distributed inductance and capacitance.

H01P 1/00

Auxiliary devices (coupling devices of the waveguide type [H01P 5/00](#))

H01P 1/005

. {Diode mounting means }

H01P 1/02

. Bends; Corners; Twists

H01P 1/022

.. {in waveguides of polygonal cross-section ([H01P 1/065](#) takes precedence) }

H01P 1/025

... {in the E-plane }

H01P 1/027

... {in the H-plane }

H01P 1/04

. Fixed joints ({pipe joints [F16L](#) }; line connectors [H01R](#) ; cable fittings [H02G 15/00](#))

H01P 1/042

.. {Hollow waveguide joints }

H01P 1/045

.. {Coaxial joints }

H01P 1/047

.. {Strip line joints }

H01P 1/06

. Movable joints, e.g. rotating joints

H01P 1/061

.. {the relative movement being a translation along an axis common to at least two rectilinear parts, e.g. expansion joints }

H01P 1/062

.. {the relative movement being a rotation }

H01P 1/063

... {with a limited angle of rotation }

H01P 1/064

.... {the axis of rotation being perpendicular to the transmission path, e.g. hinge joint }

H01P 1/065

.... {the axis of rotation being parallel to the transmission path, e.g. stepped twist }

H01P 1/066

... {with an unlimited angle of rotation }

H01P 1/067

.... {the energy being transmitted in only one line located on the axis of rotation }

H01P 1/068

.... {the energy being transmitted in at least one ring-shaped transmission line located around the axis of rotation, e.g. "around the mast" rotary joint ([H01P 1/069](#) takes precedence; coaxial line with solid inner conductor [H01P 1/067](#)) }

H01P 1/069

.... {the energy being transmitted in at least one ring-shaped transmission line

located around an axial transmission line; Concentric coaxial systems }

- H01P 1/08 . Dielectric windows (coupling devices for transit time tubes [H01J 23/36](#))
- H01P 1/10 . for switching or interrupting { (in systems using reflection or reradiation of radio, acoustic or other waves [G01S 7/034](#)) }
- H01P 1/11 . . by ferromagnetic devices
- H01P 1/12 . . by mechanical chopper
- H01P 1/122 . . . {Waveguide switches }
- H01P 1/125 . . . {Coaxial switches }
- H01P 1/127 . . . {Strip line switches }
- H01P 1/14 . . by electric discharge devices (discharge devices [H01J 17/64](#))
- H01P 1/15 . . by semiconductor devices
- H01P 1/16 . for mode selection, e.g. mode suppression or mode promotion; for mode conversion (linking dissimilar lines or devices [H01P 5/08](#))
- H01P 1/161 . . sustaining two independent orthogonal modes, e.g. orthomode transducer { (combining or separating polarisations and frequencies [H01P 1/2131](#)) }
- H01P 1/162 . . absorbing spurious or unwanted modes of propagation
- H01P 1/163 . . specifically adapted for selection or promotion of the TE 01 circular-electric mode
- H01P 1/165 . for rotating the plane of polarisation
- H01P 1/17 . . for producing a continuously rotating polarisation, e.g. circular polarisation
- H01P 1/171 . . . {using a corrugated or ridged waveguide section }
- H01P 1/172 . . . {using a dielectric element }
- H01P 1/173 . . . {using a conductive element }
- H01P 1/174 . . . {using a magnetic element ([H01P 1/175](#) takes precedence) }
- H01P 1/175 . . using Faraday rotators
- H01P 1/18 . Phase-shifters ([H01P 1/165](#) takes precedence; coupling devices with variable coupling factor [H01P 5/04](#))
- H01P 1/181 . . {using ferroelectric devices }
- H01P 1/182 . . {Waveguide phase-shifters ([H01P 1/181](#), [H01P 1/185](#), [H01P 1/19](#) take precedence) }
- H01P 1/183 . . {Coaxial phase-shifters ([H01P 1/181](#), [H01P 1/185](#), [H01P 1/19](#) take precedence) }
- H01P 1/184 . . {Strip line phase-shifters ([H01P 1/181](#), [H01P 1/185](#), [H01P 1/19](#) take precedence) }
- H01P 1/185 . . using a diode or a gas filled discharge tube
- H01P 1/19 . . using a ferromagnetic device
- H01P 1/195 . . . having a toroidal shape
- H01P 1/20 . Frequency-selective devices, e.g. filters ({variable impedance transformers, e.g. slug tuners or stub tuners [H01P 5/04](#) }; resonators [H01P 7/00](#))
- H01P 1/2002 . . {Dielectric waveguide filters ([H01P 1/212](#), [H01P 1/213](#), [H01P 1/215](#), [H01P 1/219](#) take precedence) }
- H01P 1/2005 . . { Electromagnetic photonic bandgaps [EPB], or photonic bandgaps [PBG] }
- H01P 1/2007 . . {Filtering devices for biasing networks or DC returns }

H01P 1/201	..	Filters for transverse electromagnetic waves (H01P 1/212 , H01P 1/213 , H01P 1/215 , H01P 1/219 take precedence)
H01P 1/2013	...	{Coplanar line filters }
H01P 1/2016	...	{Slot line filters; Fin line filters }
H01P 1/202	...	Coaxial filters (cascaded coaxial cavities H01P 1/205)
H01P 1/203	...	Strip line filters
H01P 1/20309	{with dielectric resonator }
H01P 1/20318	{ with dielectric resonators as non-metallised opposite openings in the metallised surfaces of a substrate }
H01P 1/20327	{ Electromagnetic interstage coupling }
H01P 1/20336	{Comb or interdigital filters }
H01P 1/20345	{ Multilayer filters }
H01P 1/20354	{ Non-comb or non-interdigital filters }
H01P 1/20363	{ Linear resonators }
H01P 1/20372	{Hairpin resonators }
H01P 1/20381	{ Special shape resonators }
H01P 1/2039	{ Galvanic coupling between Input/Output }
H01P 1/205	...	Comb or interdigital filters; Cascaded coaxial cavities (H01P 1/203 takes precedence)
H01P 1/2053	{the coaxial cavity resonators being disposed parall to each other }
H01P 1/2056	{Comb filters or interdigital filters with metallised resonator holes in a dielectric block }
H01P 1/207	..	Hollow waveguide filters (H01P 1/212 , H01P 1/213 , H01P 1/215 , H01P 1/219 take precedence)
H01P 1/208	...	Cascaded cavities; Cascaded resonators inside a hollow waveguide structure (H01P 1/205 takes precedence)
H01P 1/2082	{with multimode resonators (H01P 1/2086 takes precedence) }
H01P 1/2084	{with dielectric resonators }
H01P 1/2086	{multimode }
H01P 1/2088	{ Integrated in a substrate }
H01P 1/209	...	comprising one or more branching arms or cavities wholly outside the main waveguide
H01P 1/211	...	Waffle-iron filters; Corrugated structures
H01P 1/212	..	suppressing or attenuating harmonic frequencies (H01P 1/215 takes precedence)
H01P 1/213	..	combining or separating two or more different frequencies (H01P 1/215 takes precedence)
H01P 1/2131	...	{with combining or separating polarisations }
H01P 1/2133	...	{using coaxial filters (H01P 1/2131 , H01P 1/2136 take precedence) }
H01P 1/2135	...	{using strip line filters (H01P 1/2131 takes precedence) }
H01P 1/2136	...	{using comb or interdigital filters; using cascaded coaxial cavities (H01P 1/2131 , H01P 1/2135 take precedence) }
H01P 1/2138	...	{using hollow waveguide filters (H01P 1/2131 takes precedence) }
H01P 1/215	..	using ferromagnetic material
H01P 1/217	...	the ferromagnetic material acting as a tuning element in resonators
H01P 1/218	...	the ferromagnetic material acting as a frequency selective coupling element,

e.g. YIG-filters

- H01P 1/219 .. Evanescent mode filters
- H01P 1/22 . Attenuating devices ([dissipative terminating devices H01P 1/26](#))
- H01P 1/222 .. {[Waveguide attenuators \(H01P 1/23 takes precedence\)](#) }
- H01P 1/225 .. {[Coaxial attenuators \(H01P 1/23 takes precedence\)](#) }
- H01P 1/227 .. {[Strip line attenuators \(H01P 1/23 takes precedence\)](#) }
- H01P 1/23 .. using ferromagnetic material
- H01P 1/24 . Terminating devices
- H01P 1/26 .. Dissipative terminations
 - H01P 1/262 ... {[the dissipative medium being a liquid or being cooled by a liquid](#) }
 - H01P 1/264 ... {[Waveguide terminations \(H01P 1/262 takes precedence\)](#) }
 - H01P 1/266 ... {[Coaxial terminations \(H01P 1/262 takes precedence\)](#) }
 - H01P 1/268 ... {[Strip line terminations \(H01P 1/262 takes precedence\)](#) }
- H01P 1/28 .. Short-circuiting plungers ([coupling devices with variable coupling factor H01P 5/04](#))
- H01P 1/30 . for compensation of, or protection against, temperature or moisture effects; {[for improving power handling capability \(H01P 1/04, H01P 1/08 take precedence\)](#) }
- H01P 1/32 . Non-reciprocal transmission devices ([H01P 1/02 to H01P 1/30 take precedence](#))
- H01P 1/36 .. Isolators
 - H01P 1/362 ... {[Edge-guided mode devices](#) }
 - H01P 1/365 ... Resonance absorption isolators
 - H01P 1/37 ... Field displacement isolators
 - H01P 1/375 ... using Faraday rotators
- H01P 1/38 .. Circulators
 - H01P 1/383 ... Junction circulators, e.g. Y-circulators
 - H01P 1/387 Strip line circulators
 - H01P 1/39 Hollow waveguide circulators
 - H01P 1/393 ... using Faraday rotators
 - H01P 1/397 ... using non- reciprocal phase shifters ([H01P 1/393 takes precedence](#))

H01P 3/00

Waveguides; Transmission lines of the waveguide type

- H01P 3/003 . {[Coplanar lines](#) }
- H01P 3/006 .. { [Conductor backed coplanar waveguides](#) }
- H01P 3/02 . with two longitudinal conductors
- H01P 3/023 .. {[Fin lines; Slot lines](#) }
- H01P 3/026 .. { [Coplanar striplines \(CPS\)](#) }
- H01P 3/04 .. Lines formed as Lecher wire pairs
- H01P 3/06 .. Coaxial lines ([not suitable for handling frequencies considerably beyond the audio range, {coaxial cables in general} H01B 11/18](#))

NOTE

This subgroup is only used for documents disclosing typical HF-features of coaxial cables, e.g. propagation of non-TEM-modes, multimoding, oversized coaxial cables, particular cross-section adapted for HF-propagation

- H01P 3/08 . . Microstrips; Strip lines
- H01P 3/081 . . . { Micro-striplines }
- H01P 3/082 { Multilayer dielectric }
- H01P 3/084 { Suspended micro-striplines }
- H01P 3/085 . . . { Triplate lines }
- H01P 3/087 { Suspended triplate lines }
- H01P 3/088 . . . { Stacked transmission lines }

- H01P 3/10 . Wire waveguides, i.e. with a single solid longitudinal conductor

- H01P 3/12 . Hollow waveguides ([H01P 3/20](#) takes precedence)
- H01P 3/121 . . { integrated in a substrate }
- H01P 3/122 . . { Dielectric loaded (not air) }
- H01P 3/123 . . with a complex or stepped cross-section, e.g. ridged or grooved waveguides ([H01P 3/14](#) takes precedence)
- H01P 3/127 . . with a circular, elliptic, or parabolic cross-section
- H01P 3/13 . . specially adapted for transmission of the TE₀₁ circular-electric mode { ([selection, promotion H01P 1/163](#)) }
- H01P 3/14 . . flexible

- H01P 3/16 . Dielectric waveguides, i.e. without a longitudinal conductor
- H01P 3/165 . . { Non-radiating dielectric waveguides }

- H01P 3/18 . built-up from several layers to increase operating surface, i.e. alternately conductive and dielectric layers

- H01P 3/20 . Quasi-optical arrangements for guiding a wave, e.g. focusing by dielectric lenses ([quasi-optical devices in general H01Q 15/00](#))

- H01P 5/00** **Coupling devices of the waveguide type** ([non-reciprocal devices H01P 1/32](#); for introducing or removing wave energy to or from the discharge in transit-time tubes [H01J 23/36](#))

- H01P 5/02 . with invariable factor of coupling ([H01P 5/12](#) takes precedence {choke joints [H01P 1/04](#), [H01P 1/06](#) })
- H01P 5/022 . . {Transitions between lines of the same kind and shape, but with different dimensions }
- H01P 5/024 . . . {between hollow waveguides }
- H01P 5/026 . . . {between coaxial lines }
- H01P 5/028 . . . {between strip lines }

- H01P 5/04 . with variable factor of coupling

- H01P 5/08 . for linking dissimilar lines or devices ([H01P 1/16](#), [H01P 5/04](#) take precedence; linking lines of the same kind but with different dimensions [H01P 5/02](#))
- H01P 5/082 . . {Transitions between hollow waveguides of different shape, e.g. between a rectangular and a circular waveguide }
- H01P 5/085 . . {Coaxial-line/strip-line transitions }
- H01P 5/087 . . {Transitions to a dielectric waveguide }
- H01P 5/10 . . for coupling balanced with unbalanced lines or devices
- H01P 5/1007 . . . {Microstrip transitions to Slotline or finline }
- H01P 5/1015 . . . {Coplanar line transitions to Slotline or finline }
- H01P 5/1022 . . . {Transitions to dielectric waveguide }
- H01P 5/103 . . . Hollow-waveguide/coaxial-line transitions
- H01P 5/107 . . . Hollow-waveguide/strip-line transitions

- H01P 5/12 . Coupling devices having more than two ports ([H01P 5/04](#) takes precedence)
- H01P 5/16 . . Conjugate devices, i.e. devices having at least one port decoupled from one other port
- H01P 5/18 . . . consisting of two coupled guides, e.g. directional couplers
- H01P 5/181 {the guides being hollow waveguides }
- H01P 5/182 {the waveguides being arranged in parallel }
- H01P 5/183 {at least one of the guides being a coaxial line }
- H01P 5/184 {the guides being strip lines or microstrips }
- H01P 5/185 { Edge coupled lines }
- H01P 5/186 { Lange couplers }
- H01P 5/187 { Broadside coupled lines }
- H01P 5/188 {the guides being dielectric waveguides }
- H01P 5/19 . . . of the junction type
- H01P 5/20 . . . Magic-T junctions
- H01P 5/22 . . . Hybrid ring junctions
- H01P 5/222 { 180° rat race hybrid rings }
- H01P 5/225 { 180° reversed phase hybrid rings }
- H01P 5/227 { 90° branch line couplers }

H01P 7/00 **Resonators of the waveguide type** ({ variable impedance transformers [H01P 5/04](#) }; structurally associated with transit-time tubes and interacting with the discharge therein [H01J 23/18](#); { generators of electronic oscillations using resonators of this type [H03B 5/18](#), [H03B 7/14](#), [H03B 9/14](#); electronic amplifiers using resonators of this type [H03F 3/54](#) }; microwave heating devices [H05B 6/64](#))

- H01P 7/005 . {Helical resonators; Spiral resonators }
- H01P 7/02 . Lecher resonators
- H01P 7/04 . Coaxial resonators
- H01P 7/06 . Cavity resonators

- H01P 7/065 . . {integrated in a substrate }
- H01P 7/08 . Strip line resonators
- H01P 7/082 . . { Microstripline resonators ([H01P 7/088](#) takes precedence) }
- H01P 7/084 . . { Triplate line resonators ([H01P 7/088](#) takes precedence) }
- H01P 7/086 . . { Coplanar waveguide resonators ([H01P 7/088](#) takes precedence) }
- H01P 7/088 . . { Tunable resonators }
- H01P 7/10 . Dielectric resonators
- H01P 7/105 . . { Multimode resonators }
- H01P 9/00** **Delay lines of the waveguide type** (structurally associated with transit-time tubes and interacting with the discharge therein [H01J 23/24](#))
- H01P 9/003 . {Delay equalizers }
- H01P 9/006 . {Meander lines }
- H01P 9/02 . Helical lines
- H01P 9/04 . Interdigital lines
- H01P 11/00** **Apparatus or processes specially adapted for manufacturing waveguides or resonators, lines, or other devices of the waveguide type** (manufacture of coaxial cables [H01B 13/00](#))
- H01P 11/001 . {Manufacturing waveguides or transmission lines of the waveguide type }
- H01P 11/002 . . {Manufacturing hollow waveguides }
- H01P 11/003 . . {Manufacturing lines with conductors on a substrate, e.g. strip lines, slot lines }
- H01P 11/005 . . {Manufacturing coaxial lines }
- H01P 11/006 . . {Manufacturing dielectric waveguides }
- H01P 11/007 . {Manufacturing frequency-selective devices (resonators [H01P 11/008](#)) }
- H01P 11/008 . {Manufacturing resonators }