

**CPC****COOPERATIVE PATENT CLASSIFICATION****B60B**

**VEHICLE WHEELS** (making wheels or wheel parts by rolling [B21H 1/00](#), by forging, hammering or pressing [B21K 1/28](#)); **CASTORS; AXLES FOR WHEELS OR CASTORS; INCREASING WHEEL ADHESION**

**NOTE**

Attention is drawn to the Explanatory Note following the class title ([B60](#))

**Wheels** (wheels for roller skates [A63C 17/22](#); making wheels or wheel parts [B21D 53/26](#); by rolling [B21H 1/00](#); by forging, hammering, or pressing [B21K 1/28](#))

**B60B 1/00**

**Spoked wheels; Spokes thereof** (non-metallic [B60B 5/00](#) {; spoked wheels comprising rail-engaging elements [B60B 17/001](#); making wheel spokes [B21F 39/00](#)})

- B60B 1/003 . {specially adapted for bicycles ([B60B 1/041](#) takes precedence)}
- B60B 1/006 . {specially adapted for light-weight wheels, e.g. of strollers or wheel-chairs ([B60B 1/003](#) takes precedence)}
- B60B 1/02 . Wheels with wire or other tension spokes
- B60B 1/0207 . . {characterised by non-standard number of spokes, i.e. less than 12 or more than 32 spokes}
- B60B 1/0215 . . {characterised by specific grouping of spokes}
- B60B 1/0223 . . . {the dominant aspect being the spoke arrangement pattern}
- B60B 1/023 . . . . {multiple exclusively parallel spokes arranged in a group}
- B60B 1/0238 . . . {the dominant aspect being the number of spokes per group}
- B60B 1/0246 . . {characterised by cross-section of the spoke, e.g. polygon or elliptic shape}
- B60B 1/0253 . . {the spoke being hollow}
- B60B 1/0261 . . {characterised by spoke form}
- B60B 1/0269 . . . {the spoke being curved or deformed over substantial part of length}
- B60B 1/0276 . . . {the spoke being crooked in the middle and having double length}
- B60B 1/0284 . . . {the spoke being threaded at both ends}
- B60B 1/0292 . . . {the spoke being bent at both ends}
- B60B 1/04 . . Attaching spokes to rim or hub
- B60B 1/041 . . . {of bicycle wheels (bicycle rims characterised by means for attaching spokes [B60B 21/062](#))}
- B60B 1/042 . . . {Attaching spokes to hub}
- B60B 1/043 . . . {Attaching spokes to rim}
- B60B 1/044 . . . . {by the use of spoke nipples}
- B60B 1/045 . . . . . {characterised by their specific shape}
- B60B 1/046 . . . . . {characterised by adaptations of the nipple for tightening tools}
- B60B 1/047 . . . . . {the nipple comprising sealing means}
- B60B 1/048 . . . . . {by the use of screws}

- B60B 1/06 . Wheels with compression spokes ([wheels of high resiliency B60B 9/00](#))
- B60B 1/08 . . formed by casting
- B60B 1/10 . . fabricated by sheet metal ([B60B 1/12](#), [B60B 3/08](#) take precedence)
- B60B 1/12 . . with tubular spokes ([B60B 1/08](#) takes precedence)
- B60B 1/14 . . Attaching spokes to rim or hub
  
- B60B 3/00** **Disc wheels, i.e. wheels with load-supporting disc body** (non-metallic [B60B 5/00](#); wheel cover discs [B60B 7/00](#) {; disc wheels comprising rail-engaging elements [B60B 17/0006](#)})
- B60B 3/001 . {Lightweight wheels, e.g. for strollers or toys}
- B60B 3/002 . {characterised by the shape of the disc}
- B60B 3/004 . . {in the hub section}
- B60B 3/005 . . {in the section adjacent to rim}
- B60B 3/007 . . {in the intermediate section}
- B60B 3/008 . {by the form of wheel bolt mounting section}
- B60B 3/02 . with a single disc body integral with rim
- B60B 3/04 . with a single disc body not integral with rim, {i.e. disc body and rim being manufactured independently and then permanently attached to each other in a second step, e.g. by welding}
- B60B 3/041 . . {characterised by the attachment of rim to wheel disc}
- B60B 3/042 . . . {characterised by circumferential position of attachment means}
- B60B 3/044 . . . {characterised by cross-sectional details of the attachment, e.g. the profile}
- B60B 3/045 . . . {characterised by the attachment portions}
- B60B 3/047 . . . . {comprising specific torque transmitting means}
- B60B 3/048 . . {the rim being rotatably mounted to the wheel disc}
- B60B 3/06 . formed by casting
- B60B 3/08 . with disc body formed by two or more axially spaced discs {(comprising rail-engaging elements formed by two or more axially spaced discs [B60B 17/0013](#))}
- B60B 3/082 . . {especially for light-weight wheels}
- B60B 3/085 . . {Discs having no mutual contact}
- B60B 3/087 . . {Discs having several mutual contact regions}
- B60B 3/10 . apertured to simulate spoked wheels
- B60B 3/12 . Means of reinforcing disc bodies
- B60B 3/14 . Attaching disc body to hub ([resiliently B60B 9/00](#); attaching rim to wheel body [B60B 23/00](#) ) {Wheel adapters}
- B60B 3/142 . . {by central locking nut}
- B60B 3/145 . . {using washers or distance bushes}
- B60B 3/147 . . {using wheel adapters}
- B60B 3/16 . . by bolts or the like
- B60B 3/165 . . . {with locking devices for the fixing means, e.g. screw or nut covers}
- B60B 3/18 . . by circlips or the like

<b>B60B 5/00</b>	<b>Wheels, spokes, disc bodies, rims, hubs, wholly or predominantly made of non-metallic material</b> (wheel cover discs <a href="#">B60B 7/00</a> ; wheels of high resiliency <a href="#">B60B 9/00</a> {;wheel bodies comprising rail-engaging elements characterised by use of non-metallic material <a href="#">B60B 17/0003</a> })
B60B 5/02	<ul style="list-style-type: none"> <li>made of synthetic material</li> </ul>
B60B 5/04	<ul style="list-style-type: none"> <li>made of wood</li> </ul>
<b>B60B 7/00</b>	<b>Wheel cover discs, rings, or the like, for ornamenting, protecting, {venting,} or obscuring, wholly or in part, the wheel body, rim, hub, or tyre sidewall {e.g. wheel cover discs, wheel cover discs with cooling fins</b> (wheels with cooling fins not provided on the wheel cover disc <a href="#">B60B 19/10</a> ; apparatus or tools for removing or attaching cover discs hub caps or the like <a href="#">B60B 31/06</a> })
B60B 7/0006	<ul style="list-style-type: none"> <li>{for cycle wheels or similar}</li> </ul>
B60B 7/0013	<ul style="list-style-type: none"> <li>{Hub caps}</li> </ul>
B60B 7/002	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{being of the ventilated type}</li> </ul> </li> </ul>
B60B 7/0026	<ul style="list-style-type: none"> <li>{characterised by the surface}</li> </ul>
B60B 7/0033	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the dominant aspect being the surface appearance}</li> </ul> </li> </ul>
B60B 7/004	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the surface being painted}</li> </ul> </li> </ul> </li> </ul>
B60B 7/0046	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the surface being plated or coated}</li> </ul> </li> </ul> </li> </ul>
B60B 7/0053	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the surface being decorated}</li> </ul> </li> </ul> </li> </ul>
B60B 7/006	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the surface being reflective or including lighting}</li> </ul> </li> </ul> </li> </ul>
B60B 7/0066	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the dominant aspect being the surface structure}</li> </ul> </li> </ul>
B60B 7/0073	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{being completely closed, i.e. having no cooling openings for the brakes}</li> </ul> </li> </ul> </li> </ul>
B60B 7/008	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{having decorative holes or openings, i.e. openings going beyond mere cooling openings}</li> </ul> </li> </ul> </li> </ul>
B60B 7/0086	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{having cooling fins}</li> </ul> </li> </ul> </li> </ul>
B60B 7/0093	<ul style="list-style-type: none"> <li>{being reinforced against thermal deformation}</li> </ul>
B60B 7/01	<ul style="list-style-type: none"> <li>Rings specially adapted for covering only the wheel rim or the tyre sidewall, e.g. removable tyre sidewall trim rings</li> </ul>
B60B 7/02	<ul style="list-style-type: none"> <li>made essentially in one part ({<a href="#">B60B 7/0006</a>,} <a href="#">B60B 7/01</a> take precedence)</li> </ul>
B60B 7/04	<ul style="list-style-type: none"> <li>built-up of several main parts (<a href="#">B60B 7/01</a>, <a href="#">B60B 7/20</a> take precedence)</li> </ul>
B60B 7/06	<ul style="list-style-type: none"> <li>Fastening arrangements therefor (<a href="#">B60B 7/01</a>, <a href="#">B60B 7/20</a> take precedence)</li> </ul>
B60B 7/061	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{characterised by the part of the wheels to which the discs, rings or the like are mounted}</li> </ul> </li> </ul>
B60B 7/063	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{to the rim}</li> </ul> </li> </ul> </li> </ul>
B60B 7/065	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{to the disc}</li> </ul> </li> </ul> </li> </ul>
B60B 7/066	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{to the hub}</li> </ul> </li> </ul> </li> </ul>
B60B 7/068	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{to the wheel bolts or wheel nuts}</li> </ul> </li> </ul> </li> </ul>
B60B 7/08	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>having gripping elements consisting of formations integral with the cover</li> </ul> </li> </ul>
B60B 7/10	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>comprising a plurality of spaced spring clips individually mounted on the cover, e.g. riveted, welded or readily releasable</li> </ul> </li> </ul>
B60B 7/105	<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>{the spring clip mounted on the rim}</li> </ul> </li> </ul> </li> </ul>

- B60B 7/12
  - . comprising an annular spring or gripping element mounted on the cover ([B60B 7/08](#) takes precedence)
- B60B 7/14
  - . comprising screw-threaded means
- B60B 7/16
  - Anti-theft devices
- B60B 7/18
  - simulating spoked or wire wheel
- B60B 7/20
  - having an element mounted for rotation independently of wheel rotation

**B60B 9/00** **Wheels of high resiliency {, e.g. with conical interacting pressure-surfaces (resilient wheels comprising rail-engaging elements [B60B 17/0027](#))}**

- B60B 9/005
  - {Comprising a resilient hub (hubs per se [B60B 27/00](#))}
- B60B 9/02
  - using springs {resiliently mounted bicycle rims} (wheels comprising resilient spokes [B60B 9/26](#))
- B60B 9/04
  - . in leaf form
- B60B 9/06
  - . in helical form
- B60B 9/08
  - . in flat coiled form
- B60B 9/10
  - . of rubber or the like
- B60B 9/12
  - . . in the form of sleeves or rings concentric with the wheel axis
- B60B 9/14
  - . . with means limiting relative lateral movements between hub and remainder of wheel
- B60B 9/16
  - . . modified to ensure electric conductivity
- B60B 9/18
  - using fluid ([within spokes B60B 9/26](#))
- B60B 9/20
  - . in rings concentric with wheel axis
- B60B 9/22
  - . . inflatable
- B60B 9/24
  - . with pistons and cylinders
- B60B 9/26
  - comprising resilient spokes
- B60B 9/28
  - . with telescopic action

**B60B 11/00** **Units comprising multiple wheels arranged side by side; Wheels having more than one rim or capable of carrying more than one tyre**

- B60B 11/02
  - Units of separate wheels mounted for independent or coupled rotation
- B60B 11/04
  - Wheels with a rim capable of carrying more than one tyre
- B60B 11/06
  - Wheels with more than one rim mounted on a single wheel body
- B60B 11/08
  - Arrangements of balancing mechanisms enabling a uniform distribution of load to tyres
- B60B 11/10
  - Emergency wheels ([collapsible tyres B60C 3/08](#); [tyres characterised by means enabling restricted operation in damaged or deflated condition B60C 17/00](#))

**B60B 15/00** **Wheels or wheel attachments designed for increasing traction ([vehicle tires B60C](#); [non-skid devices temporarily attachable to resilient tires or resiliently-tired wheels B60C](#))**

- B60B 15/02
  - Wheels with spade lugs
- B60B 15/021
  - . {made of resilient material}
- B60B 15/023
  - . {being of the broad form type}
- B60B 15/025
  - . . {with non-cylindrical shape}

- B60B 15/026 . . {characterised by mud deposit prevention}
- B60B 15/028 . . {characterised by active rotation of the lugs}
- B60B 15/04 . . with resiliently-mounted spade lugs
- B60B 15/06 . . with pivotally-mounted spade lugs
- B60B 15/08 . . with spade lugs axially displaced relatively to the tread surface of the tire
- B60B 15/10 . . with radially-adjustable spade lugs; Control mechanisms therefor
- B60B 15/12 . . . involving cams or eccentric hoops
- B60B 15/14 . . . involving an axially-displaceable cone
- B60B 15/16 . . . involving gearing, e.g. gear pinions acting upon threaded shafts on the spade lugs
- B60B 15/18 . Wheels with ground-engaging plate-like shoes
- B60B 15/20 . . with resiliently-mounted shoes, e.g. on a spider
- B60B 15/22 . . connected by links to the hub
- B60B 15/24 . Tread bands or rings for fairing lugs when travelling on the road
- B60B 15/26 . Auxiliary wheels or rings with traction-increasing surface attachable to the main wheel body
- B60B 15/263 . . {Traction increasing surface being located axially beside tire}
- B60B 15/266 . . {Traction increasing surface being located radially outside tire circumferential surface}
- B60B 15/28 . Wheel-ballasting weights; Their attachment
- B60B 17/00** **Wheels characterised by rail-engaging elements** ({wheel-axle combinations [B60B 37/00;](#) of model railways [A63H 19/22](#))
- B60B 17/0003 . {Wheel bodies characterised by use of non-metallic material ([B60B 17/0034](#) takes precedence)}
- B60B 17/0006 . {Construction of wheel bodies, e.g. disc wheels ([B60B 17/0003](#) takes precedence)}
- B60B 17/001 . . {Spoked wheels; Spokes thereof}
- B60B 17/0013 . . {formed by two or more axially spaced discs}
- B60B 17/0017 . . . {with insonorisation means}
- B60B 17/002 . . {with counter-balance}
- B60B 17/0024 . . {with noise reducing means ([B60B 17/0017](#) takes precedence)}
- B60B 17/0027 . {Resilient wheels, e.g. resilient hubs ([B60B 17/02](#) takes precedence)}
- B60B 17/0031 . . {using springs}
- B60B 17/0034 . . . {of rubber or other non-metallic material}
- B60B 17/0037 . . . . {of circular or elliptical cross section}
- B60B 17/0041 . . . . {of substantially rectangular cross section}
- B60B 17/0044 . . . . {single element arranged in V-form}
- B60B 17/0048 . . . . {pair of elements arranged in V-form}
- B60B 17/0051 . . {using fluid}
- B60B 17/0055 . {with non-elastic tyres (e.g. of particular profile or composition)}
- B60B 17/0058 . . {characterised by their fixing to wheel bodies}

- B60B 17/0062 . . {having teeth or protrusions on the circumference of the wheel}
- B60B 17/0065 . {Flange details}
- B60B 17/0068 . . {the flange being provided on a single side}
- B60B 17/0072 . . {the flange being provided on both sides}
- B60B 17/0075 . . {the flange being movable, for adaptation to variable rail or track widths}
- B60B 17/0079 . {the flange having a guide wheel}
- B60B 17/0082 . {Wheels designed to interact with a particular rail profile}
- B60B 17/0086 . . {H-type rail profiles, i.e. the wheels are arranged between upper and lower rail extensions}
- B60B 17/0089 . . {Circular rail profiles}
- B60B 17/0093 . . {Rectangular rail profiles}
- B60B 17/0096 . . {Triangular rail profiles}
- B60B 17/02 . with elastic tyres

**B60B 19/00** **Wheels not otherwise provided for or having characteristics specified in one of the sub-groups of this group**

- B60B 19/003 . {Multidirectional wheels}
- B60B 19/006 . {Magnetic wheels}
- B60B 19/02 . convertible, e.g. from road wheel to rail wheel; Wheels specially designed for alternative use on road and rail
- B60B 19/04 . expansible
- B60B 19/06 . with compartments for fluid, packing or loading material; Buoyant wheels
- B60B 19/08 . with lubricating passages, channels, or reservoirs
- B60B 19/10 . with cooling fins
- B60B 19/12 . Roller-type wheels ([B60B 19/06](#) takes precedence)
- B60B 19/125 . . {with helical projections on radial outer surface translating rotation of wheel into movement along the direction of the wheel axle}
- B60B 19/14 . Ball-type wheels ([B60B 19/06](#) takes precedence)

**Rims; Hubs**

**B60B 21/00** **Rims (non-metallic [B60B 5/00](#); of high resiliency [B60B 9/00](#); capable of carrying more than one tyre [B60B 11/04](#); multiple rims on a single wheel body [B60B 11/06](#); of multi-part type [B60B 25/00](#); metal tyres [B60C](#))**

- B60B 21/02 . characterised by transverse section
- B60B 21/021 . . {with inwardly directed flanges, i.e. the tyre-seat being reversed}
- B60B 21/023 . . {the transverse section being non-symmetrical}
- B60B 21/025 . . {the transverse section being hollow}
- B60B 21/026 . . {the shape of rim well}
- B60B 21/028 . . {the shape of hump}
- B60B 21/04 . . with substantially radial flanges (with rail-engaging flanges [B60B 17/00](#) )  
{([B60B 21/021](#) takes precedence)}
- B60B 21/06 . characterised by means for attaching spokes {, i.e. spoke seats}

- B60B 21/062 . . {for bicycles}
- B60B 21/064 . . {characterised by shape of spoke mounting holes, e.g. elliptical or triangular}
- B60B 21/066 . . {the spoke mounting means being located on a flange oriented radially and formed on the radially inner side of the rim well}
- B60B 21/068 . . {the spoke seat comprising sealing means, e.g. for tubeless racing bike tyres}
- B60B 21/08 . characterised by having braking surfaces
- B60B 21/10 . characterised by the form of tyre-seat or flange, e.g. corrugated ([B60B 21/02 takes precedence](#))
- B60B 21/102 . . {the shape of bead seats}
- B60B 21/104 . . {the shape of flanges}
- B60B 21/106 . . . {the shape of flange end-sections}
- B60B 21/108 . . {the surface of bead seats}
- B60B 21/12 . Appurtenances, e.g. lining bands
- B60B 21/125 . . {Bead clamping elements}

**B60B 23/00**

**Attaching rim to wheel body** (attaching spokes to rim [B60B 1/04](#), [B60B 1/14](#); attaching rims resiliently to wheel body [B60B 9/00](#); {devices for fastening or securing constructional elements or machine parts together [F16B](#)})

**NOTE**

Group [B60B 23/12](#) takes precedence over groups [B60B 23/02](#) to [B60B 23/10](#)

- B60B 23/02 . by split or other expansible ring devices
- B60B 23/04 . by bayonet joint, screw-thread, or like attachments
- B60B 23/06 . by screws, bolts, pins, or clips
- B60B 23/08 . . arranged radially
- B60B 23/10 . . arranged axially
- B60B 23/12 . by devices arranged to permit variation of axial position of rim relative to wheel body for track width adjustment

**B60B 25/00**

**Rims built up of several main parts** {**Locking means for the rim parts**} (tools for assembling divided rims [B60B 31/04](#))

- B60B 25/002 . {Rims split in circumferential direction}
- B60B 25/004 . . {one rim part comprising the wheel disc}
- B60B 25/006 . . {Rims split symmetrically}
- B60B 25/008 . . {comprising spacer means}
- B60B 25/02 . Segmented rims, e.g. with segments arranged in sections; Connecting equipment, e.g. hinges; Insertable flange rings therefor
- B60B 25/04 . Rims with dismountable flange rings, seat rings, or lock rings
- B60B 25/045 . . {on both sides}
- B60B 25/06 . . Split flange rings, e.g. transversely split; Connecting equipment for overlapping the slot
- B60B 25/08 . . Continuous flange rings; Arrangement of recesses enabling the flange rings to be slipped over the rim body



- B60B 25/10 . . . . . Seat rings for the tyre bead part, e.g. split
- B60B 25/12 . . . . . with integral flange part
- B60B 25/14 . . . . . Locking means for flange rings or seat rings
- B60B 25/16 . . . . . Arrangement of bayonet catches
- B60B 25/18 . . . . . Arrangement of split rings
- B60B 25/20 . . . . . Arrangement of screws, bolts, or shouldered pins
- B60B 25/22 . . . . . Other apurtenances, e.g. for sealing the component parts enabling the use of tubeless tyres

**B60B 27/00****Hubs** (non-metallic [B60B 5/00](#); of high resiliency [B60B 9/00](#))

- B60B 27/0005 . . . {with ball bearings}
- B60B 27/001 . . . {with roller-bearings}
- B60B 27/0015 . . . {for driven wheels}
- B60B 27/0021 . . . {characterised by torque transmission means from drive axle}
- B60B 27/0026 . . . . . {of the radial type, e.g. splined key}
- B60B 27/0031 . . . . . {of the axial type, e.g. front teeth}
- B60B 27/0036 . . . {comprising homokinetic joints}
- B60B 27/0042 . . . . . {characterised by the fixation of the homokinetic joint to the hub}
- B60B 27/0047 . . . {characterised by functional integration of other elements}
- B60B 27/0052 . . . {the element being a brake disc}
- B60B 27/0057 . . . {the element being a brake drum}
- B60B 27/0063 . . . {the element being a brake caliper mount}
- B60B 27/0068 . . . {the element being a sensor}
- B60B 27/0073 . . . {characterised by sealing means}
- B60B 27/0078 . . . {characterised by the fixation of bearings}
- B60B 27/0084 . . . . . {caulking to fix inner race}
- B60B 27/0089 . . . . . {caulking to fix outer race}
- B60B 27/0094 . . . {one or more of the bearing races are formed by the hub}
- B60B 27/02 . . . adapted to be rotatably arranged on axle
- B60B 27/023 . . . . . {specially adapted for bicycles}
- B60B 27/026 . . . . . {comprising quick release devices}
- B60B 27/04 . . . housing driving means, e.g. sprockets
- B60B 27/042 . . . . . {comprising a rotational dampers}
- B60B 27/045 . . . . . {comprising a spoke protectors}
- B60B 27/047 . . . . . {comprising a freewheel mechanisms}
- B60B 27/06 . . . adapted to be fixed on axle
- B60B 27/065 . . . . . {characterised by the fixation of the hub to the axle}



**Apparatus or tools for mounting wheels or parts thereof** (hand tools in general [B25](#); tools for mounting tyres [B60C 25/00](#))

**B60B 29/00**      **Apparatus or tools for mounting or dismounting wheels** {(mounting of wheels at assembly lines [B62D 65/12](#))}

- B60B 29/001      . {comprising lifting or aligning means ([B60B 29/002](#) takes precedence)}
- B60B 29/002      . {provided with a dolly}
- B60B 29/003      . {Wrenches, e.g. of the ratchet type ([B60B 29/001](#) takes precedence; wrenches per se [B25B 13/00](#))}
- B60B 29/004      . . {for dual wheels}
- B60B 29/005      . . {hand-driven operating with multiplied forces ([B60B 29/004](#) takes precedence; hand-driven gear-operated wrenches per se [B25B 17/00](#), with torque amplification [B25B 17/02](#))}
- B60B 29/006      . . {with electric or pneumatic drive (power-driven nut setting or loosening tool per se [B25B 21/00](#))}
- B60B 29/007      . . {Supports for wrenches ([B60B 29/005](#), [B60B 29/006](#) take precedence)}
- B60B 29/008      . {Wheel pullers; tools for axial movement of wheels (adjustable axle units for varying track [B60B 35/10](#))}

**B60B 30/00**      **Means for holding wheels or parts thereof** (spare wheel stowing, holding or mounting arrangements on vehicles [B62D 43/00](#))

- B60B 30/02      . engaging the tyre, e.g. the tyre being mounted on the wheel rim
- B60B 30/04      . . the tyre not being mounted on a rim, i.e. holders or supports for tyres alone
- B60B 30/06      . engaging the wheel body, e.g. the rim
- B60B 30/08      . . the central part of the wheel body
- B60B 30/10      . characterised by being provided on a dolly

**B60B 31/00**      **Apparatus or tools for assembling or disassembling wheels**

- B60B 31/005      . {especially for spoked wheels}
- B60B 31/02      . for tightening or straightening wire spokes in situ; for extracting spokes from wheels
- B60B 31/04      . for assembling divided rims
- B60B 31/06      . for removing or attaching cover discs, hub caps, or the like

**B60B 33/00**      **Castors in general; {Anti-clogging castors}** (castors for large containers [B65D 90/18](#))

- B60B 33/0002      . {assembling to the object, e.g. furniture}
- B60B 33/0005      . . {characterised by mounting method}
- B60B 33/0007      . . . {by screwing}
- B60B 33/001      . . . {by snapping, clicking or latching in}
- B60B 33/0013      . . . {by straps, bands or similar}
- B60B 33/0015      . . {characterised by adaptations made to castor}
- B60B 33/0018      . . . {in the form of a flat mounting plate}

B60B 33/0021	. . . {in the form of a mounting pin}
B60B 33/0023	. . . {in the form of specific adaptations to the form of the object}
B60B 33/0026	. . {characterised by adaptations made to the object}
B60B 33/0028	. {Construction of wheels; methods of assembling on axle}
B60B 33/0036	. {characterised by type of wheels}
B60B 33/0039	. . {Single wheels}
B60B 33/0042	. . {Double or twin wheels}
B60B 33/0044	. . {Roller type wheels, i.e. extra wide wheels}
B60B 33/0047	. {characterised by details of the rolling axle}
B60B 33/0049	. . {the rolling axle being horizontal}
B60B 33/0052	. . {the rolling axle being inclined}
B60B 33/0055	. . {the rolling axle intersects swivel axis}
B60B 33/0057	. . {the rolling axle being offset from swivel axis}
B60B 33/006	. {characterised by details of the swivel mechanism}
B60B 33/0063	. . {no swivelling action, i.e. no real caster}
B60B 33/0065	. . {characterised by details of the swivel axis}
B60B 33/0068	. . . {the swivel axis being vertical}
B60B 33/0071	. . . {the swivel axis being inclined}
B60B 33/0073	. . . {the swivel axis being symmetrical to wheel or wheels}
B60B 33/0076	. . . {the swivel axis being offset laterally from wheel center plane}
B60B 33/0078	. {characterised by details of the wheel braking mechanism}
B60B 33/0081	. . {acting on tire tread}
B60B 33/0084	. . {acting on axle end}
B60B 33/0086	. . {acting on rim or side portion of tyre}
B60B 33/0089	. . {acting on the floor}
B60B 33/0092	. . {actuated remotely, e.g. by cable or electrically}
B60B 33/0094	. . {actuated automatically}
B60B 33/0097	. . {acting permanently, e.g. for increased security on low friction surfaces}
B60B 33/02	. with disengageable swivel action, {i.e. comprising a swivel locking mechanism}
B60B 33/021	. . {combined with braking of castor wheel}
B60B 33/023	. . {by using friction}
B60B 33/025	. . {by using form-fit, e.g. front teeth}
B60B 33/026	. . {being actuated remotely, e.g. by cable or electrically}
B60B 33/028	. . {being actuated automatically}
B60B 33/04	. adjustable {, e.g. in height; linearly shifting castors}
B60B 33/045	. . {mounted resiliently, by means of dampers}
B60B 33/06	. . mounted retractably
B60B 33/063	. . . {by linear movement parallel to swivel axis}
B60B 33/066	. . . {by use of a hinge and lever mechanism to swing wheel upwards relative to wheel mount}

- B60B 33/08
  - Ball castors [{\(B60B 33/0028 takes precedence\)}](#)
- B60B 35/00**
  - Axle units; Parts thereof (steerable vehicle stub axles [B62D](#) ) [{Arrangements for lubrication of axles}](#)**
- B60B 35/001
  - [{Axles of the portal type, i.e. axles designed for higher ground clearance}](#)
- B60B 35/002
  - [{Axles of the low floor type, e.g. for low-floor city busses}](#)
- B60B 35/003
  - [{Steerable axles}](#)
- B60B 35/004
  - [{Mounting arrangements for axles}](#)
- B60B 35/005
  - . [{with adaptations at chassis structure}](#)
- B60B 35/006
  - . [{with mounting plates or consoles fitted to axles}](#)
- B60B 35/007
  - . . [{for mounting suspension elements to axles}](#)
- B60B 35/008
  - . . [{for mounting air suspension elements to axles}](#)
- B60B 35/009
  - [{adapted for tiltable wheels}](#)
- B60B 35/02
  - Dead axles, i.e. not transmitting torque
- B60B 35/025
  - . [{the wheels being removable}](#)
- B60B 35/04
  - . straight
- B60B 35/06
  - . cranked
- B60B 35/08
  - . of closed hollow section
- B60B 35/10
  - . adjustable for varying track [{\(tools for axial movement of wheels on axles \[B60B 29/008\]\(#\)\)}](#)
- B60B 35/1009
  - . . [{operated manually}](#)
- B60B 35/1018
  - . . . [{comprising a locking pin}](#)
- B60B 35/1027
  - . . . [{comprising a clamping mechanism}](#)
- B60B 35/1036
  - . . . [{operated with power assistance}](#)
- B60B 35/1045
  - . . . [{electrically}](#)
- B60B 35/1054
  - . . . [{hydraulically}](#)
- B60B 35/1063
  - . . . [{automatically dependent on operational state of the vehicle}](#)
- B60B 35/1072
  - . . . [{by transversally movable elements}](#)
- B60B 35/1081
  - . . . [{the element is a wheel}](#)
- B60B 35/109
  - . . . [{the element is an axle part}](#)
- B60B 35/12
  - Torque-transmitting axles [\(independent suspension aspects \[B60G\]\(#\)\)](#)
- B60B 35/121
  - . [{Power-transmission from drive shaft to hub}](#)
- B60B 35/122
  - . . [{using gearings}](#)
- B60B 35/124
  - . . . [{of the helical or worm type}](#)
- B60B 35/125
  - . . . [{of the planetary type}](#)
- B60B 35/127
  - . . . [{using universal joints}](#)
- B60B 35/128
  - . . . [{of the homokinetic or constant velocity type}](#)
- B60B 35/14
  - . Composite or split, e.g. half- axles; Couplings between axle parts or sections
- B60B 35/16
  - . Axle housings
- B60B 35/163
  - . . [{characterised by specific shape of the housing, e.g. adaptations to give space for other vehicle elements like chassis or exhaust system}](#)

B60B 35/166	<ul style="list-style-type: none"> <li>. . . {characterised by reinforcements, e.g. reinforcement ribs}</li> </ul>
B60B 35/18	<ul style="list-style-type: none"> <li>. . Arrangement of bearings</li> </ul>
<b>B60B 37/00</b>	<b>Wheel-axle combinations, e.g. wheel sets</b> (units comprising multiple wheels arranged side-by-side <a href="#">B60B 11/00</a> ; rail vehicle axle-boxes <a href="#">B61F</a> )
B60B 37/02	<ul style="list-style-type: none"> <li>. the wheels being integral with solid axles</li> </ul>
B60B 37/04	<ul style="list-style-type: none"> <li>. the wheels being rigidly attached to solid axles</li> </ul>
B60B 37/06	<ul style="list-style-type: none"> <li>. the wheels being integral with, or rigidly attached to, hollow axles</li> </ul>
B60B 37/08	<ul style="list-style-type: none"> <li>. . the hollow axles being rotatable around fixed axles</li> </ul>
B60B 37/10	<ul style="list-style-type: none"> <li>. the wheels being individually rotatable around the axles</li> </ul>
B60B 37/12	<ul style="list-style-type: none"> <li>. Axles with a fixed ground wheel and a loose wheel</li> </ul>
<b>B60B 39/00</b>	<b>Increasing wheel adhesion</b> (wheels, wheel attachments or tyre attachments, designed for increasing traction <a href="#">B60B 15/00</a> , <a href="#">B60C</a> ; tyre constructions <a href="#">B60C</a> ; road surface conditioning to prevent slipperiness <a href="#">E01C</a> )
B60B 39/003	<ul style="list-style-type: none"> <li>. {Vehicle mounted non-skid chains actuated by centrifugal force (non-skid devices temporarily attachable to resilient tyres <a href="#">B60C 27/00</a>)}</li> </ul>
B60B 39/006	<ul style="list-style-type: none"> <li>. . {characterised by a control system for the actuation of the rotating chain wheel}</li> </ul>
B60B 39/02	<ul style="list-style-type: none"> <li>. Vehicle fittings for scattering or dispensing material in front of its wheels</li> </ul>
B60B 39/021	<ul style="list-style-type: none"> <li>. . {Details of the dispensing device}</li> </ul>
B60B 39/022	<ul style="list-style-type: none"> <li>. . . {related to reservoirs}</li> </ul>
B60B 39/023	<ul style="list-style-type: none"> <li>. . . {related to metering valves}</li> </ul>
B60B 39/024	<ul style="list-style-type: none"> <li>. . . {related to preconditioning of the dispensing materials}</li> </ul>
B60B 39/025	<ul style="list-style-type: none"> <li>. . . {related to the control system}</li> </ul>
B60B 39/026	<ul style="list-style-type: none"> <li>. . {the material being in gas form}</li> </ul>
B60B 39/027	<ul style="list-style-type: none"> <li>. . . {the gas being heated on purpose}</li> </ul>
B60B 39/028	<ul style="list-style-type: none"> <li>. . . {the gas being exhaust gas}</li> </ul>
B60B 39/04	<ul style="list-style-type: none"> <li>. . the material being granular, e.g. sand (combined control of sanding apparatus and brakes of rail vehicles <a href="#">B61H</a>)</li> </ul>
B60B 39/06	<ul style="list-style-type: none"> <li>. . . the dispensing being effected by mechanical means</li> </ul>
B60B 39/08	<ul style="list-style-type: none"> <li>. . . the dispensing being effected by fluid means</li> </ul>
B60B 39/083	<ul style="list-style-type: none"> <li>. . . . {dispensing being effected by liquid}</li> </ul>
B60B 39/086	<ul style="list-style-type: none"> <li>. . . . {dispensing being effected by gas}</li> </ul>
B60B 39/10	<ul style="list-style-type: none"> <li>. . . the dispensing being controlled electrically or electro-magnetically</li> </ul>
B60B 39/12	<ul style="list-style-type: none"> <li>. . the material being sheet-like or web-like</li> </ul>
<b>B60B 2200/00</b>	<b>Type of product being used or applied</b> (kind of vehicle product being used or applied <a href="#">B60Y 2200/00</a> )
B60B 2200/20	<ul style="list-style-type: none"> <li>. Furniture or medical appliances</li> </ul>
B60B 2200/22	<ul style="list-style-type: none"> <li>. . Chairs</li> </ul>
B60B 2200/222	<ul style="list-style-type: none"> <li>. . . Office chairs</li> </ul>
B60B 2200/224	<ul style="list-style-type: none"> <li>. . . Arm chairs</li> </ul>

- B60B 2200/24 . . Beds
- B60B 2200/242 . . . Hospital beds
- B60B 2200/26 . . Medical appliances
- B60B 2200/40 . Articles of daily use
- B60B 2200/41 . . Waste bins
- B60B 2200/43 . . Carts
- B60B 2200/432 . . . Shopping carts
- B60B 2200/434 . . . Wheel barrows
- B60B 2200/45 . . Suitcases
- B60B 2200/47 . . Physical activity equipment, e.g. leisure or sports articles
- B60B 2200/49 . . Domestic appliances, e.g. vacuum cleaners

**B60B 2310/00****Manufacturing methods**

- B60B 2310/20 . Shaping
- B60B 2310/202 . . by casting
- B60B 2310/204 . . by moulding, e.g. injection moulding, i.e. casting of plastics material
- B60B 2310/206 . . by stamping
- B60B 2310/208 . . by forging
- B60B 2310/2082 . . . by swaging
- B60B 2310/211 . . by folding or bending
- B60B 2310/212 . . by drawing
- B60B 2310/213 . . by punching
- B60B 2310/214 . . by extrusion
- B60B 2310/218 . . by hydroforming
- B60B 2310/221 . . by magnetic pulse forming
- B60B 2310/222 . . by twisting
- B60B 2310/224 . . by rolling
- B60B 2310/226 . . by cutting
- B60B 2310/228 . . by machining
- B60B 2310/231 . . by turning
- B60B 2310/232 . . by milling
- B60B 2310/234 . . by grinding
- B60B 2310/238 . . by thermal spraying of molten material
- B60B 2310/241 . . by weaving or knitting of fibers
- B60B 2310/242 . . by laminating, e.g. fabrication of sandwich sheets
- B60B 2310/30 . joining
- B60B 2310/302 . . by welding
- B60B 2310/3021 . . . by autogen welding
- B60B 2310/3022 . . . by spot welding, plug welding
- B60B 2310/3023 . . . by arc welding, e.g. inert gas arc welding

B60B 2310/3025	. . . by thermal welding, e.g. friction, induction or ultrasonic welding
B60B 2310/3026	. . . by laser welding
B60B 2310/3027	. . . by electron beam welding
B60B 2310/3028	. . . by magnetic pulse welding
B60B 2310/303	. . by soldering
B60B 2310/305	. . by screwing
B60B 2310/306	. . by clamping or wedging, e.g. by clamping inserts as joining means
B60B 2310/307	. . by removably mountable securing elements, e.g. circlips
B60B 2310/311	. . by riveting
B60B 2310/3112	. . . by punch-riveting
B60B 2310/312	. . by hemming or seaming, e.g. by folding of the rim
B60B 2310/314	. . by deformation
B60B 2310/3142	. . by caulking
B60B 2310/316	. . by press-fitting, shrink-fitting
B60B 2310/318	. . by adhesive bonding, e.g. glueing
B60B 2310/321	. . by overmolding
B60B 2310/323	. . by coextrusion
B60B 2310/329	. . by splicing, e.g. of ropes
B60B 2310/50	. Thermal treatment
B60B 2310/52	. . Curing
B60B 2310/54	. . Hardening
B60B 2310/542	. . . Quenching
B60B 2310/56	. . Co-curing; Vulcanisation
B60B 2310/60	. Surface treatment; After treatment
B60B 2310/612	. . Polishing
B60B 2310/614	. . Painting
B60B 2310/616	. . Coating with thin films
B60B 2310/6162	. . . Conductive films
B60B 2310/618	. . Coating with foils
B60B 2310/621	. . Electro-chemical processes
B60B 2310/622	. . Shot-peening
B60B 2310/64	. . Effect of treatments
B60B 2310/642	. . . Matted
B60B 2310/644	. . . Polished
B60B 2310/646	. . . Engraved
B60B 2310/648	. . . Structured
B60B 2310/651	. . . glossy
B60B 2310/652	. . . Reflecting
B60B 2310/654	. . . Anti-corrosive
B60B 2310/656	. . . Decorative

- B60B 2310/658 . . . For advertising
- B60B 2310/661 . . . for protection, e.g. against scratches or stone chips
- B60B 2310/80 . Filament winding

**B60B 2320/00****Manufacturing or maintenance operations**

- B60B 2320/10 . Assembling; disassembling
- B60B 2320/12 . . Assembly devices for spoked wheels
  - B60B 2320/122 . . . for spoke tensioning
  - B60B 2320/124 . . . for trueing of spoked wheels
  - B60B 2320/126 . . . for restoring form or removing local distortions of wheel rims in unassembled state
- B60B 2320/14 . . Assembly devices for divided rims
- B60B 2320/16 . . Devices for attaching or removing cover discs, hub caps or other ornamental rings or elements
- B60B 2320/30 . Balancing
- B60B 2320/50 . Securing
  - B60B 2320/52 . . to prevent loss
    - B60B 2320/522 . . . by locking washer
    - B60B 2320/524 . . . by securing plate

**B60B 2340/00****Wheel transporting, Mounting of wheels**

- B60B 2340/10 . Operation mode
  - B60B 2340/12 . . Operated manually
  - B60B 2340/14 . . Power driven
  - B60B 2340/16 . . Included in assembly line
  - B60B 2340/18 . . Automated process
- B60B 2340/30 . Wheel transporting or handling devices
  - B60B 2340/32 . . for gripping the wheel
  - B60B 2340/34 . . for positioning the wheel to hub or boltholes
  - B60B 2340/36 . . the devices being provided on a dolly
- B60B 2340/50 . Wheel mounting or removal devices
  - B60B 2340/52 . . Auxiliary tools, e.g. For alignment
- B60B 2340/70 . Lifting jacks

**B60B 2360/00****Materials; Physical forms thereof**

- B60B 2360/10 . Metallic materials
  - B60B 2360/102 . . Steel
  - B60B 2360/104 . . Aluminum
  - B60B 2360/106 . . Magnesia
  - B60B 2360/108 . . Titanium
  - B60B 2360/109 . . Bronze
- B60B 2360/14 . Physical forms of metallic parts



B60B 2360/141	. . Sheet-metals
B60B 2360/143	. . Bars, i.e. being solid
B60B 2360/1432	. . . of circular cross section
B60B 2360/1434	. . . of polygonal cross section, e.g. triangular or rectangular
B60B 2360/1436	. . . of elliptical cross section
B60B 2360/144	. . Tubes, i.e. being hollow
B60B 2360/1442	. . . of circular cross section
B60B 2360/1444	. . . of rectangular cross section
B60B 2360/1446	. . . of elliptical cross section
B60B 2360/1448	. . . of irregular cross-section
B60B 2360/145	. . Profiles, i.e. being solid and having irregular cross-section
B60B 2360/1452	. . . L-profiles
B60B 2360/1454	. . . T or H-Profiles
B60B 2360/1456	. . . X or Y-Profiles
B60B 2360/1458	. . . U or V-Profiles
B60B 2360/147	. . Castings
B60B 2360/148	. . Sinterings
B60B 2360/149	. . Metal foams
B60B 2360/30	. Synthetic materials
B60B 2360/32	. . Plastic compositions
B60B 2360/322	. . . Comprising polypropylene
B60B 2360/324	. . . Comprising polyurethane
B60B 2360/33	. . Synthetic foams
B60B 2360/34	. . Reinforced plastics
B60B 2360/341	. . . with fibres
B60B 2360/3412	. . . . Glass fibres
B60B 2360/3414	. . . . Aramide fibres
B60B 2360/3416	. . . . Carbone fibres
B60B 2360/3418	. . . . Aramid fibres
B60B 2360/342	. . . With strands
B60B 2360/3422	. . . . consisting of fibres oriented substantially parallel
B60B 2360/3424	. . . . consisting of braided fibres
B60B 2360/344	. . . With woven material
B60B 2360/3442	. . . . characterised by material mixes
B60B 2360/3444	. . . . characterised by weaving patterns
B60B 2360/346	. . . Material impregnated with resin before being put into form, i.e. prepregs
B60B 2360/3462	. . . . comprising strands
B60B 2360/3464	. . . . comprising woven material
B60B 2360/348	. . . Resins
B60B 2360/36	. . Composite materials

B60B 2360/362	. . . Compounded sheets
B60B 2360/364	. . . comprising honeycomb structures
B60B 2360/366	. . . comprising foams, e.g. synthetic or metal foams
B60B 2360/368	. . . Coproduced material combinations, e.g. By over-molding, co-extrusion, co-curing or vulcanizing
B60B 2360/50	. Rubbers
B60B 2360/70	. Ceramics
B60B 2360/90	. Wood
B60B 2360/92	. Leather
B60B 2360/94	. Cardboard or papers

**B60B 2380/00****Bearings**

B60B 2380/10	. Type
B60B 2380/12	. . Ball bearings
B60B 2380/14	. . Roller bearings
B60B 2380/16	. . Needle bearings
B60B 2380/18	. . Plain or sleeve bearings
B60B 2380/20	. . Linear bearings
B60B 2380/22	. . Magnetic bearings
B60B 2380/30	. Cage
B60B 2380/32	. . Without cage
B60B 2380/40	. Modularity
B60B 2380/42	. . Single-piece
B60B 2380/44	. . Multi-piece
B60B 2380/50	. Load bearing capacity
B60B 2380/60	. Rolling elements
B60B 2380/62	. . Specific number
B60B 2380/64	. . Specific shape
B60B 2380/70	. Arrangements
B60B 2380/71	. . Single track
B60B 2380/73	. . Double track
B60B 2380/75	. . Twin or multiple bearings having identical diameters
B60B 2380/76	. . Twin or multiple bearings having different diameters
B60B 2380/77	. . Diameters of bearings at opposite ends of hub
B60B 2380/772	. . . Identical diameters of bearings at opposite ends of hub
B60B 2380/774	. . . Different diameters of bearings at opposite ends of hub
B60B 2380/80	. Shafts specially adapted to receive bearings
B60B 2380/82	. . Caulked to fix race
B60B 2380/90	. Casings or housings specially adapted to receive bearings
B60B 2380/92	. . Caulked to fix race

**B60B 2900/00****Purpose of invention**

- B60B 2900/10 . Reduction of
- B60B 2900/111 . . Weight
- B60B 2900/112 . . Costs
- B60B 2900/113 . . Production or maintenance time
- B60B 2900/114 . . Size
- B60B 2900/115 . . Complexity
- B60B 2900/116 . . Product variety, e.g. by standardisation or use of adapters
- B60B 2900/121 . . Resisting forces
- B60B 2900/1212 . . . due to friction
- B60B 2900/1214 . . . due to inertia
- B60B 2900/1216 . . . due to air-drag
- B60B 2900/131 . . Vibrations
- B60B 2900/133 . . Noise
- B60B 2900/141 . . Corrosions
- B60B 2900/20 . Avoidance of
- B60B 2900/211 . . Soiling
- B60B 2900/212 . . Damage
- B60B 2900/30 . Increase in
- B60B 2900/311 . . Rigidity or stiffness
- B60B 2900/313 . . Resiliency
- B60B 2900/321 . . Lifetime
- B60B 2900/323 . . Timespan between services
- B60B 2900/325 . . Reliability
- B60B 2900/331 . . Safety or security
- B60B 2900/3312 . . . during regular use
- B60B 2900/3313 . . . during maintenance
- B60B 2900/3314 . . . during production or assembly
- B60B 2900/3315 . . . by avoiding misuse
- B60B 2900/3316 . . . by indicating wear, failure or loss
- B60B 2900/3318 . . . by theft prevention
- B60B 2900/351 . . versatility, e.g. usable for different purposes or different arrangements
- B60B 2900/50 . Improvement of
- B60B 2900/511 . . Sealing
- B60B 2900/5112 . . . against dust or dirt
- B60B 2900/5114 . . . against humidity or water
- B60B 2900/5116 . . . against air-loss
- B60B 2900/5118 . . . against oil-loss
- B60B 2900/513 . . Cooling, e.g. of brakes

<a href="#">B60B 2900/521</a>	<ul style="list-style-type: none"><li>. . Tire mounting or removal (<a href="#">devices therefor B60B 2340/50</a>)</li></ul>
<a href="#">B60B 2900/523</a>	<ul style="list-style-type: none"><li>. . Tire fixation on rim, e.g. fixing axially or circumferentially thereon</li></ul>
<a href="#">B60B 2900/531</a>	<ul style="list-style-type: none"><li>. . User-friendliness</li></ul>
<a href="#">B60B 2900/541</a>	<ul style="list-style-type: none"><li>. . Servicing</li></ul>
<a href="#">B60B 2900/551</a>	<ul style="list-style-type: none"><li>. . Handling of obstacles or difficult terrains</li></ul>
<a href="#">B60B 2900/561</a>	<ul style="list-style-type: none"><li>. . Lubrication</li></ul>
<a href="#">B60B 2900/571</a>	<ul style="list-style-type: none"><li>. . Visibility</li></ul>
<a href="#">B60B 2900/572</a>	<ul style="list-style-type: none"><li>. . Visual appearance</li></ul>
<a href="#">B60B 2900/70</a>	<ul style="list-style-type: none"><li>. Adaptation for</li></ul>
<a href="#">B60B 2900/711</a>	<ul style="list-style-type: none"><li>. . High loads, e.g. by reinforcements</li></ul>
<a href="#">B60B 2900/721</a>	<ul style="list-style-type: none"><li>. . Use under adverse external conditions</li></ul>
<a href="#">B60B 2900/731</a>	<ul style="list-style-type: none"><li>. . Use in cases of damage, failure or emergency</li></ul>
<a href="#">B60B 2900/90</a>	<ul style="list-style-type: none"><li>. Providing or changing</li></ul>
<a href="#">B60B 2900/911</a>	<ul style="list-style-type: none"><li>. . Eccentricity</li></ul>
<a href="#">B60B 2900/921</a>	<ul style="list-style-type: none"><li>. . Conductivity</li></ul>
<a href="#">B60B 2900/931</a>	<ul style="list-style-type: none"><li>. . Magnetic effects</li></ul>