

# CPC COOPERATIVE PATENT CLASSIFICATION

## F05B INDEXING SCHEME RELATING TO MACHINES OR ENGINES OTHER THAN NON-POSITIVE-DISPLACEMENT MACHINES OR ENGINES, TO WIND MOTORS, TO NON-POSITIVE DISPLACEMENT PUMPS, AND TO GENERATING COMBUSTION PRODUCTS OF HIGH PRESSURE OR HIGH VELOCITY

### NOTE

This subclass constitutes an internal scheme for indexing only.

<b>2200/00</b>	<b>Mathematical features</b>	<b>2210/18</b>	• Air and water being simultaneously used as working fluid
2200/10	• Basic functions	<b>2210/20</b>	• Properties
2200/11	• . Sum	<b>2210/30</b>	• Flow characteristics
2200/12	• . Substraction	<b>2210/301</b>	• . with Mach-number kept constant along the flow
2200/13	• . Product	<b>2210/302</b>	• . Pressure kept constant along the flow
2200/14	• . Division	<b>2210/40</b>	• Flow geometry or direction
2200/15	• . Inverse	<b>2210/401</b>	• . upwards due to the buoancy of compressed air
2200/20	• Special functions	<b>2210/402</b>	• . Axial inlet and radial outlet
2200/21	• . Root	<b>2210/403</b>	• . Radial inlet and axial outlet
2200/211	• . . Square root	<b>2210/404</b>	• . bidirectional, i.e. in opposite, alternating directions
2200/212	• . . Cubic root	<b>2220/00</b>	<b>Application</b>
2200/22	• . Power	<b>2220/10</b>	• in ram-jet engines or ram-jet driven vehicles
2200/221	• . . Square power	<b>2220/20</b>	• within closed fluid conduits, e.g. pipes
2200/222	• . . Cubic power	<b>2220/25</b>	• as advertisement
2200/23	• . Logarithm	<b>2220/30</b>	• in turbines
2200/24	• . exponential	<b>2220/301</b>	• . in steam turbines
2200/25	• . Hyperbolic trigonometric, e.g. sinh, cosh, tanh	<b>2220/302</b>	• . in gas turbines
2200/26	• . trigonometric	<b>2220/3021</b>	• . . for a special turbine stage
2200/261	• . . Sine	<b>2220/3022</b>	• . . . the first stage of a turbine
2200/262	• . . Cosine	<b>2220/3023</b>	• . . . an intermediate stage of the turbine
2200/263	• . . Tangent	<b>2220/3025</b>	• . . . the last stage of the turbine
2200/264	• . . Cotangent	<b>2220/303</b>	• . . for aircraft propulsion, e.g. jet engines
2200/30	• miscellaneous	<b>2220/304</b>	• . . to drive unshrouded, low solidity propeller
2200/31	• . odd	<b>2220/305</b>	• . . to drive unshrouded, high solidity propeller
2200/32	• . even	<b>2220/306</b>	• . . to drive shrouded, low solidity propeller
2200/33	• . bigger/smaller	<b>2220/307</b>	• . . to drive shrouded, high solidity propeller
2200/34	• . biggest/smallest	<b>2220/308</b>	• . . providing direct vertical lift
2200/35	• . first	<b>2220/309</b>	• . . in a helicopter
2200/36	• . last	<b>2220/31</b>	• . in ram-air turbines ("RATS")
<b>2210/00</b>	<b>Working fluid</b>	<b>2220/32</b>	• . in water turbines
	<b>NOTE</b>	<b>2220/33</b>	• . specially adapted for the fan of turbofan engines
	Indexing codes of group <a href="#">F05B 2210/00</a> can be followed by a name for a specific working fluid preceded by the "+" sign, e.g. <a href="#">F05B 2210/11</a> +water.	<b>2220/40</b>	• in turbochargers
<b>2210/10</b>	• Kind or type	<b>2220/50</b>	• for auxiliary power units (APU's)
<b>2210/11</b>	• . liquid, i.e. incompressible	<b>2220/60</b>	• making use of surplus or waste energy
<b>2210/12</b>	• . gaseous, i.e. compressible	<b>2220/602</b>	• . with energy recovery turbines
<b>2210/13</b>	• . mixed, e.g. two-phase fluid	<b>2220/604</b>	• . for domestic central heating or production of electricity
<b>2210/132</b>	• . . Pumps with means for separating and evacuating the gaseous phase	<b>2220/61</b>	• for hydrogen and/or oxygen production
<b>2210/14</b>	• . Refrigerants with particular properties, e.g. HFC-134a	<b>2220/62</b>	• for desalination
<b>2210/16</b>	• Air or water being indistinctly used as working fluid, i.e. the machine can work equally with air or water without any modification	<b>2220/64</b>	• for aeration
		<b>2220/70</b>	• in combination with
		<b>2220/702</b>	• . a steam turbine
		<b>2220/704</b>	• . a gas turbine
		<b>2220/706</b>	• . an electrical generator
		<b>2220/7062</b>	• . . of the direct current (D.C.) type
		<b>2220/7064</b>	• . . of the alternating current (A.C.) type

- 2220/70642 . . . . of the synchronous type
- 2220/70644 . . . . of the asynchronous type, i.e. induction type
- 2220/70646 . . . . . Double fed induction generators (DFIGs)
- 2220/7066 . . . via a direct connection, i.e. a gearless transmission
- 2220/7068 . . . equipped with permanent magnets
- 2220/707 . . . of the linear type
- 2220/708 . . . Photoelectric means, i.e. photovoltaic or solar cells
- 2220/709 . . . Piezoelectric means
- 2220/80 . . in supersonic vehicles excluding hypersonic vehicles or ram, scram or rocket propulsion
- 2220/90 . . in vehicles adapted for vertical or short take off and landing (v/stol vehicles), ([gas turbines providing direct vertical lift F05B 2220/308](#))

## 2230/00 Manufacture

### NOTE

Manufacture comprises also treatment, assembly or disassembly methods, repairing, handling or the like.

- 2230/10 . . by removing material
- 2230/101 . . . by electrochemical methods
- 2230/102 . . . by spark erosion methods
- 2230/103 . . . using lasers
- 2230/104 . . Micromachining
- 2230/20 . . essentially without removing material
- 2230/21 . . . by casting
- 2230/211 . . . . by precision casting, e.g. microfusing or investment casting
- 2230/22 . . . by sintering
- 2230/23 . . . by permanently joining parts together
- 2230/232 . . . . by welding
- 2230/233 . . . . . Electron beam welding
- 2230/234 . . . . . Laser welding
- 2230/235 . . . . . Tig/Mig welding
- 2230/236 . . . . . Diffusion bonding
- 2230/237 . . . . . Brazing
- 2230/238 . . . . . Soldering
- 2230/239 . . . . . Inertia or friction welding
- 2230/24 . . . by extrusion
- 2230/25 . . . by forging
- 2230/26 . . . by rolling
- 2230/30 . . with deposition of material
- 2230/31 . . . Layer deposition
- 2230/311 . . . . by torch or flame spray
- 2230/312 . . . . by plasma spray
- 2230/313 . . . . by physical vapour deposition
- 2230/314 . . . . by chemical vapour deposition
- 2230/40 . . Heat treatment
- 2230/41 . . . Hardening; Annealing
- 2230/50 . . Building or constructing in particular ways
- 2230/502 . . . using existing or "off the shelf" parts, e.g. using standardised turbocharger elements
- 2230/60 . . Assembly methods
- 2230/601 . . . using limited numbers of standard modules which can be adapted by machining
- 2230/604 . . . using positioning or alignment devices for aligning or centering, e.g. pins
- 2230/606 . . . . using maintaining alignment while permitting differential dilatation

- 2230/608 . . . . for adjusting the position or the alignment, e.g. wedges or excenters
- 2230/61 . . . using auxiliary equipment for lifting or holding ([hoisting on to a stationary structure with provisions on the structure itself F05B 2240/916](#))
- 2230/6102 . . . . carried on a floating platform
- 2230/70 . . Disassembly methods
- 2230/80 . . Repairing, retrofitting or upgrading methods
- 2230/90 . . Coating; Surface treatment ([manufacture with deposition of material F05B 2220/30](#))

## 2240/00 Components

### NOTE

Components are the basic elements of construction.

- 2240/10 . . Stators
- 2240/11 . . . Shroud seal segments
- 2240/12 . . . Fluid guiding means, e.g. vanes
- 2240/121 . . . . Baffles or ribs
- 2240/122 . . . . Vortex generators, turbulators, or the like, for mixing ([by creating turbulence F05B 2260/222](#))
- 2240/123 . . . . Nozzles
- 2240/1231 . . . . . Plug nozzles
- 2240/124 . . . . Cascades, i.e. assemblies of similar profiles acting in parallel
- 2240/13 . . . to collect or cause flow towards or away from turbines
- 2240/131 . . . . by means of vertical structures, i.e. chimneys
- 2240/132 . . . . creating a vortex or tornado effect
- 2240/133 . . . . with a convergent-divergent guiding structure, e.g. a Venturi conduit
- 2240/14 . . . Casings, housings, nacelles, gondels or the like, protecting or supporting assemblies within
- 2240/142 . . . . in the form of a standard ISO container
- 2240/20 . . Rotors
- 2240/201 . . . using the Magnus-effect
- 2240/202 . . . with adjustable area of intercepted fluid
- 2240/2021 . . . . by means of telescoping blades
- 2240/2022 . . . . by means of tethering or coning blades
- 2240/2023 . . . . by means of radially reefing blades
- 2240/21 . . . for wind turbines
- 2240/211 . . . . with vertical axis
- 2240/212 . . . . . of the Darrieus type
- 2240/213 . . . . . of the Savonius type
- 2240/214 . . . . . of the Musgrove or "H"-type
- 2240/215 . . . . . of the panemone or "vehicle ventilator" type
- 2240/216 . . . . . of the anemometer type
- 2240/217 . . . . . of the crossflow- or "Banki"- or "double action" type
- 2240/218 . . . . . with horizontally hinged vanes
- 2240/221 . . . . with horizontal axis
- 2240/2211 . . . . . of the multibladed, low speed, e.g. "American farm" type
- 2240/2212 . . . . . perpendicular to wind direction
- 2240/2213 . . . . . and with the rotor downwind from the yaw pivot axis
- 2240/231 . . . . driven by aerodynamic lift effects
- 2240/232 . . . . . driven by drag
- 2240/24 . . . for turbines
- 2240/241 . . . . of impulse type
- 2240/2411 . . . . . Pelton type

2240/242 . . . of reaction type  
 2240/243 . . . of the Archimedes screw type  
 2240/244 . . . of the cross-flow, e.g. Banki, Ossberger type  
 2240/30 . . Characteristics of rotor blades, i.e. of any element transforming dynamic fluid energy to or from rotational energy and being attached to a rotor  
 2240/301 . . . Cross-section characteristics  
 2240/302 . . . Segmented or sectional blades  
 2240/31 . . . of changeable form or shape  
 2240/311 . . . . flexible or elastic  
 2240/312 . . . . capable of being reefed  
 2240/3121 . . . . . around an axis orthogonal to rotor rotational axis  
 2240/313 . . . . with adjustable flow intercepting area  
 (F05B 2240/312 takes precedence)  
 2240/32 . . . with roughened surfaces  
 2240/33 . . Shrouds which are part of or which are rotating with the rotor  
 2240/34 . . with auxiliary or secondary rotors attached to blades of main rotor  
 2240/35 . Combustors or associated equipment  
 2240/36 . . Fuel vaporizer  
 2240/40 . Use of a multiplicity of similar components  
 2240/50 . Bearings  
 2240/51 . . magnetic  
 2240/511 . . . with permanent magnets  
 2240/515 . . . electromagnetic  
 2240/52 . . Axial thrust bearings  
 2240/53 . . Hydrodynamic or hydrostatic bearings  
 2240/54 . . Radial bearings  
 2240/57 . Seals  
 2240/571 . . Brush seals  
 2240/572 . . Leaf seals  
 2240/60 . Shafts  
 2240/61 . . hollow  
 2240/62 . . flexible  
 2240/63 . . Glands for admission or removal of fluids from shafts  
 2240/70 . Slinger plates or washers  
 2240/80 . Platforms for stationary or moving blades  
 2240/801 . . cooled platforms  
 2240/90 . Mounting on supporting structures or systems  
 2240/91 . . on a stationary structure  
 2240/911 . . . already existing for a prior purpose  
 2240/9111 . . . . which is a chimney  
 2240/9112 . . . . which is a building  
 2240/9113 . . . . which is a roadway, rail track, or the like for recovering energy from moving vehicles  
 2240/912 . . . on a tower  
 2240/9121 . . . . on a lattice tower  
 2240/913 . . . on a mast  
 2240/914 . . . on an inflatable structure  
 2240/915 . . . which is vertically adjustable  
 2240/9151 . . . . telescopically  
 2240/9152 . . . . by being hinged  
 2240/91521 . . . . . at ground level  
 2240/916 . . . with provision for hoisting onto the structure  
 2240/917 . . . attached to cables  
 2240/92 . . on an airborne structure  
 2240/921 . . . kept aloft due to aerodynamic effects  
 2240/922 . . . kept aloft due to buoyancy effects  
 2240/923 . . . which is a vehicle

2240/93 . . on a structure floating on a liquid surface  
 2240/931 . . . which is a vehicle  
 2240/932 . . . which is a catamaran-like structure  
 2240/94 . . on a movable wheeled structure  
 2240/941 . . . which is a land vehicle  
 2240/95 . . offshore  
 2240/96 . . as part of a wind farm  
 2240/97 . . on a submerged structure  
 2240/98 . . which is inflatable  
 2240/99 . characterised by colour or colour patterns

## 2250/00 Geometry

### NOTE

Geometry indicates the shape or form of a component or the configuration or arrangement of components in a machine or in a plant.

2250/02 . variable  
 2250/10 . two-dimensional  
 2250/11 . . triangular  
 2250/12 . . rectangular  
 2250/121 . . . square  
 2250/13 . . trapezoidal  
 2250/131 . . . polygonal  
 2250/132 . . . hexagonal  
 2250/14 . . elliptical  
 2250/141 . . . circular  
 2250/15 . . spiral  
 2250/16 . . parabolic  
 2250/17 . . hyperbolic  
 2250/18 . . patterned  
 2250/181 . . . ridged  
 2250/182 . . . crenellated, notched  
 2250/183 . . . zigzag  
 2250/184 . . . sinusoidal  
 2250/19 . . machined; miscellaneous  
 2250/191 . . . perforated  
 2250/192 . . . beveled  
 2250/193 . . . milled  
 2250/20 . three-dimensional  
 2250/21 . . pyramidal  
 2250/22 . . parallelepipedic  
 2250/221 . . . cubic  
 2250/23 . . prismatic  
 2250/231 . . . cylindrical  
 2250/232 . . . conical  
 2250/24 . . ellipsoidal  
 2250/241 . . . spherical  
 2250/25 . . helical  
 2250/26 . . paraboloidal  
 2250/27 . . hyperboloidal  
 2250/28 . . patterned  
 2250/281 . . . threaded  
 2250/282 . . . Cubic pattern  
 2250/283 . . . Honeycomb  
 2250/29 . . machined; miscellaneous  
 2250/291 . . . hollowed  
 2250/292 . . . tapered  
 2250/293 . . . lathed, e.g. rotation symmetrical  
 2250/30 . Arrangement of components  
 2250/31 . . according to the direction of their main axis or their axis of rotation

- 2250/311 . . . the axes being in line
- 2250/312 . . . the axes being parallel to each other
- 2250/313 . . . the axes being perpendicular to each other
- 2250/314 . . . the axes being inclined in relation to each other
- 2250/315 . . . the main axis being substantially vertical
- 2250/32 . . according to their shape
- 2250/321 . . . asymptotic
- 2250/322 . . . tangential
- 2250/323 . . . convergent
- 2250/324 . . . divergent
- 2250/33 . . symmetrical
- 2250/34 . . translated
- 2250/35 . . rotated
- 2250/36 . . in inner-outer relationship, e.g. shaft-bearing arrangements
- 2250/40 . Movement of component
- 2250/41 . . with one degree of freedom
- 2250/411 . . . in rotation
- 2250/42 . . with two degrees of freedom
- 2250/43 . . with three degrees of freedom
- 2250/50 . Inlet or outlet
- 2250/501 . . Inlet
- 2250/5011 . . . augmenting, i.e. with intercepting fluid flow cross sectional area greater than the rest of the machine behind the inlet
- 2250/5012 . . . concentrating only, i.e. with intercepting fluid flow cross sectional area not greater than the rest of the machine behind the inlet
- 2250/502 . . Outlet
- 2250/503 . . of regenerative pumps
- 2250/60 . Structure; Surface texture
- 2250/61 . . corrugated
- 2250/611 . . . undulated
- 2250/62 . . smooth
- 2250/621 . . . polished
- 2250/70 . Shape
- 2250/71 . . curved
- 2250/711 . . . convex
- 2250/712 . . . concave
- 2250/713 . . . inflexed
- 2250/72 . . symmetric
- 2250/73 . . asymmetric
- 2250/80 . Size or power range of the machines
- 2250/82 . . Micromachines
- 2250/84 . . Nanomachines ([Nanotechnology for interacting, sensing or actuating B82Y 15/00](#))
- 2250/86 . . Megamachines
- 2260/00 Function**
- 2260/02 . Transport, e.g. specific adaptations or devices for conveyance ([transport of wind turbines or equipments therefore F03D 1/005](#))
- 2260/10 . Particular cycles
- 2260/20 . Heat transfer, e.g. cooling
- 2260/201 . . by impingement of a fluid
- 2260/202 . . by film cooling
- 2260/203 . . by transpiration cooling
- 2260/205 . . Cooling fluid recirculation, i.e. after having cooled one or more components the cooling fluid is recovered and used elsewhere for other purposes
- 2260/207 . . using a phase changing mass, (e.g. heat absorbing by melting or boiling)
- 2260/208 . . using heat pipes
- 2260/209 . . using vortex tubes
- 2260/211 . . by intercooling, e.g. during a compression cycle
- 2260/212 . . . by water injection
- 2260/221 . . Improvement of heat transfer
- 2260/222 . . . by creating turbulence ([vortex generators, turbulators or the like for mixing F05B 2240/122](#))
- 2260/224 . . . by increasing the heat transfer surface
- 2260/2241 . . . . using fins or ribs
- 2260/231 . . Preventing heat transfer
- 2260/232 . . characterised by the cooling medium
- 2260/233 . . . the medium being steam
- 2260/24 . . for draft enhancement in chimneys, using solar or other heat sources
- 2260/30 . Retaining components in desired mutual position
- 2260/301 . . Retaining bolts or nuts
- 2260/3011 . . . of the frangible or shear type
- 2260/302 . . by means of magnetic or electromagnetic forces
- 2260/303 . . with a bayonet coupling
- 2260/304 . . Balancing of radial or axial forces on regenerative rotors
- 2260/305 . . Reducing friction between regenerative impeller discs and casing walls
- 2260/40 . Transmission of power
- 2260/402 . . through friction drives
- 2260/4021 . . . through belt drives
- 2260/4022 . . . through endless chains
- 2260/4023 . . . through a friction clutch
- 2260/403 . . through the shape of the drive components
- 2260/4031 . . . as in toothed gearing
- 2260/40311 . . . . of the epicyclic, planetary or differential type
- 2260/404 . . through magnetic drive coupling
- 2260/4041 . . . the driven magnets encircling the driver magnets
- 2260/406 . . through hydraulic systems
- 2260/407 . . through piezoelectric conversion
- 2260/408 . . through magnetohydrodynamic conversion
- 2260/42 . Storage of energy
- 2260/421 . . in the form of rotational kinetic energy, e.g. in flywheels
- 2260/50 . Kinematic linkage, i.e. transmission of position
- 2260/502 . . involving springs
- 2260/503 . . using gears
- 2260/5032 . . . of the bevel or angled type
- 2260/504 . . using flat or V-belts and pulleys
- 2260/505 . . using chains and sprockets; using toothed belts
- 2260/506 . . using cams or eccentrics
- 2260/507 . . using servos, independent actuators, etc.
- 2260/60 . Fluid transfer
- 2260/601 . . using an ejector or a jet pump
- 2260/602 . . Drainage
- 2260/603 . . . of leakage having past a seal ([seals F05B 2240/57](#); [glands F05B 2240/63](#))
- 2260/604 . . Vortex non-clogging type pumps
- 2260/63 . . Preventing clogging or obstruction of flow paths by dirt, dust, or foreign particles
- 2260/64 . . Aeration, ventilation, dehumidification or moisture removal of closed spaces
- 2260/70 . Adjusting of angle of incidence or attack of rotating blades
- 2260/71 . . as a function of flow velocity

- 2260/72 . . by turning around an axis parallel to the rotor centre line
- 2260/74 . . by turning around an axis perpendicular the rotor centre line
- 2260/75 . . the adjusting mechanism not using auxiliary power sources ("servos")
- 2260/76 . . the adjusting mechanism using auxiliary power sources
- 2260/77 . . the adjusting mechanism driven or triggered by centrifugal forces
- 2260/78 . . the adjusting mechanism driven or triggered by aerodynamic forces
- 2260/79 . . Bearing, support or actuation arrangements therefor
- 2260/80 . Diagnostics
- 2260/82 . Forecasts
- 2260/821 . . Parameter estimation or prediction
- 2260/8211 . . . of the weather
- 2260/83 . Testing, e.g. methods, components or tools therefor
- 2260/84 . Modeling or simulation
- 2260/845 . Redundancy
- 2260/85 . Starting
- 2260/90 . Braking
- 2260/901 . . using aerodynamic forces, i.e. lift or drag
- 2260/9011 . . . of the tips of rotor blades
- 2260/902 . . using frictional mechanical forces
- 2260/903 . . using electrical or magnetic forces
- 2260/904 . . using hydrodynamic forces
- 2260/95 . Preventing corrosion ([coating or surface treatment F05B 2230/90](#))
- 2260/96 . Preventing, counteracting or reducing vibration or noise
- 2260/962 . . my means creating "anti-noise"
- 2260/964 . . by damping means
- 2260/966 . . by correcting static or dynamic imbalance
- 2260/97 . Reducing windage losses
- 2260/972 . . in radial flow machines
- 2260/98 . Lubrication
- 2260/99 . Radar absorption
- 2270/00 Control**
- 2270/10 . Purpose of the control system
- 2270/101 . . to control rotational speed (n)
- 2270/1011 . . . to prevent overspeed
- 2270/1012 . . . to prevent underspeed
- 2270/1013 . . . of different spools or shafts
- 2270/1014 . . . to keep rotational speed constant
- 2270/1016 . . in variable speed operation
- 2270/102 . . to control acceleration (u)
- 2270/1021 . . . by keeping it below damagingly high values
- 2270/1022 . . . by making it as high as possible
- 2270/103 . . to affect the output of the engine
- 2270/1031 . . . Thrust
- 2270/1032 . . . Torque
- 2270/1033 . . . Power (if explicitly mentioned)
- 2270/104 . . to match engine to driven device
- 2270/1041 . . . in particular the electrical frequency of driven generator
- 2270/105 . . to improve fuel economy
- 2270/1051 . . . in particular at idling speed
- 2270/106 . . to produce clean exhaust gases
- 2270/1061 . . . with as little smoke as possible
- 2270/1062 . . . with as little NOx's as possible
- 2270/1063 . . . by monitoring combustion conditions
- 2270/1064 . . . . indirectly, at the exhaust
- 2270/107 . . to cope with emergencies
- 2270/1071 . . . in particular sudden load loss
- 2270/10711 . . . . applying a low voltage ride through method
- 2270/1072 . . . in particular blow-out and relight
- 2270/1073 . . . of one engine in a multi-engine system
- 2270/1074 . . . by using back-up controls
- 2270/1075 . . . by temporary overriding set control limits
- 2270/1076 . . . caused by water or hail ingestion
- 2270/108 . . to cope with, or avoid, compressor flow instabilities
- 2270/1081 . . . Compressor surge or stall
- 2270/10812 . . . . caused by working fluid flow velocity profile distortion
- 2270/10815 . . . . . due to high angle of attack of aircraft
- 2270/10817 . . . . . due to compressor degradation
- 2270/109 . . to prolong engine life
- 2270/1091 . . . by limiting temperatures
- 2270/1095 . . . by limiting mechanical stresses
- 2270/1097 . . . by preventing reverse rotation
- 2270/11 . . to maintain desired vehicle trajectory parameters
- 2270/1101 . . . Altitude
- 2270/1102 . . . Speed or Mach number
- 2270/111 . . to control two or more engines simultaneously
- 2270/15 . . to control thermoacoustic behaviour in the combustion chambers ([counteracting noise or vibration F05B 2260/96](#))
- 2270/16 . . to control water or steam injection
- 2270/17 . . to avoid excessive deflection of the blades
- 2270/18 . . to control buoyancy
- 2270/19 . . to avoid stroboscopic flicker shadow on surroundings
- 2270/20 . . to optimise the performance of a machine
- 2270/30 . Control parameters, e.g. input parameters
- 2270/301 . . Pressure
- 2270/3011 . . . Inlet
- 2270/3013 . . . Outlet
- 2270/3015 . . . differential
- 2270/303 . . Temperature
- 2270/3032 . . . excessive temperatures, e.g. caused by overheating
- 2270/304 . . Spool rotational speed
- 2270/305 . . Tolerances
- 2270/309 . . Rate of change of parameters
- 2270/31 . . Fuel schedule for stage combustors
- 2270/32 . . Wind speeds
- 2270/3201 . . . "cut-off" or "shut-down" wind speed
- 2270/321 . . Wind directions
- 2270/322 . . the detection or prediction of a wind gust
- 2270/323 . . Air humidity
- 2270/324 . . Air pressure
- 2270/325 . . Air temperature
- 2270/326 . . Rotor angle
- 2270/327 . . Rotor or generator speeds
- 2270/328 . . Blade pitch angle
- 2270/329 . . Azimuth or yaw angle
- 2270/33 . . Proximity of blade to tower
- 2270/331 . . Mechanical loads
- 2270/332 . . Maximum loads or fatigue criteria
- 2270/333 . . Noise or sound levels
- 2270/334 . . Vibration measurements



2270/335	. . Output power or torque	2280/10307	. . . Manganese
2270/336	. . Blade lift measurements	2280/10308	. . . Lead
2270/337	. . Electrical grid status parameters, e.g. voltage, frequency or power demand	2280/10309	. . . Tin
2270/40	. Type of control system	2280/1031	. . . Zinc
2270/402	. . passive or reactive, e.g. using large wind vanes	2280/10311	. . . Mercury
2270/404	. . active, predictive, or anticipative	2280/104	. . Noble metals
2270/50	. Control logic embodiment by	2280/1041	. . . Silver
2270/502	. . electrical means, e.g. relays or switches	2280/1042	. . . Gold
2270/504	. . electronic means, e.g. electronic tubes, transistors or IC's within an electronic circuit	2280/1043	. . . Platinum group, e.g. Pt, Ir
2270/506	. . hydraulic means, e.g. hydraulic valves within a hydraulic circuit	2280/1044	. . . Palladium
2270/508	. . mechanical means, e.g. levers, gears or cams	2280/1045	. . . Ruthenium
2270/60	. Control system actuates through	2280/1046	. . . Osmium
2270/602	. . electrical actuators	2280/1047	. . . Iridium
2270/604	. . hydraulic actuators	2280/1048	. . . Rhodium
2270/605	. . Pneumatic actuators	2280/105	. . Copper
2270/606	. . mechanical actuators ( <a href="#">F05B 2270/602 takes precedence</a> )	2280/106	. . Rare earth metals, e.g. Sc, Y
2270/70	. Type of control algorithm	2280/107	. . Alloys
2270/701	. . proportional	2280/1071	. . . Steel alloys
2270/702	. . differential	2280/1072	. . Copper alloys
2270/703	. . integral	2280/10721	. . . Bronze
2270/704	. . proportional-differential	2280/10722	. . . Phosphor-bronze alloy
2270/705	. . proportional-integral	2280/10723	. . . Nickel-Copper alloy, e.g. monel
2270/706	. . proportional-integral-differential	2280/1073	. . Aluminium alloy, e.g. AlCuMgPb
2270/707	. . fuzzy logic	2280/1074	. . Alloys not otherwise provided for
2270/708	. . with comparison tables	2280/10741	. . . Superalloys
2270/709	. . with neural networks	2280/10742	. . . Heat stable alloys
2270/80	. Devices generating input signals, e.g. transducers, sensors, cameras or strain gauges	2280/10743	. . . Ni - Si alloys
2270/802	. . Calibration thereof	2280/10744	. . . Metal-aluminide intermetallic compounds
2270/803	. . Sampling thereof	2280/20	. Inorganic materials, e.g. non-metallic materials
2270/804	. . Optical devices	2280/2001	. . Glass
2270/8041	. . . Cameras	2280/20011	. . . MIBA
2270/8042	. . . Lidar systems	2280/20012	. . . Quartz
2270/805	. . Radars	2280/2002	. . Phosphor
2270/806	. . Sonars	2280/2003	. . Silicon
2270/807	. . Accelerometers	2280/2004	. . Ceramics; Oxides
2270/808	. . Strain gauges; Load cells	2280/20041	. . . Aluminium oxides
2270/809	. . Encoders	2280/20042	. . . Zinc oxides
2270/81	. . Microphones	2280/20043	. . . Zirconium oxides
2270/821	. . Displacement measuring means, e.g. inductive	2280/2005	. . Non-oxide ceramics
<b>2280/00</b>	<b>Materials; Properties thereof</b>	2280/2006	. . Carbon, e.g. graphite
2280/10	. Inorganic materials, e.g. metals	2280/2007	. . Carbides
2280/101	. . Iron	2280/20071	. . . of silicon
2280/1011	. . Cast iron	2280/20072	. . . of titanium, e.g. TiB
2280/102	. . Light metals	2280/20073	. . . of wolfram, e.g. tungsten carbide
2280/1021	. . . Aluminium	2280/2008	. . Nitrides
2280/1022	. . . Beryllium	2280/20081	. . . of aluminium
2280/1023	. . . Boron	2280/20082	. . . of boron
2280/1024	. . . Lithium	2280/20083	. . . of silicon
2280/1025	. . . Magnesium	2280/20084	. . . of titanium
2280/103	. . Heavy metals	2280/20085	. . . of zirconium
2280/10301	. . . Refractory metals, e.g. V, W	2280/2009	. . Sulfides
2280/10302	. . . Chromium	2280/20091	. . . of molybdenum
2280/10303	. . . Molybdenum	2280/201	. . Sapphire
2280/10304	. . . Titanium	2280/2011	. . Aluminium titanate
2280/10305	. . . Zirconium	2280/2013	. . Silica
2280/10306	. . . Hafnium	2280/2014	. . Arsenic
		2280/2015	. . Antimony
		2280/2016	. . Bismuth
		2280/2017	. . Barium
		2280/30	. Inorganic materials not otherwise provided for
		2280/40	. Organic materials

- 2280/4001 . . Leather
- 2280/4002 . . Cellulosic materials, e.g. wood
- 2280/4003 . . Synthetic polymers, e.g. plastics; Rubber
- 2280/4004 . . Rubber
- 2280/4005 . . PTFE [PolyTetraFluorEthylene]
- 2280/4006 . . Polyamides, e.g. NYLON
- 2280/4007 . . Thermoplastics
- 2280/4008 . . Polyamides, e.g. Aurum
- 2280/4009 . . Polyetherketones, e.g. PEEK
- 2280/401 . . Silicon polymers
- 2280/4011 . . Organic materials not otherwise provided for
- 2280/50 . . Intrinsic material properties or characteristics
- 2280/5001 . . Elasticity
- 2280/5002 . . Thermal properties
- 2280/5003 . . Expansivity
- 2280/50031 . . . similar
- 2280/50032 . . . dissimilar
- 2280/5004 . . Heat transfer
- 2280/5005 . . Reflective properties
- 2280/5006 . . Shape memory
- 2280/5007 . . Hardness
- 2280/5008 . . Magnetic properties
- 2280/5009 . . non-magnetic
- 2280/501 . . Self lubricating materials; Solid lubricants
- 2280/5011 . . Surface roughness
- 2280/60 . . Properties or characteristics given to material by treatment or manufacturing
- 2280/6001 . . Fabrics
- 2280/6002 . . . Woven fabrics
- 2280/6003 . . Composites; e.g. fibre-reinforced
- 2280/6004 . . amorphous
- 2280/6005 . . crystalline
- 2280/6006 . . Directionally-solidified crystalline structures
- 2280/6007 . . monocrystalline
- 2280/6008 . . Structures
- 2280/6009 . . Grain size
- 2280/601 . . Syntactic
- 2280/6011 . . Coating
- 2280/6012 . . Foam
- 2280/6013 . . Fibres
- 2280/6014 . . Filler
- 2280/6015 . . Resin
- 2280/70 . . Treatments or modification of materials
- 2280/701 . . Heat treatments
- 2280/702 . . Reinforcements