

CPC COOPERATIVE PATENT CLASSIFICATION

H04S STEREOPHONIC SYSTEMS (information storage on discs or tapes [G11B](#); broadcast systems for the distribution of stereophonic information [H04H 20/88](#); multiplex systems in general [H04J](#))

NOTE

In this subclass, the following term is used with the meaning indicated:

- "stereophonic systems" covers quadrasonic or similar systems

1/00	Two-channel systems (H04S 5/00 , H04S 7/00 take precedence)	7/302	. . {Electronic adaptation of stereophonic sound system to listener position or orientation (H04S 7/301 takes precedence)}
1/002	. {Non-adaptive circuits, e.g. manually adjustable or static, for enhancing the sound image or the spatial distribution (control circuits for electronic adaptation of the sound field H04S 7/30)}	7/303	. . . {Tracking of listener position or orientation}
1/005	. . {For headphones}	7/304 {For headphones}
1/007	. {in which the audio signals are in digital form (data reduction aspects thereof based on psychoacoustics G10L 19/02)}	7/305	. . {Electronic adaptation of stereophonic audio signals to reverberation of the listening space (H04S 7/301 takes precedence; arrangements for producing a reverberation or echo sound G10K 15/08 ; for public address systems H04R 27/00 , H04R 29/00)}
3/00	Systems employing more than two channels, e.g. quadrasonic (H04S 5/00 , H04S 7/00 take precedence)	7/306	. . . {For headphones}
3/002	. {Non-adaptive circuits, e.g. manually adjustable or static, for enhancing the sound image or the spatial distribution (control circuits for electronic adaptation of the sound field H04S 7/30)}	7/307	. . {Frequency adjustment, e.g. tone control (H04S 7/301 takes precedence; circuits for correcting the frequency response of transducers H04R 3/04 ; tone control circuits in amplifiers see H03G 5/00)}
3/004	. . {For headphones}	7/308	. . {Electronic adaptation dependent on speaker or headphone connection}
3/006	. {in which a plurality of audio signals are transformed in a combination of audio signals and modulated signals, e.g. CD-4 systems (for broadcasting H04H 20/88 , H04B 1/1646)}	7/40	. {Visual indication of stereophonic sound image (visual indication of individual signal levels H04R 29/008)}
3/008	. {in which the audio signals are in digital form, i.e. employing more than two discrete digital channels, e.g. Dolby Digital, Digital Theatre Systems [DTS] (data reduction aspects thereof based on psychoacoustics G10L 19/02)}	2400/00	Details of stereophonic systems covered by H04S but not provided for in its groups (not used, see subgroups)
3/02	. of the matrix type, i.e. in which input signals are combined algebraically, e.g. after having been phase shifted with respect to each other	2400/01	. Multi-channel, i.e. more than two input channels, sound reproduction with two speakers wherein the multi-channel information is substantially preserved
5/00	Pseudo-stereo systems, e.g. in which additional channel signals are derived from monophonic signals by means of phase shifting, time delay or reverberation (arrangements for producing a reverberation or echo sound G10K 15/08)	2400/03	. Aspects of down-mixing multi-channel audio to configurations with lower numbers of playback channels, e.g. 7.1 -> 5.1 (H04S 2400/01 takes precedence)
5/005	. {of the pseudo five- or more-channel type, e.g. virtual surround}	2400/05	. Generation or adaptation of centre channel in multi-channel audio systems
5/02	. of the pseudo four-channel type, e.g. in which rear channel signals are derived from two-channel stereo signals	2400/07	. Generation or adaptation of the Low Frequency Effect [LFE] channel, e.g. distribution or signal processing
7/00	Indicating arrangements; Control arrangements, e.g. balance control	2400/09	. Electronic reduction of distortion of stereophonic sound systems
7/30	. {Control circuits for electronic adaptation of the sound field (non-adaptive circuits, i.e. manually adjustable or static, for enhancing the sound image or the spatial distribution H04S 1/002 , H04S 3/002)}	2400/11	. Positioning of individual sound objects, e.g. moving airplane, within a sound field (H04S 2420/13 takes precedence)
7/301	. . {Automatic calibration of stereophonic sound system, e.g. with test microphone}	2400/13	. Aspects of volume control, not necessarily automatic, in stereophonic sound systems
		2400/15	. Aspects of sound capture and related signal processing for recording or reproduction
		2420/00	Techniques used stereophonic systems covered by H04S but not provided for in its groups (not used, see subgroups)

- 2420/01 . Enhancing the perception of the sound image or of the spatial distribution using head related transfer functions [HRTF's] or equivalents thereof, e.g. interaural time difference [ITD] or interaural level difference [ILD]
- 2420/03 . Application of parametric coding in stereophonic audio systems
- 2420/05 . Application of the precedence or Haas effect, i.e. the effect of first wavefront, in order to improve sound-source localisation
- 2420/07 . Synergistic effects of band splitting and sub-band processing
- 2420/11 . Application of ambisonics in stereophonic audio systems
- 2420/13 . Application of wave-field synthesis in stereophonic audio systems