

# CPC COOPERATIVE PATENT CLASSIFICATION

## B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

### SHAPING

**B29 WORKING OF PLASTICS; WORKING OF SUBSTANCES IN A PLASTIC STATE, IN GENERAL** (processing doughs [A21C](#); working chocolate [A23G](#); casting of metals [B22](#); working cement, clay [B28](#); chemical aspects, see section [C](#), particularly [C08](#); working glass [C03B](#); candle making [C11C 5/02](#); making soap [C11D 13/00](#); manufacture of artificial filaments, threads, fibres, bristles or ribbons [D01D](#), [D01F](#); manufacture of articles from cellulosic fibrous suspensions or from papier-mâché [D21J](#))

(NOTES omitted)

**B29C SHAPING OR JOINING OF PLASTICS; SHAPING OF MATERIAL IN A PLASTIC STATE, NOT OTHERWISE PROVIDED FOR; AFTER-TREATMENT OF THE SHAPED PRODUCTS, e.g. REPAIRING** (making preforms [B29B 11/00](#); making laminated products by combining previously unconnected layers which become one product whose layers will remain together [B32B 37/00](#) - [B32B 41/00](#))

#### NOTES

1. This subclass covers:
  - shaping or joining of plastics;
  - shaping of material in a plastic state when a specific material is not identified;
  - shaping of material in a plastic state, not otherwise provided for.
2. This subclass does not cover:
  - working of plastics sheet material in a manner analogous to the working of paper, which is covered by class [B31](#);
  - shaping of materials provided for elsewhere, e.g. of metal, clay or foodstuffs.
3. Attention is drawn to Note (3) following the title of class [B29](#).
4. In this subclass:
  - repairing of articles made from plastics or materials in a plastic state, e.g. of articles shaped or produced by using techniques covered by this subclass or subclass [B29D](#), is classified in group [B29C 73/00](#);
  - component parts, details, accessories or auxiliary operations which are applicable to more than one moulding technique are classified in groups [B29C 31/00](#) - [B29C 37/00](#);
  - component parts, details, accessories or auxiliary operations which are only applicable or only of use for one specific shaping technique are classified only in the relevant subgroups of groups [B29C 39/00](#)-[B29C 71/00](#).
5. In this subclass, it is desirable to add the indexing codes of subclasses [B29K](#) and [B29L](#).

#### Component parts, details or accessories; Auxiliary operations

#### NOTE

{ Attention is drawn to Note (4) following the subclass title. }

- 31/00 Handling, e.g. feeding of the material to be shaped, {storage of plastics material before moulding; Automation, i.e. automated handling lines in plastics processing plants, e.g. using manipulators or robots (discharging moulded articles from the mould [B29C 37/0003](#); storage of preregs or SMC after impregnation or during ageing [B29C 70/54](#); baling of rubber [B29B 15/02](#); in general [B65G](#))}**
- 31/002 • {Handling tubes, e.g. transferring between shaping stations, loading on mandrels}
- 31/004 • {Arrangements for converting the motion of a material which is continuously fed to a working station in a stepwise motion}

- 31/006 • {Handling moulds, e.g. between a mould store and a moulding machine (movable moulds [B29C 33/34](#); for injection moulding [B29C 45/1756](#))}
- 31/008 • {Handling preformed parts, e.g. inserts ([B29C 37/001](#) takes precedence; for injection moulding [B29C 45/14008](#); for blow moulding [B29C 49/2408](#); for thermoforming [B29C 51/165](#))}
- 31/02 • Dispensing from vessels, e.g. hoppers {(into a mould cavity [B29C 31/04](#); large containers characterised by discharge means [B65D 88/28](#), [B65D 88/54](#))}
- 31/04 • Feeding {of the material to be moulded}, e.g. into a mould cavity ({[B29C 39/08](#) takes precedence; using a material distribution system to two or more fixed injection moulds [B29C 45/125](#) } ; to presses in general [B30B 15/30](#))
- 31/041 • {using filling or dispensing heads placed in closed moulds or in contact with mould walls ([B29C 45/27](#) takes precedence)}

31/042	. . {using dispensing heads, e.g. extruders, placed over or apart from the moulds ( <a href="#">positioning extruded preforms on conveyors B29C 31/085</a> )}	33/0033	. {constructed for making articles provided with holes}
31/044	. . . {with moving heads for distributing liquid or viscous material into the moulds}		<b>NOTE</b>
31/045	. . . . {moving along predetermined circuits or distributing the material according to predetermined patterns}		If the hole is made by cutting means associated with the mould, see the relevant moulding technique
31/047	. . . {combined with moving moulds ( <a href="#">B29C 31/044</a> , <a href="#">B29C 31/048</a> take precedence)}	33/0038	. {with sealing means or the like ( <a href="#">seals on envelopes used in tyre retreading B29D 30/542</a> ; for injection moulding footwear <a href="#">B29D 35/0045</a> )}
31/048	. . . {the material being severed at the dispensing head exit, e.g. as ring, drop or gob, and transported immediately into the mould, e.g. by gravity}	33/0044	. . {for sealing off parts of inserts projecting into the mould cavity}
31/06	. . in measured doses, {e.g. by weighting ( <a href="#">feeding mixers with measured doses B01F 15/0216</a> , <a href="#">B01F 15/0454</a> , <a href="#">B29B 7/24</a> , <a href="#">B29B 7/603</a> ; in general <a href="#">G01F</a> )}	33/005	. {characterised by the location of the parting line of the mould parts}
31/061	. . . {using stationary volumetric measuring chambers}	33/0055	. {with incorporated overflow cavities ( <a href="#">in particular in injection moulds B29C 45/2669</a> )}
31/063	. . . . {of the piston type}	33/0061	. {characterised by the configuration of the material feeding channel ( <a href="#">sprue channels for injection moulding B29C 45/27</a> )}
31/065	. . . {using volumetric measuring chambers moving between a charging station and a discharge station}	33/0066	. . {with a subdivided channel for feeding the material to a plurality of locations}
31/066	. . . . {using feed frames, e.g. for dry material}	33/0072	. . {with a configuration promoting turbulence, e.g. for after-mixing in the mould}
31/068	. . . . {of the piston type}	33/0077	. {characterised by the configuration of the mould filling gate ( <a href="#">mixing chambers situated in the mould opening B29B 7/7471</a> ); accessories for connecting the mould filling gate with the filling spout}
31/08	. . of preforms {to be moulded, e.g. tablets, fibre reinforced preforms, extruded ribbons, tubes or profiles; Manipulating means specially adapted for feeding preforms, e.g. supports conveyors ( <a href="#">B29C 31/066</a> , <a href="#">B29C 37/001</a> , <a href="#">B29C 43/085</a> take precedence)}	33/0083	. {Electrical or fluid connection systems therefor}
	<b>NOTE</b>	33/0088	. {Multi-face stack moulds}
	Documents describing feeding preforms, e.g. parisons, tubes, sheets in connection with shaping techniques described in groups <a href="#">B29C 49/00</a> - <a href="#">B29C 65/00</a> are not classified in group <a href="#">B29C 31/08</a> , but in the relevant groups of these techniques	2033/0094	. {Means for masking a part of the moulding surface}
		33/02	. with incorporated heating or cooling means
		2033/023	. . {Thermal insulation of moulds or mould parts}
		33/026	. . {in rolls, calenders or drums}
		33/04	. . using liquids, gas or steam ({ <a href="#">tyre moulds with incorporated heating or cooling means using liquids, gas or steam B29D 30/0601</a> })
		2033/042	. . . {Meander or zig-zag shaped cooling channels, i.e. continuous cooling channels whereby a plurality of cooling channel sections are oriented in a substantial parallel direction}
31/085	. . . {combined with positioning the preforms according to predetermined patterns, e.g. positioning extruded preforms on conveyors ( <a href="#">B29C 70/30</a> takes precedence; for building tyres <a href="#">B29D 30/08</a> )}	33/044	. . . {in rolls calenders or drums}
31/10	. . of several materials	33/046	. . . {using gas}
	<b>33/00 Moulds or cores; Details thereof or accessories therefor</b>	33/048	. . . {using steam}
2033/0005	. {with transparent parts, e.g. permitting visual inspection of the interior of the cavity}	33/06	. . using radiation {, e.g. electro-magnetic waves, induction heating}
33/0011	. {thin-walled moulds}	33/065	. . . {in rolls, calenders or drums}
33/0016	. . {Lost moulds, e.g. staying on the moulded object (flexible bags without particular shape filled with expandable material <a href="#">B29C 44/182</a> ; single use mandrels for winding and forming <a href="#">B29C 53/822</a> )}	33/08	. . for dielectric heating
33/0022	. {Multi-cavity moulds ( <a href="#">B29C 33/301</a> takes precedence)}	33/085	. . . {using rolls, calenders or drums}
33/0027	. . {with deep narrow cavities, e.g. for making piles (non-woven pile fabrics <a href="#">D04H 11/00</a> )}	33/10	. with incorporated venting means
		33/12	. with incorporated means for positioning inserts, e.g. labels ({ <a href="#">positioning reinforcements B29C 70/541</a> })
		33/123	. . {for centering the inserts}
		33/126	. . . {using centering means forming part of the insert}
		33/14	. . against the mould wall
		33/16	. . . using magnetic means
		33/18	. . . using vacuum
		33/20	. Opening, closing or clamping
		33/202	. . {Clamping means operating on closed or nearly closed mould parts, the clamping means being independently movable of the opening or closing means ( <a href="#">clamping devices for injection moulding machines B29C 45/64</a> )}

- 2033/205 . . . {mould clamping by membranes, e.g. inflatable membranes or cushions}
- 2033/207 . . . {mould clamping by pivoting members}
- 33/22 . . by rectilinear movement
- 33/24 . . . using hydraulic or pneumatic means
- 33/26 . . by pivotal movement
- 33/28 . . . using hydraulic or pneumatic means
- 33/30 . Mounting, exchanging or centering {(moulds, mould parts or cores; [B29C 33/485](#) takes precedence)}
- 33/301 . . {Modular mould systems [MMS], i.e. moulds built up by stacking mould elements, e.g. plates, blocks, rods ([B29C 33/0088](#) takes precedence)}
- 33/302 . . . {Assembling a large number of mould elements to constitute one cavity}
- 33/303 . . {centering mould parts or halves, e.g. during mounting}
- 33/304 . . . {centering cores}
- 33/305 . . {Mounting of moulds or mould support plates (handling of moulds [B29C 31/006](#); mounting of moulds for injection moulding [B29C 45/1742](#))}
- 33/306 . . {Exchangeable mould parts, e.g. cassette moulds, mould inserts (moulds with exchangeable mould parts for injection moulding [B29C 45/2673](#); mounting of exchangeable mould inserts for injection moulding [B29C 45/2675](#))}
- 33/307 . . {Mould plates mounted on frames; Mounting the mould plates; Frame constructions therefor (shaping plates for making moulds [B29C 33/3842](#); thin walled moulds [B29C 33/0011](#))}
- 33/308 . . {Adjustable moulds (for injection moulding [B29C 45/376](#))}
- 33/32 . . using magnetic means
- 33/34 . movable, e.g. to or from the moulding station
- 33/36 . . continuously movable {in one direction, e.g. in a closed circuit ([B29C 49/0021](#) takes precedence)}
- 33/38 . characterised by the material or the manufacturing process ([B29C 33/44](#) takes precedence; manufacture of moulds or parts thereof from metal [B22](#), [B23](#))
- 33/3807 . . {Resin-bonded materials, e.g. inorganic particles}
- 33/3814 . . {Porous moulds (adapted for vacuum forming [B29C 51/365](#))}
- 33/3821 . . {composed of particles enclosed in a bag}
- 33/3828 . . {Moulds made of at least two different materials having different thermal conductivities}
- 33/3835 . . {Designing moulds, e.g. using CAD-CAM}
- 33/3842 . . {Manufacturing moulds, e.g. shaping the mould surface by machining}
- 2033/385 . . . {by laminating a plurality of layers (moulds built up by stacking mould elements, e.g. plates, blocks, rods, in general [B29C 33/301](#), tyre moulds made of a plurality of laminations [B29D 2030/0609](#))}
- 33/3857 . . . {by making impressions of one or more parts of models, e.g. shaped articles and including possible subsequent assembly of the parts}
- 2033/3864 . . . . {Spraying at least one layer to create the mould}
- 2033/3871 . . . . {the models being organic material, e.g. living or dead bodies or parts thereof}
- 33/3878 . . . . {used as masters for making successive impressions}
- 33/3885 . . . . . {the mould parts being co-operating impressions}
- 33/3892 . . . . {Preparation of the model, e.g. by assembling parts}
- 33/40 . . Plastics, e.g. foam, rubber
- 33/405 . . . {Elastomers, e.g. rubber ([B29C 33/50](#) takes precedence)}
- 33/42 . characterised by the shape of the moulding surface, e.g. ribs, grooves
- 2033/422 . . {Moulding surfaces provided with a shape to promote flow of material in the mould cavity}
- 33/424 . . {Moulding surfaces provided with means for marking or patterning (for injection moulding [B29C 45/372](#))}
- 2033/426 . . . {Stampers}
- 33/428 . . . {For altering indicia, e.g. data, numbers (for injection moulding [B29C 45/374](#))}
- 33/44 . with means for, or specially constructed to facilitate, the removal of articles, e.g. of undercut articles
- 33/442 . . {with mechanical ejector or drive means therefor}
- 33/444 . . . {for stripping articles from a mould core, e.g. using stripper plates}
- 33/446 . . . . {and using a rotating movement to unscrew articles (in particular in injection moulds [B29C 45/262](#))}
- 33/448 . . {destructible ([B29C 33/52](#) takes precedence; in particular used in injection moulding [B29C 45/4457](#))}
- 33/46 . . using fluid pressure
- 33/48 . . with means for collapsing or disassembling
- 33/485 . . . {cores or mandrels (collapsible mandrels for shaping tube ends [B29C 57/02](#); collapsible mandrels for winding and joining [B29C 53/824](#))}
- 33/50 . . . elastic {or flexible (for isostatic pressing [B29C 43/3642](#))}
- 33/505 . . . . {cores or mandrels, e.g. inflatable ([B29C 33/0016](#) takes precedence; for winding and joining [B29C 53/824](#); for supporting articles during joining [B29C 66/634](#); flexible cores for vulcanizing tyres [B29D 30/0654](#))}
- 33/52 . . soluble or fusible {(in particular used in injection moulding [B29C 45/4457](#))}
- 2033/525 . . . {Cores made of frozen liquids, e.g. ice}
- 33/54 . . made of powdered or granular material
- 33/56 . Coatings {, e.g. enamelled, galvanised}; Releasing, lubricating or separating agents {(in-mould coating [B29C 37/0028](#); using or applying separating agents [B29C 37/0067](#))}
- 33/565 . . {Consisting of shell-like structures supported by backing material}
- 33/58 . . Applying the releasing agents
- 33/60 . . Releasing, lubricating or separating agents {(in general [C10M](#))}
- 33/62 . . . based on polymers or oligomers
- 33/64 . . . . Silicone
- 33/66 . . . . Cellulose; Derivatives thereof
- 33/68 . . Release sheets
- 33/70 . Maintenance
- 2033/705 . . {Mould inspection means, e.g. cameras}
- 33/72 . . Cleaning {(extruder parts [B29C 47/0877](#); in general [B08B 7/00](#))}
- 33/722 . . . {Compositions for cleaning moulds}

2033/725	. . . {cleaning by plasma treatment}	2035/044	. . . . . {mercury}
2033/727	. . . {cleaning during moulding}	35/045	. . . {using gas or flames}
33/74	. . Repairing	2035/046	. . . . . {dried air}
33/76	. Cores ( <a href="#">B29C 33/02</a> - <a href="#">B29C 33/70</a> , { <a href="#">B29C 41/40</a> , <a href="#">B29C 53/74</a> , <a href="#">B29C 53/82</a> } take precedence)	2035/047	. . . . . {other than air}
<b>35/00</b>	<b>Heating, cooling or curing, e.g. crosslinking, vulcanising; Apparatus therefor</b> (moulds with incorporated heating or cooling means <a href="#">B29C 33/02</a> ; {thermal after-treatment of shaped articles <a href="#">B29C 71/02</a> } ; curing devices for plastics dental prostheses <a href="#">A61C 13/14</a> ; before moulding <a href="#">B29B 13/00</a> ; chemical aspects <a href="#">C08J 3/00</a> )	2035/048	. . . . . {inert gas}
35/002	. {Component parts, details or accessories; Auxiliary operations}	35/049	. . . {using steam or damp}
2035/005	. . {Enveloping the material to be cured, e.g. by helically winding a film around the material}	35/06	. . . for articles of indefinite length
35/007	. {Tempering units for temperature control of moulds or cores, e.g. comprising heat exchangers, controlled valves, temperature-controlled circuits for fluids ( <a href="#">B29C 35/0294</a> takes precedence)}	35/065	. . . . . {in long tubular vessels}
35/02	. Heating or curing, e.g. crosslinking, vulcanising {during moulding, e.g. in a mould} (coldvulcanisation <a href="#">B29C 35/18</a> ; {vulcanising tyres, presses therefor <a href="#">B29D 30/0601</a> })	35/08	. . by wave energy or particle radiation {( <a href="#">B29C 64/00</a> , <a href="#">B29C 71/04</a> take precedence)}
2035/0211	. . {resistance heating ( <a href="#">B29C 2035/0811</a> takes precedence)}	35/0805	. . . {using electromagnetic radiation}
2035/0216	. . {using Peltier-effect}	2035/0811	. . . . . {using induction}
35/0222	. . {the curing continuing after removal from the mould ( <a href="#">B29C 35/0233</a> takes precedence)}	2035/0816	. . . . . {using eddy currents}
35/0227	. . {using pressure vessels, e.g. autoclaves, vulcanising pans ( <a href="#">B29C 35/065</a> takes precedence)}	2035/0822	. . . . . {using IR radiation}
35/0233	. . . {the curing continuing after removal from the mould}	2035/0827	. . . . . {using UV radiation}
35/0238	. . . {Presses provided with pressure vessels, e.g. steam chambers}	2035/0833	. . . . . {using actinic light}
35/0244	. . {using fluidised bed}	2035/0838	. . . . . {using laser}
35/025	. . . {for articles of indefinite length}	2035/0844	. . . . . {using X-ray}
35/0255	. . {using friction}	2035/085	. . . . . {using gamma-ray}
35/0261	. . {using ultrasonic or sonic vibrations}	2035/0855	. . . . . {using microwave}
35/0266	. . {Local curing (for repairing <a href="#">B29C 73/34</a> )}	2035/0861	. . . . . {using radio frequency}
35/0272	. . {using lost heating elements, i.e. heating means incorporated and remaining in the formed article (for preforms with internal stresses <a href="#">B29C 61/0625</a> ; joining using lost heating elements <a href="#">B29C 65/34</a> ; making electrically conductive articles <a href="#">B29C 70/882</a> )}	35/0866	. . . {using particle radiation}
35/0277	. . {Apparatus with continuous transport of the material to be cured ( <a href="#">B29C 35/025</a> , <a href="#">B29C 35/06</a> , <a href="#">B29C 35/10</a> , <a href="#">B29C 35/14</a> take precedence)}	2035/0872	. . . . . {using ion-radiation, e.g. alpha-rays}
2035/0283	. . {Thermal pretreatment of the plastics material (thermal after-treatment <a href="#">B29C 71/02</a> )}	2035/0877	. . . . . {using electron radiation, e.g. beta-rays}
35/0288	. . {Controlling heating or curing of polymers during moulding, e.g. by measuring temperatures or properties of the polymer and regulating the process (controlling or regulating chemical, physical or physico- chemical processes in general <a href="#">B01J 19/0006</a> )}	2035/0883	. . . . . {using neutron radiation}
35/0294	. . . {using tempering units for temperature control of moulds or cores}	35/0888	. . . {using transparant moulds}
35/04	. . using liquids, gas or steam	35/0894	. . . . . {provided with masks or diaphragms}
35/041	. . . {using liquids}	35/10	. . . for articles of indefinite length
2035/042	. . . . . {other than water}	35/12	. . Dielectric heating
2035/043	. . . . . {oil}	35/14	. . . for articles of indefinite length
		35/16	. Cooling {( <a href="#">cooling extruded material <a href="#">B29C 47/8815</a></a> ; <a href="#">cooling preforms for blow moulding <a href="#">B29C 49/6427</a></a> ; <a href="#">cooling blown articles <a href="#">B29C 49/66</a></a> ; <a href="#">cooling tyres during post cure inflation <a href="#">B29D 30/0643</a></a> )}
		2035/1608	. . {using Peltier-effect}
		2035/1616	. . {using liquids}
		2035/1625	. . . {other than water}
		2035/1633	. . . . . {oil}
		2035/1641	. . . . . {mercury}
		2035/165	. . . . . {liquified gases}
		2035/1658	. . {using gas}
		2035/1666	. . . {dried air}
		2035/1675	. . . {other than air}
		2035/1683	. . . . . {inert gas}
		2035/1691	. . {using gas-liquid mixtures}
		35/18	. Cold vulcanisation
		<b>37/00</b>	<b>Component parts, details, accessories or auxiliary operations, not covered by group <a href="#">B29C 33/00</a> or <a href="#">B29C 35/00</a></b>
		37/0003	. {Discharging moulded articles from the mould (constructions for removing the articles <a href="#">B29C 33/44</a> )}
		37/0007	. . {using means operable from outside the mould for moving between mould parts, e.g. robots}
		37/001	. . . {combined with means for loading preforms to be moulded or inserts, e.g. preformed layers}
		37/0014	. . {by flexibly or permanently deforming undercut portions of the articles}
		37/0017	. . {by stripping articles from mould cores}
		37/0021	. . . {and using a rotating movement to unscrew articles (in particular used in injection moulding <a href="#">B29C 45/178</a> )}



37/0025	• {Applying surface layers, e.g. coatings, decorative layers, printed layers, to articles during shaping, e.g. in-mould printing ( <a href="#">moulding on preformed layers as inserts B29C 70/68</a> ; <a href="#">applying fluent material to surfaces in general B05</a> )}	37/04	• • of welded articles, e.g. deburring or deflashing in combination with welding ( <a href="#">shaping the burr B29C 66/32</a> )
37/0028	• • {In-mould coating, e.g. by introducing the coating material into the mould after forming the article}		<b>NOTE</b> Attention is drawn to Note (3) following the subclass title.
37/0032	• • • {the coating being applied upon the mould surface before introducing the moulding compound, e.g. applying a gelcoat ( <a href="#">B29C 44/14</a> and <a href="#">B29C 44/32</a> take precedence)}	2037/80	• {Identifying, e.g. coding, dating, marking, numbering}
2037/0035	• • • {the coating being applied as liquid, gel, paste or the like}	2037/90	• {Measuring, controlling or regulating}
2037/0039	• • • {the coating being applied in powder or particle form}	2037/903	• • {by means of a computer}
2037/0042	• • • {the coating being applied in solid sheet form, e.g. as meltable sheet}	2037/906	• • {using visualisation means or linked accessories, e.g. screens, printers}
2037/0046	• • • {In-mould printing, in-mould transfer printing}	2037/92	• {Lubricating}
37/005	• {Compensating volume or shape change during moulding, in general}	2037/94	• {Safety devices}
37/0053	• {Moulding articles characterised by the shape of the surface, e.g. ribs, high polish ( <a href="#">mould construction therefor B29C 33/42</a> ; <a href="#">surface shaping of articles B29C 59/00</a> ; by incorporating filler in or near the surface <a href="#">B29C 70/64</a> )}	2037/96	• {Filters}
37/0057	• • {Moulding single grooves or ribs, e.g. tear lines ( <a href="#">folding lines B29C 53/06</a> )}	<b>Particular shaping techniques, e.g. moulding, joining; Apparatus therefor</b>	
37/006	• {Degassing moulding material or draining off gas during moulding ( <a href="#">venting means in moulds B29C 33/10</a> )}	39/00	<b>Shaping by casting, i.e. introducing the moulding material into a mould or between confining surfaces without significant moulding pressure; Apparatus therefor (<a href="#">B29C 41/00</a> takes precedence)</b>
37/0064	• • {of reinforced material}	39/003	• {characterised by the choice of material}
37/0067	• {Using separating agents during or after moulding; Applying separating agents on preforms or articles, e.g. to prevent sticking to each other ( <a href="#">separating agents B29C 33/60</a> )}		<b>NOTE</b> When classifying in this group, it is desirable to add the indexing codes of subclass <a href="#">B29K</a> to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
37/0071	• • {Dusting machines}	39/006	• • {Monomers or prepolymers ( <a href="#">by reaction injection moulding B29C 67/246</a> )}
37/0075	• • {using release sheets}	39/02	• for making articles of definite length, i.e. discrete articles
37/0078	• {Measures or configurations for obtaining anchoring effects in the contact areas between layers ( <a href="#">surface shaping B29C 59/00</a> ; <a href="#">B29C 66/02</a> takes precedence)}	39/021	• • {by casting in several steps}
37/0082	• • {Mechanical anchoring ( <a href="#">B29C 66/303</a> takes precedence)}	39/023	• • • {for making multicoloured articles}
37/0085	• • • {by means of openings in the layers ( <a href="#">joining through openings B29C 66/304</a> )}	39/025	• • • {for making multilayered articles}
37/0089	• {Sealing devices placed between articles and treatment installations during moulding or shaping, e.g. sealing off the entrance or exit of ovens or irradiation rooms, connections between rooms at different pressures}	39/026	• • {characterised by the shape of the surface}
37/0092	• {Drying moulded articles or half products, e.g. preforms, during or after moulding or cooling}	39/028	• • {having an axis of symmetry}
37/0096	• {Trouble-shooting during starting or stopping moulding or shaping apparatus ( <a href="#">B29C 66/872</a> takes precedence)}	39/04	• • using movable moulds ( <a href="#">B29C 41/02</a> takes precedence) {not applied}
37/02	• Deburring or deflashing ( <a href="#">by grinding or polishing B24B</a> ; <a href="#">thermal deburring in general B23D 79/005</a> )}	39/06	• • • continuously movable, e.g. along a production line
		39/08	• • • Introducing the material into the mould by centrifugal force
		39/10	• • incorporating preformed parts or layers, e.g. casting around inserts or for coating articles ( <a href="#">coating a surface by casting in general B05D 1/30</a> , <a href="#">B29C 39/126</a> takes precedence)}
		39/12	• • Making multilayered or multicoloured articles ( <a href="#">B29C 39/021</a> takes precedence)}
		39/123	• • • {Making multilayered articles}
		39/126	• • • • {by casting between two preformed layers, e.g. deformable layers ( <a href="#">between two glass layers B32B 17/10917</a> )}
		39/14	• for making articles of indefinite length ( <a href="#">by depositing material on a substrate and stripping off the shaped article B29C 41/24</a> )}
		39/142	• • {by casting in several steps}
		39/144	• • • {for making multicoloured articles}

- 39/146 . . . {for making multilayered articles}
- 39/148 . . {characterised by the shape of the surface}
- 39/16 . . between endless belts
- 39/18 . . incorporating preformed parts or layers, e.g. casting around inserts or for coating articles {[\(B29C 39/206 takes precedence\)](#)}
- 39/20 . . Making multilayered or multicoloured articles {[\(B29C 39/142 takes precedence\)](#)}
- 39/203 . . . {Making multilayered articles}
- 39/206 . . . . {by casting between two preformed layers, e.g. deformable layers}
- 39/22 . Component parts, details or accessories; Auxiliary operations
- 39/24 . . Feeding the material into the mould
- 39/26 . . Moulds or cores
- 39/265 . . . {comprising two large plates positioned at a small distance from each other, e.g. for making panels}
- 39/28 . . . with means to avoid flashes {[\(B29C 39/30 takes precedence\)](#)}
- 39/30 . . . with means for cutting the article
- 39/32 . . . with joints or the like for making the mould impervious
- 39/34 . . . for undercut articles
- 39/36 . . Removing moulded articles
- 39/38 . . Heating or cooling
- 39/40 . . Compensating volume change, e.g. retraction {[\(in general B29C 37/005\)](#)}
- 39/405 . . . {by applying pressure to the casting composition}
- 39/42 . . Casting under special conditions, e.g. vacuum
- 39/44 . . Measuring, controlling or regulating
- 41/00 Shaping by coating a mould, core or other substrate, i.e. by depositing material and stripping-off the shaped article; Apparatus therefor (with compacting pressure [B29C 43/00](#) {; by lay-up of reinforcement of substantial or continuous length [B29C 70/30](#)})**
- 41/003 . {characterised by the choice of material}
- NOTE**  
When classifying in this group, it is desirable to add the indexing codes of subclass [B29K](#) to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
- 41/006 . {using an electrostatic field for applying the material}
- 41/02 . for making articles of definite length, i.e. discrete articles
- 41/025 . . {having hollow walls}
- 41/04 . . Rotational or centrifugal casting, i.e. coating the inside of a mould by rotating the mould
- 41/042 . . . {by rotating a mould around its axis of symmetry [\(for concrete B28B 21/30\)](#)}
- 41/045 . . . . {the axis being placed vertically, e.g. spin casting}
- 41/047 . . . . {the mould cavity lying totally outside the axis, e.g. toroidal moulds}
- 41/06 . . . about two or more axes
- 41/08 . . Coating a former, core or other substrate by spraying or fluidisation, e.g. spraying powder {[\(spray-up of reinforcing fibres B29C 70/305\)](#)}
- 41/085 . . . {by rotating the former around its axis of symmetry}
- 41/10 . . . by fluidisation
- 41/12 . . Spreading-out the material on a substrate {, e.g. on the surface of a liquid}
- 41/14 . . Dipping a core {[\(B29C 41/10 takes precedence\)](#)}
- 41/16 . . Slip casting, i.e. applying a slip or slurry on a perforated or porous or absorbent surface with the liquid being drained away
- 41/18 . . Slush casting, i.e. pouring moulding material into a hollow mould with excess material being poured off
- 41/20 . . incorporating preformed parts or layers, e.g. moulding inserts or for coating articles
- 41/22 . . Making multilayered or multicoloured articles
- 41/24 . for making articles of indefinite length
- 41/26 . . by depositing flowable material on a rotating drum
- 41/265 . . . {on the inside of the drum}
- 41/28 . . by depositing flowable material on an endless belt
- 41/30 . . incorporating preformed parts or layers, e.g. moulding around inserts or for coating articles
- 41/32 . . Making multilayered or multicoloured articles
- 41/34 . Component parts, details or accessories; Auxiliary operations
- 41/36 . . Feeding the material on to the mould, core or other substrate
- 41/365 . . . {Construction of spray-up equipment, e.g. spray-up guns [\(spraying apparatus in general B05B\)](#)}
- 41/38 . . Moulds, cores or other substrates
- 41/383 . . . {with means for cutting the article}
- 41/386 . . . {for undercut articles}
- 41/40 . . . Cores
- 41/42 . . Removing articles from moulds, cores or other substrates {[\(B29C 33/444 and B29C 37/0017 take precedence\)](#)}
- 41/44 . . . Articles of indefinite length
- 41/46 . . Heating or cooling
- 41/48 . . Compensating volume change, e.g. retraction
- 41/50 . . Shaping under special conditions, e.g. vacuum
- 41/52 . . Measuring, controlling or regulating
- 43/00 Compression moulding, i.e. applying external pressure to flow the moulding material; Apparatus therefor ({by liberation of internal stresses [B29C 61/006](#) ; shaping or impregnating by compression composites comprising reinforcements other than fibres of short length { [B29C 70/12](#)}; presses in general [B30B](#)})**
- 43/003 . {characterised by the choice of material}
- NOTE**  
When classifying in this group, it is desirable to add the indexing codes of subclass [B29K](#) to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
- 43/006 . {Pressing and sintering powders, granules or fibres}

- 43/02 . . of articles of definite length, i.e. discrete articles  
{(B29C 35/0227 takes precedence)}
- 43/021 . . {characterised by the shape of the surface}
- 2043/022 . . . {having locally depressed lines, e.g. hinges  
(single grooves B29C 37/0057; folding lines  
B29C 53/06; parting line of the mould parts  
B29C 33/005)}
- 2043/023 . . . {having a plurality of grooves}
- 2043/024 . . . . {forming a threaded surface}
- 2043/025 . . . . {forming a microstructure, i.e. fine  
patterning}
- 2043/026 . . . {having functional projections, e.g. fasteners}
- 43/027 . . {having an axis of symmetry (B29C 43/102 takes  
precedence)}
- 2043/028 . . . {using radial compression}
- 2043/029 . . . {using axial compression along a longitudinal  
axis}
- 43/04 . . using movable moulds
- 2043/043 . . . {rotating on their own axis without linear  
displacement}
- 2043/046 . . . {travelling between different stations, e.g.  
feeding, moulding, curing stations}
- 43/06 . . . continuously movable {in one direction, e.g.  
mounted on chains, belts}
- 43/08 . . . . with circular movement {, e.g. mounted on  
rolls, turntables}
- 43/085 . . . . . {and material fed in a continuous form,  
e.g. as a band}
- 43/10 . . Isostatic pressing, i.e. using non-rigid pressure-  
exerting members against rigid parts or dies {(in  
general B30B 11/001)}
- 43/102 . . . {using rigid mould parts specially adapted for  
moulding articles having an axis of symmetry}
- 43/104 . . . . {the mould cavity lying totally outside the  
axis of symmetry, e.g. toroidal moulds}
- 2043/106 . . . {using powder material}
- 2043/108 . . . {using deformable metals, e.g. flowable metals,  
low melting point eutectic metals, liquified  
metals}
- 43/12 . . . using bags surrounding the moulding  
material {or using membranes contacting  
the moulding material (B29C 70/44 takes  
precedence; flexible cores for vulcanizing tyres  
B29D 30/0654)}
- 43/14 . . in several steps
- 2043/141 . . . {for making single layer articles (for indefinite  
articles B29C 43/26)}
- 2043/142 . . . . {by moving a single mould or the article  
progressively, i.e. portionwise}
- 2043/143 . . . . {stepwise in a vertical direction, i.e. each  
time modifying the thickness}
- 2043/144 . . . . {using different moulds, i.e. the layer is  
compressed in consecutive steps by using  
different moulds for each portion of the  
article}
- 43/145 . . . {for making multicoloured articles}
- 43/146 . . . {for making multilayered articles}
- 2043/147 . . . . {by compressing after the laying of further  
material}
- 2043/148 . . . . {using different moulds}
- 43/16 . . Forging
- 43/18 . . incorporating preformed parts or layers,  
e.g. compression moulding around inserts  
or for coating articles {(B29C 43/206 takes  
precedence)}
- 2043/181 . . . {encapsulated (outsert moulding B29C 70/74)}
- 2043/182 . . . . {completely (completely encapsulating  
inserts B29C 70/70)}
- 43/183 . . . {the preformed layer being a lining, e.g. shaped  
in the mould before compression moulding, or  
a preformed shell adapted to the shape of the  
mould}
- 43/184 . . . . {shaped by the compression of the material  
during moulding}
- 2043/185 . . . {using adhesives (joining using adhesives  
B29C 65/48)}
- 2043/186 . . . . {hot-melt or heat activated adhesives  
(applying molten plastics B29C 65/40;  
joining using adhesives B29C 65/48)}
- 2043/187 . . . . {pressure activated or pressure sensitive  
adhesives}
- 2043/188 . . . . {thermosetting adhesives, e.g. polyurethane  
adhesives (joining by heating B29C 65/02)}
- 2043/189 . . . {the parts being joined}
- 43/20 . . Making multilayered or multicoloured articles  
{(B29C 43/14 takes precedence)}
- 43/203 . . . {Making multilayered articles}
- 43/206 . . . . {by pressing the material between two  
preformed layers, e.g. deformable layers}
- 43/22 . . of articles of indefinite length {(for articles with  
reinforcements of substantial or continuous length  
B29C 70/50)}
- 43/222 . . {characterised by the shape of the surface}
- 43/224 . . {having a profiled section, e.g. tubes, rods}
- 43/226 . . . {having a corrugated section}
- 43/228 . . {using endless belts feeding the material between  
non-rotating pressure members, e.g. vibrating  
pressure members}
- 43/24 . . Calendering
- 43/245 . . . {Adjusting calender parameters, e.g. bank  
quantity}
- 43/26 . . in several steps (B29C 43/30 takes precedence  
{not applied})
- 43/265 . . . {for making multilayered articles}
- 43/28 . . incorporating preformed parts or layers, e.g.  
compression moulding around inserts or for  
coating articles
- 43/30 . . Making multilayered or multicoloured articles  
{(B29C 43/26 takes precedence)}
- 43/305 . . . {Making multilayered articles}
- 43/32 . . Component parts, details or accessories; Auxiliary  
operations
- 2043/3205 . . {particular pressure exerting means for making  
definite articles (B29C 43/36 takes precedence)}
- 2043/3211 . . . {magnets}
- 2043/3216 . . . {deformable nets, meshes, lattices or fabrics,  
e.g. tubular ones}
- 2043/3222 . . . {pressurized gas, e.g. air}
- 2043/3227 . . . . {inside the material, e.g. gas injection  
compression moulding}
- 2043/3233 . . . . {exerting pressure on mould parts}
- 2043/3238 . . . {pressurized liquid acting directly or indirectly  
on the material to be formed}
- 2043/3244 . . . {retraction of an expanded member}
- 2043/325 . . . {screws}

- 2043/3255 . . . {springs}
- 2043/3261 . . . {thermal expansion}
- 2043/3266 . . . {vibrating tool means}
- 2043/3272 . . {driving means}
- 2043/3277 . . . {for rotatable supports, e.g. carousels, drums}
- 2043/3283 . . . {for moving moulds or mould parts}
- 2043/3288 . . . . {using cam drives}
- 2043/3294 . . . . {using screw drives}
- 43/34 . . Feeding the material to the mould or the compression means {(B29C 43/085 takes precedence)}
- 2043/3405 . . . {using carrying means}
- 2043/3411 . . . . {mounted onto arms, e.g. grippers, fingers, clamping frame, suction means}
- 2043/3416 . . . . {conveyor belts}
- 2043/3422 . . . . {rollers}
- 2043/3427 . . . . {hopper, vessel, chute, tube, conveying screw, for material in discrete form, e.g. particles, powder, fibres (dispensing from vessels B29C 31/02)}
- 2043/3433 . . . {using dispensing heads, e.g. extruders, placed over or apart from the moulds (feeding using dispensing heads B29C 31/042; applying fluent material for coatings B05D 1/26; extrusion coating B05D 1/265)}
- 2043/3438 . . . . {moving during dispensing over the moulds, e.g. laying up (feeding using moving dispensing heads B29C 31/044; applying fluent material for coatings B05D 1/26; extrusion coating B05D 1/265)}
- 2043/3444 . . . {using pressurizing feeding means located into the mold, e.g. plungers, pistons (injection-compression moulding B29C 45/561)}
- 2043/345 . . . {using gas, e.g. air, to transport non liquid material}
- 2043/3455 . . . . {for particles, powder, fibres, e.g. fluidized or sprayed}
- 2043/3461 . . . . {for foils, sheets, gobs, e.g. floated}
- 2043/3466 . . . {using rotating supports, e.g. turntables, drums (in general B29C 31/065; turntables as movable moulds B29C 43/08; feeding materials to moulding presses B30B 15/302; transfer turntables B65G 47/80)}
- 2043/3472 . . . . {using star wheels comprising arms (transfer stars B65G 47/84)}
- 2043/3477 . . . {centrally fed, e.g. feeding the material in the center of the mold turntables (turntables as movable moulds B29C 43/08)}
- 2043/3483 . . . {using band or film carriers}
- 2043/3488 . . . {uniformly distributed into the mould}
- 2043/3494 . . . . {using vibrating means}
- 43/36 . . Moulds for making articles of definite length, i.e. discrete articles
- 2043/3602 . . . {with means for positioning, fastening or clamping the material to be formed or preforms inside the mould (moulds with incorporated means for positioning inserts B29C 33/14; positioning articles in the mould for injection moulding B29C 45/14065)}
- 2043/3605 . . . . {vacuum}
- 43/3607 . . . {with sealing means or the like}
- 43/361 . . . {with pressing members independently movable of the parts for opening or closing the mould, e.g. movable pistons (transfer moulding B29C 45/02; injection-compression moulding B29C 45/561)}
- 2043/3613 . . . . {applying pressure locally}
- 2043/3615 . . . . {forming elements, e.g. mandrels, rams, stampers, pistons, plungers, punching devices (ram pressing B30B 11/02, B30B 11/04; forming pockets in sheets B65B 47/04; moulding lenses B29D 11/00413)}
- 2043/3618 . . . . . {plurality of counteracting elements}
- 2043/3621 . . . . . {a plurality of individual elements acting on the material in the same or different directions, e.g. making tubular T-joints, profiles}
- 2043/3623 . . . . . {coupled on a support, e.g. plate}
- 2043/3626 . . . . . {multi-part rams, plungers or mandrels}
- 2043/3628 . . . . . {moving inside a barrel or container like sleeve}
- 2043/3631 . . . . . {moving in a frame for pressing and stretching; material being subjected to compressing stretching}
- 2043/3634 . . . . . {having specific surface shape, e.g. grooves, projections, corrugations}
- 2043/3636 . . . . . {ultrasonically or sonically vibrating, e.g. sonotrodes}
- 2043/3639 . . . . . {hand operated (forming pockets or receptacles in or from sheets, blanks, or webs B65B 47/04)}
- 43/3642 . . . {Bags, bleeder sheets or cauls for isostatic pressing (flexible cores for vulcanizing tyres B29D 30/0654)}
- 2043/3644 . . . . {vacuum bags and related details, e.g. fixing, clamping (vacuum bagging B29C 70/44; flexible pressing means B30B 5/02; membrane press B30B 9/22; applying pressure through membranes B29C 51/28; bladders for making tires B29D 30/0601; vacuum laminating B32B 37/1018)}
- 2043/3647 . . . . {membranes, diaphragms (vacuum bagging B29C 70/44; applying pressure through membranes B29C 51/28; bladders for making tires B29D 30/0601; vacuum laminating B32B 37/1018; flexible pressing means B30B 5/02; membrane press B30B 9/22)}
- 2043/3649 . . . . {infatable bladders using gas or fluid and related details (vacuum bagging B29C 70/44; flexible moulds B29C 33/50; flexible pressing means B30B 5/02; membrane press B30B 9/22; deep drawing membranes B29C 51/28; bladders for making tires B29D 30/0601; vacuum laminating B32B 37/1018)}
- 2043/3652 . . . . {elastic moulds or mould parts, e.g. cores, inserts (isostatic pressing B29C 43/10; moulds in elastomer B29C 33/405; plastic cores B29C 33/50)}
- 2043/3655 . . . . {pressure transmitters, e.g. caul plates, pressure pads}
- 2043/3657 . . . . {additional materials, e.g. permeable bleeder or breather sheets, cloths, blankets}



- 2043/366 . . . {plates pressurized by an actuator, e.g. ram drive, screw, vulcanizing presses}
- 2043/3663 . . . . {confined in a chamber}
- 2043/3665 . . . {cores or inserts, e.g. pins, mandrels, sliders}
- 2043/3668 . . . . {destructible or fusible ([moulds for making articles with holes B29C 33/0033](#); [lost moulds B29C 33/0016](#); [fusible cores B29C 33/52](#); [making porous articles B22F 3/11](#))}
- 2043/3671 . . . {preforms constituting part of the cavity mould wall}
- 2043/3673 . . . . {preform constituting a mould half}
- 2043/3676 . . . {moulds mounted on rotating supporting constructions}
- 2043/3678 . . . . {on cylindrical supports with moulds or mould cavities provided on the periphery ([rollers for making indefinite articles B29C 43/46](#); [turntables presses B30B 11/08](#), [roller presses B30B 11/006](#))}
- 2043/3681 . . . . . {opening and closing axially, i.e. parallel to the rotation axis}
- 2043/3684 . . . . . {opening/closing or acting radially, i.e. vertical to the rotation axis}
- 2043/3686 . . . . . {opening and closing tangential to the rotation, i.e. vertical to the rotation axis and vertical to the radius}
- 2043/3689 . . . . . {on a support table, flat disk-like tables having moulds on the periphery ([press rams on turntables B30B 11/08](#), [B30B 9/042](#))}
- 2043/3692 . . . . . {cooperating with non rotating parts}
- 2043/3694 . . . . . {on rotating star wheels}
- 43/3697 . . . {comprising rollers or belts cooperating with non-rotating mould parts}
- 43/38 . . . with means to avoid flashes {([B29C 43/40 takes precedence](#))}
- 43/40 . . . with means for cutting the article
- 2043/403 . . . . {knife blades}
- 2043/406 . . . . {laser cutting means}
- 43/42 . . . for undercut articles
- 2043/425 . . . . {mould parts or sliders being movable independently from the mould halves for making undercut portions ([collapsible cores or mandrels B29C 33/485](#))}
- 43/44 . . Compression means for making articles of indefinite length
- 43/46 . . . Rollers
- 2043/461 . . . . {the rollers having specific surface features}
- 2043/462 . . . . . {smooth surface}
- 2043/463 . . . . . {corrugated, patterned or embossed surface}
- 2043/464 . . . . . {having projections or knives, e.g. for cutting-out or for forming local depressions}
- 2043/465 . . . . . {having one or more cavities, e.g. for forming distinct products}
- 2043/466 . . . . {the rollers having specific shape, e.g. non cylindrical rollers, conical rollers}
- 2043/467 . . . . {plurality of rollers arranged in a specific manner in relation to each other ([calender configuration B29C 43/24](#))}
- 2043/468 . . . . {take-off rollers, i.e. arranged adjacent a material feeding device ([calendering B29C 43/24](#))}
- 43/48 . . . Endless belts
- 2043/483 . . . . {cooperating with a second endless belt, i.e. double band presses}
- 2043/486 . . . . {cooperating with rollers or drums}
- 43/50 . . Removing moulded articles
- 2043/5007 . . . {using cores, i.e. the cores forming part of the mould cavity}
- 2043/5015 . . . . {having undercuts or being threaded ([using a rotating movement to unscrew articles B29C 33/446](#))}
- 2043/5023 . . . . {moving away ([collapsible cores or mandrels B29C 33/485](#))}
- 2043/503 . . . {using ejector pins, rods}
- 2043/5038 . . . . {having an annular or tubular shape}
- 2043/5046 . . . {using vacuum}
- 2043/5053 . . . {using pressurised gas, e.g. air}
- 2043/5061 . . . {using means movable from outside the mould between mould parts}
- 2043/5069 . . . . {take-off members or carriers for the moulded articles, e.g. grippers}
- 2043/5076 . . . {using belts}
- 2043/5084 . . . {using rotary devices, e.g. turntables, carousels ([blow moulding machines B29C 49/36](#), [B29C 49/4205](#))}
- 2043/5092 . . . {using vibrations means}
- 43/52 . . Heating or cooling
- 2043/522 . . . {selectively heating a part of the mould to achieve partial heating, differential heating}
- 2043/525 . . . {at predetermined points for local melting, curing or bonding}
- 2043/527 . . . {selectively cooling, e.g. locally, on the surface of the material}
- 43/54 . . Compensating volume change, e.g. retraction
- 43/56 . . Compression moulding under special conditions, e.g. vacuum
- 2043/561 . . . {under vacuum conditions ([vacuum laminating B32B 37/1018](#))}
- 2043/562 . . . . {combined with isostatic pressure, e.g. pressurising fluids, gases}
- 2043/563 . . . . {combined with mechanical pressure, i.e. mould plates, rams, stampers}
- 2043/565 . . . {in a clean sterile environment, e.g. to avoid contamination}
- 2043/566 . . . {in a specific gas atmosphere, with or without pressure}
- 2043/567 . . . {in a liquid, i.e. the moulded parts being embedded in liquid}
- 2043/568 . . . {in a magnetic or electric field}
- 43/58 . . Measuring, controlling or regulating {(for [bank adjustment in calendering B29C 43/245](#))}
- 2043/5808 . . . {pressure or compressing force}
- 2043/5816 . . . {temperature}
- 2043/5825 . . . {dimensions or shape, e.g. size, thickness}
- 2043/5833 . . . {movement of moulds or mould parts, e.g. opening or closing, actuating}
- 2043/5841 . . . . {for accommodating variation in mould spacing or cavity volume during moulding ([compensating shrinkage B29C 43/54](#))}
- 2043/585 . . . {detecting defects, e.g. foreign matter between the moulds, inaccurate position, breakage}
- 2043/5858 . . . . {for preventing tilting of movable mould plate during closing or clamping}
- 2043/5866 . . . {ejection of moulded articles}

- 2043/5875 . . . {the material feed to the moulds or mould parts, e.g. controlling feed flow, velocity, weight, doses}
- 2043/5883 . . . {ensuring cavity filling, e.g. providing overflow means}
- 2043/5891 . . . {using imaging devices, e.g. cameras}
- 44/00 Shaping by internal pressure generated in the material, e.g. swelling, foaming (; Producing porous or cellular expanded plastics articles)**
- 44/005 . {Avoiding skin formation; Making foams with porous surfaces}
- 44/02 . for articles of definite length, i.e. discrete articles
- 44/022 . . {Foaming unrestricted by cavity walls, e.g. without using moulds or using only internal cores}
- 44/025 . . {Foaming in open moulds, followed by closing the moulds}
- 44/027 . . {the foaming continuing or beginning when the mould is opened}
- 44/04 . . consisting of at least two parts of chemically or physically different materials, e.g. having different densities
- 44/0407 . . . {by regulating the temperature of the mould or parts thereof, e.g. cold mould walls inhibiting foaming of an outer layer}
- 44/0415 . . . {by regulating the pressure of the material during or after filling of the mould, e.g. by local venting}
- 44/0423 . . . {by density separation}
- 44/043 . . . . {using a rotating mould}
- 44/0438 . . . . {using flotation}
- 44/0446 . . . {by increasing the density locally by compressing part of the foam while still in the mould}
- 44/0453 . . . {by joining the different materials using compression moulding before the foaming step}
- 44/0461 . . . {by having different chemical compositions in different places, e.g. having different concentrations of foaming agent, feeding one composition after the other}
- 44/0469 . . . . {provided with physical separators between the different materials, e.g. separating layers, mould walls}
- 44/0476 . . . . {by pouring more than one composition into an open mould}
- 44/0484 . . . {by having different solubility of the foaming agent}
- 44/0492 . . . {Devices for feeding the different materials}
- 44/06 . . . Making multilayered articles  
{(B29C 44/0407 - B29C 44/0492 take precedence)}
- 44/065 . . . . {comprising at least one barrier layer}
- 44/08 . . using several expanding {or moulding} steps
- 44/083 . . . {Increasing the size of the cavity after a first part has foamed, e.g. substituting one mould part with another}
- 44/086 . . . . {and feeding more material into the enlarged cavity}
- 44/10 . . Applying counter-pressure during expanding
- 44/105 . . . {the counterpressure being exerted by a fluid}
- 44/12 . . Incorporating or moulding on preformed parts, e.g. inserts, reinforcements
- 44/1204 . . . {and giving the material during expanding the shape of a particular article to be supported, e.g. a human body-part}
- 44/1209 . . . {by impregnating a preformed part, e.g. a porous lining}
- 44/1214 . . . {Anchoring by foaming into a preformed part, e.g. by penetrating through holes (anchoring by moulding in general B29C 37/0078; outsert moulding B29C 45/14344, B29C 70/74)}
- 44/1219 . . . {Foaming between a movable mould part and the preformed part}
- 44/1223 . . . {Joining preformed parts which have previously been filled with foam}
- 44/1228 . . . {Joining preformed parts by the expanding material}
- 44/1233 . . . . {the preformed parts being supported during expanding}
- 44/1238 . . . . . {and having flexible and solid areas}
- 44/1242 . . . . {the preformed parts being concentric (B29C 44/1233 takes precedence)}
- 44/1247 . . . . . {comprising dams or sealing arrangements}
- 44/1252 . . . {Removing portions of the preformed parts after the moulding step}
- 44/1257 . . . {Joining a preformed part and a lining, e.g. around the edges}
- 44/1261 . . . {Avoiding impregnation of a preformed part}
- 44/1266 . . . {the preformed part being completely encapsulated, e.g. for packaging purposes or as reinforcement}
- 44/1271 . . . {the preformed parts being partially covered}
- 44/1276 . . . {the preformed parts being three dimensional structures which are wholly or partially penetrated by the foam}
- 44/128 . . . {Internally reinforcing constructional elements, e.g. beams}
- 44/1285 . . . {the preformed part being foamed}
- 44/129 . . . {Enhancing adhesion to the preformed part using an interlayer}
- 44/1295 . . . {Foaming around pipe joints}
- 44/14 . . . the preformed part being a lining  
{(B29C 44/1209 takes precedence)}
- 44/141 . . . . {Hiding joints in the lining}
- 44/143 . . . . {Means for positioning the lining in the mould (in general B29C 33/12)}
- 44/145 . . . . {the lining being a laminate}
- 44/146 . . . . {Shaping the lining before foaming}
- 44/148 . . . . {Applying the foaming resin, moulding the lining or the like, with the lining turned inside out}
- 44/16 . . . . shaped by the expansion of the material
- 44/18 . . . Filling preformed cavities {(B29C 44/1204 takes precedence)}
- 44/181 . . . . {Filling unsupported soft shells having a particular shape}
- 44/182 . . . . {Filling flexible bags not having a particular shape}
- 44/183 . . . . . {the components being kept apart in different containers within the bag, and mixed upon rupture of the containers (B29C 44/184 takes precedence)}
- 44/184 . . . . . {and inserting the bags into preformed cavities}

- 44/185 . . . . . {Starting the expansion after rupturing or dissolving the bag}
- 44/186 . . . . . {Filling multiple cavities ([B29C 44/181](#), [B29C 44/182](#) and [B29C 44/188](#) takes precedence)}
- 44/187 . . . . . {Filling faulty voids in the foam}
- 44/188 . . . . . {Sealing off parts of the cavities}
- 44/20 . . . . . for articles of indefinite length
- 44/203 . . . {Expanding the moulding material in a vertical channel}
- 44/206 . . . {Using expandable particles or beads as starting material}
- 44/22 . . . consisting of at least two parts of chemically or physically different materials, e.g. having different densities
- 44/24 . . . Making multilayered articles
- 44/26 . . . using several expanding steps
- 44/28 . . . Expanding the moulding material on continuous moving surfaces {without restricting the upwards growth of the foam}
- 44/285 . . . {Rising trough lateral side members, e.g. following the foam expansion}
- 44/30 . . . Expanding the moulding material between endless belts or rollers {(B29C 44/203 takes precedence)}
- 44/302 . . . {Expanding the moulding material in flexible endless moulds}
- 44/304 . . . {Adjusting the belt or roller pressure}
- 44/306 . . . {Longitudinally shaping, e.g. the belt}
- 44/308 . . . {Thickness separators and side seals}
- 44/32 . . . Incorporating or moulding on preformed parts, e.g. linings, inserts, reinforcements

**WARNING**

Group [B29C 44/32](#) is impacted by reclassification into groups [B29C 44/32](#), [B29C 44/321](#), [B29C 44/3215](#), [B29C 44/329](#), [B29C 44/332](#), and [B29C 44/334](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 44/321 . . . {the preformed part being a lining, e.g. a film or a support lining}

**WARNING**

Group [B29C 44/321](#) is incomplete pending reclassification of documents from group [B29C 44/32](#).

Groups [B29C 44/32](#) and [B29C 44/321](#) should be considered in order to perform a complete search.

- 44/3215 . . . . . {Folding devices for the lining}
- 44/322 . . . {the preformed parts being elongated inserts, e.g. cables}
- 44/324 . . . . . {the preformed parts being tubular or folded to a tubular shape}
- 44/326 . . . {Joining the preformed parts, e.g. to make flat or profiled sandwich laminates}
- 44/328 . . . {the foamable components being mixed in the nip between the preformed parts}

- 44/329 . . . {the preformed parts being partially embedded}

**WARNING**

Group [B29C 44/329](#) is incomplete pending reclassification of documents from group [B29C 44/32](#).

Groups [B29C 44/32](#) and [B29C 44/321](#) should be considered in order to perform a complete search.

- 44/332 . . . {the preformed parts being three-dimensional structures}

**WARNING**

Group [B29C 44/332](#) is incomplete pending reclassification of documents from group [B29C 44/32](#).

Groups [B29C 44/32](#) and [B29C 44/332](#) should be considered in order to perform a complete search.

- 44/334 . . . {Filling the preformed spaces or cavities}

**WARNING**

Group [B29C 44/334](#) is incomplete pending reclassification of documents from group [B29C 44/32](#).

Groups [B29C 44/32](#) and [B29C 44/334](#) should be considered in order to perform a complete search.

- 44/34 . . . Auxiliary operations

**WARNING**

Group [B29C 44/34](#) is impacted by reclassification into groups [B29C 44/34](#) and [B29C 44/3402](#).

Groups [B29C 44/34](#) and [B29C 44/3402](#) should be considered in order to perform a complete search.

- 44/3402 . . . {Details of processes or apparatus for reducing environmental damage or for working-up compositions comprising inert blowing agents or biodegradable components}

**WARNING**

Group [B29C 44/3402](#) is incomplete pending reclassification of documents from group [B29C 44/34](#).

Group [B29C 44/32](#) and [B29C 44/3402](#) should be considered in order to perform a complete search.

- 44/3403 . . . {Foaming under special conditions, e.g. in sub-atmospheric pressure, in or on a liquid}

- 44/3407 . . . {Vacuum extrusion using underwater barometric leg}

- 44/3411 . . . {Relieving stresses}

- 44/3415 . . . {Heating or cooling}

- 44/3419 . . . {Quick cooling}

- 44/3423 . . . {by using a heated or cooled preformed part, e.g. in the mould}

- 44/3426 . . . {Heating by introducing steam in the mould}

- 44/343 . . . . . {by using pipes to direct the steam inside the mould}

- 44/3434 . . . . {by using a sheet, grid, etc. to distribute the steam in the mould}
- 44/3438 . . {Bursting the cell walls by a sudden pressure release}
- 44/3442 . . {Mixing, kneading or conveying the foamable material (mixing plastics [B29B 7/00](#); mixing in general [B01F](#))}
- 44/3446 . . . {Feeding the blowing agent}
- 44/3449 . . . . {through the screw}
- 44/3453 . . . . {Feeding the blowing agent to solid plastic material}
- 44/3457 . . . . {Feeding the blowing agent in solid form to the plastic material}
- 44/3461 . . {Making or treating expandable particles}
- 44/3465 . . . {by compressing particles in vacuum, followed by expansion in normal pressure}
- 44/3469 . . {Cell or pore nucleation}
- 44/3473 . . . {by shearing forces}
- 44/3476 . . . {by, e.g. compression stress}
- 44/348 . . . {by regulating the temperature and/or the pressure, e.g. suppression of foaming until the pressure is rapidly decreased}
- 44/3484 . . {Stopping the foaming reaction until the material is heated or re-heated}
- 44/3488 . . {Vulcanizing the material before foaming}
- 44/3492 . . {Expanding without a foaming agent}
- 44/3496 . . . {The foam being compressed and later released to expand ([B29C 44/3465](#) takes precedence)}
- 44/35 . . {Component parts; Details or accessories}
- 44/351 . . . {Means for preventing foam to leak out from the foaming device during foaming}
- 44/352 . . . {Means for giving the foam different characteristics in different directions}
- 44/353 . . . {Means for guiding the foaming in, e.g. a particular direction}
- 44/354 . . . {Means to prevent or reduce the effect of shrinking of the foamed article}
- 44/355 . . . {Characteristics of the foam, e.g. having particular surface properties or structure}
- 44/356 . . . . {having a porous surface}
- 44/357 . . . . {Auxetic foams, i.e. material with negative Poisson ratio; anti rubber; dilatational; re-entrant}
- 44/358 . . . . {Foamed of foamable fibres}
- 44/36 . . Feeding the material to be shaped ([B29C 44/0492](#) takes precedence)}
- 44/362 . . . {Regulating the feed w.r.t. the foam layer thickness}
- 44/365 . . . {using elongate feed conduits provided with throttle devices}
- 44/367 . . . {using spray nozzles}
- 44/38 . . . into a closed space, i.e. to make articles of definite length ([B29C 44/365](#) and [B29C 44/367](#) take precedence)}
- 44/381 . . . . {Spreading the foamable material in the mould by pressing the mould halves together}
- 44/383 . . . . {using spreading devices mounted in the mould, in front of the feed opening}
- 44/385 . . . . {using manifolds or channels directing the flow in the mould}
- 44/386 . . . . . {using a movable, elongate nozzle, e.g. to reach deep into the mould}
- 44/388 . . . . {into moving moulds}
- 44/40 . . . . by gravity, e.g. by casting
- 44/42 . . . . using pressure difference, e.g. by injection, by vacuum
- 44/421 . . . . . {by plastizising the material into a shot cavity and injecting using a plunger}
- 44/422 . . . . . {by injecting by forward movement of the plastizising screw}
- 44/424 . . . . . {Details of machines}
- 44/425 . . . . . {Valve or nozzle constructions; Details of injection devices}
- 44/427 . . . . . . {having several injection gates}
- 44/428 . . . . . {Mould constructions; Mould supporting equipment}
- 44/44 . . . . {in solid form}
- 44/445 . . . . . {in the form of expandable granules, particles or beads}
- 44/46 . . . into an open space or onto moving surfaces, i.e. to make articles of indefinite length ([B29C 44/365](#), [B29C 44/367](#) take precedence)}
- 44/461 . . . . {dispensing apparatus, e.g. dispensing foaming resin over the whole width of the moving surface}
- 44/462 . . . . . {provided with pre-foaming devices}
- 44/464 . . . . . {using centrifugal force}
- 44/465 . . . . . {with adjustable die gap}
- 44/467 . . . . {Foam spreading or levelling devices}
- 44/468 . . . . {in a plurality of parallel streams which unite during the foaming}
- 44/48 . . . . by gravity, e.g. casting onto, or between, moving surfaces ([B29C 44/468](#) takes precedence)}
- 44/485 . . . . . {the material being spread in the nip of two cooperating rollers}
- 44/50 . . . . using pressure difference, e.g. by extrusion, by spraying ([B29C 44/468](#) takes precedence)}
- WARNING**
- Group [B29C 44/50](#) is impacted by reclassification into groups [B29C 44/50](#), [B29C 44/505](#), and [B29C 44/507](#).
- Groups [B29C 44/50](#), [B29C 44/505](#), and [B29C 44/507](#) should be considered in order to perform a complete search.
- 44/505 . . . . . {extruding the compound through a flat die (in general [B29C 47/0009](#))}
- WARNING**
- Group [B29C 44/505](#) is incomplete pending reclassification of documents from group [B29C 44/50](#).
- Groups [B29C 44/505](#) and [B29C 44/50](#) should be considered in order to perform a complete search.



- 44/507 . . . . . {extruding the compound through an annular die ([in general B29C 47/0009](#))}

**WARNING**

Group [B29C 44/507](#) is incomplete pending reclassification of documents from group [B29C 44/50](#).

Groups [B29C 44/507](#) and [B29C 44/50](#) should be considered in order to perform a complete search.

- 44/52 . . . . . between moving surfaces  
 44/54 . . . . . in the form of expandable particles or beads  
 44/56 . . . After-treatment of articles, e.g. for altering the shape  
 44/5609 . . . {Purging of residual gas, e.g. noxious or explosive blowing agents}  
 44/5618 . . . {Impregnating foam articles}  
 44/5627 . . . {by mechanical deformation, e.g. crushing, embossing, stretching}  
 44/5636 . . . . . {with the addition of heat}  
 44/5645 . . . . . {Differential deformation by differential heating}  
 44/5654 . . . . . {Subdividing foamed articles to obtain particular surface properties, e.g. on multiple modules}  
 44/5663 . . . . . {by perforating the foam, e.g. to open the cells}  
 44/5672 . . . . . {by stretching the foam, e.g. to open the cells}  
 44/5681 . . . {Covering the foamed object with, e.g. a lining}  
 44/569 . . . {Shaping and joining components with different densities or hardness}  
 44/58 . . Moulds  
 44/581 . . . {Closure devices for pour holes}  
 44/582 . . . {for making undercut articles}  
 44/583 . . . {for making articles with cavities}  
 44/585 . . . {with adjustable size of the mould cavity}  
 44/586 . . . {with a cavity increasing in size during foaming}  
 44/587 . . . {with a membrane, e.g. for pressure control}  
 44/588 . . . {with means for venting, e.g. releasing foaming gas}  
 44/60 . . Measuring, controlling or regulating  
 44/605 . . . {Calibration following a shaping operation, e.g. extrusion}

- 45/00** **Injection moulding, i.e. forcing the required volume of moulding material through a nozzle into a closed mould; Apparatus therefor** ([injection blow-moulding B29C 49/06](#))

- 45/0001 . {characterised by the choice of material}

**NOTE**

When classifying in this group, it is desirable to add the indexing codes of subclass [B29K](#) to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest

- 45/0003 . {of successively moulded portions rigidly joined to each other}

- 45/0005 . {using fibre reinforcements}  
 2045/0006 . . {the fibres being oriented in a direction perpendicular to the flow direction of the moulding material into the mould}  
 2045/0008 . . {the fibres being oriented randomly}  
 2045/001 . . {Bulk moulding compounds [BMC]}  
 2045/0012 . . {Skin layers without fibres or with little fibres}  
 45/0013 . {using fillers dispersed in the moulding material, e.g. metal particles}  
 2045/0015 . . {Non-uniform dispersion of fillers}  
 45/0017 . {moulding interconnected elements which are movable with respect to one another, e.g. chains or hinges}  
 2045/0018 . . {moulding containers with handle, e.g. buckets}  
 2045/002 . . {using shrinkage}  
 2045/0022 . . {using deformation of injected material to obtain interconnection}  
 2045/0024 . . {using a mould core with a blind hole wherein the hinge shaft is moulded}  
 45/0025 . {Preventing defects on the moulded article, e.g. weld lines, shrinkage marks ([preventing defects on the preformed parts or layers B29C 45/14836](#))}  
 2045/0027 . . {Gate or gate mark locations}  
 2045/0029 . . . {gates on the central optical axis of lenses}  
 2045/0031 . . {Movable mould wall parts in contact with weld lines, e.g. rotating pins for stirring the weld line}  
 2045/0032 . . {sequential injection from multiple gates, e.g. to avoid weld lines}  
 2045/0034 . . {Mould parting lines}  
 2045/0036 . . {Submerged or recessed burrs}  
 2045/0037 . . {Moulding articles or parts thereof without parting line}  
 2045/0039 . . {intermixing the injected material front at the weld line, e.g. by applying vibrations to the melt front ([B29C 2045/0031 takes precedence](#))}  
 2045/0041 . . {preventing initial material from entering the mould cavity}  
 2045/0043 . . {preventing shrinkage by reducing the wall thickness of the moulded article}  
 2045/0044 . . {expelling moulding material outside the mould cavity at the weld line location ([moulds with overflow cavities B29C 45/2669](#))}  
 45/0046 . {Details relating to the filling pattern or flow paths or flow characteristics of moulding material in the mould cavity}  
 2045/0048 . . {Laminar flow}  
 2045/0049 . . {the injected material flowing against a mould cavity protruding part}  
 2045/0051 . . {Flow adjustment by throttles}  
 45/0053 . {combined with a final operation, e.g. shaping ([injection-compression moulding B29C 45/561](#))}  
 45/0055 . . {Shaping}  
 2045/0056 . . . {folding back undercut forming parts, e.g. tabs of closures}  
 2045/0058 . . . {removing material}  
 45/006 . . {Joining parts moulded in separate cavities}  
 45/0062 . . . {Joined by injection moulding}  
 2045/0063 . . . {facing before assembling, i.e. bringing the parts opposite to each other before assembling}  
 2045/0065 . . . {the parts being interconnected before assembling by a breaking or shearing point}  
 2045/0067 . . . {interposing an insert between the parts to be assembled}

- 2045/0068 . . . {using axially aligned and separated mould cavities}
- 2045/007 . . . {assembling a container and a handle}
- 2045/0072 . . . {the parts to be joined being moulded in a stack mould ([stack moulds in general B29C 45/32](#))}
- 2045/0074 . . . {inserting a heating tool inside the mould}
- 2045/0075 . . . {curing or polymerising by irradiation}
- 2045/0077 . . . {removing burrs or flashes ([in general B29C 37/02](#))}
- 2045/0079 . . . {applying a coating or covering}
- 45/0081 . . . {of objects with parts connected by a thin section, e.g. hinge, tear line}
- 45/0082 . . . {Reciprocating the moulding material inside the mould cavity, e.g. push-pull injection moulding}
- 45/0084 . . . {General arrangement or lay-out of plants ([B29C 45/1468 takes precedence](#))}
- 2045/0086 . . . {Runner trees, i.e. several articles connected by a runner}
- 2045/0087 . . . {making hollow articles using a floating core movable in the mould cavity by fluid pressure and expelling molten excess material}
- 2045/0089 . . . {successive filling of parts of a mould cavity, i.e. one cavity part being filled before another part is filled ([sequential filling to prevent weld lines B29C 2045/0032](#))}
- 2045/0091 . . . {Pellets or granules, e.g. their structure, composition, length, height, width}
- 2045/0093 . . . {of articles provided with an attaching element}
- 2045/0094 . . . {injection moulding of small-sized articles, e.g. microarticles, ultra thin articles}
- 2045/0096 . . . {drying the moulding material before injection, e.g. by heating}
- 2045/0098 . . . {shearing of the moulding material, e.g. for obtaining molecular orientation or reducing the viscosity ([B29C 45/0082 takes precedence](#))}
- 45/02 . . . Transfer moulding, i.e. transferring the required volume of moulding material by a plunger from a "shot" cavity into a mould cavity
- 45/021 . . . {Plunger drives; Pressure equalizing means for a plurality of transfer plungers}
- 2045/022 . . . {Stationary transfer plungers}
- 2045/024 . . . {Transfer plungers and pots with an oblong cross section}
- 2045/025 . . . {with the transfer plunger surface forming a part of the mould cavity wall at the end of the plunger transfer movement}
- 2045/027 . . . {heat insulated cold transfer moulding}
- 2045/028 . . . {using auxiliary curing or setting means}
- 45/03 . . . Injection moulding apparatus ([transfer moulding B29C 45/02](#))
- 2045/033 . . . {horizontal injection units mounted on a mould half carrying plate}
- 45/036 . . . {Injection pistols}
- 45/04 . . . using movable moulds {or mould halves} ([B29C 45/08 takes precedence](#))
- 45/0408 . . . {involving at least a linear movement ([B29C 45/0433 takes precedence](#))}
- 45/0416 . . . . . {co-operating with fixed mould halves}
- 2045/0425 . . . . . {Book moulds, i.e. a mould half can be opened and closed like a book with regard to the other mould half, the mould halves being connected by a hinge}
- 45/0433 . . . {mounted on a conveyor belt or chain}
- 45/0441 . . . . . {involving a rotational movement ([B29C 45/06 takes precedence](#))}
- 45/045 . . . . . {mounted on the circumference of a rotating support having a rotating axis perpendicular to the mould opening, closing or clamping direction}
- 2045/0458 . . . . . {Drive means for the rotating support}
- 2045/0466 . . . . . {the axial movement of the mould being linked to the rotation of the mould or mould half}
- 2045/0475 . . . . . {continuously movable moulds}
- 2045/0483 . . . . . {pivotally mounted mould halves ([B29C 2045/0425 takes precedence](#))}
- 2045/0491 . . . . . {both mould halves being shifted to the injection unit for obtaining nozzle touch}
- 45/06 . . . . . {mounted} on a turntable {, i.e. on a rotating support having a rotating axis parallel to the mould opening, closing or clamping direction}
- 45/062 . . . . . {carrying mould halves co-operating with fixed mould halves}
- 2045/065 . . . . . {continuously rotating turntables}
- 2045/067 . . . . . {one mould being openable during clamping of the other moulds}
- 45/07 . . . . . using movable injection units
- 2045/073 . . . . . {pivotable horizontal injection unit with a nozzle pushed against a mould half}
- 45/076 . . . . . {cooperating with two or more moulds}
- 45/08 . . . . . moving with the mould during the injection operation
- 45/10 . . . . . using moulds or injection units usable in different arrangements or combinations to each other
- 45/12 . . . . . using two or more fixed moulds, e.g. in tandem ([B29C 45/076 takes precedence](#))}
- 45/125 . . . . . {using a material distributing system}
- 45/13 . . . . . using two or more injection units co-operating with a single mould
- 2045/135 . . . . . {selectively injecting different materials in the same mould for making different articles in the same mould}
- 45/14 . . . . . incorporating preformed parts or layers, e.g. injection moulding around inserts or for coating articles ([B29C 45/1671 takes precedence](#))}
- 45/14008 . . . . . {Inserting articles into the mould ([B29C 45/14827 takes precedence](#))}
- 45/14016 . . . . . {Intermittently feeding endless articles, e.g. transfer films, to the mould ([B29C 45/14262 takes precedence](#))}
- 45/14024 . . . . . {and punching or cutting a portion from the endless articles during mould closing}
- 45/14032 . . . . . {Transferring the inserts from a storage space inside the mould to the mould cavity}
- 2045/1404 . . . . . {feeding inserts cut out from an endless sheet outside the mould}
- 2045/14049 . . . . . {feeding inserts by a swing arm}
- 2045/14057 . . . . . {feeding inserts wrapped on a core}
- 45/14065 . . . . . {Positioning or centering articles in the mould}
- 45/14073 . . . . . {using means being retractable during injection}
- 2045/14081 . . . . . {centering means retracted by the injection pressure}
- 2045/1409 . . . . . {using control means for retraction of the centering means}
- 2045/14098 . . . . . {fixing or clamping inserts having variable dimensions}

- 2045/14106 . . . {using electrostatic attraction or static electricity}
- 2045/14114 . . . {using an adhesive}
- 2045/14122 . . . {using fixed mould wall projections for centering the insert}
- 2045/14131 . . . {using positioning or centering means forming part of the insert}
- 2045/14139 . . . {positioning inserts having a part extending into a positioning cavity outside the mould cavity}
- 2045/14147 . . . {using pins or needles penetrating through the insert}
- 2045/14155 . . . {using vacuum or suction}
- 2045/14163 . . . {using springs being part of the positioning means}
- 2045/14172 . . . {using light to define the position of the insert}
- 45/1418 . . {the inserts being deformed or preformed, e.g. by the injection pressure}
- 2045/14188 . . . {trimming the article in the mould}
- 45/14196 . . . {the inserts being positioned around an edge of the injected part}
- 2045/14204 . . . . {the edges formed by an intermediate mould part}
- 2045/14213 . . . {deforming by gas or fluid pressure in the mould cavity}
- 45/14221 . . . {by tools, e.g. cutting means}
- 2045/14229 . . . . {deforming wire-like articles}
- 2045/14237 . . . {the inserts being deformed or preformed outside the mould or mould cavity}
- 2045/14245 . . . . {using deforming or preforming means outside the mould cavity}
- 2045/14254 . . . . {deforming or preforming endless articles outside the mould}
- 45/14262 . . . {Clamping or tensioning means for the insert}
- 2045/1427 . . . . {controlling the slip of the insert}
- 2045/14278 . . . . {controlling the tension of the insert}
- 2045/14286 . . . {means for heating the insert}
- 2045/14295 . . . . {the heating means being used for feeding the insert into the mould}
- 2045/14303 . . . {progressively transferring the insert from one mould wall to the other mould wall of the mould cavity}
- 45/14311 . . {using means for bonding the coating to the articles ([B29C 45/14795 takes precedence](#))}
- 2045/14319 . . . {bonding by a fusion bond}
- 2045/14327 . . . {anchoring by forcing the material to pass through a hole in the article}
- 45/14336 . . {Coating a portion of the article, e.g. the edge of the article ([B29C 45/14573](#) and [B29C 45/14598 take precedence](#))}
- 45/14344 . . . {Moulding in or through a hole in the article, e.g. outsert moulding}
- 2045/14352 . . . . {injecting into blind holes}
- 2045/1436 . . . . {coating hollow articles having holes passing through the wall}
- 2045/14368 . . . . {holes with means for anchoring the injected material}
- 45/14377 . . . {using an additional insert, e.g. a fastening element}
- 45/14385 . . . {Coating a portion of a bundle of inserts, e.g. making brushes}
- 2045/14393 . . . . {preventing leakage of injected material into tuft insertion holes of the mould}
- 2045/14401 . . . . {using a hot gas for forming a knob on the tuft end}
- 45/14409 . . . {Coating profiles or strips by injecting end or corner or intermediate parts}
- 45/14418 . . . {Sealing means between mould and article}
- 45/14426 . . . {Coating the end of wire-like or rod-like or cable-like or blade-like or belt-like articles}
- 45/14434 . . . {Coating brittle material, e.g. glass ([B29C 45/14377](#), [B29C 45/14418 take precedence](#))}
- 2045/14442 . . . {injecting a grill or grid on the insert}
- 2045/1445 . . . {injecting a part onto a blow moulded object}
- 2045/14459 . . . {injecting seal elements}
- 45/14467 . . {Joining articles or parts of a single article ([B29C 45/14377](#), [B29C 45/14385](#), [B29C 45/14581](#), [B29C 45/14614](#) and [B29C 45/006 take precedence](#))}
- 45/14475 . . . {Joining juxtaposed parts of a single article, e.g. edges of a folded container blank}
- 2045/14483 . . . . {overlapping edges of the juxtaposed parts}
- 45/14491 . . . {Injecting material between coaxial articles, e.g. between a core and an outside sleeve for making a roll}
- 2045/145 . . . . {making rolls}
- 45/14508 . . . {Joining juxtaposed sheet-like articles, e.g. for making trim panels}
- 2045/14516 . . . . {the transition area of juxtaposed parts being hidden in a groove of the moulded article}
- 2045/14524 . . . {making hollow articles}
- 2045/14532 . . . {injecting between two sheets}
- 2045/1454 . . . {injecting between inserts not being in contact with each other}
- 45/14549 . . {Coating rod-like, wire-like or belt-like articles ([B29C 45/14426 takes precedence](#))}
- 2045/14557 . . . {coating spliced fibres or cables, e.g. optical fiber splices or junctions}
- 45/14565 . . . {at spaced locations, e.g. coaxial-cable wires}
- 45/14573 . . . . {Coating the edge of the article, e.g. for slide-fasteners}
- 45/14581 . . . . {Coating the cross-over points of articles in the form of a network}
- 45/1459 . . {Coating annular articles}
- 45/14598 . . {Coating tubular articles}
- 2045/14606 . . . {Mould cavity sealing means}
- 45/14614 . . . {Joining tubular articles}
- 45/14622 . . . {Lining the inner or outer surface of tubular articles}
- 45/14631 . . {Coating reinforcements ([fibre reinforcements B29C 45/0005](#))}
- 45/14639 . . {for obtaining an insulating effect, e.g. for electrical components}
- 45/14647 . . . {Making flat card-like articles with an incorporated IC or chip module, e.g. IC or chip cards}
- 45/14655 . . . {connected to or mounted on a carrier, e.g. lead frame}
- 2045/14663 . . . . {the mould cavity walls being lined with a film, e.g. release film}
- 2045/14672 . . . . {moulding with different depths of the upper and lower mould cavity}
- 45/1468 . . . . {Plants therefor}
- 45/14688 . . {Coating articles provided with a decoration}
- 2045/14696 . . . {transparent decorated inserts}

- 2045/14704 . . . {ink decorations}
- 2045/14713 . . . {decorations in contact with injected material}
- 2045/14721 . . . {decorations transferred by diffusion or sublimation}
- 2045/14729 . . . {decorations not in contact with injected material}
- 2045/14737 . . . {decorations printed on the insert by a digital imaging technique}
- 2045/14745 . . . {in-line printing}
- 45/14754 . . {being in movable or releasable engagement with the coating, e.g. bearing assemblies}
- 2045/14762 . . . {using shrinkage}
- 2045/1477 . . . {Removable inserts, e.g. the insert being peeled off after moulding}
- 45/14778 . . {the article consisting of a material with particular properties, e.g. porous, brittle}
- 45/14786 . . . {Fibrous material or fibre containing material, e.g. fibre mats or fibre reinforced material}
- 45/14795 . . . {Porous or permeable material, e.g. foam}
- 2045/14803 . . . . {the injected material entering minute pores}
- 45/14811 . . . {Multilayered articles ([B29C 45/14827 takes precedence](#))}
- 45/14819 . . {the inserts being completely encapsulated}
- 45/14827 . . {using a transfer foil detachable from the insert}
- 45/14836 . . {Preventing damage of inserts during injection, e.g. collapse of hollow inserts, breakage ([B29C 45/14434 takes precedence](#))}
- 2045/14844 . . . {Layers protecting the insert from injected material}
- 2045/14852 . . {incorporating articles with a data carrier, e.g. chips ([memory cards, chip cards B29L 2017/006](#))}
- 2045/1486 . . {Details, accessories and auxiliary operations}
- 2045/14868 . . . {Pretreatment of the insert, e.g. etching, cleaning}
- 2045/14877 . . . . {preheating or precooling the insert for non-deforming purposes}
- 2045/14885 . . . . {by plasma treatment}
- 2045/14893 . . . {Preventing defects relating to shrinkage of inserts or coating material}
- 2045/14901 . . . {Coating a sheet-like insert smaller than the dimensions of the adjacent mould wall}
- 2045/14909 . . . . {the edge of the sheet-like insert being hidden, e.g. in a groove or protruding into the injected material}
- 2045/14918 . . . . {in-mould-labelling}
- 2045/14926 . . . . {multiple labels in the same cavity}
- 2045/14934 . . . {Preventing penetration of injected material between insert and adjacent mould wall ([sealing means between mould and article B29C 45/14418](#))}
- 2045/14942 . . . {Floating inserts, e.g. injecting simultaneously onto both sides of an insert through a pair of opposed gates}
- 2045/1495 . . . {Coating undercut inserts}
- 2045/14959 . . . {Flashing the injected material to the outside of the mould cavity for any purpose}
- 2045/14967 . . . {Injecting through an opening of the insert}
- 2045/14975 . . . . {the injection nozzle penetrating through the insert}
- 2045/14983 . . . {Bursting or breakthrough of the insert by the injection pressure}
- 2045/14991 . . . {Submerged burrs, e.g. using protruding mould parts forming a cavity in which the burr on the insert is formed for preventing surface defects}
- 45/16 . . Making multilayered or multicoloured articles {([B29C 45/0062 takes precedence; feeding colouring materials into the injection unit B29C 45/1816](#))}
- 2045/1601 . . {the injected materials not being adhered or bonded to each other ([B29C 45/0017 takes precedence](#))}
- 45/1603 . . {Multi-way nozzles specially adapted therefor}
- 45/1604 . . . {using a valve urged by the injection pressure}
- 45/1606 . . . {using a rotatable valve}
- 45/1607 . . . {having at least three different ways}
- 2045/1609 . . . {having independent heating or cooling means for each way}
- 2045/161 . . . {using a hollow needle valve through which one material is injected}
- 2045/1612 . . . {using needle valves with at least four positions}
- 2045/1614 . . . {side-by-side flow of materials in the same channel}
- 45/1615 . . {The materials being injected at different moulding stations}
- 2045/1617 . . . {using stack moulds}
- 45/1618 . . . {using an auxiliary treatment station, e.g. for cooling or ejecting ([B29C 45/1628 takes precedence](#))}
- 45/162 . . . {using means, e.g. mould parts, for transferring an injected part between moulding stations}
- 2045/1621 . . . . {the transfer means operating independently from the injection mould cavity, i.e. during injection the transfer means are completely outside the mould cavity}
- 2045/1623 . . . . {transfer by a slidable element forming a part of both cavities}
- 45/1625 . . . {Injecting parison-like articles}
- 2045/1626 . . . . {using a cooling station}
- 45/1628 . . . {using a mould carrier rotatable about an axis perpendicular to the opening and closing axis of the moulding stations}
- 2045/1629 . . . . {turrets with incorporated ejection means}
- 2045/1631 . . . . {turrets fixed with regard to the machine frame}
- 2045/1632 . . . . {injection units supported by a movable mould plate}
- 45/1634 . . {with a non-uniform dispersion of the moulding material in the article, e.g. resulting in a marble effect}
- 45/1635 . . {using displaceable mould parts, e.g. retractable partition between adjacent mould cavities}
- 2045/1637 . . . {the first injected part and the movable mould part being movable together}
- 45/1639 . . . {Removable partitions between adjacent mould cavity portions}
- 45/164 . . {The moulding materials being injected simultaneously}
- 45/1642 . . {having a "sandwich" structure ([B29C 45/1603 takes precedence](#))}
- 45/1643 . . . {from at least three different materials or with at least four layers}
- 45/1645 . . . {Injecting skin and core materials from the same injection cylinder, e.g. mono-sandwich moulding}



- 45/1646 . . . {Injecting parison-like articles ([B29C 45/1643 takes precedence](#))}
- 2045/1648 . . . . {the parison core layer being a barrier material}
- 2045/165 . . . . {the parison core layer comprising recycled or scrap material}
- 2045/1651 . . . . {Independent injection runners or nozzles}
- 2045/1653 . . . . {using a core injection nozzle penetrating through the skin or into the mould cavity}
- 2045/1654 . . . . {whereby the core material is penetrating through the skin}
- 2045/1656 . . . . {Injecting the skin material through the central passage of the multiway nozzle}
- 45/1657 . . {using means for adhering or bonding the layers or parts to each other ([mechanical anchoring B29C 37/0082](#))}
- 2045/1659 . . . . {Fusion bonds}
- 2045/166 . . . . {Roughened surface bonds}
- 2045/1662 . . . . {plasma roughened surface bonds}
- 2045/1664 . . . . {Chemical bonds}
- 2045/1665 . . . . {Shrinkage bonds}
- 2045/1667 . . . . {Deformation bonds}
- 2045/1668 . . . . {Penetration bonds}
- 2045/167 . . {injecting the second layer through the first layer}
- 45/1671 . . {with an insert}
- 2045/1673 . . . . {injecting the first layer, then feeding the insert, then injecting the second layer}
- 45/1675 . . {using exchangeable mould halves}
- 45/1676 . . {using a soft material and a rigid material, e.g. making articles with a sealing part}
- 2045/1678 . . . . {first moulding the soft material}
- 45/1679 . . {applying surface layers onto injection-moulded substrates inside the mould cavity, e.g. in-mould coating [IMC] ([applying surface layers after ejection B29C 45/0053](#))}
- 2045/1681 . . {one layer penetrating at one or more areas through another layer}
- 2045/1682 . . {preventing defects}
- 45/1684 . . {Injecting parison-like articles ([B29C 45/1625](#), [B29C 45/1643](#) and [B29C 45/1646 take precedence](#))}
- 2045/1685 . . {mounting of the additional injection unit}
- 2045/1687 . . {preventing leakage of second injected material from the mould cavity}
- 2045/1689 . . {injecting layers having identical injection cycle times}
- 2045/169 . . {injecting electrical circuits, e.g. one layer being made of conductive material}
- 2045/1692 . . {one layer comprising fibres}
- 2045/1693 . . {shaping the first molding material before injecting the second molding material, e.g. by cutting, folding}
- 2045/1695 . . {injecting ceramic powder layers and plastic material layers}
- 2045/1696 . . {injecting metallic layers and plastic material layers}
- 2045/1698 . . {multicoloured articles moulded in one step ([non-uniform dispersion of colours B29C 45/1634](#))}
- 45/17 . . Component parts, details or accessories; Auxiliary operations
- 45/1701 . . {using a particular environment during moulding, e.g. moisture-free or dust-free}
- 2045/1702 . . . . {dissolving or absorbing a fluid in the plastic material}
- 45/1703 . . {Introducing an auxiliary fluid into the mould ([B29C 45/1701 takes precedence](#))}
- 45/1704 . . . . {the fluid being introduced into the interior of the injected material which is still in a molten state, e.g. for producing hollow articles ([B29C 45/1732](#) and [B29C 45/1734 take precedence](#); [injection blow-moulding B29C 49/06](#))}
- 45/1705 . . . . {using movable mould parts}
- 45/1706 . . . . {using particular fluids or fluid generating substances}
- 2045/1707 . . . . . {using a liquid, e.g. water}
- 2045/1708 . . . . . {removing the liquid from the hollow}
- 2045/1709 . . . . . {using a cooling fluid}
- 2045/171 . . . . . {using an evaporating substance}
- 45/1711 . . . . {and removing excess material from the mould cavity by the introduced fluid, e.g. to an overflow cavity}
- 2045/1712 . . . . . {plastic material flowing back into the injection unit}
- 2045/1713 . . . . . {using several overflow cavities}
- 2045/1714 . . . . . {overflow cavities provided with heating means}
- 2045/1715 . . . . . {Filled hollows}
- 2045/1717 . . . . {Temperature controlled mould parts to control the location or configuration of the hollow}
- 2045/1718 . . . . {sealing or closing the fluid injection opening}
- 2045/1719 . . . . {making tubular articles}
- 2045/172 . . . . {making roof racks for vehicles or parts thereof}
- 2045/1721 . . . . {making wheels}
- 2045/1722 . . . . {injecting fluids containing plastic material}
- 2045/1723 . . . . {using fibre reinforcements}
- 2045/1724 . . . . {hollows used as conduits}
- 2045/1725 . . . . {making hollow seals}
- 2045/1726 . . . . {moving the fluid through the hollow using a fluid inlet and a fluid outlet}
- 2045/1727 . . . . {using short shots of moulding material}
- 2045/1728 . . . . {injecting fluid from an end of the mould cavity and in the longitudinal direction thereof}
- 2045/1729 . . . . {fluid venting means}
- 2045/173 . . . . {using a plurality of fluid injection nozzles}
- 2045/1731 . . . . {vacuum or underpressure for forming the hollow}
- 45/1732 . . . . {Control circuits therefor}
- 45/1734 . . . . {Nozzles therefor}
- 45/1735 . . . . {Nozzles for introducing the fluid through the mould gate, e.g. incorporated in the injection nozzle}
- 45/1736 . . . . {provided with small holes permitting the flow of gas therethrough, e.g. using a porous element of sintered material ([B29C 45/1735 takes precedence](#))}
- 2045/1737 . . . . {Pin-in-sleeve devices}
- 2045/1738 . . . . {using a valve mounted in movable valve sleeve}
- 2045/1739 . . . . {controlling the temperature or heat-transfer in fluid injection nozzles}

- 45/174 . . . {Applying a pressurised fluid to the outer surface of the injected material inside the mould cavity, e.g. for preventing shrinkage marks}
- 2045/1741 . . . . {Seals preventing pressurized fluid to escape from the mould cavity ([mould seals B29C 45/2608](#))}
- 45/1742 . . {Mounting of moulds; Mould supports ([mounting of exchangeable mould inserts B29C 45/2675](#))}
- 45/1743 . . . {using mounting means projecting from the back side of the mould or from the front side of the mould support}
- 45/1744 . . . {Mould support platens}
- 2045/1745 . . . {using vacuum means}
- 2045/1746 . . . {using magnetic means}
- 45/1747 . . {Tie-rod connections}
- 45/1748 . . {Retractable tie-rods}
- 2045/175 . . . {using the movable mould plate for extracting a tie rod}
- 45/1751 . . {Adjustment means allowing the use of moulds of different thicknesses}
- 2045/1752 . . . {using the mould clamping means for displacing the rear platen}
- 45/1753 . . {Cleaning or purging, e.g. of the injection unit ([B29C 45/24 takes precedence](#))}
- 2045/1754 . . . {purging cooling channels}
- 45/1755 . . . {Means for receiving or discharging purged material; Purge shields}
- 45/1756 . . {Handling of moulds or mould parts, e.g. mould exchanging means ([moulds per se B29C 45/26](#))}
- 2045/1757 . . . {common exchange means for several injection machines}
- 2045/1758 . . . {exchanging stampers}
- 45/1759 . . {Removing sprues from sprue-channels}
- 45/176 . . {Exchanging the injection unit or parts thereof}
- 45/1761 . . {Means for guiding movable mould supports or injection units on the machine base or frame; Machine bases or frames ([B29C 45/1747 takes precedence](#))}
- 2045/1762 . . . {compensating frame distortion proportional to the mould clamping force}
- 2045/1763 . . . {preventing distortion of the machine part guiding the movable mould}
- 2045/1764 . . . {Guiding means between the movable mould plate and tie rods}
- 2045/1765 . . . {Machine bases}
- 2045/1767 . . . . {connecting means for machine base parts}
- 2045/1768 . . . {constructions of C-shaped frame elements}
- 45/1769 . . {Handling of moulded articles or runners, e.g. sorting, stacking, grinding of runners}
- 2045/177 . . . {stacking moulded articles}
- 45/1771 . . . {Means for guiding or orienting articles while dropped from the mould, e.g. guide rails or skirts}
- 2045/1772 . . . . {sorting different articles}
- 45/1773 . . {Means for adjusting or displacing the injection unit into different positions, e.g. for co-operating with different moulds ([B29C 45/1781 takes precedence](#))}
- 45/1774 . . {Display units or mountings therefor; Switch cabinets}
- 45/1775 . . {Connecting parts, e.g. injection screws, ejectors, to drive means}
- 2045/1776 . . . {magnetic connecting means}
- 45/1777 . . {Nozzle touch mechanism}
- 2045/1778 . . . {separate drive means for moving and producing the touch force}
- 2045/1779 . . . {using chains or the like as drive transmission means for the movement of the injection unit}
- 45/178 . . {Means disposed outside the mould for unscrewing threaded articles, e.g. chuck devices ([moulds with incorporated unscrewing drive means B29C 45/262](#))}
- 45/1781 . . {Aligning injection nozzles with the mould sprue bush}
- 45/1782 . . {Mounting or clamping means for heating elements or thermocouples}
- 2045/1784 . . {Component parts, details or accessories not otherwise provided for; Auxiliary operations not otherwise provided for}
- 2045/1785 . . . {Movement of a part, e.g. opening or closing movement of the mould, generating fluid pressure in a built-in fluid pressure generator}
- 2045/1786 . . . {Electric wire or cable guides, e.g. for manifolds}
- 2045/1787 . . . {Mould parts driven by pressure of injected material ([B29C 2045/14081 takes precedence](#))}
- 2045/1788 . . . {Preventing tilting of movable mould plate during closing or clamping}
- 2045/1789 . . . . {using weight compensating means for the movable mould half}
- 2045/179 . . . {Frames or machine parts made of concrete}
- 2045/1791 . . . {Means for spacing or distancing mould supporting plates, e.g. for mould exchange}
- 2045/1792 . . . {Machine parts driven by an electric motor, e.g. electric servomotor}
- 2045/1793 . . . . {by an electric linear motor ([linear motors in general H02K 41/02](#))}
- 2045/1794 . . . . {by a rotor or directly coupled electric motor, e.g. using a tubular shaft motor ([for driving axially movable screws B29C 2045/5024](#))}
- 2045/1795 . . . {Means for detecting resin leakage or drooling from the injection nozzle}
- 2045/1796 . . . {Moulds carrying mould related information or codes, e.g. bar codes, counters}
- 2045/1797 . . . {Machine parts provided with a shroud or cover or shield, e.g. for preventing oil or dust scattering ([used as safety device B29C 45/84; for guiding or orienting ejected articles B29C 45/1771; for obtaining a particular moulding environment B29C 45/1701; for obtaining a vacuum environment B29C 45/34](#))}
- 2045/1798 . . . {Using spring tension to drive movable machine parts}
- 45/18 . . Feeding the material into the injection moulding apparatus {, i.e. feeding the non-plastified material into the injection unit}
- 45/1808 . . . {Feeding measured doses}
- 45/1816 . . . {Feeding auxiliary material, e.g. colouring material}
- 2045/1825 . . . . {feeding auxiliary material for either skin or core of the injected article}
- 2045/1833 . . . . {recycling sprues or runners}
- 2045/1841 . . . . {into runner channel or runner nozzle}
- 2045/185 . . . . {controlling the amount of auxiliary material}
- 45/1858 . . . {Changing the kind or the source of material, e.g. using a plurality of hoppers}

45/1866	. . . {Feeding multiple materials ( <a href="#">B29C 45/1816 takes precedence</a> )}	2045/264	. . . . . {Holders retaining the inner periphery of the stamper}
2045/1875	. . . {Hoppers connected to a feed screw}	45/2642	. . . . . {Heating or cooling means therefor}
2045/1883	. . . {directly injecting moulding material from the chemical production plant into the mould without granulating}	2045/2644	. . . . . {for the outer peripheral ring}
2045/1891	. . . {Means for detecting presence or level of raw material inside feeding ducts, e.g. level sensors inside hoppers}	2045/2646	. . . . . {Means for adjusting the axial dimension of the mould cavity}
45/20	. . Injection nozzles {( <a href="#">B29C 45/1603 takes precedence</a> )}	2045/2648	. . . . . {Outer peripheral ring constructions}
2045/202	. . . {Laterally adjustable nozzle or nozzle tip mountings}	2045/2651	. . . . . {using a plurality of mould cavities}
2045/205	. . . {Elongated nozzle openings}	2045/2653	. . . . . {using two stampers}
2045/207	. . . {Preventing stringing of the moulding material}	2045/2655	. . . . . {Means for adjusting the radial dimension of the mould cavity}
45/22	. . . Multiple nozzle systems	2045/2657	. . . . . {Drive means for the outer peripheral ring}
45/23	. . . Feed stopping equipment	2045/2659	. . . . . {for making substrates for laminated disks}
45/231	. . . . . {Needle valve systems therefor}	2045/2661	. . . . . {The thickness of the mould cavity being changeable in radial direction ( <a href="#">B29C 2045/2667 takes precedence</a> )}
45/232	. . . . . {comprising closing means disposed outside the nozzle}	2045/2663	. . . . . {Maintaining the axial dimension of the mould cavity during injection}
45/234	. . . . . {Valves opened by the pressure of the moulding material ( <a href="#">B29C 45/231 takes precedence</a> )}	2045/2665	. . . . . {using vacuum means for holding the disc on one of the mould walls during opening of the mould}
2045/235	. . . . . {axially movable inclined or orthogonal valves}	2045/2667	. . . . . {Particular inner or outer peripheral portions of the substrate}
2045/237	. . . . . {two or more cooperating valve elements}	45/2669	. . . . . {with means for removing excess material, e.g. with overflow cavities ( <a href="#">B29C 45/1711 takes precedence</a> )}
2045/238	. . . . . {Injection nozzles extending into the sprue channel or <i>vice versa</i> }	2045/2671	. . . . . {Resin exit gates or bleeder passages}
45/24	. . . Cleaning equipment	45/2673	. . . . . {with exchangeable mould parts, e.g. cassette moulds ( <a href="#">B29C 45/1756 takes precedence</a> )}
45/26	. . Moulds	45/2675	. . . . . {Mounting of exchangeable mould inserts}
45/2602	. . . {Mould construction elements}	2045/2677	. . . . . {The exchangeable mould parts being combinable or rearrangeable in different ways}
2045/2604	. . . . . {Latching means for successive opening or closing of mould plates}	2045/2679	. . . . . {Simultaneously producing different products}
45/2606	. . . . . {Guiding or centering means}	45/2681	. . . . . {with rotatable mould parts}
45/2608	. . . {Mould seals}	2045/2683	. . . . . {Plurality of independent mould cavities in a single mould}
45/261	. . . {having tubular mould cavities}	2045/2685	. . . . . {filled with different materials}
45/2612	. . . . . {for manufacturing tubular articles with an annular groove}	2045/2687	. . . . . {controlling the filling thereof ( <a href="#">B29C 2045/2691 takes precedence</a> )}
45/2614	. . . . . {for manufacturing bent tubular articles using an undercut forming mould core}	2045/2689	. . . . . {separate independent mould halves mounted on one plate}
45/2616	. . . {having annular mould cavities}	2045/2691	. . . . . {sequentially filled}
45/2618	. . . {having screw-threaded mould walls}	2045/2693	. . . . . {Mould cores with a built-in injection nozzle}
45/262	. . . . . {provided with unscrewing drive means ( <a href="#">unscrewing means outside the mould B29C 45/178</a> )}	2045/2695	. . . . . {injecting articles with varying wall thickness, e.g. for making a tear line}
45/2622	. . . . . {for moulding interrupted screw threads}	2045/2697	. . . . . {Deformed geometry of the cavity}
45/2624	. . . {provided with a multiplicity of wall-like cavities connected to a common cavity, e.g. for battery cases}	45/27	. . . Sprue channels {Runner channels or runner nozzles}
45/2626	. . . {provided with a multiplicity of narrow cavities connected to a common cavity, e.g. for brushes, combs}	45/2701	. . . . . {Details not specific to hot or cold runner channels ( <a href="#">B29C 45/2725 takes precedence</a> )}
45/2628	. . . {with mould parts forming holes in or through the moulded article, e.g. for bearing cages}	45/2703	. . . . . {Means for controlling the runner flow, e.g. runner switches, adjustable runners or gates}
45/263	. . . {with mould wall parts provided with fine grooves or impressions, e.g. for record discs}	45/2704	. . . . . {Controlling the filling rates or the filling times of two or more mould cavities by controlling the cross section or the length of the runners or the gates}
45/2632	. . . . . {Stampers; Mountings thereof}	2045/2706	. . . . . {rotatable sprue bushings or runner channels for controlling runner flow in one cavity}
2045/2634	. . . . . {mounting layers between stamper and mould or on the rear surface of the stamper}	45/2708	. . . . . {Gates ( <a href="#">B29C 45/2703 takes precedence</a> )}
2045/2636	. . . . . {insulating layers}		
2045/2638	. . . . . {Magnetic means for mounting stampers}		

2045/2709	. . . . .	{ with a plurality of mould cavity inlets in close proximity }	2045/2772	. . . . .	{ Means for fixing the nozzle to the manifold }
45/2711	. . . . .	{ Gate inserts }	2045/2774	. . . . .	{ The nozzle head or the collar portion and central portion being made of different parts or materials }
2045/2712	. . . . .	{ Serial gates for moulding articles in successively filled serial mould cavities }	2045/2775	. . . . .	{ Nozzles or parts thereof being mountable or exchangeable from the front side of the mould half }
2045/2714	. . . . .	{ elongated, e.g. film-like, annular }	2045/2777	. . . . .	{ Means for controlling heat flow or temperature distribution in the nozzle }
2045/2716	. . . . .	{ The gate axis being perpendicular to main injection axis, e.g. injecting into side walls of a container }	2045/2779	. . . . .	{ Nozzles with a plurality of outlets }
2045/2717	. . . . .	{ Reconfigurable runner channels }	45/278	. . . . .	{ Nozzle tips ( <a href="#">B29C 45/2735</a> takes precedence) }
2045/2719	. . . . .	{ Fixing or locking of nozzles or sprue bushings in the mould }	2045/2782	. . . . .	{ Nozzle tips metallurgically bonded to the nozzle body }
2045/272	. . . . .	{ Part of the nozzle, bushing or runner in contact with the injected material being made from ceramic material }	2045/2783	. . . . .	{ Nozzle tips with a non-axial outlet opening of the melt channel }
2045/2722	. . . . .	{ Nozzles or runner channels provided with a pressure sensor }	2045/2785	. . . . .	{ Nozzle tips with high thermal conductivity }
2045/2724	. . . . .	{ Preventing stringing of the moulding material }	2045/2787	. . . . .	{ Nozzle tips made of at least 2 different materials }
45/2725	. . . . .	{ Manifolds }	2045/2788	. . . . .	{ Nozzles having a polygonal cross section }
45/2727	. . . . .	{ Modular manifolds; Connections between spaced manifold elements }	2045/279	. . . . .	{ Controlling the flow of material of two or more nozzles or gates to a single mould cavity }
2045/2729	. . . . .	{ with thermal expansion }	2045/2791	. . . . .	{ Alignment means between nozzle and manifold }
2045/273	. . . . .	{ stacked manifolds }	2045/2793	. . . . .	{ Means for providing access to the runner system }
2045/2732	. . . . .	{ sealing means between them }	2045/2795	. . . . .	{ Insulated runners }
2045/2733	. . . . .	{ Inserts, plugs, bushings }	2045/2796	. . . . .	{ Axially movable nozzles or nozzle tips }
45/2735	. . . . .	{ for non-coaxial gates, e.g. for edge gates }	2045/2798	. . . . .	{ for compensating thermal expansion }
45/2737	. . . . .	{ Heating or cooling means therefor ( <a href="#">B29C 45/7331</a> takes precedence) }	45/28	. . . . .	Closure devices therefor
45/2738	. . . . .	{ specially adapted for manifolds }	45/2803	. . . . .	{ comprising a member with an opening or the injection nozzle movable into or out of alignment with the sprue channel or mould gate }
2045/274	. . . . .	{ Thermocouples or heat sensors }	45/2806	. . . . .	{ consisting of needle valve systems ( <a href="#">B29C 45/2896</a> takes precedence) }
2045/2741	. . . . .	{ Plurality of independent thermocouples or heat sensors }	45/281	. . . . .	{ Drive means therefor }
2045/2743	. . . . .	{ Electrical heating element constructions }	2045/2813	. . . . .	{ Common drive means for several needle valves }
2045/2745	. . . . .	{ Film-like electrical heaters }	2045/2817	. . . . .	{ Several valve pin drive cylinders connected to the fluid distributor }
2045/2746	. . . . .	{ Multilayered electrical heaters }	2045/282	. . . . .	{ Needle valves driven by screw and nut means }
2045/2748	. . . . .	{ Insulating layers covering the electrical heating element }	2045/2824	. . . . .	{ Needle valves driven by an electric motor }
2045/275	. . . . .	{ Planar heating or cooling elements }	2045/2827	. . . . .	{ Needle valves driven by an annular piston mounted around the nozzle }
2045/2751	. . . . .	{ Electrical power supply connections }	2045/2831	. . . . .	{ Needle valves driven by a cam }
2045/2753	. . . . .	{ Heating means and cooling means, e.g. heating the runner nozzle and cooling the nozzle tip }	2045/2834	. . . . .	{ Needle valves driven by a lever }
2045/2754	. . . . .	{ Plurality of independent heating or cooling means, e.g. independently controlling the heating of several zones of the nozzle, ( <a href="#">B29C 2045/2753</a> takes precedence) }	2045/2837	. . . . .	{ Needle valves driven by rack and pinion }
45/2756	. . . . .	{ Cold runner channels }	2045/2841	. . . . .	{ Needle valves driven by a plurality of coaxial pistons }
45/2758	. . . . .	{ Means for preventing drooling by decompression of the moulding material }	2045/2844	. . . . .	{ Needle valves driven by racks only }
2045/2759	. . . . .	{ Nozzle centering or guiding means }	2045/2848	. . . . .	{ having an adjustable stroke length }
2045/2761	. . . . .	{ Seals between nozzle and mould or gate }	2045/2851	. . . . .	{ Lateral movement between drive piston and needle valve }
2045/2762	. . . . .	{ Seals between nozzle and manifold }	2045/2855	. . . . .	{ intersecting the nozzle or runner channel }
2045/2764	. . . . .	{ Limited contact between nozzle and mould }	2045/2858	. . . . .	{ Materials or coatings therefor }
2045/2766	. . . . .	{ Heat insulation between nozzle and mould }	2045/2862	. . . . .	{ being tubular }
2045/2767	. . . . .	{ the heat insulation being provided with an axial opening being part of the melt flow channel }			
2045/2769	. . . . .	{ Insulating layer of injected material }			
2045/277	. . . . .	{ Spacer means or pressure pads between manifold and mould plates }			



2045/2865	. . . . .	{having position detecting means}	2045/386	. . . . .	{returning the cutted sprue into the injection nozzle}
2045/2868	. . . . .	{with an incorporated heat pipe}	2045/388	. . . . .	{Locking pins for retaining the sprue}
2045/2872	. . . . .	{with at least three positions, e.g. two different open positions to control the melt flow}	45/40	. . . . .	Removing or ejecting moulded articles
2045/2875	. . . . .	{Preventing rotation of the needle valve}	45/4005	. . . . .	{Ejector constructions; Ejector operating mechanisms ( <a href="#">B29C 45/44</a> takes precedence)}
2045/2879	. . . . .	{Back flow of material into nozzle channel}	45/401	. . . . .	{Ejector pin constructions or mountings}
2045/2882	. . . . .	{closing by a movement in the counterflow direction}	2045/4015	. . . . .	{Ejector pins provided with sealing means}
2045/2886	. . . . .	{closing at a distance from the gate}	2045/4021	. . . . .	{Adjustable ejector pins}
2045/2889	. . . . .	{Sealing guide bushings therefor}	2045/4026	. . . . .	{Ejectors with internal cooling}
2045/2893	. . . . .	{Multiple coaxial needle valves}	2045/4031	. . . . .	{driven by a lever}
45/2896	. . . . .	{extending in or through the mould cavity, e.g. valves mounted opposite the sprue channel}	2045/4036	. . . . .	{driven by a screw and nut mechanism}
45/30	. . . . .	Flow control means disposed within the sprue channel, e.g. "torpedo" construction	2045/4042	. . . . .	{driven by rack and pinion means}
2045/302	. . . . .	{Torpedoes in the sprue channel for heating the melt of cross-linkable material}	2045/4047	. . . . .	{driven by a crank or eccentric}
2045/304	. . . . .	{Adjustable torpedoes}	2045/4052	. . . . .	{Ejector boxes}
2045/306	. . . . .	{Movable torpedoes}	2045/4057	. . . . .	{the ejecting surface being large with regard to the surface of the article}
2045/308	. . . . .	{Mixing or stirring devices}	2045/4063	. . . . .	{preventing damage to articles caused by the ejector}
45/32	. . . . .	having several axially spaced mould cavities {, i.e. for making several separated articles}	2045/4068	. . . . .	{using an auxiliary mould part carrying the moulded article and removing it from the mould}
45/322	. . . . .	{Runner systems for distributing the moulding material to the stacked mould cavities}	2045/4073	. . . . .	{Ejection devices located outside the injection moulding machine}
2045/324	. . . . .	{Linked ejection means}	2045/4078	. . . . .	{using stripping means}
2045/326	. . . . .	{Supporting means for the central mould plate}	2045/4084	. . . . .	{Progressive ejection}
2045/328	. . . . .	{having a movable mould plate between two fixed mould plates}	2045/4089	. . . . .	{Hollow articles retained in the female mould during mould opening}
45/33	. . . . .	having transversely, e.g. radially, movable mould parts	2045/4094	. . . . .	{Ejectors located on the fixed mould half}
45/332	. . . . .	{Mountings or guides therefor; Drives therefor}	45/42	. . . . .	using means movable from outside the mould between mould parts {, e.g. robots}
2045/334	. . . . .	{several transversely movable mould parts driven by a single drive means}	45/4208	. . . . .	{and driven by the movable mould part}
2045/336	. . . . .	{Cam drives}	2045/4216	. . . . .	{releasable drive connections between the robot and the movable mould}
2045/338	. . . . .	{Mould parts with combined axial and transversal movements}	45/4225	. . . . .	{Take-off members or carriers for the moulded articles, e.g. grippers}
45/34	. . . . .	having venting means	2045/4233	. . . . .	{loading or holding moulded articles in take-off member by fluid ejection}
45/345	. . . . .	{using a porous mould wall or a part thereof, e.g. made of sintered metal}	2045/4241	. . . . .	{Auxiliary means for removing moulded articles from the robot}
45/36	. . . . .	having means for locating or centering cores	2045/425	. . . . .	{Single device for unloading moulded articles and loading inserts into the mould}
2045/363	. . . . .	{using a movable core or core part}	2045/4258	. . . . .	{Article removing means movable into a closed mould}
2045/366	. . . . .	{using retractable pins}	2045/4266	. . . . .	{Robot grippers movable along three orthogonal axes}
45/37	. . . . .	Mould cavity walls {, i.e. the inner surface forming the mould cavity, e.g. linings}	2045/4275	. . . . .	{Related movements between the robot gripper and the movable mould or ejector}
45/372	. . . . .	{provided with means for marking or patterning, e.g. numbering articles}	2045/4283	. . . . .	{Means for coupling robots to the injection moulding machine}
45/374	. . . . .	{for displaying altering indicia, e.g. data, numbers}	2045/4291	. . . . .	{Robots mounted on a tie rod}
45/376	. . . . .	{adjustable ( <a href="#">B29C 45/374</a> takes precedence)}	45/43	. . . . .	using fluid under pressure
2045/378	. . . . .	{built by a stack of modular elements}	45/435	. . . . .	{introduced between a mould core and a hollow resilient undercut article, e.g. bellows}
45/38	. . . . .	Cutting-off equipment for sprues or ingates	45/44	. . . . .	for undercut articles
45/382	. . . . .	{disposed outside the mould}	45/4407	. . . . .	{by flexible movement of undercut portions of the articles}
2045/384	. . . . .	{cutting the sprue by a plunger movable into the runner channel}	2045/4414	. . . . .	{Flexible undercut parts divided into segments}
			45/4421	. . . . .	{using expansible or collapsible cores}

2045/4428	. . . . .	{ driven by the moulded article during ejection thereof }	2045/5048	. . . . .	{ screws axially driven and rotated by a drive shaft having a screw threaded part and spline part }
45/4435	. . . . .	{ using inclined, tiltable or flexible undercut forming elements driven by the ejector means }	2045/5052	. . . . .	{ screws axially driven by a rotatable nut cooperating with a fixed screw shaft }
2045/4442	. . . . .	{ Flexible undercut forming elements }	2045/5056	. . . . .	{ screws axially driven by a rotatable screw shaft cooperating with a fixed nut }
2045/445	. . . . .	{ using the movable undercut forming element for ejection of the moulded article }	2045/506	. . . . .	{ using a hydraulic transmission between drive motor and the axially movable screw }
45/4457	. . . . .	{ using fusible, soluble or destructible cores }	2045/5064	. . . . .	{ coupling means between rotation motor and rectilinear drive motor }
2045/4464	. . . . .	{ injecting the core and the undercut article in separate cavities }	2045/5068	. . . . .	{ mechanical drive means in series with hydraulic drive means for axially movable screw }
45/4471	. . . . .	{ using flexible or pivotable undercut forming elements (B29C 45/4435 takes precedence) }	2045/5072	. . . . .	{ using a drive screw comprising screw parts having opposite thread directions }
45/4478	. . . . .	{ using non-rigid undercut forming elements, e.g. elastic or resilient }	2045/5076	. . . . .	{ using a single drive motor for rotary and for axial movements of the screw }
2045/4485	. . . . .	{ the undercut forming mould part being rotatable into the space made available by the translation movement of another mould part }	2045/508	. . . . .	{ idle or dead stroke elements between injection screw and drive means }
2045/4492	. . . . .	{ preventing damage or deformation of undercut articles during ejection }	2045/5084	. . . . .	{ screws axially driven by roller elements }
45/46	. . . . .	Means for plasticising or homogenising the moulding material or forcing it into the mould {(combined with mould opening, closing or clamping devices B29C 45/70) }	2045/5088	. . . . .	{ screws axially and rotatably driven by a piston }
45/461	. . . . .	{ Injection of measured doses }	45/5092	. . . . .	{ Intrusion moulding, i.e. the screw rotates during injection }
45/462	. . . . .	{ Injection of preformed charges of material }	2045/5096	. . . . .	{ decompression of the moulding material by retraction or opposite rotation of the screw }
45/463	. . . . .	{ using packaged or wrapped charges }	45/52	. . . . .	Non-return devices
45/464	. . . . .	{ using a rotating plasticising or injection disc }	2045/522	. . . . .	{ Spring biased check rings }
2045/465	. . . . .	{ using pumps for injecting the material into the mould }	2045/524	. . . . .	{ Flexible valves }
2045/466	. . . . .	{ supplying the injection unit directly by a compounder }	2045/526	. . . . .	{ Abrasion resistant means in the screw head or non-return device }
2045/467	. . . . .	{ injecting material into the mould by sudden expansion of compressed material in the injection unit }	2045/528	. . . . .	{ Mixing means forming part of or in close proximity to the non-return valve }
2045/468	. . . . .	{ using a fluid as directly acting injection means }	45/53	. . . . .	using injection ram or piston
45/47	. . . . .	using screws (B29C 45/54 takes precedence)	45/531	. . . . .	{ Drive means therefor }
45/48	. . . . .	Plasticising screw and injection screw { comprising two separate screws }	45/532	. . . . .	{ using a hollow injection ram co-operating with a coaxial screw }
45/50	. . . . .	Axially movable screw	2045/533	. . . . .	{ using a continuously rotating plasticising screw }
2045/5004	. . . . .	{ the forward screw end provided with an injection ram }	45/535	. . . . .	{ using two or more cooperating injection rams, e.g. coaxially or alternately operating rams }
45/5008	. . . . .	{ Drive means therefor }	2045/536	. . . . .	{ rotatable injection plungers }
2045/5012	. . . . .	{ screws axially driven by a toggle mechanism }	2045/537	. . . . .	{ the injection plunger cooperating with a coaxial hollow transfer plunger }
2045/5016	. . . . .	{ screws axially driven by a lever mechanism }	2045/538	. . . . .	{ the plunger being part of the mould cavity wall after injection }
2045/502	. . . . .	{ screws axially driven by a crank or eccentric mechanism }	45/54	. . . . .	and plasticising screw {(B29C 45/532 takes precedence) }
2045/5024	. . . . .	{ screws rotated by the coaxial rotor of an electric motor }	45/541	. . . . .	{ using a hollow plasticising screw co-operating with a coaxial injection ram }
2045/5028	. . . . .	{ screws axially driven by the coaxial rotor of an electric motor }	45/542	. . . . .	{ using an accumulator between plasticising and injection unit, e.g. for a continuously operating plasticising screw }
2045/5032	. . . . .	{ using means for detecting injection or back pressures }	45/544	. . . . .	{ the plasticising unit being connected to a transfer chamber in the injection unit at the upstream side of the injection piston }
2045/5036	. . . . .	{ back pressure obtaining means }	2045/545	. . . . .	{ alternately operating injection plungers }
2045/504	. . . . .	{ electric motors for rotary and axial movement of the screw being coaxial with the screw }			
2045/5044	. . . . .	{ screws axially driven by rack and pinion means }			

2045/547	. . . . .	{continuously rotating plasticising screw cooperating with a single injection plunger (B29C 45/542 takes precedence)}	45/60	. . . . .	Screws
2045/548	. . . . .	{Reciprocating plasticising screws}	2045/605	. . . . .	{comprising a zone or shape enhancing the degassing of the plastic material}
45/56	. . . . .	using mould parts movable during or after injection, e.g. injection-compression moulding {(B29C 45/1705 and B29C 45/572 take precedence)}	45/62	. . . . .	Barrels or cylinders
45/5605	. . . . .	{Rotatable mould parts}	2045/623	. . . . .	{Cylinders and inner linings having different thermal expansion coefficients}
45/561	. . . . .	{Injection-compression moulding}	2045/626	. . . . .	{Cylinders and inner linings having similar thermal expansion coefficients}
2045/5615	. . . . .	{Compression stroke, e.g. length thereof}	45/63	. . . . .	Venting or degassing means
2045/562	. . . . .	{Velocity profiles of the compression stroke}	45/64	. . . . .	Mould opening, closing or clamping devices {(combined with means for plasticising or homogenising B29C 45/70)}
2045/5625	. . . . .	{Closing of the feed opening before or during compression}	45/641	. . . . .	{Clamping devices using means for straddling or interconnecting the mould halves, e.g. jaws, straps, latches}
2045/563	. . . . .	{Enlarging the mould cavity during injection}	2045/642	. . . . .	{using coupling rods for clamping}
2045/5635	. . . . .	{Mould integrated compression drive means}	2045/644	. . . . .	{mould clamping by nozzle touch pressure}
2045/564	. . . . .	{Compression drive means acting independently from the mould closing and clamping means}	2045/645	. . . . .	{using magnetic means}
2045/5645	. . . . .	{Resilient compression means}	2045/647	. . . . .	{using magnetostriction}
2045/565	. . . . .	{Closing of the mould during injection}	2045/648	. . . . .	{Rack and pinion means for mould opening and closing a pair of mould halves}
2045/5655	. . . . .	{using a screw mechanism as compression drive means}	45/66	. . . . .	mechanical
2045/566	. . . . .	{Reducing compression pressure during cooling of the moulded material}	45/661	. . . . .	{using a toggle mechanism for mould clamping}
2045/5665	. . . . .	{Compression by transversely movable mould parts (transversely movable mould parts in general B29C 45/33)}	2045/662	. . . . .	{using toggles directly connected or linked to the fixed platen and indirectly to the movable platen}
2045/567	. . . . .	{Expelling resin through the gate}	2045/664	. . . . .	{using mould clamping means operating independently from the mould closing means}
45/5675	. . . . .	{for making orifices in or through the moulded article}	2045/665	. . . . .	{using a screw or screws having differently threaded parts arranged in series}
45/568	. . . . .	{Applying vibrations to the mould parts}	2045/667	. . . . .	{Cam drive for mould closing or clamping}
2045/5685	. . . . .	{for eliminating internal voids in the moulding material}	2045/668	. . . . .	{using tilting elements for obtaining mould clamping}
2045/569	. . . . .	{using a mould part for decreasing and a mould part for increasing the volume of the mould cavity}	45/67	. . . . .	hydraulic
2045/5695	. . . . .	{using a movable mould part for continuously increasing the volume of the mould cavity to its final dimension during the whole injection step}	45/6707	. . . . .	{without relative movement between the piston and the cylinder of the clamping device during the mould opening or closing movement}
45/57	. . . . .	Exerting after-pressure on the moulding material {(B29C 45/174 takes precedence)}	45/6714	. . . . .	{using a separate element transmitting the mould clamping force from the clamping cylinder to the mould}
45/572	. . . . .	{using movable mould wall or runner parts}	45/6721	. . . . .	{the separate element being displaceable with respect to the mould or the clamping cylinder}
2045/575	. . . . .	{preventing backflow of moulding material to the injection means during after-pressure}	45/6728	. . . . .	{the separate element consisting of coupling rods}
2045/577	. . . . .	{pushing the material in the runner channel until a pin or slider reaches the mould cavity wall}	2045/6735	. . . . .	{Rotatable means coaxial with the coupling rod for locking the coupling rod to the mould platen}
45/58	. . . . .	Details	2045/6742	. . . . .	{the coupling rods facilitating access between the mould halves}
45/581	. . . . .	{Devices for influencing the material flow, e.g. "torpedo constructions" or mixing devices}	2045/675	. . . . .	{Rotatable means coaxial with the tie rod for locking the movable platen to the tie rod, e.g. bayonet couplings using teeth or splines interrupted by longitudinal grooves}
2045/583	. . . . .	{Mixing devices connected to drive means}	2045/6757	. . . . .	{Hydraulic locking means}
45/585	. . . . .	{Vibration means for the injection unit or parts thereof}	45/6764	. . . . .	{using hydraulically connectable chambers of the clamping cylinder during the mould opening and closing movement}
45/586	. . . . .	{Injection or transfer plungers}	45/6771	. . . . .	{the connection being provided within the clamping cylinder}
2045/588	. . . . .	{Means for retaining sprues on the end surface of the plunger}			

45/6778	. . . . {Stroke adjusting or limiting means}	2045/7356	. . . . {the temperature of the mould being near or higher than the melting temperature or glass transition temperature of the moulding material}
2045/6785	. . . . {interconnecting two cylinders to supply fluid from one cylinder to the other during movement of the pistons}	2045/7362	. . . . {turbulent flow of heating or cooling fluid}
2045/6792	. . . . {Combined pneumatic-hydraulic cylinders}	2045/7368	. . . . {combining a heating or cooling fluid and non-fluid means}
45/68	. . . hydro-mechanical	2045/7375	. . . . {heating a mould surface by a heated gas}
45/681	. . . . {using a toggle mechanism as mould clamping device}	2045/7381	. . . . {heating by gas combustion}
45/683	. . . . {using both a toggle mechanism as mould closing device and another mechanism as mould clamping device}	2045/7387	. . . . {jetting a cooling fluid onto the moulded article while still in the mould}
2045/685	. . . . {using mechanical drive means for mould closing to obtain the hydraulic clamping pressure}	2045/7393	. . . . {alternately heating and cooling}
2045/686	. . . . {using a screw and nut mechanism for mould closing and a mould clamping ram acting on another nut}	45/74	. . . of the injection unit
2045/688	. . . . {using tie rods as separate elements for clamping}	45/76	. . Measuring, controlling or regulating {(measuring in general <a href="#">G01</a> ; controlling or regulating in general <a href="#">G05</a> )}
45/70	. . Means for plasticising or homogenising the moulding material or forcing it into the mould, combined with mould opening, closing or clamping devices	<b>NOTE</b>	
2045/703	. . . {using clamping and injection pressures that are proportional to each other}	In groups <a href="#">B29C 45/76</a> - <a href="#">B29C 45/80</a> it is desirable to add the indexing codes of <a href="#">B29C 2945/76</a> relating to measuring, controlling or regulating in injection moulding	
45/706	. . . {using a single drive system providing both the mould closing and clamping pressure and also the injection pressure, e.g. using a fixed injection piston}	2045/7606	. . . {Controlling or regulating the display unit}
45/72	. . Heating or cooling	45/7613	. . . {the termination of flow of material into the mould}
45/7207	. . . {of the moulded articles}	45/762	. . . {the sequence of operations of an injection cycle}
2045/7214	. . . . {Preform carriers for cooling preforms}	45/7626	. . . {the ejection or removal of moulded articles}
2045/7221	. . . . {Means for ejecting the preforms}	2045/7633	. . . . {Take out or gripping means}
2045/7228	. . . . {turret-like}	2045/764	. . . . {detecting or preventing overload of an ejector (controlling overload in general <a href="#">G01L 5/0071</a> )}
2045/7235	. . . . {Mechanical retaining means for preform ends}	45/7646	. . . {viscosity}
2045/7242	. . . . {Alignment means for preforms}	45/7653	. . . {mould clamping forces}
2045/725	. . . . {Cooling circuits within the preform carriers}	45/766	. . . {the setting or resetting of moulding conditions, e.g. before starting a cycle}
2045/7257	. . . . {Cooling or heating pins with temperature adjustment enhancing surface structure}	45/7666	. . . {of power or energy, e.g. integral function of force}
2045/7264	. . . . {Cooling or heating the neck portion of preforms}	2045/7673	. . . . {Recovering energy or power from drive motors}
2045/7271	. . . {Cooling of drive motors}	45/768	. . . {Detecting defective moulding conditions ( <a href="#">B29C 45/84</a> takes precedence)}
2045/7278	. . . {Heating by friction of the moulding material}	45/7686	. . . {the ejected articles, e.g. weight control}
2045/7285	. . . {using hydraulic oil as tempering medium}	45/7693	. . . {using rheological models of the material in the mould, e.g. finite elements method}
2045/7292	. . . {Recovering waste heat}	45/77	. . . of velocity or pressure of moulding material
45/73	. . . of the mould {( <a href="#">B29C 45/2642</a> and <a href="#">B29C 45/2737</a> take precedence)}	2045/773	. . . . {Zero point correction}
45/7306	. . . . {Control circuits therefor}	2045/776	. . . . {determining the switchover point to the holding pressure}
45/7312	. . . . {Construction of heating or cooling fluid flow channels}	45/78	. . . of temperature
2045/7318	. . . . {multilayered fluid channel constructions}	45/80	. . . of relative position of mould parts
2045/7325	. . . . {Mould cavity linings for covering fluid channels or provided therewith}	45/82	. . . Hydraulic {or pneumatic} circuits
45/7331	. . . . {Heat transfer elements, e.g. heat pipes}	2045/822	. . . . {Pneumatic circuits}
45/7337	. . . . {using gas or steam ( <a href="#">B29C 45/7331</a> takes precedence)}	2045/824	. . . . {Accumulators}
2045/7343	. . . . {heating or cooling different mould parts at different temperatures}	2045/826	. . . . {Plurality of hydraulic actuators driven by one hydraulic pump}
2045/735	. . . . {heating a mould part and cooling another mould part during moulding}	2045/828	. . . . {Bidirectional pumps}
		45/83	. . Lubricating means
		2045/835	. . . {for ball screws or ball nuts}
		45/84	. . Safety devices {( <a href="#">B29C 45/7626</a> takes precedence)}
		45/842	. . . {Detection of insert defects, e.g. inaccurate position, breakage}



- 45/844 . . . {Preventing damage caused by obstructions or foreign matter caught between mould halves during mould closing, e.g. moulded parts or runners}
- 2045/846 . . . {Windable safety screens}
- 2045/848 . . . {detecting or preventing overload of an injection plunger ([controlling overload in general G01L 5/0071](#))}
- 47/00 Extrusion moulding, i.e. expressing the moulding material through a die or nozzle which imparts the desired form; Apparatus therefor** ([extrusion blow-moulding B29C 49/04](#); [extrusion presses in general B30B 11/22](#))
- 47/0002 . {Small extruders, e.g. handheld extruders or laboratory extruders}
- 47/0004 . {characterised by the choice of material}
- NOTE**
- When classifying in this group, it is desirable to add the indexing codes of subclass [B29K](#) to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
- 47/0007 . . {Extruding materials comprising incompatible ingredients}
- 47/0009 . {characterised by the shape of the articles}
- 47/0011 . . {Particle-shaped ([making granules B29B 9/00](#))}
- 47/0014 . . {Filamentary-shaped articles, e.g. strands ([making granules in the form of filamentary material B29B 9/06](#))}
- 47/0016 . . {Rod-shaped articles}
- 47/0019 . . {Flat rigid articles, e.g. panels, plates}
- 47/0021 . . {Flat flexible articles, e.g. sheets, foils or films}
- 47/0023 . . {Hollow rigid articles having only one tubular passage}
- 47/0026 . . {Hollow flexible articles, e.g. blown foils or films}
- 47/0028 . . {Multi-passage hollow articles, e.g. having at least two holes, e.g. honeycomb articles}
- 47/003 . . {Articles having cross-sectional irregularities, i.e. being non-flat or having cylindrical cross-sections perpendicular to the extrusion direction}
- 47/0033 . . {Articles having longitudinal irregularities, i.e. the cross-section being non-constant in the extrusion direction}
- 47/0035 . . {Curved articles}
- 47/0038 . {Combined shaping operations}
- 47/004 . . {Extrusion moulding combined with compression moulding ([compression moulding in general B29C 43/00](#))}
- 47/0042 . . {Extrusion moulding combined with shaping by internal pressure generated in the material, e.g. foaming ([shaping by internal pressure generated in the material, e.g. foaming, in general B29C 44/00](#))}
- 47/0045 . . {Extrusion moulding in several steps, i.e. components merging outside the die ([B29C 47/02 takes precedence](#))}
- 47/0047 . . . {producing flat articles having components brought in contact outside the extrusion die}
- 47/005 . . . {producing hollow articles having components brought in contact outside the extrusion die}
- 47/0052 . . . . {using a plurality of extrusion dies}
- 47/0054 . . {Extrusion moulding combined with blow-moulding or thermoforming ([blow-moulding in general B29C 49/00](#); [thermoforming in general B29C 51/00](#))}
- 47/0057 . . {Extrusion moulding combined with shaping by orienting, stretching or shrinking, e.g. film blowing ([B29C 47/0054 takes precedence](#); [shaping by stretching in general B29C 55/00](#); [shaping by liberation of internal stresses in general B29C 61/00](#))}
- 47/0059 . . {Extrusion moulding combined with shaping by flattening, folding or bending ([bending, folding or flattening in general B29C 53/00](#))}
- 47/0061 . . {Extrusion moulding combined with surface shaping ([surface shaping in general B29C 59/00](#))}
- 47/0064 . . {Extrusion moulding combined with joining, lining or laminating ([joining in general B29C 65/00](#); [lining in general B29C 63/00](#); [laminating in general B32B 37/00](#))}
- 47/0066 . . {Extrusion moulding combined with cutting}
- 47/0069 . . {Extrusion moulding combined with printing or marking}
- 47/0071 . {extruding under particular conditions, e.g. in particular environments or using vacuum or vibrations}
- 47/0073 . . {extruding in a clean room}
- 47/0076 . . {using force fields, e.g. gravity or electrical fields ([B29C 47/887 takes precedence](#))}
- 47/0078 . . {at a location before or in the feed unit, e.g. influencing the material in the hopper}
- 47/008 . . {at the plasticising zone}
- 47/0083 . . {at a venting zone}
- 47/0085 . . {in the die}
- 47/0088 . . {after the die nozzle}
- 47/009 . . . {at the die nozzle exit zone}
- 47/0092 . . . {at a calibration zone}
- 47/0095 . . . {at a conveyor}
- 47/0097 . . . {at a storing zone}
- 47/02 . . incorporating preformed parts or layers, e.g. extrusion moulding around inserts or for coating articles
- 47/021 . . {Coating hollow articles}
- 47/022 . . . {Coating the interior of hollow articles}
- 47/023 . . . {Coating the inner and outer surfaces of hollow reinforcement}
- 47/025 . . {Coating non-hollow articles}
- 47/026 . . . {partially}
- 47/027 . . {Simultaneous coating of more than one article}
- 47/028 . . {Coating discontinuous element or linked elements}
- 47/04 . . of multilayered {or multi-component, e.g. co-extruded layers or components} or multicoloured articles {or coloured articles} {([adapter blocks B29C 47/56](#))}
- 47/043 . . {Coloured articles}
- 47/046 . . . {comprising a multi-coloured single component, e.g. striated, marbled or wood-like patterned}
- 47/06 . . Multilayered articles {or multi-component articles}

- 47/061 . . . {comprising six or more components, i.e. each component being counted once for each time it is present, e.g. in a layer}
- 47/062 . . . {with components adjacent to each other, i.e. components merging at their short sides}
- 47/064 . . . . {in the form of a thin strip, e.g. in the form of a helical pattern or mark lines}
- 47/065 . . . {with components in layered configuration, i.e. components merging at their long sides}
- 47/067 . . . {using means for adhering the layers or components, e.g. using tie layers, irregularities or undercuts}
- 47/068 . . . {using means for avoiding adhering the layers or components, e.g. articles comprising peelable layers}
- 47/08 . . Component parts, details or accessories; Auxiliary operations
- 47/0801 . . {Drive or actuation means; Transmission means; Screw supporting means}
- 47/0803 . . . {Shaft or screw supports, e.g. bearings}
- 47/0805 . . . {Direct drives or gear boxes}
- 47/0806 . . . {Drive or actuation means for non-plasticising purposes, e.g. dosing unit}
- 47/0808 . . {Sealing means}
- 47/081 . . . {for filters}
- 47/0811 . . {Flow control means, i.e. adjustable parts, e.g. valves ([throttling of flow B29C 47/0871](#))}
- 47/0813 . . . {in the feeding, melting, plasticising or pumping zone, e.g. screw, barrel, gear-pump or ram}
- 47/0815 . . . {provided in or in the proximity of filter devices}
- 47/0816 . . . {provided in or in the proximity of dies ([B29C 47/124](#), [B29C 47/16](#), [B29C 47/22](#) take precedence)}
- 47/0818 . . {Exchangeable extruder parts ([B29C 47/681](#) takes precedence)}
- 47/082 . . . {Mounting and handling of the screw}
- 47/0822 . . . {Mounting and handling of the die}
- 47/0823 . . . {Mounting and handling of the hopper or feeder}
- 47/0825 . . . {Screw parts}
- 47/0827 . . . {Barrel parts}
- 47/0828 . . . {Die parts}
- 47/083 . . . {Hopper or feeder parts}
- 47/0832 . . . {Inserts}
- 47/0833 . . . . {for screws}
- 47/0835 . . . . {for barrels}
- 47/0837 . . . . {for dies}
- 47/0838 . . {General arrangement or layout of plants}
- 47/084 . . . {for extruding parallel streams of material, e.g. several separate parallel streams of extruded material forming separate articles ([B29C 47/30](#), [B29C 47/0045](#) take precedence)}
- 47/0842 . . {Extruder machines or parts thereof characterised by the material or by their manufacturing process ([B29C 47/0818](#) take precedence; [making of dies B23P 15/24](#))}
- 47/0844 . . . {Screws}
- 47/0845 . . . . {Material therefor, e.g. coating or lining}
- 47/0847 . . . {Barrels}
- 47/0849 . . . . {Material therefor, e.g. coating or lining}
- 47/085 . . . {Dies}
- 47/0852 . . . . {Material therefor, e.g. coating or lining}
- 47/0854 . . {Design of extruder parts, e.g. by modelling based on mathematical theories or experiments}
- 47/0855 . . . {by modelling material flow, e.g. melt interaction with screw and barrel}
- 47/0857 . . . . {in the plasticising zone}
- 47/0859 . . . . {in the die zone}
- 47/0861 . . . {of intermeshing screws}
- 47/0862 . . . {by modelling of mechanical strength}
- 47/0864 . . {Machine bases, support structures or frames}
- 47/0866 . . {Means for allowing relative movements between the apparatus parts, e.g. for twisting the extruded article or for moving the die along a surface to be coated}
- 47/0867 . . . {allowing small relative movement, e.g. adjustments for aligning the apparatus parts or for compensating for thermal expansion}
- 47/0869 . . {Intermediate treatments, e.g. relaxation, annealing or decompression step for the melt ([B29C 47/76](#) takes precedence)}
- 47/0871 . . {Throttling of the flow, e.g. for cooperating with plasticising elements or for degassing ([flow control means B29C 47/0811](#))}
- 47/0872 . . {Extrusion in non-steady condition, e.g. start-up or shut-down}
- 47/0874 . . . {Material change}
- 47/0876 . . . {Intermittent extrusion}
- 47/0877 . . {Cleaning, purging; Avoiding contamination for cleaning extruder parts}
- 47/0879 . . . {of feeding units}
- 47/0881 . . . {of plasticising units}
- 47/0883 . . . {of dies}
- 47/0884 . . . {of filters}
- 47/0886 . . . . {using back flow}
- 47/0888 . . . . {using scrapers}
- 47/0889 . . . {of the extruded articles}
- 47/0891 . . {Recovering or reusing of energy, materials or the like}
- 47/0893 . . . {of energy}
- 47/0894 . . . {of materials}
- 47/0896 . . . . {of additives or processing aids}
- 47/0898 . . {Storing of the manufactured articles, e.g. winding up or stacking}
- 47/10 . . Feeding the material to the extruder
- 47/1009 . . . {Raw material dosing}
- 47/1018 . . . {Raw material pre-treatment while feeding ([pre-treatment of the material to be shaped in general B29B 15/00](#); [handling of the material to be shaped in general B29C 31/00](#); [B29C 47/78](#) takes precedence)}
- 47/1027 . . . {in solid form, e.g. powder or granules}
- 47/1036 . . . . {of preformed parts, e.g. inserts that are fed and transported generally uninfluenced through the extruder or fed directly to the die}
- 47/1045 . . . . {of fibrous, filamentary or filling materials, e.g. thin fibrous reinforcements or fillers}
- 47/1054 . . . . {in band and/or in strip form, e.g. rubber strips}
- 47/1063 . . . {in liquid form}
- 47/1072 . . . {in gaseous form}
- 47/1081 . . . {at several locations, e.g. using several hoppers or using a separate additive feeding}

- 47/109 . . . {in a location other than through a barrel, e.g. through a screw}
- 47/12 . . Extrusion nozzles or dies
- 47/122 . . . {having reciprocating, oscillating or rotating parts}
- 47/124 . . . {being adjustable, i.e. having adjustable exit sections}
- 47/126 . . . {using dies or die parts movable in a closed circuit, e.g. mounted on movable endless support ([B29C 47/32](#) takes precedence)}
- 47/128 . . . {specially adapted for bringing together components, e.g. melts within the die}
- 47/14 . . . with broad opening, e.g. for sheets
- 47/145 . . . . {specially adapted for bringing together components, e.g. melts within the die}
- 47/16 . . . . {being} adjustable {, i.e. having adjustable exit sections}
- 47/165 . . . . . {by positioning the die lips}
- 47/18 . . . . with die parts oscillating relative to each other
- 47/20 . . . with annular opening, e.g. for tubular articles
- 47/22 . . . . {being} adjustable {, i.e. having adjustable exit sections}
- 47/225 . . . . . {with centering means}
- 47/24 . . . . with die parts rotatable relative to each other
- 47/26 . . . . Multiple annular extrusion nozzles {specially adapted for bringing together components, e.g. melts within the die}
- 47/261 . . . . . {the components merging one by one down streams in the die}
- 47/263 . . . . . {using a layered die, e.g. stacked discs}
- 47/265 . . . . . {using a die with concentric parts, e.g. rings, cylinders}
- 47/266 . . . . . {the components merging at a common location}
- 47/268 . . . . . {using a die with concentric parts, e.g. rings, cylinders}
- 47/28 . . . . Cross-head annular extrusion nozzles
- 47/30 . . . Multi-port extrusion nozzles {(for making granules in the form of elementary material [B29B 9/06](#))}
- 47/32 . . . Roller-extrusion nozzles
- 47/34 . . Conveyors for extruded material {([B29C 47/0898](#) takes precedence)}
- 47/36 . . Means for plasticising or homogenising the moulding material or forcing it through the nozzle or die
- 47/361 . . . {with the barrel or with a part thereof rotating}
- 47/362 . . . {using static mixing devices}
- 47/363 . . . {using non-actuated dynamic mixing devices}
- 47/364 . . . {using gear pumps}
- 47/365 . . . {Multi stage plasticisers, homogenisers or feeders (multi stage plasticisers using at least two screws in the same barrel [B29C 47/50](#))}
- 47/366 . . . . {using a first screw extruder and a second screw extruder}
- 47/367 . . . . {using a screw extruder and a gear pump}
- 47/368 . . . . {using a screw extruder and a ram or piston}
- 47/369 . . . . {Partial multi-stage}
- 47/38 . . . using screws {surrounded by a cooperating barrel}
- 47/385 . . . . {using a single screw}
- 47/40 . . . . using at least two {parallel} intermeshing screws {or at least two parallel non-intermeshing screws}
- 47/402 . . . . . {the screws having intermeshing parts}
- 47/404 . . . . . {the screws having non-intermeshing parts}
- 47/406 . . . . . {using non-identical or non-mirrored screws}
- 47/408 . . . . . {using more than two screws ([B29C 47/42](#) takes precedence)}
- 47/42 . . . . . using sub-screws, e.g. planetary screws
- 47/44 . . . . using axially movable screws {in relation to the barrel}
- 47/46 . . . . using screws extruding in opposite directions {, e.g. separate screws arranged after each other and feeding in opposite directions}
- 47/48 . . . . using screws arranged coaxially, one within the other
- 47/50 . . . . using at least two screws {in the same barrel}, one after the other, e.g. multi stage plasticisers
- 47/52 . . . using rollers or discs
- 47/522 . . . . {using rollers}
- 47/525 . . . . . {using single rollers, e.g. provided with protrusions, closely surrounded by a housing with movement of the material in the axial direction}
- 47/527 . . . . . {Cavity transfer mixing devices, i.e. a roller and surrounding barrel both provided with cavities; Barrels and rollers therefor}
- 47/54 . . . using press rams or pistons {or accumulators}
- 47/56 . . . using more than one extruder to feed one die
- 47/58 . . . Details
- 47/585 . . . . {Extruder feed section}
- 47/60 . . . . Screws {(screws characterized by the material or by their manufacturing process [B29C 47/0844](#))}
- 47/6006 . . . . . {Hollow screws, i.e. comprising flow passage inside the screws}
- 47/6012 . . . . . {having varying outer diameter, e.g. screws with a conical part}
- 47/6018 . . . . . {having varying channel depth}
- 47/6025 . . . . . {having variable channel pitch}
- 47/6031 . . . . . {having forward feeding elements}
- 47/6037 . . . . . {having reverse feeding elements}
- 47/6043 . . . . . {having grooves or cavities}
- 47/605 . . . . . {having projections with a short length in the screw direction, e.g. pins}
- 47/6056 . . . . . {having kneading disc like elements, e.g. staggered discontinuous elements with a generally oval cross section}
- 47/6062 . . . . . {having shear ring like elements, i.e. with a generally circular cross section}
- 47/6068 . . . . . {having gears, i.e. interacting with the flow}
- 47/6075 . . . . . {characterised by thread details, i.e. by the special shape of a single thread, e.g. by irregularities within one thread}
- 47/6081 . . . . . {characterised by valley details, i.e. by the special shape of a single valley, e.g. by irregularities within one valley}
- 47/6087 . . . . . {characterised by the length of the screw or of a section}

47/6093	. . . . . {having parts without mixing elements, e.g. having cylinder shaped sections}	47/762	. . . . . {Vapour stripping}
47/62	. . . . . having more than one screw-thread {, i.e. the screw cross section showing at least two threads}	47/763	. . . . . {Vent constructions, e.g. venting means avoiding melt escape}
47/622	. . . . . {the neighbouring threads and channels having identical configurations}	47/765	. . . . . {in the extruder apparatus}
47/625	. . . . . {the neighbouring threads or channels having different configurations, e.g. one flight having constantly a smaller diameter or height than the neighbouring flight}	47/766	. . . . . {in screw extruders}
47/627	. . . . . {being multi-flight and having three or more flights}	47/767	. . . . . {through a degassing opening of a barrel}
47/64	. . . . . having incorporated mixing devices { <a href="#">(B29C 47/6006 - B29C 47/627 take precedence)</a> }	47/768	. . . . . {outside the apparatus, e.g. after the die}
47/66	. . . . . Barrels or cylinders	47/78	. . Heating or cooling the material to be extruded or the stream of extruded material {or of a preformed part}
47/661	. . . . . {for single screws}	47/782	. . . {of a preformed part, e.g. a core before entering a die or before entering a barrel}
47/662	. . . . . {for twin screws}	47/784	. . . {at a location before the plasticising zone, e.g. of the material in the hopper}
47/663	. . . . . {for more than two screws}	47/786	. . . . . {heating}
47/664	. . . . . {having adaptable feed or discharge locations, e.g. for varying the amount of kneading by changing hopper position or discharge exit}	47/788	. . . . . {cooling}
47/665	. . . . . {with irregular inner surfaces}	47/80	. . . at plasticising zone {, e.g. from the feed section until the die entrance}
47/666	. . . . . {having grooves or cavities}	47/802	. . . . . {heating}
47/667	. . . . . {having projections with a short length in the barrel direction, e.g. pins}	47/805	. . . . . {cooling}
47/668	. . . . . {having threads}	47/807	. . . . . {characterised by differential heating or cooling}
47/68	. . . . . Filters {; Screens}	47/82	. . . . . Heating {or cooling} the cylinders
47/681	. . . . . {Filtering devices with at least two parallel filters to be used alternately; Movable filters and changing mechanisms therefor}	47/822	. . . . . {heating}
47/682	. . . . . {the filters being fitted on a single rectilinearly reciprocating slide <a href="#">(B29C 47/685 takes precedence)</a> }	47/825	. . . . . {cooling}
47/683	. . . . . {the filters being fitted on a rotatable or pivotable disc or on the circumference of a rotatable or pivotable cylinder}	47/827	. . . . . {characterised by differential heating or cooling}
47/684	. . . . . {Continuously rotating cylindrical filters}	47/84	. . . . . Heating {or cooling} the screws
47/685	. . . . . {the filters being in the form of a continuous web displaceable to utilise adjacent areas consecutively}	47/842	. . . . . {heating}
47/686	. . . . . {Substantially flat filters mounted at the end of an extruder screw and perpendicular to its axis <a href="#">(B29C 47/681 takes precedence)</a> }	47/845	. . . . . {cooling}
47/687	. . . . . {Cylindrical or conical filters <a href="#">(B29C 47/681 takes precedence)</a> }	47/847	. . . . . {characterised by differential heating or cooling}
47/688	. . . . . {surrounding a rotating screw}	47/86	. . . at nozzle zone
47/70	. . . . . Flow dividers	47/862	. . . . . {heating}
47/702	. . . . . {comprising means for dividing, distributing and recombining melt flows}	47/864	. . . . . {cooling}
47/705	. . . . . {in the die zone, e.g. to create flow homogeneity}	47/866	. . . . . {characterised by differential heating or cooling}
47/707	. . . . . {component or layer multiplying}	47/868	. . . . . {in the direction of the stream of the material}
47/72	. . . . . Feedback means	47/88	. . . Heating or cooling the stream of extruded material
47/725	. . . . . {for plasticising or homogenising devices}	<b>NOTE</b>	
47/74	. . . . . By-pass means	{Attention is drawn to Note (3) following the subclass title}	
47/745	. . . . . {for plasticising or homogenising devices}	47/8805	. . . . . {Heating}
47/76	. . . . . Venting, {drying} or degassing means	47/881	. . . . . {of hollow articles}
47/761	. . . . . {the vented material being in liquid form}	47/8815	. . . . . {cooling}
		47/882	. . . . . {of hollow articles}
		47/8825	. . . . . {of tubular films}
		47/883	. . . . . {internally}
		47/8835	. . . . . {externally}
		47/884	. . . . . {of flat articles, e.g. using specially adapted supporting means}
		47/8845	. . . . . {cooling drums}
		47/885	. . . . . {Endless cooling belts}
		47/8855	. . . . . {with means for improving the adhesion to the supporting means}
		47/886	. . . . . {Pressure rollers}
		47/8865	. . . . . {using vacuum}
		47/887	. . . . . {Electrostatic pinning}



47/8875	. . . . . {by applying pressurised gas to the surface of the flat article}	49/0042	. {without using a mould}
47/888	. . . . . {by interposing a fluid layer between the supporting means and the flat article}	49/0047	. {Sheet blow-moulding, i.e. using at least two parallel sheets or a folded sheet as a preform}
47/8885	. . . . {characterized by differential heating or cooling}	2049/0052	. . {using a folded sheet as a preform}
47/889	. . . . . {in the direction of the stream of the material}	2049/0057	. . {using two parallel sheets as a preform}
47/8895	. . . . {using a bath, e.g. extruding into an open bath to coagulate or cool the material}	2049/0063	. . {whereby the folded sheets or the two parallel sheets are separated from each other at least at one place, e.g. to allow inserting of a blowing means}
47/90	. . . . with calibration or sizing	2049/0068	. . {Means for avoiding the sheets to stick together before or during the blow moulding operation}
47/901	. . . . . {of hollow bodies}	49/0073	. {characterised by the parison configuration, e.g. nestable (B29C 49/22 takes precedence)}
47/902	. . . . . {internally}	49/0078	. . {Parisons having internal or external ribs}
47/903	. . . . . {externally}	49/0084	. . . {the internal ribs being connected to the opposite wall, e.g. forming an internal separating wall}
47/904	. . . . . {using dry calibration, i.e. no quenching tank, e.g. with water spray for cooling or lubrication}	2049/0089	. . {the parison being a tube, e.g. a tube which has to be reheated before blow moulding}
47/905	. . . . . {using wet calibration, i.e. in a quenching tank}	2049/0094	. {Blow moulding plants, e.g. using at least two blow moulding apparatuses at the same time}
47/906	. . . . . {using roller calibration}	49/02	. Combined blow-moulding and manufacture of the preform or the parison
47/907	. . . . . {using adjustable calibrators, e.g. the dimensions of the calibrator being changeable}	2049/021	. . {the preform or parison being made out of several parts, e.g. by welding or gluing parts together}
47/908	. . . . . {characterised by calibrator surface, e.g. structure or holes for lubrication, cooling or venting}	49/022	. . {the parison being partly injected and partly extruded}
47/92	. . Measuring, controlling or regulating	2049/023	. . {using inherent heat of the preform, i.e. 1 step blow moulding}
<b>NOTE</b>		2049/024	. . {not using inherent heat of the preform, i.e. 2 step blow moulding}
When classifying in group B29C 47/92 it is desirable to add the indexing codes of B29C 2947/00 relating to measuring, controlling or regulating in extrusion moulding		2049/025	. . {the preform or parison being made of powder}
		2049/026	. . {Coating a preform or parison, e.g. with reinforcing material}
47/94	. . Lubricating {, e.g. adding lubrication to the melt}	2049/027	. . . {on the inside}
47/96	. . Safety devices	2049/028	. . {Compression blow-moulding}
47/965	. . . {Personnel safety, e.g. safety for the operator}	49/04	. . Extrusion blow-moulding
<b>49/00</b>	<b>Blow-moulding, i.e. blowing a preform or parison to a desired shape within a mould; Apparatus therefor {(extrusion moulding of tubular films B29C 47/0026; enlarging tube ends using pressure difference B29C 57/08)}</b>	49/041	. . . {using an accumulator head}
49/0005	. {characterised by the choice of material}	2049/042	. . . . {disclosing the push out speed}
<b>NOTE</b>		2049/044	. . . {extruding the material continuously}
When classifying in this group, it is desirable to add the indexing codes of subclass B29K to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest		2049/045	. . . . {with means to move the extruder head up and down, e.g. to continue extruding the next parison while blow moulding the previous parison in the blow mould}
2049/001	. . {The material comprising particles or additives to induce special properties in the preform}	2049/047	. . . {extruding the material discontinuously}
49/0015	. {for making articles of indefinite length, e.g. corrugated tubes}	2049/048	. . . {extruding several parisons parallel to each other at the same time}
49/0021	. . {using moulds or mould parts movable in a closed path, e.g. mounted on movable endless supports}	49/06	. . Injection blow-moulding {(introducing a fluid into the interior of the injected material which is still in a molten state B29C 45/1704)}
49/0026	. . . {using independent mould parts, i.e. the mould parts not being interconnected, e.g. for speeding up the transfer of the moulds to the beginning of the moulding area}	49/061	. . . {with parison holding means displaceable between injection and blow stations}
49/0031	. {for making articles having hollow walls}	49/062	. . . . {following an arcuate path, e.g. rotary or oscillating-type}
2049/0036	. . {by ballooning the parison in an open mould}	49/063	. . . . . {with the parison axis held in the plane of rotation}
		49/064	. . . . {following a rectilinear path, e.g. shuttle-type}
		2049/065	. . . {Means to compensate or avoid the shrinking of the preforms, e.g. in the injection mould or outside the injection mould}
		2049/066	. . . {One injection moulding station supplies several blow moulding stations with preforms}

- 2049/067 . . . {Several injection moulding stations supply one blow moulding station with preforms}
- 2049/068 . . . {Moving the injection mould cavity and blow mould cavity to the geometrically fixed injection core mould}
- 2049/069 . . . {using a porous core}
- 49/08 . . . Biaxial stretching during blow-moulding {with or without prestretching}
- 49/085 . . {without prestretching}
- 49/10 . . using mechanical means {for prestretching}
- 49/12 . . . Stretching rods
- 2049/1204 . . . . {Means for fixing the stretching rod to the driving means, e.g. clamping means or bayonet connections}
- 2049/1209 . . . . {rotating during stretching of the preform}
- 2049/1214 . . . . {Using at least two stretching rods for stretching different parts of the preform}
- 2049/1219 . . . . {Using additional means to clamp the preform bottom while stretching the preform}
- 2049/1223 . . . . {Stretching rod configuration, e.g. geometry; Stretching rod material}
- 2049/1228 . . . . . {the stretching rod comprises at least one opening on the surface through which compressed air is blown into the preform to expand the same}
- 2049/1233 . . . . . {the opening being at the end where it touches the preform, e.g. to avoid direct contact between the preform and the stretching rod}
- 2049/1238 . . . . . {Geometry of the stretching rod, e.g. specific stretching rod end shape}
- 2049/1242 . . . . . {Material for parts or the whole stretching rod, e.g. heat insulating material}
- 2049/1247 . . . . . {to stretch heated tubes}
- 2049/1252 . . . . . {Drive means therefore}
- 2049/1257 . . . . . {Pneumatic}
- 2049/1261 . . . . . {Hydraulic}
- 2049/1266 . . . . . {Mechanical}
- 2049/1271 . . . . . {being a cam mechanism}
- 2049/1276 . . . . . . {adaptable to different sized stretching rods}
- 2049/128 . . . . . . {being a toggle mechanism}
- 2049/1285 . . . . . . {being a spindle nut mechanism}
- 2049/129 . . . . . {Electric direct drives, e.g. linear motors}
- 2049/1295 . . . . . {Magnetic}
- 49/14 . . . Clamps
- 49/16 . . using pressure difference {for prestretching}, e.g. pre-blowing {[\(B29C 49/649 takes precedence\)](#)}
- 2049/165 . . . {pre-blowing without using a mould}
- 49/18 . . using several blowing steps [\(B29C 49/16 takes precedence\)](#)
- 49/185 . . {in different mould cavities}
- 49/20 . . of articles having inserts or reinforcements {; Handling of inserts or reinforcements}
- 2049/2004 . . {with a specific location of the inserts or reinforcements in or on the final article}
- 2049/2008 . . . {Inside}
- 2049/2013 . . . . {Connecting opposite walls, e.g. baffles in a fuel tank}
- 2049/2017 . . . {Outside}
- 2049/2021 . . {Particular inserts}
- 2049/2026 . . . {Neck portions}
- 2049/203 . . . . {Carpets}
- 2049/2034 . . . . {Attachments, e.g. hooks to hold or hang the blown article}
- 2049/2039 . . . . . {Handles, e.g. handles or grips on bottles}
- 2049/2043 . . . . {comprising threads, e.g. screws or nuts}
- 2049/2047 . . . . {Tubular inserts, e.g. tubes}
- 2049/2052 . . . . {having means to avoid that the preform or parison gets into contact with parts of the insert}
- 2049/2056 . . . . {being constructed in such a way that opposite preform or parison walls do not touch each other during extrusion or mould closing}
- 2049/206 . . . . {being constructed in such a way that the joining between the insert and the preform or parison is avoided}
- 2049/2065 . . . . {for reinforcing specific areas of the final blow moulded article}
- 2049/2069 . . . . {being injection moulded, e.g. in the same mould before or after blow moulding}
- 2049/2073 . . {Means for feeding the inserts into the mould, preform or parison, e.g. grippers}
- 2049/2078 . . . . {being retractable during or after blow moulding}
- 2049/2082 . . . . {Feeding the insert and the preform at the same time, e.g. using the same feeding means for the insert and the preform}
- 2049/2086 . . {Means for verifying the position of insert}
- 2049/2091 . . {Means for avoiding cooling of the inserts where the inserts touch the preform or the mould}
- 2049/2095 . . {Means for heating the inserts}
- 49/22 . . using multilayered preforms or parisons
- 49/221 . . {at least one layer being injected ([injection moulding of multilayered parisons B29C 45/1643, B29C 45/1646](#))}
- 2049/222 . . {only parts of the preforms or parisons are layered}
- 2049/224 . . . {neck portion}
- 2049/225 . . . {body portion}
- 2049/227 . . {with particular bonding between the layers}
- 2049/228 . . {at least one layer has a variable thickness}
- 49/24 . . Lining or labelling
- 2049/2402 . . {lining articles}
- 2049/2404 . . . {on their inside surface, e.g. the inside of a bottle or box}
- 2049/2406 . . . . {the lining being used to line a previously coated mould}
- 49/2408 . . {Inserting labels or films into blow-moulds, e.g. in-mould-labellers}
- 2049/241 . . {In-mould labelling}
- 2049/2412 . . . {the label being on the outside surface of the blow moulded article, e.g. bottle with a label on its outside surface}
- 2049/2414 . . {Particular linings or labels, e.g. specific geometry, multilayered; Pretreatment thereof}
- 2049/2416 . . . {Specific shapes or geometries}
- 2049/2418 . . . . {Double folded labels}
- 2049/242 . . . . {Labels have round edges}
- 2049/2422 . . . . {Cylindrical labels}
- 2049/2425 . . . . {Perforated labels}
- 2049/2427 . . . . {Corrugated or embossed labels}
- 2049/2429 . . . {Multilayered labels}
- 2049/2431 . . . {Pretreatment or preshaping of labels}
- 2049/2433 . . . . {Applying glue}

- 2049/2435 . . . . . {in a specific pattern}
- 2049/2437 . . . . . {Cutting}
- 2049/2439 . . . . . {by means in the mould cavity}
- 2049/2441 . . . . . {Preshaping while in the mould cavity}
- 2049/2443 . . {Means for inserting the linings or labels into the mould}
- 2049/2445 . . . {holding the labels or linings by magnetic force}
- 2049/2447 . . . {holding the labels or linings by electrostatic force}
- 2049/2449 . . . {holding the labels or linings by vacuum}
- 2049/2452 . . . {being a transfer foil}
- 2049/2454 . . . {for placing labels at the same time in two opposite mould cavities}
- 2049/2456 . . . {and removing with the same means the final article}
- 2049/2458 . . . {Driving means}
- 2049/246 . . . . . {Cams}
- 2049/2462 . . . . . {Conveyor belt}
- 2049/2464 . . {Means for positioning labels (moulds with incorporated means for positioning inserts in general [B29C 33/12](#))}
- 2049/2466 . . . {using electrostatic force}
- 2049/2468 . . . {using magnetic force}
- 2049/247 . . . {using needles}
- 2049/2472 . . . {using vacuum}
- 2049/2474 . . . {using adhesive}
- 2049/2477 . . {Deforming linings or the labels during blow moulding}
- 2049/2479 . . {Label or lining movements}
- 2049/2481 . . . {vertical only}
- 2049/2483 . . . {horizontal only}
- 2049/2485 . . . {multidirectional}
- 2049/2487 . . . {comprising a rotary movement}
- 2049/2489 . . {Folding the label around the edges of the final blow moulded article, e.g. via mould closing or via additional means}
- 2049/2491 . . {Label materials}
- 2049/2493 . . . {using identical material for the label and the preform}
- 2049/2495 . . . {using different material for the label and the preform}
- 2049/2497 . . . {Labels comprising data carriers or detection means, e.g. chips, RFIDs, antennas}
- 49/26 . . inner lining of tubes
- 49/28 . Blow-moulding apparatus
- 2049/283 . . {configured to easily exchange modules, e.g. heating or feeding module}
- 2049/286 . . {using several moulds whereby at least one mould is different from a plurality of identical moulds in at least one feature, e.g. size or shape}
- 49/30 . . having movable moulds or mould parts
- 49/32 . . . moving "to and fro"
- 2049/325 . . . . . {by using guide rails}
- 49/34 . . . . the mould parts moving "hand-over-hand"
- 49/36 . . . rotatable about one axis
- 49/38 . . . mounted on movable endless supports {[\(B29C 49/0021 takes precedence\)](#)}
- 49/40 . . . . on co-operating drums
- 49/42 . Component parts, details or accessories; Auxiliary operations
- 49/4205 . . {Handling means, e.g. transfer, loading or discharging means ([handling of inserts or reinforcements B29C 49/20](#); [handling of labels B29C 49/2408](#))}
- 49/421 . . . {for blown articles}
- 49/4215 . . . {for increasing the space between preforms, e.g. in order to perform the blow moulding step}
- 2049/4221 . . . {for transferring at least two preforms to the mould}
- 2049/4226 . . . {for orienting preforms in the mould, e.g. depending on their heat profile}
- 2049/4231 . . . {for aligning disorderly arranged preforms}
- 49/4236 . . {Drive means}
- 49/4242 . . {Means for deforming the parison prior to the blowing operation ([B29C 49/08 takes precedence](#))}
- 49/4247 . . . {Spreading or extending means}
- 49/4252 . . {Auxiliary operations prior to the blow moulding operation, e.g. cutting ([B29C 49/64](#), [B29C 49/76](#), [B29C 49/78 take precedence](#))}
- 2049/4257 . . . {Means for heating the mould cavity surface from the side of the cavity, e.g. putting an external heating member between the mould halves}
- 2049/4263 . . . . . {using flames}
- 49/4268 . . {Auxiliary operations during the blow moulding operation ([B29C 49/64](#), [B29C 49/76](#), [B29C 49/78 take precedence](#))}
- 49/4273 . . {Auxiliary operations after the blow moulding operation ([B29C 49/64](#), [B29C 49/70](#), [B29C 49/72](#), [B29C 49/76](#), [B29C 49/78 take precedence](#))}
- 49/4278 . . . {Cutting, rearranging and joining the cut parts}
- 49/4284 . . {Means for recycling or reusing auxiliaries or materials, e.g. blowing fluids or energy}
- 49/4289 . . {Valve constructions or configurations, e.g. arranged to reduce blowing fluid consumption}
- 2049/4294 . . {Sealing means, i.e. for avoiding blowing air to escape}
- 49/44 . . for applying pressure through the walls of an inflated bag
- 2049/445 . . . {having wall areas with different elasticity}
- 49/46 . . characterised by using a particular environment or blow fluids other than air
- 2049/4602 . . . {Blowing fluids}
- 2049/4605 . . . . . {containing an inert gas, e.g. helium}
- 2049/4608 . . . . . {Nitrogen}
- 2049/4611 . . . . . {containing a reactive gas}
- 2049/4614 . . . . . {Chlorine}
- 2049/4617 . . . . . {Fluor}
- 2049/462 . . . . . {Oxygen}
- 2049/4623 . . . . . {the gas containing sulfur, e.g. sulfur trioxide}
- 2049/4626 . . . . . {containing carbon dioxide}
- 2049/4629 . . . . . {containing a polar gas}
- 2049/4632 . . . . . {being filtered air}
- 2049/4635 . . . . . {being sterile}
- 2049/4638 . . . . . {being a hot gas, i.e. gas with a temperature higher than ambient temperature}
- 2049/4641 . . . . . {being a cooled gas, i.e. gas with a temperature lower than ambient temperature}
- 2049/4644 . . . . . {created by evaporating material, e.g. solid powder}

- 2049/4647 . . . . {created by an explosive gas mixture}
- 2049/465 . . . . {being incompressible}
- 2049/4652 . . . . {hot liquids}
- 2049/4655 . . . . {water}
- 2049/4658 . . . . {oil}
- 2049/4661 . . . . {solid media, e.g. powder  
([B29C 2049/4644 takes precedence](#))}
- 2049/4664 . . . . {staying in the final article}
- 2049/4667 . . . . {being foamable}
- 2049/467 . . . . {created by thermal expansion of enclosed  
amount of gas, e.g. heating enclosed air in  
preforms or parisons}
- 2049/4673 . . . {Particular environments}
- 2049/4676 . . . . {being dry air to surround or flush parts  
of the blow moulding apparatus, e.g. blow  
mould, preforms or parisons}
- 2049/4679 . . . . {being sterile gas to surround or flush parts  
of the blow moulding apparatus, e.g. blowing  
means, preforms or parisons}
- 2049/4682 . . . . {surrounding or flushing preforms or  
parisons, e.g. flushing the inside of  
extruded parisons}
- 2049/4685 . . . . {after blow moulding}
- 2049/4688 . . . . {using reactive gas}
- 2049/4691 . . . . {using steam during blow moulding, e.g.  
to expand foamable beads}
- 2049/4694 . . . . {purging or cleaning the blow moulding  
apparatus or parts of it, e.g. cleaning  
blow moulds ([cleaning moulds in general  
B29C 33/72](#))}
- 2049/4697 . . . . {Clean room}
- 49/48 . . Moulds
- 49/4802 . . . {with means for locally compressing part(s) of  
the parison in the main blowing cavity}
- 2049/4805 . . . . {by closing the mould halves}
- 2049/4807 . . . . {by movable mould parts in the mould  
halves}
- 2049/481 . . . . {the movable mould parts moving  
outwardly, e.g. the mould size being  
increased due to the movement of the  
movable mould parts}
- 2049/4812 . . . . {and welding opposite wall parts of the  
parisons or preforms to each other}
- 49/4815 . . . . {by means of movable mould parts}
- 49/4817 . . . {with means for closing off parison ends}
- 49/482 . . . {with means for moulding parts of the parisons  
in an auxiliary cavity, e.g. moulding a handle}
- 49/4823 . . . {with incorporated heating or cooling means}
- 2049/4825 . . . . {for cooling moulds or mould parts  
([B29C 2049/5889 takes precedence](#))}
- 2049/4828 . . . . {for cooling mould parts}
- 2049/483 . . . . {in different areas of the mould at different  
temperatures, e.g. neck, shoulder or  
bottom}
- 2049/4833 . . . . {the cooling means being connected to an  
external heat exchanger}
- 2049/4835 . . . . {releasing the blowing fluid via the  
cooling channels of the moulds}
- 2049/4838 . . . . {for heating moulds or mould parts}
- 2049/4841 . . . . {for heating mould parts}
- 2049/4843 . . . . {for heating the bottom, e.g. heating the  
bottom part independently}
- 2049/4846 . . . . {in different areas of the mould at different  
temperatures, e.g. neck, shoulder or  
bottom}
- 2049/4848 . . . . {Bottom}
- 2049/4851 . . . . {Side walls}
- 2049/4853 . . . . {having additional means for improving  
heat transfer between the mould cavity  
and the parisons or preforms ([in general  
B29C 33/30](#))}
- 2049/4856 . . . {Mounting, exchanging or centering moulds  
or parts thereof ([B29C 2049/5893 takes  
precedence; in general B29C 33/30](#))}
- 2049/4858 . . . . {Exchanging mould parts, e.g. for changing  
the mould size or geometry for making  
different products in the same mould}
- 2049/4861 . . . . {Neck portions of bottle producing  
moulds}
- 2049/4864 . . . . {Fixed by a special construction to the mould  
half carriers, e.g. using insulating material  
between the mould and the mould half  
carrier}
- 2049/4866 . . . . {center the moulds with the mould half  
carriers}
- 2049/4869 . . . {containing more than one mould cavity}
- 2049/4871 . . . . {having different sizes or shapes mould  
cavities, e.g. for producing different sized  
bottles with the same mould}
- 2049/4874 . . . {Moulds made of at least two different  
materials, e.g. a hard material and a soft  
material, materials having different thermal  
conductivities}
- 2049/4876 . . . . {one material being heat insulating material}
- 2049/4879 . . . {defined by special mould configurations}
- 2049/4882 . . . . {Having a special mould cavity geometry}
- 2049/4884 . . . . {Mould halves are made of one piece}
- 2049/4887 . . . . {Mould halves consisting of an independent  
neck and main part}
- 2049/4889 . . . . {Mould halves consisting of an independent  
neck, main and bottom part}
- 2049/4892 . . . . {Mould halves consisting of an independent  
main and bottom part}
- 2049/4894 . . . . {With at least a part of the mould cavity  
formed by a cylindrical mould}
- 2049/4897 . . . {characterised by the manufacturing process ([in  
general B29C 33/38](#))}
- 49/50 . . . having cutting or deflashing means
- 2049/503 . . . . {being independently movable during the  
mould closing}
- 2049/506 . . . . {being heated}
- 49/52 . . . having decorating or printing means
- 49/54 . . . for undercut articles
- 49/541 . . . . {having a recessed undersurface}
- 2049/542 . . . . {having means to facilitate the removal  
of the blow moulded articles ([in general  
B29C 33/44](#))}
- 2049/543 . . . . {at the neck portion}
- 2049/545 . . . . {by rotationally actuating an auxiliary  
mould part while the mould is still in a  
closed position}
- 2049/546 . . . . {by translatorily actuating an auxiliary  
mould part while the mould is still in a  
closed position}



2049/547	. . . . . {which are self actuated during the removing of the blow moulded articles, e.g. the means are spring loaded or flexible}	2049/6045	. . . . . {The air outlet being open and closable}
2049/548	. . . . . {the movement of the mould parts during opening of the mould are interlinked}	2049/6054	. . . . . {Means for avoiding blowing fluid leakage between the blow needle and parisons or preforms}
49/56	. . . . . Opening, closing or clamping means	2049/6063	. . . . . {having means which facilitate the puncturing of the parison}
2049/563	. . . . . {Clamping means}	2049/6072	. . . . . {being movable, e.g. blow needles move to pierce the parison}
2049/566	. . . . . {Locking means}	2049/6081	. . . . . {being rotatable}
49/58	. . . . . Blowing means { <a href="#">(B29C 45/1734 takes precedence)</a> }	2049/609	. . . . . {being at least two}
2049/5803	. . . . . {Constructional features}	49/62	. . . . . Venting means
2049/5806	. . . . . {Means for fixing the blowing means with the mould}	2049/622	. . . . . {Air gaps between closed mould halves}
2049/581	. . . . . {Mechanical, e.g. fingers or toothed wheels}	2049/625	. . . . . {by using spacing means between the mould halves}
2049/5813	. . . . . {Hydraulic}	2049/627	. . . . . {Vacuum means}
2049/5817	. . . . . {Pneumatic}	49/64	. . . . . Heating or cooling preforms, parisons or blown articles
2049/582	. . . . . {Magnetic, e.g. permanent magnets}	49/6409	. . . . . {Thermal conditioning of preforms <a href="#">(B29C 49/68 takes precedence)</a> }
2049/5824	. . . . . {Electromagnetic means, e.g. electromagnets}	49/6418	. . . . . {by reheating cold preforms in a single stage <a href="#">(B29C 49/6436 takes precedence)</a> }
2049/5827	. . . . . {Blowing means not touching the preform}	49/6427	. . . . . {by cooling hot or molten preforms in a single stage <a href="#">(B29C 49/6436 takes precedence)</a> }
2049/5831	. . . . . {Diaphragms or bellows protecting the blowing means against contamination}	49/6436	. . . . . {producing a temperature differential}
2049/5834	. . . . . {Lost blowing means}	49/6445	. . . . . {through the preform length}
2049/5837	. . . . . {Plural independent blowing means}	49/6454	. . . . . {along the preform thickness}
2049/5841	. . . . . {Plural independent blowing paths}	49/6463	. . . . . {Mandrels or cores specially adapted for heating or cooling preforms}
2049/5844	. . . . . {Compacting means, e.g. to compact the neck portion of the blown article with the blowing means}	49/6472	. . . . . {in several stages <a href="#">(B29C 49/6409 takes precedence)</a> }
2049/5848	. . . . . {Cutting means, e.g. to cut parts of the preform or parison with the blowing means}	49/6481	. . . . . {using several mould cavities for each article}
2049/5851	. . . . . {Means to avoid clogging of the blowing paths}	49/649	. . . . . {at least one stage being a heating stage used for shrinking of a preform prior to a subsequent blowing stage}
2049/5855	. . . . . {allowing injecting additional cooling medium during the blowing operation, e.g. water droplets}	49/66	. . . . . Cooling by refrigerant introduced into the blown article
2049/5858	. . . . . {Connecting means, e.g. to allow connection of fluid supply lines to the blowing means}	2049/6607	. . . . . {Flushing blown articles}
2049/5862	. . . . . {Drive means therefore}	2049/6615	. . . . . {and exhausting through the blowing means}
2049/5865	. . . . . {Pneumatic}	2049/6623	. . . . . {and exhausting through an opening in the blown article}
2049/5868	. . . . . {Hydraulic}	2049/663	. . . . . {against ambient pressure}
2049/5872	. . . . . {Mechanical}	2049/6638	. . . . . {against a pressure higher than ambient pressure}
2049/5875	. . . . . {Electric direct drives, e.g. linear electric motor}	2049/6646	. . . . . {while keeping the final blowing pressure in the article}
2049/5879	. . . . . {Magnetic means, e.g. permanent magnets}	2049/6653	. . . . . {the refrigerant being other than cooled air}
2049/5882	. . . . . {Electromagnetic means, e.g. electromagnets}	2049/6661	. . . . . {the refrigerant being water}
2049/5886	. . . . . {for introducing from below into the extruded parison, e.g. for reducing contamination of the preforms or parisons}	2049/6669	. . . . . {the refrigerant being gas with water droplets}
2049/5889	. . . . . {being cooled}	2049/6676	. . . . . {the refrigerant being oriented towards special areas of the blown article}
2049/5893	. . . . . {Mounting, exchanging or centering blowing means}	2049/6684	. . . . . {Neck area}
2049/5896	. . . . . {Centering means therefore}	2049/6692	. . . . . {Bottom area}
49/60	. . . . . Blow-needles	49/68	. . . . . Ovens specially adapted for heating preforms or parisons
2049/6009	. . . . . {Constructional features}	49/70	. . . . . Removing or ejecting blown articles from the mould
2049/6018	. . . . . {related to the air outlet}	2049/701	. . . . . {Ejecting means}
2049/6027	. . . . . {Having several air outlets, e.g. for directing the blowing fluid in different directions}	2049/702	. . . . . {Air pressure}
2049/6036	. . . . . {the air outlet being located distant from the end of the needle}	2049/704	. . . . . {Pins}

- 2049/705 . . . . . {Driving means therefore}
- 2049/707 . . . . . {Hydraulic}
- 2049/708 . . . . . {Pneumatic}
- 49/72 . . Deflashing outside the mould
- 2049/725 . . . {Means for removing the deflashed parts from the deflashing area, e.g. burrs being removed from the deflashing area by a conveyor}
- 49/74 . . . Deflashing the neck portion
- 49/76 . . Neck calibration
- 49/78 . . Measuring, controlling or regulating
- 49/783 . . . {the blowing pressure}
- 49/786 . . . {the temperature}
- 49/80 . . . Testing, e.g. for leaks
- 51/00 Shaping by thermoforming {, i.e. shaping sheets or sheet like preforms after heating}, e.g. shaping sheets in matched moulds or by deep-drawing; Apparatus therefor {(blow moulding of tubular preforms B29C 49/00, deforming of tubular or hollow preforms B29C 67/0014)}**
- 51/002 . {characterised by the choice of material}
- NOTE**  
When classifying in this group, it is desirable to add the indexing codes of subclass [B29K](#) to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
- 51/004 . . {Textile or other fibrous material made from plastics fibres (combined with plastic layers [B29C 51/145](#); compression moulding of reinforced plastic articles in matched moulds [B29C 70/46](#); using pressure difference [B29C 70/44](#))}
- 51/006 . {for making articles having hollow walls}
- 51/008 . {without using a mould, e.g. ballooning (as prestretching step [B29C 51/06](#))}
- 51/02 . Combined thermoforming and manufacture of the preform
- 51/04 . Combined thermoforming and prestretching, e.g. biaxial stretching
- 51/06 . . using pressure difference {for prestretching}
- 51/08 . Deep drawing or matched-mould forming, i.e. using mechanical means only
- 51/082 . . {by shaping between complementary mould parts}
- 51/085 . . . {with at least one of the shaping surfaces being made of resilient material, e.g. rubber}
- 51/087 . . . {with at least one of the mould parts comprising independently movable sections ([B29C 51/32](#) and [B29C 51/34](#) take precedence)}
- 51/10 . Forming by pressure difference, e.g. vacuum
- 51/105 . . {Twin sheet thermoforming, i.e. deforming two parallel opposing sheets or foils at the same time by using one common mould cavity and without welding them together during thermoforming ([B29C 51/267](#), [B29C 49/0047](#) take precedence)}
- 51/12 . of articles having inserts or reinforcements
- 51/14 . using multilayered preforms or sheets
- 51/145 . . {having at least one layer of textile or fibrous material combined with at least one plastics layer}
- 51/16 . Lining or labelling
- 51/162 . . {of deep containers or boxes}
- 51/165 . . {combined with the feeding or the shaping of the lining or the labels (by injection moulding [B29C 45/14008](#), [B29C 45/1418](#))}
- 51/167 . . . {of a continuous strip}
- 51/18 . Thermoforming apparatus
- 51/20 . . having movable moulds or mould parts
- 51/22 . . . rotatable about an axis
- 51/225 . . . . {mounted on a vacuum drum (for surface shaping [B29C 59/06](#))}
- 51/24 . . . mounted on movable endless supports
- 51/26 . Component parts, details or accessories; Auxiliary operations
- 51/261 . . {Handling means, e.g. transfer means, feeding means ([B29C 51/44](#) takes precedence)}
- 51/262 . . . {Clamping means for the sheets, e.g. clamping frames}
- 51/263 . . {characterised by using a particular environment, e.g. sterile}
- 51/264 . . {Auxiliary operations prior to the thermoforming operation, e.g. cutting ([B29C 51/42](#), [B29C 51/46](#) take precedence)}
- 51/265 . . {Auxiliary operations during the thermoforming operation ([B29C 51/42](#), [B29C 51/46](#) take precedence)}
- 51/266 . . {Auxiliary operations after the thermoforming operation ([B29C 51/42](#), [B29C 51/44](#), [B29C 51/46](#) take precedence)}
- 51/267 . . . {Two sheets being thermoformed in separate mould parts and joined together while still in the mould ([B29C 49/0047](#) takes precedence)}
- 51/268 . . . {Cutting, rearranging and joining the cut parts}
- 51/28 . . for applying pressure through the wall of an inflated bag or diaphragm
- 51/30 . . Moulds
- 51/303 . . . {with sealing means or the like}
- 51/306 . . . {with means for forming a rim (combined with cutting [B29C 51/325](#); rim rolling [per se](#) [B29C 53/34](#))}
- 51/32 . . . having cutting means
- 51/325 . . . . {combined with means for forming a rim}
- 51/34 . . . for undercut articles
- 51/343 . . . . {having recessed undersurfaces}
- 51/346 . . . . {specially adapted to facilitate the destacking of nestable containers}
- 51/36 . . . specially adapted for vacuum forming {, Manufacture thereof}
- 51/365 . . . . {Porous moulds}
- 51/38 . . . Opening, closing or clamping means
- 51/40 . . . Venting means
- 51/42 . . Heating or cooling
- 51/421 . . . {of preforms, specially adapted for thermoforming (preheating sheets in general [B29B 13/023](#); [B29C 51/427](#) takes precedence)}
- 51/422 . . . . {to produce a temperature differential ([B29C 51/426](#) takes precedence)}
- 51/423 . . . . . {through the thickness of the preform}
- 51/424 . . . . {using a heated fluid}
- 51/425 . . . . {using movable heating devices}

51/426	. . . {Producing specific thermal regimes during thermoforming to obtain particular properties}	2053/365	. . . {provided with a string}
51/427	. . . {Cooling of the material with a fluid blast}	2053/367	. . . {provided with a strip}
51/428	. . . {of moulds or mould parts}	53/38	. . by bending sheets or strips at right angles to the longitudinal axis of the article being formed and joining the edges
51/44	. . Removing or ejecting moulded articles	53/382	. . . {using laminated sheets}
51/445	. . . {from a support after moulding, e.g. by cutting}	53/385	. . . {using several sheets to form the circumference}
51/46	. . Measuring, controlling or regulating	53/387	. . . {the joining being done from the inside}
<b>53/00</b>	<b>Shaping by bending, folding, twisting, straightening or flattening; Apparatus therefor (B29C 61/10 takes precedence)</b>	53/40	. . . for articles of definite length, i.e. discrete articles
53/005	. {characterised by the choice of material (B29C 53/36 and B29C 53/56 take precedence)}	53/42	. . . . using internal forming surfaces, e.g. mandrels
<b>NOTE</b>		53/44	. . . . . rotatable about the axis of the article
	When classifying in this group, it is desirable to add the indexing codes of subclass <a href="#">B29K</a> to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest	53/46	. . . . using external forming surfaces, e.g. sleeves
		53/48	. . . for articles of indefinite length, i.e. bending a strip progressively
53/02	. Bending or folding ( <a href="#">B29C 53/22</a> , <a href="#">B29C 53/34</a> , <a href="#">B29C 53/36</a> , <a href="#">B29C 53/56</a> take precedence)	53/50	. . . . using internal forming surfaces, e.g. mandrels
53/025	. . {using a folding bag}	53/52	. . . . using external forming surfaces, e.g. sleeves
53/04	. . of plates or sheets {( <a href="#">B29C 63/04</a> takes precedence; bending or folding paper <a href="#">B31F 1/0003</a> ; folding films <a href="#">B65H 45/00</a> )}	53/54	. . . . Guiding, aligning or shaping edges
53/043	. . . {using rolls or endless belts}	53/56	. Winding and joining, e.g. winding spirally {( <a href="#">winding in general B65H</a> )}
53/046	. . . {using centrifugal force}	53/562	. . {spirally}
53/06	. . . Forming folding lines by pressing or scoring	53/564	. . {for making non-tubular articles (for winding of reinforced articles having a non-circular cross-section followed by compression <a href="#">B29C 70/347</a> )}
53/063	. . . . {combined with folding}	53/566	. . {for making tubular articles followed by compression}
53/066	. . . . . {and joining the sides of the folding line, e.g. "Abkantschweissen"}	53/568	. . {without using a forming surface}
53/08	. . of tubes {or other profiled members}	53/58	. . helically
53/083	. . . {bending longitudinally, i.e. modifying the curvature of the tube axis}	53/581	. . . {using sheets or strips consisting principally of plastics material (using profiled sheets or strips <a href="#">B29C 53/78</a> )}
53/086	. . . {bending radially, i.e. deforming the cross-section of the tube}	53/582	. . . . {comprising reinforcements, e.g. wires, threads}
53/10	. . of blown tubular films, e.g. gusseting {(flattening blown films during extrusion moulding <a href="#">B29C 47/0009</a> )}	53/583	. . . {for making tubular articles with particular features}
53/12	. . helically, e.g. for making springs {(for textile fibres <a href="#">D02G 1/00</a> )}	53/584	. . . . {having a non-circular cross-section}
53/14	. Twisting {(for textile fibres <a href="#">D01H</a> )}	53/585	. . . . {the cross-section varying along their axis, e.g. tapered, with ribs, or threads, with socket-ends}
53/16	. Straightening or flattening	53/586	. . . . . {having corrugations}
53/18	. . of plates or sheets	53/587	. . . . {having a non-uniform wall-structure, e.g. with inserts, perforations, locally concentrated reinforcements}
53/20	. . of tubes	53/588	. . . . {having a non-linear axis, e.g. elbows, toroids}
53/22	. Corrugating	53/60	. . . using internal forming surfaces, e.g. mandrels
53/24	. . of plates or sheets	53/602	. . . . {for tubular articles having closed or nearly closed ends, e.g. vessels, tanks, containers}
53/26	. . . parallel with direction of feed	53/605	. . . . . {by polar winding}
53/265	. . . . {using rolls or endless bands}	53/607	. . . . {having driving means for advancing the wound articles, e.g. belts, rolls ( <a href="#">B29C 53/74</a> takes precedence)}
53/28	. . . transverse to direction of feed	53/62	. . . . . rotatable about the winding axis
53/285	. . . . {using rolls or endless bands}	53/64	. . . . . and moving axially
53/30	. . of tubes (by blow-moulding <a href="#">B29C 49/00</a> )	53/66	. . . . . with axially movable winding feed member {, e.g. lathe type winding}
53/305	. . . {using a cording process}	53/665	. . . . . {Coordinating the movements of the winding feed member and the mandrel}
53/32	. Coiling ( <a href="#">B29C 53/56</a> takes precedence)	53/68	. . . . with rotatable winding feed member
53/34	. Rim rolling (of tube ends <a href="#">B29C 57/12</a> )	53/70	. . . . . and moving axially
53/36	. Bending and joining, e.g. for making hollow articles ( <a href="#">B29C 53/56</a> takes precedence; from paper <a href="#">B31C</a> {, <a href="#">B31F</a> })		
2053/362	. . {for making hems}		

- 53/72 . . . using external forming surfaces
- 53/74 . . . using a forming surface in the shape of an endless belt which is recycled after the forming operation
- 53/76 . . . about more than one axis {, e.g. T-pieces, balls}
- 53/78 . . . using profiled sheets or strips
- 53/785 . . . . {with reinforcements}
- 53/80 . Component parts, details or accessories; Auxiliary operations
- 53/8008 . . {specially adapted for winding and joining}
- 53/8016 . . . {Storing, feeding or applying winding materials, e.g. reels, thread guides, tensioners}
- 2053/8025 . . . . {tensioning}
- 2053/8033 . . . . {fixing the trailing edge of winding materials}
- 53/8041 . . . {Measuring, controlling or regulating (B29C 53/665 takes precedence)}
- 53/805 . . . {Applying axial reinforcements}
- 53/8058 . . . . {continuously}
- 53/8066 . . . {Impregnating (impregnating as pretreatment B29B 15/10)}
- 53/8075 . . . . {on the forming surfaces}
- 53/8083 . . . {Improving bonding of wound materials or layers}
- 53/8091 . . . {Cutting the ends, surface finishing}
- 53/82 . . Cores or mandrels
- 53/821 . . . {Mandrels especially adapted for winding and joining}
- 53/822 . . . . {Single use mandrels, e.g. destructible, becoming part of the wound articles (B29C 53/825 takes precedence)}
- 53/824 . . . . {collapsible, e.g. elastic or inflatable; with removable parts, e.g. for regular shaped, straight tubular articles (B29C 53/825 takes precedence)}
- 53/825 . . . . {for continuous winding}
- 53/827 . . . . {formed by several elements rotating about their own axes}
- 53/828 . . . . {Arrangements comprising a plurality of cores or mandrels, e.g. to increase production speed (B29C 53/827 takes precedence)}
- 53/84 . . Heating or cooling
- 53/845 . . . {especially adapted for winding and joining}
- 55/00 Shaping by stretching, e.g. drawing through a die; Apparatus therefor (B29C 61/08 takes precedence)**
- 55/005 . {characterised by the choice of materials}
- NOTE**
- When classifying in this group, it is desirable to add the indexing codes of subclass [B29K](#) to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
- 55/02 . of plates or sheets
- 55/023 . . {using multilayered plates or sheets}
- 55/026 . . . {of preformed plates or sheets coated with a solution, a dispersion or a melt of thermoplastic material}
- 55/04 . . uniaxial, e.g. oblique
- 55/045 . . . {in a direction which is not parallel or transverse to the direction of feed, e.g. oblique}
- 55/06 . . . parallel with the direction of feed
- 55/065 . . . . {in several stretching steps}
- 55/08 . . . transverse to the direction of feed
- 55/085 . . . . {in several stretching steps}
- 55/10 . . multiaxial
- 55/12 . . . biaxial
- 55/14 . . . . successively
- 55/143 . . . . . {firstly parallel to the direction of feed and then transversely thereto}
- 55/146 . . . . . {firstly transversely to the direction of feed and then parallel thereto}
- 55/16 . . . . simultaneously
- 55/165 . . . . . {Apparatus therefor}
- 55/18 . . by squeezing between surfaces, e.g. rollers
- 55/20 . . Edge clamps
- 55/22 . of tubes { (B29C 61/08 takes precedence)}
- 55/24 . . radial
- 55/26 . . biaxial
- 55/28 . of blown tubular films, e.g. by inflation {(extrusion moulding of tubular films B29C 47/0009)}
- 55/285 . . {by using internal mechanical means}
- 55/30 . Drawing through a die {(pultrusion B29C 70/52)}
- 57/00 Shaping of tube ends, e.g. flanging, bellling, closing; Apparatus therefor {, e.g. collapsible mandrels}**
- 57/005 . {the end of an internal lining (fixing the end of the lining B29C 63/346)}
- 57/02 . Bellling or enlarging, e.g. combined with forming a groove
- 57/025 . . {combined with the introduction of a sealing ring, e.g. using the sealing element as forming element}
- 57/04 . . using mechanical means {(B29C 57/025 takes precedence)}
- 57/045 . . . {rotating}
- 57/06 . . . elastically deformable
- 57/08 . . using pressure difference
- 57/10 . Closing
- 57/12 . Rim rolling
- 57/125 . . {using tools with helical grooves}
- 59/00 Surface shaping {of articles}, e.g. embossing; Apparatus therefor {(in-mould printing B29C 37/0025; by using liquids B29C 71/0009; by using gases without chemical reaction B29C 71/009; for decorating in general B44; abrasive blasting B24C; chemical aspects C08J 7/00)}**
- 59/002 . {Component parts, details or accessories; Auxiliary operations}
- 59/005 . {characterised by the choice of material}
- NOTE**
- Documents in which moulding materials are mentioned are indexed using indexing codes of subclass [B29K](#). However, when, for example, documents concerning the choice of moulding material having a particular influence on the moulding technique cannot be satisfactorily indexed, the documents may be classified in this group if of interest



59/007	<ul style="list-style-type: none"> <li>{Forming single grooves or ribs, e.g. tear lines, weak spots (by moulding <a href="#">B29C 37/0057</a>; folding lines <a href="#">B29C 53/06</a>; in metal articles <a href="#">B21D 17/00</a>; by cutting <a href="#">B26D 3/08</a>)}</li> </ul>	moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
59/02	<ul style="list-style-type: none"> <li>by mechanical means, e.g. pressing {(B29C 59/007 takes precedence; embossing expanded porous articles <a href="#">B29C 44/5627</a>)}</li> </ul>	61/006 <ul style="list-style-type: none"> <li>{the force created by the liberation of the internal stresses being used for compression moulding or for pressing preformed material}</li> </ul>
59/021	<ul style="list-style-type: none"> <li>. . {of profiled articles, e.g. hollow or tubular articles, beams}</li> </ul>	61/02 <ul style="list-style-type: none"> <li>Thermal shrinking</li> </ul>
59/022	<ul style="list-style-type: none"> <li>. . {characterised by the disposition or the configuration, e.g. dimensions, of the embossments or the shaping tools therefor}</li> </ul>	61/025 <ul style="list-style-type: none"> <li>. . {for the production of hollow or tubular articles}</li> </ul>
2059/023	<ul style="list-style-type: none"> <li>. . . {Microembossing}</li> </ul>	61/04 <ul style="list-style-type: none"> <li>Thermal expansion</li> </ul>
59/025	<ul style="list-style-type: none"> <li>. . . {Fibrous surfaces with piles or similar fibres substantially perpendicular to the surface}</li> </ul>	61/06 <ul style="list-style-type: none"> <li>Making preforms having internal stresses, e.g. plastic memory</li> </ul>
59/026	<ul style="list-style-type: none"> <li>. . {of layered or coated substantially flat surfaces}</li> </ul>	61/0608 <ul style="list-style-type: none"> <li>. . {characterised by the configuration or structure of the preforms}</li> </ul>
2059/027	<ul style="list-style-type: none"> <li>. . {Grinding; Polishing}</li> </ul>	61/0616 <ul style="list-style-type: none"> <li>. . . {layered or partially layered preforms, e.g. preforms with layers of adhesive or sealing compositions (<a href="#">B29C 61/0625</a> and <a href="#">B29C 61/065</a> take precedence)}</li> </ul>
2059/028	<ul style="list-style-type: none"> <li>. . {Incorporating particles by impact in the surface, e.g. using fluid jets or explosive forces to implant particles}</li> </ul>	61/0625 <ul style="list-style-type: none"> <li>. . . {Preforms comprising incorporated or associated heating means}</li> </ul>
59/04	<ul style="list-style-type: none"> <li>. . using rollers or endless belts</li> </ul>	61/0633 <ul style="list-style-type: none"> <li>. . . {Preforms comprising reinforcing elements (<a href="#">B29C 61/0625</a> takes precedence)}</li> </ul>
59/043	<ul style="list-style-type: none"> <li>. . . {for profiled articles}</li> </ul>	61/0641 <ul style="list-style-type: none"> <li>. . . {Clips for dividing preforms or forming branch-offs (clips in general <a href="#">F16B 2/20</a>)}</li> </ul>
59/046	<ul style="list-style-type: none"> <li>. . . {for layered or coated substantially flat surfaces}</li> </ul>	61/065 <ul style="list-style-type: none"> <li>. . . {Preforms held in a stressed condition by means of a removable support; Supports therefor}</li> </ul>
59/06	<ul style="list-style-type: none"> <li>. . using vacuum drums {(for thermoforming <a href="#">B29C 51/225</a>)}</li> </ul>	61/0658 <ul style="list-style-type: none"> <li>. . . {consisting of fibrous plastics material, e.g. woven}</li> </ul>
59/08	<ul style="list-style-type: none"> <li>by flame treatment {; using hot gases}</li> </ul>	61/0666 <ul style="list-style-type: none"> <li>. . . {comprising means indicating that the shrinking temperature is reached}</li> </ul>
59/085	<ul style="list-style-type: none"> <li>. . {of profiled articles, e.g. hollow or tubular articles}</li> </ul>	2061/0675 <ul style="list-style-type: none"> <li>. . . . {the means being a material exuding outside the preform when the temperature is reached}</li> </ul>
59/10	<ul style="list-style-type: none"> <li>by electric discharge treatment (electrodes <a href="#">H01T</a>)</li> </ul>	2061/0683 <ul style="list-style-type: none"> <li>. . . . {the means being a thermochromic painting or coating}</li> </ul>
59/103	<ul style="list-style-type: none"> <li>. . {of profiled articles, e.g. hollow or tubular articles}</li> </ul>	2061/0691 <ul style="list-style-type: none"> <li>. . . . {the means being protrusions on the preform surface disappearing when the temperature is reached}</li> </ul>
59/106	<ul style="list-style-type: none"> <li>. . {the electrodes being placed on the same side of the material to be treated}</li> </ul>	61/08 <ul style="list-style-type: none"> <li>. . by stretching tubes {(in general <a href="#">B29C 55/22</a>, <a href="#">B29C 55/28</a>)}</li> </ul>
59/12	<ul style="list-style-type: none"> <li>. . in an environment other than air</li> </ul>	61/10 <ul style="list-style-type: none"> <li>. . by bending plates or sheets {(in general <a href="#">B29C 53/36</a>)}</li> </ul>
59/14	<ul style="list-style-type: none"> <li>by plasma treatment (in general <a href="#">H05H</a> {; plasma tubes per se <a href="#">H01J</a>)}</li> </ul>	<b>63/00 Lining or sheathing, i.e. applying preformed layers or sheathings of plastics; Apparatus therefor</b> ( <a href="#">B29C 73/00</a> takes precedence; by blowing <a href="#">B29C 49/00</a> ; by thermoforming <a href="#">B29C 51/00</a> )
59/142	<ul style="list-style-type: none"> <li>. . {of profiled articles, e.g. hollow or tubular articles}</li> </ul>	63/0004 <ul style="list-style-type: none"> <li>. {Component parts, details or accessories; Auxiliary operations}</li> </ul>
2059/145	<ul style="list-style-type: none"> <li>. . {Atmospheric plasma}</li> </ul>	2063/0008 <ul style="list-style-type: none"> <li>. . {Registering, centering the lining material on the substrate}</li> </ul>
2059/147	<ul style="list-style-type: none"> <li>. . {Low pressure plasma; Glow discharge plasma}</li> </ul>	63/0013 <ul style="list-style-type: none"> <li>. . {Removing old coatings}</li> </ul>
59/16	<ul style="list-style-type: none"> <li>by wave energy or particle radiation {, e.g. infra-red heating (<a href="#">B29C 59/007</a> takes precedence)}</li> </ul>	63/0017 <ul style="list-style-type: none"> <li>. {characterised by the choice of the material}</li> </ul>
59/165	<ul style="list-style-type: none"> <li>. . {of profiled articles, e.g. hollow or tubular articles}</li> </ul>	<b>NOTE</b>
59/18	<ul style="list-style-type: none"> <li>by liberation of internal stresses, e.g. plastic memory</li> </ul>	When classifying in this group, it is desirable to add the indexing codes of subclass <a href="#">B29K</a> to identify the moulding materials and their properties. Documents concerning the choice of moulding materials having a particular influence on the moulding technique should be classified in this group if of interest
<b>61/00</b>	<b>Shaping by liberation of internal stresses; Making preforms having internal stresses; Apparatus therefor</b> (for surface shaping <a href="#">B29C 59/18</a> ; for lining articles <a href="#">B29C 63/38</a> ; for joining preformed parts <a href="#">B29C 65/66</a> {; for packaging <a href="#">B65B 53/00</a> ; connecting arrangements or other fittings for plastics pipes using shrink-down material <a href="#">F16L 47/22</a> , electrical connections insulated using heat shrinking insulating sleeves <a href="#">H01R 4/72</a> ; cable junctions protected by sleeves <a href="#">H02G 15/18</a> )}	63/0021 <ul style="list-style-type: none"> <li>. . {with coherent impregnated reinforcing layers}</li> </ul>
61/003	<ul style="list-style-type: none"> <li>. {characterised by the choice of material}</li> </ul>	
	<b>NOTE</b>	
	When classifying in this group, it is desirable to add the indexing codes of subclass <a href="#">B29K</a> to identify the moulding materials and their properties. Documents concerning the choice of	

- 63/0026 . {an edge face with strip material, e.g. a panel edge (securing a veneer strip to a panel edge [B27D 5/003](#))}
- 63/003 . . {continuously}
- 63/0034 . . {the strip material being folded}
- 63/0039 . . . {continuously}
- 63/0043 . {Fixing the layers by electrostatic charges, by the use of structured surfaces or by mechanical means}
- 63/0047 . {Preventing air-inclusions}
- 63/0052 . {Testing, e.g. testing for the presence of pinholes}
- 63/0056 . {Provisional sheathings}
- 2063/006 . {of surfaces having irregularities or roughness}
- 63/0065 . {Heat treatment}
- 63/0069 . . {of tubular articles}
- 63/0073 . {of non-flat surfaces, e.g. curved, profiled ([B29C 63/042](#) takes precedence)}
- 63/0078 . . {having local protrusions, e.g. rivet heads}
- 63/0082 . {Finishing the edges of holes or perforations in the lined product}
- 63/0086 . . {and removing the portion of the lining covering the holes}
- 63/0091 . {in particular atmospheres}
- 63/0095 . {using a provisional carrier}
- 63/02 . using sheet or web-like material ([B29C 63/26](#) {and [B29C 63/38](#)} take precedence)
- 2063/021 . . {characterized by the junction of material sections}
- 2063/022 . . . {the junction being located in a groove}
- 63/024 . . {the sheet or web-like material being supported by a moving carriage}
- 63/025 . . {applied by a die matching with the profile of the surface of resilient articles, e.g. cushions, seat pads}
- 2063/027 . . {applied by a squeegee}
- 2063/028 . . {applied by a fluid jet}
- 63/04 . . by folding, winding, bending or the like
- 63/042 . . . {of L- or Z- shaped surfaces, e.g. for counter-tops}
- 63/044 . . . {continuously ([B29C 63/065](#), [B29C 63/105](#) take precedence)}
- 63/046 . . . {using a folding shoulder}
- 63/048 . . . {specially adapted for articles having local protrusions, e.g. tubes having a bead weld}
- 63/06 . . . around tubular articles
- 63/065 . . . . {continuously}
- 63/08 . . . by winding helically
- 63/10 . . . . around tubular articles
- 63/105 . . . . . {continuously}
- 63/12 . . . by winding spirally
- 63/14 . . . . around tubular articles
- 63/145 . . . . . {the tubular articles being mounted on transfer means}
- 63/16 . . applied by "rubber" bag or diaphragm
- 63/18 . using tubular layers or sheathings ([B29C 63/26](#) {and [B29C 63/38](#)} take precedence; {placing tubular labels around rigid containers [B65C 3/065](#)})
- 63/182 . . {applied by a "rubber" bag or diaphragm}
- 63/185 . . {by turning inside-out or by derolling}
- 63/187 . . {by removing a shirred or pleated hose from a support}
- 63/20 . . using pressure difference, e.g. vacuum
- 63/22 . using layers or sheathings having a shape adapted to the shape of the article ([B29C 63/26](#) {and [B29C 63/38](#)} take precedence)
- 63/24 . using threads
- 63/26 . Lining or sheathing of internal surfaces ([B29C 63/38](#) takes precedence)
- 63/28 . . applied by "rubber" bag or diaphragm
- 63/30 . . using sheet or web-like material
- 63/32 . . . by winding helically
- 63/34 . . using tubular layers or sheathings
- 63/341 . . . {pressed against the wall by mechanical means}
- 63/343 . . . {the tubular sheathing having a deformed non-circular cross-section prior to introduction}
- 63/345 . . . {whilst rotating the article}
- 63/346 . . . {Fixing the end of the lining (shaping tube ends [B29C 57/005](#))}
- 2063/348 . . . {combined with reducing the diameter of the substrate to be lined}
- 63/36 . . . being turned inside out {(for plastic tubes in general [B29C 67/0018](#))}
- 63/38 . by liberation of internal stresses
- 63/40 . . using sheet or web-like material
- 63/42 . . using tubular layers or sheathings
- 63/423 . . . {specially applied to the mass-production of externally coated articles, e.g. bottles}
- 63/426 . . . . {in combination with the *in situ* shaping of the external tubular layer}
- 63/44 . . the shape of the layers or sheathings being adapted to the shape of the articles
- 63/46 . . of internal surfaces
- 63/48 . Preparation of the surfaces
- 63/481 . . {mechanically}
- 2063/483 . . {by applying a liquid}
- 2063/485 . . . {the liquid being an adhesive}
- 63/486 . . {of metal surfaces ([B29C 63/481](#) takes precedence)}
- 2063/488 . . {providing the surface with fixing elements on which the plastic liner is bonded}
- 64/00 Additive manufacturing, i.e. manufacturing of three-dimensional [3D] objects by additive deposition, additive agglomeration or additive layering, e.g. by 3D printing, stereolithography or selective laser sintering**
- WARNING**  
Group [B29C 64/00](#) is impacted by reclassification into groups [B29C 64/10](#) - [B29C 64/379](#).  
All groups listed in this Warning should be considered in order to perform a complete search.
- 64/10 . Processes of additive manufacturing
- WARNING**  
Group [B29C 64/10](#) is incomplete pending reclassification of documents from group [B29C 64/00](#).  
Groups [B29C 64/10](#) and [B29C 64/00](#) should be considered in order to perform a complete search.

- 64/106 . . . using only liquids or viscous materials, e.g. depositing a continuous bead of viscous material

**WARNING**

Group [B29C 64/106](#) is impacted by reclassification into group [B29C 64/118](#).  
Groups [B29C 64/106](#) and [B29C 64/118](#) should be considered in order to perform a complete search.

- 64/112 . . . using individual droplets, e.g. from jetting heads

- 64/118 . . . using filamentary material being melted, e.g. fused deposition modelling [FDM]

**WARNING**

Group [B29C 64/118](#) is incomplete pending reclassification of documents from group [B29C 64/106](#).

Groups [B29C 64/106](#) and [B29C 64/118](#) should be considered in order to perform a complete search.

- 64/124 . . . using layers of liquid which are selectively solidified

- 64/129 . . . characterised by the energy source therefor, e.g. by global irradiation combined with a mask

- 64/135 . . . . the energy source being concentrated, e.g. scanning lasers or focused light sources

- 64/141 . . using only solid materials

**WARNING**

Group [B29C 64/141](#) is impacted by reclassification into group [B29C 64/147](#).

Groups [B29C 64/141](#) and [B29C 64/147](#) should be considered in order to perform a complete search.

- 64/147 . . . using sheet material, e.g. laminated object manufacturing [LOM] or laminating sheet material precut to local cross sections of the 3D object

**WARNING**

Group [B29C 64/147](#) is incomplete pending reclassification of documents from group [B29C 64/141](#).

Groups [B29C 64/141](#) and [B29C 64/147](#) should be considered in order to perform a complete search.

- 64/153 . . . using layers of powder being selectively joined, e.g. by selective laser sintering or melting

- 64/159 . . using only gaseous substances, e.g. vapour deposition

**WARNING**

Group [B29C 64/159](#) is incomplete pending reclassification of documents from group [B29C 64/00](#).

Groups [B29C 64/00](#) and [B29C 64/159](#) should be considered in order to perform a complete search.

- 64/165 . . . using a combination of solid and fluid materials, e.g. a powder selectively bound by a liquid binder, catalyst, inhibitor or energy absorber
- 64/171 . . specially adapted for manufacturing multiple 3D objects

**WARNING**

Group [B29C 64/171](#) – [B29C 64/182](#) are incomplete pending reclassification of documents from group [B29C 64/00](#).

Groups [B29C 64/00](#) and [B29C 64/171](#) – [B29C 64/182](#) should be considered in order to perform a complete search.

- 64/176 . . . . Sequentially

- 64/182 . . . in parallel batches

- 64/188 . . involving additional operations performed on the added layers, e.g. smoothing, grinding or thickness control ([surface shaping B29C 59/00](#); [after-treatment of articles without altering their shape B29C 71/00](#))

**WARNING**

Group [B29C 64/188](#) and [B29C 64/194](#) are incomplete pending reclassification of documents from group [B29C 64/00](#).

Groups [B29C 64/00](#), [B29C 64/188](#) and [B29C 64/194](#) should be considered in order to perform a complete search.

- 64/194 . . . during lay-up

- 64/20 . . Apparatus for additive manufacturing; Details thereof or accessories therefor

**WARNING**

Group [B29C 64/20](#) is impacted by reclassification into groups [B29C 64/205](#) - [B29C 64/379](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 64/205 . . Means for applying layers

**WARNING**

Groups [B29C 64/205](#) - [B29C 64/223](#) are incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#) and [B29C 64/205](#) – [B29C 64/223](#) should be considered in order to perform a complete search.

- 64/209 . . . Heads; Nozzles

- 64/214 . . . Doctor blades

- 64/218 . . . Rollers

- 64/223 . . . Foils or films, e.g. for transferring layers of building material from one working station to another

64/227 . . Driving means

**WARNING**

Groups [B29C 64/227](#) – [B29C 64/241](#) are incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#) and [B29C 64/227](#) – [B29C 64/241](#) should be considered in order to perform a complete search.

64/232 . . . for motion along the axis orthogonal to the plane of a layer

64/236 . . . for motion in a direction within the plane of a layer

64/241 . . . for rotary motion

64/245 . . Platforms or substrates (support structures intended to be sacrificed after manufacture [B29C 64/40](#))

**WARNING**

Group [B29C 64/245](#) is incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#) and [B29C 64/245](#) should be considered in order to perform a complete search.

64/25 . . Housings, e.g. machine housings

**WARNING**

Group [B29C 64/25](#) is incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#) and [B29C 64/25](#) should be considered in order to perform a complete search.

64/255 . . Enclosures for the building material, e.g. powder containers

**WARNING**

Group [B29C 64/255](#) and [B29C 64/259](#) are incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#), [B29C 64/255](#) and [B29C 64/259](#) should be considered in order to perform a complete search.

64/259 . . . Interchangeable

64/264 . . Arrangements for irradiation

**WARNING**

Groups [B29C 64/264](#) – [B29C 64/291](#) are incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#) and [B29C 64/264](#) – [B29C 64/291](#) should be considered in order to perform a complete search.

64/268 . . . using laser beams; using electron beams [EB]

64/273 . . . pulsed; frequency modulated

64/277 . . . using multiple radiation means, e.g. micromirrors or multiple light-emitting diodes [LED]

64/282 . . . of the same type, e.g. using different energy levels

64/286 . . . Optical filters, e.g. masks

64/291 . . . for operating globally, e.g. together with selectively applied activators or inhibitors

64/295 . . Heating elements

**WARNING**

Group [B29C 64/295](#) is incomplete pending reclassification of documents from group [B29C 64/20](#).

Groups [B29C 64/20](#) and [B29C 64/295](#) should be considered in order to perform a complete search.

64/30 . . Auxiliary operations or equipment

**WARNING**

Groups [B29C 64/30](#) – [B29C 64/343](#) are incomplete pending reclassification of documents from groups [B29C 64/00](#) and [B29C 64/20](#).

All groups listed in this Warning should be considered in order to perform a complete search.

64/307 . . Handling of material to be used in additive manufacturing

64/314 . . . Preparation

64/321 . . . Feeding

64/329 . . . . using hoppers

64/336 . . . . of two or more materials

64/343 . . . Metering

64/35 . . Cleaning

**WARNING**

Group [B29C 64/35](#) is impacted by reclassification into group [B29C 64/357](#).

Groups [B29C 64/35](#) and [B29C 64/357](#) should be considered in order to perform a complete search.

64/357 . . Recycling

**WARNING**

Group [B29C 64/357](#) is incomplete pending reclassification of documents from group [B29C 64/35](#).

Groups [B29C 64/20](#) and [B29C 64/357](#) should be considered in order to perform a complete search.

64/364 . . Conditioning of environment

**WARNING**

Groups [B29C 64/364](#) and [B29C 64/371](#) are incomplete pending reclassification of documents from groups [B29C 64/00](#) and [B29C 64/20](#).

All groups listed in this Warning should be considered in order to perform a complete search.

64/371 . . . using an environment other than air, e.g. inert gas



- 64/379 . . . Handling of additively manufactured objects, e.g. using robots  
**WARNING**  
 Group [B29C 64/379](#) is incomplete pending reclassification of documents from groups [B29C 64/00](#) and [B29C 64/20](#).  
 Groups [B29C 64/00](#), [B29C 64/20](#), and [B29C 64/379](#) should be considered in order to perform a complete search.
- 64/386 . . . Data acquisition or data processing for additive manufacturing  
**WARNING**  
 Group [B29C 64/386](#) is impacted by reclassification into group [B29C 64/393](#).  
 Groups [B29C 64/386](#) and [B29C 64/393](#) should be considered in order to perform a complete search.
- 64/393 . . . for controlling or regulating additive manufacturing processes  
**WARNING**  
 Group [B29C 64/393](#) is incomplete pending reclassification of documents from group [B29C 64/386](#).  
 Groups [B29C 64/386](#) and [B29C 64/393](#) should be considered in order to perform a complete search.
- 64/40 . . Structures for supporting 3D objects during manufacture and intended to be sacrificed after completion thereof
- 65/00** **Joining {or sealing} of preformed parts, {e.g. welding of plastics materials}; Apparatus therefor** ({general aspects of processes or apparatus for joining preformed parts [B29C 66/00](#); using porous material formed by internal pressure generated therein for joining preformed parts [B29C 44/1228](#), [B29C 44/326](#); } for making boxes, cartons, envelopes or bags [B31B](#); for sealing or securing package folds or closures [B65B 51/00](#); joining constructional elements in general [F16B](#); splicing of light guides [G02B 6/255](#))  
**WARNING**  
 Groups [B29C 65/00](#) - [B29C 65/70](#) are not complete, mainly for documents published before the year 1995, pending reclassification; see also [B29C 65/74](#) and its subgroups
- 65/002 . . {Joining methods not otherwise provided for}  
 65/004 . . {Cold joining}  
 65/006 . . {Diffusion joining (measures for intermixing the material of the joint interlayer [B29C 66/341](#))}  
 65/008 . . {making use of electrostatic charges (holding means using electrostatic forces to hold at least one of the parts to be joined [B29C 65/7852](#))}  
 65/02 . . by heating, with or without pressure  
**WARNING**  
 Group [B29C 65/02](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/48](#) and its subgroups
- 65/022 . . {Particular heating or welding methods not otherwise provided for}  
 65/024 . . . {making use of combustible material, i.e. the combustible material is in contact with the material to be joined}  
 65/026 . . . {making use of hot liquids, i.e. the liquid is in direct contact with the material to be joined}  
 65/028 . . . {making use of inherent heat, i.e. the heat for the joining comes from the moulding process of one of the parts to be joined}  
 65/04 . . Dielectric heating, e.g. high-frequency welding {, i.e. radio frequency welding of plastic materials having dielectric properties, e.g. PVC}  
 65/06 . . using friction, e.g. spin welding {(non-plastics elements to plastic elements [B29C 65/645](#))}  
 65/0609 . . . {characterised by the movement of the parts to be joined ([B29C 65/0672](#) takes precedence)}  
 65/0618 . . . . {Linear}  
 65/0627 . . . . {Angular, i.e. torsional ([B29C 65/082](#) takes precedence)}  
 65/0636 . . . . {Orbital}  
 65/0645 . . . . . {Circular}  
 65/0654 . . . . . {Elliptical}  
 65/0663 . . . . . {Other specific orbital movements not provided for in [B29C 65/0645](#) - [B29C 65/0654](#), e.g. Lissajous}  
 65/0672 . . . {Spin welding}  
 65/0681 . . . {created by a tool}  
 65/069 . . . {the welding tool cooperating with specially formed features of at least one of the parts to be joined, e.g. cooperating with holes or ribs of at least one of the parts to be joined}  
 65/08 . . using ultrasonic vibrations {(non-plastics element to plastics elements [B29C 65/645](#))}  
 65/081 . . . {having a component of vibration not perpendicular to the welding surface}  
 65/082 . . . . {Angular, i.e. torsional ultrasonic welding}  
 65/083 . . . {using a rotary sonotrode or a rotary anvil}  
 65/085 . . . . {using a rotary sonotrode}  
 65/086 . . . . {using a rotary anvil}  
 65/087 . . . . {using both a rotary sonotrode and a rotary anvil}  
 65/088 . . . {using several cooperating sonotrodes, i.e. interacting with each other, e.g. for realising the same joint}  
 65/10 . . using hot gases {(e.g. combustion gases) or flames coming in contact with at least one of the parts to be joined}  
 65/103 . . . {direct heating both surfaces to be joined}  
 65/106 . . . {using flames coming in contact with at least one of the parts to be joined}  
 65/12 . . . and welding bar  
 65/125 . . . . {characterised by the composition of the welding bar}  
 65/14 . . using wave energy {, i.e. electromagnetic radiation, } or particle radiation {(using mechanical waves [B29C 65/06](#); using ultrasonic waves [B29C 65/08](#); pressing means transparent to electromagnetic radiation [B29C 66/81267](#))}  
 65/1403 . . . {characterised by the type of electromagnetic or particle radiation ([B29C 65/1603](#) takes precedence)}  
 65/1406 . . . . {Ultraviolet [UV] radiation}

- 65/1409 . . . . { Visible light radiation }
- 65/1412 . . . . { Infrared [IR] radiation }
- 65/1416 . . . . { Near-infrared radiation [NIR] }
- 65/1419 . . . . { Mid-infrared radiation [MIR] }
- 65/1422 . . . . { Far-infrared radiation [FIR] }
- 65/1425 . . . . { Microwave radiation }
- 65/1429 . . . { characterised by the way of heating the interface ([B29C 65/1629 takes precedence](#)) }
- 65/1432 . . . . { direct heating of the surfaces to be joined }
- 65/1435 . . . . { at least passing through one of the parts to be joined, i.e. transmission welding }
- 65/1438 . . . . { focusing the wave energy or particle radiation on the interface }
- 65/1441 . . . . { making use of a reflector on the opposite side, e.g. a polished mandrel or a mirror ([pressing means reflective to electromagnetic radiation B29C 66/81268](#)) }
- 65/1445 . . . . { heating both sides of the joint }
- 65/1448 . . . . { radiating the edges of the parts to be joined, e.g. for curing a layer of adhesive placed between two flat parts to be joined, e.g. for making CDs or DVDs }
- 65/1451 . . . . { radiating the edges of holes or perforations }
- 65/1454 . . . . { scanning at least one of the parts to be joined }
- 65/1458 . . . . { once, i.e. contour welding }
- 65/1461 . . . . { repeatedly, i.e. quasi-simultaneous welding }
- 65/1464 . . . . { making use of several radiators }
- 65/1467 . . . . { at the same time, i.e. simultaneous welding }
- 65/1477 . . . { making use of an absorber or impact modifier ([B29C 65/1677 takes precedence](#)) }
- 65/148 . . . . { placed at the interface }
- 65/1483 . . . . { coated on the article }
- 65/1487 . . . { making use of light guides ([B29C 65/1687 takes precedence](#)) }
- 65/149 . . . . { being a part of the joined article }
- 65/1493 . . . . { in the form of a cavity }
- 65/1496 . . . { making use of masks ([B29C 65/1696 takes precedence](#)) }
- 65/16 . . . . Laser beams
- 65/1603 . . . . { characterised by the type of electromagnetic radiation }
- 65/1606 . . . . { Ultraviolet [UV] radiation, e.g. by ultraviolet excimer lasers }
- 65/1609 . . . . { Visible light radiation, e.g. by visible light lasers }
- 65/1612 . . . . { Infrared [IR] radiation, e.g. by infrared lasers }
- 65/1616 . . . . { Near infrared radiation [NIR], e.g. by YAG lasers }
- 65/1619 . . . . { Mid infrared radiation [MIR], e.g. by CO or CO<sub>2</sub> lasers }
- 65/1622 . . . . { Far infrared radiation [FIR], e.g. by FIR lasers }
- 65/1629 . . . . { characterised by the way of heating the interface }
- 65/1632 . . . . { direct heating the surfaces to be joined }
- 65/1635 . . . . { at least passing through one of the parts to be joined, i.e. laser transmission welding }
- 65/1638 . . . . { focusing the laser beam on the interface }
- 65/1641 . . . . { making use of a reflector on the opposite side, e.g. a polished mandrel or a mirror ([pressing means reflective to electromagnetic radiation B29C 66/81268](#)) }
- 65/1645 . . . . { heating both sides of the joint, e.g. by using two lasers or a split beam }
- 65/1648 . . . . { radiating the edges of the parts to be joined }
- 65/1651 . . . . { radiating the edges of holes or perforations }
- 65/1654 . . . . { scanning at least one of the parts to be joined }
- 65/1658 . . . . { scanning once, e.g. contour laser welding }
- 65/1661 . . . . { scanning repeatedly, e.g. quasi-simultaneous laser welding }
- 65/1664 . . . . { making use of several radiators }
- 65/1667 . . . . { at the same time, i.e. simultaneous laser welding }
- 65/167 . . . . { using laser diodes }
- 65/1674 . . . . { making use of laser diodes ([B29C 65/167 takes precedence](#)) }
- 65/1677 . . . { making use of an absorber or impact modifier }
- 65/168 . . . . { placed at the interface }
- 65/1683 . . . . { coated on the article }
- 65/1687 . . . . { making use of light guides }
- 65/169 . . . . { being a part of the joined article }
- 65/1693 . . . . { in the form of a cavity }
- 65/1696 . . . . { making use of masks }
- 65/18 . . . . using heated tools
- 65/20 . . . . with direct contact, e.g. using "mirror"
- 65/2007 . . . . { characterised by the type of welding mirror }
- 65/2015 . . . . { being a single welding mirror comprising several separate heating surfaces in different planes, e.g. said heating surfaces having different temperatures }
- 65/2023 . . . . { said welding mirror comprising several sectors }
- 65/203 . . . . { being several single mirrors, e.g. not mounted on the same tool }
- 65/2038 . . . . { being a wire }
- 65/2046 . . . . { using a welding mirror which also cuts the parts to be joined, e.g. for sterile welding }
- 65/2053 . . . . { characterised by special ways of bringing the welding mirrors into position }
- 65/2061 . . . . { by sliding }
- 65/2069 . . . . { with an angle with respect to the plane comprising the parts to be joined }
- 65/2076 . . . . { perpendicularly to the plane comprising the parts to be joined }
- 65/2084 . . . . { by pivoting }
- 65/2092 . . . . { and involving the use of a facer }
- 65/22 . . . . Heated wire { resistive ribbon, resistive band or resistive strip ([electrical insulating support therefor B29C 66/81871](#)) }

- 65/221 . . . . {characterised by the type of heated wire, resistive ribbon, band or strip ([specific electrical or thermal properties also to be classified in B29C 66/81262 or B29C 66/81261](#))}
- 65/222 . . . . . {comprising at least a single heated wire}
- 65/223 . . . . . {comprising several heated wires}
- 65/224 . . . . . {being a resistive ribbon, a resistive band or a resistive strip}
- 65/225 . . . . . {being a coating or being printed, e.g. being applied as a paint or forming a printed circuit}
- 65/226 . . . . . {characterised by the cross-section of said heated wire, resistive ribbon, resistive band or resistive strip, e.g. being triangular}
- 65/227 . . . . . {said cross-section being hollow}
- 65/228 . . . . {characterised by the means for electrically connecting the ends of said heated wire, resistive ribbon, resistive band or resistive strip}
- 65/229 . . . . {characterised by the means for tensioning said heated wire, resistive ribbon, resistive band or resistive strip ([means for compensating for the thermal expansion of welding jaws in general B29C 66/8185](#))}
- 65/24 . . . characterised by the means for heating the tool {([by impulse heating B29C 65/38](#))}
- NOTES**
1. Classification is made in groups [B29C 65/24 - B29C 65/32](#) only if the details or adaptations of the heating means are of interest.
  2. When classifying in this group, heated tools are additionally classified in groups [B29C 65/18](#), [B29C 65/20](#) or [B29C 65/22](#)
- 65/242 . . . . {the heat transfer being achieved by contact, i.e. a heated tool being brought into contact with the welding tool and afterwards withdrawn from it}
- 65/245 . . . . {the heat transfer being achieved contactless, e.g. by radiation ([B29C 65/32 takes precedence](#))}
- 65/247 . . . . {the heat resulting from a chemical reaction}
- 65/26 . . . . Hot fluid
- 65/28 . . . . Flame or combustible material
- 65/30 . . . . Electrical means {([B29C 65/38 takes precedence](#))}
- 65/305 . . . . . {involving the use of cartridge heaters}
- 65/32 . . . . . Induction
- 65/34 . . . using heated elements which remain in the joint, e.g. "verlorenes Schweisselement"
- 65/3404 . . . {characterised by the type of heated elements which remain in the joint ([B29C 65/3604 takes precedence](#))}
- 65/3408 . . . . {comprising single particles, e.g. fillers or discontinuous fibre-reinforcements}
- 65/3412 . . . . . {comprising fillers}
- 65/3416 . . . . . {comprising discontinuous fibre-reinforcements}
- 65/342 . . . . {comprising at least a single wire, e.g. in the form of a winding}
- 65/3424 . . . . . {said at least a single wire having the form of a coil spring}
- 65/3428 . . . . . {said at least a single wire having a waveform, e.g. a sinusoidal form}
- 65/3432 . . . . . {comprising several wires, e.g. in the form of several independent windings ([B29C 65/3436](#), [B29C 65/344 take precedence](#))}
- 65/3436 . . . . {comprising independent continuous fibre-reinforcements}
- 65/344 . . . . {being a woven or non-woven fabric or being a mesh}
- 65/3444 . . . . {being a ribbon, band or strip}
- 65/3448 . . . . . {said ribbon, band or strip being perforated}
- 65/3452 . . . . . {forming a sleeve, e.g. a wrap-around sleeve}
- 65/3456 . . . . {being a layer of a multilayer part to be joined, e.g. for joining plastic-metal laminates}
- 65/346 . . . . {being a coating or being printed, e.g. being applied as a paint or forming a printed circuit}
- 65/3464 . . . . {characterised by the cross-section of said heated elements which remain in the joint or by the cross-section of their coating, e.g. being triangular}
- 65/3468 . . . {characterised by the means for supplying heat to said heated elements which remain in the joint, e.g. special electrical connectors of windings ([B29C 65/3668 takes precedence](#))}
- 65/3472 . . . {characterised by the composition of the heated elements which remain in the joint ([B29C 65/3672 takes precedence](#))}
- 65/3476 . . . . . {being metallic}
- 65/348 . . . . . {with a polymer coating}
- 65/3484 . . . . . {being non-metallic}
- 65/3488 . . . . . {being an electrically conductive polymer}
- 65/3492 . . . . . {being carbon}
- 65/3496 . . . . . {with a coating, e.g. a metallic or a carbon coating}
- 65/36 . . . heated by induction
- 65/3604 . . . . {characterised by the type of elements heated by induction which remain in the joint}
- 65/3608 . . . . . {comprising single particles, e.g. fillers or discontinuous fibre-reinforcements}
- 65/3612 . . . . . {comprising fillers}
- 65/3616 . . . . . {comprising discontinuous fibre-reinforcements}
- 65/362 . . . . . {comprising at least a single wire, e.g. in the form of a winding}
- 65/3624 . . . . . {said at least a single wire having the form of a coil spring}
- 65/3628 . . . . . {said at least a single wire having a waveform, e.g. a sinusoidal form}
- 65/3632 . . . . . {comprising several wires, e.g. in the form of several independent windings ([B29C 65/364 takes precedence](#))}
- 65/3636 . . . . . {comprising independent continuous fibre-reinforcements}
- 65/364 . . . . . {being a woven or non-woven fabric or being a mesh}
- 65/3644 . . . . . {being a ribbon, band or strip}
- 65/3648 . . . . . {said strip being perforated}

- 65/3652 . . . . . {forming a sleeve, e.g. a wrap-around sleeve}
- 65/3656 . . . . . {being a layer of a multilayer part to be joined, e.g. for joining plastic-metal laminates}
- 65/366 . . . . . {being a coating or being printed, e.g. being applied as a paint or forming a printed circuit}
- 65/3668 . . . . . {characterised by the means for supplying heat to said heated elements which remain in the join, e.g. special induction coils}
- 65/3672 . . . . . {characterised by the composition of the elements heated by induction which remain in the joint}
- 65/3676 . . . . . {being metallic}
- 65/368 . . . . . {with a polymer coating}
- 65/3684 . . . . . {being non-metallic}
- 65/3696 . . . . . {with a coating}
- 65/38 . . . . . Impulse heating

**NOTE**

When classifying in this group, heated tools are additionally classified in the relevant groups, e.g. [B29C 65/22](#)

- 65/40 . . . . . Applying molten plastics, e.g. hot melt (using welding bar {combined with hot gases} [B29C 65/12](#); by moulding [B29C 65/70](#))
- 65/405 . . . . . {characterised by the composition of the applied molten plastics ([B29C 65/425](#) takes precedence)}
- 65/42 . . . . . between pre-assembled parts {([B29C 65/605](#) takes precedence)}
- 65/425 . . . . . {characterised by the composition of the molten plastics applied between pre-assembled parts}
- 65/44 . . . . . Joining a heated non plastics element to a plastics element

**NOTE**

When classifying in this group, compositions of the non-plastics element are additionally classified in the relevant groups, i.e. in [B29C 66/74](#) and subgroups

- 65/46 . . . . . heated by induction

**NOTE**

When classifying in this group, compositions of the non-plastics element are additionally classified in the relevant groups, i.e. in [B29C 66/74](#) and subgroups

- 65/48 . . . . . using adhesives {, i.e. using supplementary joining material} (heat-activated {to be additionally classified in} [B29C 65/02](#) {and subgroups}; {applying molten plastics, e.g.} hot melts {to be additionally classified in} [B29C 65/40](#); non-mechanical parts of adhesive processes, in general [C09J 5/00](#)); {solvent bonding}

**NOTE**

When classifying in this group, heat-activated adhesives are further classified in group [B29C 65/02](#). When classifying in this group,

applying molten plastics is further classified in group [B29C 65/40](#).

- 65/4805 . . . . . {characterised by the type of adhesives}
- 65/481 . . . . . {Non-reactive adhesives, e.g. physically hardening adhesives}
- 65/4815 . . . . . {Hot melt adhesives, e.g. thermoplastic adhesives}
- 65/482 . . . . . {Drying adhesives, e.g. solvent based adhesives}
- 65/4825 . . . . . {Pressure sensitive adhesives}
- 65/483 . . . . . {Reactive adhesives, e.g. chemically curing adhesives}
- 65/4835 . . . . . {Heat curing adhesives}
- 65/484 . . . . . {Moisture curing adhesives}
- 65/4845 . . . . . {Radiation curing adhesives, e.g. UV light curing adhesives}
- 65/485 . . . . . {Multi-component adhesives, i.e. chemically curing as a result of the mixing of said multi-components}
- 65/4855 . . . . . {characterised by their physical properties, e.g. being electrically-conductive}
- 65/486 . . . . . {characterised by their physical form being non-liquid, e.g. in the form of granules or powders ([B29C 65/50](#) takes precedence)}
- 65/4865 . . . . . {containing additives ([C09J 11/00](#) and subgroups take precedence)}
- 65/487 . . . . . {characterised by their shape, e.g. being fibres or being spherical}
- 65/4875 . . . . . {being spherical, e.g. particles or powders}
- 65/488 . . . . . {being longitudinal, e.g. fibres}
- 65/4885 . . . . . {characterised by their composition being non-plastics}
- 65/489 . . . . . {being metals}
- 65/4895 . . . . . {Solvent bonding, i.e. the surfaces of the parts to be joined being treated with solvents, swelling or softening agents, without adhesives}
- 65/50 . . . . . using adhesive tape {, e.g. thermoplastic tape; using threads or the like ([B29C 65/3444](#) takes precedence)}
- 65/5007 . . . . . {characterised by the structure of said adhesive tape, threads or the like}
- 65/5014 . . . . . {being fibre-reinforced ([B29C 65/5028](#) takes precedence)}
- 65/5021 . . . . . {being multi-layered}
- 65/5028 . . . . . {being textile in woven or non-woven form}
- 65/5035 . . . . . {being in thread form, i.e. in the form of a single filament, e.g. in the form of a single coated filament}
- 65/5042 . . . . . {covering both elements to be joined}
- 65/505 . . . . . {and placed in a recess formed in the parts to be joined, e.g. in order to obtain a continuous surface}
- 65/5057 . . . . . {positioned between the surfaces to be joined ([B29C 65/5035](#) takes precedence)}
- 65/5064 . . . . . {of particular form, e.g. being C-shaped, T-shaped}
- 65/5071 . . . . . {and being composed by one single element}
- 65/5078 . . . . . {and being composed by several elements}
- 65/5085 . . . . . {and comprising grooves, e.g. being E-shaped, H-shaped}
- 65/5092 . . . . . {characterised by the tape handling mechanisms, e.g. using vacuum}



- 65/52 . . {characterised by the way of} applying the adhesive {[\(B29C 65/50 takes precedence; apparatus for applying liquids in general B05C; processes for applying liquids in general B05D\)](#)}
- 65/521 . . . {by spin coating}
- 65/522 . . . {by spraying, e.g. by flame spraying}
- 65/523 . . . {by dipping}
- 65/524 . . . {by applying the adhesive from an outlet device in contact with, or almost in contact with, the surface of the part to be joined}
- 65/525 . . . . {by extrusion coating}
- 65/526 . . . {by printing or by transfer from the surfaces of elements carrying the adhesive, e.g. using brushes, pads, rollers, stencils or silk screens}
- 65/527 . . . {by gravity only, e.g. by pouring}
- 65/528 . . . {by CVD or by PVD, i.e. by chemical vapour deposition or by physical vapour deposition}
- 65/54 . . . between pre-assembled parts
- 65/542 . . . . {by injection}
- 65/544 . . . . {by suction}
- 65/546 . . . . {by gravity, e.g. by pouring}
- 65/548 . . . . {by capillarity}
- 65/56 . . using mechanical means {or mechanical connections, e.g. form-fits}
- 65/561 . . {using screw-threads being integral at least to one of the parts to be joined}
- 65/562 . . {using extra joining elements, i.e. which are not integral with the parts to be joined [\(using plastic snap elements B29C 65/58; using plastic rivets B29C 65/601\)](#)}
- 65/564 . . . {hidden in the joint, e.g. dowels or Z-pins [\(B29C 65/603 takes precedence\)](#)}
- 65/565 . . {involving interference fits, e.g. force-fits or press-fits [\(B29C 65/66 takes precedence\)](#)}
- 65/567 . . {using a tamping or a swaging operation, i.e. at least partially deforming the edge or the rim of a first part to be joined to clamp a second part to be joined}
- 65/568 . . . {using a swaging operation, i.e. totally deforming the edge or the rim of a first part to be joined to clamp a second part to be joined}
- 65/58 . . Snap connection
- 65/60 . . Riveting {or staking}
- 65/601 . . . {using extra riveting elements, i.e. the rivets being non-integral with the parts to be joined}
- 65/602 . . . . {using hollow rivets [\(B29C 65/607 takes precedence\)](#)}
- 65/603 . . . . {the rivets being pushed in blind holes}
- 65/604 . . . . . {in both parts}
- 65/605 . . . . {the rivets being molded in place, e.g. by injection}
- 65/606 . . . {the rivets being integral with one of the parts to be joined, i.e. staking}
- 65/607 . . . . {the integral rivets being hollow}
- 65/608 . . . . {the integral rivets being pushed in blind holes}
- 65/609 . . . . {the integral rivets being plunge-formed}
- 65/62 . . Stitching
- 65/64 . . Joining a non-plastics element to a plastics element, e.g. by force [\(B29C 65/44 takes precedence\)](#)  
**NOTE**  
When classifying in this group, compositions of the non-plastics element are additionally classified in the relevant groups, i.e. in [B29C 66/74](#) and subgroups
- 65/645 . . . {using friction or ultrasonic vibrations}  
**NOTE**  
When classifying in this group, compositions of the non-plastics element are additionally classified in the relevant groups, i.e. in [B29C 66/74](#) and subgroups
- 65/66 . . by liberation of internal stresses, e.g. shrinking of one of the parts to be joined
- 65/665 . . {using shrinking during cooling}
- 65/68 . . using auxiliary shrinkable elements
- 65/70 . . by moulding [\(using a particular moulding technique, see the relevant technique {, e.g. by injection B29C 45/14467}\)](#)  
**NOTE**  
This group covers only techniques involving the use of a mould
- 65/72 . . by combined operations {or combined techniques}, e.g. welding and stitching
- 65/74 . . by welding and severing {, or by joining and severing, the severing being performed in the area to be joined, next to the area to be joined, in the joint area or next to the joint area}  
**NOTE**  
When classifying in this group, joining techniques are additionally classified in the relevant groups, e.g. in [B29C 65/02](#) and subgroups
- 65/741 . . {characterised by the relationships between the joining step and the severing step [\(cutting as mechanical pre-treatment B29C 66/02241; cutting as thermal pre-treatment B29C 66/0246; cutting as mechanical after-treatment B29C 66/0326; cutting as thermal after-treatment B29C 66/0346\)](#)}
- 65/7411 . . . {characterised by the temperature relationship between the joining step and the severing step}
- 65/7412 . . . . {the joining step and the severing step being performed at different temperatures}
- 65/7415 . . . {characterised by the pressure relationship between the joining step and the severing step}
- 65/7416 . . . . {the joining step and the severing step being performed at different pressures}
- 65/7419 . . . {characterised by the time relationship between the joining step and the severing step, said joining step and said severing step being performed by the same tool but at different times}
- 65/743 . . {using the same tool for both joining and severing, said tool being monobloc or formed by several parts mounted together and forming a monobloc [\(B29C 65/2046 takes precedence\)](#)}

- 65/7433 . . . {the tool being a wire}
  - 65/7435 . . . {the tool being a roller}
  - 65/7437 . . . {the tool being a perforating tool ([perforating as mechanical pre-treatment B29C 66/02242](#))}
  - 65/7439 . . . {for continuously and longitudinally welding and severing webs ([B29C 65/7435 takes precedence](#))}
  - 65/7441 . . . {for making welds and cuts of other than simple rectilinear form}
  - 65/7443 . . . {by means of ultrasonic vibrations}
  - 65/745 . . {using a single unit having both a severing tool and a welding tool}
  - 65/7451 . . . {the severing tool and the welding tool being movable with respect to one-another}
  - 65/7453 . . . {the severing tool being a wire}
  - 65/7455 . . . {the unit being a roller}
  - 65/7457 . . . {comprising a perforating tool}
  - 65/7459 . . . {for continuously and longitudinally welding and severing webs ([B29C 65/7455 takes precedence](#))}
  - 65/7461 . . . {for making welds and cuts of other than simple rectilinear form}
  - 65/747 . . {using other than mechanical means}
  - 65/7471 . . . {using a fluid, e.g. hot gases}
  - 65/7473 . . . {using radiation, e.g. laser, for simultaneously welding and severing}
  - 65/749 . . {Removing scrap ([deburring welded articles B29C 37/04](#))}
  - 65/76 . Making non-permanent or releasable joints
  - 65/78 . Means for handling the parts to be joined, e.g. for making containers or hollow articles {, e.g. means for handling sheets, plates, web-like materials, tubular articles, hollow articles or elements to be joined therewith; Means for discharging the joined articles from the joining apparatus}
- WARNING**
- Subgroups of [B29C 65/78](#) are not complete, pending a reorganisation; see also this group and its subgroups and [B29C 65/20](#) and its subgroups
- 65/7802 . . {Positioning the parts to be joined, e.g. aligning, indexing or centring}
  - 65/7805 . . . {the parts to be joined comprising positioning features}
  - 65/7808 . . . . {in the form of holes or slots ([B29C 65/7814 takes precedence](#); holding or clamping means cooperating with specially formed features of at least one of the parts to be joined [B29C 65/7844](#))}
  - 65/7811 . . . . {for centring purposes}
  - 65/7814 . . . . {in the form of inter-cooperating positioning features (holding or clamping means cooperating with specially formed features of at least one of the parts to be joined [B29C 65/7844](#)), e.g. tenons and mortises (tenon and mortise joints [B29C 66/126](#); tongue and groove joints [B29C 66/124](#))}
  - 65/7817 . . . . {in the form of positioning marks}
  - 65/782 . . . {by setting the gap between the parts to be joined ([controlling or regulating the gap between the joining tools B29C 66/92611](#))}
  - 65/7823 . . . . {by using distance pieces, i.e. by using spacers positioned between the parts to be joined and forming a part of the joint}
  - 65/7826 . . . . . {said distance pieces being non-integral with the parts to be joined, e.g. particles}
  - 65/7829 . . . . . {said distance pieces being integral with at least one of the parts to be joined}
  - 65/7832 . . . {by setting the overlap between the parts to be joined, e.g. the overlap between sheets, plates or web-like materials}
  - 65/7835 . . . {by using stops ([B29C 65/7823](#), [B29C 66/92651 take precedence](#); tongue and groove joints [B29C 66/124](#); tenon and mortise joints [B29C 66/126](#))}
  - 65/7838 . . . {from the inside, e.g. of tubular or hollow articles ([B29C 66/3242 takes precedence](#))}
  - 65/7841 . . {Holding or clamping means for handling purposes (clamping means for the purpose of applying pressure on the parts to be joined, in the area to be joined [B29C 66/81](#); work holders in general [B25B](#); devices for holding or positioning work for welding metal [B23K 37/04](#))}
  - 65/7844 . . . {cooperating with specially formed features of at least one of the parts to be joined, e.g. cooperating with holes or ribs of at least one of the parts to be joined (parts to be joined comprising holes or slots for the purpose of positioning said parts [B29C 65/7808](#); parts to be joined comprising inter-cooperating positioning features [B29C 65/7814](#); welding using friction, the welding tool cooperating with specially formed features of at least one of the parts to be joined, e.g. cooperating with holes or ribs of at least one of the parts to be joined [B29C 65/069](#))}
  - 65/7847 . . . {using vacuum to hold at least one of the parts to be joined (vacuum work holders in general [B25B 11/005](#))}
  - 65/785 . . . {using magnetic forces to hold at least one of the parts to be joined (magnetic work holders in general [B25B 11/002](#))}
  - 65/7852 . . . {using electrostatic forces to hold at least one of the parts to be joined}
  - 65/7855 . . {Provisory fixing}
  - 65/7858 . . {characterised by the feeding movement of the parts to be joined}
  - 65/7861 . . . {In-line machines, i.e. feeding, joining and discharging are in one production line ([B29C 65/7879](#), [B29C 65/7888 take precedence](#))}
  - 65/7864 . . . . {using a feeding table which moves to and fro (oscillating around an axis [B29C 65/7876](#))}
  - 65/7867 . . . . {using carriers, provided with holding means, said carriers moving in a closed path}
  - 65/787 . . . . {using conveyor belts or conveyor chains ([B29C 66/83421](#), [B29C 66/83521](#), [B29C 66/83531 take precedence](#))}
  - 65/7873 . . . . . {using cooperating conveyor belts or cooperating conveyor chains ([B29C 66/83423](#), [B29C 66/83523](#), [B29C 66/83533 take precedence](#))}
  - 65/7876 . . . {oscillating around an axis ([B29C 65/7888 takes precedence](#))}
  - 65/7879 . . . {said parts to be joined moving in a closed path, e.g. a rectangular path ([B29C 65/7888 takes precedence](#))}

- 65/7882 . . . . {said parts to be joined moving in a circular path}
- 65/7885 . . . . {Rotary turret joining machines, i.e. having several joining tools moving around an axis}

**WARNING**[B29C 65/0672](#)

- 65/7888 . . . {Means for handling of moving sheets or webs}
- 65/7891 . . . . {of discontinuously moving sheets or webs}
- 65/7894 . . . . {of continuously moving sheets or webs}
- 65/7897 . . {Means for discharging the joined articles from the joining apparatus ([B29C 66/005 takes precedence](#); discharging moulded articles from moulds [B29C 37/0003](#))}
- 65/80 . . Rotatable transfer means {for loading or unloading purposes, i.e. turret transfer means ([B29C 65/7879 takes precedence](#); in-line machines using carriers, provided with holding means, said carriers moving in a closed path [B29C 65/7867](#); in-line machines using conveyor belts or conveyor chains [B29C 65/787](#))}
- 65/82 . . Testing the joint
- 65/8207 . . {by mechanical methods}
- 65/8215 . . . {Tensile tests}
- 65/8223 . . . {Peel tests}
- 65/823 . . . {Bend tests}
- 65/8238 . . . {Impact tests}
- 65/8246 . . . {Pressure tests, e.g. hydrostatic pressure tests}
- 65/8253 . . {by the use of waves or particle radiation, e.g. visual examination, scanning electron microscopy, or X-rays ([B29C 65/8292 takes precedence](#))}
- 65/8261 . . {by the use of thermal means}
- 65/8269 . . {by the use of electric or magnetic means}
- 65/8276 . . . {by the use of electric means}
- 65/8284 . . . {by the use of magnetic means}
- 65/8292 . . {by the use of ultrasonic, sonic or infrasonic waves}

**66/00** {General aspects of processes or apparatus for joining preformed parts (means for handling the parts to be joined [B29C 65/78](#); testing the joint [B29C 65/82](#))}

- 66/001 . {Joining in special atmospheres}

**WARNING**

Subgroups of [B29C 66/001](#) are not complete, pending a reorganisation; see also this group

- 66/0012 . . {characterised by the type of environment}
- 66/0014 . . . {Gaseous environments}
- 66/00141 . . . . {Protective gases}
- 66/00143 . . . . {Active gases}
- 66/00145 . . . . {Vacuum, e.g. partial vacuum}
- 66/0016 . . . {Liquid environments, i.e. the parts to be joined being submerged in a liquid}
- 66/0018 . . . {being sterile}
- 66/002 . {Removing toxic gases}
- 66/003 . {Protecting areas of the parts to be joined from overheating ([B29C 66/348](#), [B29C 66/8744 take precedence](#))}

- 66/004 . {Preventing sticking together, e.g. of some areas of the parts to be joined}
- 66/0042 . . {of the joining tool and the parts to be joined ([B29C 66/0046 takes precedence](#); joining tool characterized by its composition [B29C 66/8122](#); joining tool characterized by its microstructure [B29C 66/8124](#))}

- 66/0044 . . . {using a separating sheet, e.g. fixed on the joining tool}
- 66/00441 . . . . {movable, e.g. mounted on reels}
- 66/0046 . . {by the use of a lubricant, e.g. fluid, powder}

**WARNING**

Group [B29C 66/0046](#) and subgroups are not complete, pending a reorganisation; see also [B29C 66/004](#) and its subgroups

- 66/00461 . . . {being liquid, e.g. oil based}
- 66/00463 . . . {being solid, e.g. a powder}
- 66/005 . {Detaching the article from the joining tool}
- 66/006 . {Preventing damaging, e.g. of the parts to be joined ([B29C 66/003](#), [B29C 66/004](#), [B29C 66/348 take precedence](#))}

**WARNING**

Group [B29C 66/006](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and subgroups

- 66/0062 . . {of the joining tool, e.g. avoiding wear of the joining tool}
- 66/01 . {General aspects dealing with the joint area or with the area to be joined ([B29C 65/76](#), [B29C 65/82 take precedence](#))}
- 66/02 . . {Preparation of the material, in the area to be joined, prior to joining or welding ([B29C 66/32 takes precedence](#))}
- 66/022 . . . {Mechanical pre-treatments, e.g. reshaping}

**WARNING**

Subgroups of [B29C 66/022](#) are not complete, pending a reorganisation; see also this group

- 66/0222 . . . . {without removal of material, e.g. cleaning by air blowing or using brushes}
- 66/0224 . . . . {with removal of material}
- 66/02241 . . . . . {Cutting, e.g. by using waterjets, or sawing (using heat [B29C 66/0246](#); cutting-off or cutting-out a part of a strip-like or sheet-like material, transferring that part and fixing it to an article [B29C 69/005](#))}
- 66/02242 . . . . . {Perforating or boring}
- 66/02245 . . . . . {Abrading, e.g. grinding, sanding, sandblasting or scraping}
- 66/024 . . . {Thermal pre-treatments}

**WARNING**

Subgroups of [B29C 66/024](#) are not complete, pending a reorganisation; see also this group

- 66/0242 . . . . {Heating, or preheating, e.g. drying ([B29C 66/3464 takes precedence](#))}
- 66/0244 . . . . {Cooling}

- 66/0246 . . . . {Cutting or perforating, e.g. burning away by using a laser or using hot air (simultaneously welding and severing using a fluid [B29C 65/7471](#); simultaneously welding and severing using radiation [B29C 65/7473](#); cutting-off or cutting-out a part of a strip-like or sheet-like material, transferring that part and fixing it to an article [B29C 69/005](#))}
- 66/026 . . . {Chemical pre-treatments ([B29C 66/028](#) takes precedence)}

**WARNING**

Not complete, pending a reorganisation; see also [B29C 66/02](#)

- 66/028 . . . {Non-mechanical surface pre-treatments, i.e. by flame treatment, electric discharge treatment, plasma treatment, wave energy or particle radiation ([B29C 65/14](#) takes precedence; non-mechanical surface treatment of plastics in general [B29C 59/08](#) - [B29C 59/16](#))}

**WARNING**

Not complete, pending a reorganisation; see also [B29C 66/02](#)

- 66/03 . . {After-treatments in the joint area ([B29C 66/3262](#) takes precedence)}
- 66/032 . . . {Mechanical after-treatments (deburring welded articles [B29C 37/04](#))}
- 66/0322 . . . . {Post-pressing without reshaping, i.e. keeping the joint under pressure after joining}
- 66/0324 . . . . {Reforming or reshaping the joint, e.g. folding over (reshaping the burr [B29C 66/326](#))}
- 66/03241 . . . . . {Flattening}
- 66/03242 . . . . . {of sheets being positioned in abutment, e.g. after folding open of an overlap joint}
- 66/0326 . . . . {Cutting, e.g. by using waterjets, or perforating (using heat [B29C 66/0346](#))}

**WARNING**

Not complete, pending a reorganisation; see also [B29C 66/032](#)

- 66/034 . . . {Thermal after-treatments}
- 66/0342 . . . . {Cooling, e.g. transporting through welding and cooling zone}
- 66/0344 . . . . {Annealing}

**WARNING**

Not complete, pending a reorganisation; see also [B29C 66/034](#)

- 66/0346 . . . . {Cutting or perforating, e.g. burning away by using a laser or using hot air (simultaneously joining and severing using a fluid [B29C 65/7471](#); simultaneously welding and severing using radiation [B29C 65/7473](#))}

**WARNING**

Not complete, pending a reorganisation; see also [B29C 66/034](#)

- 66/038 . . . {Covering the joint by a coating material}
- 66/0382 . . . . {the coating material being in liquid or paste form (joining by applying molten plastics [B29C 65/40](#))}
- 66/0384 . . . . {the coating material being in tape, strip or band form (joining using adhesive tapes covering both elements to be joined [B29C 65/5042](#))}
- 66/05 . . {Particular design of joint configurations}

**NOTE**

In this group the possible supplementary joining material, e.g. adhesive or adhesive tape, is not taken into account for the joint configuration. The use of supplementary joining material, e.g. adhesive or adhesive tape, has to be additionally classified as such, e.g. in [B29C 65/48](#) and subgroups or [B29C 65/50](#) and subgroups

**WARNING**

Group [B29C 66/05](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups

- 66/10 . . . {particular design of the joint cross-sections}

**NOTE**

The scope of the subgroups is defined by the drawings in the Definitions

- 66/11 . . . . {Joint cross-sections comprising a single joint-segment, i.e. one of the parts to be joined comprising a single joint-segment in the joint cross-section ([B29C 66/12](#) and subgroups take precedence)}
- 66/112 . . . . . {Single lapped joints}
- 66/1122 . . . . . {Single lap to lap joints, i.e. overlap joints ([B29C 66/45](#), [B29C 66/472](#), [B29C 66/52272](#) take precedence)}
- 66/114 . . . . . {Single butt joints}
- 66/1142 . . . . . {Single butt to butt joints}
- 66/116 . . . . . {Single bevelled joints, i.e. one of the parts to be joined being bevelled in the joint area}
- 66/1162 . . . . . {Single bevel to bevel joints, e.g. mitre joints}
- 66/118 . . . . . {Single monotone curved joints}
- 66/1182 . . . . . {the joint being C-shaped}
- 66/12 . . . . {Joint cross-sections combining only two joint-segments; Tongue and groove joints; Tenon and mortise joints; Stepped joint cross-sections}
- 66/122 . . . . . {Joint cross-sections combining only two joint-segments, i.e. one of the parts to be joined comprising only two joint-segments in the joint cross-section ([B29C 66/124](#) takes precedence)}
- 66/1222 . . . . . {comprising at least a lapped joint-segment}
- 66/12221 . . . . . {the two joint-segments being lapped}
- 66/1224 . . . . . {comprising at least a butt joint-segment}
- 66/12241 . . . . . {the two joint-segments being butt}



66/1226	. . . . .	{comprising at least one bevelled joint-segment}	66/13	. . . . .	{Single flanged joints; Fin-type joints; Single hem joints; Edge joints; Interpenetrating fingered joints; Other specific particular designs of joint cross-sections not provided for in groups <a href="#">B29C 66/11</a> - <a href="#">B29C 66/12</a> }
66/12261	. . . . .	{the two joint-segments being bevelled, e.g. the two joint-segments forming a V}	66/131	. . . . .	{Single flanged joints, i.e. one of the parts to be joined being rigid and flanged in the joint area}
66/1228	. . . . .	{comprising at least one monotone curved joint-segment}	66/1312	. . . . .	{Single flange to flange joints, the parts to be joined being rigid (the parts to be joined being flexible <a href="#">B29C 66/133</a> )}
66/12281	. . . . .	{the two joint-segments being monotone curved}	66/133	. . . . .	{Fin-type joints, the parts to be joined being flexible (the parts to be joined being rigid <a href="#">B29C 66/1312</a> )}
66/124	. . . . .	{Tongue and groove joints}	66/135	. . . . .	{Single hemmed joints, i.e. one of the parts to be joined being hemmed in the joint area}
66/1242	. . . . .	{comprising interlocking undercuts}	66/1352	. . . . .	{Single hem to hem joints}
66/12421	. . . . .	{Teardrop-like, waterdrop-like or mushroom-like interlocking undercuts}	66/137	. . . . .	{Beaded-edge joints or bead seals (for sealing or securing package folds or closures <a href="#">B65B 51/24</a> )}
66/12423	. . . . .	{Dovetailed interlocking undercuts}	66/139	. . . . .	{Interpenetrating fingered joints}
66/12425	. . . . .	{Other specific interlocking undercuts not provided for in <a href="#">B29C 66/12421</a> - <a href="#">B29C 66/12423</a> }	66/14	. . . . .	{the joint having the same thickness as the thickness of the parts to be joined ( <a href="#">B29C 66/1142</a> takes precedence)}
66/1244	. . . . .	{characterised by the male part, i.e. the part comprising the tongue}	66/20	. . . . .	{particular design of the joint lines, e.g. of the weld lines}
66/12441	. . . . .	{being a single wall}	<b>NOTE</b>		
66/12443	. . . . .	{having the tongue substantially in the middle}	The scope of the subgroups is defined by the drawings in the Definitions		
66/12445	. . . . .	{having the tongue on the side}	66/21	. . . . .	{said joint lines being formed by a single dot or dash or by several dots or dashes, i.e. spot joining or spot welding}
66/12449	. . . . .	{being asymmetric ( <a href="#">B29C 66/12445</a> takes precedence)}	66/22	. . . . .	{said joint lines being in the form of recurring patterns ( <a href="#">B29C 66/234</a> takes precedence)}
66/1246	. . . . .	{characterised by the female part, i.e. the part comprising the groove}	66/221	. . . . .	{being in the form of a sinusoidal wave ( <a href="#">B29C 66/2272</a> takes precedence)}
66/12461	. . . . .	{being rounded, i.e. U-shaped or C-shaped}	66/223	. . . . .	{being in the form of a triangle wave or of a sawtooth wave, e.g. zigzagged}
66/12463	. . . . .	{being tapered}	66/225	. . . . .	{being castellated, e.g. in the form of a square wave or of a rectangular wave ( <a href="#">B29C 66/2276</a> takes precedence)}
66/12464	. . . . .	{being V-shaped}	66/227	. . . . .	{being in the form of repetitive interlocking undercuts, e.g. in the form of puzzle cuts (tongue and groove joints or tenon and mortise joints comprising interlocking undercuts <a href="#">B29C 66/1242</a> )}
66/12469	. . . . .	{being asymmetric}	66/2272	. . . . .	{Teardrop-like, waterdrop-like or mushroom-like interlocking undercuts (tongue and groove joints or tenon and mortise joints comprising teardrop-like, waterdrop-like or mushroom-like interlocking undercuts <a href="#">B29C 66/12421</a> )}
66/1248	. . . . .	{Interpenetrating groove joints (interpenetrating fingered joints <a href="#">B29C 66/139</a> )}	66/2274	. . . . .	{Dovetailed interlocking undercuts (tongue and groove joints or tenon and mortise joints comprising dovetailed interlocking undercuts <a href="#">B29C 66/12423</a> )}
66/126	. . . . .	{Tenon and mortise joints (tenons and mortises for positioning purposes <a href="#">B29C 65/7814</a> )}			
66/128	. . . . .	{Stepped joint cross-sections}			
66/1282	. . . . .	{comprising at least one overlap joint-segment}			
66/12821	. . . . .	{comprising at least two overlap joint-segments}			
66/12822	. . . . .	{comprising at least three overlap joint-segments}			
66/1284	. . . . .	{comprising at least one butt joint-segment}			
66/12841	. . . . .	{comprising at least two butt joint-segments}			
66/12842	. . . . .	{comprising at least three butt joint-segments}			
66/1286	. . . . .	{comprising at least one bevelled joint-segment}			
66/12861	. . . . .	{comprising at least two bevelled joint-segments}			
66/12862	. . . . .	{comprising at least three bevelled joint-segments}			
66/1288	. . . . .	{comprising at least one monotone curved joint-segment}			
66/12881	. . . . .	{comprising at least two monotone curved joint-segments}			
66/12882	. . . . .	{comprising at least three monotone curved joint-segments}			

- 66/2276 . . . . . {Other specific local geometries of interlocking undercuts not provided for in [B29C 66/2272](#) - [B29C 66/2274](#) (tongue and groove joints or tenon and mortise joints comprising other specific interlocking undercuts [B29C 66/12425](#))}
  - 66/229 . . . . . {Other specific patterns not provided for in [B29C 66/221](#) - [B29C 66/227](#)}
  - 66/23 . . . . . {said joint lines being multiple and parallel or being in the form of tessellations}
  - 66/232 . . . . . {said joint lines being multiple and parallel, i.e. the joint being formed by several parallel joint lines}
  - 66/234 . . . . . {said joint lines being in the form of tessellations}
  - 66/24 . . . . . {said joint lines being closed or non-straight}
  - 66/242 . . . . . {said joint lines being closed, i.e. forming closed contours}
  - 66/2422 . . . . . {being circular, oval or elliptical}
  - 66/24221 . . . . . {being circular ([B29C 66/51](#) takes precedence)}
  - 66/24223 . . . . . {being oval}
  - 66/24225 . . . . . {being elliptical}
  - 66/2424 . . . . . {being a closed polygonal chain}
  - 66/24241 . . . . . {forming a triangle}
  - 66/24243 . . . . . {forming a quadrilateral}
  - 66/24244 . . . . . {forming a rectangle}
  - 66/24245 . . . . . {forming a square}
  - 66/24249 . . . . . {forming a specific polygon not provided for in [B29C 66/24241](#) - [B29C 66/24243](#)}
  - 66/244 . . . . . {said joint lines being non-straight, e.g. forming non-closed contours}
  - 66/2442 . . . . . {in the form of a single arc of circle}
  - 66/246 . . . . . {said joint lines forming figures, e.g. animals, flowers, hearts}
  - 66/301 . . . . . {Three-dimensional joints, i.e. the joined area being substantially non-flat ([B29C 66/5223](#), [B29C 66/5224](#), [B29C 66/5225](#) take precedence)}
  - 66/302 . . . . . {the area to be joined comprising melt initiators}
  - 66/3022 . . . . . {said melt initiators being integral with at least one of the parts to be joined}
  - 66/30221 . . . . . {said melt initiators being point-like}
  - 66/30223 . . . . . {said melt initiators being rib-like}
  - 66/3024 . . . . . {said melt initiators being non-integral with the parts to be joined}
  - 66/303 . . . . . {the joint involving an anchoring effect ([B29C 66/341](#), [B29C 65/56](#) and subgroups take precedence)}
  - 66/3032 . . . . . {making use of protusions or cavities belonging to at least one of the parts to be joined ([B29C 66/3034](#) takes precedence)}
  - 66/30321 . . . . . {making use of protusions belonging to at least one of the parts to be joined}
  - 66/30322 . . . . . {in the form of rugosity}
  - 66/30325 . . . . . {making use of cavities belonging to at least one of the parts to be joined}
  - 66/30326 . . . . . {in the form of porosity}
  - 66/3034 . . . . . {making use of additional elements, e.g. meshes}
  - 66/30341 . . . . . {non-integral with the parts to be joined, e.g. making use of extra elements ([B29C 65/562](#) takes precedence)}
  - 66/304 . . . . . {Joining through openings in an intermediate part of the article ([B29C 66/3034](#) takes precedence)}
  - 66/305 . . . . . {Decorative or coloured joints (optical properties of the material of the parts to be joined [B29C 66/733](#))}
  - 66/306 . . . . . {Applying a mark during joining}
  - 66/3062 . . . . . {in the form of letters or numbers}
  - 66/30621 . . . . . {in the form of letters}
  - 66/30623 . . . . . {in the form of numbers}
  - 66/32 . . . . . {Measures for keeping the burr form under control; Avoiding burr formation; Shaping the burr ([deburring welded articles B29C 37/04](#))}
  - 66/322 . . . . . {Providing cavities in the joined article to collect the burr}
  - 66/324 . . . . . {Avoiding burr formation}
  - 66/3242 . . . . . {on the inside of a tubular or hollow article}
  - 66/326 . . . . . {Shaping the burr, e.g. by the joining tool}
  - 66/3262 . . . . . {as after-treatment, e.g. by a separate tool}
  - 66/328 . . . . . {Leaving the burrs unchanged for providing particular properties to the joint, e.g. as decorative effect}
  - 66/3282 . . . . . {for reinforcing the joint}
  - 66/3284 . . . . . {for weakening the joint}
  - 66/341 . . . . . {Measures for intermixing the material of the joint interlayer}
  - 66/342 . . . . . {Preventing air-inclusions}
  - 66/343 . . . . . {Making tension-free or wrinkle-free joints}
  - 66/3432 . . . . . {by holding the material loose or tension-free during joining}
  - 66/344 . . . . . {Stretching or tensioning the joint area during joining}
  - 66/345 . . . . . {Progressively making the joint, e.g. starting from the middle ([B29C 66/8341](#), [B29C 65/12](#), [B29C 65/14](#), [B29C 65/16](#) take precedence)}
  - 66/3452 . . . . . {Making complete joints by combining partial joints}
  - 66/346 . . . . . {Making joints having variable thicknesses in the joint area, e.g. by using jaws having an adapted configuration}
  - 66/3462 . . . . . {by differentially heating the zones of different thickness}
  - 66/3464 . . . . . {by preheating}
  - 66/347 . . . . . {using particular temperature distributions or gradients; using particular heat distributions or gradients}
  - 66/3472 . . . . . {in the plane of the joint, e.g. along the joint line in the plane of the joint or perpendicular to the joint line in the plane of the joint}
  - 66/3474 . . . . . {perpendicular to the plane of the joint}
  - 66/348 . . . . . {Avoiding melting or weakening of the zone directly next to the joint area, e.g. by cooling}
  - 66/349 . . . . . {Cooling the welding zone on the welding spot}
- WARNING**
- Subgroups of [B29C 66/349](#) are not complete, pending a reorganisation; see also this group
- 66/3492 . . . . . {by means placed on the side opposed to the welding tool}

- 66/3494 . . . {while keeping the welding zone under pressure}
- 66/40 . {General aspects of joining substantially flat articles, e.g. plates, sheets or web-like materials; Making flat seams in tubular or hollow articles; Joining single elements to substantially flat surfaces}
- WARNING**
- Group [B29C 66/40](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/41 . . {Joining substantially flat articles ([B29C 66/47](#) and subgroups take precedence); Making flat seams in tubular or hollow articles ([B29C 66/51](#) and subgroups take precedence)}
- 66/43 . . . {Joining a relatively small portion of the surface of said articles ([B29C 66/45](#) takes precedence)}
- 66/431 . . . . {Joining the articles to themselves ([B29C 66/4322](#) and [B29C 66/4332](#) take precedence)}
- 66/4312 . . . . . {for making flat seams in tubular or hollow articles, e.g. transversal seams}
- 66/43121 . . . . . {Closing the ends of tubular or hollow single articles, e.g. closing the ends of bags (closing tube ends [B29C 57/10](#))}
- 66/43122 . . . . . {Closing the top of gable top containers (gable top containers [B65D 5/067](#))}
- 66/43123 . . . . . {Closing the ends of squeeze tubes, e.g. for toothpaste or cosmetics (producing flexible squeeze tubes by combined operations [B29D 23/20](#); collapsible tubes [B65D 35/00](#))}
- 66/43129 . . . . . {said flat seams being transversal but non-orthogonal with respect to the tubular or hollow articles, i.e. oblique}
- 66/432 . . . . {for making tubular articles or closed loops, e.g. by joining several sheets ([B29C 66/547](#) takes precedence; bending and joining sheets at right angles to the longitudinal axis of the article being formed and joining the edges [B29C 53/38](#)); for making hollow articles or hollow preforms}
- 66/4322 . . . . . {by joining a single sheet to itself ([B29C 66/4332](#) takes precedence)}
- 66/4324 . . . . . {for making closed loops, e.g. belts}
- 66/4326 . . . . . {for making hollow articles or hollow-preforms, e.g. half-shells}
- 66/4329 . . . . . {the joint lines being transversal but non-orthogonal with respect to the axis of said tubular articles, i.e. being oblique}
- 66/433 . . . . {Casing-in, i.e. enclosing an element between two sheets by an outlined seam (for bookbinding [B42C 11/06](#); for packaging [B65B](#); by laminating [B32B 37/00](#); enclosing tubular articles between substantially flat elements [B29C 66/53261](#))}
- 66/4332 . . . . . {by folding a sheet over}
- 66/434 . . . . {Joining substantially flat articles for forming corner connections, fork connections or cross connections}
- 66/4342 . . . . . {Joining substantially flat articles for forming corner connections, e.g. for making V-shaped pieces}
- 66/43421 . . . . . {with a right angle, e.g. for making L-shaped pieces}
- 66/4344 . . . . . {Joining substantially flat articles for forming fork connections, e.g. for making Y-shaped pieces}
- 66/43441 . . . . . {with two right angles, e.g. for making T-shaped pieces, H-shaped pieces}
- 66/4346 . . . . . {Joining substantially flat articles for forming cross connections, e.g. for making X-shaped pieces}
- 66/43461 . . . . . {with four right angles, e.g. for making +-shaped pieces}
- 66/435 . . . . {Making large sheets by joining smaller ones or strips together}
- 66/436 . . . . {Joining sheets for making articles comprising cushioning or padding materials, the weld being performed through the cushioning material, e.g. car seats (joining through openings [B29C 66/304](#))}
- 66/437 . . . . {Joining plastics plates for making venetian blinds (making venetian blinds in general [E06B 9/266](#))}
- 66/438 . . . . {Joining sheets for making hollow-walled, channelled structures or multi-tubular articles}
- WARNING**
- Not complete, pending a reorganisation; see also [B29C 66/439](#)
- 66/439 . . . . {Joining sheets for making inflated articles without using a mould}
- WARNING**
- Not complete, pending a reorganisation; see also [B29C 66/438](#)
- 66/45 . . . {Joining of substantially the whole surface of the articles (methods or apparatus for laminating [B32B 37/00](#))}
- 66/452 . . . . {the article having a disc form, e.g. making CDs or DVDs}
- 66/47 . . {Joining single elements to sheets, plates or other substantially flat surfaces ([B29C 66/5326](#) takes precedence)}
- 66/472 . . . {said single elements being substantially flat}
- 66/4722 . . . . {Fixing strips to surfaces other than edge faces (fixing strips to edge faces [B29C 63/0026](#))}
- 66/4724 . . . . {said single elements being appliques, e.g. in the form of a text or drawing}
- 66/474 . . . {said single elements being substantially non-flat}
- 66/4742 . . . . {said single elements being spouts}
- 66/47421 . . . . . {said spouts comprising flanges}
- 66/49 . . {Internally supporting the, e.g. tubular, article during joining ([B29C 66/63](#) takes precedence)}
- 66/492 . . . {using a fluid}
- 66/494 . . . {using an inflatable core}
- 66/496 . . . {using a support which remains in the joined object}

- 66/50 . . . {General aspects of joining tubular articles; General aspects of joining long products, i.e. bars or profiled elements; General aspects of joining single elements to tubular articles, hollow articles or bars; General aspects of joining several hollow-preforms to form hollow or tubular articles}
- WARNING**
- Group [B29C 66/50](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/51 . . . {Joining tubular articles, profiled elements or bars; Joining single elements to tubular articles, hollow articles or bars; Joining several hollow-preforms to form hollow or tubular articles}
- 66/52 . . . {Joining tubular articles, bars or profiled elements}
- 66/522 . . . . {Joining tubular articles ([B29C 66/53241](#) takes precedence)}
- 66/5221 . . . . . {for forming coaxial connections, i.e. the tubular articles to be joined forming a zero angle relative to each other}
- 66/52211 . . . . . . {for making endless tubular articles, e.g. endless inner tubes}
- 66/5223 . . . . . {for forming corner connections or elbows, e.g. for making V-shaped pieces}
- 66/52231 . . . . . . {with a right angle, e.g. for making L-shaped pieces}
- 66/5224 . . . . . {for forming fork-shaped connections, e.g. for making Y-shaped pieces}
- 66/52241 . . . . . . {with two right angles, e.g. for making T-shaped pieces}
- 66/5225 . . . . . {for forming cross-shaped connections, e.g. for making X-shaped pieces}
- 66/52251 . . . . . . {with four right angles, e.g. for making +-shaped pieces}
- 66/5227 . . . . . {for forming multi-tubular articles by longitudinally joining elementary tubular articles wall-to-wall (e.g. joining the wall of a first tubular article to the wall of a second tubular article) or for forming multilayer tubular articles}
- 66/52271 . . . . . . {one tubular article being placed inside the other}
- 66/52272 . . . . . . . {concentrically, e.g. for forming multilayer tubular articles}
- 66/5229 . . . . . {involving the use of a socket}
- 66/52291 . . . . . . {said socket comprising a stop}
- 66/52292 . . . . . . . {said stop being internal}
- 66/52293 . . . . . . . {said stop being external}
- 66/52294 . . . . . . . {said stop being heated}
- 66/52295 . . . . . . {said socket comprising reinforcements}
- 66/52296 . . . . . . {said socket comprising sealing elements, e.g. gaskets}
- 66/52297 . . . . . . {said socket comprising slip-off prevention means ([B29C 66/52296](#) takes precedence)}
- 66/52298 . . . . . . {said socket being composed by several elements}
- 66/524 . . . . . {Joining profiled elements}
- 66/5241 . . . . . {for forming coaxial connections, i.e. the profiled elements to be joined forming a zero angle relative to each other}
- 66/5243 . . . . . {for forming corner connections, e.g. for making window frames or V-shaped pieces ([welded corner joints for window frames E06B 3/9604](#))}
- 66/52431 . . . . . . {with a right angle, e.g. for making L-shaped pieces}
- 66/5244 . . . . . {for forming fork-shaped connections, e.g. for making window frames or Y-shaped pieces}
- 66/52441 . . . . . . {with two right angles, e.g. for making T-shaped pieces}
- 66/5245 . . . . . {for forming cross-shaped connections, e.g. for making window frames or X-shaped pieces}
- 66/52451 . . . . . . {with four right angles, e.g. for making +-shaped pieces}
- 66/526 . . . . . {Joining bars}
- 66/5261 . . . . . {for forming coaxial connections, i.e. the bars to be joined forming a zero angle relative to each other}
- 66/5263 . . . . . {for forming corner connections, e.g. for making V-shaped pieces}
- 66/52631 . . . . . . {with a right angle, e.g. for making L-shaped pieces}
- 66/5264 . . . . . {for forming fork-shaped connections, e.g. for making Y-shaped pieces}
- 66/52641 . . . . . . {with two right angles, e.g. for making T-shaped pieces}
- 66/5265 . . . . . {for forming cross-shaped connections, e.g. for making X-shaped pieces}
- 66/52651 . . . . . . {with four right angles, e.g. for making +-shaped pieces}
- 66/5268 . . . . . {characterised by their solid cross sections being non-circular, e.g. being elliptical, square or rectangular}
- 66/53 . . . . {Joining single elements to tubular articles, hollow articles or bars}
- 66/532 . . . . . {Joining single elements to the wall of tubular articles, hollow articles or bars}
- 66/5324 . . . . . {said single elements being substantially annular, i.e. of finite length ([B29C 66/5326](#) takes precedence)}
- 66/53241 . . . . . . {said articles being tubular and said substantially annular single elements being of finite length relative to the infinite length of said tubular articles ([making T-shaped pieces by joining tubular articles B29C 66/52241](#))}
- 66/53242 . . . . . . . {said single elements being spouts, e.g. joining spouts to tubes}
- 66/53243 . . . . . . . {said spouts comprising flanges}
- 66/53245 . . . . . . {said articles being hollow}
- 66/53246 . . . . . . . {said single elements being spouts, e.g. joining spouts to containers}
- 66/53247 . . . . . . . {said spouts comprising flanges}
- 66/5326 . . . . . {said single elements being substantially flat}
- 66/53261 . . . . . . {Enclosing tubular articles between substantially flat elements}
- 66/53262 . . . . . . . {Enclosing spouts between the walls of bags, e.g. of medical bags}



- 66/53263 . . . . . {said spouts comprising wings, e.g. said spouts being of ship-like or canoe-like form to avoid leaks in the corners}
- 66/534 . . . . . {Joining single elements to open ends of tubular or hollow articles or to the ends of bars}
- 66/5342 . . . . . {a substantially flat extra element being placed between and clamped by the joined single elements and the end of said tubular or hollow articles}
- 66/53421 . . . . . {said substantially flat extra element being flexible, e.g. a membrane ([B29C 66/53425 takes precedence](#))}
- 66/53423 . . . . . {said substantially flat extra element being rigid, e.g. a plate ([B29C 66/53425 takes precedence](#))}
- 66/53425 . . . . . {said substantially flat extra element being perforated, e.g. a screen}
- 66/5344 . . . . . {said single elements being substantially annular, i.e. of finite length, e.g. joining flanges to tube ends ([B29C 66/5346 takes precedence](#))}
- 66/5346 . . . . . {said single elements being substantially flat}
- 66/53461 . . . . . {joining substantially flat covers and/or substantially flat bottoms to open ends of container bodies}
- 66/53462 . . . . . {joining substantially flat covers and substantially flat bottoms to open ends of container bodies}
- 66/53465 . . . . . {said single flat elements being provided with holes facing the tube ends, e.g. for making heat-exchangers}
- 66/536 . . . . . {Joining substantially flat single elements to hollow articles to form tubular articles}
- 66/54 . . . . . {Joining several hollow-preforms, e.g. half-shells, to form hollow articles, e.g. for making balls, containers; Joining several hollow-preforms, e.g. half-cylinders, to form tubular articles}
- 66/541 . . . . . {a substantially flat extra element being placed between and clamped by the joined hollow-preforms}
- 66/5412 . . . . . {said substantially flat extra element being flexible, e.g. a membrane ([B29C 66/5416 takes precedence](#))}
- 66/5414 . . . . . {said substantially flat extra element being rigid, e.g. a plate ([B29C 66/5416 takes precedence](#))}
- 66/5416 . . . . . {said substantially flat extra element being perforated, e.g. a screen}
- 66/542 . . . . . {joining hollow covers or hollow bottoms to open ends of container bodies}
- 66/543 . . . . . {joining more than two hollow-preforms to form said hollow articles}
- 66/5432 . . . . . {joining hollow covers and hollow bottoms to open ends of container bodies}
- 66/545 . . . . . {one hollow-preform being placed inside the other}
- 66/5452 . . . . . {joining hollow bottoms to bottom of bottles}
- 66/547 . . . . . {Joining several hollow-preforms, e.g. half-cylinders, to form tubular articles, e.g. endless tubes}
- 66/5472 . . . . . {for making elbows or V-shaped pieces}
- 66/54721 . . . . . {for making L-shaped pieces}
- 66/5474 . . . . . {for making fork-shaped pieces, i.e. with 3 branches, e.g. Y-shaped pieces}
- 66/54741 . . . . . {for making T-shaped pieces}
- 66/5476 . . . . . {for making cross-shaped pieces, e.g. with 4 branches, e.g. X-shaped pieces}
- 66/54761 . . . . . {for making +-shaped pieces}
- 66/549 . . . . . {said hollow-preforms being interconnected during their moulding process, e.g. by a hinge}
- 66/55 . . . . . {sealing elements being incorporated into the joints, e.g. gaskets ([B29C 66/52296 takes precedence](#))}
- 66/61 . . . . . {Joining from or joining on the inside (for making tubes by bending sheets and joining from the inside [B29C 53/387](#))}
- 66/612 . . . . . {Making circumferential joints}
- 66/63 . . . . . {Internally supporting the article during joining ([B29C 66/49 takes precedence](#))}
- 66/632 . . . . . {using a fluid}
- 66/634 . . . . . {using an inflatable core}
- 66/636 . . . . . {using a support which remains in the joined object}
- 66/65 . . . . . {with a relative motion between the article and the welding tool ([B29C 65/10](#), [B29C 65/12 take precedence](#))}
- 66/652 . . . . . {moving the welding tool around the fixed article}
- 66/69 . . . . . {General aspects of joining filaments (bundling articles [B65B 13/00](#); interconnecting successive lengths of material [B65H 69/00](#))}
- 66/70 . . . . . {characterised by the composition, physical properties or the structure of the material of the parts to be joined; Joining with non-plastics material (chemical aspects [C08J 5/12](#), [C09J](#))}
- WARNING**
- Group [B29C 66/70](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/71 . . . . . {characterised by the composition of the plastics material of the parts to be joined (welding bar compositions [B29C 65/125](#))}
- WARNING**
- Group [B29C 66/71](#) and subgroups are not complete, pending a reorganisation
- 66/712 . . . . . {the composition of one of the parts to be joined being different from the composition of the other part}
- 66/72 . . . . . {characterised by the structure of the material of the parts to be joined}
- 66/721 . . . . . {Fibre-reinforced materials ([B29C 66/729 takes precedence](#))}
- WARNING**
- Subgroups of [B29C 66/721](#) are not complete, pending a reorganisation; see also this group

- 66/7212 . . . . {characterised by the composition of the fibres}
- WARNING**
- Not complete, pending a reorganisation
- 66/7214 . . . . {characterised by the length of the fibres}
- 66/72141 . . . . {Fibres of continuous length}
- 66/72143 . . . . {Fibres of discontinuous lengths}
- 66/723 . . . {being multi-layered ([B29C 66/7292](#), [B29C 66/72941](#) take precedence)}
- 66/7232 . . . . {comprising a non-plastics layer}
- 66/72321 . . . . {consisting of metals or their alloys}
- 66/72322 . . . . {consisting of elements other than metals, e.g. boron}
- 66/72323 . . . . {Carbon}
- 66/72324 . . . . {consisting of inorganic materials not provided for in [B29C 66/72321](#) - [B29C 66/72322](#)}
- 66/72325 . . . . {Ceramics}
- 66/72326 . . . . {Glass}
- 66/72327 . . . . {consisting of natural products or their composites, not provided for in [B29C 66/72321](#) - [B29C 66/72324](#)}
- 66/72328 . . . . {Paper}
- 66/72329 . . . . {Wood}
- 66/7234 . . . . {comprising a barrier layer}
- 66/72341 . . . . {for gases}
- 66/72343 . . . . {for liquids}
- 66/725 . . . {being hollow-walled or honeycombs}
- 66/7252 . . . . {hollow-walled}
- 66/72521 . . . . {comprising corrugated cores}
- 66/72523 . . . . {multi-channelled or multi-tubular ([B29C 66/438](#), [B29C 66/5227](#) take precedence)}
- 66/72525 . . . . {comprising honeycomb cores}
- 66/7254 . . . . {honeycomb structures}
- 66/727 . . . {being porous, e.g. foam}
- 66/729 . . . {Textile or other fibrous material made from plastics}
- 66/7292 . . . . {coated ([B29C 66/72941](#) takes precedence)}
- 66/7294 . . . . {Non woven mats, e.g. felt}
- 66/72941 . . . . {coated}
- 66/73 . . . {characterised by the intensive physical properties of the material of the parts to be joined, by the optical properties of the material of the parts to be joined, by the extensive physical properties of the parts to be joined, by the state of the material of the parts to be joined or by the material of the parts to be joined being a thermoplastic or a thermoset}
- 66/731 . . . {characterised by the intensive physical properties of the material of the parts to be joined}
- 66/7311 . . . . {Thermal properties}
- 66/73111 . . . . {Thermal expansion coefficient}
- 66/73112 . . . . {of different thermal expansion coefficient, i.e. the thermal expansion coefficient of one of the parts to be joined being different from the thermal expansion coefficient of the other part}
- 66/73113 . . . . {Thermal conductivity}
- 66/73114 . . . . . {of different thermal conductivity, i.e. the thermal conductivity of one of the parts to be joined being different from the thermal conductivity of the other part}
- 66/73115 . . . . . {Melting point}
- 66/73116 . . . . . {of different melting point, i.e. the melting point of one of the parts to be joined being different from the melting point of the other part}
- 66/73117 . . . . . {Tg, i.e. glass transition temperature}
- 66/73118 . . . . . {of different glass transition temperature, i.e. the glass transition temperature of one of the parts to be joined being different from the glass transition temperature of the other part}
- 66/7312 . . . . {Rheological properties}
- 66/73121 . . . . {Viscosity}
- 66/73122 . . . . . {of different viscosity, i.e. the viscosity of one of the parts to be joined being different from the viscosity of the other part}
- 66/7313 . . . . {Density}
- 66/73132 . . . . . {of different density, i.e. the density of one of the parts to be joined being different from the density of the other part}
- 66/7314 . . . . {Electrical and dielectric properties}
- 66/73141 . . . . {Electrical conductivity}
- 66/73143 . . . . {Dielectric properties}
- 66/7315 . . . . {Mechanical properties}
- 66/73151 . . . . {Hardness}
- 66/73152 . . . . . {of different hardness, i.e. the hardness of one of the parts to be joined being different from the hardness of the other part}
- 66/7316 . . . . {Surface properties}
- 66/73161 . . . . {Roughness or rugosity}
- 66/73162 . . . . . {of different roughness or rugosity, i.e. the roughness or rugosity of the surface of one of the parts to be joined being different from the roughness or rugosity of the surface of the other part}
- 66/7317 . . . . {Hydrophilicity or hydrophobicity}
- 66/73171 . . . . {Hydrophilicity}
- 66/73172 . . . . . {of different hydrophilicity, i.e. the hydrophilicity of one of the parts to be joined being different from the hydrophilicity of the other part}
- 66/73175 . . . . {Hydrophobicity}
- 66/73176 . . . . . {of different hydrophobicity, i.e. the hydrophobicity of one of the parts to be joined being different from the hydrophobicity of the other part}
- 66/7318 . . . . {Permeability to gases or liquids}
- 66/73181 . . . . {permeable}
- 66/73182 . . . . {to gases}
- 66/73183 . . . . {to liquids}
- 66/73185 . . . . {non-permeable}
- 66/73186 . . . . {to gases}
- 66/73187 . . . . {to liquids}
- 66/733 . . . {characterised by the optical properties of the material of the parts to be joined, e.g. fluorescence, phosphorescence}

- 66/7332 . . . . {at least one of the parts to be joined being coloured}
- 66/73321 . . . . {both parts to be joined being coloured}
- 66/73322 . . . . {both parts to be joined having a different colour}
- 66/7334 . . . . {at least one of the parts to be joined being glossy or matt, reflective or refractive}
- 66/73341 . . . . {at least one of the parts to be joined being glossy or reflective}
- 66/73343 . . . . {at least one of the parts to be joined being matt or refractive}
- 66/7336 . . . . {at least one of the parts to be joined being opaque, transparent or translucent to visible light}
- 66/73361 . . . . {at least one of the parts to be joined being opaque to visible light}
- 66/73362 . . . . {both parts to be joined being opaque to visible light}
- 66/73365 . . . . {at least one of the parts to be joined being transparent or translucent to visible light}
- 66/73366 . . . . {both parts to be joined being transparent or translucent to visible light}
- 66/7338 . . . . {at least one of the parts to be joined being polarising}
- 66/735 . . . {characterised by the extensive physical properties of the parts to be joined}
- 66/7352 . . . . {Thickness, e.g. very thin}
- 66/73521 . . . . {of different thickness, i.e. the thickness of one of the parts to be joined being different from the thickness of the other part}
- 66/737 . . . {characterised by the state of the material of the parts to be joined}
- 66/7371 . . . . {oriented or heat-shrinkable}
- 66/73711 . . . . {oriented}
- 66/73712 . . . . {mono-axially}
- 66/73713 . . . . {bi-axially or multi-axially}
- 66/73715 . . . . {heat-shrinkable}
- 66/7373 . . . . {Joining soiled or oxidised materials}
- 66/7375 . . . . {uncured, partially cured or fully cured}
- 66/73751 . . . . {the to-be-joined area of at least one of the parts to be joined being uncured, i.e. non cross-linked, non vulcanized}
- 66/73752 . . . . {the to-be-joined areas of both parts to be joined being uncured}
- 66/73753 . . . . {the to-be-joined area of at least one of the parts to be joined being partially cured, i.e. partially cross-linked, partially vulcanized}
- 66/73754 . . . . {the to-be-joined areas of both parts to be joined being partially cured}
- 66/73755 . . . . {the to-be-joined area of at least one of the parts to be joined being fully cured, i.e. fully cross-linked, fully vulcanized}
- 66/73756 . . . . {the to-be-joined areas of both parts to be joined being fully cured}
- 66/7377 . . . . {amorphous, semi-crystalline or crystalline}
- 66/73771 . . . . {the to-be-joined area of at least one of the parts to be joined being amorphous}
- 66/73772 . . . . {the to-be-joined areas of both parts to be joined being amorphous}
- 66/73773 . . . . {the to-be-joined area of at least one of the parts to be joined being semi-crystalline}
- 66/73774 . . . . {the to-be-joined areas of both parts to be joined being semi-crystalline}
- 66/73775 . . . . {the to-be-joined area of at least one of the parts to be joined being crystalline}
- 66/73776 . . . . {the to-be-joined areas of both parts to be joined being crystalline}
- 66/7379 . . . . {degradable}
- 66/73791 . . . . {biodegradable}
- 66/73793 . . . . {soluble, e.g. water-soluble}
- 66/739 . . . {characterised by the material of the parts to be joined being a thermoplastic or a thermoset}
- 66/7392 . . . . {characterised by the material of at least one of the parts being a thermoplastic}
- 66/73921 . . . . {characterised by the materials of both parts being thermoplastics}
- 66/7394 . . . . {characterised by the material of at least one of the parts being a thermoset}
- 66/73941 . . . . {characterised by the materials of both parts being thermosets}
- 66/74 . . {Joining plastics material to non-plastics material}
- NOTE**
- When classifying in this group, joining techniques are additionally classified in the relevant groups, i.e. in [B29C 65/44](#) and subgroups or in [B29C 65/64](#) and subgroups
- WARNING**
- Group [B29C 66/74](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/742 . . . {to metals or their alloys}
- 66/7422 . . . . {Aluminium or alloys of aluminium}
- 66/7424 . . . . {Lead or alloys of lead}
- 66/7426 . . . . {Tin or alloys of tin}
- 66/7428 . . . . {Transition metals or their alloys}
- 66/74281 . . . . {Copper or alloys of copper}
- 66/74283 . . . . {Iron or alloys of iron, e.g. steel}
- 66/74285 . . . . {Noble metals, e.g. silver, gold, platinum or their alloys}
- 66/744 . . . {to elements other than metals}
- 66/7442 . . . . {Boron}
- 66/7444 . . . . {Carbon}
- 66/746 . . . {to inorganic materials not provided for in groups [B29C 66/742](#) - [B29C 66/744](#)}
- 66/7461 . . . . {Ceramics}
- 66/74611 . . . . {Carbides; Nitrides}
- 66/7463 . . . . {Concrete}
- 66/7465 . . . . {Glass}
- 66/7467 . . . . {Mica}
- 66/7469 . . . . {Asbestos}
- 66/748 . . . {to natural products or their composites, not provided for in groups [B29C 66/742](#) - [B29C 66/746](#)}
- 66/7481 . . . . {Cork}
- 66/7482 . . . . {Linoleum}
- 66/7483 . . . . {Bone, horn, ivory}
- 66/7484 . . . . {Leather}
- 66/7485 . . . . {Natural fibres, e.g. wool, cotton}
- 66/7486 . . . . {Paper, e.g. cardboard}
- 66/7487 . . . . {Wood}

- 66/80 . . . {General aspects of machine operations or constructions and parts thereof}
- WARNING**
- Group [B29C 66/80](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/81 . . . {General aspects of the pressing elements, i.e. the elements applying pressure on the parts to be joined in the area to be joined, e.g. the welding jaws or clamps ([holding or clamping means for handling purposes B29C 65/7841](#))}
- WARNING**
- Group [B29C 66/81](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/812 . . . {characterised by the composition, by the structure, by the intensive physical properties or by the optical properties of the material constituting the pressing elements, e.g. constituting the welding jaws or clamps}
- 66/8122 . . . {characterised by the composition of the material constituting the pressing elements, e.g. constituting the welding jaws or clamps}
- WARNING**
- Not complete, pending a reorganisation; see also [B29K 2801/00](#) - [B29K 2911/14](#)
- 66/8124 . . . {characterised by the structure of the material constituting the pressing elements, e.g. constituting the welding jaws or clamps}
- 66/81241 . . . {being porous or sintered}
- 66/8126 . . . {characterised by the intensive physical properties or by the optical properties of the material constituting the pressing elements, e.g. constituting the welding jaws or clamps}
- 66/81261 . . . {Thermal properties, e.g. thermal conductivity, thermal expansion coefficient}
- 66/81262 . . . {Electrical and dielectric properties, e.g. electrical conductivity}
- 66/81263 . . . {Dielectric properties}
- 66/81264 . . . {Mechanical properties, e.g. hardness}
- 66/81265 . . . {Surface properties, e.g. surface roughness or rugosity}
- 66/81266 . . . {Optical properties, e.g. transparency, reflectivity}
- 66/81267 . . . {Transparent to electromagnetic radiation, e.g. to visible light}
- 66/81268 . . . {Reflective to electromagnetic radiation, e.g. to visible light}
- 66/814 . . . {characterised by the design of the pressing elements, e.g. of the welding jaws or clamps}
- 66/8141 . . . {characterised by the surface geometry of the part of the pressing elements, e.g. welding jaws or clamps, coming into contact with the parts to be joined}
- 66/81411 . . . {characterised by its cross-section, e.g. transversal or longitudinal, being non-flat}
- 66/81413 . . . {being non-symmetrical ([B29C 66/81415 takes precedence](#))}
- 66/81415 . . . {being bevelled}
- 66/81417 . . . {being V-shaped}
- 66/81419 . . . {and flat}
- 66/81421 . . . {being convex or concave}
- 66/81422 . . . {being convex}
- 66/81423 . . . {being concave}
- 66/81425 . . . {being stepped, e.g. comprising a shoulder}
- 66/81427 . . . {comprising a single ridge, e.g. for making a weakening line; comprising a single tooth}
- 66/81429 . . . {comprising a single tooth}
- 66/81431 . . . {comprising a single cavity, e.g. a groove}
- 66/81433 . . . {being toothed, i.e. comprising several teeth or pins ([comprising a single tooth B29C 66/81429](#)), or being patterned}
- 66/81435 . . . {comprising several parallel ridges, e.g. for crimping ([comprising a single ridge B29C 66/81427](#))}
- 66/8145 . . . {characterised by the constructional aspects of the pressing elements, e.g. of the welding jaws or clamps ([B29C 66/816](#) and [B29C 66/818 take precedence](#); adaptable for making articles or joints of different dimensions [B29C 66/841](#))}
- 66/81451 . . . {being adaptable to the surface of the joint ([B29C 66/81453](#), [B29C 66/81455](#), [B29C 66/81457](#), [B29C 66/81459](#), [B29C 66/81461 take precedence](#))}
- 66/81453 . . . {being made of flexible slats, flexible fins, flexible bristles or springs, e.g. coiled springs}
- 66/81455 . . . {being a fluid inflatable bag or bladder, a diaphragm or a vacuum bag for applying isostatic pressure ([inflatable element positioned between the joining tool and a backing-up part B29C 66/82421](#))}
- 66/81457 . . . {comprising a block or layer of deformable material, e.g. sponge, foam, rubber ([pressing elements supported or backed-up by resilient material B29C 66/8161](#))}
- 66/81459 . . . {being a filled deformable bladder, e.g. bladder filled with oil, with granules or with a meltable solid material ([B29C 66/81455 takes precedence](#))}
- 66/81461 . . . {being multi-lamellar or segmented, i.e. comprising a plurality of strips, plates or stacked elements}
- 66/81463 . . . {comprising a plurality of single pressing elements, e.g. a plurality of sonotrodes, or comprising a plurality of single counter-pressing elements, e.g. a plurality of anvils, said plurality of said single elements being suitable for making a single joint}
- 66/81465 . . . {one placed behind the other in a single row in the feed direction}
- 66/81467 . . . {arranged in an offset pattern}
- 66/81469 . . . {one placed next to the other in a single line transverse to the feed direction, e.g. shoulder to shoulder sonotrodes}
- 66/81471 . . . {being a wrap-around tape or band}
- 66/816 . . . {characterised by the mounting of the pressing elements, e.g. of the welding jaws or clamps}



- 66/8161 . . . . {said pressing elements being supported or backed-up by springs or by resilient material}
- 66/81611 . . . . {by resilient material}
- 66/8163 . . . . {Self-aligning to the joining plane, e.g. mounted on a ball and socket}
- 66/8165 . . . . {Carrier plates for mounting joining tool parts, e.g. for re-arranging the tool parts to make other forms}
- 66/8167 . . . . {Quick change joining tools or surfaces}
- 66/8169 . . . . {the mounting of said pressing elements being laterally movable, e.g. adjustable ([B29C 66/836](#), [B29C 66/841](#), [B29C 66/863](#) take precedence)}
- 66/818 . . . {characterised by the cooling constructional aspects, or by the thermal or electrical insulating or conducting constructional aspects of the welding jaws or of the clamps (characterised by the heating means [B29C 65/24](#)); comprising means for compensating for the thermal expansion of the welding jaws or of the clamps}
- 66/8181 . . . . {characterised by the cooling constructional aspects}
- 66/81811 . . . . {of the welding jaws}
- 66/81812 . . . . {the welding jaws being cooled from the outside, e.g. by blowing a gas or spraying a liquid}
- 66/81815 . . . . {of the clamps}
- 66/8182 . . . . {characterised by the thermal insulating constructional aspects}
- 66/81821 . . . . {of the welding jaws}
- 66/81825 . . . . {of the clamps}
- 66/8183 . . . . {characterised by the thermal conducting constructional aspects}
- 66/81831 . . . . {of the welding jaws}
- 66/81835 . . . . {of the clamps}
- 66/8185 . . . . {comprising means for compensating for the thermal expansion of the welding jaws or of the clamps (means for tensioning resistive elements [B29C 65/229](#))}
- 66/8187 . . . . {characterised by the electrical insulating constructional aspects}
- 66/81871 . . . . {of the welding jaws}
- 66/81875 . . . . {of the clamps}
- 66/8188 . . . . {characterised by the electrical conducting constructional aspects}
- 66/81881 . . . . {of the welding jaws}
- 66/81885 . . . . {of the clamps}
- 66/82 . . {Pressure application arrangements, e.g. transmission or actuating mechanisms for joining tools or clamps}
- WARNING**  
Group [B29C 66/82](#) and subgroups are not complete, pending a reorganisation; see also [B29C 65/00](#) and its subgroups
- 66/822 . . . {Transmission mechanisms}
- 66/8221 . . . . {Scissor or lever mechanisms, i.e. involving a pivot point}
- 66/8222 . . . . {Pinion or rack mechanisms}
- 66/8223 . . . . {Worm or spindle mechanisms}
- 66/8224 . . . . {Chain or sprocket drives}
- 66/8225 . . . . {Crank mechanisms}
- 66/8226 . . . . {Cam mechanisms; Wedges; Eccentric mechanisms}
- 66/82261 . . . . {Wedges}
- 66/82263 . . . . {Follower pin or roller cooperating with a groove}
- 66/82265 . . . . {Eccentric mechanisms}
- 66/8227 . . . . {using springs}
- 66/824 . . . {Actuating mechanisms}
- 66/8242 . . . . {Pneumatic or hydraulic drives (using fluid pressure directly acting on the parts to be joined [B29C 66/8266](#))}
- 66/82421 . . . . {using an inflatable element positioned between the joining tool and a backing-up part}
- 66/82423 . . . . {using vacuum (using vacuum directly acting on the parts to be joined [B29C 66/82661](#))}
- 66/8244 . . . . {magnetically driven}
- 66/8246 . . . . {Servomechanisms, e.g. servomotors}
- 66/8248 . . . . {Pressure application by weights (by the own weight of the joining tool [B29C 66/8282](#))}
- 66/826 . . . {without using a separate pressure application tool, e.g. the own weight of the parts to be joined ([B29C 65/66](#) takes precedence)}
- 66/8262 . . . . {using "pressure means" which are associated with at least one of the parts to be joined and remain in or on it}
- 66/8264 . . . . {using the thermal expansion of the parts to be joined}
- 66/8266 . . . . {using fluid pressure directly acting on the parts to be joined}
- 66/82661 . . . . {by means of vacuum}
- 66/828 . . . {Other pressure application arrangements}
- 66/8282 . . . . {using the own weight of the joining tool}
- 66/8284 . . . . {using the thermal expansion of the joining tool}
- 66/8286 . . . . {Hand placed clamps (wrap-around tapes or bands [B29C 66/81471](#))}
- 66/83 . . {characterised by the movement of the joining or pressing tools}
- WARNING**  
Group [B29C 66/83](#) and subgroups are not complete, pending a reorganisation; see also this group and its subgroups and [B29C 65/00](#) and its subgroups
- 66/832 . . . {Reciprocating joining or pressing tools ([B29C 66/834](#) takes precedence)}
- 66/8322 . . . . {Joining or pressing tools reciprocating along one axis}
- 66/83221 . . . . {cooperating reciprocating tools, each tool reciprocating along one axis}
- 66/8324 . . . . {Joining or pressing tools pivoting around one axis (scissor or lever transmission mechanisms [B29C 66/8221](#); tools self-aligning to the joining plane [B29C 66/8163](#))}
- 66/83241 . . . . {cooperating pivoting tools}
- 66/834 . . . {moving with the parts to be joined}
- 66/8341 . . . . {Roller, cylinder or drum types; Band or belt types; Ball types ([B29C 66/8351](#) takes precedence)}

- 66/83411 . . . . . {Roller, cylinder or drum types  
([B29C 66/83431](#) takes precedence; rollers, cylinders or drums moving relative to and tangentially to the parts to be joined  
[B29C 66/8362](#))}
  - 66/83413 . . . . . {cooperating rollers, cylinders or drums}
  - 66/83415 . . . . . {the contact angle between said rollers, cylinders or drums and said parts to be joined being a non-zero angle  
([B29C 66/83433](#) takes precedence)}
  - 66/83417 . . . . . {said rollers, cylinders or drums being hollow}
  - 66/83421 . . . . . {band or belt types ([B29C 66/83431](#) takes precedence)}
  - 66/83423 . . . . . {cooperating bands or belts}
  - 66/83431 . . . . . {rollers, cylinders or drums cooperating with bands or belts}
  - 66/83433 . . . . . {the contact angle between said rollers, cylinders or drums and said bands or belts being a non-zero angle}
  - 66/83435 . . . . . {said rollers, cylinders or drums being hollow}
  - 66/83441 . . . . . {Ball types}
  - 66/8351 . . . . . {Jaws mounted on rollers, cylinders, drums, bands, belts or chains; Flying jaws}
  - 66/83511 . . . . . {jaws mounted on rollers, cylinders or drums}
  - 66/83513 . . . . . {cooperating jaws mounted on rollers, cylinders or drums and moving in a closed path}
  - 66/83517 . . . . . {said rollers, cylinders or drums being hollow}
  - 66/83521 . . . . . {jaws mounted on bands or belts}
  - 66/83523 . . . . . {Cooperating jaws mounted on cooperating bands or belts and moving in a closed path}
  - 66/83531 . . . . . {jaws mounted on chains}
  - 66/83533 . . . . . {Cooperating jaws mounted on cooperating chains and moving in a closed path}
  - 66/83541 . . . . . {flying jaws, e.g. jaws mounted on crank mechanisms or following a hand over hand movement}
  - 66/83543 . . . . . {cooperating flying jaws}
  - 66/836 . . . . . {Moving relative to and tangentially to the parts to be joined, e.g. transversely to the displacement of the parts to be joined, e.g. using a X-Y table ([B29C 66/65](#) takes precedence)}
  - 66/8362 . . . . . {Rollers, cylinders or drums moving relative to and tangentially to the parts to be joined}
  - 66/84 . . . . . {Specific machine types or machines suitable for specific applications}
  - 66/841 . . . . . {Machines or tools adaptable for making articles of different dimensions or shapes or for making joints of different dimensions}
  - 66/8412 . . . . . {of different length, width or height}
  - 66/84121 . . . . . {of different width}
  - 66/84123 . . . . . {of different height}
  - 66/8414 . . . . . {of different diameter}
  - 66/8416 . . . . . {of different thickness}
  - 66/843 . . . . . {Machines for making separate joints at the same time in different planes; Machines for making separate joints at the same time mounted in parallel or in series}
  - 66/8432 . . . . . {Machines for making separate joints at the same time mounted in parallel or in series}
  - 66/845 . . . . . {C-clamp type or sewing machine type}
  - 66/847 . . . . . {Drilling standard machine type}
  - 66/849 . . . . . {Packaging machines}
  - 66/8491 . . . . . {welding through a filled container, e.g. tube or bag}
  - 66/851 . . . . . {Bag or container making machines}
  - 66/8511 . . . . . {Bag making machines}
  - 66/853 . . . . . {Machines for changing web rolls or filaments, e.g. for joining a replacement web to an expiring web}
  - 66/855 . . . . . {Belt splicing machines}
  - 66/857 . . . . . {Medical tube welding machines}
  - 66/861 . . . . . {Hand-held tools}
  - 66/8612 . . . . . {Ironing tool type}
  - 66/8614 . . . . . {Tongs, pincers or scissors}
  - 66/8616 . . . . . {Pen or pencil like}
  - 66/8618 . . . . . {being battery operated}
  - 66/863 . . . . . {Robotised, e.g. mounted on a robot arm}
  - 66/865 . . . . . {Independently movable welding apparatus, e.g. on wheels}
  - 66/8652 . . . . . {being pushed by hand or being self-propelling}
  - 66/86521 . . . . . {being self-propelling}
  - 66/86523 . . . . . {the traction being made on the seam}
  - 66/86531 . . . . . {being guided}
  - 66/86533 . . . . . {by rails}
  - 66/86535 . . . . . {by the edge of one of the parts to be joined or by a groove between the parts to be joined, e.g. using a roller}
  - 66/87 . . . . . {Auxiliary operations or devices}
  - 66/872 . . . . . {Starting or stopping procedures}
  - 66/874 . . . . . {Safety measures or devices}
  - 66/8742 . . . . . {for operators ([B29C 66/002](#) takes precedence)}
  - 66/8744 . . . . . {Preventing overheating of the parts to be joined, e.g. if the machine stops or slows down}
  - 66/87441 . . . . . {by lowering or shutting down the power supply}
  - 66/87443 . . . . . {by withdrawing the heating tools}
  - 66/87445 . . . . . {by introducing protection shields}
  - 66/8746 . . . . . {Detecting the absence of the articles to be joined}
  - 66/8748 . . . . . {involving the use of warnings}
  - 66/876 . . . . . {Maintenance or cleaning}
  - 66/8762 . . . . . {Cleaning of the joining tools}
  - 66/90 . . . . . {Measuring or controlling the joining process}
- WARNING**
- Group [B29C 66/90](#) and subgroups are not complete, pending a reorganisation; see also this group and its subgroups
- 66/91 . . . . . {by measuring or controlling the temperature, the heat or the thermal flux}
  - 66/912 . . . . . {by measuring the temperature, the heat or the thermal flux}
  - 66/9121 . . . . . {by measuring the temperature}

- 66/91211 . . . . . {with special temperature measurement means or methods}
- 66/91212 . . . . . {involving measurement means being part of the welding jaws, e.g. integrated in the welding jaws}
- 66/91213 . . . . . {and measuring the electrical resistance of a resistive element belonging to said welding jaws, said element being, e.g. a thermistor}
- 66/91214 . . . . . {by measuring the electrical resistance of a resistive element belonging to one of the parts to be welded, said element acting, e.g. as a thermistor}
- 66/91216 . . . . . {enabling contactless temperature measurements, e.g. using a pyrometer}
- 66/91218 . . . . . {using colour change, e.g. using separate colour indicators}
- 66/91221 . . . . . {of the parts to be joined}
- 66/91231 . . . . . {of the joining tool}
- 66/9131 . . . . . {by measuring the heat or the thermal flux, i.e. the heat flux}
- 66/91311 . . . . . {by measuring the heat generated by Joule heating or induction heating}
- 66/91313 . . . . . {by measuring the voltage, i.e. the electric potential difference or electric tension}
- 66/91315 . . . . . {by measuring the current intensity}
- 66/91317 . . . . . {by measuring the electrical resistance}
- 66/914 . . . . . {by controlling or regulating the temperature, the heat or the thermal flux}
- 66/9141 . . . . . {by controlling or regulating the temperature}
- 66/91411 . . . . . {of the parts to be joined, e.g. the joining process taking the temperature of the parts to be joined into account}
- 66/91413 . . . . . {the parts to be joined having different temperatures}
- 66/91421 . . . . . {of the joining tools}
- 66/91423 . . . . . {using joining tools having different temperature zones or using several joining tools with different temperatures}
- 66/91431 . . . . . {the temperature being kept constant over time}
- 66/91441 . . . . . {the temperature being non-constant over time}
- 66/91443 . . . . . {following a temperature-time profile (B29C 65/38 takes precedence)}
- 66/91445 . . . . . {by steps}
- 66/9161 . . . . . {by controlling or regulating the heat or the thermal flux, i.e. the heat flux}
- 66/91631 . . . . . {the heat or the thermal flux being kept constant over time}
- 66/91641 . . . . . {the heat or the thermal flux being non-constant over time}
- 66/91643 . . . . . {following a heat-time profile (B29C 65/38 takes precedence)}
- 66/91645 . . . . . {by steps}
- 66/91651 . . . . . {by controlling or regulating the heat generated by Joule heating or induction heating}
- 66/91653 . . . . . {by controlling or regulating the voltage, i.e. the electric potential difference or electric tension}
- 66/91655 . . . . . {by controlling or regulating the current intensity}
- 66/919 . . . . . {characterised by specific temperature, heat or thermal flux values or ranges (specific electrical resistance values B29C 66/81262)}
- 66/9192 . . . . . {in explicit relation to another variable, e.g. temperature diagrams}
- 66/91921 . . . . . {in explicit relation to another temperature, e.g. to the softening temperature or softening point, to the thermal degradation temperature or to the ambient temperature}
- 66/91931 . . . . . {in explicit relation to the fusion temperature or melting point of the material of one of the parts to be joined}
- 66/91933 . . . . . {higher than said fusion temperature}
- 66/91935 . . . . . {lower than said fusion temperature}
- 66/91941 . . . . . {in explicit relation to T<sub>g</sub>, i.e. the glass transition temperature, of the material of one of the parts to be joined}
- 66/91943 . . . . . {higher than said glass transition temperature}
- 66/91945 . . . . . {lower than said glass transition temperature}
- 66/91951 . . . . . {in explicit relation to time, e.g. temperature-time diagrams}
- 66/92 . . . . . {by measuring or controlling the pressure, the force, the mechanical power or the displacement of the joining tools}
- 66/922 . . . . . {by measuring the pressure, the force, the mechanical power or the displacement of the joining tools}
- 66/9221 . . . . . {by measuring the pressure, the force or the mechanical power}
- 66/92211 . . . . . {with special measurement means or methods}
- 66/9231 . . . . . {by measuring the displacement of the joining tools}
- 66/92311 . . . . . {with special measurement means or methods}
- 66/924 . . . . . {by controlling or regulating the pressure, the force, the mechanical power or the displacement of the joining tools}
- 66/9241 . . . . . {by controlling or regulating the pressure, the force or the mechanical power}
- 66/92431 . . . . . {the pressure, the force or the mechanical power being kept constant over time (B29C 66/92613 takes precedence)}
- 66/92441 . . . . . {the pressure, the force or the mechanical power being non-constant over time}
- 66/92443 . . . . . {following a pressure-time profile}
- 66/92445 . . . . . {by steps}
- 66/92451 . . . . . {using joining tools having different pressure zones or using several joining tools with different pressures}
- 66/9261 . . . . . {by controlling or regulating the displacement of the joining tools}
- 66/92611 . . . . . {by controlling or regulating the gap between the joining tools}
- 66/92613 . . . . . {the gap being kept constant over time}
- 66/92615 . . . . . {the gap being non-constant over time}
- 66/92651 . . . . . {by using stops}
- 66/92653 . . . . . {said stops being adjustable}
- 66/92655 . . . . . {by using several stops}

- 66/929 . . . {characterized by specific pressure, force, mechanical power or displacement values or ranges}
- 66/9292 . . . . {in explicit relation to another variable, e.g. pressure diagrams}
- 66/92921 . . . . . {in specific relation to time, e.g. pressure-time diagrams}
- 66/93 . . {by measuring or controlling the speed}
- 66/932 . . . {by measuring the speed}
- 66/9321 . . . . {with special speed measurement means or methods}
- 66/934 . . . {by controlling or regulating the speed}
- 66/93411 . . . . {the parts to be joined having different speeds}
- 66/93431 . . . . {the speed being kept constant over time}
- 66/93441 . . . . {the speed being non-constant over time}
- 66/93451 . . . . {by controlling or regulating the rotational speed, i.e. the speed of revolution}
- 66/939 . . . {characterised by specific speed values or ranges}
- 66/9392 . . . . {in explicit relation to another variable, e.g. speed diagrams}
- 66/94 . . {by measuring or controlling the time}
- 66/942 . . . {by measuring the time}
- 66/9421 . . . . {with special time measurement means or methods}
- 66/944 . . . {by controlling or regulating the time}
- 66/9441 . . . . {the time being controlled or regulated as a function of another parameter}
- 66/949 . . . {characterised by specific time values or ranges}
- 66/9492 . . . . {in explicit relation to another variable}
- 66/95 . . {by measuring or controlling specific variables not covered by groups [B29C 66/91](#) - [B29C 66/94](#)}
- 66/951 . . . {by measuring or controlling the vibration frequency and/or the vibration amplitude of vibrating joining tools, e.g. of ultrasonic welding tools}
- 66/9511 . . . . {by measuring their vibration frequency}
- 66/9512 . . . . {by controlling their vibration frequency}
- 66/9513 . . . . {characterised by specific vibration frequency values or ranges}
- 66/9515 . . . . {by measuring their vibration amplitude}
- 66/9516 . . . . {by controlling their vibration amplitude}
- 66/9517 . . . . {characterised by specific vibration amplitude values or ranges}
- 66/952 . . . {by measuring or controlling the wavelength}
- 66/953 . . . {by measuring or controlling the humidity}
- 66/9532 . . . . {of the parts to be joined, i.e. taking the humidity of the parts to be joined into account}
- 66/9534 . . . . {of the atmosphere, i.e. taking the ambient humidity into account}
- 66/954 . . . {by measuring or controlling the thickness of the parts to be joined}
- 66/959 . . . {characterised by specific values or ranges of said specific variables}
- 66/9592 . . . . {in explicit relation to another variable, e.g. X-Y diagrams}
- 66/96 . . {characterised by the method for implementing the controlling of the joining process}
- 66/961 . . . {involving a feedback loop mechanism, e.g. comparison with a desired value}
- 66/962 . . . {using proportional controllers, e.g. PID controllers [proportional–integral–derivative controllers]}
- 66/963 . . . {using stored or historical data sets, e.g. using expert systems}
- 66/964 . . . {involving trial and error}
- 66/965 . . . {using artificial neural networks}
- 66/966 . . . {using fuzzy logic}
- 66/967 . . . {involving special data inputs or special data outputs, e.g. for monitoring purposes}
- 66/9672 . . . . {involving special data inputs, e.g. involving barcodes, RFID tags}
- 66/9674 . . . . {involving special data outputs, e.g. special data display means ([B29C 66/8748](#) takes precedence)}
- 66/97 . . {Checking completion of joining or correct joining by using indications on at least one of the joined parts}
- 66/972 . . . {by extrusion of molten material}
- 66/974 . . . {by checking the bead or burr form}
- 66/976 . . . {by the use of an indicator pin, e.g. being integral with one of the parts to be joined}
- 66/98 . . {Determining the joining area by using markings on at least one of the parts to be joined}
- 67/00 Shaping techniques not covered by groups [B29C 39/00](#) - [B29C 65/00](#), [B29C 70/00](#) or [B29C 73/00](#)**
- 67/0003 . {Moulding articles between moving mould surfaces, e.g. turning surfaces}
- 67/0007 . {Manufacturing coloured articles not otherwise provided for, e.g. by colour change}
- 67/0011 . {for shaping plates or sheets}
- 67/0014 . {for shaping tubes or blown tubular films}
- 67/0018 . . {Turning tubes inside out ([for lining internal surfaces B29C 63/36](#))}
- 67/0022 . . {using an internal mandrel}
- 67/0025 . . . {and pressure difference}
- 67/0029 . {Cold deforming of thermoplastics material ([B29C 43/16](#), [B29C 59/00](#) take precedence)}
- 67/0033 . {by shock-waves}
- 67/0037 . {Forming articles from a moulding composition enclosed in a deformable bag ([making moulds composed of particles enclosed in a bag B29C 33/3821](#); [from expandable material in flexible bags B29C 44/182](#); [with reinforcements placed in a covering element B29C 70/542](#))}
- 67/004 . {Closing perforations or small holes, e.g. using additional moulding material}
- 67/0044 . {for shaping edges or extremities ([B29C 57/00](#) takes precedence)}
- 67/0048 . {Local deformation of formed objects}
- 67/02 . Moulding by agglomerating ([B29C 67/20](#) takes precedence)}
- 67/04 . . Sintering ([combined with compression B29C 43/00](#))
- 67/06 . . Coagulating
- 67/08 . Screen moulding, e.g. forcing the moulding material through a perforated screen on to a moulding surface
- 67/20 . for porous or cellular articles, e.g. of foam plastics, coarse-pored ([chemical aspects of working up macro-molecular substances to porous or cellular articles C08J 9/00](#))}



- 67/202 . . {comprising elimination of a solid or a liquid ingredient}
- 67/205 . . {comprising surface fusion, and bonding of particles to form voids, e.g. sintering}
- 67/207 . . {comprising impregnating expanded particles or fragments with a binder}
- 67/24 . characterised by the choice of material
- 67/241 . . {Moulding wax}
- 67/242 . . {Moulding mineral aggregates bonded with resin, e.g. resin concrete (shaping ceramic compositions without binder or water-setting cementitious material [B28B](#); compositions per se [C04B](#))}
- 67/243 . . . {for making articles of definite length}
- 67/244 . . . {by vibrating the composition before or during moulding}
- 67/245 . . . {for making articles of indefinite length}
- 67/246 . . {Moulding high reactive monomers or prepolymers, e.g. by reaction injection moulding [RIM], liquid injection moulding [LIM] (casting monomers [B29C 39/006](#), mixing construction [B29B 7/74](#))}
- 67/247 . . {Moulding polymers or prepolymers containing ingredients in a frangible packaging, e.g. microcapsules (expandable components kept in frangible containers within a flexible bag [B29C 44/183](#))}
- 67/248 . . {Moulding mineral fibres or particles bonded with resin, e.g. for insulating or roofing board (articles from wood or lignocellulosic material with binding agents [B27N](#); mineral aggregates bonded with resin [B29C 67/242](#); thermal insulation in general [F16L 59/00](#))}
- 67/249 . . . {for making articles of indefinite length}
- 69/00 Combinations of shaping techniques not provided for in a single one of main groups [B29C 39/00](#) - [B29C 67/00](#), e.g. associations of moulding and joining techniques; Apparatus therefore {([B29C 47/0038](#) takes precedence)}**
- 69/001 . {a shaping technique combined with cutting, e.g. in parts or slices combined with rearranging and joining the cut parts (for reinforced material [B29C 70/545](#); [B29C 49/4278](#), [B29C 51/268](#) take precedence)}
- 69/002 . . {Winding (cutting of individual length [B26D](#))}
- 69/003 . . . {and cutting longitudinally, e.g. for making O-rings; chain links, insulation tubes}
- 69/004 . {making articles by joining parts moulded in separate cavities, said parts being in said separate cavities during said joining ([B29C 45/006](#), [B29C 51/267](#) take precedence)}
- 69/005 . {cutting-off or cutting-out a part of a strip-like or sheet-like material, transferring that part and fixing it to an article (if labeling see [B65C](#), in combination with box-making [B31B 50/81](#); labelling in general [B65C](#))}
- 69/006 . . {rotating transfer means}
- 69/007 . {Lining or sheathing in combination with forming the article to be lined}
- 69/008 . . {of tubular articles}
- 69/02 . of moulding techniques only
- 69/025 . . {Deforming articles in a simpler intermediate shape without internal stresses for packaging transporting or storage and reshaping and fixing the original configuration on the place of use (shaping by liberation of internal stresses [B29C 61/00](#))}
- 70/00 Shaping composites, i.e. plastics material comprising reinforcements, fillers or preformed parts, e.g. inserts (chemical aspects [C08](#), e.g. [C08J 5/00](#))**
- NOTE**
- In this group, the following terms or expressions are used with the meanings indicated:
- "reinforcement" means a structure in the form of fibres, wires, rods, bars, sections, plates or blocks, which improves the strength of an article;
  - "filler" means a relatively inert substance in the form of particles, powder, beads, flakes or spheres, which improves the physical properties or increases the bulk or weight of an article;
  - "preformed part" means a part made of any material, being completely shaped to have a determined form and which is not used as a reinforcement, e.g. wires or nets forced only into the surface of an article;
  - "insert" means a preformed part incorporated in an article during moulding.
- 70/02 . comprising combinations of reinforcements, {e.g. non-specified reinforcements, fibrous reinforcing inserts} and fillers, {e.g. particulate fillers}, incorporated in matrix material, forming one or more layers and with or without non-reinforced or non-filled layers {(combinations of fibrous reinforcement only [B29C 70/04](#); combinations of fillers only [B29C 70/58](#); combinations with non reinforcing inserts, e.g. foam blocks, [B29C 70/68](#))}
- 70/021 . . {Combinations of fibrous reinforcement and non-fibrous material}
- 70/023 . . . {with reinforcing inserts}
- 70/025 . . . {with particular filler}
- 70/026 . . {and with one or more layers of pure plastics material, e.g. foam layers (applying a non-preformed coating, e.g. a gel-coat [B29C 37/0025](#); with foam blocks [B29C 70/86](#))}
- 70/028 . . {and with one or more layers of non-plastics material or non-specified material, e.g. supports}
- 70/04 . comprising reinforcements only, e.g. self-reinforcing plastics
- 70/06 . . Fibrous reinforcements only
- 70/08 . . . comprising combinations of different forms of fibrous reinforcements incorporated in matrix material, forming one or more layers, and with or without non-reinforced layers
- 70/081 . . . . {Combinations of fibres of continuous or substantial length and short fibres}
- 70/083 . . . . {Combinations of continuous fibres or fibrous profiled structures oriented in one direction and reinforcements forming a two dimensional structure, e.g. mats ([B29D 24/00](#), [B29D 99/001](#) take precedence)}

- 70/085 . . . . . {the structure being deformed in a three dimensional configuration ([B29C 53/805 takes precedence](#))}
- 70/086 . . . . . {and with one or more layers of pure plastics material, e.g. foam layers ([applying a non-preformed coating, e.g. a gel-coat, B29C 37/0025; with foam blocks B29C 70/86](#))}
- 70/088 . . . . . {and with one or more layers of non-plastics material or non-specified material, e.g. supports}
- 70/10 . . . characterised by the structure of fibrous reinforcements {, e.g. hollow fibres}
- 70/12 . . . . . using fibres of short length, e.g. in the form of a mat {([non-woven fabrics per se D04H 1/00](#))}
- 70/14 . . . . . oriented ([oriented filler material B29C 70/62](#))
- 70/16 . . . . . using fibres of substantial or continuous length {([non-woven fabrics per se D04H 3/00](#))}
- 70/18 . . . . . in the form of a mat, e.g. sheet moulding compound [SMC]
- 70/20 . . . . . oriented in a single direction, e.g. roofing or other parallel fibres {([B29C 70/083, B29C 70/226 take precedence](#))}
- 70/202 . . . . . {arranged in parallel planes or structures of fibres crossing at substantial angles, e.g. cross-moulding compound [XMC] ([B29C 70/207 takes precedence](#))}
- 70/205 . . . . . {the structure being shaped to form a three-dimensional configuration}
- 70/207 . . . . . {arranged in parallel planes of fibres crossing at substantial angles}
- 70/22 . . . . . oriented in at least two directions forming a two dimensional structure {([woven fabrics per se D03D; knitted fabrics per se D04D; braid per se D04C](#))}
- 70/222 . . . . . {the structure being shaped to form a three dimensional configuration}
- 70/224 . . . . . {the structure being a net ([B29C 70/688 takes precedence](#))}
- 70/226 . . . . . {the structure comprising mainly parallel filaments interconnected by a small number of cross threads}
- 70/228 . . . . . {the structure being stacked in parallel layers with fibres of adjacent layers crossing at substantial angles}
- 70/24 . . . . . oriented in at least three directions forming a three dimensional structure
- 70/26 . . Non-fibrous reinforcements only {([B29C 35/0272, B29C 61/0625, B29C 70/887 take precedence; combined with fibres B29C 70/023](#))}
- 70/28 . . Shaping operations therefor
- NOTES**
1. This group covers:
- the shaping of a coherent fibrous reinforcements which are pre-impregnated or without binder; or of non-coherent reinforcements of fibres in a mould or on a support;
  - the impregnation or introduction of a plastics matrix in reinforcements during shaping;
2. This group does not cover:
- the moulding by a single technique of plastics matrix material mixed with and containing reinforcing fibres of short length, which is covered by the appropriate place for that technique;
  - the pretreatment, e.g. impregnation, of reinforcements *per se*, i.e. independently of their shaping, which is covered by group [B29B 15/08](#)
- 70/30 . . . Shaping by lay-up, i.e. applying fibres, tape or broadsheet on a mould, former or core; Shaping by spray-up, i.e. spraying of fibres on a mould, former or core {([by winding and joining, e.g. filament winding B29C 53/56; for building tyres B29D 30/08](#))}
- 70/305 . . . . . {Spray-up of reinforcing fibres with or without matrix to form a non-coherent mat in or on a mould ([B29C 41/365, B29C 70/32, B29C 70/34, B29C 70/502, B29C 70/508 take precedence; coating a former by spraying plastics B29C 41/08](#))}
- 70/32 . . . . . on a rotating mould, former or core
- 70/323 . . . . . {on the inner surface of a rotating mould}
- 70/326 . . . . . {by rotating the mould around its axis of symmetry}
- 70/34 . . . . . and shaping or impregnating by compression {, i.e. combined with compressing after the lay-up operation}
- 70/342 . . . . . {using isostatic pressure}
- 70/345 . . . . . {using matched moulds}
- 70/347 . . . . . {combined with compressing after the winding of lay-ups having a non-circular cross-section, e.g. flat spiral windings}
- 70/36 . . . . . and impregnating by casting, e.g. vacuum casting
- 70/38 . . . . . Automated lay-up, e.g. using robots, laying filaments according to predetermined patterns {([application heads for tyres B29D 30/28](#))}
- 70/382 . . . . . {Automated fiber placement [AFP]}
- 70/384 . . . . . {Fiber placement heads, e.g. component parts, details or accessories}
- 70/386 . . . . . {Automated tape laying [ATL]}
- 70/388 . . . . . {Tape placement heads, e.g. component parts, details or accessories}
- 70/40 . . . Shaping or impregnating by compression ([B29C 70/34 takes precedence](#)) {not applied}
- 70/42 . . . . . for producing articles of definite length, i.e. discrete articles
- 70/44 . . . . . using isostatic pressure, e.g. pressure difference-, vacuum bag-, autoclave- or expanding rubber-moulding
- 70/443 . . . . . {and impregnating by vacuum or injection}
- 70/446 . . . . . {Moulding structures having an axis of symmetry or at least one channel, e.g. tubular structures, frames}
- 70/46 . . . . . using matched moulds, e.g. for deforming sheet moulding compound [SMC], prepreps

- 70/462 . . . . . {Moulding structures having an axis of symmetry or at least one channel, e.g. tubular structures, frames}
- 70/465 . . . . . {and impregnating by melting a solid material, e.g. sheets, powders of fibres}
- 70/467 . . . . . {and impregnating the reinforcements during mould closing ([B29C 70/465](#) takes precedence)}
- 70/48 . . . . . and impregnating the reinforcements in the closed mould, e.g. resin transfer moulding [RTM], {e.g. by vacuum}
- 70/50 . . . . . for producing articles of indefinite length, e.g. prepregs, sheet moulding compounds [SMC], cross moulding compounds [XMC]
- 70/502 . . . . . {by first forming a mat composed of short fibres}
- 70/504 . . . . . {using rollers or pressure bands (for corrugating [B29C 53/22](#))}
- 70/506 . . . . . {and impregnating by melting a solid material, e.g. sheet, powder, fibres ([B29C 70/508](#) takes precedence)}
- 70/508 . . . . . {and first forming a mat composed of short fibres}
- 70/52 . . . . . Pultrusion, i.e. forming and compressing by continuously pulling through a die
- 70/521 . . . . . {and impregnating the reinforcement before the die}
- 70/522 . . . . . {the transport direction being vertical}
- 70/523 . . . . . {and impregnating the reinforcement in the die}
- 70/524 . . . . . {the transport direction being vertical}
- 70/525 . . . . . {Component parts, details or accessories; Auxiliary operations}
- 70/526 . . . . . {Pultrusion dies, e.g. dies with moving or rotating parts ([B29C 70/523](#) takes precedence)}
- 70/527 . . . . . {Pulling means}
- 70/528 . . . . . {Heating or cooling}
- 70/54 . . . . . Component parts, details or accessories; Auxiliary operations {, e.g. feeding or storage of prepregs or SMC after impregnation or during ageing (pretreatment, e.g. impregnation, of reinforcements [B29B 15/08](#))}
- 70/541 . . . . . {Positioning reinforcements in a mould, e.g. using clamping means for the reinforcement (positioning inserts in moulds [B29C 33/12](#); lay-up on a mould [B29C 70/30](#))}
- 70/542 . . . . . {Placing or positioning the reinforcement in a covering or packaging element before or during moulding, e.g. drawing in a sleeve}
- 70/543 . . . . . {Fixing the position or configuration of fibrous reinforcements before or during moulding (for non-woven fabrics [D04H 3/08](#))}
- 70/545 . . . . . {Perforating, cutting or machining during or after moulding}
- 70/546 . . . . . {Measures for feeding or distributing the matrix material in the reinforcing structure}
- 70/547 . . . . . {using channels or porous distribution layers incorporated in or associated with the product}
- 70/548 . . . . . {using distribution constructions, e.g. channels incorporated in or associated with the mould}
- 70/56 . . . . . Tensioning reinforcements before or during shaping
- 70/58 . . . . . comprising fillers only {, e.g. particles, powder, beads, flakes, spheres ([B29C 70/025](#) takes precedence, agglomerating hollow spheres to produce synthetic foam [B29C 70/66](#); compounding ingredients *per se* [C08K](#))}
- NOTE**
- Moulding of plastics matrix material mixed with fillers by a single technique is classified in the appropriate place for that technique.
- 70/585 . . . . . {incorporation of light reflecting filler, e.g. lamellae to obtain pearlescent effect (partially embedding reflective elements into the surface of or support [B29D 11/00615](#))}
- 70/60 . . . . . comprising a combination of distinct filler types incorporated in matrix material, forming one or more layers, and with or without non-filled layers
- 70/603 . . . . . {and with one or more layers of pure plastics material, e.g. foam layers (applying a non-preformed coating, e.g. a gel-coat [B29C 37/0025](#); with foam blocks [B29C 70/86](#))}
- 70/606 . . . . . {and with one or more layers of non-plastics material or non-specified material, e.g. supports}
- 70/62 . . . . . the filler being oriented during moulding (for short fibres [B29C 70/14](#))
- 70/64 . . . . . the filler influencing the surface characteristics of the material, e.g. by concentrating near the surface or by incorporating in the surface by force
- 70/66 . . . . . the filler comprising hollow constituents, e.g. syntactic foam
- 70/68 . . . . . by incorporating or moulding on preformed parts, e.g. inserts, layers {, e.g. foam blocks (mould constructions therefor [B29C 33/12](#); joining preformed parts by moulding [B29C 65/70](#))}
- NOTE**
- This group does not cover:
- incorporating, or moulding on, preformed parts by a single technique, which is covered by the appropriate place for that technique;
  - pretreatment of preformed parts *per se*, i.e. independently of their shaping, which is covered by group [B29B 15/00](#)
- 70/681 . . . . . {Component parts, details or accessories; Auxiliary operations}
- 70/682 . . . . . {Preformed parts characterised by their structure, e.g. form}
- 70/683 . . . . . {Pretreatment of the preformed part, e.g. insert}
- 70/685 . . . . . {by laminating inserts between two plastic films or plates}
- 70/686 . . . . . {the inserts being sheets or documents, e.g. ID cards}
- 70/687 . . . . . {the inserts being oriented, e.g. nets or meshes}
- 70/688 . . . . . {the inserts being meshes or lattices ([B29C 70/82](#), [B29C 70/683](#) take precedence)}

- 70/70 . . Completely encapsulating inserts {[\(B29C 70/86 takes precedence\)](#)}
- 70/72 . . Encapsulating inserts having non-encapsulated projections, e.g. extremities, terminal portions of electrical components {[\(B29C 70/742 takes precedence\)](#)}
- 70/74 . . Moulding material on a relatively small portion of the preformed part, e.g. outsert moulding {[\(B29C 70/845 takes precedence\)](#)}
- 70/742 . . . {Forming a hollow body around the preformed part}
- 70/745 . . . {Filling cavities in the preformed part (for joining [B29C 70/84](#))}
- 70/747 . . . {Applying material, e.g. foam, only in a limited number of places or in a pattern, e.g. to create a decorative effect}
- 70/76 . . . Moulding on edges or extremities of the preformed part
- 70/763 . . . . {the edges being disposed in a substantial flat plane}
- 70/766 . . . . {on the end part of a tubular article}
- 70/78 . . Moulding material on one side only of the preformed part
- 70/80 . . . Moulding sealing material into closure members {[\(placing sealings in closures B21D 51/46\)](#)}
- 70/82 . . Forcing elongated elements, wires, nets or the like partially or completely in the surface of an article, e.g. by cutting and pressing [\(pressing beads or the like in a surface B29C 70/64\)](#)
- 70/84 . . by moulding material on preformed parts to be joined {[\(joining plastic parts by moulding B29C 65/70\)](#)}
- 70/845 . . . {by moulding material on a relative small portion of the preformed parts}
- 70/86 . . Incorporated in coherent impregnated reinforcing layers, {e.g. by winding}
- 70/865 . . . {completely encapsulated}
- 70/88 . characterised primarily by possessing specific properties, e.g. electrically conductive, locally reinforced
- 70/882 . . {partly or totally electrically conductive, e.g. for EMI shielding [\(conductive floors or floor coverings H05F 3/025; EMI shielding in general H05K 9/00\)](#)}
- 70/885 . . . {with incorporated metallic wires, nets, films or plates [\(as lost heating elements B29C 35/0272, B29C 61/0625\)](#)}
- 70/887 . . {locally reinforced, e.g. by fillers (filler concentrated near the surface [B29C 70/64](#))}
- 71/00 After-treatment of articles without altering their shape; Apparatus therefor** [\(B29C 73/00 takes precedence; surface shaping B29C 59/00; {for joined or sealed parts B29C 66/03; after-treatment specially adapted for vulcanising tyres B29D 30/0633} ; chemical aspects C08J 7/00\)](#)
- 71/0009 . {using liquids, e.g. solvents, swelling agents (spectacle cases, e.g. for cleaning contact lenses [A45C 11/04](#); disinfecting or sterilising contact lenses [A61L 12/00](#), using liquid substances [A61L 2/20](#); cleaning involving the use of liquid in general [B08B 3/00](#); for hydrating contact lenses [B29D 11/00067](#))}
- 2071/0018 . . {Absorbing ingredients, e.g. drugs, flavourings, UV screeners, embedded in the articles}
- 2071/0027 . . {Removing undesirable residual components, e.g. solvents, unreacted monomers [\(of material to be shaped B29B 9/16, B29B 13/00\)](#)}
- 2071/0036 . . {Extracting, degassing, removing gases from moulded articles}
- 2071/0045 . . {Washing using non-reactive liquids}
- 2071/0054 . . {Supercritical fluid treatment, i.e. using a liquid in which distinct liquid and gas phases do not exist}
- 71/0063 . {for changing crystallisation}
- 71/0072 . {for changing orientation}
- 71/0081 . {using an electric field, e.g. for electrostatic charging [\(electrostatic pinning of extruded material B29C 47/887; fixing linings by electrostatic charges B29C 63/0043\)](#)}
- 71/009 . {using gases without chemical reaction [\(C08J 7/12 takes precedence; in combination with blow-moulding B29C 49/46; surface treatment using plasma B29C 59/14, ionised gas B29C 59/16\)](#)}
- 71/02 . Thermal after-treatment {[\(B29C 71/0063 and B29C 71/0072 take precedence\)](#)}
- 2071/022 . . {Annealing}
- 2071/025 . . {Quenching, i.e. rapid cooling of an object}
- 2071/027 . . {Tempering, i.e. heating an object to a high temperature and quenching it}
- 71/04 . by wave energy or particle radiation {, e.g. for curing or vulcanising preformed articles [\(during moulding, e.g. in a mould B29C 35/08\)](#)}
- 73/00 Repairing of articles made from plastics or substances in a plastic state, e.g. of articles shaped or produced by using techniques covered by this subclass or subclass B29D** [\(retreading tyres B29D 30/54; {linings for tyres acting locally B60C5/145; } devices for covering leaks in pipes or hoses F16L 55/16\)](#)
- 73/02 . using liquid or paste-like material [\(B29C 73/16 takes precedence\)](#)
- 73/025 . . {fed under pressure}
- 73/04 . using preformed elements
- 73/06 . . using plugs sealing in the hole
- 73/063 . . . {expandable}
- 73/066 . . . . {by mechanical means provided on the plug}
- 73/08 . . . Apparatus therefor, e.g. for inserting
- 73/10 . . using patches sealing on the surface of the article [\(B29C 73/14 takes precedence\)](#)
- 73/105 . . . {provided with a centering element}
- 73/12 . . . Apparatus therefor, e.g. for applying [\(B29C 73/30 takes precedence\)](#)
- 73/14 . . using elements composed of two parts joined together after having been placed one on each side of the article
- 73/16 . Auto-repairing or self-sealing arrangements or agents [\(sealing compositions, see Section C, e.g. C09K 3/10 ; incorporating auto-repairing or self-sealing arrangements or agents on or into tyres B29D 30/0685\)](#)}
- 73/163 . . {Sealing compositions or agents, e.g. combined with propellant agents}
- 73/166 . . {Devices or methods for introducing sealing compositions into articles}
- 73/18 . . the article material itself being self-sealing, e.g. by compression



- 73/20 . . . the article material only consisting in part of a deformable sealing material
- 73/22 . . the article containing elements including a sealing composition, e.g. powder being liberated when the article is damaged
- 73/24 . Apparatus or accessories not otherwise provided for
- 73/245 . . {for removing the element having caused the damage}
- 73/26 . . for mechanical pretreatment
- 2073/262 . . . {for polishing, roughening, buffing or sanding the area to be repaired}
- 2073/264 . . . {for cutting out or grooving the area to be repaired}
- 2073/266 . . . {for cutting out an undercut for anchoring the repairing material}
- 2073/268 . . . {for drilling holes in the area to be repaired}
- 73/28 . . for clamping and stretching flexible material, e.g. inner tubes
- 73/30 . . for local pressing or local heating
- 73/305 . . . {specially adapted for toroidal articles, e.g. tyres (B29C 73/325 takes precedence)}
- 73/32 . . . using an elastic element, e.g. inflatable bag
- 73/325 . . . . {specially adapted for toroidal articles, e.g. tyres}
- 73/34 . . . for local heating

**2791/00 Shaping characteristics in general**

- 2791/001 . Shaping in several steps
- 2791/002 . Making articles of definite length, i.e. discrete articles (B29C 53/40 takes precedence)
- 2791/003 . Making articles of indefinite length (B29C 53/48 takes precedence)
- 2791/004 . Shaping under special conditions
- 2791/005 . . Using a particular environment, e.g. sterile fluids other than air
- 2791/006 . . Using vacuum
- 2791/007 . . Using fluid under pressure
- 2791/008 . . Using vibrations during moulding
- 2791/009 . . Using laser (curing using laser B29C 2035/0838, welding using laser beams B29C 65/16)

**Particular articles****NOTE**

Parts of specified articles are indexed with the same indexing codes as the articles

**2793/00 Shaping techniques involving a cutting or machining operation**

- 2793/0009 . Cutting out
- 2793/0018 . . for making a hole
- 2793/0027 . Cutting off
- 2793/0036 . Slitting
- 2793/0045 . Perforating
- 2793/0054 . partially cutting through the material
- 2793/0063 . Cutting longitudinally
- 2793/0072 . combined with rearranging and joining the cut parts
- 2793/0081 . before shaping
- 2793/009 . after shaping

**2795/00 Printing on articles made from plastics or substances in a plastic state**

- 2795/002 . before shaping

- 2795/005 . during shaping
- 2795/007 . after shaping

**2945/00 Indexing scheme relating to injection moulding, i.e. forcing the required volume of moulding material through a nozzle into a closed mould**

- 2945/76 . Measuring, controlling or regulating
- 2945/76003 . . Measured parameter (not used)
- 2945/76006 . . . Pressure
- 2945/7601 . . . . derivative, change thereof
- 2945/76013 . . . Force
- 2945/76016 . . . . derivative, change thereof
- 2945/7602 . . . Torque
- 2945/76023 . . . . derivative, change thereof
- 2945/76026 . . . Energy, power
- 2945/7603 . . . . Power
- 2945/76033 . . . Electric current or voltage
- 2945/76036 . . . Frequency
- 2945/7604 . . . Temperature
- 2945/76043 . . . . derivative, change thereof
- 2945/76046 . . . . Heat flux, heat transfer
- 2945/7605 . . . Viscosity
- 2945/76053 . . . . derivative, change thereof
- 2945/76056 . . . Flow rate
- 2945/7606 . . . . derivative, change thereof
- 2945/76063 . . . . MFI, MFR
- 2945/76066 . . . Time
- 2945/7607 . . . . start
- 2945/76073 . . . . termination
- 2945/76076 . . . . duration
- 2945/7608 . . . . pause, wilful interruption
- 2945/76083 . . . Position
- 2945/76086 . . . . Start position
- 2945/7609 . . . . End position
- 2945/76093 . . . . Angular position
- 2945/76096 . . . . Distance
- 2945/761 . . . Dimensions, e.g. thickness
- 2945/76103 . . . . shrinkage, dilation, dimensional change, warpage
- 2945/76107 . . . . volume
- 2945/7611 . . . Velocity
- 2945/76113 . . . . linear movement
- 2945/76117 . . . . . derivative, change thereof
- 2945/7612 . . . . . rotational movement
- 2945/76123 . . . . . derivative, change thereof
- 2945/76127 . . . Density
- 2945/7613 . . . Weight
- 2945/76133 . . . Crystallinity
- 2945/76137 . . . Degree of crosslinking, solidification
- 2945/7614 . . . Humidity, moisture
- 2945/76143 . . . Volatiles
- 2945/76147 . . . Contaminants
- 2945/7615 . . . Electrical properties
- 2945/76153 . . . Optical properties
- 2945/76157 . . . Magnetic properties
- 2945/7616 . . . Surface properties
- 2945/76163 . . . Errors, malfunctioning
- 2945/76167 . . . Presence, absence of objects
- 2945/7617 . . . Sequence, e.g. the order in which operations are conducted
- 2945/76173 . . . Others
- 2945/76177 . . . Location of measurement (not used)

2945/7618	. . .	Injection unit	2945/76384	. . .	Holding, dwelling
2945/76183	. . . .	hopper	2945/76387	. . .	Mould closing
2945/76187	. . . .	screw	2945/76391	. . .	Mould clamping, compression of the cavity
2945/7619	. . . .	barrel	2945/76394	. . .	Mould opening
2945/76193	. . . . .	barrel-chamber	2945/76397	. . .	Switch-over
2945/76197	. . . . .	screw ante-chamber	2945/76401	. . . .	metering-injection
2945/762	. . . .	injection piston	2945/76404	. . . .	injection-holding
2945/76204	. . . .	injection piston cylinder	2945/76408	. . . .	holding-metering
2945/76207	. . . .	accumulators	2945/76411	. . . .	others
2945/7621	. . . .	nozzle	2945/76414	. . .	Solidification, setting phase
2945/76214	. . . .	drive means	2945/76418	. . .	Ejection
2945/76217	. . . .	nozzle-touch mechanism	2945/76421	. . .	Removing or handling ejected articles
2945/7622	. . . .	others	2945/76424	. . .	After-treatment
2945/76224	. . .	Closure or clamping unit	2945/76428	. . .	Purging
2945/76227	. . . .	mould platen	2945/76431	. . .	Calibration, e.g. zero-point correction
2945/7623	. . . .	clamping or closing drive means	2945/76434	. . .	Parameter setting
2945/76234	. . . .	tie-bars	2945/76438	. . .	Start up
2945/76237	. . . .	others	2945/76441	. . .	Shut down
2945/7624	. . .	Ejection unit	2945/76444	. . . .	in case of emergency
2945/76244	. . . .	ejectors	2945/76448	. . .	Others
2945/76247	. . . . .	drive means thereof	2945/76451	. . .	Measurement means (not used)
2945/7625	. . . .	others	2945/76454	. . .	Electrical, e.g. thermocouples
2945/76254	. . .	Mould	2945/76458	. . . .	piezo-electric
2945/76257	. . . .	cavity	2945/76461	. . .	Optical, e.g. laser
2945/7626	. . . . .	cavity walls	2945/76464	. . . .	cameras
2945/76264	. . . . .	movable	2945/76468	. . .	Manual
2945/76267	. . . .	non-cavity forming parts	2945/76471	. . .	Acoustic
2945/7627	. . . . .	movable	2945/76474	. . .	Ultrasonic
2945/76274	. . . .	runners, nozzles	2945/76478	. . .	Mechanical
2945/76277	. . . . .	nozzles	2945/76481	. . .	Strain gauges
2945/7628	. . . . .	manifolds	2945/76484	. . .	Fluid type
2945/76284	. . . .	others	2945/76488	. . .	Magnetic, electro-magnetic
2945/76287	. . .	Moulding material	2945/76491	. . .	Others
2945/7629	. . .	Moulded articles	2945/76494	. . .	Controlled parameter (not used)
2945/76294	. . .	Inserts	2945/76498	. . .	Pressure
2945/76297	. . .	Fluids	2945/76501	. . . .	derivative, change thereof
2945/76301	. . . .	auxiliary fluids introduced into the cavity	2945/76505	. . .	Force
2945/76304	. . . .	temperature control fluids	2945/76508	. . . .	derivative, change thereof
2945/76307	. . . .	hydraulic fluids	2945/76511	. . .	Torque
2945/76311	. . . .	environment	2945/76515	. . . .	derivative, change thereof
2945/76314	. . .	Auxiliary devices	2945/76518	. . .	Energy, power
2945/76317	. . . .	robots, grippers	2945/76521	. . . .	power
2945/76321	. . . .	conveyors	2945/76525	. . .	Electric current or voltage
2945/76324	. . . .	pre-treatment devices	2945/76528	. . .	Frequency
2945/76327	. . . .	post-treatment devices	2945/76531	. . .	Temperature
2945/76331	. . . .	raw material feeding devices	2945/76535	. . . .	derivative, change thereof
2945/76334	. . . .	auxiliary fluid supplying devices	2945/76538	. . .	Viscosity
2945/76337	. . . .	other auxiliary devices	2945/76541	. . . .	derivative, change thereof
2945/76341	. . .	Others	2945/76545	. . .	Flow rate
2945/76344	. . .	Phase or stage of measurement (not used)	2945/76548	. . . .	derivative, change thereof
2945/76347	. . .	Pre-treatment	2945/76551	. . .	Time
2945/76351	. . .	Feeding	2945/76555	. . . .	start
2945/76354	. . . .	raw materials	2945/76558	. . . .	termination
2945/76357	. . . .	inserts	2945/76561	. . . .	duration
2945/76361	. . . .	auxiliary fluids, e.g. gas, liquid	2945/76565	. . . .	pause, wilful interruption
2945/76364	. . . .	others	2945/76568	. . .	Position
2945/76367	. . .	Metering	2945/76571	. . . .	start position
2945/76371	. . .	Intrusion	2945/76575	. . . .	end position
2945/76374	. . .	Pre-compression prior to injection	2945/76578	. . . .	angular position
2945/76377	. . .	De-compression after injection	2945/76581	. . . .	distance
2945/76381	. . .	Injection	2945/76585	. . .	Dimensions, e.g. thickness

2945/76588	. . . . shrinkage, dilation, dimensional change, warpage	2945/76785	. . . . hydraulic fluids
2945/76591	. . . . volume	2945/76789	. . . . environment
2945/76595	. . . Velocity	2945/76792	. . . Auxiliary devices
2945/76598	. . . . linear movement	2945/76795	. . . . robots, grippers
2945/76602	. . . . . derivative, change thereof	2945/76799	. . . . conveyors
2945/76605	. . . . rotational movement	2945/76802	. . . . pre-treatment devices
2945/76608	. . . . . derivative, change thereof	2945/76806	. . . . post-treatment devices
2945/76612	. . . Density	2945/76809	. . . . raw material feeding devices
2945/76615	. . . Weight	2945/76812	. . . . Auxiliary fluid supplying devices
2945/76618	. . . Crystallinity	2945/76816	. . . . others auxiliary devices
2945/76622	. . . Degree of crosslinking, solidification	2945/76819	. . . Others
2945/76625	. . . Humidity, moisture	2945/76822	. . Phase or stage of control (not used)
2945/76628	. . . Volatiles	2945/76826	. . . Pre-treatment
2945/76632	. . . Contaminants	2945/76829	. . . Feeding
2945/76635	. . . Electrical properties	2945/76832	. . . . raw materials
2945/76638	. . . Optical properties	2945/76836	. . . . inserts
2945/76642	. . . Magnetic properties	2945/76839	. . . . auxiliary fluids, e.g. gas, liquid
2945/76645	. . . Surface properties	2945/76842	. . . . others
2945/76648	. . . Sequence, e.g. the order in which operations are conducted	2945/76846	. . . Metering
2945/76652	. . . Others	2945/76849	. . . Intrusion
2945/76655	. . Location of control (not used)	2945/76852	. . . Pre-compression prior to injection
2945/76658	. . . Injection unit	2945/76856	. . . De-compression after injection
2945/76662	. . . . hopper	2945/76859	. . . Injection
2945/76665	. . . . screw	2945/76862	. . . Holding, dwelling
2945/76668	. . . . barrel	2945/76866	. . . Mould closing
2945/76672	. . . . . barrel-chamber	2945/76869	. . . Mould clamping, compression of the cavity
2945/76675	. . . . . screw ante-chamber	2945/76872	. . . Mould opening
2945/76678	. . . . injection piston	2945/76876	. . . Switch-over
2945/76682	. . . . injection piston cylinder	2945/76879	. . . . metering-injection
2945/76685	. . . . accumulators	2945/76882	. . . . injection-holding
2945/76688	. . . . nozzle	2945/76886	. . . . holding-metering
2945/76692	. . . . drive means	2945/76889	. . . . others
2945/76695	. . . . nozzle-touch mechanism	2945/76892	. . . Solidification, setting phase
2945/76698	. . . . others	2945/76896	. . . Ejection
2945/76702	. . . Closure or clamping device	2945/76899	. . . Removing or handling ejected articles
2945/76705	. . . . mould platen	2945/76903	. . . After-treatment
2945/76709	. . . . clamping or closing drive means	2945/76906	. . . Purging
2945/76712	. . . . tie-bars	2945/76909	. . . Calibration, e.g. zero-point correction
2945/76715	. . . . others	2945/76913	. . . Parameter setting
2945/76719	. . . Ejection unit	2945/76916	. . . Start up
2945/76722	. . . . ejectors	2945/76919	. . . Shut down
2945/76725	. . . . . drive means thereof	2945/76923	. . . . in case of emergency
2945/76729	. . . . others	2945/76926	. . . Others
2945/76732	. . . Mould	2945/76929	. . Controlling method (not used)
2945/76735	. . . . cavity	2945/76933	. . . Open loop, i.e. the operating conditions are corrected immediately, during the same phase or cycle
2945/76739	. . . . . cavity walls	2945/76936	. . . Closed loop, i.e. the operating conditions are corrected in the next phase or cycle
2945/76742	. . . . . movable	2945/76939	. . . Using stored or historical data sets
2945/76745	. . . . non-cavity forming parts	2945/76943	. . . . compare with thresholds
2945/76749	. . . . . movable	2945/76946	. . . . using an expert system, i.e. the system possesses a database in which human experience is stored, e.g. to help interfering the possible cause of a fault
2945/76752	. . . . runners, nozzles	2945/76949	. . . . using a learning system, i.e. the system accumulates experience from previous occurrences, e.g. adaptive control
2945/76755	. . . . . nozzles	2945/76953	. . . Distributed, i.e. several control units perform different tasks
2945/76759	. . . . . manifolds	2945/76956	. . . Proportional
2945/76762	. . . . others	2945/76959	. . . . and derivative, i.e. PD regulation
2945/76765	. . . Moulding material		
2945/76769	. . . Moulded articles		
2945/76772	. . . Inserts		
2945/76775	. . . Fluids		
2945/76779	. . . . auxiliary fluids introduced into the cavity		
2945/76782	. . . . temperature control fluids		

2945/76963	. . . . .	using a second derivative, e.g. determination of inflexion points	2947/9238	. . . . .	Feeding, melting, plasticising or pumping zones, e.g. the melt itself
2945/76966	. . . . .	and integral, i.e. PI regulation	2947/9239	. . . . .	Screw or gear
2945/76969	. . . . .	derivative and integral, i.e. PID regulation	2947/924	. . . . .	Barrel or housing
2945/76973	. . . . .	By counting	2947/92409	. . . . .	Die; Nozzle zone
2945/76976	. . . . .	By trial and error, trial tests	2947/92419	. . . . .	Degassing unit
2945/76979	. . . . .	Using a neural network	2947/92428	. . . . .	Calibration, after-treatment, or cooling zone
2945/76983	. . . . .	Using fuzzy logic	2947/92438	. . . . .	Conveying, transporting or storage of articles
2945/76986	. . . . .	Interpolating	2947/92447	. . . . .	Moulded article
2945/76989	. . . . .	Extrapolating	2947/92457	. . . . .	Drive section, e.g. gearbox, motor or drive fluids
2945/76993	. . . . .	Remote, e.g. LAN, wireless LAN	2947/92466	. . . . .	Auxiliary unit, e.g. for external melt filtering, re-combining or transfer between units
2945/76996	. . . . .	Others	2947/92476	. . . . .	Fluids, e.g. for temperature control or of environment
<b>2947/00</b>		<b>Indexing scheme relating to extrusion moulding</b>	2947/92485	. . . . .	Start-up, shut-down or parameter setting phase; Emergency shut-down; Material change; Test or laboratory equipment or studies
2947/92	. . . . .	Measuring, controlling or regulating	2947/92495	. . . . .	Treatment of equipment, e.g. purging, cleaning, lubricating or filter exchange
2947/92009	. . . . .	Measured parameter	2947/92504	. . . . .	Controlled parameter
2947/92019	. . . . .	Pressure	2947/92514	. . . . .	Pressure
2947/92028	. . . . .	Force; Tension	2947/92523	. . . . .	Force; Tension
2947/92038	. . . . .	Torque	2947/92533	. . . . .	Torque
2947/92047	. . . . .	Energy, power, electric current or voltage	2947/92542	. . . . .	Energy, power, electric current or voltage
2947/92057	. . . . .	Frequency	2947/92552	. . . . .	Frequency
2947/92066	. . . . .	Time, e.g. start, termination, duration or interruption	2947/92561	. . . . .	Time, e.g. start, termination, duration or interruption
2947/92076	. . . . .	Position, e.g. linear or angular	2947/92571	. . . . .	Position, e.g. linear or angular
2947/92085	. . . . .	Velocity	2947/9258	. . . . .	Velocity
2947/92095	. . . . .	Angular velocity	2947/9259	. . . . .	Angular velocity
2947/92104	. . . . .	Flow or feed rate	2947/926	. . . . .	Flow or feed rate
2947/92114	. . . . .	Dimensions	2947/92609	. . . . .	Dimensions
2947/92123	. . . . .	Diameter or circumference	2947/92619	. . . . .	Diameter or circumference
2947/92133	. . . . .	Width or height	2947/92628	. . . . .	Width or height
2947/92142	. . . . .	Length	2947/92638	. . . . .	Length
2947/92152	. . . . .	Thickness	2947/92647	. . . . .	Thickness
2947/92161	. . . . .	Volume or quantity	2947/92657	. . . . .	Volume or quantity
2947/92171	. . . . .	Distortion, shrinkage, dilatation, swell or warpage	2947/92666	. . . . .	Distortion, shrinkage, dilatation, swell or warpage
2947/9218	. . . . .	Weight	2947/92676	. . . . .	Weight
2947/9219	. . . . .	Density, e.g. per unit length or area	2947/92685	. . . . .	Density, e.g. per unit length or area
2947/922	. . . . .	Viscosity; Melt flow index [MFI]; Molecular weight	2947/92695	. . . . .	Viscosity; Melt flow index [MFI]; Molecular weight
2947/92209	. . . . .	Temperature	2947/92704	. . . . .	Temperature
2947/92219	. . . . .	Degree of crosslinking, solidification, crystallinity or homogeneity	2947/92714	. . . . .	Degree of crosslinking, solidification, crystallinity or homogeneity
2947/92228	. . . . .	Content, e.g. percentage of humidity, volatiles, contaminants or degassing	2947/92723	. . . . .	Content, e.g. percentage of humidity, volatiles, contaminants or degassing
2947/92238	. . . . .	Electrical properties	2947/92733	. . . . .	Electrical properties
2947/92247	. . . . .	Optical properties	2947/92742	. . . . .	Optical properties
2947/92257	. . . . .	Colour	2947/92752	. . . . .	Colour
2947/92266	. . . . .	Mechanical properties	2947/92761	. . . . .	Mechanical properties
2947/92276	. . . . .	Magnetic properties	2947/92771	. . . . .	Magnetic properties
2947/92285	. . . . .	Surface properties	2947/9278	. . . . .	Surface properties
2947/92295	. . . . .	Errors or malfunctioning, e.g. for quality control	2947/9279	. . . . .	Errors or malfunctioning, e.g. for quality control
2947/92304	. . . . .	Presence or absence; Sequence; Counting	2947/928	. . . . .	Presence or absence; Sequence; Counting
2947/92314	. . . . .	Particular value claimed	2947/92809	. . . . .	Particular value claimed
2947/92323	. . . . .	Location or phase of measurement	2947/92819	. . . . .	Location or phase of control
2947/92333	. . . . .	Raw material handling or dosing, e.g. active hopper or feeding device	2947/92828	. . . . .	Raw material handling or dosing, e.g. active hopper or feeding device
2947/92342	. . . . .	Raw material pre-treatment, e.g. drying or cleaning			
2947/92352	. . . . .	Inserts			
2947/92361	. . . . .	Extrusion unit			
2947/92371	. . . . .	Inlet shaft or slot, e.g. passive hopper; Injector, e.g. injector nozzle on barrel			



2947/92838	. . .	Raw material pre-treatment, e.g. drying or cleaning	2949/78252	. . . . .	Die; Nozzle zone
2947/92847	. . .	Inserts	2949/7826	. . . . .	Handling phase or unit, e.g. feeding device
2947/92857	. . .	Extrusion unit	2949/78268	. . . . .	of blow moulded articles
2947/92866	. . . .	Inlet shaft or slot, e.g. passive hopper; Injector, e.g. injector nozzle on barrel	2949/78277	. . . . .	of inserts
2947/92876	. . . .	Feeding, melting, plasticising or pumping zones, e.g. the melt itself	2949/78285	. . . . .	of labels
2947/92885	. . . . .	Screw or gear	2949/78294	. . . . .	Blow moulding phase
2947/92895	. . . . .	Barrel or housing	2949/78302	. . . . .	Closure, opening or clamping phase or unit
2947/92904	. . . . .	Die; Nozzle zone	2949/7831	. . . . .	during opening phase
2947/92914	. . . . .	Degassing unit	2949/78319	. . . . .	during clamping phase
2947/92923	. . .	Calibration, after-treatment or cooling zone	2949/78327	. . . . .	Ejection phase or unit
2947/92933	. . .	Conveying, transporting or storage of articles	2949/78336	. . . . .	Mould
2947/92942	. . .	Moulded article	2949/78344	. . . . .	cavity
2947/92952	. . .	Drive section, e.g. gearbox, motor or drive fluids	2949/78352	. . . . .	non cavity forming parts
2947/92961	. . .	Auxiliary unit, e.g. for external melt filtering, re-combining or transfer between units	2949/78361	. . . . .	core of the injection blow moulding machine, e.g. core transporting preform to blow moulding machine
2947/92971	. . .	Fluids, e.g. for temperature control or of environment	2949/78369	. . . . .	Stretching phase or unit
2947/9298	. . .	Start-up, shut-down or parameter setting phase; Emergency shut-down; Material change; Test or laboratory equipment or studies	2949/78378	. . . . .	Blowing means, pressurized phase
2947/9299	. . .	Treatment of equipment, e.g. purging, cleaning, lubricating or filter exchange	2949/78386	. . . . .	Preform or parison
2949/00		<b>Blow moulding, i.e. blowing a preform or parison to a desired shape within a mould</b>	2949/78394	. . . . .	Moulded articles
2949/78	. . .	Measuring, controlling or regulating	2949/78403	. . . . .	Inserts
2949/78008	. . .	Measuring	2949/78411	. . . . .	Fluids
2949/78016	. . .	Measured parameter	2949/7842	. . . . .	introduced into the preform, parison or blown article
2949/78025	. . . . .	Pressure	2949/78428	. . . . .	for temperature control
2949/78033	. . . . .	Energy, power, electric current or voltage	2949/78436	. . . . .	Temperature control fluids, i.e. to regulate the temperature in the blow mould
2949/78042	. . . . .	Time, e.g. start, termination, duration or interruption	2949/78445	. . . . .	Driving means, e.g. motor or drive fluids
2949/7805	. . . . .	Position, e.g. start, end or actual position	2949/78453	. . . . .	Auxiliary phases or units
2949/78058	. . . . .	Velocity	2949/78462	. . . . .	Pre-treatment phase or devices
2949/78067	. . . . .	Dimension	2949/7847	. . . . .	Post-treatment phases or devices
2949/78075	. . . . .	Diameter	2949/78478	. . . . .	Start-up, shut-down phase; Emergency shut down
2949/78084	. . . . .	Length	2949/78487	. . . . .	Measurement means
2949/78092	. . . . .	Thickness	2949/78495	. . . . .	Electrical, e.g. thermocouples
2949/781	. . . . .	of individual layers of multilayered objects	2949/78504	. . . . .	Optical, e.g. laser
2949/78109	. . . . .	Volume or quantity	2949/78512	. . . . .	Cameras
2949/78117	. . . . .	Dimensional change, e.g. distortion or shrinkage	2949/78521	. . . . .	Controlling or regulating
2949/78126	. . . . .	Weight	2949/78529	. . . . .	Controlled parameter
2949/78134	. . . . .	Density, e.g. per unit length or area	2949/78537	. . . . .	Pressure
2949/78142	. . . . .	Viscosity	2949/78546	. . . . .	Energy, power, electric current or voltage
2949/78151	. . . . .	Temperature	2949/78554	. . . . .	Time, e.g. start, termination, duration or interruption
2949/78159	. . . . .	Electrical properties	2949/78563	. . . . .	Position, e.g. start, end or actual position
2949/78168	. . . . .	Optical properties	2949/78571	. . . . .	Velocity
2949/78176	. . . . .	Colour, e.g. transparency	2949/78579	. . . . .	Dimension
2949/78184	. . . . .	Mechanical properties	2949/78588	. . . . .	Diameter
2949/78193	. . . . .	Magnetic properties	2949/78596	. . . . .	Length
2949/78201	. . . . .	Surface properties	2949/78605	. . . . .	Thickness
2949/7821	. . . . .	Errors or malfunctioning	2949/78613	. . . . .	of individual layers of multilayered objects
2949/78218	. . . . .	Presence or absence, e.g. of preforms or parisons	2949/78621	. . . . .	Volume or quantity
2949/78226	. . .	Location or phase of measurement	2949/7863	. . . . .	Dimensional change, e.g. distortion or shrinkage
2949/78235	. . . . .	Injection phase or unit	2949/78638	. . . . .	Weight
2949/78243	. . . . .	Extrusion phase or unit	2949/78647	. . . . .	Density, e.g. per unit length or area
			2949/78655	. . . . .	Viscosity
			2949/78663	. . . . .	Temperature
			2949/78672	. . . . .	Electrical properties
			2949/7868	. . . . .	Optical properties
			2949/78689	. . . . .	Colour, e.g. transparency
			2949/78697	. . . . .	Mechanical properties

2949/78705	. . . .	Magnetic properties
2949/78714	. . . .	Surface properties
2949/78722	. . . .	Errors or malfunctioning
2949/78731	. . . .	Presence or absence, e.g. of preforms or parisons
2949/78739	. . . .	Location or phase of control
2949/78747	. . . .	Injection phase or unit
2949/78756	. . . .	Extrusion phase or unit
2949/78764	. . . . .	Die; Nozzle zone
2949/78773	. . . .	Handling phase or unit, e.g. feeding device
2949/78781	. . . . .	of blow moulded articles
2949/78789	. . . . .	of inserts
2949/78798	. . . . .	of labels
2949/78806	. . . .	Blow moulding phase
2949/78815	. . . .	Closure, opening or clamping phase or unit
2949/78823	. . . . .	during opening phase
2949/78831	. . . . .	during clamping phase
2949/7884	. . . .	Ejection phase or unit
2949/78848	. . . .	Mould
2949/78857	. . . . .	cavity
2949/78865	. . . . .	non cavity forming parts
2949/78873	. . . . .	core of the injection blow moulding machine, e.g. core transporting preform to blow moulding machine
2949/78882	. . . .	Stretching phase or unit
2949/7889	. . . .	Blowing means, pressurized phase
2949/78899	. . . .	Preform or parison
2949/78907	. . . .	Moulded articles
2949/78915	. . . .	Inserts
2949/78924	. . . .	Fluids
2949/78932	. . . . .	introduced into the preform, parison or blown article
2949/78941	. . . . .	for temperature control
2949/78949	. . . . .	Temperature control fluids, i.e. to regulate the temperature in the blow mould
2949/78957	. . . .	Driving means, e.g. motor or drive fluids
2949/78966	. . . .	Auxiliary phases or units
2949/78974	. . . . .	Pre-treatment phases or devices
2949/78983	. . . . .	Post-treatment phases or devices
2949/78991	. . . .	Start-up, shut-down phase; Emergency shut down