

CPC COOPERATIVE PATENT CLASSIFICATION

G PHYSICS (NOTES omitted)

INSTRUMENTS

G01 MEASURING; TESTING (NOTES omitted)

G01C MEASURING DISTANCES, LEVELS OR BEARINGS; SURVEYING; NAVIGATION; GYROSCOPIC INSTRUMENTS; PHOTOGRAMMETRY OR VIDEOGRAMMETRY (measuring liquid level [G01F](#); radio navigation, determining distance or velocity by use of propagation effects, e.g. Doppler effects, propagation time, of radio waves, analogous arrangements using other waves [G01S](#))

NOTES

1. In this subclass, the following term is used with the meaning indicated:
"navigation" means determining the position and course of land vehicles, ships, aircraft, and space vehicles.
2. Attention is drawn to the Notes following the title of class [G01](#).

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:
[G01C 11/36](#) covered by [G01C 11/00-G01C 11/34](#)
2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Measuring angles	3/18	. . with one observation point at each end of the base (G01C 3/20 takes precedence)
1/02	. Theodolites	3/20	. . with adaptation to the measurement of the height of an object
1/04	. . combined with cameras	3/22	. using a parallactic triangle with variable angles and a base of fixed length at, near, or formed by the object
1/06	. . Arrangements for reading scales	3/24	. using a parallactic triangle with fixed angles and a base of variable length in the observation station, e.g. in the instrument
1/08	. Sextants	3/26	. using a parallactic triangle with fixed angles and a base of variable length, at, near, or formed by the object
1/10	. . including an artificial horizon (G01C 1/14 takes precedence)	3/28	. . with provision for reduction of the distance into the horizontal plane
1/12	. . . with a stabilised mirror	3/30	. . . with adaptation to the measurement of the height of an object, e.g. tachometers
1/14	. . Periscopic sextants	3/32	. by focusing the object, e.g. on a ground glass screen
3/00	Measuring distances in line of sight; Optical rangefinders (tapes, chains or wheels for measuring length G01B 3/00; active triangulation systems, i.e. using the transmission and reflection of electromagnetic waves other than radio waves, G01S 17/48)	5/00	Measuring height; Measuring distances transverse to line of sight; Levelling between separated points; Surveyors' levels (G01C 3/20, G01C 3/30 take precedence)
3/02	. Details	5/005	. {altimeters for aircraft (G01C 5/02 , G01C 5/06 take precedence)}
3/04	. . Adaptation of rangefinders for combination with telescopes or binoculars	5/02	. involving automatic stabilisation of the line of sight
3/06	. . Use of electric means to obtain final indication	5/04	. Hydrostatic levelling, i.e. by flexibly interconnected liquid containers at separated points
3/08	. . . Use of electric radiation detectors	5/06	. by using barometric means
3/085 {with electronic parallax measurement}		
3/10	. using a parallactic triangle with variable angles and a base of fixed length in the observation station, e.g. in the instrument	7/00	Tracing profiles (by photogrammetry or videogrammetry G01C 11/00)
3/12	. . with monocular observation at a single point, e.g. coincidence type (G01C 3/20 takes precedence)		
3/14	. . with binocular observation at a single point, e.g. stereoscopic type (G01C 3/20 takes precedence)		
3/16	. . . Measuring marks		

7/02	. of land surfaces	11/14 with optical projection (G01C 11/26 takes precedence)
7/04	. . involving a vehicle which moves along the profile to be traced	11/16 in a common plane
7/06	. of cavities, e.g. tunnels	11/18 involving scanning means
9/00	Measuring inclination, e.g. by clinometers, by levels	11/20 in separate planes
9/005	. { specially adapted for use in aircraft }	11/22 with mechanical projection (G01C 11/26 takes precedence)
9/02	. Details	11/24 with optical-mechanical projection (G01C 11/26 takes precedence)
9/04	. . Transmission means between sensing element and final indicator for giving an enlarged reading	11/26 using computers to control the position of the pictures
9/06	. . Electric or photoelectric indication or reading means	11/28	. . . Special adaptation for recording picture point data, e.g. for profiles
2009/062	. . . { capacitive }	11/30	. . by triangulation
2009/064	. . . { inductive }	11/32	. . . Radial triangulation
2009/066	. . . { optical }	11/34	. . . Aerial triangulation
2009/068	. . . { resistive }	2011/36	. { Videogrammetry, i.e. electronic processing of video signals from a single source or from different sources to give parallax or range information }
9/08	. . Means for compensating acceleration forces due to movement of instrument	13/00	Surveying specially adapted to open water, e.g. sea, lake, river or canal (liquid level metering G01F)
9/10	. by using rolling bodies {, e.g. spheres, cylinders, mercury droplets }	13/002	. { Measuring the movement of open water }
2009/102	. . { cylinders }	13/004	. . { vertical movement }
2009/105	. . { mercury droplets }	13/006	. . { horizontal movement }
2009/107	. . { spheres }	13/008	. { measuring depth of open water }
9/12	. by using a single pendulum { plumb lines G01C 15/10 }	15/00	Surveying instruments or accessories not provided for in groups G01C 1/00 - G01C 13/00
9/14	. . movable in more than one direction	15/002	. { Active optical surveying means (optical plumbing G01C 15/105) }
9/16	. by using more than one pendulum	15/004	. . { Reference lines, planes or sectors }
9/18	. by using liquids	15/006	. . . { Detectors therefor }
2009/182	. . { conductive }	15/008	. . { combined with inclination sensor }
2009/185	. . { dielectric }	15/02	. Means for marking measuring points
2009/187	. . { magnetic, e.g. ferromagnetic }	15/04	. . Permanent marks; Boundary markers
9/20	. . the indication being based on the inclination of the surface of a liquid relative to its container	15/06	. . Surveyors' staffs; Movable markers
9/22	. . . with interconnected containers in fixed relation to each other	15/08	. . . Plumbing or registering staffs or markers over ground marks
9/24	. . in closed containers partially filled with liquid so as to leave a gas bubble	15/10	. Plumb lines
9/26	. . . Details	15/105	. . { Optical plumbing }
9/28 Mountings	15/12	. Instruments for setting out fixed angles, e.g. right angles
9/30 Means for adjusting dimensions of bubble	15/14	. Artificial horizons
9/32 Means for facilitating the observation of the position of the bubble, e.g. illuminating means	17/00	Compasses; Devices for ascertaining true or magnetic north for navigation or surveying purposes (using gyroscopic effect G01C 19/00)
9/34	. . . of the tubular type, i.e. for indicating the level in one direction only	17/02	. Magnetic compasses
9/36	. . . of the spherical type, i.e. for indicating the level in all directions	17/04	. . with north-seeking magnetic elements, e.g. needles
11/00	Photogrammetry or videogrammetry, e.g. stereogrammetry; Photographic surveying	17/06	. . . Suspending magnetic elements
11/02	. Picture taking arrangements specially adapted for photogrammetry or photographic surveying, e.g. controlling overlapping of pictures	17/08 by flotation
11/025	. . { by scanning the object }	17/10	. . . Comparing observed direction with north indication
11/04	. Interpretation of pictures	17/12 by sighting means, e.g. for surveyors' compasses
11/06	. . by comparison of two or more pictures of the same area	17/14 by reference marks, e.g. for ships' compasses
11/08	. . . the pictures not being supported in the same relative position as when they were taken	17/16 by clinometers, e.g. for determining dip or strike of geological strata
11/10 using computers to control the position of the pictures	17/18	. . . Supporting or suspending compasses, e.g. by gimbal, by flotation
11/12	. . . the pictures being supported in the same relative position as when they were taken	17/20	. . . Observing the compass card or needle
		17/22 by projection

- 17/24 Illumination
- 17/26 using electric pick-offs for transmission to final indicator, e.g. photocell
- 17/28 . . Electromagnetic compasses ([with north seeking magnetic elements and having electric pick-offs G01C 17/26](#))
- 17/30 . . . Earth-inductor compasses
- 17/32 . . . Electron compasses
- 17/34 . Sun- or astro-compasses
- 17/36 . Repeaters for remote indication of readings of a master compass
- 17/38 . Testing, calibrating, or compensating of compasses
- 19/00 Gyroscopes; Turn-sensitive devices using vibrating masses; Turn-sensitive devices without moving masses; Measuring angular rate using gyroscopic effects**
- 19/02 . Rotary gyroscopes
- 19/025 . . {[Special arrangements for gyros functioning during a short period](#)}
- 19/04 . . Details
- 19/06 . . . Rotors
- 19/065 {[Measurement or control of angular velocity, specifically adapted to gyrorotors](#)}
- 19/08 electrically driven ([G01C 19/14 takes precedence](#))
- 19/10 Power supply
- 19/12 fluid driven ([G01C 19/14 takes precedence](#))
- 19/14 Fluid rotors
- 19/16 . . . Suspensions; Bearings
- 19/18 providing movement of rotor with respect to its rotational axes ([G01C 19/20, G01C 19/24 take precedence](#))
- 19/20 in fluid
- 19/22 torsional
- 19/24 using magnetic or electrostatic fields
- 19/26 . . . Caging, i.e. immobilising moving parts, e.g. for transport
- 19/28 . . . Pick-offs, i.e. devices for taking-off an indication of the displacement of the rotor axis
- 19/30 . . . Erection devices, i.e. devices for restoring rotor axis to a desired position ([for instrument indicating the vertical G01C 19/46](#))
- 19/32 . . . Indicating or recording means specially adapted for rotary gyroscopes
- 19/34 . . for indicating a direction in the horizontal plane, e.g. directional gyroscopes
- 19/36 . . . with north-seeking action by magnetic means, e.g. gyromagnetic compasses
- 19/38 . . . with north-seeking action by other than magnetic means, e.g. gyrocompasses using earth's rotation
- 19/40 . . for control by signals from a master compass, i.e. repeater compasses
- 19/42 . . for indicating rate of turn; for integrating rate of turn
- 19/44 . . for indicating the vertical
- 19/46 . . . Erection devices for restoring rotor axis to a desired position
- 19/48 operating by electrical means ([G01C 19/54 takes precedence](#))
- 19/50 operating by mechanical means ([G01C 19/54 takes precedence](#))
- 19/52 operating by fluid means ([G01C 19/54 takes precedence](#))
- 19/54 with correction for acceleration forces due to movement of instrument
- 19/56 . Turn-sensitive devices using vibrating masses, e.g. vibratory angular rate sensors based on Coriolis forces
- 19/5607 . . using vibrating tuning forks ([double-ended tuning forks using planar vibrating masses suspended at opposite ends G01C 19/5719](#))
- 19/5614 . . . Signal processing
- 19/5621 . . . the devices involving a micromechanical structure
- 19/5628 . . . Manufacturing; Trimming; Mounting; Housings
- 19/5635 . . using vibrating wires or strings
- 19/5642 . . using vibrating bars or beams
- 19/5649 . . . Signal processing
- 19/5656 . . . the devices involving a micromechanical structure
- 19/5663 . . . Manufacturing; Trimming; Mounting; Housings
- 19/567 . . using the phase shift of a vibration node or antinode
- 19/5677 . . . of essentially two-dimensional vibrators, e.g. ring-shaped vibrators
- 19/5684 the devices involving a micromechanical structure
- 19/5691 . . . of essentially three-dimensional vibrators, e.g. wine glass-type vibrators
- 19/5698 . . using acoustic waves, e.g. surface acoustic wave gyros
- 19/5705 . . using masses driven in reciprocating rotary motion about an axis
- 19/5712 . . . the devices involving a micromechanical structure
- 19/5719 . . using planar vibrating masses driven in a translation vibration along an axis
- 19/5726 . . . Signal processing
- 19/5733 . . . Structural details or topology
- 19/574 the devices having two sensing masses in anti-phase motion
- 19/5747 each sensing mass being connected to a driving mass, e.g. driving frames
- 19/5755 the devices having a single sensing mass
- 19/5762 the sensing mass being connected to a driving mass, e.g. driving frames
- 19/5769 . . . Manufacturing; Mounting; Housings
- 19/5776 . . Signal processing not specific to any of the devices covered by groups [G01C 19/5607](#) - [G01C 19/5719](#)
- 19/5783 . . Mountings or housings not specific to any of the devices covered by groups [G01C 19/5607](#) - [G01C 19/5719](#)
- 19/58 . Turn-sensitive devices without moving masses
- 19/60 . . Electronic or nuclear magnetic resonance gyrometers
- 19/62 . . . with optical pumping
- 19/64 . . Gyrometers using the Sagnac effect, i.e. rotation-induced shifts between counter-rotating electromagnetic beams
- 19/66 . . . Ring laser gyrometers
- 19/661 {[details](#)}
- 19/662 {[signal readout; dither compensators](#)}

- 19/664 { means for removing the dither signal }
- 19/665 { control of the cavity }
- 19/667 { using a multioscillator ring laser }
- 19/668 { Assemblies for measuring along different axes, e.g. triads }
- 19/68 Lock-in prevention
- 19/70 by mechanical means
- 19/72 with counter-rotating light beams in a passive ring, e.g. fibre laser gyrometers
- 19/721 { Details }
- 19/722 { of the mechanical construction }
- 19/723 { Heterodyning fibre optic gyrometers }
- 19/725 { using nxn optical couplers, e.g. 3x3 couplers }
- 19/726 { Phase nulling gyrometers, i.e. compensating the Sagnac phase shift in a closed loop system }
- 19/727 { using a passive ring resonator }
- 19/728 { Assemblies for measuring along different axes, e.g. triads }

21/00 **Navigation; Navigational instruments not provided for in groups G01C 1/00 - G01C 19/00** (measuring distance traversed on the ground by a vehicle [G01C 22/00](#); control of position, course, altitude or attitude of vehicles [G05D 1/00](#); traffic control systems for road vehicles involving transmission of navigation instructions to the vehicle [G08G 1/0968](#))

WARNING

Group [G01C 21/00](#) is impacted by reclassification into groups [G01C 21/38](#) - [G01C 21/3896](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 21/005 . { with correlation of navigation data from several sources, e.g. map or contour matching ([G01C 21/30](#) takes precedence) }
- 21/02 . by astronomical means ([G01C 21/24](#), [G01C 21/26](#) take precedence)
- 21/025 . . { with the use of startrackers }
- 21/04 . by terrestrial means ([G01C 21/24](#), [G01C 21/26](#) take precedence)
- 21/06 . . involving measuring of drift angle; involving correction for drift
- 21/08 . . involving use of the magnetic field of the earth
- 21/10 . by using measurements of speed or acceleration ([G01C 21/24](#), [G01C 21/26](#) take precedence)
- 21/12 . . executed aboard the object being navigated; Dead reckoning
- 21/14 . . . by recording the course traversed by the object ([G01C 21/16](#) takes precedence)
- 21/16 . . . by integrating acceleration or speed, i.e. inertial navigation

WARNING

Group [G01C 21/16](#) is impacted by reclassification into groups [G01C 21/166](#), [G01C 21/183](#), [G01C 21/185](#), and [G01C 21/188](#).

Groups [G01C 21/16](#), [G01C 21/166](#), [G01C 21/183](#), [G01C 21/185](#), and [G01C 21/188](#) should be considered in order to perform a complete search.

- 21/165 { combined with non-inertial navigation instruments }

WARNING

Group [G01C 21/165](#) is impacted by reclassification into groups [G01C 21/1652](#), [G01C 21/1654](#), and [G01C 21/1656](#).

Groups [G01C 21/165](#), [G01C 21/1652](#), [G01C 21/1654](#), and [G01C 21/1656](#) should be considered in order to perform a complete search.

- 21/1652 { with ranging devices, e.g. LIDAR or RADAR }

WARNING

Group [G01C 21/1652](#) is incomplete pending reclassification of documents from group [G01C 21/165](#).

Groups [G01C 21/165](#) and [G01C 21/1652](#) should be considered in order to perform a complete search.

- 21/1654 { with electromagnetic compass }

WARNING

Group [G01C 21/1654](#) is incomplete pending reclassification of documents from group [G01C 21/165](#).

Groups [G01C 21/165](#) and [G01C 21/1654](#) should be considered in order to perform a complete search.

- 21/1656 { with passive imaging devices, e.g. cameras }

WARNING

Group [G01C 21/1656](#) is incomplete pending reclassification of documents from group [G01C 21/165](#).

Groups [G01C 21/165](#) and [G01C 21/1656](#) should be considered in order to perform a complete search.

- 21/166 { Mechanical, construction or arrangement details of inertial navigation systems }

WARNING

Group [G01C 21/166](#) is incomplete pending reclassification of documents from group [G01C 21/16](#).

Groups [G01C 21/16](#) and [G01C 21/166](#) should be considered in order to perform a complete search.

- 21/18 Stabilised platforms, e.g. by gyroscope

- 21/183 {Compensation of inertial measurements, e.g. for temperature effects}
WARNING
 Group [G01C 21/183](#) is incomplete pending reclassification of documents from groups [G01C 21/16](#).
 Groups [G01C 21/16](#) and [G01C 21/183](#) should be considered in order to perform a complete search.
- 21/185 {for gravity}
WARNING
 Group [G01C 21/185](#) is incomplete pending reclassification of documents from groups [G01C 21/16](#).
 Groups [G01C 21/16](#) and [G01C 21/185](#) should be considered in order to perform a complete search.
- 21/188 {for accumulated errors, e.g. by coupling inertial systems with absolute positioning systems}
WARNING
 Group [G01C 21/188](#) is incomplete pending reclassification of documents from groups [G01C 21/16](#).
 Groups [G01C 21/16](#) and [G01C 21/188](#) should be considered in order to perform a complete search.
- 21/20 . Instruments for performing navigational calculations ([G01C 21/24](#), [G01C 21/26](#) take precedence)
- 21/203 . . {Specially adapted for sailing ships}
- 21/206 . . {specially adapted for indoor navigation}
- 21/22 . . Plotting boards
- 21/24 . specially adapted for cosmonautical navigation
- 21/26 . specially adapted for navigation in a road network
- 21/265 . . {constructional aspects of navigation devices, e.g. housings, mountings, displays ([G01C 21/3688](#) takes precedence)}
- 21/28 . . with correlation of data from several navigational instruments
- 21/30 . . . Map- or contour-matching
- 21/32 Structuring or formatting of map data
WARNING
 Group [G01C 21/32](#) is impacted by reclassification into groups [G01C 21/38](#) - [G01C 21/3896](#).
 Groups [G01C 21/32](#) and [G01C 21/38](#) - [G01C 21/3896](#) should be considered in order to perform a complete search.
- 21/34 . . Route searching; Route guidance
- 21/3407 . . . {specially adapted for specific applications}
- 21/3415 {Dynamic re-routing, e.g. recalculating the route when the user deviates from calculated route or after detecting real-time traffic data or accidents}
- 21/3423 {Multimodal routing, i.e. combining two or more modes of transportation, where the modes can be any of, e.g. driving, walking, cycling, public transport}
- 21/343 {Calculating itineraries, i.e. routes leading from a starting point to a series of categorical destinations using a global route restraint, round trips, touristic trips ([travelling salesman problem G06Q 10/04](#); [optimisation of routes G06Q 10/047](#))}
- 21/3438 {Rendez-vous, i.e. searching a destination where several users can meet, and the routes to this destination for these users; Ride sharing, i.e. searching a route such that at least two users can share a vehicle for at least part of the route}
- 21/3446 . . . {Details of route searching algorithms, e.g. Dijkstra, A*, arc-flags, using precalculated routes}
- 21/3453 . . . {Special cost functions, i.e. other than distance or default speed limit of road segments}
- 21/3461 {Preferred or disfavoured areas, e.g. dangerous zones, toll or emission zones, intersections, manoeuvre types, segments such as motorways, toll roads, ferries}
- 21/3469 {Fuel consumption; Energy use; Emission aspects}
- 21/3476 {using point of interest [POI] information, e.g. a route passing visible POIs}
- 21/3484 {Personalized, e.g. from learned user behaviour or user-defined profiles}
- 21/3492 {employing speed data or traffic data, e.g. real-time or historical ([traffic control systems for road vehicles involving transmission of navigation instructions to the vehicle G08G 1/0968](#))}
- 21/36 . . . Input/output arrangements for on-board computers
- 21/3602 {Input other than that of destination using image analysis, e.g. detection of road signs, lanes, buildings, real preceding vehicles using a camera}
- 21/3605 {Destination input or retrieval}
- 21/3608 {using speech input, e.g. using speech recognition}
- 21/3611 {using character input or menus, e.g. menus of POIs ([character input methods in general G06F 3/0233](#))}
- 21/3614 {through interaction with a road map, e.g. selecting a POI icon on a road map}
- 21/3617 {using user history, behaviour, conditions or preferences, e.g. predicted or inferred from previous use or current movement}
- 21/362 {received from an external device or application, e.g. PDA, mobile phone or calendar application}
- 21/3623 {using a camera or code reader, e.g. for optical or magnetic codes}
- 21/3626 {Details of the output of route guidance instructions ([traffic control systems for road vehicles involving transmission of navigation instructions to the vehicle G08G 1/0968](#))}
- 21/3629 {Guidance using speech or audio output, e.g. text-to-speech ([text to speech systems per se G10L 13/00](#))}

- 21/3632 {Guidance using simplified or iconic instructions, e.g. using arrows ([G01C 21/365 takes precedence](#))}
- 21/3635 {Guidance using 3D or perspective road maps}
- 21/3638 {including 3D objects and buildings (three dimensional [3D] modelling, e.g. data description of 3D objects [G06T 17/00](#); geographic models [G06T 17/05](#))}
- 21/3641 {Personalized guidance, e.g. limited guidance on previously travelled routes}
- 21/3644 {Landmark guidance, e.g. using POIs or conspicuous other objects}
- 21/3647 {Guidance involving output of stored or live camera images or video streams}
- 21/365 {Guidance using head up displays or projectors, e.g. virtual vehicles or arrows projected on the windscreen or on the road itself}
- 21/3652 {Guidance using non-audiovisual output, e.g. tactile, haptic or electric stimuli}
- 21/3655 {Timing of guidance instructions}
- 21/3658 {Lane guidance}
- 21/3661 {Guidance output on an external device, e.g. car radio}
- 21/3664 {Details of the user input interface, e.g. buttons, knobs or sliders, including those provided on a touch screen; remote controllers; input using gestures}
- 21/3667 {Display of a road map ([G01C 21/3614 takes precedence](#); guidance using 3D or perspective road maps [G01C 21/3635](#))}
- 21/367 {Details, e.g. road map scale, orientation, zooming, illumination, level of detail, scrolling of road map or positioning of current position marker}
- 21/3673 {Labelling using text of road map data items, e.g. road names, POI names}
- 21/3676 {Overview of the route on the road map}
- 21/3679 {Retrieval, searching and output of POI information, e.g. hotels, restaurants, shops, filling stations, parking facilities ([G01C 21/3611 takes precedence](#))}
- 21/3682 {output of POI information on a road map ([G01C 21/3614](#), [G01C 21/3685 take precedence](#))}
- 21/3685 {the POI's being parking facilities}
- 21/3688 {Systems comprising multiple parts or multiple output devices (not client-server), e.g. detachable faceplates, key fobs or multiple output screens}
- 21/3691 {Retrieval, searching and output of information related to real-time traffic, weather, or environmental conditions ([arrangements for giving variable traffic instructions G08G 1/09](#))}
- 21/3694 {Output thereof on a road map}
- 21/3697 {Output of additional, non-guidance related information, e.g. low fuel level ([G01C 21/3679 takes precedence](#))}
- 21/38 {Electronic maps specially adapted for navigation; Updating thereof}
- WARNING**
Groups [G01C 21/38](#) - [G01C 21/3896](#) are incomplete pending reclassification of documents from groups [G01C 21/00](#) and [G01C 21/32](#).
Groups [G01C 21/00](#), [G01C 21/32](#), and [G01C 21/38](#) - [G01C 21/3896](#) should be considered in order to perform a complete search.
- 21/3804 . . . {Creation or updating of map data}
- 21/3807 . . . {characterised by the type of data}
- 21/3811 {Point data, e.g. Point of Interest [POI]}
- 21/3815 {Road data}
- 21/3819 {Road shape data, e.g. outline of a route}
- 21/3822 {Road feature data, e.g. slope data}
- 21/3826 {Terrain data}
- 21/383 {Indoor data}
- 21/3833 . . . {characterised by the source of data}
- 21/3837 {Data obtained from a single source}
- 21/3841 {Data obtained from two or more sources, e.g. probe vehicles}
- 21/3844 {Data obtained from position sensors only, e.g. from inertial navigation}
- 21/3848 {Data obtained from both position sensors and additional sensors}
- 21/3852 {Data derived from aerial or satellite images}
- 21/3856 {Data obtained from user input}
- 21/3859 . . . {Differential updating map data}
- 21/3863 . . . {Structures of map data}
- 21/3867 . . . {Geometry of map features, e.g. shape points, polygons or for simplified maps}
- 21/387 . . . {Organisation of map data, e.g. version management or database structures}
- 21/3874 {Structures specially adapted for data searching and retrieval}
- 21/3878 {Hierarchical structures, e.g. layering}
- 21/3881 {Tile-based structures}
- 21/3885 . . . {Transmission of map data to client devices; Reception of map data by client devices}
- 21/3889 . . . {Transmission of selected map data, e.g. depending on route}
- 21/3893 . . . {Transmission of map data from distributed sources, e.g. from roadside stations}
- 21/3896 . . . {Transmission of map data from central databases}
- 22/00 Measuring distance traversed on the ground by vehicles, persons, animals or other moving solid bodies, e.g. using odometers, using pedometers**
- 22/002 . . . {for cycles}
- 22/004 . . . {for golf carts }
- 22/006 . . . {Pedometers}
- 22/008 . . . {for skates}
- 22/02 . . . by conversion into electric waveforms and subsequent integration, e.g. using tachometer generator {([G01C 22/002](#), [G01C 22/004](#), [G01C 22/006 take precedence](#))}
- 22/025 . . . {Differential odometers}

G01C

- 23/00** Combined instruments indicating more than one navigational value, e.g. for aircraft; Combined measuring devices for measuring two or more variables of movement, e.g. distance, speed, acceleration
- 23/005
 - {Flight directors (indicating arrangements specially adapted for rotary gyroscopes [G01C 19/32](#))}
- 25/00** Manufacturing, calibrating, cleaning, or repairing instruments or devices referred to in the other groups of this subclass (testing, calibrating or compensating compasses [G01C 17/38](#))
- 25/005
 - {initial alignment, calibration or starting-up of inertial devices}