

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F16 ENGINEERING ELEMENTS AND UNITS; GENERAL MEASURES FOR PRODUCING AND MAINTAINING EFFECTIVE FUNCTIONING OF MACHINES OR INSTALLATIONS; THERMAL INSULATION IN GENERAL

F16J PISTONS {(specially adapted for dampers [F16F 9/32](#))}; CYLINDERS; SEALINGS

NOTE

Attention is drawn to the following places:

A47J 27/08	Pressure cookers
E04B 1/68	Sealing building joints
E05C 9/00	Multi-point fastening of wings in general
F01B	Machines or engines in general or of reciprocating type, e.g. cylinders peculiar to steam engines
F01B 31/28	
F02F 1/00	Cylinders for combustion engines
F02F 3/00	Pistons for combustion engines
F04D 29/08	Sealings of non-positive displacement pumps
F17B 1/04	Sealing devices for sliding parts of gas holders of variable capacity
F28F 9/04	Arrangements for sealing elements into header boxes or end plates of heat-exchangers.

WARNINGS

- The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:
[F16J 15/53](#) covered by [F16J 15/43](#)
- In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Pistons; Trunk pistons; Plungers (bellows pistons F16J 3/06; piston-rings or seats therefor F16J 9/00; {manufacture of pistons B23P 15/10}; rotary pistons, e.g. for "Wankel" type engines F01C; specific for combustion engines, i.e. constructed to withstand high temperature or modified for guiding, igniting, vaporising or otherwise treating the charge F02F; {pistons for hydraulic engines F03C}; pumps F04B; floats F16K 33/00)	1/14	. . with connecting-rods, i.e. pivotal connections
		1/16	. . . with gudgeon-pin; Gudgeon-pins
		1/18 Securing of gudgeon-pins
		1/20	. . . with rolling contact, other than in ball or roller bearings
		1/22	. . . with universal joint, e.g. ball-joint
		1/24	. . designed to give the piston some rotary movement about its axis
		3/00	Diaphragms; Bellows; Bellows pistons (connection of valves to inflatable elastic bodies B60C 29/00; bellows or the like used in instruments G12B 1/04; diaphragms for electromechanical transducers H04R 7/00)
1/001	. {One-piece pistons}	3/02	. Diaphragms
1/003	. . {with integral sealing lips}	3/04	. Bellows
1/005	. {obtained by assembling several pieces}	3/041	. . {Non-metallic bellows}
1/006	. . {of different materials}	3/042	. . . {Fastening details}
1/008	. . . {with sealing lips}	3/043	. . . {with particular means for limiting wear}
1/01	. characterised by the use of particular materials (F16J 1/02 takes precedence)	3/045	. . . {Split bellows}
1/02	. Bearing surfaces	3/046	. . . {Lubrication or venting arrangements}
1/04	. Resilient guiding parts, e.g. skirts, particularly for trunk pistons	3/047	. . {Metallic bellows}
1/06	. . with separate expansion members; Expansion members	3/048	. . {with guiding or supporting means}
1/08	. Constructional features providing for lubrication	3/06	. Bellows pistons
1/09	. with means for guiding fluids (F16J 1/08 takes precedence)	7/00	Piston-rods
1/10	. Connection to driving members		
1/12	. . with piston-rods, e.g. rigid connections		

9/00	Piston-rings {, e.g. non-metallic piston-rings}, seats therefor; Ring sealings of similar construction (other sealings between pistons and cylinders F16J 3/06 , F16J 15/16 {; manufacture of piston-rings B23P 15/06 , B23P 15/08 }; tools for mounting or removing piston-rings or the like B25B ; piston sealing arrangements on brake master cylinders B60T 11/236 {; sealing provided on pump pistons F04B 53/143 })	13/00	Covers or similar closure members for pressure vessels in general (for engines or like cylinders F16J 10/00 ; sealings F16J 15/02 ; covers for box-like containers B65D 43/00 ; devices for securing or retaining closure members B65D 45/00 ; closures for containers not otherwise provided for B65D 51/00 ; manholes, covers for large containers B65D 90/10 ; gates or closures for large containers B65D 90/54 ; for vessels for containing or storing compressed, liquefied or solidified gases F17C 13/06 ; steam boilers F22B)
9/02	• L-section rings	13/02	• Detachable closure members; Means for tightening closures (F16J 13/16 , F16J 13/22 take precedence)
9/04	• Helical rings	13/04	• . . attached with a bridge member
9/06	• using separate springs {or elastic elements} expanding the rings; Springs therefor {; Expansion by wedging}	13/06	• . . attached only by clamps along the circumference
9/061	• . {using metallic coiled or blade springs (F16J 9/145 takes precedence)}	13/065	• . . {the clamp comprising a ring encircling the flange}
9/062	• . . {Coiled spring along the entire circumference}	13/08	• . . attached by one or more members actuated to project behind a part or parts of the frame (similar constructions for doors or windows E05C 9/00)
9/063	• . . {Strip or wire along the entire circumference}	13/10	• . . attached by means of a divided ring
9/064	• . {Rings with a flat annular side rail}	13/12	• . . attached by wedging action by means of screw-thread, interrupted screw-thread, bayonet closure, or the like
9/065	• . . {Spring expander with massive cross-section}	13/14	• . . attached exclusively by spring action or elastic action
9/066	• . . {Spring expander from sheet metal}	13/16	• Pivoted closures (F16J 13/22 takes precedence)
9/067	• . . . {corrugated in the radial direction}	13/18	• . . pivoted directly on the frame
9/068	• . . . {corrugated in the axial direction}	13/20	• . . mounted by mobile fastening on swinging arms
9/069	• . . . {with a "C"-shaped cross section along the entire circumference}	13/22	• with movement parallel to the plane of the opening
9/08	• with expansion obtained by pressure of the medium	13/24	• with safety devices, e.g. to prevent opening prior to pressure release
9/10	• Special members for adjusting the rings	15/00	Sealings
9/12	• Details	15/002	• {comprising at least two sealings in succession (F16J 15/162 , F16J 15/40 take precedence)}
9/14	• . Joint-closures	15/004	• . {forming of recuperation chamber for the leaking fluid}
9/145	• . . {of spring expanders}	15/006	• . {with division of the pressure (F16J 15/44 takes precedence)}
9/16	• . . obtained by stacking of rings	15/008	• . {with provision to put out of action at least one sealing; One sealing sealing only on standstill; Emergency or servicing sealings (F16J 15/164 takes precedence)}
9/18	• . . with separate bridge-elements	15/02	• between relatively-stationary surfaces (F16J 15/46 , F16J 15/48 take precedence)
9/20	• . Rings with special cross-section (L-section rings F16J 9/02); Oil-scraping rings { (F16J 9/06 takes precedence)}	15/021	• . . {with elastic packing (F16J 15/08 takes precedence)}
9/203	• . . {Oil-scraping rings}	15/022	• . . {characterised by structure or material}
	WARNING	15/024	• . . . {the packing being locally weakened in order to increase elasticity}
	The group F16J 9/203 is no longer used for the classification of new documents from August 1st, 2002. The backlog of this group is being continuously reclassified to F16J 9/206 , and to F16J 9/06 and sub-groups	15/025	• {and with at least one flexible lip}
9/206	• . . {One-piece oil-scraping rings}	15/027	• {and with a hollow profile}
9/22	• . Rings for preventing wear of grooves or like seatings	15/028	• . . {the packing being mechanically expanded against the sealing surface}
9/24	• . Members preventing rotation of rings in grooves	15/04	• . without packing between the surfaces, e.g. with ground surfaces, with cutting edge
9/26	• characterised by the use of particular materials	15/06	• . with solid packing compressed between sealing surfaces
9/28	• of non-metals	15/061	• . . {with positioning means (F16J 15/0831 takes precedence)}
10/00	Engine or like cylinders (pressure vessels in general F16J 12/00 ; cylinders for engines or other apparatus of particular kinds, see the appropriate subclasses, e.g. for combustion engines F02F); Features of hollow, e.g. cylindrical, bodies in general	15/062	• . . {characterised by the geometry of the seat}
10/02	• Cylinders designed to receive moving pistons or plungers	15/064	• . . {the packing combining the sealing function with other functions}
10/04	• . Running faces; Liners		
12/00	Pressure vessels in general (covers therefor F16J 13/00 ; for particular applications, see the relevant subclasses, e.g. B01J , F17C , G21C)		

15/065 {fire resistant}	15/183 {using a lantern ring}
15/067	. . . {Split packings}	15/184	. . . {Tightening mechanisms}
15/068	. . . {the packing swelling under working conditions}	15/185 {with continuous adjustment of the compression of the packing}
15/08	. . . with exclusively metal packing	15/186 {using springs}
15/0806 {characterised by material or surface treatment}	15/187	. . . {Self-aligning stuffing-boxes}
15/0812 {with a braided or knitted body}	15/188	. . . {Split assemblies}
15/0818 {Flat gaskets}	15/189	. . . {Means for facilitating the removal of the packing}
15/0825 {laminated}	15/20	. . . Packing materials therefor
15/0831 {with mounting aids}	15/22 shaped as strands, ropes, threads, ribbons, or the like
2015/0837 {with an edge portion folded over a second plate or shim}	15/24	. . . with radially or tangentially compressed packing
2015/0843 {with an edge portion folded over the plate itself}	15/26	. . with stuffing-boxes for rigid sealing rings
2015/085 {without fold over}	15/28	. . . with sealing rings made of metal
2015/0856 {with a non-metallic coating or strip}	15/30	. . . with sealing rings made of carbon
2015/0862 {with a bore ring}	15/32	. . with elastic sealings, e.g. O-rings
2015/0868 {Aspects not related to the edges of the gasket}	15/3204	. . . with at least one lip
2015/0875 {comprising welds}	15/3208 provided with tension elements, e.g. elastic rings
15/0881 {the sealing effect being obtained by plastic deformation of the packing}	15/3212 with metal springs
15/0887 {the sealing effect being obtained by elastic deformation of the packing}	15/3216 supported in a direction parallel to the surfaces
15/0893 {the packing having a hollow profile}	15/322 supported in a direction perpendicular to the surfaces
15/10	. . . with non-metallic packing	15/3224 capable of accommodating changes in distances or misalignment between the surfaces, e.g. able to compensate for defaults of eccentricity or angular deviations
15/102 {characterised by material}	15/3228 formed by deforming a flat ring
15/104 {characterised by structure}	15/3232 having two or more lips
15/106 {homogeneous}	15/3236 with at least one lip for each surface, e.g. U-cup packings
15/108 {Special methods for making a non-metallic packing}	15/324	. . . Arrangements for lubrication or cooling of the sealing itself
15/12 with metal reinforcement or covering	15/3244	. . . with hydrodynamic pumping action
15/121 {with metal reinforcement}	15/3248	. . . provided with casings or supports
15/122 {generally parallel to the surfaces}	15/3252 with rigid casings or supports
15/123 {Details relating to the edges of the packing}	15/3256 comprising two casing or support elements, one attached to each surface, e.g. cartridge or cassette seals
15/125 {generally perpendicular to the surfaces}	15/326 with means for detecting or measuring relative rotation of the two elements
15/126 {consisting of additions, e.g. metallic fibres, metallic powders, randomly dispersed in the packing}	15/3264 the elements being separable from each other
15/127 {the reinforcement being a compression stopper}	15/3268	. . . Mounting of sealing rings
15/128 {with metal covering}	15/3272 the rings having a break or opening, e.g. to enable mounting on a shaft otherwise than from a shaft end
15/14	. . by means of granular or plastic material, or fluid	15/3276 with additional static sealing between the sealing, or its casing or support, and the surface on which it is mounted
15/16	. between relatively-moving surfaces (F16J 15/50 , F16J 15/52 take precedence; bellows pistons F16J 3/06 ; piston-rings or ring sealings of similar construction F16J 9/00)	15/328	. . . Manufacturing methods specially adapted for elastic sealings (moulding B29C)
15/162	. . {Special parts or details relating to lubrication or cooling of the sealing itself (F16J 15/324 , F16J 15/3404 , F16J 15/40 take precedence)}	15/3284	. . . characterised by their structure; Selection of materials
15/164	. . {the sealing action depending on movements; pressure difference, temperature or presence of leaking fluid}	15/3288 Filamentary structures, e.g. brush seals
15/166	. . {with means to prevent the extrusion of the packing}	15/3292 Lamellar structures
15/168	. . {which permits material to be continuously conveyed}		
15/18	. . with stuffing-boxes for elastic or plastic packings		
15/181	. . . {for plastic packings}		
15/182	. . . {with lubricating, cooling or draining means}		

- 15/3296 . . . Arrangements for monitoring the condition or operation of elastic sealings ([F16J 15/326 takes precedence](#)); Arrangements for control of elastic sealings, e.g. of their geometry or stiffness
- 15/34 . . with slip-ring pressed against a more or less radial face on one member
- 15/3404 . . . {and characterised by parts or details relating to lubrication, cooling or venting of the seal}
- 15/3408 {at least one ring having an uneven slipping surface}
- 15/3412 {with cavities ([F16J 15/3424 takes precedence](#))}
- 15/3416 {with at least one continuous groove}
- 15/342 {with means for feeding fluid directly to the face}
- 15/3424 {with microcavities}
- 15/3428 {with a wavy surface}
- 15/3432 {the geometry of the surface being able to vary during operation}
- 15/3436 . . . {Pressing means}
- 15/344 {the pressing force being applied by means of an elastic ring supporting the slip-ring}
- 15/3444 {by magnetic attraction}
- 15/3448 {the pressing force resulting from fluid pressure}
- 15/3452 {the pressing force resulting from the action of a spring}
- 15/3456 {without external means for pressing the ring against the face, e.g. slip-ring with a resilient lip}
- 15/346 {the pressing force varying during operation}
- 15/3464 . . . {Mounting of the seal}
- 15/3468 {Means for controlling the deformations of the contacting faces}
- 15/3472 {Means for centering or aligning the contacting faces}
- 15/3476 {Means for minimising vibrations of the slip-ring}
- 15/348 {Pre-assembled seals, e.g. cartridge seals}
- 15/3484 {Tandem seals}
- 15/3488 {Split-rings}
- 15/3492 . . . {with monitoring or measuring means associated with the seal}
- 15/3496 . . . {use of special materials}
- 15/36 . . . connected by a diaphragm {or bellow} to the other member
- 15/363 {the diaphragm or bellow being made of metal}
- 15/366 {and comprising vibration-damping means}
- 15/38 . . . sealed by a packing
- 15/40 . . by means of fluid
- 15/403 . . . {by changing the state of matter}
- 15/406 . . . {by at least one pump}
- 15/42 . . . kept in sealing position by centrifugal force
- 15/43 . . . kept in sealing position by magnetic force
- 15/44 . Free-space packings
- 15/441 . . {with floating ring}
- 15/442 . . . {segmented}
- 15/443 . . {provided with discharge channels}
- 15/444 . . {with facing materials having honeycomb-like structure}
- 15/445 . . {with means for adjusting the clearance}
- 15/447 . . Labyrinth packings
- 15/4472 . . . {with axial path}
- 15/4474 {Pre-assembled packings}
- 15/4476 {with radial path}
- 15/4478 {Pre-assembled packings}
- 15/453 . . . characterised by the use of particular materials {([F16J 15/444 takes precedence](#))}
- 15/46 . with packing ring expanded or pressed into place by fluid pressure, e.g. inflatable packings ([connection of valves to inflatable elastic bodies B60C 29/00](#); {for sealing arrangements in vehicles [B60J 10/244](#); for sealing arrangements of openings in buildings [E06B 7/2318](#)}; for tube connections [F16L](#))
- 15/48 . . influenced by the pressure within the member to be sealed
- 15/50 . between relatively-movable members, by means of a sealing without relatively-moving surfaces, e.g. fluid-tight sealings for transmitting motion through a wall
- 15/52 . . by means of sealing bellows or diaphragms ([connection of valves to inflatable elastic bodies B60C 29/00](#))
- 15/525 . . . {fixed to a part of a transmission performing a wobbling or a circular translatory movement}
- 15/54 . Other sealings for rotating shafts
- 15/545 . . {submitted to unbalanced pressure in circumference; seals for oscillating actuator}
- 15/56 . Other sealings for reciprocating rods