

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F16 ENGINEERING ELEMENTS AND UNITS; GENERAL MEASURES FOR PRODUCING AND MAINTAINING EFFECTIVE FUNCTIONING OF MACHINES OR INSTALLATIONS; THERMAL INSULATION IN GENERAL

F16M FRAMES, CASINGS OR BEDS OF ENGINES, MACHINES OR APPARATUS, NOT SPECIFIC TO ENGINES, MACHINES OR APPARATUS PROVIDED FOR ELSEWHERE; STANDS; SUPPORTS

NOTE

Attention is drawn to the following places:

[B21B 31/02](#)

Metal-rolling stand frames

[G01D 11/30](#)

Supports specially adapted for indicating or recording instruments.

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Frames or casings of engines, machines or apparatus; Frames serving as machinery beds	11/00	Stands or trestles as supports for apparatus or articles placed thereon {; Stands for scientific apparatus such as gravitational force meters}
1/02	. for reciprocating engines or similar machines		(without heads F16M 13/00 ; easels or stands for blackboards or the like A47B 97/04 ; show-stands A47F 7/00 ; for workmen E04G 1/32 ; {sockets or holders for poles or posts E04H 12/22 ;} supporting or suspending for lighting devices F21V 21/00)
1/021	. . for housing crankshafts		
1/022	. . . of tunnel type, i.e. wherein the crankshaft can only be introduced axially (for engines or machines with star-shaped cylinder arrangement F16M 1/023)		
1/023	. . . specially adapted for engines or machines with star-shaped cylinder arrangement	11/02	. Heads
1/024	. . . facilitating assembly of power-transmitting parts of engines or machines, e.g. of connecting-rods	11/04	. . Means for attachment of apparatus; Means allowing adjustment of the apparatus relatively to the stand
1/025	. . . Assembling bearings in casings, e.g. having anchor bolts	11/041	. . . {Allowing quick release of the apparatus}
1/026	. . for housing movable engine or machine parts other than crankshafts, e.g. valve-gear housings	11/043	. . . {Allowing translations}
1/04	. for rotary engines or similar machines	11/045 {adapted to left-right translation movement}
1/08	. characterised by being built-up of sheet material or welded parts	11/046 {adapted to upward-downward translation movement}
3/00	Portable or wheeled frames or beds, e.g. for emergency power-supply aggregates, compressor sets (construction of vehicles in general B60 - B62)	11/048 {adapted to forward-backward translation movement}
5/00	Engine beds, i.e. means for supporting engines or machines on foundations	11/06	. . . allowing pivoting
7/00	Details of attaching or adjusting engine beds, frames, or supporting-legs on foundation or base; Attaching non-moving engine parts, e.g. cylinder blocks (elastic or equivalent mounting for absorbing vibrations F16F, especially F16F 15/04)	11/08 around a vertical axis {, e.g. panoramic heads (F16M 11/12 takes precedence)}
9/00	Special layout of foundations with respect to machinery to be supported (foundations for machinery E02D 27/44)	11/10 around a horizontal axis {(F16M 11/12 takes precedence)}
		11/105 {the horizontal axis being the roll axis, e.g. for creating a landscape-portrait rotation}
		11/12 in more than one direction
		11/121 {constituted of several dependent joints}
		11/123 {the axis of rotation intersecting in a single point, e.g. by using gimbals}
		11/125 {for tilting and rolling (F16M 11/14 takes precedence)}
		11/126 {for tilting and panning (F16M 11/14 takes precedence)}

11/128 {for panning and rolling (F16M 11/14 takes precedence)}	11/38	. . . by folding {, e.g. pivoting or scissors tong mechanisms}
11/14 with ball-joint (ball-jointed hinges F16C 11/06 {; adjustable mountings employing universal joints for lighting devices F21V 21/26 - F21V 21/30 })	11/40	. . . by means of coilable or bendable legs {or spiral shaped legs}
11/16	. . Details concerning attachment of head-supporting legs, with or without actuation of locking members thereof	11/42	. with arrangement for propelling the support {stands on wheels}
11/18	. . with mechanism for moving the apparatus relatively to the stand	11/425	. . {along guiding means}
11/20	. Undercarriages with or without wheels	13/00	Other supports for positioning apparatus or articles (heads thereof F16M 11/02 {; undercarriages thereof F16M 11/20 {; adapted to be stuck in the ground A45F 3/44 {; sockets or holders for poles or posts E04H 12/22 }); Means for steadying hand-held apparatus or articles {(supports for measuring instruments G01D 11/30 ; supports for casings of remote control switching devices H01H 9/025)}
11/2007	. . {comprising means allowing pivoting adjustment}	13/005	. {integral with the apparatus or articles to be supported}
11/2014	. . . {around a vertical axis (F16M 11/2035 takes precedence)}	13/02	. for supporting on, or attaching to, an object, e.g. tree, gate, window-frame, cycle
11/2021	. . . {around a horizontal axis (F16M 11/2035 takes precedence)}	13/022	. . {repositionable}
11/2028 {for rolling, i.e. for creating a landscape-portrait rotation}	13/025	. . {Corner supports}
11/2035	. . . {in more than one direction}	13/027	. . {Ceiling supports}
11/2042 {constituted of several dependent joints}	13/04	. for supporting on, or holding steady relative to, a person, e.g. by chains {, e.g. rifle butt or pistol grip supports, supports attached to the chest or head (apparatus or arrangements for taking photographs or for projecting or viewing them G03B)}
11/205 {the axis of rotation intersecting in a single point, e.g. gimbals}	13/06	. also serviceable for other purposes, e.g. to be used as spade, chair, ski-stick
11/2057 {for tilting and rolling (F16M 11/2078 takes precedence)}	13/08	. . for use as a walking-cane
11/2064 {for tilting and panning (F16M 11/2078 takes precedence)}	2200/00	Details of stands or supports
11/2071 {for panning and rolling (F16M 11/2078 takes precedence)}	2200/02	. Locking means
11/2078 {with ball-joint (ball-jointed hinges F16C 11/06)}	2200/021	. . for rotational movement
11/2085	. . {comprising means allowing sideward adjustment, i.e. left-right translation of the head relatively to the undercarriage}	2200/022	. . . by friction
11/2092	. . {comprising means allowing depth adjustment, i.e. forward-backward translation of the head relatively to the undercarriage}	2200/024	. . . by positive interaction, e.g. male-female connections
11/22	. . with approximately constant height, e.g. with constant length of column or of legs (F16M 11/42 takes precedence)	2200/025	. . for translational movement
11/24	. . changeable in height or length of legs, also for transport only, {e.g. by means of tubes screwed into each other} (F16M 11/42 takes precedence)	2200/027	. . . by friction
11/242	. . . {by spreading of the legs (F16M 11/32 takes precedence)}	2200/028	. . . by positive interaction, e.g. male-female connections
11/245 {Members limiting spreading of legs, e.g. "umbrella legs" (for supports with three or more telescoping legs F16M 11/34)}	2200/04	. Balancing means
11/247 {Members preventing slipping of the feet (for supports with three or more telescoping legs F16M 11/36)}	2200/041	. . for balancing rotational movement of the head
11/26	. . . by telescoping, with or without folding (details concerning the constructional features of telescoping parts only F16B 7/10)	2200/042	. . . for panning movement
11/28 Undercarriages for supports with one single telescoping pillar	2200/044	. . for balancing rotational movement of the undercarriage
11/30 with co-moving side-struts	2200/045	. . . for panning movement
11/32 Undercarriages for supports with three or more telescoping legs	2200/047	. . for balancing translational movement of the head
11/34 Members limiting spreading of legs {, e.g. "umbrella legs"}	2200/048	. . for balancing translational movement of the undercarriage
11/36 Members preventing slipping of the feet	2200/06	. Arms
		2200/061	. . Scissors arms
		2200/063	. . Parallelogram arms
		2200/065	. . with a special structure, e.g. reinforced or adapted for space reduction
		2200/066	. . being part of the head
		2200/068	. . being part of the undercarriage
		2200/08	. Foot or support base