

# CPC COOPERATIVE PATENT CLASSIFICATION

## F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

### ENGINEERING IN GENERAL

#### F16 ENGINEERING ELEMENTS AND UNITS; GENERAL MEASURES FOR PRODUCING AND MAINTAINING EFFECTIVE FUNCTIONING OF MACHINES OR INSTALLATIONS; THERMAL INSULATION IN GENERAL

#### F16K VALVES; TAPS; COCKS; ACTUATING-FLOATS; DEVICES FOR VENTING OR AERATING {(devices for emptying and evacuating the excess liquid in valves or conduits [F16L 55/07](#))}

##### NOTE

Attention is drawn to the following places:

<a href="#">A47J 27/09</a>	Safety devices for pressure cookers
<a href="#">A47J 31/46</a>	Dispensing spouts, drain valves or like beverage-making apparatus
<a href="#">A61B 5/0235</a>	Valves specially adapted for measuring pressure in heart or blood vessels
<a href="#">A61F 2/24</a>	Heart valves
<a href="#">A61M 16/20</a>	Valves specially adapted for medical respiratory devices
<a href="#">A61M 39/00</a>	Tube connectors, tube couplings, valves or branch units specially adapted for medical use in general
<a href="#">A62B 9/02</a>	Valves for respiratory apparatus
<a href="#">A62B 18/10</a>	Valves for breathing masks or helmets
<a href="#">A62C</a>	Fire extinguishers
<a href="#">{B01D 35/04}</a>	<a href="#">{Plug, tap, or cock filters}</a>
<a href="#">B05B</a>	Nozzles, spray heads or other discharge apparatus for spraying or atomising
<a href="#">B60C 29/00</a>	Arrangements of tyre-inflating valves relative to tyres or wheel rims; Connection of valves to wheel rims, tyres or other inflatable elastic bodies
<a href="#">B60G 17/048</a>	Valves specially adapted for adjusting vehicle fluid-spring characteristics
<a href="#">B60T</a>	Valves specially adapted for vehicle brake control systems
<a href="#">B62D 5/08</a>	Vehicle power-assisted steering characterised by the type of valve used
<a href="#">B63B 7/00, B63C 9/00</a>	Arrangement of inflating valves for floatable life-saving equipment
<a href="#">B65D 47/04</a>	Container closures with discharging valves
<a href="#">B65D 90/32</a>	Safety valves for large containers
<a href="#">B65D 90/54</a>	Gates or closures on large containers
<a href="#">B67C 3/28</a>	Flow control devices for bottling liquids
<a href="#">B67D</a>	Dispensing, delivering or transferring liquids
<a href="#">{C21B 9/12}</a>	<a href="#">{Hot-blast valves for blast furnaces}</a>
<a href="#">E02B 8/00</a>	Details, e.g. valves, of barrages or weirs
<a href="#">E02B 13/02</a>	Closures for irrigation conduits
<a href="#">{E03C 1/04}</a>	<a href="#">{Water-basin installations specially adapted for wash-basins or baths}</a>
<a href="#">{E03C 1/05}</a>	<a href="#">{Arrangements on wash-basins for the remote control of taps}</a>
<a href="#">E03D</a>	Flushing valves for water-closets or urinals
<a href="#">{E03F 7/04}</a>	<a href="#">{Valves for preventing return flow in sewer systems}</a>
<a href="#">E05F 3/12</a>	Valve arrangements in door closers
<a href="#">E21B 21/10</a>	Valve arrangements in drilling-fluid circulation systems
<a href="#">E21B 34/00</a>	Valve arrangements for boreholes or wells
<a href="#">{E21D 15/51}</a>	<a href="#">{Arrangement of relief valves in hydraulic mine props}</a>
<a href="#">F01B 25/10</a>	Working-fluid valves for controlling machines or engines in general or of positive-displacement type
<a href="#">F01D 17/10</a>	Final actuators for controlling non-positive displacement machines or engines
<a href="#">F01L</a>	Cyclically operated valves for machines or engines
<a href="#">F02D 9/08</a>	Throttle valves for controlling combustion engines
<a href="#">F02K 9/58</a>	Propellant feed valves for rocket-engines
<a href="#">F02M</a>	Carburettors, fuel injection
<a href="#">F02M 59/46</a>	Valves for fuel injection pumps
<a href="#">F04</a>	Pumps
<a href="#">F16F 9/34</a>	Valves for shock absorbers
<a href="#">F16L 29/00, F16L 37/28</a>	Pipe joints or quick-acting couplings with fluid cut-off means
<a href="#">F16L 55/00</a>	Arrangement of valves in pipes

## F16K

(continued)

<a href="#">F16L 55/055</a>	Valves specially adapted to prevent or minimise the effect of water hammer
<a href="#">F16L 55/46</a>	Launching devices for pigs or moles
<a href="#">F16N 23/00</a>	Check valves for lubrication systems
<a href="#">{F16T}</a>	<a href="#">{Draining-off liquids from steam traps}</a>
<a href="#">F17C 13/04</a>	Arrangement of valves in pressure vessels
<a href="#">F22B 37/44</a>	Arrangement of safety valves on steam boilers
<a href="#">F22D 5/34</a>	Application of valves to automatic water-feed in boiler
<a href="#">F23L 13/00</a>	Valves for air supply control to burners
<a href="#">{F23Q 2/16}</a>	<a href="#">{Valves for lighters with gaseous fuel and adjustable flame}</a>
<a href="#">F24C 3/12</a> , <a href="#">F24C 5/16</a>	Arrangement of valves on stoves or ranges
<a href="#">F24F</a>	Air conditioning; Ventilation
<a href="#">F25B 41/20</a>	Disposition of fluid circulation valves in refrigeration machines
<a href="#">G05D</a>	Controlling non-electric variables
<a href="#">G10B 3/06</a>	Valves for organs
<a href="#">G10D 9/04</a>	Valves for other wind-actuated musical instruments
<a href="#">{G21C 9/06}</a>	<a href="#">{Safety valves structurally associated with nuclear reactors}</a>
<a href="#">{H01M 50/30}</a>	<a href="#">{Vent plugs in batteries or cells}</a>

**WARNINGS**

- The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

<a href="#">F16K 31/11</a>	covered by	<a href="#">F16K 31/06</a> , <a href="#">F16K 31/08</a> , <a href="#">F16K 31/10</a>
<a href="#">F16K 31/64</a>	covered by	<a href="#">F16K 31/002</a> , <a href="#">G05D 23/00</a>
<a href="#">F16K 31/66</a>	covered by	<a href="#">F16K 31/06</a> , <a href="#">G05D 23/00</a>
<a href="#">F16K 31/68</a>	covered by	<a href="#">F16K 31/001</a> , <a href="#">G05D 23/00</a>
<a href="#">F16K 31/70</a>	covered by	<a href="#">F16K 31/002</a> , <a href="#">G05D 23/08</a>
<a href="#">F16K 31/72</a>	covered by	<a href="#">F16K 31/00</a>

- In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

**Constructional types** (check valves [F16K 15/00](#))**NOTE**

In groups [F16K 1/00](#) - [F16K 13/00](#), an initial seal breaking or final sealing movement which is different from the opening or closing movement of the valve is not considered in determining the movement to be classified.

<b>1/00</b>	<b>Lift valves {or globe valves}, i.e. cut-off apparatus with closure members having at least a component of their opening and closing motion perpendicular to the closing faces ({in combination with sliding valves <a href="#">F16K 3/246</a>, <a href="#">F16K 3/267</a>} ; diaphragm valves <a href="#">F16K 7/00</a>)</b>	1/18	. . . with pivoted discs or flaps
1/02	. with screw-spindle ( <a href="#">F16K 1/12</a> - <a href="#">F16K 1/28</a> take precedence; actuating mechanisms with screw-spindles <a href="#">F16K 31/50</a> )	1/20	. . . with axis of rotation arranged externally of valve member
1/04	. . with a cut-off member rigid with the spindle, e.g. main valves	1/2007	. . . . {specially adapted operating means therefor ( <a href="#">operating means per se F16K 31/00</a> )}
1/06	. . Special arrangements for improving the flow, e.g. special shape of passages or casings	1/2014	. . . . {Shaping of the valve member}
1/08	. . . in which the spindle is perpendicular to the general direction of flow	1/2021	. . . . {with a plurality of valve members}
1/10	. . . in which the spindle is inclined to the general direction of flow	1/2028	. . . . {Details of bearings for the axis of rotation}
1/12	. with streamlined valve member around which the fluid flows when the valve is opened	1/2035	. . . . . {the axis of rotation having only one bearing}
1/123	. . {with stationary valve member and moving sleeve}	1/2042	. . . . . {Special features or arrangements of the sealing}
1/126	. . {actuated by fluid}	1/205	. . . . . {the sealing being arranged on the valve member}
1/14	. with ball-shaped valve member (check valves <a href="#">F16K 15/04</a> )	1/2057	. . . . . {the sealing being arranged on the valve seat}
1/16	. with pivoted closure-members	1/2064	. . . . . {with a channel- or U-shaped seal covering a central body portion}
1/165	. . {with a plurality of closure members}	1/2071	. . . . . {and being forced into sealing contact with the valve member by a spring or a spring-like member}
		1/2078	. . . . . {Sealing means for the axis of rotation}
		1/2085	. . . . . {Movable sealing bodies}
		1/2092	. . . . . {the movement being caused by the flowing medium}
		1/22	. . . with axis of rotation crossing the valve member, e.g. butterfly valves
		1/221	. . . . {specially adapted operating means therefor ( <a href="#">operating means per se F16K 31/00</a> )}
		1/222	. . . . {Shaping of the valve member}
		1/223	. . . . {with a plurality of valve members}
		1/224	. . . . {Details of bearings for the axis of rotation}

1/225	. . . . . {the axis of rotation having only one bearing}	1/465	. . . . . {to the valve seats}
1/226	. . . . . Shaping or arrangements of the sealing	1/48	. . . Attaching valve members to screw-spindles
1/2261	. . . . . {the sealing being arranged on the valve member}	1/482	. . . {with a collar on the spindle or a groove in the spindle, by which a fixing element is supported, the spindle reaching into the valve member}
1/2263	. . . . . {the sealing being arranged on the valve seat}	1/485	. . . . . {with a groove in the spindle}
1/2265	. . . . . {with a channel- or U-shaped seal covering a central body portion}	1/487	. . . {by a fixing element extending in the axial direction of the spindle, e.g. a screw}
1/2266	. . . . . {and being forced into sealing contact with the valve member by a spring or a spring-like member}	1/50	. . . Preventing rotation of valve members
1/2268	. . . . . {Sealing means for the axis of rotation}	1/52	. . . Means for additional adjustment of the rate of flow
1/228	. . . . . Movable sealing bodies	1/523	. . . {for limiting the maximum flow rate, using a stop}
1/2285	. . . . . {the movement being caused by the flowing medium}	1/526	. . . {for limiting the maximum flow rate, using a second valve}
1/24	. . . with valve members that, on opening of the valve, are initially lifted from the seat and next are turned around an axis parallel to the seat	1/54	. . . Arrangements for modifying the way in which the rate of flow varies during the actuation of the valve
1/26	. . . Shape or arrangement of the sealing {Not used}	<b>3/00</b>	<b>Gate valves or sliding valves, i.e. cut-off apparatus with closing members having a sliding movement along the seat for opening and closing (<a href="#">F16K 5/00</a> takes precedence; in barrages or weirs <a href="#">E02B 8/04</a>)</b>
1/28	. . . Movable sealing bodies {Not used}	3/02	. . . with flat sealing faces; Packings therefor
1/30	. . . specially adapted for pressure containers	3/0209	. . . {the valve having a particular passage, e.g. provided with a filter, throttle or safety device}
1/301	. . . {only shut-off valves, i.e. valves without additional means}	3/0218	. . . {with only one sealing face}
1/302	. . . {with valve member and actuator on the same side of the seat}	3/0227	. . . {Packings}
1/303	. . . {with a valve member, e.g. stem or shaft, passing through the seat}	3/0236	. . . {the packing being of a non-resilient material, e.g. ceramic, metal}
1/304	. . . {Shut-off valves with additional means}	3/0245	. . . {Curtain gate valves}
1/305	. . . {with valve member and actuator on the same side of the seat}	3/0254	. . . {being operated by particular means}
1/306	. . . {with a valve member, e.g. stem or shaft, passing through the seat}	3/0263	. . . {using particular material or covering means}
1/307	. . . {Additional means used in combination with the main valve}	3/0272	. . . {permitting easy assembly or disassembly}
1/308	. . . {Connecting means}	3/0281	. . . {Guillotine or blade-type valves, e.g. no passage through the valve member}
1/32	. . . Details ( <a href="#">details of more general applicability F16K 25/00 - F16K 51/00</a> )	3/029	. . . {with two or more gates}
1/34	. . . Cutting-off parts, e.g. valve members, seats ( <a href="#">F16K 1/06</a> , <a href="#">F16K 1/12</a> , <a href="#">F16K 1/14</a> , <a href="#">F16K 1/26</a> take precedence)	3/03	. . . with a closure member in the form of an iris-diaphragm
1/36	. . . Valve members ( <a href="#">for double-seat valves F16K 1/44</a> ; <a href="#">for butterfly valves F16K 1/222</a> , <a href="#">F16K 1/223</a> )	3/04	. . . with pivoted closure members
1/38	. . . . . of conical shape	3/06	. . . in the form of closure plates arranged between supply and discharge passages ( <a href="#">F16K 3/10</a> takes precedence)
1/385	. . . . . {contacting in the closed position, over a substantial axial length, a seat surface having the same inclination}	3/08	. . . . . with circular plates rotatable around their centres
1/40	. . . . . of helical shape	3/085	. . . . . {the axis of supply passage and the axis of discharge passage being coaxial and parallel to the axis of rotation of the plates}
1/42	. . . Valve seats ( <a href="#">for double-seat valves F16K 1/44</a> )	3/10	. . . with special arrangements for separating the sealing faces or for pressing them together
1/422	. . . . . {attachable by a threaded connection to the housing}	3/12	. . . with wedge-shaped arrangements of sealing faces
1/425	. . . . . {Attachment of the seat to the housing by plastical deformation, e.g. valve seat or housing being plastically deformed during mounting}	3/14	. . . with special arrangements for separating the sealing faces or for pressing them together
1/427	. . . . . {Attachment of the seat to the housing by one or more additional fixing elements}	3/16	. . . with special arrangements for separating the sealing faces or for pressing them together ( <a href="#">F16K 3/10</a> , <a href="#">F16K 3/14</a> take precedence)
1/44	. . . Details of seats or valve members of double-seat valves	3/18	. . . by movement of the closure members
1/443	. . . . . {the seats being in series}	3/182	. . . . . {by means of toggle links}
1/446	. . . . . {with additional cleaning or venting means between the two seats}	3/184	. . . . . {by means of cams}
1/46	. . . Attachment of sealing rings	3/186	. . . . . {by means of cams of wedge form}
		3/188	. . . . . {by means of hydraulic forces}
		3/20	. . . by movement of the seats
		3/202	. . . . . {by movement of toggle links}

- 3/205 . . . . {by means of cams}
- 3/207 . . . . {by means of hydraulic forces}
- 3/22 . with sealing faces shaped as surfaces of solids of revolution ([F16K 13/02 takes precedence](#); with resilient valve members [F16K 3/28](#))
- 3/24 . . with cylindrical valve members
- 3/243 . . . {Packings ([F16K 3/246 takes precedence](#))}
- 3/246 . . . {Combination of a sliding valve and a lift valve}
- 3/26 . . . with fluid passages in the valve member
- 3/262 . . . . {with a transverse bore in the valve member}
- 3/265 . . . . {with a sleeve sliding in the direction of the flow line}
- 3/267 . . . . {Combination of a sliding valve and a lift valve ([F16K 3/262](#), [F16K 3/265 take precedence](#))}
- 3/28 . with resilient valve members
- 3/30 . Details
- 3/312 . . Line blinds
- 3/314 . . Forms or constructions of slides; Attachment of the slide to the spindle
- 3/316 . . Guiding of the slide
- 3/3165 . . . {with rollers or balls}
- 3/32 . . Means for additional adjustment of the rate of flow
- 3/34 . . Arrangements for modifying the way in which the rate of flow varies during the actuation of the valve
- 3/36 . . Features relating to lubrication
- 5/00 {Plug valves;} Taps or cocks comprising only cut-off apparatus having at least one of the sealing faces shaped as a more or less complete surface of a solid of revolution, the opening and closing movement being predominantly rotary (taps of the lift-valve type [F16K 1/00](#))**
- 5/02 . with plugs having conical surfaces; Packings therefor
- 5/0207 . . {with special plug arrangement, e.g. special shape or built in means}
- 5/0214 . . {Plug channel at 90 degrees to the inlet}
- 5/0221 . . {Fixed plug and turning sleeve}
- 5/0228 . . {with a conical segment mounted around a supply pipe}
- 5/0235 . . {with the angle the spindle makes housing being other than 90 degrees}
- 5/0242 . . {Spindles and actuating means}
- 5/025 . . {Particular coverings or materials}
- 5/0257 . . {Packings}
- 5/0264 . . . {in the housing}
- 5/0271 . . . {between housing and plug}
- 5/0278 . . . {on the plug}
- 5/0285 . . . {spindle sealing}
- 5/0292 . . {Easy mounting or dismounting means}
- 5/04 . with plugs having cylindrical surfaces; Packings therefor
- 5/0407 . . {with particular plug arrangements, e.g. particular shape or built-in means}
- 5/0414 . . {Plug channel at 90 degrees to the inlet}
- 5/0421 . . {Fixed plug and turning sleeve}
- 5/0428 . . {with a cylindrical segment mounted around a supply pipe}
- 5/0435 . . {the angle the spindle makes with the housing being other than 90 degrees}
- 5/0442 . . {Spindles and actuating means}
- 5/045 . . {Particular coverings and materials}
- 5/0457 . . {Packings}
- 5/0464 . . . {in the housing}
- 5/0471 . . . {between housing and plug}
- 5/0478 . . . {on the plug}
- 5/0485 . . . {Spindle sealing}
- 5/0492 . . {Easy mounting or dismounting means}
- 5/06 . with plugs having spherical surfaces; Packings therefor
- 5/0605 . . {with particular plug arrangements, e.g. particular shape or built-in means}
- 5/061 . . {knee-joint}
- 5/0615 . . {the angle the spindle makes with the housing being other than 90 degrees}
- 5/0621 . . {with a spherical segment mounted around a supply pipe}
- 5/0626 . . {Easy mounting or dismounting means}
- 5/0631 . . . {between two flanges}
- 5/0636 . . . {the spherical plug being insertable from the top of the housing}
- 5/0642 . . . {the spherical plug being insertable from one and only one side of the housing}
- 5/0647 . . {Spindles or actuating means}
- 5/0652 . . . {for remote operation}
- 5/0657 . . {Particular coverings or materials}
- 5/0663 . . {Packings}
- 5/0668 . . . {Single packings}
- 5/0673 . . . {Composite packings}
- 5/0678 . . . . {in which only one of the components of the composite packing is contacting the plug}
- 5/0684 . . . {on the plug}
- 5/0689 . . . {between housing and plug}
- 5/0694 . . . {Spindle sealings}
- 5/08 . Details
- 5/10 . . Means for additional adjustment of the rate of flow
- 5/103 . . . {specially adapted for gas valves}
- 5/106 . . . . {with pilot flame}
- 5/12 . . Arrangements for modifying the way in which the rate of flow varies during the actuation of the valve
- 5/14 . . Special arrangements for separating the sealing faces or for pressing them together
- 5/16 . . . for plugs with conical surfaces
- 5/161 . . . . {with the housing or parts of the housing mechanically pressing the seal against the plug}
- 5/162 . . . . {with the plugs or parts of the plugs mechanically pressing the seal against the housing}
- 5/163 . . . . . {adjustable in height}
- 5/165 . . . . . {Means pressing on the small diameter}
- 5/166 . . . . . {Means pressing on the large diameter}
- 5/167 . . . . . {Means pressing radially}
- 5/168 . . . . {Sealing effected by the flowing medium}
- 5/18 . . . for plugs with cylindrical surfaces
- 5/181 . . . . {with the housing or parts of the housing mechanically pressing the seals against the plugs}
- 5/182 . . . . . {by means of conical surfaces}

5/184	. . . . {with the plugs or parts of the plugs mechanically pressing the seals against the housing}	11/04	. . comprising only lift valves
5/185	. . . . . {by means of conical surfaces}	11/044	. . . with movable valve members positioned between valve seats
5/187	. . . . . {with rolling action}	11/0445	. . . . {Bath/shower selectors}
5/188	. . . . . {Sealing effected by the flowing medium}	11/048	. . . with valve seats positioned between movable valve members
5/20	. . . for plugs with spherical surfaces	11/052	. . . with pivoted closure members, e.g. butterfly valves
5/201	. . . . {with the housing or parts of the housing mechanically pressing the seal against the plug}	11/0525	. . . . {the closure members being pivoted around an essentially central axis}
5/202	. . . . . {with conical surfaces}	11/056	. . . with ball-shaped valve members
5/204	. . . . {with the plugs or parts of the plugs mechanically pressing the seals against the housing}	11/0565	. . . . {moving in a combined straight line and rotating movement}
5/205	. . . . . {Sealing effected by the flowing medium}	11/06	. . comprising only sliding valves {, i.e. sliding closure elements}
5/207	. . . . . {using bellows}	11/065	. . . with linearly sliding closure members
5/208	. . . . . {with tongue-shaped means}	11/0655	. . . . {with flat slides}
5/22	. . Features relating to lubrication	11/07	. . . . with cylindrical slides
5/222	. . . {for plugs with conical surfaces}	11/0704	. . . . . {comprising locking elements}
5/225	. . . {for plugs with cylindrical surfaces}	11/0708	. . . . . {comprising means to avoid jamming of the slide or means to modify the flow}
5/227	. . . {for plugs with spherical surfaces}	11/0712	. . . . . {comprising particular spool-valve sealing means}
<b>7/00</b>	<b>Diaphragm {valves or} cut-off apparatus, e.g. with a member deformed, but not moved bodily, to close the passage (container gates or closures operating by deformation of flexible walls <a href="#">B65D 90/56</a>; means for plugging pipes or hoses <a href="#">F16L 55/10</a>); Pinch valves}</b>	11/0716	. . . . . {with fluid passages through the valve member ( <a href="#">F16K 11/0704</a> , <a href="#">F16K 11/0708</a> , <a href="#">F16K 11/0712</a> take precedence)}
7/02	. with tubular diaphragm	11/072	. . . with pivoted closure members
7/04	. . constrictable by external radial force	11/074	. . . . with flat sealing faces
7/045	. . . {by electric or magnetic means}	11/0743	. . . . . {with both the supply and the discharge passages being on one side of the closure plates}
7/06	. . . by means of a screw-spindle, cam, or other mechanical means {( <a href="#">F16K 7/045</a> takes precedence)}	11/0746	. . . . . {with two or more closure plates comprising a single lever control}
7/061	. . . . . {Screw clamps}	11/076	. . . . with sealing faces shaped as surfaces of solids of revolution
7/063	. . . . . {Lever clamps}	11/078	. . . with pivoted and linearly movable closure members
7/065	. . . . . {Cam clamps}	11/0782	. . . . {Single-lever operated mixing valves with closure members having flat sealing faces}
7/066	. . . . . {Wedge clamps}	11/0785	. . . . . {the movable closure member being pivotally supported at one point and being linked to the operating lever at only one other point}
7/068	. . . . {by bending the hose}	11/0787	. . . . . {with both the supply and the discharge passages being on the same side of the closure members ( <a href="#">F16K 11/0785</a> takes precedence)}
7/07	. . . by means of fluid pressure	11/08	. . comprising only taps or cocks
7/075	. . . . {a rigid body being located within the tubular diaphragm}	11/083	. . . with tapered plug
7/08	. . constrictable by twisting	11/0833	. . . . {having all the connecting conduits situated in a single plane perpendicular to the axis of the plug}
7/10	. with inflatable member	11/0836	. . . . {having all the connecting conduits situated in more than one plane perpendicular to the axis of the plug}
7/12	. with flat, dished, or bowl-shaped diaphragm	11/085	. . . with cylindrical plug
7/123	. . {the seat being formed on the bottom of the fluid line}	11/0853	. . . . {having all the connecting conduits situated in a single plane perpendicular to the axis of the plug}
7/126	. . {the seat being formed on a rib perpendicular to the fluid line}	11/0856	. . . . {having all the connecting conduits situated in more than one plane perpendicular to the axis of the plug}
7/14	. . arranged to be deformed against a flat seat	11/087	. . . with spherical plug
7/16	. . . the diaphragm being mechanically actuated, e.g. by screw-spindle or cam		
7/17	. . . the diaphragm being actuated by fluid pressure		
7/18	. with diaphragm secured at one side only, e.g. to be laid on the seat by rolling action		
7/20	. with a compressible solid closure member		
<b>11/00</b>	<b>Multiple-way valves, e.g. mixing valves; Pipe fittings incorporating such valves</b>		
11/02	. with all movable sealing faces moving as one unit		
11/022	. . {comprising a deformable member}		
11/025	. . . {with an O-ring}		
11/027	. . . {the fluid flowing through a constrictable tubular diaphragm}		



- 11/0873 . . . . {the plug being only rotatable around one spindle}
- 11/0876 . . . . {one connecting conduit having the same axis as the spindle}
- 11/10 . with two or more closure members not moving as a unit
- 11/105 . . {Three-way check or safety valves with two or more closure members}
- 11/12 . . with one plug turning in another
- 11/14 . . operated by one actuating member, e.g. a handle (with one plug turning in another [F16K 11/12](#))
- 11/16 . . . which only slides, or only turns, or only swings in one plane
- 11/161 . . . . {only slides}
- 11/163 . . . . {only turns}
- 11/165 . . . . {with the rotating spindles parallel to the closure members}
- 11/166 . . . . {with the rotating spindles at right angles to the closure members}
- 11/168 . . . . {only swings}
- 11/18 . . . with separate operating movements for separate closure members
- 11/185 . . . . {with swinging shafts}
- 11/20 . . operated by separate actuating members (with one plug turning in another [F16K 11/12](#))
- 11/202 . . . {with concentric handles}
- 11/205 . . . {with two handles at right angles to each other}
- 11/207 . . . {with two handles or actuating mechanisms at opposite sides of the housing}
- 11/22 . . . with an actuating member for each valve, e.g. interconnected to form multiple-way valves
- 11/24 . . . with an electromagnetically-operated valve, e.g. for washing machines
- 13/00 Other constructional types of cut-off apparatus (means for plugging pipes or hoses [F16L 55/10](#)); Arrangements for cutting-off**
- 13/02 . with both sealing faces shaped as small segments of a cylinder and the moving member pivotally mounted
- 13/04 . {with a breakable closure member}
- 13/06 . . {constructed to be ruptured by an explosion}
- 13/08 . Arrangements for cutting-off {not used}
- 13/10 . . by means of liquid or granular medium

### Functional types

#### NOTE

Attention is drawn to Note (2) following the title of subclass [G05D](#) and also the subdivisions of that subclass, according to which pressure regulators and flow regulators, e.g. flow regulating valves with pressure compensator, even with the whole regulating system contained in a valve, operating with or without auxiliary power, are covered by groups [G05D 16/00](#) or [G05D 7/00](#), respectively.

However, details of the valve parts, *per se*, are classified in the appropriate groups of this subclass.

#### **15/00 Check valves (valves specially adapted for inflatable balls [A63B 41/00](#))**

##### **WARNING**

Groups [F16K 15/00](#), [F16K 15/20](#), [F16K 15/202](#) and [F16K 15/205](#) are incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/02 . with guided rigid valve members

##### **WARNING**

Groups [F16K 15/02](#), [F16K 15/021](#), [F16K 15/023](#), [F16K 15/04](#) and [F16K 15/048](#) are incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/021 . . {the valve member being a movable body around which the medium flows when the valve is open ([F16K 15/025](#) - [F16K 15/12](#) take precedence)}
- 15/023 . . . {the valve member consisting only of a predominantly disc-shaped flat element}
- 15/025 . . {the valve being loaded by a spring ([F16K 15/03](#) - [F16K 15/12](#) take precedence)}

##### **WARNING**

Group [F16K 15/025](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/026 . . . {the valve member being a movable body around which the medium flows when the valve is open}

##### **WARNING**

Groups [F16K 15/026](#) and [F16K 15/028](#) are incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/028 . . . . {the valve member consisting only of a predominantly disc-shaped flat element}
- 15/03 . . with a hinged closure member {or with a pivoted closure member}

##### **WARNING**

Group [F16K 15/03](#) is impacted by reclassification into groups [F16K 15/031](#) - [F16K 15/207](#) and [F16K 17/00](#) - [F16K 17/42](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/031 . . . {the hinge being flexible}

**WARNING**

Group [F16K 15/031](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/035](#), [F16K 15/036](#) and [F16K 15/038](#).

Group [F16K 15/031](#) is also impacted by reclassification into group [F16K 15/034](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/033 . . . {spring-loaded}

**WARNING**

Group [F16K 15/033](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/035](#), [F16K 15/036](#) and [F16K 15/038](#).

Group [F16K 15/033](#) is also impacted by reclassification into group [F16K 15/034](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/034 . . . {weight-loaded}

**WARNING**

Group [F16K 15/034](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/031](#), [F16K 15/033](#), [F16K 15/035](#), [F16K 15/036](#) and [F16K 15/038](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/035 . . . {with a plurality of valve members}

**WARNING**

Group [F16K 15/035](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/035](#) is also impacted by reclassification into groups [F16K 15/031](#), [F16K 15/033](#) and [F16K 15/034](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/036 . . . . {Dual valve members with hinges crossing the flow line substantially diametrical}

**WARNING**

Group [F16K 15/036](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/036](#) is also impacted by reclassification into groups [F16K 15/031](#), [F16K 15/033](#) and [F16K 15/034](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/038 . . . . . {having a common hinge}

**WARNING**

Group [F16K 15/038](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/038](#) is also impacted by reclassification into groups [F16K 15/031](#), [F16K 15/033](#) and [F16K 15/034](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/04 . . shaped as balls

15/042 . . . {with a plurality of balls}

**WARNING**

Group [F16K 15/042](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/042](#) is also impacted by reclassification into groups [F16K 15/044](#) and [F16K 15/046](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/044 . . . {spring-loaded}

**WARNING**

Groups [F16K 15/044](#) and [F16K 15/046](#) are incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/042](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/046 . . . . {by a spring other than a helicoidal spring}

15/048 . . . {Ball features}

15/06 . . with guided stems

**WARNING**

Group [F16K 15/06](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/06](#) is also impacted by reclassification into groups [F16K 15/063](#), [F16K 15/064](#), [F16K 15/065](#), [F16K 15/066](#) and [F16K 15/067](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/063 . . . {the valve being loaded by a spring}

**WARNING**

Group [F16K 15/063](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/06](#) and [F16K 15/066](#).

Group [F16K 15/063](#) is also impacted by reclassification into groups [F16K 15/064](#), [F16K 15/065](#), [F16K 15/066](#) and [F16K 15/067](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/064 . . . . {with a spring other than a helicoidal spring}

**WARNING**

Group [F16K 15/064](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/06](#), [F16K 15/063](#) and [F16K 15/066](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/065 . . . . {spring pulling the closure member against the seat}

**WARNING**

Group [F16K 15/065](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/06](#), [F16K 15/063](#) and [F16K 15/066](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/066 . . . . {with a plurality of valve members}

**WARNING**

Group [F16K 15/066](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/06](#) and [F16K 15/063](#).

Group [F16K 15/066](#) is also impacted by reclassification into groups [F16K 15/063](#), [F16K 15/064](#), [F16K 15/065](#) and [F16K 15/067](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/067 . . . {stem guided at two or more points}

**WARNING**

Group [F16K 15/067](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/06](#), [F16K 15/063](#) and [F16K 15/066](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/08 . . shaped as rings

**WARNING**

Groups [F16K 15/08](#), [F16K 15/10](#), and [F16K 15/12](#) are incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/10 . . . integral with, or rigidly fixed to, a common valve plate

15/12 . . . Springs for ring valves

15/14 . with flexible valve members

**WARNING**

Group [F16K 15/14](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/14](#) is also impacted by reclassification into groups [F16K 15/1401](#) and [F16K 15/1402](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1401 . . {having a plurality of independent valve members}

**WARNING**

Group [F16K 15/1401](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/14](#), [F16K 15/144](#), [F16K 15/147](#), [F16K 15/148](#) and [F16K 15/16](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1402 . . {having an integral flexible member cooperating with a plurality of seating surfaces}

**WARNING**

Group [F16K 15/1402](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/14](#), [F16K 15/144](#), [F16K 15/147](#), [F16K 15/148](#) and [F16K 15/16](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/141 . . {the closure elements not being fixed to the valve body}

**WARNING**

Groups [F16K 15/141](#) and [F16K 15/142](#) are incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/142 . . . {the closure elements being shaped as solids of revolution, e.g. toroidal or cylindrical rings}



- 15/144 . . . {the closure elements being fixed along all or a part of their periphery}

**WARNING**

Group [F16K 15/144](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/144](#) is also impacted by reclassification into groups [F16K 15/1401](#), [F16K 15/1402](#) and [F16K 15/1441](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/1441 . . . {with biasing means in addition to material resiliency, e.g. spring}

**WARNING**

Group [F16K 15/1441](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/144](#) and [F16K 15/147](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/145 . . . {the closure elements being shaped as a solids of revolution, e.g. cylindrical or conical}

**WARNING**

Group [F16K 15/145](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/147 . . . {the closure elements having specially formed slits or being of an elongated easily collapsible form}

**WARNING**

Group [F16K 15/147](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/147](#) is also impacted by reclassification into groups [F16K 15/1401](#), [F16K 15/1402](#), [F16K 15/1441](#), [F16K 15/1471](#) and [F16K 15/1472](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/1471 . . . . {slits arranged along multiple axes}

**WARNING**

Group [F16K 15/1471](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/147](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/1472 . . . . {the closure elements being fixed onto an internally extending mount}

**WARNING**

Group [F16K 15/1472](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/147](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/148 . . {the closure elements being fixed in their centre}

**WARNING**

Group [F16K 15/148](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/148](#) is also impacted by reclassification into groups [F16K 15/1401](#), [F16K 15/1402](#) and [F16K 15/1481](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/1481 . . . {with biasing means in addition to material resiliency, e.g. spring}

**WARNING**

Group [F16K 15/1481](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/148](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/16 . . with tongue-shaped laminae

**WARNING**

Group [F16K 15/16](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/16](#) is also impacted by reclassification into groups [F16K 15/1401](#), [F16K 15/1402](#), [F16K 15/161](#) and [F16K 15/162](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/161 . . . {with biasing means in addition to material resiliency, e.g. spring}

**WARNING**

Group [F16K 15/161](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/16](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/162 . . . {with limit stop}

**WARNING**

Group [F16K 15/162](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/16](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/18 . . with actuating mechanism; Combined check valves and actuated valves

**WARNING**

Group [F16K 15/18](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/18](#) is also impacted by reclassification into groups [F16K 15/182](#), [F16K 15/184](#), [F16K 15/1841](#), [F16K 15/1843](#) and [F16K 15/1845](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/182 . . {with actuating mechanism}

**WARNING**

Group [F16K 15/182](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/18](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1821 . . . {for check valves with a hinged or pivoted closure member}

**WARNING**

Group [F16K 15/1821](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/1821](#) is also impacted by reclassification into group [F16K 15/1841](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1823 . . . {for ball check valves}

**WARNING**

Group [F16K 15/1823](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/1823](#) is also impacted by reclassification into group [F16K 15/1843](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1825 . . . {for check valves with flexible valve members}

**WARNING**

Group [F16K 15/1825](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

Group [F16K 15/1825](#) is also impacted by reclassification into group [F16K 15/1845](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1826 . . . {Check valves which can be actuated by a pilot valve}

**WARNING**

Group [F16K 15/1826](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/184 . . {Combined check valves and actuated valves}

**WARNING**

Group [F16K 15/184](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#) and [F16K 15/18](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1841 . . . {for check valves with a hinged closure member}

**WARNING**

Group [F16K 15/1841](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/18](#) and [F16K 15/1821](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1843 . . . {for ball check valves}

**WARNING**

Group [F16K 15/1843](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/18](#) and [F16K 15/1823](#).

All groups listed in this Warning should be considered in order to perform a complete search.

15/1845 . . . {for check valves with flexible valve members}

**WARNING**

Group [F16K 15/1845](#) is incomplete pending reclassification of documents from groups [F16K 15/03](#), [F16K 15/18](#) and [F16K 15/1825](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 15/1848 . . . {Check valves combined with valves having a rotating tap or cock}
- WARNING**
- Group [F16K 15/1848](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 15/20 . . specially designed for inflatable bodies, e.g. tyres (connecting valves to inflatable bodies [B60C 29/00](#))
- 15/202 . . {and with flexible valve member}
- 15/205 . . {and with closure plug}
- 15/207 . . {and combined with other valves, e.g. safety valves}
- WARNING**
- Group [F16K 15/207](#) is incomplete pending reclassification of documents from group [F16K 15/03](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 17/00 Safety valves; Equalising valves, {e.g. pressure relief valves}**
- WARNING**
- Groups [F16K 17/00](#) - [F16K 17/42](#) are incomplete pending reclassification of documents from group [F16K 15/03](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 17/003 . . {reacting to pressure and temperature}
- 17/006 . . {specially adapted for shelters}
- 17/02 . . opening on surplus pressure on one side; closing on insufficient pressure on one side (check valves [F16K 15/00](#))
- 17/025 . . {and remaining open after return of the normal pressure}
- 17/04 . . spring-loaded
- 17/0406 . . . {in the form of balls}
- 17/0413 . . . {in the form of closure plates}
- 17/042 . . . {with locking or disconnecting arrangements}
- 17/0426 . . . {with seat protecting means}
- 17/0433 . . . {with vibration preventing means}
- 17/044 . . . {with more than one spring}
- 17/0446 . . . {with an obturating member having at least a component of their opening and closing motion not perpendicular to the closing faces}
- 17/0453 . . . . {the member being a diaphragm}
- 17/046 . . . . {the valve being of the gate valve type or the sliding valve type}
- 17/0466 . . . {with a special seating surface}
- 17/0473 . . . {Multiple-way safety valves}
- 17/048 . . . {combined with other safety valves, or with pressure control devices}
- 17/0486 . . . {with mechanical actuating means}
- 17/0493 . . . {with a spring other than a helicoidal spring}
- 17/06 . . . with special arrangements for adjusting the opening pressure
- 17/065 . . . . {with differential piston}

- 17/08 . . . with special arrangements for providing a large discharge passage
- 17/082 . . . . {with piston}
- 17/085 . . . . {with diaphragm}
- 17/087 . . . . {with bellows}
- 17/10 . . . with auxiliary valve for fluid operation of the main valve
- 17/105 . . . . {using choking or throttling means to control the fluid operation of the main valve}
- 17/12 . . weight-loaded
- 17/14 . . with fracturing member
- 17/16 . . . with fracturing diaphragm {; Rupture discs}
- 17/1606 . . . . {of the reverse-buckling-type ([F16K 17/1633](#) takes precedence)}
- 17/1613 . . . . . {with additional cutting means}
- 17/162 . . . . . {of the non reverse-buckling-type ([F16K 17/1633](#) takes precedence)}
- 17/1626 . . . . . {with additional cutting means}
- 17/1633 . . . . {made of graphite}
- 17/164 . . and remaining closed after return of the normal pressure
- 17/168 . . combined with manually-controlled valves, e.g. a valve combined with a safety valve
- 17/18 . . opening on surplus pressure on either side
- 17/19 . . Equalising valves predominantly for tanks { (when combined with safety valve by change of position [F16K 17/36](#)) }
- 17/192 . . . with closure member in the form of a movable liquid column
- 17/194 . . . weight-loaded
- 17/196 . . . spring-loaded
- 17/20 . . Excess-flow valves (actuated in consequence of shock or similar extraneous influence [F16K 17/36](#))
- 17/205 . . . {specially adapted for flexible gas lines}
- 17/22 . . actuated by the difference of pressure between two places in the flow line
- 17/24 . . . acting directly on the cutting-off member
- 17/26 . . . . operating in either direction
- 17/28 . . . . operating in one direction only
- 17/285 . . . . . {the cutting-off member being a ball ([F16K 17/30](#) takes precedence)}
- 17/30 . . . . . spring-loaded
- 17/32 . . . acting on a servo-mechanism or on a catch-releasing mechanism
- 17/34 . . in which the flow-energy of the flowing medium actuates the closing mechanism
- 17/36 . . actuated in consequence of extraneous circumstances, e.g. shock, change of position
- 17/363 . . . {the closure members being rotatable or pivoting ([F16K 17/386](#) takes precedence)}
- 17/366 . . . {the closure member being a movable ball ([F16K 17/38](#) takes precedence)}
- 17/38 . . of excessive temperature
- 17/383 . . . {the valve comprising fusible, softening or meltable elements, e.g. used as link, blocking element, seal, closure plug ([F16K 17/386](#) takes precedence)}
- 17/386 . . . {the closure members being rotatable or pivoting}
- 17/40 . . with a fracturing member, e.g. fracturing diaphragm, glass, fusible joint (valves opening on surplus pressure [F16K 17/14](#))
- 17/403 . . . {with a fracturing valve member}

- 17/406 . . {the fracturing member being a generally elongated member, e.g. rod or wire, which is directly connected to a movable valve member, the breaking or buckling of the elongated member allowing the valve member to move to a closed or open position}
- 17/42 . Valves preventing penetration of air in the outlet of containers for liquids
- 19/00** **{Arrangements of valves and flow lines specially adapted for mixing fluids (multiple-way valves F16K 11/00)}**
- 19/003 . {Specially adapted for boilers}
- 19/006 . {Specially adapted for faucets}
- 21/00** **Fluid-delivery valves, {e.g. self-closing valves}{for liquid handling B67D; for flushing devices for water-closets or the like E03D}**
- 21/02 . providing a continuous small flow
- 21/04 . Self-closing valves, i.e. closing automatically after operation {(pneumatic tools B25B 9/00)}
- 21/06 . . in which the closing movement, either retarded or not, starts immediately after opening
- 21/08 . . . with ball-shaped closing members
- 21/10 . . . with hydraulic brake cylinder acting on the closure member
- 21/12 . . . with hydraulically-operated opening means; with arrangements for pressure relief before opening
- 21/14 . . with special means for preventing the self-closing
- 21/16 . . closing after a predetermined quantity of fluid has been delivered (F16K 21/10 takes precedence)
- 21/165 . . . {with means sensing the weight of said fluid quantity}
- 21/18 . . closed when a rising liquid reaches a predetermined level (float-actuated valves F16K 31/18)
- 21/185 . . . {with electrical or magnetical means, e.g. with magnetic floats, for sensing the liquid level}
- 21/20 . . . by means making use of air-suction through an opening closed by the rising liquid
- 23/00** **Valves for preventing drip from nozzles**
- 24/00** **Devices, e.g. valves, for venting or aerating enclosures (equalising valves F16K 17/00; arrangement or mounting in pipes or pipe systems F16L 55/07; venting or aerating as an additional function of steam traps or like apparatus F16T; ventilation of rooms, vehicles, see the appropriate subclass, e.g. F24F)**
- 24/02 . the enclosure being itself a valve, tap, or cock
- 24/04 . for venting only (F16K 24/02 takes precedence)
- 24/042 . . {actuated by a float}
- 24/044 . . . {the float being rigidly connected to the valve element, the assembly of float and valve element following a substantially translational movement when actuated, e.g. also for actuating a pilot valve}
- 24/046 . . . . {the assembly of float and valve element being a single spherical element}
- 24/048 . . . {a transmission element, e.g. arm, being interposed between the float and the valve element, the transmission element following a non-translational, e.g. pivoting or rocking, movement when actuated}

- 24/06 . for aerating only (F16K 24/02 takes precedence)

**Details****NOTE**

Details not provided for in the following groups are classified in the preceding groups.

- 25/00** **Details relating to contact between valve members and seats (movement of valve members other than for opening and closing F16K 29/00)**
- 25/005 . {Particular materials for seats or closure elements}
- 25/02 . Arrangements using fluid issuing from valve members or seats
- 25/04 . Arrangements for preventing erosion, not otherwise provided for
- 27/00** **Construction of housing (methods for welding housings B23K); Use of materials therefor**
- 27/003 . {Housing formed from a plurality of the same valve elements}
- 27/006 . {of hydrants}
- 27/02 . of lift valves (for reducing the flow resistance of screw-spindle lift-valves F16K 1/06)
- 27/0209 . . {Check valves or pivoted valves}
- 27/0218 . . . {Butterfly valves}
- 27/0227 . . . {with the valve members swinging around an axis located at the edge of or outside the valve member}

**WARNING**

Group F16K 27/0227 is impacted by reclassification into group F16K 27/0232. Groups F16K 27/0227 and F16K 27/0232 should be considered in order to perform a complete search.

- 27/0232 . . . . {the valve member retained by a removable closure}

**WARNING**

Group F16K 27/0232 is incomplete pending reclassification of documents from group F16K 27/0227.

Groups F16K 27/0227 and F16K 27/0232 should be considered in order to perform a complete search.

- 27/0236 . . {Diaphragm cut-off apparatus}
- 27/0245 . . {with ball-shaped valve members}
- 27/0254 . . {with conical shaped valve members}
- 27/0263 . . {multiple way valves}
- 27/0272 . . {valves provided with a lining}
- 27/0281 . . {Housings in two parts which can be orientated in different positions}
- 27/029 . . {Electromagnetically actuated valves}
- 27/04 . of sliding valves
- 27/041 . . {cylindrical slide valves}
- 27/042 . . . {Hydraulic fluid leak traps}
- 27/044 . . {slide valves with flat obturating members}
- 27/045 . . . {with pivotal obturating members}
- 27/047 . . . {with wedge-shaped obturating members}
- 27/048 . . {Electromagnetically actuated valves}
- 27/06 . of taps or cocks
- 27/062 . . {with conical plugs}

- 27/065 . . {with cylindrical plugs}
- 27/067 . . {with spherical plugs}
- 27/07 . of cutting-off parts of tanks, e.g. tank-cars
- 27/08 . Guiding yokes for spindles; Means for closing housings; Dust caps, e.g. for tyre valves
- 27/10 . Welded housings
- 27/102 . . {for lift-valves}
- 27/105 . . {for gate valves}
- 27/107 . . {for taps or cocks}
- 27/12 . Covers for housings
- 29/00 Arrangements for movement of valve members other than for opening and closing the valve, e.g. for grinding-in, for preventing sticking**
- 29/02 . providing for continuous motion
- 31/00 {Actuating devices;} Operating means; Releasing devices {(regulating means G05D)}**
- 31/001 . {actuated by volume variations caused by an element soluble in a fluid or swelling in contact with a fluid (life-boats B63C 9/24)}
- 31/002 . {actuated by temperature variation (thermo-electric F16K 31/025)}
- 31/003 . {operated without a stable intermediate position, e.g. with snap action (F16K 31/56 takes precedence)}
- 31/004 . {actuated by piezoelectric means}
- 31/005 . . {Piezoelectric benders}
- 31/006 . . . {having a free end}
- 31/007 . . {Piezoelectric stacks}
- 31/008 . . . {for sliding valves}
- 31/02 . electric {(F16K 31/004 takes precedence)}; magnetic
- 31/025 . . {actuated by thermo-electric means}
- 31/04 . . using a motor
- 31/041 . . . {for rotating valves (F16K 31/055 takes precedence)}
- 31/042 . . . . {with electric means, e.g. for controlling the motor or a clutch between the valve and the motor}
- 31/043 . . . . {characterised by mechanical means between the motor and the valve, e.g. lost motion means reducing backlash, clutches, brakes or return means}
- 31/045 . . . . . {with torque limiters}
- 31/046 . . . {with electric means, e.g. electric switches, to control the motor or to control a clutch between the valve and the motor (F16K 31/041 takes precedence)}
- 31/047 . . . {characterised by mechanical means between the motor and the valve, e.g. lost motion means reducing backlash, clutches, brakes or return means (F16K 31/043 takes precedence)}
- 31/048 . . . . {with torque limiters (F16K 31/041 takes precedence)}
- 31/05 . . . specially adapted for operating hand-operated valves or for combined motor and hand operation
- 31/055 . . . . {for rotating valves}
- 31/06 . . using a magnet {, e.g. diaphragm valves, cutting off by means of a liquid}
- 31/0603 . . . {Multiple-way valves}
- 31/0606 . . . . {fluid passing through the solenoid coil}
- 31/061 . . . . {Sliding valves}
- 31/0613 . . . . . {with cylindrical slides}
- 31/0617 . . . . . {with flat slides}
- 31/062 . . . . {the valve element being at least partially ball-shaped}
- 31/0624 . . . . {Lift valves}
- 31/0627 . . . . . {with movable valve member positioned between seats}
- 31/0631 . . . . . {with ball shaped valve members}
- 31/0634 . . . . . {with fixed seats positioned between movable valve members}
- 31/0637 . . . . . {with ball shaped valve members}
- 31/0641 . . . . {the valve member being a diaphragm}
- 31/0644 . . . {One-way valve}
- 31/0648 . . . . {the armature and the valve member forming one element (F16K 31/0651 takes precedence)}
- 31/0651 . . . . {the fluid passing through the solenoid coil}
- 31/0655 . . . . {Lift valves}
- 31/0658 . . . . . {Armature and valve member being one single element}
- 31/0662 . . . . . {with a ball-shaped valve member}
- 31/0665 . . . . . {with valve member being at least partially ball-shaped (F16K 31/0662 takes precedence)}
- 31/0668 . . . . {Sliding valves}
- 31/0672 . . . . {the valve member being a diaphragm}
- 31/0675 . . . {Electromagnet aspects, e.g. electric supply therefor}
- 31/0679 . . . . {with more than one energising coil}
- 31/0682 . . . {with an articulated or pivot armature}
- 31/0686 . . . {Braking, pressure equilibration, shock absorbing}
- 31/0689 . . . . {Braking of the valve element}
- 31/0693 . . . . {Pressure equilibration of the armature}
- 31/0696 . . . . {Shock absorbing, e.g. using a dash-pot}
- 31/08 . . . using a permanent magnet
- 31/082 . . . . {using an electromagnet and a permanent magnet}
- 31/084 . . . . {the magnet being used only as a holding element to maintain the valve in a specific position, e.g. check valves (F16K 31/082, F16K 31/086 take precedence)}
- 31/086 . . . . {the magnet being movable and actuating a second magnet connected to the closing element}
- 31/088 . . . . . {the movement of the first magnet being a rotating or pivoting movement}
- 31/10 . . . with rotating mechanism between armature and closure member
- 31/105 . . . . {for rotating valves}
- 31/12 . . actuated by fluid ({fluid-actuated lift valves F16K 1/126} ; fluid-actuated check valves F16K 15/00; fluid-actuated safety valves F16K 17/00)
- 31/122 . . the fluid acting on a piston (F16K 31/143, F16K 31/163, F16K 31/363, F16K 31/383 take precedence)
- 31/1221 . . . {one side of the piston being spring-loaded}
- 31/1223 . . . {one side of the piston being acted upon by the circulating fluid}
- 31/1225 . . . {with a plurality of pistons}
- 31/1226 . . . {the fluid circulating through the piston}
- 31/1228 . . . {with a stationary piston}



- 31/124 . . . servo actuated
- 31/1245 . . . {with more than one valve}
- 31/126 . . the fluid acting on a diaphragm, bellows, or the like ([F16K 31/145](#), [F16K 31/165](#), [F16K 31/365](#), [F16K 31/385](#) take precedence)
- 31/1262 . . . {one side of the diaphragm being spring loaded}
- 31/1264 . . . {with means to allow the side on which the springs are positioned to be altered}
- 31/1266 . . . {one side of the diaphragm being acted upon by the circulating fluid}
- 31/1268 . . . {with a plurality of the diaphragms}
- 31/128 . . . servo actuated
- 31/14 . . for mounting on, or in combination with, hand-actuated valves
- 31/143 . . . the fluid acting on a piston
- 31/145 . . . the fluid acting on a diaphragm
- 31/16 . . with a mechanism, other than pulling-or pushing-rod, between fluid motor and closure member ([with float F16K 31/18](#))
- 31/163 . . . the fluid acting on a piston
- 31/1635 . . . {for rotating valves}
- 31/165 . . . the fluid acting on a diaphragm
- 31/1655 . . . {for rotating valves}
- 31/18 . . actuated by a float ([floats F16K 33/00](#); [float-actuated valves in steam-traps F16T 1/20](#), in [boilers F22D 5/08](#))
- 31/20 . . . actuating a lift valve
- 31/22 . . . with the float rigidly connected to the valve
- 31/24 . . . with a transmission with parts linked together from a single float to a single valve
- 31/26 . . . with the valve guided for rectilinear movement and the float attached to a pivoted arm
- 31/265 . . . {with a second lever or toggle between the pivoted arm and the valve}
- 31/28 . . . with two or more floats actuating one valve
- 31/30 . . . actuating a gate valve or sliding valve
- 31/32 . . . actuating a tap or cock
- 31/34 . . . acting on pilot valve controlling the cut-off apparatus
- 31/36 . . in which fluid from the circuit is constantly supplied to the fluid motor
- 31/363 . . . the fluid acting on a piston ([F16K 31/38](#) takes precedence)
- 31/365 . . . the fluid acting on a diaphragm
- 31/38 . . in which the fluid works directly on both sides of the fluid motor, one side being connected by means of a restricted passage and the motor being actuated by operating a discharge from that side ([F16K 31/40](#) takes precedence)
- 31/383 . . . the fluid acting on a piston
- 31/3835 . . . {the discharge being effected through the piston and being blockable by a mechanically-actuated member making contact with the piston}
- 31/385 . . . the fluid acting on a diaphragm
- 31/3855 . . . {the discharge being effected through the diaphragm and being blockable by a mechanically-actuated member making contact with the diaphragm}
- 31/40 . . . with electrically-actuated member in the discharge of the motor
- 31/402 . . . {acting on a diaphragm}
- 31/404 . . . {the discharge being effected through the diaphragm and being blockable by an electrically-actuated member making contact with the diaphragm}
- 31/406 . . . {acting on a piston}
- 31/408 . . . {the discharge being effected through the piston and being blockable by an electrically-actuated member making contact with the piston}
- 31/42 . . by means of electrically-actuated members in the supply or discharge conduits of the fluid motor ([F16K 31/40](#) takes precedence)
- 31/423 . . . {the actuated members consisting of multiple way valves}
- 31/426 . . . {the actuated valves being cylindrical sliding valves}
- 31/44 . Mechanical actuating means
- 31/445 . . {with exterior sleeve}
- 31/46 . . for remote operation
- 31/465 . . . {by flexible transmission means, e.g. cable, chain, bowden wire}
- 31/48 . . actuated by mechanical timing-device, e.g. with dash-pot ([self-closing valves F16K 21/16](#))
- 31/485 . . . {and specially adapted for gas valves}
- 31/50 . . with screw-spindle {or internally threaded actuating means}
- 31/502 . . . {actuating pivotable valve members}
- 31/504 . . . {the actuating means being rotatable, rising, and having internal threads which co-operate with threads on the outside of the valve body}
- 31/506 . . . {with plural sets of thread, e.g. with different pitch}
- 31/508 . . . {the actuating element being rotatable, non-rising, and driving a non-rotatable axially-sliding element}
- 31/52 . . with crank, eccentric, or cam
- 31/521 . . . {comprising a pivoted disc or flap}
- 31/522 . . . {comprising a tap or cock}
- 31/523 . . . {comprising a sliding valve}
- 31/524 . . . with a cam
- 31/52408 . . . {comprising a lift valve}
- 31/52416 . . . {comprising a multiple-way lift valve}
- 31/52425 . . . {with a ball-shaped valve member}
- 31/52433 . . . {with a streamlined or helically shaped valve member, e.g. for reducing flow losses or guiding the fluid flow}
- 31/52441 . . . {with a pivoted disc or flap}
- 31/5245 . . . {with a valve member of conical shape}
- 31/52458 . . . {comprising a tap or cock}
- 31/52466 . . . {comprising a multiple-way tap or cock}
- 31/52475 . . . {comprising a sliding valve}
- 31/52483 . . . {comprising a multiple-way sliding valve}
- 31/52491 . . . {comprising a diaphragm cut-off apparatus}
- 31/528 . . . with pin and slot
- 31/5282 . . . {comprising a pivoted disc or flap}
- 31/5284 . . . {comprising a tap or cock}
- 31/5286 . . . {comprising a sliding valve}
- 31/5288 . . . {comprising a diaphragm cut-off apparatus}
- 31/53 . . with toothed gearing
- 31/535 . . . {for rotating valves ([F16K 31/54](#) takes precedence)}
- 31/54 . . . with pinion and rack

31/56	. . without stable intermediate position, e.g. with snap action	37/0091	. . {by measuring fluid parameters}
31/563	. . . {for rotating or pivoting valves}	<b>39/00</b>	<b>Devices for relieving the pressure on the sealing faces</b>
31/566	. . . {using a bistable spring device arranged symmetrically around the actuating stem}	39/02	. for lift valves
31/58	. . comprising a movable discharge-nozzle	39/022	. . {using balancing surfaces}
31/60	. . Handles {(form, features or function of taps or faucet handles for domestic plumbing installations E03C 1/04)}	39/024	. . {using an auxiliary valve on the main valve}
31/602	. . . {Pivoting levers, e.g. single-sided (F16K 31/605 takes precedence)}	39/026	. . {using an external auxiliary valve}
31/605	. . . {for single handle mixing valves}	39/028	. . {with pivoted closure members, e.g. butterfly valves}
31/607	. . . {characterised by particular material, by special measures to obtain aesthetical effects, or by auxiliary functions, e.g. storage}	39/04	. for sliding valves
31/62	. . Pedals or like operating members, e.g. actuated by knee or hip	39/045	. . {of rotating or pivoting type}
<b>33/00</b>	<b>Floats for actuation of valves or other apparatus {(float actuated valves F16K 31/18)}</b>	39/06	. for taps or cocks
<b>35/00</b>	<b>Means to prevent accidental or unauthorised actuation</b>	<b>41/00</b>	<b>Spindle sealings</b>
35/02	. to be locked or disconnected by means of a pushing or pulling action	41/003	. {by fluid}
35/022	. . {the locking mechanism being actuated by a separate actuating element}	41/006	. {by establishing an under-pressure}
35/025	. . . {said actuating element being operated manually (e.g. a push-button located in the valve actuator)}	41/02	. with stuffing-box {; Sealing rings}
35/027	. . {the locking mechanism being actuated by pushing or pulling the valve actuator, the valve actuator being rotated subsequently to bring the valve closure element in the desired position}	41/023	. . {for spindles which only rotate, i.e. non-rising spindles (F16K 41/043, F16K 41/063 and F16K 41/083 take precedence)}
35/04	. yieldingly resisting the actuation	41/026	. . . {for rotating valves}
35/06	. using a removable actuating or locking member, e.g. a key (F16K 35/10, F16K 35/12 take precedence)	41/04	. . with at least one ring of rubber or like material between spindle and housing
35/08	. requiring setting according to a code, e.g. permutation locks	41/043	. . . {for spindles which only rotate, i.e. non-rising spindles}
35/10	. with locking caps or locking bars	41/046	. . . . {for rotating valves}
35/12	. with sealing wire	41/06	. . with at least one ring attached to both spindle and housing
35/14	. interlocking two or more valves	41/063	. . . {for spindles which only rotate, i.e. non-rising spindles}
35/16	. with locking member actuated by magnet	41/066	. . . . {for rotating valves}
<b>37/00</b>	<b>Special means in or on valves or other cut-off apparatus for indicating or recording operation thereof, or for enabling an alarm to be given</b>	41/08	. . with at least one ring provided with axially-protruding peripheral closing-lip
37/0008	. {Mechanical means (F16K 37/0075 takes precedence)}	41/083	. . . {for spindles which only rotate, i.e. non-rising spindles}
37/0016	. . {having a graduated scale}	41/086	. . . . {for rotating valves}
37/0025	. {Electrical or magnetic means (F16K 37/0075 takes precedence)}	41/10	. with diaphragm, e.g. shaped as bellows or tube
37/0033	. . {using a permanent magnet, e.g. in combination with a reed relays}	41/103	. . {the diaphragm and the closure member being integrated in one member}
37/0041	. . {for measuring valve parameters (F16K 37/0033 takes precedence)}	41/106	. . {for use with rotating spindles or valves (F16K 41/125 takes precedence)}
37/005	. . {for measuring fluid parameters (F16K 37/0033 takes precedence)}	41/12	. . with approximately flat diaphragm
37/0058	. {Optical means, e.g. light transmission, observation ports (F16K 37/0075 takes precedence)}	41/125	. . . {the part of the spindle traversing the diaphragm being rotatable or pivotable}
37/0066	. {Hydraulic or pneumatic means (F16K 37/0075 takes precedence)}	41/14	. with conical flange on the spindle which co-operates with a conical surface in the housing
37/0075	. {For recording or indicating the functioning of a valve in combination with test equipment}	41/16	. with a flange on the spindle which rests on a sealing ring
37/0083	. . {by measuring valve parameters}	41/18	. . sealing only when the closure member is in the opened position
		<b>43/00</b>	<b>Auxiliary closure means in valves, which in case of repair, e.g. rewashing, of the valve, can take over the function of the normal closure means; Devices for temporary replacement of parts of valves for the same purpose</b>
		43/001	. {an auxiliary valve being actuated independently of the main valve}
		43/003	. . {the auxiliary valve being a rotary valve}
		43/005	. {an auxiliary valve closing automatically when the main valve is being disassembled}
		43/006	. . {the auxiliary valve being held open by the main valve}

- 43/008 . {the main valve having a back-seat position, e.g. to service the spindle sealing}
- 47/00 Means in valves for absorbing fluid energy (for pipes F16L 55/00)**
- WARNING**
- Group [F16K 47/00](#) is impacted by reclassification into groups [F16K 47/01](#), [F16K 47/011](#), [F16K 47/0111](#), [F16K 47/0112](#) and [F16K 47/012](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 47/01 . {Damping of valve members}
- WARNING**
- Groups [F16K 47/01](#) and [F16K 47/012](#) are incomplete pending reclassification of documents from groups [F16K 47/00](#), [F16K 47/02](#) and [F16K 47/023](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 47/011 . . {by means of a dashpot}
- WARNING**
- Groups [F16K 47/011](#), [F16K 47/0111](#), and [F16K 47/0112](#) are incomplete pending reclassification of documents from groups [F16K 47/00](#), [F16K 47/02](#) and [F16K 47/023](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 47/0111 . . . {the valve members comprising a plunger sliding within a fixed dashpot}
- 47/0112 . . . {the valve members comprising a dashpot sliding over a fixed plunger}
- 47/012 . . {by means of a resilient damping element}
- 47/02 . for preventing water-hammer or noise
- WARNING**
- Group [F16K 47/02](#) is impacted by reclassification into groups [F16K 47/01](#), [F16K 47/011](#), [F16K 47/0111](#), [F16K 47/0112](#) and [F16K 47/012](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 47/023 . . {for preventing water-hammer, e.g. damping of the valve movement}
- WARNING**
- Group [F16K 47/023](#) is impacted by reclassification into groups [F16K 47/01](#), [F16K 47/011](#), [F16K 47/0111](#), [F16K 47/0112](#) and [F16K 47/012](#).
- All groups listed in this Warning should be considered in order to perform a complete search.
- 47/026 . . {preventing noise in a single handle mixing valve}
- 47/04 . for decreasing pressure {or noise level}, the throttle being incorporated in the closure member
- 47/045 . . {and the closure member being rotatable}
- 47/06 . . with a throttle in the form of a helical channel
- 47/08 . for decreasing pressure {or noise level} and having a throttling member separate from the closure member {, e.g. screens, slots, labyrinths}
- 47/10 . . in which the medium in one direction must flow through the throttling channel, and in the other direction may flow through a much wider channel parallel to the throttling channel
- 47/12 . . the throttling channel being of helical form
- 47/14 . . the throttling member being a perforated membrane
- 47/16 . . the throttling member being a cone
- 49/00 Means in or on valves for heating or cooling (heating or cooling of pipes or pipe systems F16L 53/00; thermal insulation in connection with pipes or pipe systems F16L 59/16)**
- 49/002 . {Electric heating means}
- 49/005 . {Circulation means for a separate heat transfer fluid}
- 49/007 . . {located within the obturating element}
- 51/00 Other details not peculiar to particular types of valves or cut-off apparatus**
- 51/02 . specially adapted for high-vacuum installations
- 99/00 Subject matter not provided for in other groups of this subclass**
- 99/0001 . {Microvalves (microdevices [B81B 1/00](#); manufacture or treatment of devices or systems in or on a substrate [B81C 1/00](#); microfluidic structures [B01L 3/5027](#); micropumps [F04B 19/006](#))}
- 99/0003 . . {Constructional types of microvalves; Details of the cutting-off member}
- 99/0005 . . . {Lift valves}
- 99/0007 . . . . {of cantilever type}
- 99/0009 . . . . {the valve element held by multiple arms}
- 99/0011 . . . {Gate valves or sliding valves}
- 99/0013 . . . {Rotary valves}
- 99/0015 . . . {Diaphragm or membrane valves}
- 99/0017 . . . {Capillary or surface tension valves, e.g. using electro-wetting or electro-capillarity effects}
- 99/0019 . . . {Valves using a microdroplet or microbubble as the valve member}
- 99/0021 . . . {No-moving-parts valves}
- 99/0023 . . . {with ball-shaped valve members}
- 99/0025 . . . {Valves using microporous membranes}
- 99/0026 . . . {Valves using channel deformation}
- 99/0028 . . . {Valves having multiple inlets or outlets}
- 99/003 . . . {Valves for single use only}
- 99/0032 . . . {using phase transition or influencing viscosity}
- 99/0034 . . {Operating means specially adapted for microvalves}
- 99/0036 . . . {operated by temperature variations}
- 99/0038 . . . . {using shape memory alloys}
- 99/004 . . . . {using radiation}
- 99/0042 . . . {Electric operating means therefor}
- 99/0044 . . . . {using thermo-electric means}
- 99/0046 . . . . {using magnets}
- 99/0048 . . . . {using piezoelectric means}
- 99/0049 . . . . {using an electroactive polymer [EAP]}
- 99/0051 . . . . {using electrostatic means}

99/0053	. . . . {using magnetostrictive means}	2200/502	. . Cages for valves, i.e. means to be inserted within the valve housing, surrounding and guiding the closure member
99/0055	. . . {actuated by fluids}		
99/0057	. . . . {the fluid being the circulating fluid itself, e.g. check valves}		
99/0059	. . . . {actuated by a pilot fluid}		
99/0061	. . . . {actuated by an expanding gas or liquid volume}		
99/0063	. . . {using centrifugal forces}		
99/0065	. . . {using chemical activation}		
99/0067	. . . . {actuated by a pyrotechnical charge}		
2099/0069	. . {Bistable microvalves}		
2099/0071	. . {with latching means}		
2099/0073	. {Fabrication methods specifically adapted for microvalves}		
2099/0074	. . {using photolithography, e.g. etching}		
2099/0076	. . {using electrical discharge machining [EDM], milling or drilling}		
2099/0078	. . {using moulding or stamping}		
2099/008	. . {Multi-layer fabrications}		
2099/0082	. {Microvalves adapted for a particular use}		
2099/0084	. . {Chemistry or biology, e.g. "lab-on-a-chip" technology}		
2099/0086	. . {Medical applications}		
2099/0088	. . . {Implanted devices}		
2099/009	. . {Fluid power devices}		
2099/0092	. . {Inkjet printers}		
2099/0094	. . {Micropumps}		
2099/0096	. . {Fuel injection devices}		
2099/0098	. . {Refrigeration circuits, e.g. for cooling integrated circuits}		
<b>2200/00</b>	<b>Details of valves</b>		
2200/10	. Means for compensation of misalignment between seat and closure member		
2200/101	. . closure member self-aligning to seat		
2200/102	. . seat self-aligning to closure member		
2200/20	. Common housing having a single inlet, a single outlet and multiple valve members		
2200/201	. . of diverse type, size or shape		
2200/202	. . one valve arranged inside of the valve member of a second valve, e.g. nested valve members		
2200/203	. . in parallel		
2200/204	. . in series		
2200/30	. Spring arrangements		
2200/301	. . Common spring for multiple closure members		
2200/302	. . Plurality of biasing means, e.g. springs, for opening or closing single valve member		
2200/303	. . Means for protecting the spring in the fluid flow path		
2200/304	. . Adjustable spring pre-loading		
2200/305	. . Constructional features of springs		
2200/3051	. . . Generally flat springs		
2200/3052	. . . Cantilever springs		
2200/3053	. . . Helicoidal springs of variable pitch, diameter or spring rate		
2200/40	. Bleeding means in closed position of the valve, e.g. bleeding passages		
2200/401	. . arranged on the closure member		
2200/402	. . arranged on the valve housing or seat		
2200/50	. Self-contained valve assemblies		
2200/501	. . Cartridge valves		