

# CPC COOPERATIVE PATENT CLASSIFICATION

## H ELECTRICITY

(NOTE omitted)

## H04 ELECTRIC COMMUNICATION TECHNIQUE

(NOTE omitted)

## H04B TRANSMISSION

### NOTE

This subclass covers the transmission of information-carrying signals, the transmission being independent of the nature of the information, and includes monitoring and testing arrangements and the suppression and limitation of noise and interference.

### WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

- |        |  |        |   |
|--------|--|--------|---|
| 1/00   | <b>Details of transmission systems, not covered by a single one of groups <a href="#">H04B 3/00</a> - <a href="#">H04B 13/00</a>; Details of transmission systems not characterised by the medium used for transmission</b><br><b>NOTE</b><br>In this group, group <a href="#">H04B 1/0003</a> takes precedence over groups <a href="#">H04B 1/005</a> - <a href="#">H04B 1/76</a>   | 1/0035 | . . . {Channel filtering, i.e. selecting a frequency channel within a software radio system (multiplexing of multicarrier modulation signals being represented by different frequencies <a href="#">H04L 5/06</a> ; multiplexing of multicarrier modulation signals <a href="#">H04L 5/023</a> )} |
| 1/0003 | . {Software-defined radio [SDR] systems, i.e. systems wherein components typically implemented in hardware, e.g. filters or modulators/demodulators, are implented using software, e.g. by involving an AD or DA conversion stage such that at least part of the signal processing is performed in the digital domain (digital baseband systems <a href="#">H04L 25/00</a> ; digital modulation/demodulation <a href="#">H04L 27/00</a> ; CDMA <a href="#">H04B 1/707</a> ; TDMA <a href="#">H04B 7/2643</a> ; image transmission <a href="#">H04N 5/00</a> )} | 1/0039 | . . . {using DSP [Digital Signal Processor] quadrature modulation and demodulation}   |
| 1/0007 | . . {wherein the AD/DA conversion occurs at radiofrequency or intermediate frequency stage}  | 1/0042 | . . . {Digital filtering ( <a href="#">H04B 1/0035</a> takes precedence; digital filters per se <a href="#">H03H 17/00</a> )}   |
| 1/001  | . . . {Channel filtering, i.e. selecting a frequency channel within the SDR system (multiplexing of multicarrier modulation signals being represented by different frequencies <a href="#">H04L 5/06</a> ; multiplexing of multicarrier modulation signals <a href="#">H04L 5/023</a> )}   | 1/0046 | . . . {Decimation, i.e. data rate reduction techniques}   |
| 1/0014 | . . . {using DSP [Digital Signal Processor] quadrature modulation and demodulation}  | 1/005  | . {adapting radio receivers, transmitters and transceivers for operation on two or more bands, i.e. frequency ranges}   |
| 1/0017 | . . . {Digital filtering ( <a href="#">H04B 1/001</a> takes precedence; digital filters per se <a href="#">H03H 17/00</a> )}   | 1/0053 | . . {with common antenna for more than one band}  |
| 1/0021 | . . . {Decimation, i.e. data rate reduction techniques ( <a href="#">H04B 1/0025</a> takes precedence)}  | 1/0057 | . . . {using diplexing or multiplexing filters for selecting the desired band}  |
| 1/0025 | . . . {using a sampling rate lower than twice the highest frequency component of the sampled signal (for demodulation of angle-modulated signals <a href="#">H03D 3/006</a> )}   | 1/006  | . . . {using switches for selecting the desired band ( <a href="#">H04B 1/0057</a> takes precedence)}   |
| 1/0028 | . . {wherein the AD/DA conversion occurs at baseband stage}  | 1/0064 | . . {with separate antennas for the more than one band ( <a href="#">H04B 1/0053</a> takes precedence)}   |
| 1/0032 | . . . {with analogue quadrature frequency conversion to and from the baseband (quadrature modulators and demodulators per se <a href="#">H03D 3/007</a> , <a href="#">H03C 3/40</a> )}   | 1/0067 | . . {with one or more circuit blocks in common for different bands}   |
|        |  | 1/0071 | . . . {using a common intermediate frequency for more than one band ( <a href="#">H04B 1/0075</a> takes precedence)}  |
|        |  | 1/0075 | . . . {using different intermediate frequencied for the different bands}  |
|        |  | 1/0078 | . . . . {with a common intermediate frequency amplifier for the different intermediate frequencies, e.g. when using switched intermediate frequency filters}  |
|        |  | 1/0082 | . . . {with a common local oscillator for more than one band}   |
|        |  | 1/0085 | . . . . {where one band is the image frequency band of the other and the band selection is done by image rejection}   |
|        |  | 1/0089 | . . . . {using a first intermediate frequency higher than the highest of any band received}   |
|        |  | 1/0092 | . . . . . {using a wideband front end}  |
|        |  | 1/0096 | . . {where a full band is frequency converted into another full band}   |

1/02	. Transmitters	1/126	. . . . . {having multiple inputs, e.g. auxiliary antenna for receiving interfering signal (aerials in general <a href="#">H01Q</a> )}
1/03	. . Constructional details, e.g. casings, housings	1/14	. . . Automatic detuning arrangements
1/034	. . . Portable transmitters	1/16	. . Circuits
1/0343	. . . . {to be carried on the body}	1/1607	. . . {Supply circuits (converters <a href="#">H02M</a> ; filters therefor <a href="#">H02M 1/14</a> ; voltage stabilisers <a href="#">G05F 1/46</a> )}
1/0346	. . . . {Hand-held transmitters}	1/1615	. . . . {Switching on; Switching off, e.g. remotely (battery saving circuits associated with selective call operation <a href="#">H04W 52/00</a> ; details of power consumption reduction in a PLL, <a href="#">H03L 7/0802</a> , <a href="#">H03L 7/14</a> , <a href="#">H03L 2207/08</a> , <a href="#">H03L 2207/18</a> ; muting amplifiers by gain control see <a href="#">H03G 3/34</a> )}
1/036	. . . Cooling arrangements	1/1623	. . . . {using tubes}
1/04	. . Circuits	1/163	. . . {Special arrangements for the reduction of the damping of resonant circuits of receivers (amplifiers <a href="#">H03F</a> ; negative impedance networks for line transmission systems <a href="#">H04B 3/16</a> )}
2001/0408	. . . {with power amplifiers}	1/1638	. . . {Special circuits to enhance selectivity of receivers not otherwise provided for (resonant circuits <a href="#">H03H</a> )}
2001/0416	. . . . {having gain or transmission power control}	1/1646	. . . {adapted for the reception of stereophonic signals}
2001/0425	. . . . {with linearisation using predistortion}	1/1653	. . . . {Detection of the presence of stereo signals and pilot signal regeneration}
2001/0433	. . . . {with linearisation using feedback}	1/1661	. . . . {Reduction of noise by manipulation of the baseband composite stereophonic signal or the decoded left and right channels}
2001/0441	. . . . {with linearisation using feed-forward}	1/1669	. . . . . {of the demodulated composite stereo signal}
2001/045	. . . . {with means for improving efficiency}	1/1676	. . . . . {of the sum or difference signal}
1/0458	. . . {Arrangements for matching and coupling between power amplifier and antenna or between amplifying stages (matching circuits in general <a href="#">H03H</a> )}	1/1684	. . . . . {of the decoded left or right stereo channel}
1/0466	. . . {Fault detection or indication ( <a href="#">H04B 1/0483</a> takes precedence)}	1/1692	. . . . {using companding of the stereo difference signal, e.g. FMX (volume compression or expansion in amplifiers <a href="#">H03G 7/00</a> )}
1/0475	. . . {with means for limiting noise, interference or distortion ( <a href="#">H04B 1/0483</a> takes precedence)}	1/18	. . . Input circuits, e.g. for coupling to an antenna or a transmission line (coupling networks between antennas or lines and receivers independent of the nature of the receiver <a href="#">H03H</a> )
1/0483	. . . {Transmitters with multiple parallel paths}	1/20	. . . for coupling gramophone pick-up, recorder output, or microphone to receiver
2001/0491	. . . {with frequency synthesizers, frequency converters or modulators}	1/202	. . . . {by remote control}
1/06	. Receivers	1/205	. . . . {with control bus for exchanging commands between units}
1/08	. . Constructional details, e.g. cabinet	1/207	. . . . {with an audio or audio/video bus for signal distribution ( <a href="#">H04B 1/205</a> takes precedence)}
1/082	. . . {to be used in vehicles ( <a href="#">H04B 1/086</a> takes precedence; holding or mounting accessories <a href="#">B60R 11/02</a> )}	1/22	. . . for receivers in which no local oscillation is generated
2001/084	. . . . {with removable front panel}	1/24	. . . . the receiver comprising at least one semiconductor device having three or more electrodes
1/086	. . . {Portable receivers}	1/26	. . . for superheterodyne receivers (multiple frequency-changing <a href="#">H03D 7/16</a> )
1/088	. . . . {with parts of the receiver detachable or collapsible}	1/28	. . . . the receiver comprising at least one semiconductor device having three or more electrodes
1/10	. . Means associated with receiver for limiting or suppressing noise or interference	1/30	. . . for homodyne or synchrodyne receivers (demodulator circuits <a href="#">H03D 1/22</a> )
1/1009	. . . {Placing the antenna at a place where the noise level is low and using a noise-free transmission line between the antenna and the receivers (screened aerials <a href="#">H01Q 7/04</a> ; feeders for aerials <a href="#">H01Q 9/00</a> )}	1/302	. . . . {for single sideband receivers (demodulator circuits <a href="#">H03D 1/24</a> )}
1/1018	. . . {noise filters connected between the power supply and the receiver}		
1/1027	. . . {assessing signal quality or detecting noise/interference for the received signal}		
1/1036	. . . . {with automatic suppression of narrow band noise or interference, e.g. by using tuneable notch filters ( <a href="#">H04B 1/123</a> takes precedence; filter circuits <a href="#">H03H</a> )}		
2001/1045	. . . . {Adjacent-channel interference}		
2001/1054	. . . . {by changing bandwidth}		
2001/1063	. . . . {using a notch filter}		
2001/1072	. . . . {by tuning the receiver frequency}		
1/1081	. . . {Reduction of multipath noise (by equalising <a href="#">H04B 7/005</a> )}		
1/109	. . . {by improving strong signal performance of the receiver when strong unwanted signals are present at the receiver input}		
1/12	. . . Neutralising, balancing, or compensation arrangements		
1/123	. . . . {using adaptive balancing or compensation means (adaptive filter circuits and algorithms <a href="#">H03H</a> )}		

2001/305	. . . . {using DC offset compensation techniques}	1/403	. . . using the same oscillator for generating both the transmitter frequency and the receiver local oscillator frequency
2001/307	. . . . {using n-port mixer}	1/405	. . . . with multiple discrete channels
1/38	. Transceivers, i.e. devices in which transmitter and receiver form a structural unit and in which at least one part is used for functions of transmitting and receiving	1/406	. . . . {with more than one transmission mode, e.g. analog and digital modes}
1/3805	. . with built-in auxiliary receivers	1/408	. . . . the transmitter oscillator frequency being identical to the receiver local oscillator frequency
2001/3811	. . . {Split configuration of transmission devices}	1/44	. . . Transmit/receive switching
1/3816	. . Mechanical arrangements for accommodating identification devices, e.g. cards or chips; with connectors for programming identification devices	1/46	. . . . by voice-frequency signals; by pilot signals
1/3818	. . . Arrangements for facilitating insertion or removal of identification devices	1/48	. . . . in circuits for connecting transmitter and receiver to a common transmission path, e.g. by energy of transmitter { <a href="#">H04B 1/46 takes precedence</a> }
1/3822	. . specially adapted for use in vehicles ( <a href="#">H04B 1/3827 takes precedence</a> )	2001/485	. . . . . {inhibiting unwanted transmission}
1/3827	. . Portable transceivers	1/50	. . . using different frequencies for the two directions of communication
1/3833	. . . {Hand-held transceivers}	1/52	. . . . Hybrid arrangements, i.e. arrangements for transition from single-path two-direction transmission to single-direction transmission on each of two paths or vice versa
1/3838	. . . . {Arrangements for reducing RF exposure to the user, e.g. by changing the shape of the transceiver while in use}	1/525	. . . . . with means for reducing leakage of transmitter signal into the receiver
2001/3844	. . . . . {with means to alert the user that a certain exposure has been reached}	1/54	. . . using the same frequency for two directions of communication ( <a href="#">H04B 1/44 takes precedence</a> )
1/385	. . . {Transceivers carried on the body, e.g. in helmets}	1/56	. . . . with provision for simultaneous communication in two directions
2001/3855	. . . . {carried in a belt or harness}	1/58	. . . . Hybrid arrangements, i.e. arrangements for transition from single-path two-direction transmission to single-direction transmission on each of two paths or vice versa
<b>WARNING</b>		1/581	. . . . . {using a transformer}
Group <a href="#">H04B 2001/3855</a> is impacted by reclassification into group <a href="#">A45F 5/1516</a> .		1/582	. . . . . {with automatic balancing}
Groups <a href="#">H04B 2001/3855</a> and <a href="#">A45F 5/1516</a> should be considered in order to perform a complete search.		1/583	. . . . . {using a bridge network}
2001/3861	. . . . {carried in a hand or on fingers}	1/585	. . . . . {with automatic balancing}
<b>WARNING</b>		1/586	. . . . . {using an electronic circuit}
Group <a href="#">H04B 2001/3861</a> is impacted by reclassification into group <a href="#">A45F 5/1516</a> .		1/587	. . . . . {using opto-couplers ( <a href="#">light transmission systems H04B 10/00</a> )}
Groups <a href="#">H04B 2001/3861</a> and <a href="#">A45F 5/1516</a> should be considered in order to perform a complete search.		1/588	. . . . . {using sampling gates}
2001/3866	. . . . {carried on the head}	1/59	. Responders; Transponders
2001/3872	. . . . {with extendable microphones or earphones}	1/60	. Supervising unattended repeaters
1/3877	. . . Arrangements for enabling portable transceivers to be used in a fixed position, e.g. cradles or boosters	1/62	. for providing a predistortion of the signal in the transmitter and corresponding correction in the receiver, e.g. for improving the signal/noise ratio
1/3883	. . . Arrangements for mounting batteries or battery chargers	1/64	. . Volume compression or expansion arrangements
1/3888	. . . Arrangements for carrying or protecting transceivers	1/66	. for reducing bandwidth of signals; for improving efficiency of transmission ( <a href="#">H04B 1/68 takes precedence</a> )
<b>WARNING</b>		1/662	. . {using a time/frequency relationship, e.g. time compression or expansion}
Group <a href="#">H04B 1/3888</a> is impacted by reclassification into groups <a href="#">A45C 11/002</a> , <a href="#">A45C 11/003</a> , <a href="#">G06F 1/1629</a> and <a href="#">H04M 1/0203</a> .		1/665	. . {using psychoacoustic properties of the ear, e.g. masking effect}
All groups listed in this Warning should be considered in order to perform a complete search.		1/667	. . {using a division in frequency subbands ( <a href="#">for TV signals H04N 19/63</a> )}
2001/3894	. . {Waterproofing of transmission device}	1/68	. for wholly or partially suppressing the carrier or one side band
1/40	. . Circuits	1/69	. Spread spectrum techniques
1/401	. . . for selecting or indicating operating mode	2001/6904	. . {using code hopping}
		2001/6908	. . {using time hopping}
		2001/6912	. . {using chirp}
		2001/6916	. . {Related theory}
		1/692	. . Hybrid techniques using combinations of two or more spread spectrum techniques

1/707	. . .	using direct sequence modulation	1/7113	. . . . .	Determination of path profile
2001/70706	. . .	{using a code tracking loop, e.g. a delay locked loop}	1/7115	. . . . .	Constructive combining of multi-path signals, i.e. RAKE receivers
1/70712	. . .	{with demodulation by means of convolvers, e.g. of the SAW type (SAW convolvers in general <a href="#">G06G 7/195</a> )}	1/7117	. . . . .	Selection, re-selection, allocation or re-allocation of paths to fingers, e.g. timing offset control of allocated fingers
1/70718	. . .	{with asynchronous demodulation, i.e. not requiring code synchronisation}	1/712	. . . . .	Weighting of fingers for combining, e.g. amplitude control or phase rotation using an inner loop
2001/70724	. . .	{featuring pilot assisted reception}	1/713	. . .	using frequency hopping
1/7073	. . .	Synchronisation aspects	1/7136	. . .	Arrangements for generation of hop frequencies, e.g. using a bank of frequency sources, using continuous tuning or using a transform
1/70735	. . . .	{Code identification ( <a href="#">H04B 1/7083</a> takes precedence)}	2001/71362	. . . .	{using a bank of frequency sources}
1/7075	. . . .	with code phase acquisition	2001/71365	. . . .	{using continuous tuning of a single frequency source}
1/70751	. . . . .	{using partial detection ( <a href="#">H04B 1/70758</a> takes precedence)}	2001/71367	. . . .	{using a transform}
1/70752	. . . . .	{Partial correlation}	1/7143	. . .	Arrangements for generation of hop patterns
1/70753	. . . . .	{Partial phase search}	1/715	. . .	Interference-related aspects
1/70754	. . . . .	{Setting of search window, i.e. range of code offsets to be searched ( <a href="#">H04B 1/70758</a> takes precedence)}	2001/7152	. . . .	{with means for suppressing interference}
1/70755	. . . . .	{Setting of lock conditions, e.g. threshold}	2001/7154	. . . .	{with means for preventing interference}
1/70756	. . . . .	{Jumping within the code, i.e. masking or slewing ( <a href="#">H04B 1/70758</a> takes precedence)}	1/7156	. . .	Arrangements for sequence synchronisation
1/70757	. . . . .	{with increased resolution, i.e. higher than half a chip ( <a href="#">H04B 1/70758</a> takes precedence)}	2001/71563	. . . .	{Acquisition}
1/70758	. . . . .	{Multimode search, i.e. using multiple search strategies}	2001/71566	. . . .	{Tracking}
1/7077	. . . . .	Multi-step acquisition, e.g. multi-dwell, coarse-fine or validation	1/7163	. . .	using impulse radio
1/70775	. . . . .	{Multi-dwell schemes, i.e. multiple accumulation times}	1/71632	. . .	{Signal aspects ( <a href="#">H04B 1/7172</a> and <a href="#">H04B 1/7176</a> take precedence)}
1/708	. . . . .	Parallel implementation	1/71635	. . .	{Transmitter aspects ( <a href="#">H04B 1/7174</a> takes precedence)}
1/7083	. . . .	Cell search, e.g. using a three-step approach	1/71637	. . .	{Receiver aspects ( <a href="#">H04B 1/7183</a> takes precedence)}
1/7085	. . . .	using a code tracking loop, e.g. a delay-locked loop	1/717	. . .	Pulse-related aspects
2001/70855	. . . . .	{Dithering}	1/7172	. . . .	{Pulse shape (in general <a href="#">H04L 25/03834</a> )}
1/7087	. . . .	Carrier synchronisation aspects	1/7174	. . . .	{Pulse generation (in general <a href="#">H04L 25/03834</a> )}
1/709	. . .	Correlator structure	1/7176	. . .	Data mapping, e.g. modulation
1/7093	. . . .	Matched filter type	1/7183	. . .	Synchronisation
2001/70935	. . . . .	{using a bank of matched filters, e.g. Fast Hadamard Transform}	1/719	. . .	Interference-related aspects
1/7095	. . . .	Sliding correlator type	1/72	. . .	Circuits or components for simulating antennas, e.g. dummy antennas
1/7097	. . .	Interference-related aspects	1/74	. . .	for increasing reliability, e.g. using redundant or spare channels or apparatus {(replacing by standby devices for amplifiers <a href="#">H03F 1/52</a> , <a href="#">H03F 1/542</a> )}
1/71	. . . .	the interference being narrowband interference	1/745	. . .	{using by-passing or self-healing methods}
1/7101	. . . . .	{with estimation filters}	1/76	. . .	Pilot transmitters or receivers for control of transmission or for equalising
1/7102	. . . . .	{with transform to frequency domain}	<b>3/00</b>		<b>Line transmission systems (combined with near-field transmission systems <a href="#">H04B 5/00</a>)</b>
1/7103	. . . .	the interference being multiple access interference	3/02	. . .	Details
1/7105	. . . . .	Joint detection techniques, e.g. linear detectors	3/03	. . .	Hybrid circuits (for transceivers <a href="#">H04B 1/52</a> , <a href="#">H04B 1/58</a> )
1/71052	. . . . .	{using decorrelation matrix}	3/04	. . .	Control of transmission; Equalising
1/71055	. . . . .	{using minimum mean squared error [MMSE] detector}	3/06	. . .	by the transmitted signal
1/71057	. . . . .	{using maximum-likelihood sequence estimation [MLSE]}	3/08	. . . .	in negative-feedback path of line amplifier
1/7107	. . . . .	Subtractive interference cancellation	3/10	. . .	by pilot signal
1/71072	. . . . .	{Successive interference cancellation}	3/11	. . . .	using pilot wire ( <a href="#">H04B 3/12</a> takes precedence)
1/71075	. . . . .	{Parallel interference cancellation}	3/12	. . . .	in negative-feedback path of line amplifier
2001/71077	. . . . .	{Partial interference cancellation}	3/14	. . .	characterised by the equalising network used
1/711	. . . .	the interference being multi-path interference	3/141	. . . .	{using multiequalisers, e.g. bump, cosine, Bode}



- 3/142 . . . . {using echo-equalisers, e.g. transversal}
- 3/143 . . . . {using amplitude-frequency equalisers}
- 3/144 . . . . . {fixed equalizers}
- 3/145 . . . . . {variable equalisers}
- 3/146 . . . . {using phase-frequency equalisers}
- 3/147 . . . . . {fixed equalisers}
- 3/148 . . . . . {variable equalisers}
- 3/16 . . . characterised by the negative-impedance network used
- 3/18 . . . . wherein the network comprises semiconductor devices
- 3/20 . . Reducing echo effects or singing; Opening or closing transmitting path; Conditioning for transmission in one direction or the other
- 3/21 . . . using a set of bandfilters
- 3/23 . . . using a replica of transmitted signal in the time domain, e.g. echo cancellers
- 3/231 . . . . {Echo cancellers using readout of a memory to provide the echo replica}
- 3/232 . . . . {using phase shift, phase roll or frequency offset correction}
- 3/234 . . . . {using double talk detection}
- 3/235 . . . . {combined with adaptive equaliser}
- 3/237 . . . . {using two adaptive filters, e.g. for near end and for end echo cancelling}
- 3/238 . . . . {using initial training sequence}
- 3/26 . . Improving frequency characteristic by the use of loading coils
- 3/28 . . Reducing interference caused by currents induced in cable sheathing or armouring
- 3/30 . . Reducing interference caused by unbalanced currents in a normally balanced line
- 3/32 . . Reducing cross-talk, e.g. by compensating
- 3/34 . . . by systematic interconnection of lengths of cable during laying; by addition of balancing components to cable during laying
- 3/36 . . Repeater circuits ([H04B 3/58 takes precedence](#))
- 3/38 . . . for signals in two different frequency ranges transmitted in opposite directions over the same transmission path
- 3/40 . . Artificial lines; Networks simulating a line of certain length
- 3/42 . . Circuits for by-passing of ringing signals
- 3/44 . . Arrangements for feeding power to a repeater along the transmission line
- 3/46 . . Monitoring; Testing
- 3/462 . . . Testing group delay or phase shift, e.g. timing jitter
- 3/466 . . . . Testing attenuation in combination with at least one of group delay and phase shift
- 3/48 . . . Testing attenuation ([H04B 3/466 takes precedence](#))
- 3/487 . . . Testing crosstalk effects
- 3/493 . . . Testing echo effects or singing
- 3/50 . . Systems for transmission between fixed stations via two-conductor transmission lines ([H04B 3/54 takes precedence](#))
- 3/52 . . Systems for transmission between fixed stations via waveguides
- 3/54 . . Systems for transmission via power distribution lines
- 3/542 . . {the information being in digital form}
- 3/544 . . {Setting up communications; Call and signalling arrangements}
- 3/546 . . {Combination of signalling, telemetering, protection (circuits for remote indication of supply or distribution network condition [H02J 13/00](#))}
- 3/548 . . {the power on the line being DC (arrangements for feeding power [H04L 12/10](#); extracting feeding power from signals [H04L 25/02](#))}
- 3/56 . . Circuits for coupling, blocking, or by-passing of signals
- 3/58 . . Repeater circuits
- 3/60 . . Systems for communication between relatively movable stations, e.g. for communication with lift ([H04B 3/54 takes precedence](#))
- 5/00 Near-field transmission systems, e.g. inductive or capacitive transmission systems**
- WARNING**  
Group [H04B 5/00](#) is impacted by reclassification into groups [H04B 5/40](#), [H04B 5/43](#) and [H04B 5/45](#).  
All groups listed in this Warning should be considered in order to perform a complete search.
- 5/20 . . characterised by the transmission technique; characterised by the transmission medium
- WARNING**  
Groups [H04B 5/20](#), [H04B 5/22](#), [H04B 5/24](#), [H04B 5/26](#), [H04B 5/263](#), [H04B 5/266](#) and [H04B 5/28](#) are incomplete pending reclassification of documents from group [H04B 5/72](#).  
All groups listed in this Warning should be considered in order to perform a complete search.
- 5/22 . . Capacitive coupling
- 5/24 . . Inductive coupling
- 5/26 . . . using coils
- 5/263 . . . . {Multiple coils at either side}
- 5/266 . . . . {One coil at each side, e.g. with primary and secondary coils}
- 5/28 . . using the near field of leaky cables, e.g. of leaky coaxial cables
- 5/40 . . characterised by components specially adapted for near-field transmission
- WARNING**  
Groups [H04B 5/40](#) and [H04B 5/43](#) are incomplete pending reclassification of documents from group [H04B 5/00](#).  
Groups [H04B 5/00](#), [H04B 5/40](#) and [H04B 5/43](#) should be considered in order to perform a complete search.
- 5/43 . . Antennas

5/45 . . Transponders

**WARNING**

Group [H04B 5/45](#) is incomplete pending reclassification of documents from groups [H04B 5/00](#) and [H04B 5/72](#).

Groups [H04B 5/00](#), [H04B 5/72](#) and [H04B 5/45](#) should be considered in order to perform a complete search.

5/48 . . Transceivers

5/70 . specially adapted for specific purposes

**WARNING**

Group [H04B 5/70](#) is incomplete pending reclassification of documents from group [H04B 5/72](#).

Groups [H04B 5/72](#) and [H04B 5/70](#) should be considered in order to perform a complete search.

5/72 . . for local intradevice communication

**WARNING**

Group [H04B 5/72](#) is impacted by reclassification into groups [H04B 5/20](#), [H04B 5/22](#), [H04B 5/24](#), [H04B 5/26](#), [H04B 5/263](#), [H04B 5/266](#), [H04B 5/28](#), [H04B 5/45](#) and [H04B 5/70](#).

All groups listed in this Warning should be considered in order to perform a complete search.

5/73 . . for taking measurements, e.g. using sensing coils

5/75 . . for isolation purposes

5/77 . . for interrogation

5/79 . . for data transfer in combination with power transfer

**7/00 Radio transmission systems, i.e. using radiation field ([H04B 10/00](#), [H04B 15/00](#) take precedence)**

7/002 . {Reducing depolarization effects}

7/005 . Control of transmission; Equalising

7/01 . Reducing phase shift

7/015 . Reducing echo effects

7/02 . Diversity systems; Multi-antenna system, i.e. transmission or reception using multiple antennas ([RAKE receivers H04B 1/7115](#))

7/022 . . Site diversity; Macro-diversity (using two or more spaced independent antennas [H04B 7/04](#))

7/024 . . . Co-operative use of antennas of several sites, e.g. in co-ordinated multipoint or co-operative multiple-input multiple-output [MIMO] systems

7/026 . . . Co-operative diversity, e.g. using fixed or mobile stations as relays

7/028 . . {Spatial transmit diversity using a single antenna at the transmitter}

7/04 . . using two or more spaced independent antennas

**WARNING**

Group [H04B 7/04](#) is impacted by reclassification into groups [H04B 7/04013](#) and [H04B 7/04026](#).

Groups [H04B 7/04](#), [H04B 7/04013](#) and [H04B 7/04026](#) should be considered in order to perform a complete search.

7/04013 . . . {Intelligent reflective surfaces}

**WARNING**

Groups [H04B 7/04013](#) and [H04B 7/04026](#) are incomplete pending reclassification of documents from group [H04B 7/04](#).

Groups [H04B 7/04](#), [H04B 7/04013](#) and [H04B 7/04026](#) should be considered in order to perform a complete search.

7/04026 . . . . {with codebook-based beamforming}

7/0404 . . . the mobile station comprising multiple antennas, e.g. to provide uplink diversity

7/0408 . . . using two or more beams, i.e. beam diversity

7/0413 . . . MIMO systems

7/0417 . . . . Feedback systems

7/0421 . . . . . {utilizing implicit feedback, e.g. steered pilot signals}

7/0426 . . . . Power distribution

7/043 . . . . . {using best eigenmode, e.g. beam forming or beam steering}

7/0434 . . . . . {using multiple eigenmodes}

7/0439 . . . . . {utilizing channel inversion}

7/0443 . . . . . {utilizing "waterfilling" technique}

7/0447 . . . . . {utilizing uniform distribution}

7/0452 . . . . Multi-user MIMO systems

7/0456 . . . . Selection of precoding matrices or codebooks, e.g. using matrices antenna weighting

7/046 . . . . . {taking physical layer constraints into account}

7/0465 . . . . . {taking power constraints at power amplifier or emission constraints, e.g. constant modulus, into account}

7/0469 . . . . . {taking special antenna structures, e.g. cross polarized antennas into account}

7/0473 . . . . . {taking constraints in layer or codeword to antenna mapping into account}

7/0478 . . . . . {Special codebook structures directed to feedback optimisation}

**WARNING**

Group [H04B 7/0478](#) is impacted by reclassification into groups [H04B 7/0479](#), [H04B 7/048](#) and [H04B 7/0481](#).

All groups listed in this Warning should be considered in order to perform a complete search.

7/0479	. . . . .	{for multi-dimensional arrays, e.g. horizontal or vertical pre-distortion matrix index [PMI]}	7/0608	. . . . .	{Antenna selection according to transmission parameters}
		<b>WARNING</b>	7/061	. . . . .	{using feedback from receiving side}
		Group <a href="#">H04B 7/0479</a> is incomplete pending reclassification of documents from group <a href="#">H04B 7/0478</a> .	7/0613	. . . . .	{using simultaneous transmission ( <a href="#">H04B 7/0686</a> takes precedence)}
		Groups <a href="#">H04B 7/0478</a> and <a href="#">H04B 7/0479</a> should be considered in order to perform a complete search.	7/0615	. . . . .	{of weighted versions of same signal}
7/048	. . . . .	{using three or more PMIs}	7/0617	. . . . .	{for beam forming}
		<b>WARNING</b>	7/0619	. . . . .	{using feedback from receiving side (feedback signaling for adaptive modulation/coding <a href="#">H04L 1/0001</a> )}
		Group <a href="#">H04B 7/048</a> is incomplete pending reclassification of documents from group <a href="#">H04B 7/0478</a> .	7/0621	. . . . .	{Feedback content}
		Groups <a href="#">H04B 7/0478</a> and <a href="#">H04B 7/048</a> should be considered in order to perform a complete search.	7/0623	. . . . .	{Auxiliary parameters, e.g. power control [PCB] or not acknowledged commands [NACK], used as feedback information}
7/0481	. . . . .	{using subset selection of codebooks}	7/0626	. . . . .	{Channel coefficients, e.g. channel state information [CSI]}
		<b>WARNING</b>	7/0628	. . . . .	{Diversity capabilities}
		Group <a href="#">H04B 7/0481</a> is incomplete pending reclassification of documents from group <a href="#">H04B 7/0478</a> .	7/063	. . . . .	{Parameters other than those covered in groups <a href="#">H04B 7/0623</a> - <a href="#">H04B 7/0634</a> , e.g. channel matrix rank or transmit mode selection}
		Groups <a href="#">H04B 7/0478</a> and <a href="#">H04B 7/0481</a> should be considered in order to perform a complete search.	7/0632	. . . . .	{Channel quality parameters, e.g. channel quality indicator [CQI]}
7/0482	. . . . .	{Adaptive codebooks}	7/0634	. . . . .	{Antenna weights or vector/matrix coefficients}
7/0486	. . . . .	{taking channel rank into account}	7/0636	. . . . .	{Feedback format}
		<b>WARNING</b>	7/0639	. . . . .	{Using selective indices, e.g. of a codebook, e.g. pre-distortion matrix index [PMI] or for beam selection}
		Group <a href="#">H04B 7/0486</a> is impacted by reclassification into group <a href="#">H04B 7/0487</a> .	7/0641	. . . . .	{Differential feedback}
		Groups <a href="#">H04B 7/0486</a> and <a href="#">H04B 7/0487</a> should be considered in order to perform a complete search.	7/0643	. . . . .	{Feedback on request}
7/0487	. . . . .	{Codebooks having a nested structure}	7/0645	. . . . .	{Variable feedback}
		<b>WARNING</b>	7/0647	. . . . .	{Variable feedback rate}
		Group <a href="#">H04B 7/0487</a> is incomplete pending reclassification of documents from group <a href="#">H04B 7/0486</a> .	7/065	. . . . .	{Variable contents, e.g. long-term or short-short}
		Groups <a href="#">H04B 7/0486</a> and <a href="#">H04B 7/0487</a> should be considered in order to perform a complete search.	7/0652	. . . . .	{Feedback error handling}
7/0491	. . .	using two or more sectors, i.e. sector diversity	7/0654	. . . . .	{at the receiver, e.g. antenna verification at mobile station}
7/0495	. . .	using overlapping sectors in the same base station to implement MIMO for antennas	7/0656	. . . . .	{at the transmitter, e.g. error detection at base station}
7/06	. . .	at the transmitting station	7/0658	. . . . .	{Feedback reduction}
7/0602	. . . . .	{using antenna switching ( <a href="#">H04B 7/0686</a> takes precedence; antenna beam directivity switching <a href="#">H01Q 3/24</a> )}	7/066	. . . . .	{Combined feedback for a number of channels, e.g. over several subcarriers like in orthogonal frequency division multiplexing [OFDM]}
7/0604	. . . . .	{with predefined switching scheme}	7/0663	. . . . .	{using vector or matrix manipulations}
7/0606	. . . . .	{Random or pseudo-random switching scheme}	7/0665	. . . . .	{Feed forward of transmit weights to the receiver}
			7/0667	. . . . .	{of delayed versions of same signal (using space-time coding <a href="#">H04L 1/0618</a> )}
			7/0669	. . . . .	{using different channel coding between antennas (space-time coding <a href="#">H04L 1/0618</a> )}
			7/0671	. . . . .	{using different delays between antennas}
			7/0673	. . . . .	{using feedback from receiving side}
			7/0676	. . . . .	{using random or pseudo-random delays}
			7/0678	. . . . .	{using different spreading codes between antennas ( <a href="#">code allocation H04J 13/16</a> )}

7/068	. . . . .	{using space frequency diversity ( <a href="#">space-frequency coding H04L 1/0606</a> )}	7/0802	. . . . .	{using antenna selection ( <a href="#">H04B 7/0868</a> takes precedence; antenna beam directivity switching <a href="#">H01Q 3/24</a> )}
7/0682	. . . . .	{using phase diversity (e.g. phase sweeping)}	7/0805	. . . . .	{with single receiver and antenna switching ( <a href="#">H04B 7/0822</a> takes precedence)}
7/0684	. . . . .	{using different training sequences per antenna}	7/0808	. . . . .	{comparing all antennas before reception}
7/0686	. . . . .	{Hybrid systems, i.e. switching and simultaneous transmission}	7/0811	. . . . .	{during preamble or gap period}
7/0689	. . . . .	{using different transmission schemes, at least one of them being a diversity transmission scheme}	7/0814	. . . . .	{based on current reception conditions, e.g. switching to different antenna when signal level is below threshold}
7/0691	. . . . .	{using subgroups of transmit antennas}	7/0817	. . . . .	{with multiple receivers and antenna path selection}
7/0693	. . . . .	{switching off a diversity branch, e.g. to save power}	7/082	. . . . .	{selecting best antenna path}
7/0695	. . . . .	{using beam selection}	7/0822	. . . . .	{according to predefined selection scheme}
<b>WARNING</b>			7/0825	. . . . .	{with main and with auxiliary or diversity antennas}
Group <a href="#">H04B 7/0695</a> is impacted by reclassification into groups <a href="#">H04B 7/06952</a> , <a href="#">H04B 7/06954</a> , <a href="#">H04B 7/06956</a> , <a href="#">H04B 7/06958</a> , <a href="#">H04B 7/0696</a> , <a href="#">H04B 7/06962</a> , <a href="#">H04B 7/06964</a> , <a href="#">H04B 7/06966</a> and <a href="#">H04B 7/06968</a> .			7/0828	. . . . .	{with delay elements in antenna paths}
All groups listed in this Warning should be considered in order to perform a complete search.			7/0831	. . . . .	{Compensation of the diversity switching process for non-uniform properties or faulty operations of the switches used in the diversity switching process}
7/06952	. . . . .	{Selecting one or more beams from a plurality of beams, e.g. beam training, management or sweeping}	7/0834	. . . . .	{based on external parameters, e.g. subscriber speed or location}
<b>WARNING</b>			7/0837	. . . . .	{using pre-detection combining ( <a href="#">H04B 7/0868</a> takes precedence)}
Groups <a href="#">H04B 7/06952</a> , <a href="#">H04B 7/06954</a> , <a href="#">H04B 7/06956</a> , <a href="#">H04B 7/06958</a> , <a href="#">H04B 7/0696</a> , <a href="#">H04B 7/06962</a> , <a href="#">H04B 7/06964</a> , <a href="#">H04B 7/06966</a> and <a href="#">H04B 7/06968</a> are incomplete pending reclassification of documents from group <a href="#">H04B 7/0695</a> .			7/084	. . . . .	{Equal gain combining, only phase adjustments (antenna beam scanning or forming by phase or amplitude control <a href="#">H01Q 3/26</a> , e.g. phased arrays)}
All groups listed in this Warning should be considered in order to perform a complete search.			7/0842	. . . . .	{Weighted combining}
7/06954	. . . . .	{Sidelink beam training with support from third instance, e.g. the third instance being a base station}	7/0845	. . . . .	{per branch equalization, e.g. by an FIR-filter or RAKE receiver per antenna branch (rake receivers as such <a href="#">H04B 1/7115</a> )}
7/06956	. . . . .	{using a selection of antenna panels}	7/0848	. . . . .	{Joint weighting}
7/06958	. . . . .	{Multistage beam selection, e.g. beam refinement}	7/0851	. . . . .	{using training sequences or error signal (minimizing error signal <a href="#">H04B 7/0854</a> )}
7/0696	. . . . .	{Determining beam pairs}	7/0854	. . . . .	{using error minimizing algorithms, e.g. minimum mean squared error [MMSE], "cross-correlation" or matrix inversion}
7/06962	. . . . .	{Simultaneous selection of transmit [Tx] and receive [Rx] beams at both sides of a link}	7/0857	. . . . .	{using maximum ratio combining techniques, e.g. signal-to- interference ratio [SIR], received signal strenght indication [RSS]}
7/06964	. . . . .	{Re-selection of one or more beams after beam failure}	7/086	. . . . .	{using weights depending on external parameters, e.g. direction of arrival [DOA], predetermined weights or beamforming}
7/06966	. . . . .	{using beam correspondence; using channel reciprocity, e.g. downlink beam training based on uplink sounding reference signal [SRS]}	7/0862	. . . . .	{receiver computing weights based on information from the transmitter}
7/06968	. . . . .	{using quasi-colocation [QCL] between signals}	7/0865	. . . . .	{Independent weighting, i.e. weights based on own antenna reception parameters}
7/0697	. . . . .	{using spatial multiplexing}	7/0868	. . . . .	{Hybrid systems, i.e. switching and combining}
7/08	. . . . .	at the receiving station	7/0871	. . . . .	{using different reception schemes, at least one of them being a diversity reception scheme}
			7/0874	. . . . .	{using subgroups of receive antennas}



7/0877	. . . . .	{switching off a diversity branch, e.g. to save power}	7/15571	. . . . .	{by signal isolation, e.g. isolation by frequency or by antenna pattern, or by polarization}
7/088	. . . . .	{using beam selection}	7/15578	. . . . .	{by gain adjustment}
7/0882	. . . . .	{using post-detection diversity}	7/15585	. . . . .	{by interference cancellation}
7/0885	. . . . .	{with combination}	7/15592	. . . . .	{Adapting at the relay station communication parameters for supporting cooperative relaying, i.e. transmission of the same data via direct - and relayed path (cooperative diversity <a href="#">H04B 7/024</a> )}
7/0888	. . . . .	{with selection}			
7/0891	. . . . .	{Space-time diversity (rake receivers <a href="#">H04B 1/7115</a> ; space-time decoding <a href="#">H04L 1/0631</a> )}	7/165	. . . . .	employing angle modulation
7/0894	. . . . .	{using different delays between antennas}	7/17	. . . . .	employing pulse modulation, e.g. pulse code modulation
7/0897	. . . . .	{using beamforming per multi-path, e.g. to cope with different directions of arrival [DOA] at different multi-paths}	7/185	. . . . .	Space-based or airborne stations; {Stations for satellite systems} ( <a href="#">H04B 7/204</a> takes precedence)
7/10	. .	Polarisation diversity; Directional diversity	7/18502	. . . . .	{Airborne stations}
7/12	. .	Frequency diversity	7/18504	. . . . .	{Aircraft used as relay or high altitude atmospheric platform}
7/14	. .	Relay systems	7/18506	. . . . .	{Communications with or from aircraft, i.e. aeronautical mobile service}
7/145	. .	Passive relay systems	7/18508	. . . . .	{with satellite system used as relay, i.e. aeronautical mobile satellite service}
7/15	. .	Active relay systems	7/1851	. . . . .	{Systems using a satellite or space-based relay ( <a href="#">H04B 7/18508</a> , <a href="#">H04B 7/18521</a> take precedence; providing specific services <a href="#">H04B 7/18523</a> - <a href="#">H04B 7/18576</a> )}
7/155	. . .	Ground-based stations ( <a href="#">H04B 7/204</a> takes precedence)	7/18513	. . . . .	{Transmission in a satellite or space-based system}
7/15507	. . . . .	{Relay station based processing for cell extension or control of coverage area, (network planning with network coordinated processing with regard to cell extension <a href="#">H04W 16/26</a> ; network topologies using dedicated repeater stations <a href="#">H04W 84/047</a> ; terminal devices adapted for relaying to or from an other terminal <a href="#">H04W 88/04</a> )}	7/18515	. . . . .	{Transmission equipment in satellites or space-based relays}
7/15514	. . . . .	{for shadowing compensation (for satellite mobile telephony service systems <a href="#">H04B 7/18536</a> )}	7/18517	. . . . .	{Transmission equipment in earth stations}
7/15521	. . . . .	{combining by calculations packets received from different stations before transmitting the combined packets as part of network coding (network coding aspects for detection or prevention of errors in the information received <a href="#">H04L 1/0076</a> ; network traffic management with optimizing of information sizing, e.g. header compression, by using assembly and disassembly of packets <a href="#">H04W 28/065</a> )}	7/18519	. . . . .	{Operations control, administration or maintenance}
7/15528	. . . . .	{Control of operation parameters of a relay station to exploit the physical medium}	7/18521	. . . . .	{Systems of inter linked satellites, i.e. inter satellite service (for optical links between satellites <a href="#">H04B 10/118</a> )}
7/15535	. . . . .	{Control of relay amplifier gain (amplifier gain control in general <a href="#">H03G 3/00</a> ; gain control reducing self - or loop interference <a href="#">H04B 7/15578</a> )}	7/18523	. . . . .	{Satellite systems for providing broadcast service to terrestrial stations, i.e. broadcast satellite service (arrangements specially adapted for satellite broadcast receiving <a href="#">H04H 40/90</a> ; picture transmission via satellite <a href="#">H04N 1/00103</a> ; television transmission via satellite <a href="#">H04N 7/20</a> )}
7/15542	. . . . .	{Selecting at relay station its transmit and receive resources (selection of wireless resources by user or terminal <a href="#">H04W 72/02</a> ; arrangements affording multiple use of the transmission path by two-dimensional division of the resources <a href="#">H04L 5/0003</a> , or by allocating sub-channels <a href="#">H04L 5/003</a> )}	7/18526	. . . . .	{Arrangements for data linking, networking or transporting, or for controlling an end to end session (data switching networks <a href="#">H04L 12/00</a> )}
7/1555	. . . . .	{Selecting relay station antenna mode, e.g. selecting omnidirectional -, directional beams, selecting polarizations}	7/18528	. . . . .	{Satellite systems for providing two-way communications service to a network of fixed stations, i.e. fixed satellite service or very small aperture terminal [VSAT] system}
7/15557	. . . . .	{Selecting relay station operation mode, e.g. between amplify and forward mode, decode and forward mode or FDD - and TDD mode}	7/1853	. . . . .	{Satellite systems for providing telephony service to a mobile station, i.e. mobile satellite service (for selecting <a href="#">H04W</a> )}
7/15564	. . . . .	{Relay station antennae loop interference reduction}	7/18532	. . . . .	{Arrangements for managing transmission, i.e. for transporting data or a signalling message}
			7/18534	. . . . .	{for enhancing link reliability, e.g. satellites diversity}
			7/18536	. . . . .	{Shadowing compensation therefor, e.g. by using an additional terrestrial relay}

- 7/18539 . . . . . {Arrangements for managing radio, resources, i.e. for establishing or releasing a connection}
- 7/18541 . . . . . {for handover of resources}
- 7/18543 . . . . . {for adaptation of transmission parameters, e.g. power control (for detecting or preventing errors in the information received [H04L 1/00](#))}
- 7/18545 . . . . . {Arrangements for managing station mobility, i.e. for station registration or localisation}
- 7/18547 . . . . . {for geolocalisation of a station (position fixing by direction or distance determination [G01S 5/00](#))}
- 7/1855 . . . . . {using a telephonic control signal, e.g. propagation delay variation, Doppler frequency variation, power variation, beam identification}
- 7/18552 . . . . . {using a telephonic control signal and a second ranging satellite (determining absolute distances from a plurality of spaced points of known location [G01S 5/14](#))}
- 7/18554 . . . . . {using the position provided by an existing geolocalisation system}
- 7/18556 . . . . . {using a location database}
- 7/18558 . . . . . {Arrangements for managing communications, i.e. for setting up, maintaining or releasing a call between stations}
- 7/1856 . . . . . {for call routing}
- 7/18563 . . . . . {Arrangements for interconnecting multiple systems ([data switching networks H04L 12/00](#))}
- 7/18565 . . . . . {Arrangements for preventing unauthorised access or for providing user protection ([arrangements for secret or secure communication H04L 9/00](#))}
- 7/18567 . . . . . {Arrangements for providing additional services to the basic mobile satellite telephony service}
- 7/18569 . . . . . {Arrangements for system physical machines management, i.e. for construction operations control, administration, maintenance}
- 7/18571 . . . . . {for satellites; for fixed or mobile stations}
- 7/18573 . . . . . {for operations control, administration or maintenance}
- 7/18576 . . . . . {Satellite systems for providing narrowband data service to fixed or mobile stations, e.g. using a minisatellite, a microsatellite (for selecting [H04W](#))}
- 7/18578 . . . . . {Satellite systems for providing broadband data service to individual earth stations (for selecting [H04W](#); provisions for broadband connection, [H04Q 11/0478](#))}
- 7/1858 . . . . . {Arrangements for data transmission on the physical system, i.e. for data bit transmission between network components}
- 7/18582 . . . . . {Arrangements for data linking, i.e. for data framing, for error recovery, for multiple access}
- 7/18584 . . . . . {Arrangements for data networking, i.e. for data packet routing, for congestion control ([data switching networks H04L 12/00](#))}
- 7/18586 . . . . . {Arrangements for data transporting, e.g. for an end to end data transport or check}
- 7/18589 . . . . . {Arrangements for controlling an end to end session, i.e. for initialising, synchronising or terminating an end to end link}
- 7/18591 . . . . . {Arrangements for interconnecting multiple systems ([data switching networks H04L 12/00](#))}
- 7/18593 . . . . . {Arrangements for preventing unauthorised access or for providing user protection ([arrangements for secret or secure communication H04L 9/00](#))}
- 7/18595 . . . . . {Arrangements for adapting broadband applications to satellite systems}
- 7/18597 . . . . . {Arrangements for system physical machines management, i.e. for construction, operations control, administration, maintenance}
- 7/19 . . . . . Earth-synchronous stations
- 7/195 . . . . . Non-synchronous stations
- 7/204 . . . . . Multiple access
- 7/2041 . . . . . {Spot beam multiple access}
- 7/2043 . . . . . {Mixed mode, TDM and FDM systems}
- 7/2045 . . . . . {SS-FDMA, FDMA satellite switching}
- 7/2046 . . . . . {SS-TDMA, TDMA satellite switching}
- 7/2048 . . . . . {Frame structure, synchronisation or frame acquisition in SS-TDMA systems}
- 7/208 . . . . . Frequency-division multiple access {[FDMA]}
- 7/212 . . . . . Time-division multiple access {[TDMA]}
- 7/2121 . . . . . {Channels assignment to the different stations}
- 7/2123 . . . . . {Variable assignment, e.g. demand assignment}
- 7/2125 . . . . . {Synchronisation}
- 7/2126 . . . . . {using a reference station}
- 7/2128 . . . . . {Changing of the reference station}
- 7/216 . . . . . Code division or spread-spectrum multiple access {[CDMA, SSMA]}
- 7/22 . . . . . Scatter propagation systems {, e.g. ionospheric, tropospheric or meteor scatter}
- 7/24 . . . . . for communication between two or more posts ([wireless communication networks H04W](#))
- 7/26 . . . . . at least one of which is mobile
- 7/2603 . . . . . {Arrangements for wireless physical layer control ([H04B 7/2612](#) takes precedence)}
- 7/2606 . . . . . {Arrangements for base station coverage control, e.g. by using relays in tunnels}
- 7/2609 . . . . . {Arrangements for range control, e.g. by using remote antennas}
- 7/2612 . . . . . {Arrangements for wireless medium access control, e.g. by allocating physical layer transmission capacity ([H04B 7/2615](#) - [H04B 7/2643](#) take precedence; provision for broadband connection [H04Q 11/0478](#))}
- 7/2615 . . . . . {using hybrid frequency-time division multiple access [FDMA-TDMA]}

- 7/2618 . . . {using hybrid code-time division multiple access [CDMA-TDMA]}
- 7/2621 . . . {using frequency division multiple access [FDMA] ([H04B 7/2615 takes precedence](#))}
- 7/2625 . . . {using common wave}
- 7/2628 . . . {using code-division multiple access [CDMA] or spread spectrum multiple access [SSMA] ([H04B 7/2618 takes precedence](#))}
- 7/2631 . . . . {for broadband transmission}
- 7/2634 . . . . {for channel frequency control}
- 7/2637 . . . . {for logical channel control}
- 7/264 . . . . {for data rate control}
- 7/2643 . . . {using time-division multiple access [TDMA] ([H04B 7/2615](#), [H04B 7/2618 take precedence](#))}
- 7/2646 . . . . {for broadband transmission}
- 7/265 . . . . {for channel frequency control}
- 7/2653 . . . . {for logical channel control}
- 7/2656 . . . . {for structure of frame, burst}
- 7/2659 . . . . {for data rate control}
- 7/2662 . . . {Arrangements for Wireless System Synchronisation}
- 7/2665 . . . . {Arrangements for Wireless Frequency Division Multiple Access [FDMA] System Synchronisation}
- 7/2668 . . . . {Arrangements for Wireless Code-Division Multiple Access [CDMA] System Synchronisation, (for code acquisition [H04B 1/7075](#), for code tracking [H04B 1/7085](#))}
- 7/2671 . . . . {Arrangements for Wireless Time-Division Multiple Access [TDMA] System Synchronisation}
- 7/2675 . . . . . {Frequency synchronisation}
- 7/2678 . . . . . {Time synchronisation}
- 7/2681 . . . . . {Synchronisation of a mobile station with one base station}
- 7/2684 . . . . . {Synchronisation of a mobile station with more than one base station}
- 7/2687 . . . . . {Inter base stations synchronisation}
- 7/269 . . . . . {Master/slave synchronisation}
- 7/2693 . . . . . {Centralised synchronisation, i.e. using external universal time reference, e.g. by using a global positioning system [GPS] or by distributing time reference over the wireline network}
- 7/2696 . . . . . {Over the air autonomous synchronisation, e.g. by monitoring network activity ([H04B 7/2693 takes precedence](#))}
- 10/00** **Transmission systems employing electromagnetic waves other than radio-waves, e.g. infrared, visible or ultraviolet light, or employing corpuscular radiation, e.g. quantum communication**
- NOTE**  
In this group, non-optical transmission systems are classified in group [H04B 10/90](#).
- 10/03 . Arrangements for fault recovery
- 10/032 . . using working and protection systems ([H04J 14/0287 takes precedence](#))}
- 10/035 . . using loopbacks
- 10/038 . . using bypasses
- 10/07 . Arrangements for monitoring or testing transmission systems; Arrangements for fault measurement of transmission systems
- 10/071 . . using a reflected signal, e.g. using optical time domain reflectometers [OTDR]
- 10/073 . . using an out-of-service signal ([H04B 10/071 takes precedence](#))
- 10/0731 . . . {Testing or characterisation of optical devices, e.g. amplifiers}
- 10/075 . . using an in-service signal ([H04B 10/071 takes precedence](#))
- 10/077 . . . using a supervisory or additional signal
- 10/0771 . . . . {Fault location on the transmission path}
- 10/0773 . . . . {Network aspects, e.g. central monitoring of transmission parameters}
- 10/0775 . . . . {Performance monitoring and measurement of transmission parameters}
- 10/0777 . . . . {Monitoring line amplifier or line repeater equipment}
- 10/0779 . . . . {Monitoring line transmitter or line receiver equipment}
- 10/079 . . . using measurements of the data signal
- 10/0791 . . . . {Fault location on the transmission path}
- 10/0793 . . . . {Network aspects, e.g. central monitoring of transmission parameters}
- 10/0795 . . . . {Performance monitoring; Measurement of transmission parameters}
- 10/07951 . . . . . {Monitoring or measuring chromatic dispersion or PMD}
- 10/07953 . . . . . {Monitoring or measuring OSNR, BER or Q}
- 10/07955 . . . . . {Monitoring or measuring power}
- 10/07957 . . . . . {Monitoring or measuring wavelength}
- 10/0797 . . . . {Monitoring line amplifier or line repeater equipment}
- 10/0799 . . . . {Monitoring line transmitter or line receiver equipment}
- 10/11 . Arrangements specific to free-space transmission, i.e. transmission through air or vacuum
- 10/112 . . Line-of-sight transmission over an extended range
- 10/1121 . . . {One-way transmission}
- 10/1123 . . . {Bidirectional transmission}
- 10/1125 . . . . {using a single common optical path}
- 10/1127 . . . . {using two distinct parallel optical paths}
- 10/1129 . . . {Arrangements for outdoor wireless networking of information}
- 10/114 . . Indoor or close-range type systems
- 10/1141 . . . {One-way transmission}
- 10/1143 . . . {Bidirectional transmission}
- 10/1149 . . . {Arrangements for indoor wireless networking of information}
- 10/116 . . . Visible light communication
- 10/118 . . specially adapted for satellite communication
- 10/25 . Arrangements specific to fibre transmission
- 10/2507 . . for the reduction or elimination of distortion or dispersion
- 10/25073 . . . {using spectral equalisation, e.g. spectral filtering}
- 10/25077 . . . {using soliton propagation}
- 10/2513 . . . due to chromatic dispersion
- 10/25133 . . . . {including a lumped electrical or optical dispersion compensator ([H04B 10/2519](#), [H04B 10/2525 takes precedence](#))}

- 10/25137 . . . . {using pulse shaping at the transmitter, e.g. pre-chirping or dispersion supported transmission [DST]}
- 10/2519 . . . . using Bragg gratings
- 10/2525 . . . . using dispersion-compensating fibres
- 10/25253 . . . . . {with dispersion management, i.e. using a combination of different kind of fibres in the transmission system}
- 10/2531 . . . . using spectral inversion
- 10/2537 . . . due to scattering processes, e.g. Raman or Brillouin scattering
- 10/2543 . . . due to fibre non-linearities, e.g. Kerr effect
- 10/255 . . . . Self-phase modulation [SPM]
- 10/2557 . . . . Cross-phase modulation [XPM]
- 10/2563 . . . . Four-wave mixing [FWM]
- 10/2569 . . . due to polarisation mode dispersion [PMD]
- 10/2572 . . . {due to forms of polarisation-dependent distortion other than PMD}
- 10/2575 . . Radio-over-fibre, e.g. radio frequency signal modulated onto an optical carrier
- 10/25751 . . . {Optical arrangements for CATV or video distribution (adaptations of television systems for optical transmission [H04N 7/22](#))}
- 10/25752 . . . {Optical arrangements for wireless networks}
- 10/25753 . . . . {Distribution optical network, e.g. between a base station and a plurality of remote units}
- 10/25754 . . . . . {Star network topology}
- 10/25755 . . . . . {Ring network topology}
- 10/25756 . . . . . {Bus network topology}
- 10/25758 . . . . {between a central unit and a single remote unit by means of an optical fibre}
- 10/25759 . . . . . {Details of the reception of RF signal or the optical conversion before the optical fibre}
- 10/2581 . . Multimode transmission
- 10/2587 . . using a single light source for multiple stations
- 10/2589 . . {Bidirectional transmission}
- 10/25891 . . . {Transmission components ([H04B 10/40](#) takes precedence)}
- 10/27 . . Arrangements for networking
- 10/271 . . {Combination of different networks, e.g. star and ring configuration in the same network or two ring networks interconnected}
- 10/272 . . Star-type networks {or tree-type networks}
- 10/2725 . . . {Star-type networks without a headend}
- 10/275 . . Ring-type networks
- 10/2755 . . . {Ring-type networks with a headend}
- 10/278 . . Bus-type networks
- 10/29 . . Repeaters
- 10/291 . . in which processing or amplification is carried out without conversion of the main signal from optical form
- 10/2912 . . . {characterised by the medium used for amplification or processing}
- 10/2914 . . . . {using lumped semiconductor optical amplifiers [SOA]}
- 10/2916 . . . . {using Raman or Brillouin amplifiers}
- 10/293 . . . Signal power control
- 10/2931 . . . . {using AGC ([H04B 10/294](#) takes precedence)}
- 10/2933 . . . . {considering the whole optical path}
- 10/2935 . . . . . {with a cascade of amplifiers}
- 10/2937 . . . . . {Systems with a repeater placed only at the beginning or the end of the system, i.e. repeaterless systems, e.g. systems with only post and pre-amplification}
- 10/2939 . . . . . {Network aspects}
- 10/294 . . . . in a multiwavelength system, e.g. gain equalisation
- 10/2941 . . . . . {using an equalising unit, e.g. a filter ([H04B 10/296](#) takes precedence)}
- 10/2942 . . . . . {using automatic gain control [AGC] ([H04B 10/296](#) takes precedence)}
- 10/296 . . . . . Transient power control, e.g. due to channel add/drop or rapid fluctuations in the input power
- 10/297 . . . Bidirectional amplification
- 10/2971 . . . . {A single amplifier for both directions}
- 10/2972 . . . . {Each direction being amplified separately}
- 10/298 . . . {Two-way repeaters, i.e. repeaters amplifying separate upward and downward lines}
- 10/299 . . . Signal waveform processing, e.g. reshaping or retiming
- 10/40 . Transceivers
- 10/43 . . using a single component as both light source and receiver, e.g. using a photoemitter as a photoreceiver
- 10/50 . Transmitters
- 10/501 . . {Structural aspects}
- 10/502 . . . {LED transmitters}
- 10/503 . . . {Laser transmitters}
- 10/504 . . . . {using direct modulation}
- 10/505 . . . . {using external modulation}
- 10/5051 . . . . . {using a series, i.e. cascade, combination of modulators}
- 10/5053 . . . . . {using a parallel, i.e. shunt, combination of modulators}
- 10/5055 . . . . . {using a pre-coder}
- 10/5057 . . . . . {using a feedback signal generated by analysing the optical output}
- 10/50572 . . . . . {to control the modulating signal amplitude including amplitude distortion}
- 10/50575 . . . . . {to control the modulator DC bias}
- 10/50577 . . . . . {to control the phase of the modulating signal}
- 10/5059 . . . . . {using a feed-forward signal generated by analysing the optical or electrical input}
- 10/50593 . . . . . {to control the modulating signal amplitude including amplitude distortion}
- 10/50595 . . . . . {to control the modulator DC bias}
- 10/50597 . . . . . {to control the phase of the modulating signal}
- 10/506 . . . {Multiwavelength transmitters}
- 10/508 . . Pulse generation, e.g. generation of solitons
- 10/516 . . Details of coding or modulation
- 10/5161 . . . {Combination of different modulation schemes}
- 10/5162 . . . {Return-to-zero modulation schemes}
- 10/5165 . . . {Carrier suppressed; Single sideband; Double sideband or vestigial}
- 10/5167 . . . {Duo-binary; Alternative mark inversion; Phase shaped binary transmission}
- 10/524 . . . Pulse modulation



10/532	. . .	Polarisation modulation	10/673	. . . . .	{using an optical preamplifier}
10/54	. . .	Intensity modulation	10/674	. . . . .	{using a variable optical attenuator}
10/541	. . . .	{Digital intensity or amplitude modulation}	10/675	. . . . .	{for controlling the optical bandwidth of the input signal, e.g. spectral filtering}
10/548	. . .	Phase or frequency modulation	10/676	. . . .	{for all-optical demodulation of the input optical signal}
10/556	. . . .	Digital modulation, e.g. differential phase shift keying [DPSK] or frequency shift keying [FSK]	10/677	. . . . .	{for differentially modulated signal, e.g. DPSK signals}
10/5561	. . . . .	{Digital phase modulation}	10/69	. . .	Electrical arrangements in the receiver
10/5563	. . . . .	{Digital frequency modulation}	10/691	. . . .	{Arrangements for optimizing the photodetector in the receiver}
10/564	. .	Power control	10/6911	. . . . .	{Photodiode bias control, e.g. for compensating temperature variations}
10/572	. .	Wavelength control	10/693	. . . .	{Arrangements for optimizing the preamplifier in the receiver}
10/58	. .	Compensation for non-linear transmitter output	10/6931	. . . . .	{Automatic gain control of the preamplifier}
10/588	. . .	in external modulation systems	10/6932	. . . . .	{Bandwidth control of bit rate adaptation}
10/60	. .	Receivers	10/6933	. . . . .	{Offset control of the differential preamplifier}
10/61	. .	Coherent receivers	10/695	. . . .	{Arrangements for optimizing the decision element in the receiver, e.g. by using automatic threshold control}
10/612	. . .	{for optical signals modulated with a format different from binary or higher-order PSK [X-PSK], e.g. QAM, DPSK, FSK, MSK, ASK}	10/697	. . . .	{Arrangements for reducing noise and distortion}
10/613	. . .	{including phase diversity, e.g., having in-phase and quadrature branches, as in QPSK coherent receivers}	10/6971	. . . . .	{using equalisation}
10/614	. . .	{comprising one or more polarization beam splitters, e.g. polarization multiplexed [PolMux] X-PSK coherent receivers, polarization diversity heterodyne coherent receivers (H04J 14/06 takes precedence)}	10/6972	. . . . .	{using passive filtering}
10/615	. . .	{Arrangements affecting the optical part of the receiver}	10/6973	. . . . .	{using noise matching networks}
10/6151	. . . .	{comprising a polarization controller at the receiver's input stage}	10/70	. .	Photonic quantum communication
10/616	. . .	{Details of the electronic signal processing in coherent optical receivers}	10/80	. .	Optical aspects relating to the use of optical transmission for specific applications, not provided for in groups H04B 10/03 - H04B 10/70, e.g. optical power feeding or optical transmission through water
10/6161	. . . .	{Compensation of chromatic dispersion}	10/801	. .	{using optical interconnects, e.g. light coupled isolators, circuit board interconnections}
10/6162	. . . .	{Compensation of polarization related effects, e.g., PMD, PDL}	10/802	. . .	{for isolation, e.g. using optocouplers}
10/6163	. . . .	{Compensation of non-linear effects in the fiber optic link, e.g. self-phase modulation [SPM], cross-phase modulation [XPM], four wave mixing [FWM]}	10/803	. . .	{Free space interconnects, e.g. between circuit boards or chips}
10/6164	. . . .	{Estimation or correction of the frequency offset between the received optical signal and the optical local oscillator}	10/806	. .	{Arrangements for feeding power}
10/6165	. . . .	{Estimation of the phase of the received optical signal, phase error estimation or phase error correction}	10/807	. . .	{Optical power feeding, i.e. transmitting power using an optical signal}
10/6166	. . . .	{Polarisation demultiplexing, tracking or alignment of orthogonal polarisation components}	10/808	. . .	{Electrical power feeding of an optical transmission system}
10/63	. . .	Homodyne {, i.e. coherent receivers where the local oscillator is locked in frequency and phase to the carrier signal}	10/85	. .	Protection from unauthorised access, e.g. eavesdrop protection
10/64	. . .	Heterodyne {, i.e. coherent receivers where, after the opto-electronic conversion, an electrical signal at an intermediate frequency [IF] is obtained}	10/90	. .	Non-optical transmission systems, e.g. transmission systems employing non-photonic corpuscular radiation
10/65	. . .	{Intradyne, i.e. coherent receivers with a free running local oscillator having a frequency close but not phase-locked to the carrier signal}	11/00	<b>Transmission systems employing sonic, ultrasonic or infrasonic waves</b>	
10/66	. .	Non-coherent receivers, e.g. using direct detection	13/00	<b>Transmission systems characterised by the medium used for transmission, not provided for in groups H04B 3/00 - H04B 11/00</b>	
10/67	. . .	Optical arrangements in the receiver	13/005	. .	{Transmission systems in which the medium consists of the human body}
10/671	. . . .	{for controlling the input optical signal}	13/02	. .	Transmission systems in which the medium consists of the earth or a large mass of water thereon, e.g. earth telegraphy
10/672	. . . . .	{for controlling the power of the input optical signal}	14/00	<b>Transmission systems not characterised by the medium used for transmission (details thereof H04B 1/00)</b>	



14/002	. {characterised by the use of a carrier modulation (using subcarrier modulation <a href="#">H04B 14/08</a> )}	17/15	. . Performance testing
14/004	. . {Amplitude modulation}		<b>WARNING</b>
14/006	. . {Angle modulation}		Group <a href="#">H04B 17/15</a> is impacted by reclassification into group <a href="#">H04B 17/191</a> .
14/008	. . {Polarisation modulation}		Groups <a href="#">H04B 17/15</a> and <a href="#">H04B 17/191</a> should be considered in order to perform a complete search.
14/02	. characterised by the use of pulse modulation (in radio transmission relays <a href="#">H04B 7/17</a> )		
14/023	. . {using pulse amplitude modulation}	17/16	. . . Test equipment located at the transmitter
14/026	. . {using pulse time characteristics modulation, e.g. width, position, interval}	17/17	. . . Detection of non-compliance or faulty performance, e.g. response deviations ( <a href="#">H04B 17/18</a> takes precedence)
14/04	. . using pulse code modulation	17/18	. . . Monitoring during normal operation
14/042	. . . {Special circuits, e.g. comparators}	17/19	. . . Self-testing arrangements
14/044	. . . {Sample and hold circuits (in general <a href="#">G11C 27/02</a> )}	17/191	. . . {Over-the-air testing}
14/046	. . . {Systems or methods for reducing noise or bandwidth}		<b>WARNING</b>
14/048	. . . . {Non linear compression or expansion}		Group <a href="#">H04B 17/191</a> is incomplete pending reclassification of documents from group <a href="#">H04B 17/15</a> .
14/06	. . using differential modulation, e.g. delta modulation		Groups <a href="#">H04B 17/15</a> and <a href="#">H04B 17/191</a> should be considered in order to perform a complete search.
14/062	. . . {using delta modulation or one-bit differential modulation [1DPCM]}		
14/064	. . . . {with adaptive feedback}		
14/066	. . . {using differential modulation with several bits [NDPCM]}		
14/068	. . . . {with adaptive feedback}	17/20	. of receivers
14/08	. characterised by the use of a sub-carrier		<b>WARNING</b>
<b>15/00</b>	<b>Suppression or limitation of noise or interference (by means associated with receiver <a href="#">H04B 1/10</a>)</b>		Group <a href="#">H04B 17/20</a> is impacted by reclassification into groups <a href="#">H04B 17/201</a> , <a href="#">H04B 17/202</a> , <a href="#">H04B 17/203</a> , <a href="#">H04B 17/204</a> , <a href="#">H04B 17/22</a> , <a href="#">H04B 17/221</a> , <a href="#">H04B 17/25</a> , <a href="#">H04B 17/252</a> , <a href="#">H04B 17/253</a> , <a href="#">H04B 17/254</a> and <a href="#">H04B 17/255</a> .
15/005	. {Reducing noise, e.g. humm, from the supply}		All groups listed in this Warning should be considered in order to perform a complete search.
15/02	. Reducing interference from electric apparatus by means located at or near the interfering apparatus		
15/025	. . {Reducing interference from ignition apparatus of fuel engines (cables with high resistance <a href="#">H01B</a> )}		
15/04	. . the interference being caused by substantially sinusoidal oscillations, e.g. in a receiver or in a tape-recorder		
15/06	. . . by local oscillators of receivers	17/201	. . {for measurement of specific parameters of the receiver or components thereof}
<b>17/00</b>	<b>Monitoring; Testing (of line transmission systems <a href="#">H04B 3/46</a>; arrangements for monitoring or testing transmission systems employing electromagnetic waves other than radio waves <a href="#">H04B 10/07</a>)</b>		<b>WARNING</b>
17/0082	. {using service channels; using auxiliary channels}		Groups <a href="#">H04B 17/201</a> , <a href="#">H04B 17/202</a> , <a href="#">H04B 17/203</a> and <a href="#">H04B 17/204</a> are incomplete pending reclassification of documents from group <a href="#">H04B 17/20</a> .
17/0085	. . {using test signal generators}		All groups listed in this Warning should be considered in order to perform a complete search.
17/0087	. . {using auxiliary channels or channel simulators}		
17/10	. of transmitters		
17/101	. . {for measurement of specific parameters of the transmitter or components thereof}	17/202	. . . {Power received at the antenna}
17/102	. . . {Power radiated at antenna}	17/203	. . . {Receiver sensitivity}
17/103	. . . {Reflected power, e.g. return loss}	17/204	. . . {of interfering signals, e.g. passive intermodulation}
17/104	. . . {of other parameters, e.g. DC offset, delay or propagation times}	17/21	. . for calibration; for correcting measurements
17/11	. . for calibration		<b>WARNING</b>
17/12	. . . of transmit antennas, e.g. of the amplitude or phase		Group <a href="#">H04B 17/21</a> is impacted by reclassification into groups <a href="#">H04B 17/22</a> and <a href="#">H04B 17/221</a> .
17/13	. . . of power amplifiers, e.g. gain or non-linearity		Groups <a href="#">H04B 17/21</a> , <a href="#">H04B 17/22</a> and <a href="#">H04B 17/221</a> should be considered in order to perform a complete search.
17/14	. . . of the whole transmission and reception path, e.g. self-test loop-back		

- 17/22 . . . {for calibration of the receiver components}

**WARNING**

Groups [H04B 17/22](#) and [H04B 17/221](#) are incomplete pending reclassification of documents from groups [H04B 17/20](#) and [H04B 17/21](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 17/221 . . . . {of receiver antennas, e.g. as to amplitude or phase}

- 17/23 . . Indication means, e.g. displays, alarms, audible means

- 17/24 . . with feedback of measurements to the transmitter

- 17/25 . . {taking multiple measurements}

**WARNING**

Groups [H04B 17/25](#), [H04B 17/252](#), [H04B 17/253](#), [H04B 17/254](#) and [H04B 17/255](#) are incomplete pending reclassification of documents from group [H04B 17/20](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 17/252 . . . {measuring signals from different transmission points or directions of arrival, e.g. in multi RAT or dual connectivity}

- 17/253 . . . {measuring at different locations or reception points}

- 17/254 . . . {measuring at different reception times}

- 17/255 . . . {measuring at different states of transmission, e.g. active or idle; measuring at different measurement rates; measuring with different measurement schedules}

- 17/26 . . using historical data, averaging values or statistics

- 17/27 . . for locating or positioning the transmitter

- 17/29 . . Performance testing

**WARNING**

Group [H04B 17/29](#) is impacted by reclassification into groups [H04B 17/294](#), [H04B 17/295](#), [H04B 17/296](#) and [H04B 17/297](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 17/294 . . . {with test equipment located at the receiver}

**WARNING**

Group [H04B 17/294](#) is incomplete pending reclassification of documents from group [H04B 17/29](#).

Groups [H04B 17/29](#) and [H04B 17/294](#) should be considered in order to perform a complete search.

- 17/295 . . . {Detection of non-compliance or faulty performance, e.g. response deviations (monitoring during normal operations [H04B 17/296](#))}

**WARNING**

Group [H04B 17/295](#) is incomplete pending reclassification of documents from group [H04B 17/29](#).

Groups [H04B 17/29](#) and [H04B 17/295](#) should be considered in order to perform a complete search.

- 17/296 . . . {Monitoring performance during normal operation}

**WARNING**

Group [H04B 17/296](#) is incomplete pending reclassification of documents from group [H04B 17/29](#).

Groups [H04B 17/29](#) and [H04B 17/296](#) should be considered in order to perform a complete search.

- 17/297 . . . {Self-testing arrangements}

**WARNING**

Group [H04B 17/297](#) is incomplete pending reclassification of documents from group [H04B 17/29](#).

Groups [H04B 17/29](#) and [H04B 17/297](#) should be considered in order to perform a complete search.

- 17/30 . . of propagation channels

- 17/309 . . Measuring or estimating channel quality parameters

**WARNING**

Group [H04B 17/309](#) is impacted by reclassification into groups [H04B 17/346](#) and [H04B 17/347](#).

Groups [H04B 17/309](#), [H04B 17/346](#) and [H04B 17/347](#) should be considered in order to perform a complete search.

- 17/318 . . . Received signal strength

**WARNING**

Group [H04B 17/318](#) is impacted by reclassification into group [H04B 17/328](#).

Groups [H04B 17/318](#) and [H04B 17/328](#) should be considered in order to perform a complete search.

- 17/327 . . . . Received signal code power [RSCP]

- 17/328 . . . . {Reference signal received power [RSRP]; Reference signal received quality [RSRQ]}

**WARNING**

Group [H04B 17/328](#) is incomplete pending reclassification of documents from group [H04B 17/318](#).

Groups [H04B 17/318](#) and [H04B 17/328](#) should be considered in order to perform a complete search.

17/336	. . . Signal-to-interference ratio [SIR] or carrier-to-interference ratio [CIR]	2201/70702	. . . Intercell-related aspects
17/345	. . . Interference values ({ <a href="#">signal-to-interference ratio [SIR]</a> or <a href="#">carrier-to-interference ratio [CIR]</a> ) <a href="#">H04B 17/336</a> )	2201/70703	. . . using multiple or variable rates
17/346	. . . { <a href="#">Noise values (signal-to-interference ratio [SIR] or carrier-to-interference ratio [CIR] <a href="#">H04B 17/336</a>)</a> }	2201/70705	. . . . Rate detection
<b>WARNING</b>		2201/70706	. . . with means for reducing the peak-to-average power ratio
Group <a href="#">H04B 17/346</a> is incomplete pending reclassification of documents from group <a href="#">H04B 17/309</a> .		2201/70707	. . . Efficiency-related aspects
Groups <a href="#">H04B 17/309</a> and <a href="#">H04B 17/346</a> should be considered in order to perform a complete search.		2201/70709	. . . . with discontinuous detection
17/347	. . . { <a href="#">Path loss</a> }	2201/7071	. . . . with dynamic control of receiver resources
<b>WARNING</b>		2201/70711	. . . . . with modular structure
Group <a href="#">H04B 17/347</a> is incomplete pending reclassification of documents from group <a href="#">H04B 17/309</a> .		2201/70713	. . . . Reducing computational requirements
Groups <a href="#">H04B 17/309</a> and <a href="#">H04B 17/347</a> should be considered in order to perform a complete search.		2201/70714	. . . . Reducing hardware requirements
17/354	. . . Adjacent channel leakage power	2201/70715	. . . with application-specific features
17/364	. . . Delay profiles	2201/70716	. . . Quadrature
17/373	. . Predicting channel quality ({ <a href="#">or other radio frequency [RF]</a> ) parameters	2201/70718	. . . Particular systems or standards
17/382	. . for resource allocation, admission control or handover	2201/70719	. . . . CDMA2000
17/391	. . Modelling the propagation channel	2201/7072	. . . . HDR
17/3911	. . . { <a href="#">Fading models or fading generators</a> }	2201/70722	. . . . HSDPA/HSUPA
17/3912	. . . { <a href="#">Simulation models, e.g. distribution of spectral power density or received signal strength indicator [RSSI] for a given geographic region</a> }	2201/70723	. . . . . Multi-carrier HSPA
17/3913	. . . { <a href="#">Predictive models, e.g. based on neural network models</a> }	2201/70724	. . . . . UMTS
17/40	. of relay systems	2201/70726	. . . . Asynchronous CDMA
17/401	. . { <a href="#">with selective localization</a> }	2201/70727	. . . using fast Fourier transform
17/402	. . . { <a href="#">using different frequencies</a> }	2201/70728	. . . Frequency aspects
17/403	. . . . { <a href="#">generated by local oscillators</a> }	2201/7073	. . . Direct sequence modulation synchronisation
17/404	. . . . { <a href="#">selected by local filters</a> }	2201/70733	. . . . 2D search
17/405	. . . . { <a href="#">generated by local multipliers, dividers, modulators</a> }	2201/70736	. . . . DSA
17/406	. . . { <a href="#">using coded addresses</a> }	2201/7097	. . . Direct sequence modulation interference
17/407	. . { <a href="#">without selective localization</a> }	2201/709709	. . . . Methods of preventing interference
17/408	. . . { <a href="#">using successive loop-backs</a> }	2201/709718	. . . . Determine interference
17/409	. . . { <a href="#">by means of resistance, voltage or current measurement</a> }	2201/709727	. . . . GRAKE type RAKE receivers
<b>2201/00</b>	<b>Indexing scheme relating to details of transmission systems not covered by a single group of <a href="#">H04B 3/00</a> - <a href="#">H04B 13/00</a></b>	2201/709736	. . . . Hybrid interference mitigation schemes
2201/69	. Orthogonal indexing scheme relating to spread spectrum techniques in general	2201/709745	. . . . Iterative interference mitigation schemes
2201/692	. . Cognitive radio	2201/709754	. . . . Blind joint detection
2201/694	. . WPAN	2201/709763	. . . . Joint detection using feedback
2201/696	. . relating to Dowlink	2201/709772	. . . . Joint detection using feedforward
2201/698	. . relating to Uplink	2201/709781	. . . . Linear detectors for joint detection
2201/707	. . relating to direct sequence modulation	2201/70979	. . . . Fat finger issues in RAKE receivers
2201/70701	. . . featuring pilot assisted reception	2201/713	. . Frequency hopping
		2201/71307	. . . Partial band interference
		2201/71315	. . . Wide band interference
		2201/71323	. . . Adaptive systems
		2201/7133	. . . Asymmetric systems
		2201/71338	. . . Asynchronous systems
		2201/71346	. . . Bluetooth
		2201/71353	. . . Fast frequency hopping
		2201/71361	. . . Slow frequency hopping
		2201/71369	. . . OFCHM
		2201/71376	. . . Threshold
		2201/71384	. . . Look-up tables
		2201/7163	. . Orthogonal indexing scheme relating to impulse radio
		2201/71632	. . . Diversity
		2201/71634	. . . Applied to ranging
		2201/71636	. . . Transmitted reference
		2201/71638	. . . Spectrum issues
<b>2203/00</b>	<b>Indexing scheme relating to line transmission systems</b>		
2203/54	. Aspects of powerline communications not already covered by <a href="#">H04B 3/54</a> and its subgroups		
2203/5404	. . Methods of transmitting or receiving signals via power distribution lines		
2203/5408	. . . using protocols		

- 2203/5412 . . . by modifying wave form of the power source
- 2203/5416 . . . by adding signals to the wave form of the power source
- 2203/542 . . . using zero crossing information
- 2203/5425 . . . improving S/N by matching impedance, noise reduction, gain control
- 2203/5429 . . Applications for powerline communications
- 2203/5433 . . . Remote metering
- 2203/5437 . . . Wired telephone
- 2203/5441 . . . Wireless systems or telephone
- 2203/5445 . . . Local network
- 2203/545 . . . Audio/video application, e.g. interphone
- 2203/5454 . . . Adapter and plugs
- 2203/5458 . . . Monitor sensor; Alarm systems
- 2203/5462 . . Systems for power line communications
- 2203/5466 . . . using three phases conductors
- 2203/547 . . . via DC power distribution
- 2203/5475 . . . adapted for drill or well combined with data transmission
- 2203/5479 . . . using repeaters
- 2203/5483 . . . using coupling circuits
- 2203/5487 . . . . cables
- 2203/5491 . . . using filtering and bypassing
- 2203/5495 . . . having measurements and testing channel
- 2210/00 Indexing scheme relating to optical transmission systems**
- 2210/003 . Devices including multiple stages, e.g., multi-stage optical amplifiers or dispersion compensators
- 2210/006 . Devices for generating or processing an RF signal by optical means
- 2210/07 . Monitoring an optical transmission system using a supervisory signal
- 2210/071 . . using alarms
- 2210/072 . . using an overhead signal
- 2210/074 . . using a superposed, over-modulated signal
- 2210/075 . . using a pilot tone
- 2210/077 . . using a separate fibre
- 2210/078 . . using a separate wavelength
- 2210/08 . Shut-down or eye-safety
- 2210/25 . Distortion or dispersion compensation
- 2210/252 . . after the transmission line, i.e. post-compensation
- 2210/254 . . before the transmission line, i.e. pre-compensation
- 2210/256 . . at the repeater, i.e. repeater compensation
- 2210/258 . . treating each wavelength or wavelength band separately
- 2210/516 . Optical conversion of optical modulation formats, e.g., from optical ASK to optical PSK
- 2210/517 . Optical NRZ to RZ conversion, or vice versa
- 2215/00 Reducing interference at the transmission system level**
- 2215/061 . Reduction of burst noise, e.g. in TDMA systems
- 2215/062 . . by inhibiting burst transmission
- 2215/063 . . by smoothing the transmission power envelope
- 2215/064 . Reduction of clock or synthesizer reference frequency harmonics
- 2215/065 . . by changing the frequency of clock or reference frequency
- 2215/066 . . by stopping a clock generator
- 2215/067 . . by modulation dispersion
- 2215/068 . . by avoiding a reception frequency range
- 2215/069 . Reduction of switch mode power supply ripple