

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINES OR PUMPS

F01 MACHINES OR ENGINES IN GENERAL; ENGINE PLANTS IN GENERAL; STEAM ENGINES

F01L CYCLICALLY OPERATING VALVES FOR MACHINES OR ENGINES

NOTES

1. Groups [F01L 1/00](#) - [F01L 13/00](#) cover only valve-gear or valve arrangements without provision for variable fluid distribution.
2. Valve gear or valve arrangements specially adapted for steam engines are covered by groups [F01L 15/00](#) - [F01L 35/00](#).
3. Valve-gear arrangements specially adapted for machines or engines with variable working-fluid distribution are covered by groups [F01L 15/00](#) - [F01L 35/00](#).
4. Attention is drawn to the notes preceding class [F01](#), especially Note (3).
5. As regards the above-mentioned Note (3), attention is drawn to [F01B 3/10](#), [F01B 15/06](#), [F01C 21/18](#), [F02B 53/06](#), [F03C 1/08](#), [F04B 1/18](#), [F04B 7/00](#), [F04B 39/08](#), [F04B 39/10](#), and [F04C 15/06](#), [F04C 29/12](#).

WARNING

The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

F01L 31/20	covered by	F01L 31/08 - F01L 31/18
F01L 31/22	covered by	F01L 31/08 - F01L 31/18
F01L 31/24	covered by	F01L 31/08 - F01L 31/18

Valve-gear or valve arrangements for positive-displacement machines or engines other than steam engines, e.g. for internal-combustion piston engines, without provision for variable fluid distribution

1/00	Valve-gear or valve arrangements, e.g. lift-valve gear (lift-valve and valve-seat assemblies per se F01L 3/00; slide-valve gear F01L 5/00; actuated non-mechanically F01L 9/00; valve arrangements in working piston or piston rod F01L 11/00; modifications of valve-gear to facilitate reversing, braking, starting, changing compression ratio, or other specific operations F01L 13/00)	1/053 overhead type
		1/0532 {the cams being directly in contact with the driven valve}
		2001/0535 {Single overhead camshafts [SOHC]}
		2001/0537 {Double overhead camshafts [DOHC]}
		2001/054 {Camshafts in cylinder block}
		1/06	. . . the cams, or the like, rotating at a higher speed than that corresponding to the valve cycle, e.g. operating fourstroke engine valves directly from crankshaft
		1/08	. . . Shape of cams
		1/10	. . by means of crank-or eccentric-driven rods
1/02	. Valve drive (transmitting-gear between valve drive and valve F01L 1/12)	1/12	. Transmitting gear between valve drive and valve (simultaneously operating two or more valves F01L 1/26)
1/022	. . {Chain drive}		
1/024	. . {Belt drive}	1/14	. . Tappets {(hydraulic tappets for automatically adjusting or compensating clearance F01L 1/24)}; Push rods
1/026	. . {Gear drive}		
2001/028	. . {Pre-assembled timing arrangement, e.g. located in a cassette}	1/143	. . . {for use with overhead camshafts}
1/04	. . by means of cams, camshafts, cam discs, eccentrics or the like (F01L 1/10 takes precedence)	1/146	. . . {Push-rods}
1/042	. . . {Cam discs}	1/16	. . . Silencing impact; Reducing wear
1/044	. . . {Reciprocating cams}	1/18	. . Rocking arms or levers
1/047	. . . Camshafts	1/181	. . . {Centre pivot rocking arms}
2001/0471 {Assembled camshafts}	1/182 {the rocking arm being pivoted about an individual fulcrum, i.e. not about a common shaft}
2001/0473 {Composite camshafts, e.g. with cams or cam sleeve being able to move relative to the inner camshaft or a cam adjusting rod}	1/183 {of the boat type}
		1/185	. . . {Overhead end-pivot rocking arms}
2001/0475 {Hollow camshafts}	2001/186	. . . {Split rocking arms, e.g. rocker arms having two articulated parts and means for varying the relative position of these parts or for selectively connecting the parts to move in unison}
2001/0476 {Camshaft bearings}		
2001/0478 {Torque pulse compensated camshafts}		

2001/187	. . . {Clips, e.g. for retaining rocker arm on pivot}	1/34413	. . . {using composite camshafts, e.g. with cams being able to move relative to the camshaft}
2001/188	. . . {Fulcrums at upper surface}	1/34416	. . . {using twisted cams}
1/20	. Adjusting or compensating clearance	1/3442	. . . {using hydraulic chambers with variable volume to transmit the rotating force}
1/205	. . {by means of shims or the like}	2001/34423	. . . {Details relating to the hydraulic feeding circuit}
1/22	. . automatically, e.g. mechanically	2001/34426 {Oil control valves}
1/24	. . . by fluid means, e.g. hydraulically	2001/3443 {Solenoid driven oil control valves}
1/2405 {by means of a hydraulic adjusting device located between the cylinder head and rocker arm}	2001/34433 {Location oil control valves}
1/2411 {by means of a hydraulic adjusting device located between the valve stem and rocker arm}	2001/34436 {Features or method for avoiding malfunction due to foreign matters in oil}
1/2416 {by means of a hydraulic adjusting device attached to an articulated rocker}	2001/3444 {Oil filters}
1/2422 {by means of a hydraulic adjusting device located between the push rod and rocker arm}	2001/34443 {Cleaning control of oil control valves}
2001/2427 {by means of an hydraulic adjusting device located between cam and push rod}	2001/34446 {Fluid accumulators for the feeding circuit}
2001/2433 {Self contained, e.g. sealed hydraulic lash adjusters}	2001/3445 {Details relating to the hydraulic means for changing the angular relationship}
2001/2438 {with means permitting forced opening of check valve}	2001/34453 {Locking means between driving and driven members}
2001/2444 {Details relating to the hydraulic feeding circuit, e.g. lifter oil manifold assembly [LOMA]}	2001/34456 {Locking in only one position}
1/245 Hydraulic tappets	2001/34459 {Locking in multiple positions}
1/25 between cam and valve stem	2001/34463 {Locking position intermediate between most retarded and most advanced positions}
1/252 {for side-valve engines}	2001/34466 {with multiple locking devices}
1/255 between cam and rocker arm	2001/34469 {Lock movement parallel to camshaft axis}
2001/256 {between cam and push rod}	2001/34473 {Lock movement perpendicular to camshaft axis}
1/26	. characterised by the provision of two or more valves operated simultaneously by same transmitting-gear; peculiar to machines or engines with more than two lift-valves per cylinder (with coaxial valves F01L 1/28)	2001/34476 {Restrict range locking means}
1/262	. . {with valve stems disposed radially from a centre which is substantially the centre of curvature of the upper wall surface of a combustion chamber (F01L 1/265 takes precedence)}	2001/34479 {Sealing of phaser devices}
1/265	. . {peculiar to machines or engines with three or more intake valves per cylinder}	2001/34483 {Phaser return springs}
1/267	. . {with means for varying the timing or the lift of the valves}	2001/34486	. . . {Location and number of the means for changing the angular relationship}
1/28	. characterised by the provision of coaxial valves; characterised by the provision of valves co-operating with both intake and exhaust ports	2001/34489 {Two phasers on one camshaft}
1/285	. . {Coaxial intake and exhaust valves}	2001/34493 {Dual independent phasing system [DIPS]}
1/30	. characterised by the provision of positively opened and closed valves, i.e. desmodromic valves	2001/34496 {Two phasers on different camshafts}
1/32	. characterised by the provision of means for rotating lift valves, e.g. to diminish wear	1/348	. . . by means acting on timing belts or chains
1/34	. characterised by the provision of means for changing the timing of the valves without changing the duration of opening {and without affecting the magnitude of the valve lift}	1/352	. . . using bevel or epicyclic gear
1/344	. . changing the angular relationship between crankshaft and camshaft, e.g. using helicoidal gear	2001/3521 {Harmonic drive of flexspline type}
1/34403	. . . {using helically teathed sleeve or gear moving axially between crankshaft and camshaft}	2001/3522 {with electromagnetic brake}
1/34406 {the helically teathed sleeve being located in the camshaft driving pulley}	1/356	. . . making the angular relationship oscillate {, e.g. non-homokinetic drive}
1/34409	. . . {by torque-responsive means}	1/36	. peculiar to machines or engines of specific type other than four-stroke cycle
		1/38	. . for engines with other than four-stroke cycle, e.g. with two-stroke cycle (F01L 1/26 , F01L 1/28 take precedence)
		1/40	. . for engines with scavenging charge near top dead centre position, e.g. by overlapping inlet and exhaust time
		1/42	. . for machines or engines characterised by cylinder arrangements, e.g. star or fan
		1/44	. Multiple-valve gear or arrangements, not provided for in preceding subgroups, e.g. with lift and different valves
		1/443	. . {comprising a lift valve and at least one rotary valve}
		1/446	. . {comprising a lift valve and at least one reed valve}
		1/46	. Component parts, details, or accessories, not provided for in preceding subgroups

1/462	. . {Valve return spring arrangements}	5/16	. . with reciprocating and other movement of same valve, e.g. longitudinally of working cylinder and in cross direction
1/465	. . . {Pneumatic arrangements}	5/18	. . with reciprocatory valve and other slide valve
2001/467	. . {Lost motion springs}	5/20	. specially for two-stroke engines (F01L 5/06 , F01L 5/14 take precedence)
3/00	Lift-valve, i.e. cut-off apparatus with closure members having at least a component of their opening and closing motion perpendicular to the closing faces; Parts or accessories thereof	5/22	. Multiple-valve arrangements (with valves surrounding working cylinder or piston F01L 5/08 ; with reciprocatory and other slide valves F01L 5/18 ; specially for two-stroke engines F01L 5/20)
3/02	. Selecting particular materials for valve-members or valve-seats; Valve-members or valve-seats composed of two or more materials	5/24	. Component parts, details or accessories, not provided for in preceding subgroups in this group
3/04	. . Coated valve members or valve-seats	7/00	Rotary or oscillatory slide valve-gear or valve arrangements (slide valves with combined rotary and non-rotary movements, combinations of rotary and non-rotary slide valves F01L 5/00)
3/06	. Valve members or valve-seats with means for guiding or deflecting the medium controlled thereby, e.g. producing a rotary motion of the drawn-in cylinder charge (for rotating lift-valves F01L 1/32)	7/02	. with cylindrical, sleeve, or part-annularly shaped valves (of disc type F01L 7/06 ; of conical type F01L 7/08)
3/08	. Valves guides; Sealing of valve stem, e.g. sealing by lubricant	7/021	. . {with one rotary valve}
3/085	. . {Valve cages}	7/022	. . . {Cylindrical valves having one recess communicating successively with aligned inlet and exhaust ports}
3/10	. Connecting springs to valve members	7/023	. . . {Cylindrical valves having a hollow or partly hollow body allowing axial inlet or exhaust fluid circulation}
2003/11	. {Connecting valve members to rocker arm or tappet}	7/024	. . . {Cylindrical valves comprising radial inlet and axial outlet or axial inlet and radial outlet}
3/12	. Cooling of valves	7/025	. . . {Cylindrical valves comprising radial inlet and side outlet or side inlet and radial outlet}
3/14	. . by means of a liquid or solid coolant, e.g. sodium, in a closed chamber in a valve	7/026	. . {with two or more rotary valves, their rotational axes being parallel, e.g. 4-stroke}
3/16	. . by means of a fluid flowing through or along valve, e.g. air	7/027	. . {with two or more valves arranged coaxially (F01L 7/045 takes precedence)}
3/18	. . . Liquid cooling of valve	7/028	. . {having the rotational axis coaxial with the cylinder axis and the valve surface not surrounding piston or cylinder}
3/20	. Shapes or constructions of valve members, not provided for in preceding subgroups of this group	7/029	. . {having the rotational axis of the valve parallel to the cylinder axis}
3/205	. . {Reed valves}	7/04	. . surrounding working cylinder or piston
3/22	. Valve-seats not provided for in preceding subgroups of this group; Fixing of valve-seats	7/045	. . . {with two or more valves arranged coaxially}
3/24	. Safety means or accessories, not provided for in preceding sub- groups of this group	7/06	. with disc type valves
2003/25	. {Valve configurations in relation to engine}	7/08	. with conically or frusto-conically shaped valves
2003/251	. . {Large number of valves, e.g. five or more}	7/10	. with valves of other specific shape, e.g. spherical
2003/253	. . {configured parallel to piston axis}	7/12	. specially for two-stroke engines (F01L 7/04 takes precedence)
2003/255	. . {configured other than parallel or symmetrical relative to piston axis}	7/14	. Multiple-valve arrangements (with valves surrounding working cylinder or piston F01L 7/04 ; specially for two-stroke engines F01L 7/12)
2003/256	. . {configured other than perpendicular to camshaft axis}	7/16	. Sealing or packing arrangements specially therefor
2003/258	. . {opening away from cylinder}	7/18	. Component parts, details, or accessories not provided for in preceding subgroups of this group
5/00	Slide valve-gear or valve-arrangements (with pure rotary or oscillatory movement F01L 7/00)	9/00	Valve-gear or valve arrangements actuated non-mechanically
5/02	. with other than cylindrical, sleeve or part annularly shaped valves, e.g. with flat-type valves	9/10	. by fluid means, e.g. hydraulic
5/04	. with cylindrical, sleeve, or part-annularly shaped valves	9/11	. . in which the action of a cam is being transmitted to a valve by a liquid column
5/045	. . {Piston-type or cylinder-type valves arranged above the piston and coaxial with the cylinder axis}	9/12	. . . with a liquid chamber between a piston actuated by a cam and a piston acting on a valve stem
5/06	. . surrounding working cylinder or piston	9/14 the volume of the chamber being variable, e.g. for varying the lift or the timing of a valve
5/08	. . . Arrangements with several movements or several valves, e.g. one valve inside the other (with part-annularly shaped valves F01L 5/12)		
5/10 with reciprocating and other movements of the same valve		
5/12	. . . Arrangements with part-annularly-shaped valves		
5/14	. characterised by the provision of valves with reciprocating and other movements (surrounding working cylinder or piston F01L 5/06)		

9/16	. . Pneumatic means	2009/4092	. . {Determination of valve timing during particular working conditions, e.g. deceleration}
9/18	. . Means for increasing the initial opening force on the valve	2009/4094	. . {Engine stopping; Engine stall}
9/20	. by electric means	2009/4096	. . {relating to sticking duration}
9/21	. . actuated by solenoids	2009/4098	. . {relating to gap between armature shaft and valve stem end}
2009/2103	. . . {comprising one coil}		
2009/2105	. . . {comprising two or more coils}		
2009/2107 {being disposed coaxially to the armature shaft}		
2009/2109 {The armature being articulated perpendicularly to the coils axes}		
2009/2115	. . . {Moving coil actuators}		
2009/2117	. . . {Floating actuators for varying the valve stroke}		
2009/2125	. . . {Shaft and armature construction}		
2009/2126 {Arrangements for amplifying the armature stroke}		
2009/2128	. . . {Core and coil construction}		
2009/213	. . . {Casing construction}		
2009/2132	. . . {Biasing means}		
2009/2134 {Helical springs}		
2009/2136 {Two opposed springs for intermediate resting position of the armature}		
2009/2138 {Torsion springs}		
2009/214 {Pneumatic springs}		
2009/2142 {Means for varying the spring bias}		
2009/2144 {Means for connecting springs to valve or anchor}		
2009/2146 {Latching means}		
2009/2148 {using permanent magnet}		
2009/2149	. . . {Means for varying the air gap}		
2009/2151	. . . {Damping means}		
2009/2153	. . . {Means for counteracting cylinder pressure}		
2009/2155	. . . {Lash adjusting means}		
2009/2157	. . . {Actuator cooling means}		
2009/2159	. . . {Means for facilitating assembly}		
2009/2161	. . . {Wiring}		
2009/2163 {Connectors}		
2009/2165 {Harnesses}		
2009/2167 {Sensing means}		
2009/2169 {Position sensors}		
2009/2171 {Vibration sensors}		
2009/2173 {Temperature sensors}		
2009/2174 {Flux sensors}		
2009/2176 {Spring force sensors}		
9/22	. . actuated by rotary motors		
9/24	. . Piezoelectric actuators		
2009/25	. . {Mixed arrangement with both mechanically and electromagnetically actuated valves}		
9/26	. . Driving circuits therefor		
9/30	. Arrangements for setting the actuator position, e.g. the initial position		
9/40	. Methods of operation thereof; Control of valve actuation, e.g. duration or lift		
2009/408	. . {Engine starting}		
2009/4082	. . . {in normal conditions}		
2009/4084	. . . {Cold start}		
2009/4086	. . {Soft landing, e.g. applying braking current; Levitation of armature close to core surface}		
2009/4088	. . {Fail safe, e.g. valve kept closed if not opening properly}		
2009/409	. . {Determination of valve speed}		
		11/00	Valve arrangements in working piston or piston-rod
		11/02	. in piston
		11/04	. . operated by movement of connecting-rod
		11/06	. . . operating oscillatory valve
		13/00	Modifications of valve-gear to facilitate reversing, braking, starting, changing compression ratio, or other specific operations
		13/0005	. {Deactivating valves}
		2013/001	. . {Deactivating cylinders}
		13/0015	. {for optimising engine performances by modifying valve lift according to various working parameters, e.g. rotational speed, load, torque}
		13/0021	. . {by modification of rocker arm ratio}
		13/0026	. . . {by means of an eccentric}
		13/0031	. . {by modification of tappet or pushrod length}
		13/0036	. . {the valves being driven by two or more cams with different shape, size or timing or a single cam profiled in axial and radial direction}
		13/0042	. . . {with cams being profiled in axial and radial direction}
		13/0047	. . . {the movement of the valves resulting from the sum of the simultaneous actions of at least two cams, the cams being independently variable in phase in respect of each other}
		2013/0052	. . . {with cams provided on an axially slidable sleeve}
		13/0057	. . {by splittable or deformable cams}
		13/0063	. . {by modification of cam contact point by displacing an intermediate lever or wedge-shaped intermediate element, e.g. Tourtelot}
		2013/0068	. . . {with an oscillating cam acting on the valve of the "BMW-Valvetronic" type}
		2013/0073	. . . {with an oscillating cam acting on the valve of the "Delphi" type}
		2013/0078	. . {by modification of cam contact point by axially displacing the camshaft}
		2013/0084	. . {by modification of cam contact point by radially displacing the camshaft}
		2013/0089	. . {with means for delaying valve closing}
		2013/0094	. . . {with switchable clamp for keeping valve open}
		13/02	. for reversing
		13/04	. for starting by means of fluid pressure
		13/06	. for braking
		13/065	. . {Compression release engine retarders of the "Jacobs Manufacturing" type}
		13/08	. for decompression, e.g. during starting; for changing compression ratio
		13/085	. . {the valve-gear having an auxiliary cam protruding from the main cam profile}
		2013/10	. {Auxiliary actuators for variable valve timing}
		2013/101	. . {Electromagnets}
		2013/103	. . {Electric motors}
		2013/105	. . {Hydraulic motors}
		2013/106	. . {Pneumatic motors}

- 2013/108 . . {Centrifugal force}
- 2013/11 . {Sensors for variable valve timing}
- 2013/111 . . {Camshafts position or phase}
- 2013/113 . . {crankshafts position}
- 2013/115 . . {Pressure}
- 2013/116 . . {Temperature}
- 2013/118 . . {Valve lift}

Valve-gear or valve arrangements specially adapted for steam engines, or specially adapted for other positive-displacement machines or engines with variable working-fluid distribution

NOTES

1. Groups [F01L 15/00](#) - [F01L 31/00](#) cover:
 - valve drive or means external to valves for adjustment during operation;
 - tripping-gear;
 - reversing-gear;
 - use of pistons or piston-rods as valves or as valve-supporting elements;
 - valve-gear or valve arrangements peculiar to free-piston machines or engines.
2. Groups [F01L 15/00](#) - [F01L 31/00](#) do not fully cover subject matter restricted to rotary, oscillatory, or lift-valve gear or valve arrangements, which is covered by group [F01L 33/00](#) or [F01L 35/00](#).
 - 15/00** **Valve-gear or valve arrangements, e.g. with reciprocating slide valves, other than provided for in groups [F01L 17/00](#) - [F01L 29/00](#) (valve drive or external valve-adjustment during operation, tripping-gear or tripping of valves [F01L 31/00](#))**
 - 15/02 . with valves other than cylindrical, sleeve, or part-annularly-shaped, e.g. flat D-valves
 - 15/04 . . main valve being combined with auxiliary valve (of drag valve type [F01L 15/10](#))
 - 15/06 . . . of Meyer or Rider type, i.e. in which the expansion is varied at the expansion valve itself
 - 15/08 . with cylindrical, sleeve, or part-annularly-shaped valves; Such main valves combined with auxiliary valves
 - 15/10 . with main slide valve and auxiliary valve dragged thereby
 - 15/12 . characterised by having means for effecting pressure equilibrium between two different cylinder spaces at idling
 - 15/14 . Arrangements with several co-operating main valves, e.g. reciprocating and rotary
 - 15/16 . . with reciprocating slide valves only
 - 15/18 . Valves arrangements not provided for in preceding subgroups of this main group
 - 15/20 . Component parts, details, or accessories, not provided for in preceding subgroups of this main group
 - 17/00** **Slide valve-gear or valve arrangements with cylindrical, sleeve, or part annularly-shaped valves surrounding working cylinder or piston**
 - 17/02 . Drive or adjustment during operation, peculiar thereto, e.g. for reciprocating and oscillating movements or for several valves one inside the other

- 19/00** **Slide valve-gear or valve arrangements with reciprocating and other movement of same valve, other than provided for in [F01L 17/00](#), e.g. longitudinally of working cylinder and in cross direction**
 - 19/02 . Drive or adjustment during operation, peculiar thereto
- 21/00** **Use of working pistons or pistons-rods as fluid-distributing valves or as valve-supporting elements, e.g. in free-piston machines**
 - 21/02 . Piston or piston-rod used as valve members {[F01L 25/066](#) takes precedence}
 - 21/04 . Valves arranged in or on piston or piston-rod
- 23/00** **Valves controlled by impact by piston, e.g. in free-piston machines**
- 25/00** **Drive, or adjustment during the operation, or distribution or expansion valves by non-mechanical means**
 - 25/02 . by fluid means
 - 25/04 . . by working-fluid of machine or engine, e.g. free-piston machine
 - 25/06 . . . Arrangements with main and auxiliary valves, at least one of them being fluid-driven
 - 25/063 {the auxiliary valve being actuated by the working motor-piston or piston-rod}
 - 25/066 {piston or piston-rod being used as auxiliary valve}
 - 25/08 . by electric or magnetic means
- 27/00** **Distribution or expansion valve-gear peculiar to free-piston machines or engines and not provided for in [F01L 21/00](#) - [F01L 25/00](#)**
 - 27/02 . the machine or engine having rotary or oscillatory valves
 - 27/04 . Delayed-action controls, e.g. of cataract or dashpot type
- 29/00** **Reversing-gear**
 - 29/02 . by displacing eccentric
 - 29/04 . by links or guide rods
 - 29/06 . by interchanging inlet and exhaust ports
 - 29/08 . specially for rotary or oscillatory valves
 - 29/10 . Details, e.g. drive
 - 29/12 . . Powered reverse gear
- 31/00** **Valve drive, valve adjustment during operation, or other valve control, not provided for in groups [F01L 15/00](#) - [F01L 29/00](#) (sensing elements measuring the variable or condition to be controlled or regulated [F01B 25/04](#))**
 - 31/02 . with tripping-gear (for oscillatory valves [F01L 31/06](#)); Tripping of valves
 - 31/04 . . with positively-driven trip levers
 - 31/06 . with tripping-gear specially for oscillatory valves; Oscillatory tripping-valves, e.g. of Corliss type
 - 31/08 . Valve drive or valve adjustment, apart from tripping aspects; Positively-driven gear
 - 31/10 . . the drive being effected by eccentrics ([F01L 31/14](#) takes precedence)
 - 31/12 . . . Valve adjustment by displacing eccentric
 - 31/14 . . Valve adjustment by links or guide rods, e.g. in valve-gears with eccentric drive

- 31/16 . . the drive being effected by specific means other than eccentric, e.g. cams; Valve adjustment in connection with such drives
- 31/18 . . specially for rotary or oscillatory valves

Rotary or oscillatory slide valve-gear or lift-valve-gear or such valve arrangements specially for steam engines or specially for other machines or engines with variable working-fluid distribution (drive adjustment during operation, tripping-gear, reversing-gear, use of working pistons or piston-rods as valves or as valve-supporting elements, valve-gear or valve arrangements peculiar to free-piston machines or engines [F01L 15/00](#) - [F01L 31/00](#))

- 33/00 Rotary or oscillatory slide valve-gear or valve arrangements, specially adapted for machines or engines with variable fluid distribution** (drive, adjustment during operation, tripping-gear, reversing-gear, use of working pistons or piston-rods as valves or as valve-supporting elements, valve-gear or valve arrangements peculiar to free-piston machines or engines [F01L 15/00](#) - [F01L 31/00](#))
 - 33/02 . rotary
 - 33/04 . oscillatory
- 35/00 Lift valve-gear or valve arrangements specially adapted for machines or engines with variable fluid distribution** (drive, adjustment during operation, tripping-gear, reversing-gear, use of working pistons or piston-rods as valves or as valve-supporting elements, valve-gear or valve arrangements peculiar to free-piston machines or engines [F01L 15/00](#) - [F01L 31/00](#))
 - 35/02 . Valves
 - 35/04 . Arrangements of valves in the machine or engine, e.g. relative to working cylinder

-
- 2201/00 Electronic control systems; Apparatus or methods therefor**
 - 2250/00 Camshaft drives characterised by their transmission means**
 - 2250/02 . the camshaft being driven by chains
 - 2250/04 . the camshaft being driven by belts
 - 2250/06 . the camshaft being driven by gear wheels
 - 2301/00 Using particular materials**
 - 2301/02 . Using ceramic materials
 - 2303/00 Manufacturing of components used in valve arrangements**
 - 2303/01 . Tools for producing, mounting or adjusting, e.g. some part of the distribution
 - 2303/02 . Initial camshaft settings
 - 2305/00 Valve arrangements comprising rollers**
 - 2305/02 . Mounting of rollers
 - 2307/00 Preventing the rotation of tappets**
 - 2309/00 Self-contained lash adjusters**
 - 2311/00 Differential gears located between crankshafts and camshafts for varying the timing of valves**
 - 2313/00 Rotary valve drives**
 - 2710/00 Control of valve gear, speed or power**

- 2710/003 . Control of valve gear for two stroke engines
- 2710/006 . Safety devices therefor
- 2740/00 Control of slide-valve gear; Control pistons**
 - 2740/003 . more than one slide-valve, e.g. for four stroke engines
 - 2740/006 . more than one slide-valve, e.g. for two stroke engines
- 2750/00 Control of valve gear for four stroke engines directly driven by the crankshaft**
- 2760/00 Control of valve gear to facilitate reversing, starting, braking of four stroke engines**
 - 2760/001 . for starting four stroke engines
 - 2760/002 . for reversing or starting four stroke engines
 - 2760/003 . for switching to compressor action in order to brake
 - 2760/004 . . whereby braking is exclusively produced by compression in the cylinders
 - 2760/005 . . in cooperation with vehicle transmission or brakes; devices to facilitate switching to compressor action by means of other control devices, e.g. acceleration pedal or clutch
 - 2760/006 . for reversing two stroke engines
 - 2760/007 . for starting two stroke engines
 - 2760/008 . for reversing and restarting two stroke engines
- 2800/00 Methods of operation using a variable valve timing mechanism**
 - 2800/01 . Starting
 - 2800/02 . Cold running
 - 2800/03 . Stopping; Stalling
 - 2800/04 . Timing control at idling
 - 2800/05 . Timing control under consideration of oil condition
 - 2800/06 . Timing or lift different for valves of same cylinder
 - 2800/08 . Timing or lift different for valves of different cylinders
 - 2800/09 . Calibrating
 - 2800/10 . Providing exhaust gas recirculation [EGR]
 - 2800/11 . Fault detection, diagnosis
 - 2800/12 . Fail safe operation
 - 2800/13 . Throttleless
 - 2800/14 . Determining a position, e.g. phase or lift
 - 2800/15 . Balancing of rotating parts
 - 2800/16 . Preventing interference
 - 2800/17 . Maintenance; Servicing
 - 2800/18 . Testing or simulation
 - 2800/19 . Valves opening several times per stroke
- 2810/00 Arrangements solving specific problems in relation with valve gears**
 - 2810/01 . Cooling
 - 2810/02 . Lubrication
 - 2810/03 . Reducing vibration
 - 2810/04 . Reducing noise
 - 2810/05 . Related to pressure difference on both sides of a valve
- 2820/00 Details on specific features characterising valve gear arrangements**
 - 2820/01 . Absolute values
 - 2820/02 . Formulas
 - 2820/03 . Auxiliary actuators
 - 2820/031 . . Electromagnets
 - 2820/032 . . Electric motors

F01L

2820/033	.	.	Hydraulic engines
2820/034	.	.	Pneumatic engines
2820/035	.	.	Centrifugal forces
2820/04	.		Sensors
2820/041	.	.	Camshafts position or phase sensors
2820/042	.	.	Crankshafts position
2820/043	.	.	Pressure
2820/044	.	.	Temperature
2820/045	.	.	Valve lift