

# CPC COOPERATIVE PATENT CLASSIFICATION

## B PERFORMING OPERATIONS; TRANSPORTING (NOTES omitted)

### SHAPING

#### B21 MECHANICAL METAL-WORKING WITHOUT ESSENTIALLY REMOVING MATERIAL; PUNCHING METAL (NOTES omitted)

#### B21B ROLLING OF METAL (auxiliary operations used in connection with metal-working operations covered in [B21](#), see [B21C](#); bending by rolling [B21D](#); manufacture of particular objects, e.g. screws, wheels, rings, barrels, balls, by rolling [B21H](#); pressure welding by means of a rolling mill [B23K 20/04](#))

##### NOTE

In this subclass, the following terms or expressions are used with the meanings indicated:

- "rolling" means rolling operations in which plastic deformations occur;
- "continuous process" means a process employing a mill train designed to have the workpiece enter one pair of rolls before leaving the preceding pair.

##### WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Metal-rolling methods or mills for making semi-finished products of solid or profiled cross-section ( <a href="#">B21B 17/00</a> - <a href="#">B21B 23/00</a> take precedence; with respect to composition of material to be rolled <a href="#">B21B 3/00</a> ; extending closed shapes of metal bands by simultaneous rolling at two or more zones <a href="#">B21B 5/00</a> ; metal-rolling stands as units <a href="#">B21B 13/00</a> ; continuous casting into moulds having walls formed by moving rolls <a href="#">B22D 11/06</a> ); Sequence of operations in milling trains; Layout of rolling-mill plant, e.g. grouping of stands; Succession of passes or of sectional pass alternations	1/0815	. . {from flat-rolled products, e.g. by longitudinal shearing}
		1/082	. . Piling sections having lateral edges specially adapted for interlocking with each other in order to build a wall
		1/085	. . Rail sections
		1/0855	. . . {Rerolling or processing worn or discarded rail sections}
		1/088	. . H- or I-sections
		1/0883	. . . {using forging or pressing devices}
		1/0886	. . . {using variable-width rolls}
		1/09	. . L-sections
		1/092	. . T-sections
		1/095	. . U-or channel sections
		1/098	. . Z-sections
		1/10	. . in a single two-high or universal rolling mill {stand ( <a href="#">B21B 1/085</a> - <a href="#">B21B 1/098</a> take precedence)}
		1/12	. . in a continuous process {, i.e. without reversing stands ( <a href="#">B21B 1/085</a> - <a href="#">B21B 1/098</a> take precedence)}
		1/14	. . in a non-continuous process {, i.e. at least one reversing stand ( <a href="#">B21B 1/085</a> - <a href="#">B21B 1/098</a> take precedence)}
		1/16	. . for rolling {wire rods, bars, merchant bars, rounds} wire or material of like small cross-section
		1/163	. . {Rolling or cold-forming of concrete reinforcement bars or wire (reinforcement bars per se <a href="#">E04C 5/03</a> ); Rolls therefor}
		1/166	. . {Rolling wire into sections or flat ribbons}
		1/18	. . in a continuous process
		1/20	. . in a non-continuous process, (e.g. skew rolling, i.e. planetary cross rolling)
1/02	. for rolling heavy work, e.g. ingots, slabs, {blooms, or} billets, in which the cross-sectional form is unimportant {; Rolling combined with forging or pressing}		
2001/022	. . {Blooms or billets}		
1/024	. . {Forging or pressing (forging or pressing devices as units <a href="#">B21B 15/0035</a> )}		
1/026	. . {Rolling}		
2001/028	. . {Slabs}		
1/04	. . in a continuous process		
1/06	. . in a non-continuous process {, e.g. triplet mill, reversing mill}		
1/08	. for rolling {structural sections, i.e.} work of special cross-section, e.g. angle steel (rolling metal of indefinite length in repetitive shapes specially designed for the manufacture of particular objects <a href="#">B21H 8/00</a> )		
1/0805	. . {Flat bars, i.e. having a substantially rectangular cross-section}		
2001/081	. . {Roughening or texturing surfaces of structural sections, bars, rounds, wire rods}		

1/22	• for rolling {plates, strips,} bands or sheets of indefinite length ( <a href="#">B21B 1/42</a> takes precedence)	9/00	<b>Measures for carrying out rolling operations under special conditions, e.g. in vacuum or inert atmosphere to prevent oxidation of work; Special measures for removing fumes from rolling mills</b>
2001/221	• • {by cold-rolling}	11/00	<b>Subsidising the rolling process by subjecting rollers or work to vibrations, {e.g. ultrasonic vibrations}</b>
1/222	• • {in a rolling-drawing process; in a multi-pass mill}	13/00	<b>Metal-rolling stands, i.e. an assembly composed of a stand frame, rolls, and accessories</b> ( <a href="#">B21B 17/00</a> - <a href="#">B21B 23/00</a> take precedence)
1/224	• • {Edge rolling of flat products}	13/001	• {Convertible or tiltable stands, e.g. from duo to universal stands, from horizontal to vertical stands}
2001/225	• • {by hot-rolling}	2013/003	• {Inactive rolling stands}
1/227	• • {Surface roughening or texturing}	13/005	• {Cantilevered roll stands}
2001/228	• • {skin pass rolling or temper rolling}	2013/006	• {Multiple strand rolling mills; Mill stands with multiple caliber rolls}
1/24	• • in a continuous {or semi-continuous} process {( <a href="#">B21B 1/224</a> takes precedence)}	13/008	• {Skew rolling stands, e.g. for rolling rounds}
1/26	• • • by hot-rolling {, e.g. Steckel hot mill}	13/02	• with axes of rolls arranged horizontally
1/265	• • • {and by compressing or pushing the material in rolling direction}	2013/021	• • {Twin mills}
1/28	• • • by cold-rolling {, e.g. Steckel cold mill}	13/023	• • {the axis of the rolls being other than perpendicular to the direction of movement of the product, e.g. cross-rolling}
1/30	• • in a non-continuous process {( <a href="#">B21B 1/224</a> takes precedence)}	2013/025	• • {Quarto, four-high stands}
1/32	• • • in reversing {single stand} mills, e.g. with intermediate storage reels for accumulating work	2013/026	• • {Quinto, five high-stands}
1/34	• • • • by hot-rolling	2013/028	• • {Sixto, six-high stands}
1/36	• • • • by cold-rolling	13/04	• • Three-high arrangement
1/38	• for rolling sheets of limited length, e.g. folded sheets, superimposed sheets, {pack rolling} ( <a href="#">B21B 1/40</a> takes precedence; folding sheets before, or separating layers after, rolling <a href="#">B21B 47/00</a> )	13/06	• with axes of rolls arranged vertically {, e.g. edgers}
2001/383	• • {Cladded or coated products}	13/08	• with differently-directed roll axes, e.g. for the so-called "universal" rolling process
2001/386	• • {Plates}	13/10	• • all axes being arranged in one plane
1/40	• for rolling foils which present special problems, e.g. because of thinness	13/103	• • • {for rolling bars, rods or wire}
1/42	• for step-by-step or planetary rolling (making tubes by pilgrim-step rolling <a href="#">B21B 21/00</a> )	2013/106	• • • {for sections, e.g. beams, rails}
1/46	• for rolling metal immediately subsequent to continuous casting (metal-rolling stands <a href="#">B21B 13/22</a> ; continuous casting <a href="#">B22D 11/00</a> , e.g. into moulds with rolls <a href="#">B22D 11/06</a> )	13/12	• • axes being arranged in different planes
1/463	• • {in a continuous process, i.e. the cast not being cut before rolling}	13/14	• having counter-pressure devices acting on rolls to inhibit deflection of same under load; {Back-up rolls}(counter-pressure devices as such <a href="#">B21B 29/00</a> )
1/466	• • {in a non-continuous process, i.e. the cast being cut before rolling}	13/142	• • {by axially shifting the rolls, e.g. rolls with tapered ends or with a curved contour for continuously-variable crown CVC}
3/00	<b>Rolling materials of special alloys so far as the composition of the alloy requires or permits special rolling methods or sequences {; Rolling of aluminium, copper, zinc or other non-ferrous metals}(altering special metallurgical properties of alloys, other than structure consolidation or mechanical properties resulting therefrom <a href="#">C21D</a>, <a href="#">C22F</a>)</b>	13/145	• • {Lateral support devices for rolls acting mainly in a direction parallel to the movement of the product}
2003/001	• {Aluminium or its alloys}	13/147	• • {Cluster mills, e.g. Sendzimir mills, Rohn mills, i.e. each work roll being supported by two rolls only arranged symmetrically with respect to the plane passing through the working rolls}
3/003	• {Rolling non-ferrous metals immediately subsequent to continuous casting, i.e. in-line rolling}	13/16	• with alternatively operative rolls {, e.g. revolver stands, turret mills}
2003/005	• {Copper or its alloys}	13/18	• for step-by-step or planetary rolling; {pendulum mills}(methods <a href="#">B21B 1/42</a> ; making tubes by pilgrim-step rolling <a href="#">B21B 21/00</a> )
2003/006	• {Powder metal alloys}	13/20	• • for planetary rolling
2003/008	• {Zinc or its alloys}	13/22	• for rolling metal immediately subsequent to continuous casting, {i.e. in-line rolling of steel}(methods therefor <a href="#">B21B 1/46</a> ; continuous casting <a href="#">B22D 11/00</a> , e.g. into moulds with rolls <a href="#">B22D 11/06</a> )
3/02	• Rolling special iron alloys {, e.g. stainless steel}	15/00	<b>Arrangements for performing additional metal-working operations specially combined with or arranged in, or specially adapted for use in connection with, metal-rolling mills</b>
5/00	<b>Extending closed shapes of metal bands by rolling (manufacture of circular shapes, e.g. wheel rims, <a href="#">B21H 1/06</a>)</b>		

- 15/0007 . {Cutting or shearing the product}
- 2015/0014 . . {transversely to the rolling direction}
- 2015/0021 . . {in the rolling direction}
- 2015/0028 . {Drawing the rolled product}
- 15/0035 . {Forging or pressing devices as units}
- 15/0042 . . {Tool changers}
- 15/005 . . {Lubricating, cooling or heating means}
- 2015/0057 . {Coiling the rolled product}
- 2015/0064 . {Uncoiling the rolled product}
- 2015/0071 . {Levelling the rolled product}
- 2015/0078 . {Extruding the rolled product}
- 15/0085 . {Joining ends of material to continuous strip, bar or sheet}
- 2015/0092 . {Welding in the rolling direction}
- 15/02 . in which work is subjected to permanent internal twisting, e.g. for producing reinforcement bars for concrete

**Rolling methods or mills specially designed for making or processing tubes (control of tube rolling B21B 37/78)**

- 17/00 Tube-rolling by rollers of which the axes are arranged essentially perpendicular to the axis of the work, e.g. "axial" tube-rolling**
- 17/02 . with mandrel, {i.e. the mandrel rod contacts the rolled tube over the rod length} (B21B 17/08 takes precedence)
- 17/04 . . in a continuous process
- 17/06 . . in a discontinuous process
- 17/08 . with mandrel having one or more protrusions {, i.e. only the mandrel plugs contact the rolled tube; Press-piercing mills}
- 17/10 . . in a continuous process
- 17/12 . . in a discontinuous process {, e.g. plug-rolling mills}
- 17/14 . without mandrel {, e.g. stretch-reducing mills}
- 19/00 Tube-rolling by rollers arranged outside the work and having their axes not perpendicular to the axis of the work (straightening by rollers B21D)**
- 19/02 . the axes of the rollers being arranged essentially diagonally to the axis of the work, e.g. "cross" tube-rolling {; Diescher mills, Stiefel disc piercers or Stiefel rotary piercers}
- 19/04 . . Rolling basic material of solid, i.e. non-hollow, structure; Piercing {, e.g. rotary piercing mills}
- 19/06 . . Rolling hollow basic material, {e.g. Assel mills} (B21B 19/04 takes precedence; separating work from mandrel B21C 45/00)
- 19/08 . . . Enlarging tube diameter
- 19/10 . . . Finishing, e.g. smoothing, sizing {, reeling}
- 19/12 . the axes of the rollers being arranged essentially parallel to the axis of the work
- 19/14 . . Rolling tubes by means of additional rollers arranged inside the tubes
- 19/16 . . Rolling tubes without additional rollers arranged inside the tubes
- 21/00 Pilgrim-step tube-rolling {, i.e. pilger mills}**
- 21/005 . {with reciprocating stand, e.g. driving the stand}
- 21/02 . Rollers therefor
- 21/04 . Pilgrim-step feeding mechanisms (B21B 21/06 takes precedence)
- 21/045 . . {for reciprocating stands}
- 21/06 . Devices for revolving work between the steps

- 21/065 . . {for reciprocating stands}
- 23/00 Tube-rolling not restricted to methods provided for in only one of groups B21B 17/00, B21B 19/00, B21B 21/00, e.g. combined processes {planetary tube rolling, auxiliary arrangements, e.g. lubricating, special tube blanks, continuous casting combined with tube rolling} (B21B 25/00 takes precedence)**
- 2023/005 . {Roughening or texturing surfaces of tubes}
- 25/00 Mandrels for metal tube rolling mills, e.g. mandrels of the types used in the methods covered by group B21B 17/00; Accessories or auxiliary means therefor {; Construction of, or alloys for, mandrels or plugs}**
- 25/02 . Guides, supports, or abutments for mandrels, e.g. carriages {or steadiers}; Adjusting devices for mandrels
- 25/04 . Cooling or lubricating mandrels during operation
- 25/06 . Interchanging mandrels {, fixing plugs on mandrel rods or cooling during interchanging mandrels (separating tubes from mandrels B21C 45/00)}
- 27/00 Rolls, {roll alloys or roll fabrication} (shape of working surfaces required by special processes B21B 1/00); Lubricating, cooling or heating rolls while in use**
- 27/005 . {Rolls with a roughened or textured surface; Methods for making same}
- 27/02 . Shape or construction of rolls (for rolling metal of indefinite length in repetitive shapes specially designed for the manufacture of particular objects B21H 8/02 {; B21B 27/005 takes precedence})
- 27/021 . . {Rolls for sheets or strips}
- 2027/022 . . . {Rolls having tapered ends}
- 27/024 . . {Rolls for bars, rods, rounds, tubes, wire or the like}
- 27/025 . . . {Skew rolls}
- 27/027 . . {Vertical rolls}
- 27/028 . . {Variable-width rolls}
- 27/03 . . Sleeved rolls { (B21B 27/028 takes precedence)}
- 27/032 . . . {Rolls for sheets or strips}
- 27/035 . . . {Rolls for bars, rods, rounds, tubes, wire or the like}
- 27/037 . . . . {Skew rolls}
- 27/05 . . . with deflectable sleeves
- 27/055 . . . . {with sleeves radially deflectable on a stationary beam by means of hydraulic supports (in general F16C 13/00; for paper-making machines D21G 1/00; regulating devices therefor B21B 37/36)}
- 27/06 . Lubricating, cooling or heating rolls
- 27/08 . . internally
- 2027/083 . . . {cooling internally}
- 2027/086 . . . {heating internally}
- 27/10 . . externally
- 2027/103 . . . {cooling externally}
- 27/106 . . . {Heating the rolls}
- 28/00 Maintaining rolls or rolling equipment in effective condition (lubricating, cooling or heating rolls while in use B21B 27/06)**
- 28/02 . Maintaining rolls in effective condition, e.g. reconditioning

28/04	. . while in use, e.g. polishing {or grinding while the rolls are in their stands}	33/02	. Preventing fracture of rolls
<b>29/00</b>	<b>Counter-pressure devices acting on rolls to inhibit deflection of same under load, e.g. backing rolls {; Roll bending devices, e.g. hydraulic actuators acting on roll shaft ends (control devices responsive to roll bending <a href="#">B21B 37/38</a>)}</b>	<b>35/00</b>	<b>Drives for metal-rolling mills {, e.g. hydraulic drives}</b>
		2035/005	. {Hydraulic drive motors}
		35/02	. for continuously-operating mills ( <a href="#">B21B 35/10</a> , <a href="#">B21B 35/12</a> take precedence)
		35/025	. . {for stretch-reducing of tubes}
		35/04	. . each stand having its own motor or motors
<b>31/00</b>	<b>Rolling stand structures; Mounting, adjusting, or interchanging rolls, roll mountings, or stand frames</b>	35/06	. for non-continuously-operating mills or for single stands ( <a href="#">B21B 35/10</a> , <a href="#">B21B 35/12</a> take precedence)
31/02	. Rolling stand frames {or housings}; Roll mountings {; Roll chocks}	35/08	. . for reversing rolling mills
2031/021	. . {Integral tandem mill housings}	35/10	. Driving arrangements for rolls which have only a low-power drive; Driving arrangements for rolls which receive power from the shaft of another roll
2031/023	. . {Transverse shifting one housing}	2035/103	. . {Fluid-driven rolls or rollers}
2031/025	. . {Shifting the stand in or against the rolling direction}	2035/106	. . {Non-driven or idler rolls or rollers}
2031/026	. . {Transverse shifting the stand}	35/12	. Toothed-wheel gearings specially adapted for metal-rolling mills; Housings or mountings therefor
31/028	. . {Prestressing of rolls or roll mountings in stand frames}	35/14	. Couplings, driving spindles, or spindle carriers specially adapted for, or specially arranged in, metal-rolling mills ( <a href="#">couplings or shafts in general F16</a> )
31/04	. . with tie rods {in frameless stands}, e.g. prestressed tie rods	35/141	. . {Rigid spindle couplings, e.g. coupling boxes placed on roll necks ( <a href="#">rigid couplings in general F16D 1/00</a> )}
31/06	. . Fastening stands or frames to foundation, e.g. to the sole plate ( <a href="#">in general F16M</a> )	35/142	. . {Yielding spindle couplings; Universal joints for spindles ( <a href="#">yielding couplings in general F16D 3/00</a> )}
31/07	. Adaptation of roll {neck} bearings ( <a href="#">bearings in general F16C</a> )	35/143	. . . {having slidably-interengaging teeth, e.g. gear-type couplings ( <a href="#">universal joints with the coupling parts having slidably-interengaging teeth, in general, F16D 3/18</a> )}
2031/072	. . {Bearing materials}	35/144	. . . . {Wobbler couplings}
31/074	. . {Oil film bearings, e.g. "Morgoil" bearings}	35/145	. . . {Hooke's joints or the like with each coupling part pivoted with respect to an intermediate member ( <a href="#">Hooke's joints in general F16D 3/26</a> )}
31/076	. . {Cooling; Lubricating roller bearings}	35/146	. . . . {Tongue and slipper joints ( <a href="#">tongue and slipper joints in general F16D 3/265</a> )}
31/078	. . {Sealing devices ( <a href="#">sealings in general F16J 15/00</a> )}	35/147	. . {Lubrication of spindle couplings}
31/08	. Interchanging rolls, roll mountings, or stand frames {, e.g. using C-hooks; Replacing roll chocks on roll shafts}	35/148	. . {Spindle carriers or balancers}
31/10	. . by horizontally displacing {, i.e. horizontal roll changing}	2035/149	. . {Measuring devices for spindles or couplings}
31/103	. . . {Manipulators or carriages therefor}	<b>37/00</b>	<b>Control devices or methods specially adapted for metal-rolling mills or the work produced thereby (methods or devices for measuring specially adapted for metal-rolling mills <a href="#">B21B 38/00</a>)</b>
31/106	. . . {Vertical displacement of rolls or roll chocks during horizontal roll changing}	2037/002	. {Mass flow control}
31/12	. . by vertically displacing	37/005	. {Control of time interval or spacing between workpieces}
31/14	. . by pivotally displacing	37/007	. {Control for preventing or reducing vibration, chatter or chatter marks ( <a href="#">B21B 37/66</a> takes precedence)}
31/16	. Adjusting {or positioning} rolls ( <a href="#">control devices B21B 37/00</a> )	37/16	. Control of thickness, width, diameter or other transverse dimensions ( <a href="#">B21B 37/58</a> takes precedence)
31/18	. . by moving rolls axially	37/165	. . {responsive mainly to the measured thickness of the product}
31/185	. . . {and by crossing rolls}	37/18	. . Automatic gauge control
31/20	. . by moving rolls perpendicularly to roll axis	37/20	. . . in tandem mills
31/203	. . . {Balancing rolls}	37/22	. . Lateral spread control; Width control, e.g. by edge rolling
2031/206	. . . {Horizontal offset of work rolls}	37/24	. . Automatic variation of thickness according to a predetermined program
31/22	. . . mechanically {, e.g. by thrust blocks, inserts for removal}		
31/24	. . . . by screws		
31/26	. . . . Adjusting eccentrically-mounted roll bearings		
31/28	. . . . by toggle-lever mechanisms		
31/30	. . . . by wedges or their equivalent		
31/32	. . . by liquid pressure {, e.g. hydromechanical adjusting}		
<b>33/00</b>	<b>Safety devices not otherwise provided for (<a href="#">safety devices in general F16P</a>); Breaker blocks; Devices for freeing jammed rolls {for handling cobbles; Overload safety devices}</b>		
2033/005	. {Cobble-freeing}		



37/26	. . . for obtaining one strip having successive lengths of different constant thickness	39/00	<b>Arrangements for moving, supporting, or positioning work, or controlling its movement, combined with or arranged in, or specially adapted for use in connection with, metal-rolling mills</b> (guiding, conveying, or accumulating easily-flexible work in loops or curves <a href="#">B21B 41/00</a> ; specially associated with cooling-beds <a href="#">B21B 43/00</a> ; conveying or transporting in general <a href="#">B65G</a> )
37/28	. Control of flatness or profile during rolling of strip, sheets or plates	39/002	. {Piling, unpling, unscrambling}
37/30	. . using roll camber control	39/004	. {Transverse moving}
37/32	. . . by cooling, heating or lubricating the rolls	39/006	. {Pinch roll sets}
37/34	. . . by hydraulic expansion of the rolls	39/008	. {Rollers for roller conveyors (roller-ways in general <a href="#">B65G 13/00</a> , <a href="#">B21B 39/00</a> )}
37/36	. . . by radial displacement of the roll sleeve on a stationary roll beam by means of hydraulic supports	39/02	. Feeding or supporting work; Braking or tensioning arrangements {, e.g. <a href="#">threading arrangements</a> }
37/38	. . using roll bending ( <a href="#">B21B 37/42</a> takes precedence)	39/04	. . Lifting or lowering work for conveying purposes, e.g. tilting tables arranged immediately in front of or behind the pass ( <a href="#">turn-over or like manipulating means as such B21B 39/20</a> )
37/40	. . using axial shifting of the rolls ( <a href="#">B21B 37/42</a> takes precedence)	39/06	. . Pushing or forcing work into pass
37/42	. . using a combination of roll bending and axial shifting of the rolls	39/08	. . Braking or tensioning arrangements
37/44	. . using heating, lubricating or water-spray cooling of the product	39/082	. . . {Bridle devices}
37/46	. Roll speed or drive motor control ( <a href="#">B21B 37/52</a> , <a href="#">B21B 37/60</a> take precedence)	39/084	. . . {Looper devices}
37/48	. Tension control; Compression control	39/086	. . . {Braking devices}
37/50	. . by looper control	39/088	. . . {Bumpers, stopping devices}
37/52	. . by drive motor control	39/10	. . Arrangement or installation of feeding rollers in rolling stands
37/54	. . . including coiler drive control, e.g. reversing mills	39/12	. . Arrangement or installation of roller tables in relation to a roll stand
37/56	. Elongation control	39/14	. Guiding, positioning or aligning work ( <a href="#">B21B 43/12</a> takes precedence; guides in which work is subjected to permanent internal twisting <a href="#">B21B 15/02</a> )
37/58	. Roll-force control; Roll-gap control {( <a href="#">B21B 38/105</a> takes precedence)}	39/16	. . immediately before entering or after leaving the pass
37/60	. . by control of a motor which drives an adjusting screw	39/165	. . . {Guides or guide rollers for rods, bars, rounds, tubes ( <a href="#">B21B 39/28</a> takes precedence); Aligning guides}
37/62	. . by control of a hydraulic adjusting device	39/18	. . Switches for directing work in metal-rolling mills or trains
37/64	. . Mill spring or roll spring compensation systems, e.g. control of prestressed mill stands	39/20	. Revolving, turning-over, or like manipulation of work, {e.g. <a href="#">revolving in trio stands</a> } (guides in which work is subjected to permanent internal twisting <a href="#">B21B 15/02</a> )
37/66	. . Roll eccentricity compensation systems	39/22	. . by tipping, e.g. by lifting one side by levers or wedges ( <a href="#">B21B 39/26</a> , <a href="#">B21B 39/28</a> take precedence)
37/68	. Camber or steering control for strip, sheets or plates, e.g. preventing meandering	39/223	. . . {Side-guard manipulators}
37/70	. Length control ( <a href="#">B21B 37/56</a> takes precedence)	39/226	. . . {Tilttable ingot chairs}
37/72	. Rear end control; Front end control	39/24	. . by tongs or grippers
37/74	. Temperature control, e.g. by cooling or heating the rolls or the product ( <a href="#">B21B 37/32</a> , <a href="#">B21B 37/44</a> take precedence)	39/26	. . by members, e.g. grooved, engaging opposite sides of the work and moved relatively to each other to revolve the work
37/76	. . Cooling control on the run-out table	39/28	. . by means of guide members shaped to revolve the work during its passage
37/78	. Control of tube rolling	39/30	. . by lodging it in a rotating ring manipulator or ring segment manipulator
38/00	<b>Methods or devices for measuring, {detecting or monitoring} specially adapted for metal-rolling mills, e.g. position detection, inspection of the product {(control devices or methods <a href="#">B21B 37/00</a>)}</b>	39/32	. . Devices specially adapted for turning sheets
2038/002	. {Measuring axial forces of rolls}	39/34	. Arrangements or constructional combinations specifically designed to perform functions covered by more than one of groups <a href="#">B21B 39/02</a> , <a href="#">B21B 39/14</a> , <a href="#">B21B 39/20</a>
2038/004	. {Measuring scale thickness}	41/00	<b>Guiding, conveying, or accumulating easily-flexible work, e.g. wire, sheet metal bands, in loops or curves; Loop lifters</b>
38/006	. {for measuring temperature}		
38/008	. {Monitoring or detecting vibration, chatter or chatter marks}		
38/02	. for measuring flatness or profile of strips		
38/04	. for measuring thickness, width, diameter or other transverse dimensions of the product		
38/06	. for measuring tension or compression		
38/08	. for measuring roll-force		
38/10	. for measuring roll-gap, e.g. pass indicators		
38/105	. . {Calibrating or presetting roll-gap}		
38/12	. for measuring roll camber		

41/02	• Returning work to repeat the pass or passes {within the same stand}	2045/0236	• • {Laying heads for overlapping rings on cooling conveyor}
41/04	• • above or underneath the rolling stand or rolls	45/0239	• • {Lubricating}
41/06	• in which the direction of movement of the work is turned through approximately 180 degrees, {e.g. repeaters, i.e. from one stand to another}	45/0242	• • • {Lubricants}
41/08	• without overall change in the general direction of movement of the work	45/0245	• • • {Lubricating devices}
41/10	• • Loop deflectors {(B21B 39/084 takes precedence)}	45/0248	• • • • {using liquid lubricants, e.g. for sections, for tubes}
41/12	• Arrangements of interest only with respect to provision for indicating or controlling operations	45/0251	• • • • • {for strips, sheets, or plates}
<b>43/00</b>	<b>Cooling beds, whether stationary or moving; Means specially associated with cooling beds, e.g. for braking work or for transferring it to or from the bed (conveying means in general B65G)</b>	2045/0254	• • • • • {for structural sections, e.g. H-beams}
43/003	• {Transfer to bed}	45/0257	• • • • • {for wire, rods, rounds, bars}
43/006	• {Transfer from bed}	2045/026	• • • • • {for tubes}
43/02	• Cooling beds comprising rakes {racks, walking beams} or bars (B21B 43/10 takes precedence)	45/0263	• • • • • {using solid lubricants}
43/04	• Cooling beds comprising rolls or worms	45/0266	• • {Measuring or controlling thickness of liquid films}
43/06	• Cooling beds comprising carriages (B21B 43/08 takes precedence)	45/0269	• • {Cleaning}
43/08	• Cooling beds comprising revolving drums or recycling chains {or discs}	45/0272	• • • {Cleaning compositions}
43/10	• Cooling beds with other work-shifting elements projecting through the bed	45/0275	• • • {Cleaning devices}
43/12	• Devices for positioning workpieces "flushed", i.e. with all their axial ends arranged in line on cooling beds or on co-operating conveyors {, e.g. before cutting}	45/0278	• • • • {removing liquids}
<b>45/00</b>	<b>Devices for surface {or other} treatment of work, specially combined with or arranged in, or specially adapted for use in connection with, metal-rolling mills (B21B 15/00, {B21B 1/227 and B21B 27/005} take precedence; technical features of scaling-off devices B21C 43/00)</b>	45/0281	• • • • • {removing coolants}
45/002	• {Increasing friction between work and working rolls by using friction increasing substance}	45/0284	• • • • • {removing lubricants}
45/004	• {Heating the product}	45/0287	• • • • • {removing solid particles, e.g. dust, rust}
2045/006	• • {in vacuum or in inert atmosphere}	45/029	• • • {Liquid recovering devices}
45/008	• {Heat shields}	45/0293	• • • • {Recovering coolants}
45/02	• for lubricating, cooling, or cleaning {(in particular in combination with forging or pressing devices B21B 15/005, control of flatness or profile using lubricating or cooling B21B 37/44)}	45/0296	• • • • {Recovering lubricants}
45/0203	• • {Cooling}	45/04	• for de-scaling {, e.g. by brushing (descaling of rod or wire B21C 43/04)}
45/0206	• • • {Coolants}	45/06	• • of strip material (B21B 45/08 takes precedence)
45/0209	• • • {Cooling devices, e.g. using gaseous coolants}	45/08	• • hydraulically
2045/0212	• • • • {using gaseous coolants}	<b>47/00</b>	<b>Auxiliary arrangements, devices or methods in connection with rolling of multi-layer sheets of metal (soaking pits C21D 9/70)</b>
45/0215	• • • • • {using liquid coolants, e.g. for sections, for tubes}	47/02	• for folding sheets before rolling
45/0218	• • • • • {for strips, sheets, or plates (B21B 45/023, B21B 45/0233 take precedence)}	47/04	• for separating layers after rolling
2045/0221	• • • • • {for structural sections, e.g. H-beams}	<b>99/00</b>	<b>Subject matter not provided for in other groups of this subclass</b>
45/0224	• • • • • {for wire, rods, rounds, bars (B21B 45/023, B21B 45/0233 take precedence)}		
2045/0227	• • • • • {for tubes}		
45/023	• • • • • {by immersion in a bath}		
45/0233	• • • • • {Spray nozzles, Nozzle headers; Spray systems}		
		<b>2201/00</b>	<b>Special rolling modes</b>
		2201/02	• Austenitic rolling
		2201/04	• Ferritic rolling
		2201/06	• Thermomechanical rolling
		2201/08	• Batch rolling
		2201/10	• Endless rolling
		2201/12	• Isothermic rolling
		2201/14	• Soft reduction
		2201/16	• Two-phase or mixed-phase rolling
		2201/18	• Vertical rolling pass lines
		<b>Equipment codes</b>	
		<b>2203/00</b>	<b>Auxiliary arrangements, devices or methods in combination with rolling mills or rolling methods</b>
		2203/02	• Backlash elimination
		2203/04	• Brakes
		2203/06	• Cassettes
		2203/08	• Clutches
		2203/10	• Counterweights
		2203/12	• Covers or shieldings
		2203/14	• Dummy bars or slabs
		2203/16	• Eccentrics
		2203/18	• Rolls or rollers

2203/182	. . Fluid driven rolls or rollers	2265/22	. Pass schedule
2203/185	. . Reversible rolls for changing grooves	2265/24	. asymmetric rolling
2203/187	. . Tilting rolls	<b>2267/00</b>	<b>Roll parameters</b>
2203/20	. Flywheels	2267/02	. Roll dimensions
2203/22	. Hinged chocks	2267/06	. . Roll diameter
2203/24	. Hydrostatic bearings or guides	2267/065	. . . Top and bottom roll have different diameters; Asymmetrical rolling
2203/26	. Motors, drives	2267/08	. . Roll eccentricity
2203/28	. Mounting or dismounting bearing and chock as a unit	2267/10	. Roughness of roll surface
2203/30	. Quick or bayonet couplings	2267/12	. Roll temperature
2203/32	. Roll changing stools	2267/18	. Roll crown; roll profile
2203/34	. Rotational position or alignment	2267/19	. . Thermal crown
2203/36	. Spacers	2267/20	. . Ground camber or profile
2203/38	. Strain gauges	2267/22	. . Hydraulic expansion of rolls
2203/40	. Torsion bars or shafts	2267/24	. Roll wear
2203/42	. Turntables	2267/26	. Hardness of the roll surface
2203/44	. Vibration dampers	2267/28	. Elastic moduli of rolls
<b>2205/00</b>	<b>Particular shaped rolled products</b>	<b>2269/00</b>	<b>Roll bending or shifting</b>
2205/02	. Tailored blanks	2269/02	. Roll bending; vertical bending of rolls
2205/04	. Taper- or wedge-shaped profiles	2269/04	. . Work roll bending
<b>2261/00</b>	<b>Product parameters</b>	2269/06	. . Intermediate roll bending
2261/02	. Transverse dimensions	2269/08	. . Back-up roll bending
2261/04	. . Thickness, gauge	2269/10	. Horizontal bending of rolls
2261/043	. . . Blanks with variable thickness in the rolling direction	2269/12	. Axial shifting the rolls
2261/046	. . . Different thickness in width direction	2269/14	. . Work rolls
2261/05	. . . Different constant thicknesses in one rolled product	2269/16	. . Intermediate rolls
2261/06	. . Width	2269/18	. . Back-up rolls
2261/065	. . . Blanks with variable width	<b>2271/00</b>	<b>Mill stand parameters</b>
2261/08	. . Diameter	2271/02	. Roll gap, screw-down position, draft position
2261/10	. . Cross-sectional area	2271/025	. . Tapered roll gap
2261/12	. Length	2271/04	. . Screw-down speed, draft speed
2261/14	. Roughness	2271/06	. Mill spring
2261/18	. Weight	<b>2273/00</b>	<b>Path parameters</b>
2261/20	. Temperature	2273/02	. Vertical deviation, e.g. slack, looper height
2261/21	. . Temperature profile	2273/04	. Lateral deviation, meandering, camber of product
2261/22	. Hardness	2273/06	. Threading
<b>2263/00</b>	<b>Shape of product</b>	2273/08	. . Threading-in or before threading-in
2263/02	. Profile, e.g. of plate, hot strip, sections	2273/10	. . Threading-out or after threading-out
2263/04	. Flatness	2273/12	. End of product
2263/06	. . Edge waves	2273/14	. . Front end or leading end
2263/08	. . Centre buckles	2273/16	. . Tail or rear end
2263/10	. Lateral spread defects	2273/18	. Presence of product
2263/12	. . Dog bone	2273/20	. Track of product
2263/16	. Alligatoring	2273/22	. Aligning on rolling axis, e.g. of roll calibers
2263/20	. End shape; fish tail; tongue	2273/24	. Web positioning
2263/30	. Shape in top view	<b>2275/00</b>	<b>Mill drive parameters</b>
<b>2265/00</b>	<b>Forming parameters</b>	2275/02	. Speed
2265/02	. Tension	2275/04	. . Roll speed
2265/04	. . Front or inlet tension	2275/05	. . . Speed difference between top and bottom rolls
2265/06	. . Interstand tension	2275/06	. . Product speed
2265/08	. . Back or outlet tension	2275/08	. . Coiler speed
2265/10	. Compression, e.g. longitudinal compression	2275/10	. Motor power; motor current
2265/12	. Rolling load or rolling pressure; roll force	2275/12	. . Roll torque
2265/14	. Reduction rate		
2265/16	. . Extension		
2265/18	. Elongation		
2265/20	. Slip		