

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINES OR PUMPS

F01 MACHINES OR ENGINES IN GENERAL; ENGINE PLANTS IN GENERAL; STEAM ENGINES

F01N GAS-FLOW SILENCERS OR EXHAUST APPARATUS FOR MACHINES OR ENGINES IN GENERAL; GAS-FLOW SILENCERS OR EXHAUST APPARATUS FOR INTERNAL-COMBUSTION ENGINES (arrangements in connection with gas exhaust of propulsion units in vehicles [B60K 13/00](#); combustion-air intake silencers specially adapted for, or arranged on, internal-combustion engines [F02M 35/00](#); protecting against, or damping, noise in general [G10K 11/16](#))

NOTE

Attention is drawn to the notes preceding Class [F01](#), especially as regards Note 3.

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Silencing apparatus characterised by method of silencing	1/085	. . {throttling exhaust gas flow using a central core in a flow passage}
	NOTE	1/086	. . {having means to impart a whirling motion to the exhaust gases (with helically or spirally shaped channels F01N 1/12)}
	{In this main group, it is desirable to add the indexing codes of F01N 2210/00 , F01N 2230/00 , F01N 2290/00 , F01N 2310/00 , F01N 2450/06 , F01N 2470/00 , F01N 2490/00 and F01N 2590/00 .}	1/087	. . . {using tangential inlets into a circular chamber}
		1/088	. . . {using vanes arranged on the flow path or flow tubes with tangentially directed apertures}
1/003	. {by using dead chambers communicating with exhaust gas flow passages}	1/089	. . {using two or more expansion chambers in series (F01N 1/083 , F01N 1/084 , F01N 1/086 take precedence)}
1/006	. . {comprising at least one perforated tube extending from inlet to outlet of the silencer}	1/10	. . in combination with sound-absorbing materials (F01N 1/125 takes precedence)
1/02	. by using resonance	1/12	. . using spirally or helically shaped channels (cyclones B04C)
1/023	. . {Helmholtz resonators}	1/125	. . . {in combination with sound-absorbing materials}
1/026	. . {Annular resonance chambers arranged concentrically to an exhaust passage and communicating with it, e.g. via at least one opening in the exhaust passage}	1/14	. by adding air to exhaust gases {(in tailpipes F01N 13/082 , F01N 13/20)}
1/04	. . having sound-absorbing materials in resonance chambers	1/16	. by using movable parts
1/06	. by using interference effect	1/161	. . {for adjusting resonance or dead chambers or passages to resonance or dead chambers}
1/065	. . {by using an active noise source, e.g. speakers}	1/163	. . . {by means of valves}
1/08	. by reducing exhaust energy by throttling or whirling	1/165	. . {for adjusting flow area}
1/081	. . {by passing the exhaust gases through a mass of particles}	1/166	. . {for changing the flow path through the silencer or for adjusting the dimensions of a chamber or a pipe (F01N 1/165 takes precedence)}
1/082	. . {by passing the exhaust gases through porous members}	1/168	. . {for controlling or modifying silencing characteristics only}
1/083	. . {using transversal baffles defining a tortuous path for the exhaust gases or successively throttling exhaust gas flow}	1/18	. . having rotary movement
1/084	. . {the exhaust gases flowing through the silencer two or more times longitudinally in opposite directions, e.g. using parallel or concentric tubes}	1/20	. . having oscillating or vibrating movement {(the parts being resilient walls F01N 1/22)}
		1/22	. . the parts being resilient walls

- 1/24 . . . by using sound-absorbing materials ([F01N 1/04](#), [F01N 1/06](#), [F01N 1/10](#), [F01N 1/14](#), [F01N 1/16](#) take precedence)
- 3/00 Exhaust or silencing apparatus having means for purifying, rendering innocuous, or otherwise treating exhaust** (electric control [F01N 9/00](#); monitoring or diagnostic devices for exhaust-gas treatment apparatus [F01N 11/00](#))
- 3/005 . . . {for draining or otherwise eliminating condensates or moisture accumulating in the apparatus ([F01N 3/02](#) takes precedence)}
- 3/01 . . . by means of electric or electrostatic separators
- 3/02 . . . for cooling, or for removing solid constituents of, exhaust (by means of electric or electrostatic separators [F01N 3/01](#) {; mixing air with exhaust in tailpipes [F01N 13/082](#), [F01N 13/20](#))
- 3/0205 . . . {using heat exchangers}
- 3/021 . . . by means of filters
- 3/0211 . . . {Arrangements for mounting filtering elements in housing, e.g. with means for compensating thermal expansion or vibration}
- 3/0212 . . . {with one or more perforated tubes surrounded by filtering material, e.g. filter candles}
- 3/0214 . . . {with filters comprising movable parts, e.g. rotating filters}
- 3/0215 . . . {the filtering elements having the form of disks or plates}
- 3/0217 . . . {the filtering elements having the form of hollow cylindrical bodies}
- 3/0218 . . . {the filtering elements being made from spirally-wound filtering material}
- 3/022 . . . characterised by specially adapted filtering structure, e.g. honeycomb, mesh or fibrous
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2330/00](#).}
- 3/0222 {the structure being monolithic, e.g. honeycombs}
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2330/30](#).}
- 3/0224 {the structure being granular}
- 3/0226 {the structure being fibrous}
- 3/0228 {the structure being made of foamed rubber or plastics}
- 3/023 . . . using means for regenerating the filters, e.g. by burning trapped particles
- 3/0231 {using special exhaust apparatus upstream of the filter for producing nitrogen dioxide, e.g. for continuous filter regeneration systems [CRT]}
- 3/0232 {removing incombustible material from a particle filter, e.g. ash}
- 3/0233 {periodically cleaning filter by blowing a gas through the filter in a direction opposite to exhaust flow, e.g. exposing filter to engine air intake}
- 3/0234 {using heat exchange means in the exhaust line}
- 3/0235 {using exhaust gas throttling means}
- 3/0236 {using turbine waste gate valve}
- 3/0237 {for regenerating ex situ}
- 3/0238 {for regenerating during engine standstill}
- 3/025 using fuel burner or by adding fuel to exhaust
- 3/0253 {adding fuel to exhaust gases}
- 3/0256 {the fuel being ignited by electrical means}
- 3/027 using electric or magnetic heating means
- 3/0275 {using electric discharge means}
- 3/028 using microwaves
- 3/029 by adding non-fuel substances to exhaust
- 3/0293 {injecting substances in exhaust stream}
- 3/0296 {having means for preheating additional substances}
- 3/031 . . . having means for by-passing filters, e.g. when clogged or during cold engine start
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2410/00](#).}
- 3/032 during filter regeneration only
- 3/033 . . . in combination with other devices {(with adsorbents or absorbents [F01N 3/0821](#))}
- 3/0335 {with exhaust silencers in a single housing}
- 3/035 with catalytic reactors
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2510/06](#).}
- 3/037 . . . by means of inertial or centrifugal separators, e.g. of cyclone type, optionally combined or associated with agglomerators
- 3/038 . . . by means of perforated plates defining expansion chambers associated with condensation and collection chambers
- 3/04 . . . using liquids
- 3/043 . . . {without contact between liquid and exhaust gases}
- 3/046 {Exhaust manifolds with cooling jacket}
- 3/05 . . . by means of air, e.g. by mixing exhaust with air (silencers working by addition of air to exhaust [F01N 1/14](#); arrangements for the supply of additional air for the thermal or catalytic conversion of noxious components of exhaust [F01N 3/30](#))
- 3/055 . . . {without contact between air and exhaust gases}
- 3/06 . . . for extinguishing sparks
- 3/08 . . . for rendering innocuous (using electric or electrostatic separators [F01N 3/01](#); chemical aspects [B01D 53/92](#))
- 3/0807 . . . {by using absorbents or adsorbents}
- 3/0814 . . . {combined with catalytic converters, e.g. NOx absorption/storage reduction catalysts}
- 3/0821 . . . {combined with particulate filter}
- 3/0828 . . . {characterised by the absorbed or adsorbed substances}
- 3/0835 {Hydrocarbons}
- 3/0842 {Nitrogen oxides}
- 3/085 {Sulfur or sulfur oxides}
- 3/0857 {Carbon oxides}
- 3/0864 {Oxygen}

- 3/0871 . . . {using means for controlling, e.g. purging, the absorbents or adsorbents}
- 3/0878 {Bypassing absorbents or adsorbents}
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2410/00](#).}
- 3/0885 {Regeneration of deteriorated absorbents or adsorbents, e.g. desulfurization of NOx traps}
- 3/0892 . . {Electric or magnetic treatment, e.g. dissociation of noxious components}
- 3/10 . . by thermal or catalytic conversion of noxious components of exhaust
- 3/101 . . . {Three-way catalysts}
- 3/103 . . . {Oxidation catalysts for HC and CO only}
- 3/105 . . . {General auxiliary catalysts, e.g. upstream or downstream of the main catalyst}
- 3/106 {Auxiliary oxidation catalysts}
- 3/108 {Auxiliary reduction catalysts}
- 3/18 . . . characterised by methods of operation; Control
- 3/20 specially adapted for catalytic conversion ([F01N 3/22](#) takes precedence)
- 3/2006 {Periodically heating or cooling catalytic reactors, e.g. at cold starting or overheating (by electrically controlling the supply of combustible mixture or its constituents only [F02D 41/0235](#))}
- 3/2013 {using electric or magnetic heating means}
- 3/202 {using microwaves}
- 3/2026 {directly electrifying the catalyst substrate, i.e. heating the electrically conductive catalyst substrate by joule effect}
- 3/2033 {using a fuel burner or introducing fuel into exhaust duct}
- 3/204 {using an exhaust gas igniter, e.g. a spark or glow plug, without introducing fuel into exhaust duct}
- 3/2046 {Periodically cooling catalytic reactors}
- 3/2053 {By-passing catalytic reactors, e.g. to prevent overheating}
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2410/00](#).}
- 3/206 {Adding periodically or continuously substances to exhaust gases for promoting purification, e.g. catalytic material in liquid form, NOx reducing agents}
- 3/2066 {Selective catalytic reduction [SCR]}
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2610/00](#).}
- 3/2073 {Means for generating a reducing substance from the exhaust gases}
- 3/208 {Control of selective catalytic reduction [SCR], e.g. by adjusting the dosing of reducing agent}
- 3/2086 {Activating the catalyst by light, photo-catalysts}
- 3/2093 {Periodically blowing a gas through the converter, e.g. in a direction opposite to exhaust gas flow or by reversing exhaust gas flow direction}
- 3/22 Control of additional air supply only, e.g. using by-passes or variable air pump drives
- 3/222 {using electric valves only}
- 3/225 {Electric control of additional air supply}
- 3/227 {using pneumatically operated valves, e.g. membrane valves}
- 3/24 characterised by constructional aspects of converting apparatus ([filtering in combination with catalytic reactors F01N 3/035](#))
- 3/26 Construction of thermal reactors
- 3/28 Construction of catalytic reactors
- 3/2803 {characterised by structure, by material or by manufacturing of catalyst support}
- 3/2807 {Metal other than sintered metal ([F01N 3/2832](#) and [F01N 3/2835](#) take precedence)}
- 3/281 {Metallic honeycomb monoliths made of stacked or rolled sheets, foils or plates}
- 3/2814 {all sheets, plates or foils being corrugated}
- 3/2817 {only with non-corrugated sheets, plates or foils}
- 3/2821 {the support being provided with means to enhance the mixing process inside the converter, e.g. sheets, plates or foils with protrusions or projections to create turbulence}
- 3/2825 {Ceramics ([F01N 3/2832](#), [F01N 3/2835](#) take precedence)}
- 3/2828 {Ceramic multi-channel monoliths, e.g. honeycombs}
- 3/2832 {granular, e.g. pellets}
- 3/2835 {fibrous}
- 3/2839 {Arrangements for mounting catalyst support in housing, e.g. with means for compensating thermal expansion or vibration}
- NOTE**
{In this subgroup, it is desirable to add the indexing codes of [F01N 2350/02](#).}
- 3/2842 {specially adapted for monolithic supports, e.g. of honeycomb type ([F01N 3/2853](#) - [F01N 3/2871](#) take precedence)}
- 3/2846 {specially adapted for granular supports, e.g. pellets}
- 3/285 {specially adapted for fibrous supports, e.g. held in place by screens}
- 3/2853 {using mats or gaskets between catalyst body and housing}
- 3/2857 {the mats or gaskets being at least partially made of intumescent material, e.g. unexpanded vermiculite}

- 3/286 {the mats or gaskets having corrugations or cavities}
- 3/2864 {the mats or gaskets comprising two or more insulation layers}
- 3/2867 {the mats or gaskets being placed at the front or end face of catalyst body}
- 3/2871 {the mats or gaskets having an additional, e.g. non-insulating or non-cushioning layer, a metal foil or an adhesive layer}
- 3/2875 {by using elastic means, e.g. spring leaves, for retaining catalyst body in the housing ([F01N 3/2853](#) - [F01N 3/2871](#) take precedence)}
- 3/2878 {by using non-elastic means for retaining catalyst body in the housing, e.g. a metal chamfer, or by corrugation or deformation of the metal housing}
- 3/2882 {Catalytic reactors combined or associated with other devices, e.g. exhaust silencers or other exhaust purification devices ([combined with absorbents or adsorbents only F01N 3/0814](#); [combined with particulate filters F01N 3/035](#))}
- 3/2885 {with exhaust silencers in a single housing}
- 3/2889 {with heat exchangers in a single housing}
- 3/2892 {Exhaust flow directors or the like, e.g. upstream of catalytic device}
- 3/2896 {Liquid catalyst carrier}
- 3/30 Arrangements for supply of additional air ([control, e.g. using by-passes or variable air pump drives, F01N 3/22](#))
- 3/303 {Filtering additional air}
- 3/306 {Preheating additional air}
- 3/32 using air pump ([using jet air pumps F01N 3/34](#); [pumps in general F04](#))
- 3/323 {Electrically driven air pumps}
- 3/326 {Engine-driven air pumps}
- 3/34 using air conduits or jet air pumps, e.g. near the engine exhaust port
- 3/36 Arrangements for supply of additional fuel

NOTE

{In this subgroup, it is desirable to add the indexing codes of [F01N 2610/14](#).}

- 3/38 Arrangements for igniting
- 5/00 Exhaust or silencing apparatus combined or associated with devices profiting by exhaust energy ([using kinetic or wave energy of exhaust gases in exhaust systems for charging F02B](#))**
- 5/02 . the devices using heat
- 5/025 . . {the device being thermoelectric generators}
- 5/04 . the devices using kinetic energy

- 9/00 Electrical control of exhaust gas treating apparatus ([monitoring or diagnostic devices for exhaust-gas treatment apparatus F01N 11/00](#); [conjoint electrical control of two or more combustion engine functions F02D 43/00](#))**

NOTE

{In this subgroup, it is desirable to add the indexing codes of [F01N 2900/00](#).}

- 9/002 . {of filter regeneration}
- 9/005 . {using models instead of sensors to determine operating characteristics of exhaust systems, e.g. calculating catalyst temperature instead of measuring it directly}
- 9/007 . {Storing data relevant to operation of exhaust systems for later retrieval and analysis, e.g. to research exhaust system malfunctions}

- 11/00 Monitoring or diagnostic devices for exhaust-gas treatment apparatus**

NOTE

{In this subgroup, it is desirable to add the indexing codes of [F01N 2550/00](#) and [F01N 2900/00](#).}

- 11/002 . {the diagnostic devices measuring or estimating temperature or pressure in, or downstream of the exhaust apparatus}
- 11/005 . . {the temperature or pressure being estimated, e.g. by means of a theoretical model}
- 11/007 . {the diagnostic devices measuring oxygen or air concentration downstream of the exhaust apparatus}

- 13/00 Exhaust or silencing apparatus characterised by constructional features**

- 13/001 . {Exhaust gas flow channels or chambers being at least partly formed in the structural parts of the engine or machine ([using structural parts of the vehicle B60K 13/06](#))}
- 13/002 . {Apparatus adapted for particular uses, e.g. for portable devices driven by machines or engines}
- 13/004 . {specially adapted for marine propulsion, i.e. for receiving simultaneously engine exhaust gases and engine cooling water ([for submerged exhausting F01N 13/12](#); [treating exhaust by using liquids F01N 3/04](#))}
- 13/005 . . {with parts constructed of non-metallic material, e.g. of rubber}
- 13/007 . {Apparatus used as intake or exhaust silencer}
- 13/008 . {Mounting or arrangement of exhaust sensors in or on exhaust apparatus ([sensor arrangements for engine control F02D 41/1439](#))}
- 13/009 . {having two or more separate purifying devices arranged in series}
- 13/0093 . . {the purifying devices are of the same type}
- 13/0097 . . {the purifying devices are arranged in a single housing}
- 13/011 . {having two or more purifying devices arranged in parallel}
- 13/017 . . {the purifying devices are arranged in a single housing}
- 13/02 . having two or more separate silencers in series
- 13/04 . having two or more silencers in parallel, e.g. having interconnections for multi-cylinder engines

- 13/06 . . . specially adapted for star-arrangement of cylinders, e.g. exhaust manifolds
- 13/08 . . . Other arrangements or adaptations of exhaust conduits [{\(pipes, joints or supports therefor in general F16L; collecting or removing exhaust gases of vehicle engines in workshops B08B 15/00, on highways E01C 1/005\)}](#)
- 13/082 . . . {of tailpipe, e.g. with means for mixing air with exhaust for exhaust cooling, dilution or evacuation [\(FOIN 13/20 takes precedence\)}](#)}
- 13/085 . . . {having means preventing foreign matter from entering exhaust conduit}
- 13/087 . . . {having valves upstream of silencing apparatus for by-passing at least part of exhaust directly to atmosphere [\(valves for changing flow path through the silencer FOIN 1/166\)}](#)}
- 13/10 . . . of exhaust manifolds [{\(with cooling jacket FOIN 3/046\)}](#)}
- 13/102 . . . {having thermal insulation}
- 13/105 . . . {having the form of a chamber directly connected to the cylinder head, e.g. without having tubes connected between cylinder head and chamber}
- 13/107 . . . {More than one exhaust manifold or exhaust collector}
- 13/12 . . . specially adapted for submerged exhausting
- 13/14 . . . having thermal insulation [{\(exhaust manifolds FOIN 13/102\)}](#)}
- 13/141 . . . {Double-walled exhaust pipes or housings}
- 13/143 . . . {with air filling the space between both walls}
- 13/145 . . . {with a gas other than air filling the space between both walls}
- 13/146 . . . {with vacuum in the space between both walls}
- 13/148 . . . {Multiple layers of insulating material}
- 13/16 . . . Selection of particular materials
- 13/18 . . . Construction facilitating manufacture, assembly, or disassembly
- 13/1805 . . . {Fixing exhaust manifolds, exhaust pipes or pipe sections to each other, to engine or to vehicle body [\(pipe joints in general F16L; fixing auxiliaries in motor vehicles in general B60K\)}](#)}
- 13/1811 . . . {with means permitting relative movement, e.g. compensation of thermal expansion or vibration}
- 13/1816 {the pipe sections being joined together by flexible tubular elements only, e.g. using bellows or strip-wound pipes}
- 13/1822 {for fixing exhaust pipes or devices to vehicle body}
- 13/1827 . . . {Sealings specially adapted for exhaust systems [\(sealings in general F16J 15/00\)}](#)}
- 13/1833 . . . {specially adapted for small internal combustion engines, e.g. used in model applications}
- 13/1838 . . . {characterised by the type of connection between parts of exhaust or silencing apparatus, e.g. between housing and tubes, between tubes and baffles}
- 13/1844 . . . {Mechanical joints}
- 13/185 {the connection being realised by deforming housing, tube, baffle, plate, or parts thereof}
- 13/1855 {the connection being realised by using bolts, screws, rivets or the like}
- 13/1861 . . . {the assembly using parts formed by casting or moulding}
- 13/1866 . . . {the channels or tubes thereof being made integrally with the housing}
- 13/1872 . . . {the assembly using stamp-formed parts or otherwise deformed sheet-metal}
- 13/1877 . . . {the channels or tubes thereof being made integrally with the housing}
- 13/1883 . . . {manufactured by hydroforming}
- 13/1888 . . . {the housing of the assembly consisting of two or more parts, e.g. two half-shells}
- 13/1894 . . . {the parts being assembled in longitudinal direction}
- 13/20 . . . having flared outlets, e.g. of fish-tail shape
- 99/00 Subject matter not provided for in other groups of this subclass**
- Indexing scheme related to gas-flow silencers or exhaust apparatus**
- 2210/00 Combination of methods of silencing**
- 2210/02 . . . Resonance and interference
- 2210/04 . . . Throttling-expansion and resonance
- 2210/06 . . . Throttling-expansion and interference
- 2230/00 Combination of silencers and other devices**
- 2230/02 . . . Exhaust filters
- 2230/04 . . . Catalytic converters
- 2230/06 . . . Spark arresters
- 2230/08 . . . Thermal reactors
- 2240/00 Combination or association of two or more different exhaust treating devices, or of at least one such device with an auxiliary device, not covered by indexing codes [FOIN 2230/00](#) or [FOIN 2250/00](#), one of the devices being**
- 2240/02 . . . a heat exchanger
- 2240/04 . . . an electric, e.g. electrostatic, device other than a heater
- 2240/05 . . . a magnetic, e.g. electromagnetic, device other than a valve
- 2240/06 . . . an inertial, e.g. centrifugal, device
- 2240/10 . . . a heat accumulator
- 2240/12 . . . a thermal reactor
- 2240/14 . . . a fuel burner
- 2240/16 . . . an electric heater, i.e. a resistance heater
- 2240/18 . . . an adsorber or absorber
- 2240/20 . . . a flow director or deflector
- 2240/22 . . . a condensation chamber
- 2240/25 . . . an ammonia generator
- 2240/26 . . . an exhaust gas reservoir, e.g. emission buffer
- 2240/28 . . . a plasma reactor
- 2240/30 . . . a fuel reformer
- 2240/32 . . . a fuel cell
- 2240/34 . . . an electrolyser
- 2240/36 . . . an exhaust flap
- 2240/38 . . . an ozone (O₃) generator, e.g. for adding ozone after generation of ozone from air
- 2240/40 . . . a hydrolysis catalyst
- 2250/00 Combinations of different methods of purification**
- 2250/02 . . . filtering and catalytic conversion
- 2250/04 . . . afterburning and catalytic conversion
- 2250/06 . . . afterburning and filtering
- 2250/08 . . . filtering and inertial particulate separation
- 2250/10 . . . cooling and filtering

- 2250/12 . . . absorption or adsorption, and catalytic conversion
- 2250/14 . . . absorption or adsorption, and filtering
- 2260/00 Exhaust treating devices having provisions not otherwise provided for**
- 2260/02 . . . for cooling the device
- 2260/022 . . . using air
- 2260/024 . . . using a liquid
- 2260/04 . . . for regeneration or reactivation, e.g. of catalyst
- 2260/06 . . . for improving exhaust evacuation or circulation, or reducing back-pressure
- 2260/08 . . . for preventing heat loss or temperature drop, using other means than layers of heat-insulating material
- 2260/10 . . . for avoiding stress caused by expansions or contractions due to temperature variations
- 2260/12 . . . for resisting high pressure
- 2260/14 . . . for modifying or adapting flow area or back-pressure
- 2260/16 . . . for reducing exhaust flow pulsations
- 2260/18 . . . for improving rigidity, e.g. by wings, ribs
- 2260/20 . . . for heat or sound protection, e.g. using a shield or specially shaped outer surface of exhaust device
- 2260/22 . . . for preventing theft of exhaust parts or devices, e.g. anti-theft arrangements
- 2260/24 . . . for identifying exhaust parts or devices, e.g. by labels, stickers or directly printing
- 2260/26 . . . for preventing enter of dirt into the device
- 2270/00 Mixing air with exhaust gases**
- 2270/02 . . . for cooling exhaust gases or the apparatus
- 2270/04 . . . for afterburning
- 2270/06 . . . for silencing
- 2270/08 . . . for evacuation of exhaust gases, e.g. in tail-pipes
- 2270/10 . . . for rendering exhaust innocuous, e.g. by dilution
- 2290/00 Movable parts or members in exhaust systems for other than for control purposes**
- 2290/02 . . . with continuous rotary movement
- 2290/04 . . . driven by exhaust gases
- 2290/06 . . . driven by auxiliary drive
- 2290/08 . . . with oscillating or vibrating movement
- 2290/10 . . . actuated by pressure of exhaust gases, e.g. exhaust pulses
- 2310/00 Selection of sound absorbing or insulating material**
- 2310/02 . . . Mineral wool, e.g. glass wool, rock wool, asbestos or the like
- 2310/04 . . . Metallic wool, e.g. steel wool, copper wool or the like
- 2310/06 . . . Porous ceramics
- 2310/08 . . . Exfoliated vermiculite, e.g. zonolite, coke, pumice
- 2310/10 . . . Plastic foam
- 2310/12 . . . Granular material
- 2310/14 . . . Wire mesh fabric, woven glass cloth or the like
- 2330/00 Structure of catalyst support or particle filter**
- 2330/02 . . . Metallic plates or honeycombs, e.g. superposed or rolled-up corrugated or otherwise deformed sheet metal
- 2330/04 . . . Methods of manufacturing
- 2330/06 . . . Ceramic, e.g. monoliths
- 2330/08 . . . Granular material
- 2330/10 . . . Fibrous material, e.g. mineral or metallic wool
- 2330/101 . . . using binders, e.g. to form a permeable mat, paper or the like
- 2330/102 . . . fibrous material being fiber reinforced polymer made of plastic matrix reinforced by fine glass or in the form of a loose mass of filaments or fibers
- 2330/12 . . . Metallic wire mesh fabric or knitting
- 2330/14 . . . Sintered material
- 2330/18 . . . Composite material
- 2330/20 . . . Plastics, e.g. polymers, polyester, polyurethane
- 2330/22 . . . Metal foam
- 2330/30 . . . Honeycomb supports characterised by their structural details
- 2330/32 . . . characterised by the shape, form or number of corrugations of plates, sheets or foils
- 2330/321 . . . with two or more different kinds of corrugations in the same substrate
- 2330/322 . . . Corrugations of trapezoidal form
- 2330/323 . . . Corrugations of saw-tooth or triangular form
- 2330/324 . . . Corrugations of rectangular form
- 2330/325 . . . Corrugations of omega form
- 2330/34 . . . with flow channels of polygonal cross section
- 2330/36 . . . with flow channels formed by tubes
- 2330/38 . . . flow channels with means to enhance flow mixing,(e.g. protrusions or projections)
- 2330/40 . . . made of a single sheet, foil or plate
- 2330/42 . . . made of three or more different sheets, foils or plates stacked one on the other
- 2330/44 . . . made of stacks of sheets, plates or foils that are folded in S-form
- 2330/48 . . . characterised by the number of flow passages, e.g. cell density
- 2330/60 . . . Discontinuous, uneven properties of filter material, e.g. different material thickness along the longitudinal direction; Higher filter capacity upstream than downstream in same housing
- 2340/00 Dimensional characteristics of the exhaust system, e.g. length, diameter or volume of the exhaust apparatus; Spatial arrangements of exhaust apparatuses**
- 2340/02 . . . Distance of the exhaust apparatus to the engine or between two exhaust apparatuses
- 2340/04 . . . Arrangement of the exhaust system relative to a vehicle or parts thereof
- 2340/06 . . . Arrangement of the exhaust apparatus relative to the turbine of a turbocharger
- 2340/08 . . . Series-connected exhaust apparatuses mounted in a side-by-side spatial arrangement, e.g. U- or S-shaped
- 2350/00 Arrangements for fitting catalyst support or particle filter element in the housing**
- 2350/02 . . . Fitting ceramic monoliths in a metallic housing
- 2350/04 . . . with means compensating thermal expansion
- 2350/06 . . . with means preventing gas flow by-pass or leakage
- 2350/08 . . . with means for compressing granular material
- 2370/00 Selection of materials for exhaust purification**
- 2370/02 . . . used in catalytic reactors
- 2370/04 . . . Zeolitic material
- 2370/22 . . . used in non-catalytic purification apparatus
- 2370/24 . . . Zeolitic material
- 2370/30 . . . Materials having magnetic properties
- 2370/40 . . . Activated carbon or charcoal

- 2390/00 Arrangements for controlling or regulating exhaust apparatus**
- 2390/02 . using electric components only
 - 2390/04 . using electropneumatic components
 - 2390/06 . using pneumatic components only
 - 2390/08 . using mechanical components only, e.g. actuated manually
- 2410/00 By-passing, at least partially, exhaust from inlet to outlet of apparatus, to atmosphere or to other device**
- 2410/02 . in case of high temperature, e.g. overheating of catalytic reactor
 - 2410/03 . in case of low temperature
 - 2410/04 . during regeneration period, e.g. of particle filter
 - 2410/06 . at cold starting
 - 2410/08 . in case of clogging, e.g. of particle filter
 - 2410/10 . for reducing flow resistance, e.g. to obtain more engine power
 - 2410/12 . in case of absorption, adsorption or desorption of exhaust gas constituents
 - 2410/14 . in case of excessive pressure, e.g. using a safety valve
- 2430/00 Influencing exhaust purification, e.g. starting of catalytic reaction, filter regeneration, or the like, by controlling engine operating characteristics**
- 2430/02 . by cutting out a part of engine cylinders
 - 2430/04 . by adding non-fuel substances to combustion air or fuel, e.g. additives
 - 2430/06 . by varying fuel-air ratio, e.g. by enriching fuel-air mixture
 - 2430/08 . by modifying ignition or injection timing
 - 2430/085 . . at least a part of the injection taking place during expansion or exhaust stroke
 - 2430/10 . by modifying inlet or exhaust valve timing
- 2450/00 Methods or apparatus for fitting, inserting or repairing different elements**
- 2450/02 . Fitting monolithic blocks into the housing
 - 2450/04 . Filling or emptying a chamber with granular material
 - 2450/06 . Inserting sound absorbing material into a chamber
 - 2450/08 . Repairing the housing or pipe-joints
 - 2450/10 . Fitting temporarily exhaust apparatus on exhaust conduit, e.g. in confined environment, garage or the like
 - 2450/16 . by using threaded joints
 - 2450/18 . by using quick-active type locking mechanisms, e.g. clips
 - 2450/20 . by mechanical joints, e.g. by deforming housing, tube, baffle plate or parts thereof
 - 2450/22 . by welding or brazing
 - 2450/24 . by bolts, screws, rivets or the like
 - 2450/26 . by bayonet fittings
 - 2450/28 . by using adhesive material, e.g. cement
 - 2450/30 . Removable or rechargeable blocks or cartridges, e.g. for filters
 - 2450/40 . Retrofitting exhaust apparatus
- 2470/00 Structure or shape of exhaust gas passages, pipes or tubes**
- 2470/02 . Tubes being perforated
 - 2470/04 . . characterised by shape, disposition or dimensions of apertures
 - 2470/06 . Tubes being formed by assembly of stamped or otherwise deformed sheet-metal
 - 2470/08 . Exhaust gas passages being formed between the walls of an outer shell and an inner chamber
 - 2470/10 . Tubes having non-circular cross section
 - 2470/12 . Tubes being corrugated
 - 2470/14 . Plurality of outlet tubes, e.g. in parallel or with different length
 - 2470/16 . Plurality of inlet tubes, e.g. discharging into different chambers
 - 2470/18 . the axis of inlet or outlet tubes being other than the longitudinal axis of apparatus
 - 2470/20 . Dimensional characteristics of tubes, e.g. length, diameter
 - 2470/22 . Inlet and outlet tubes being positioned on the same side of the apparatus
 - 2470/24 . Concentric tubes or tubes being concentric to housing, e.g. telescopically assembled
 - 2470/26 . Tubes being formed by extrusion, drawing or rolling
 - 2470/28 . Tubes being formed by moulding or casting
 - 2470/30 . Tubes with restrictions, i.e. venturi or the like, e.g. for sucking air or measuring mass flow
- 2490/00 Structure, disposition or shape of gas-chambers**
- 2490/02 . Two or more expansion chambers in series connected by means of tubes
 - 2490/04 . . the gases flowing longitudinally from inlet to outlet only in one direction
 - 2490/06 . . the gases flowing longitudinally from inlet to outlet in opposite directions
 - 2490/08 . Two or more expansion chambers in series separated by apertured walls only
 - 2490/10 . Two or more expansion chambers in parallel
 - 2490/12 . Chambers having variable volumes
 - 2490/14 . Dead or resonance chambers connected to gas flow tube by relatively short side-tubes
 - 2490/15 . Plurality of resonance or dead chambers
 - 2490/155 . . being disposed one after the other in flow direction
 - 2490/16 . Chambers with particular shapes, e.g. spherical
 - 2490/18 . Dimensional characteristics of gas chambers
 - 2490/20 . Chambers being formed inside the exhaust pipe without enlargement of the cross section of the pipe, e.g. resonance chambers
- 2510/00 Surface coverings**
- 2510/02 . for thermal insulation
 - 2510/04 . for sound absorption
 - 2510/06 . for exhaust purification, e.g. catalytic reaction
 - 2510/061 . . usable with leaded fuels
 - 2510/063 . . zeolites
 - 2510/065 . . for reducing soot ignition temperature
 - 2510/067 . . usable with sulfurised fuels
 - 2510/068 . . characterised by the distribution of the catalytic coatings
 - 2510/0682 . . . having a discontinuous, uneven or partially overlapping coating of catalytic material, e.g. higher amount of material upstream than downstream or *vice versa*
 - 2510/0684 . . . having more than one coating layer, e.g. multi-layered coatings
 - 2510/08 . for corrosion prevention
 - 2510/10 . for preventing carbon deposits, e.g. chromium
 - 2510/12 . for smell removal

- 2510/14 . for dehydrating
- 2530/00 Selection of materials for tubes, chambers or housings**
- 2530/02 . Corrosion resistive metals
- 2530/04 . . Steel alloys, e.g. stainless steel
- 2530/06 . Aluminium or alloys thereof
- 2530/18 . Plastics material, e.g. polyester resin
- 2530/20 . . reinforced with mineral or metallic fibres
- 2530/22 . Flexible elastomeric material
- 2530/24 . Sintered porous material, e.g. bronze, aluminium or the like
- 2530/26 . Multi-layered walls
- 2550/00 Monitoring or diagnosing the deterioration of exhaust systems**
- 2550/02 . Catalytic activity of catalytic converters
- 2550/03 . of sorbing activity of adsorbents or absorbents
- 2550/04 . Filtering activity of particulate filters
- 2550/05 . Systems for adding substances into exhaust
- 2550/06 . By-pass systems
- 2550/10 . . of catalytic converters
- 2550/12 . . of particulate filters
- 2550/14 . Systems for adding secondary air into exhaust
- 2550/20 . Monitoring artificially aged exhaust systems
- 2550/22 . of electric heaters for exhaust systems or their power supply
- 2550/24 . Determining the presence or absence of an exhaust treating device
- 2560/00 Exhaust systems with means for detecting or measuring exhaust gas components or characteristics**
- 2560/02 . the means being an exhaust gas sensor
- 2560/021 . . for measuring or detecting ammonia NH₃
- 2560/022 . . for measuring or detecting CO or CO₂
- 2560/023 . . for measuring or detecting HC
- 2560/024 . . for measuring or detecting hydrogen H₂
- 2560/025 . . for measuring or detecting O₂, e.g. lambda sensors
- 2560/026 . . for measuring or detecting NOx
- 2560/027 . . for measuring or detecting SOx
- 2560/028 . . for measuring or detecting humidity or water
- 2560/05 . the means being a particulate sensor
- 2560/06 . the means being a temperature sensor
- 2560/07 . the means being an exhaust gas flow rate or velocity meter or sensor, intake flow meters only when exclusively used to determine exhaust gas parameters
- 2560/08 . the means being a pressure sensor
- 2560/12 . Other sensor principles, e.g. using electro conductivity of substrate or radio frequency
- 2560/14 . having more than one sensor of one kind
- 2560/20 . Sensor having heating means
- 2570/00 Exhaust treating apparatus eliminating, absorbing or adsorbing specific elements or compounds**
- 2570/02 . Lead
- 2570/04 . Sulfur or sulfur oxides
- 2570/06 . Zinc
- 2570/08 . Phosphorus
- 2570/10 . Carbon or carbon oxides
- 2570/12 . Hydrocarbons
- 2570/14 . Nitrogen oxides
- 2570/145 . . Dinitrogen oxide
- 2570/16 . Oxygen
- 2570/18 . Ammonia
- 2570/20 . Formaldehyde
- 2570/22 . Water or humidity
- 2570/24 . Hydrogen sulfide (H₂S)
- 2590/00 Exhaust or silencing apparatus adapted to particular use, e.g. for military applications, airplanes, submarines**
- 2590/02 . for marine vessels or naval applications
- 2590/021 . . for outboard engines
- 2590/022 . . for jetskis
- 2590/04 . for motorcycles
- 2590/06 . for hand-held tools or portables devices
- 2590/08 . for heavy duty applications, e.g. trucks, buses, tractors, locomotives
- 2590/10 . for stationary applications
- 2590/11 . for hybrid vehicles
- 2610/00 Adding substances to exhaust gases**
- 2610/01 . the substance being catalytic material in liquid form
- 2610/02 . the substance being ammonia or urea
- 2610/03 . the substance being hydrocarbons, e.g. engine fuel
- 2610/04 . the substance being hydrogen
- 2610/05 . the substance being carbon monoxide
- 2610/06 . the substance being in the gaseous form
- 2610/08 . with prior mixing of the substances with a gas, e.g. air
- 2610/085 . . Controlling the air supply
- 2610/10 . the substance being heated, e.g. by heating tank or supply line of the added substance
- 2610/102 . . after addition to exhaust gases, e.g. by a passively or actively heated surface in the exhaust conduit
- 2610/105 . . Control thereof
- 2610/107 . . using glow plug heating elements
- 2610/11 . the substance or part of the dosing system being cooled
- 2610/12 . the substance being in solid form, e.g. pellets or powder
- 2610/14 . Arrangements for the supply of substances, e.g. conduits
- 2610/1406 . . Storage means for substances, e.g. tanks or reservoirs
- 2610/1413 . . . Inlet and filling arrangements therefore
- 2610/142 . . . Controlling the filling of the tank
- 2610/1426 . . Filtration means
- 2610/1433 . . Pumps
- 2610/144 . . . Control thereof
- 2610/1446 . . Means for damping of pressure fluctuations in the delivery system, e.g. by puffer volumes or throttling
- 2610/1453 . . Sprayers or atomisers; Arrangement thereof in the exhaust apparatus
- 2610/146 . . . Control thereof, e.g. control of injectors or injection valves
- 2610/1466 . . Means for venting air out of conduits or tanks
- 2610/1473 . . Overflow or return means for the substances, e.g. conduits or valves for the return path
- 2610/148 . . Arrangement of sensors
- 2610/1486 . . Means to prevent the substance from freezing
- 2610/1493 . . Purging the reducing agent out of the conduits or nozzle

- 2900/00** **Details of electrical control or of the monitoring of the exhaust gas treating apparatus**
- 2900/04 . Methods of control or diagnosing
 - 2900/0402 . . using adaptive learning
 - 2900/0404 . . using a data filter
 - 2900/0406 . . using a model with a division of the catalyst or filter in several cells
 - 2900/0408 . . using a feed-back loop
 - 2900/0411 . . using a feed-forward control
 - 2900/0412 . . using pre-calibrated maps, tables or charts
 - 2900/0414 . . using a state observer
 - 2900/0416 . . using the state of a sensor, e.g. of an exhaust gas sensor
 - 2900/0418 . . using integration or an accumulated value within an elapsed period
 - 2900/0421 . . using an increment counter when a predetermined event occurs
 - 2900/0422 . . measuring the elapsed time
 - 2900/06 . Parameters used for exhaust control or diagnosing
 - 2900/0601 . . being estimated
 - 2900/0602 . . Electrical exhaust heater signals
 - 2900/08 . . said parameters being related to the engine
 - 2900/10 . . said parameters being related to the vehicle or its components
 - 2900/102 . . . Travelling distance
 - 2900/104 . . . Battery status
 - 2900/12 . . said parameters being related to the vehicle exterior
 - 2900/14 . . said parameters being related to the exhaust gas
 - 2900/1402 . . . Exhaust gas composition
 - 2900/1404 . . . Exhaust gas temperature
 - 2900/1406 . . . Exhaust gas pressure
 - 2900/1411 . . . Exhaust gas flow rate, e.g. mass flow rate or volumetric flow rate
 - 2900/16 . . said parameters being related to the exhaust apparatus, e.g. particulate filter or catalyst
 - 2900/1602 . . . Temperature of exhaust gas apparatus
 - 2900/1606 . . . Particle filter loading or soot amount
 - 2900/1611 . . . Particle filter ash amount
 - 2900/1612 . . . SO_x amount trapped in catalyst
 - 2900/1614 . . . NO_x amount trapped in catalyst
 - 2900/1616 . . . NH₃-slip from catalyst
 - 2900/1618 . . . HC-slip from catalyst
 - 2900/1621 . . . Catalyst conversion efficiency
 - 2900/1622 . . . Catalyst reducing agent absorption capacity or consumption amount
 - 2900/1624 . . . Catalyst oxygen storage capacity
 - 2900/1626 . . . Catalyst activation temperature
 - 2900/1628 . . . Moisture amount in exhaust apparatus
 - 2900/1631 . . . Heat amount provided to exhaust apparatus
 - 2900/18 . . said parameters being related to the system for adding a substance into the exhaust
 - 2900/1804 . . . Properties of secondary air added directly to the exhaust
 - 2900/1806 . . . Properties of reducing agent or dosing system
 - 2900/1808 Pressure
 - 2900/1811 Temperature
 - 2900/1812 Flow rate
 - 2900/1814 Tank level
 - 2900/1818 Concentration of the reducing agent
 - 2900/1821 Injector parameters
 - 2900/1822 Pump parameters
- 2900/1824 Properties of the air to be mixed with added substances, e.g. air pressure or air temperature